

300-435 Dumps

Automating and Programming Cisco Enterprise Solutions (ENAUTO)

<https://www.certleader.com/300-435-dumps.html>



NEW QUESTION 1

Which two actions do Python virtual environments allow users to perform? (Choose two.)

- A. Simplify the CI/CD pipeline when checking a project into a version control system, such as Git.
- B. Efficiently port code between different languages, such as JavaScript and Python.
- C. Run and simulate other operating systems within a development environment.
- D. Quickly create any Python environment for testing and debugging purposes.
- E. Quickly create an isolated Python environment with module dependencies.

Answer: DE

NEW QUESTION 2

Which two features are foundations of a software-defined network instead of a traditional network? (Choose two.)

- A. control plane and data plane are tightly coupled
- B. build upon a robust software stack
- C. requires device by device-level configurations
- D. automated through expressed intent to a software controller
- E. requires significant physical hardware resources

Answer: BD

NEW QUESTION 3

```
neighbors = ['s1', 's2', 's3']
switch = {'hostname': 'nexus', 'os': '7.0.3', 'neighbors': neighbors}
print(switch['neighbors'][1])
```

Refer to the exhibit. What is the result when running the Python scripts?

- A. s1
- B. s2
- C. s1, s2, s3
- D. s3

Answer: B

NEW QUESTION 4

```
import requests
import sys

requests.package.urllib3.disable_warnings()

HOST = '10.1.2.3'
PORT = 9443
USER = 'user'
PASS = 'password'

def main():
    url = "https://{h}:{p}/restconf/data/Cisco-IOS-XE-native:native/hostname".format(h=HOST, p=PORT)

    headers = {'Content-Type': 'application/ ',
               'Accept': 'application/ '}
    response = requests.get(url, auth=(USER, PASS),
                           headers=headers, verify=False)
    print(response.text)

if __name__ == '__main__':
    sys.exit(main())
```

Refer to the exhibit. An engineer creates a Python script using RESTCONF to display hostname information. The code must be completed so that it can be tested. Which string completes the highlighted areas in the exhibit?

- A. yang-data+json
- B. yang +json
- C. yang.data+json
- D. json

Answer: A

NEW QUESTION 5

Which statement is true for Cisco IOS XE Software?

- A. RESTCONF supports JSON and XML and NETCONF supports XM
- B. RESTCONF supports XML and NETCONF supports JSON and XML.
- C. RESTCONF and NETCONF supports JSON and XML.
- D. RESTCONF supports XML and NETCONF supports JSON.

Answer: A

NEW QUESTION 6

```
module: ietf-ip
augment /if:interfaces/if:interface:
  +--rw ipv4!
  |   +--rw enabled?      boolean
  |   +--rw forwarding?   boolean
  |   +--rw mtu?           uint16
  |   +--rw address* [ip]
  |   |   +--rw ip                inet:ipv4-address-no-zone
  |   |   +--rw (subnet)
  |   |   |   +--:(prefix-length)
  |   |   |   |   +--rw prefix-length?      uint8
  |   |   |   |   +--:{netmask}
  |   |   |   |   +--rw netmask?            yang:dotted-guad (ipv4-non-contiguous-netmasks)?
  |   |   +--ro origin?            ip-address-origin
  |   +--rw neighbor* [ip]
  |       +--rw ip                inet:ipv4-address-no-zone
  |       +--rw link-layer-address yang:phys-address
```

Refer to the exhibit. Which NETCONF statement type is represented by +--rw address* [ip]?

- A. list
- B. leaf-list
- C. container
- D. submodule

Answer: A

NEW QUESTION 7

```
- name: Create VRFs as defined by local_vrfs
  ios_vrf:
    vrfs: "{{ local_vrfs }}"
    state: 
    register: addvrf
```

Refer to the exhibit. An engineer creates an Ansible playbook to configure VRF information using a local_vrfs variable. The code must be completed so that it can be tested. Which string completes the code?

- A. present
- B. up
- C. on
- D. active

Answer: A

NEW QUESTION 8

DRAG DROP

Drag and drop the commands to the Ansible playbook that applies configuration to an interface on a Cisco IOS XE device. Not all options are used. Select and Place:

Answer Area

ioscmd	interface
parents	iosxe
iosconfig	ios_config

```
- name: configure interface settings
  :
    lines:
      -ip address 172.31.1.1 255.255.255.0
      -no shutdown
  : interface GigabitEthernet1/0
```


- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Answer Area

ioscmd	interface
parents	iosxe
iosconfig	ios_config

```
- name: configure interface settings
  ios_config:
    lines:
      -ip address 172.31.1.1 255.255.255.0
      -no shutdown
  parents: interface GigabitEthernet1/0
```

NEW QUESTION 9

FILL BLANK

Fill in the blank to complete the statement.

is a solution for automating the configuration of a device when it is first powered on, using DHCP and TFTP.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Zero touch provisioning (ZTP)

NEW QUESTION 10

```
from ncclient import manager
with manager.connect(
    host='10.0.0.1',
    port=12022,
    username='cisco',
    password='cisco',
    hostkey_verify=False,
    allow_agent=False,
    look_for_keys=False,
    device_params={'name': 'iosxe'},
) as m:
```

Refer to the exhibit. What is the correct ncclient method to use to collect the running configuration of a Cisco IOS XE device that uses NETCONF?

- A. config=m.copy_config(source='running')
- B. config=m.get(source='running')
- C. config=m.collect_config(source='running')
- D. config=m.get_config(source='running')

Answer: A

NEW QUESTION 10

What does the command boot ipxe forever switch 1 perform when executed on a Cisco IOS XE device?

- A. It continuously sends DHCP requests for iPXE until the device boots with an image.
- B. It continuously sends DNS requests for iPXE until the device restarts.
- C. It continuously sends DNS requests for iPXE until the device boots with an image.
- D. It continuously sends DHCP requests for iPXE until the device restarts.

Answer: A

NEW QUESTION 11

The Cisco DNA Center Sites API must be used to add a device to a site, but only the site name is available. Which API call must be used to retrieve the site

identifier so that the device can be properly added to the network?

- A. /dna/intent/api/site/siteId
- B. /dna/intent/api/site
- C. /dna/intent/api/v1/site
- D. /dna/intent/api/v1/site/siteName

Answer: C

NEW QUESTION 16

Webhook that are generated by Cisco DNA Center are REST calls with which properties?

- A. JSON payload delivered via PUT
- B. XML payload delivered via POST
- C. JSON payload delivered via POST
- D. XML payload delivered via PUT

Answer: A

NEW QUESTION 20

DRAG DROP

A Cisco DNA Center script must be written to retrieve a list of interfaces on a switch. Drag and drop the API calls that are needed to return the list of interfaces using the Command Running APIs from the left into the correct sequence on the right.

Select and Place:

Answer Area

Get task by ID.	run 1
Get file by ID.	run 2
Run read-only commands on devices.	run 3
Get device list.	run 4

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Answer Area

Get task by ID.	Run read-only commands on devices.
Get file by ID.	Get device list.
Run read-only commands on devices.	Get file by ID.
Get device list.	Get task by ID.

NEW QUESTION 25

In which direction does the Cisco DNA Center Intent API communicate?

- A. westbound
- B. eastbound
- C. northbound
- D. southbound

Answer: C

NEW QUESTION 27

```
1 {
2   'data':
3     [
4       {
5         'count': 4,
6         'detailsURL': '',
7         'name': 'vEdge Hardware Health',
8         'status': 'error',
9         'statusList':
10          [
11            {
12              'count': 4,
13              'detailsURL': '/dataservice/device/hardwarehealth/detail?state=normal',
14              'message': '4 {normal=4, warning=0, error=0}',
15              'name': 'normal',
16              'status': 'up'
17            }
18          ]
19       }
20     ]
21 }
```

Refer to the exhibit. Cisco SD-WAN deployment must be troubleshooted using vManage APIs. A call to vEdge Hardware Health API returns the data in the exhibit (only a portion is shown). If this JSON is converted to a Python dictionary and assigned to the variable “d”, how the status is accessed that is indicated on line 16?

- A. d[data][0][statusList][0][status]
- B. d['data']['statusList']['status']
- C. d{'data'}[0]['statusList'][0]['status']
- D. d['data'][0]['statusList'][0]['status']

Answer: B

NEW QUESTION 30

FILL BLANK

<https://vmanage-ip-address:8443/dataservice/device/action/reboot> 260faff9-2d31-4312-cf96-143b46db0211

Information about a rebooted device needs to be displayed with an ID of 260faff9-2d31-4312-cf96-143b46db0211 using the Cisco SD-WAN vManage Administration APIs. The API documentation states that deviceId is a required request parameter. Fill in the blank to create the REST call.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

“deviceId”:

NEW QUESTION 34

What is the purpose of using the Cisco SD-WAN vManage Certificate Management API?

- A. to generate a CSR
- B. to allocate resources to the certificate server
- C. to request a certificate from the certificate server
- D. to enable vManage Center

Answer: A

NEW QUESTION 35

Which action allows for creating a Python script to pull inventory for Cisco SD-WAN Viptela devices using the Viptela library in the code?

- A. from urllib.request import Viptela
- B. from viptela.devices import Viptela
- C. from viptela.viptela import Viptela
- D. from viptela.library import Viptela

Answer: B

NEW QUESTION 37

What is primary purpose of using the Cisco SD-WAN vManage Certificate Management API?

- A. to securely deploy vManage
- B. to report an issue to Cisco TAC
- C. to install signed certificates
- D. to contact Enterprise Certificate Authority

Answer: A

NEW QUESTION 42

Which two API calls must be issued to attach a device template in Cisco SD-WAN? (Choose two.)

- A. “monitor device action status” GET API request with the device ID to display the status of the attach action
- B. “monitor device action status” GET API request with the process ID to display the status of the attach action
- C. PUT call to initiate the attach action
- D. POST call to initiate the attach action
- E. GET call to initiate the attach action

Answer: BD

NEW QUESTION 47

FILL BLANK

Fill in the blank to complete the URL for an API call to Cisco SD-WAN to display the history of the Bidirectional Forwarding Detection sessions that run on a vEdge router.

https://<vmanage-ip-address>/dataservice/device/ deviceid=<deviceid>

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

bfd/synced/sessions?

NEW QUESTION 50

Which Python snippet receives a Meraki webhook request?

A.

```
@app.route('/mynet/webhook', methods=['PUT'])
@app.accept_body(WebhookSchema)
def receive_webhook(**kwargs):
    send_sms_alert(kwargs['alertType'])
```

A.

```
@app.route('/mynet/webhook', methods=['GET'])
@app.accept_body(WebhookSchema)
def receive_webhook(**kwargs):
    send_sms_alert(kwargs['alertType'])
```

B.

```
@app.route('/mynet/webhook', methods=['PATCH'])
@app.accept_body(WebhookSchema)
def receive_webhook(**kwargs):
    send_sms_alert(kwargs['alertType'])
```

C.

```
@app.route('/mynet/webhook', methods=['POST'])
@app.accept_body(WebhookSchema)
def receive_webhook(**kwargs):
    send_sms_alert(kwargs['alertType'])
```

Answer: D

NEW QUESTION 53

Which URI with the request body of Request body: {"name":"Test","organizationId":<org_id>,"type":"appliance"} creates a new Meraki network called “Test”, when using APIs?

- A. PUT https://api.meraki.com/api/v0/organizations/<org_id>/networks
- B. POST <https://api.meraki.com/api/v0/networks>
- C. POST https://api.meraki.com/api/v0/organizations/<org_id>/networks/<net_id>
- D. POST https://api.meraki.com/api/v0/organizations/<org_id>/networks

Answer: D

NEW QUESTION 55

```
{
  "id": "L_123456",
  "organizationId": 1357924,
  "name": "Long Island Office",
  "timeZone": "America/Los_Angeles",
  "tags": "tag1 tag2",
  "type": "combined",
  "disableMyMerakiCom": false
}
```

Refer to the exhibit. Which two parameters are mandatory when the Cisco Meraki API is used to create a network? (Choose two.)

- A. timezone
- B. disableMyMerakiCom
- C. type
- D. tags
- E. organizationId

Answer: AE

NEW QUESTION 59

Which HTTP request is valid to create a new wireless network called "Demo Wireless Network" in the organization "QASD- EROA-MKAW"?

- A. **POST /organizations/networks**
Host: **https://api.meraki.com/api/v0**


```
{
  "name": "Demo Wireless Network",
  "organizationId": "QASD-EROA-MKAW",
  "type": "wireless"
}
```
- B. **POST /organizations/QASD-EROA-MKAW/networks**
Host: **https://api.meraki.com/api/v0**


```
{
  "name": "Demo Wireless Network",
  "type": "combined"
}
```
- C. **POST /organizations/QASD-EROA-MKAW/networks**
Host: **https://api.meraki.com/api/v0**


```
{
  "name": "Demo Wireless Network",
  "organizationId": "QASD-EROA-MKAW",
  "type": "wireless"
}
```

Answer: A

NEW QUESTION 61

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 300-435 Exam with Our Prep Materials Via below:

<https://www.certleader.com/300-435-dumps.html>