

1z0-083 Dumps

Oracle Database Administration II

<https://www.certleader.com/1z0-083-dumps.html>



NEW QUESTION 1

Which two are true about RMAN backups when using a media manager to write backups to tape when there are only two tape drives? (Choose two.)

- A. SBT tape compression can be used even if no RMAN compression is configured.
- B. Any backup set written to the SBT device in this configuration can contain a maximum of two backup pieces.
- C. Any backup written to the SBT device in this configuration can contain a maximum of two backup sets.
- D. SBT tape compression and RMAN backup compression should be used in parallel.
- E. The SBT device should be configured to use PARALLELISM 2 to allow both tape drive to be used simultaneously.

Answer: DE

NEW QUESTION 2

Which two are true about data movement between a non-CDB and a PDB using Data Pump? (Choose two.)

- A. Tablespaces are automatically created as needed while importing full exports in either a non-CDB or a PDB.
- B. Oracle attempts to convert conventional database users to local users when moving schemas from a non- CDB to a PDB.
- C. A new PDB is automatically created when importing a non-CDB into a CDB.
- D. Oracle attempts to convert common users to conventional users when moving schemas from a PDB to a non-CDB.
- E. Moving data from a PDB to anon-CDB is only possible by using transportable tablespace export and import.
- F. Moving data from a non-CDB to a PDB is only possible by using conventional export and import.

Answer: DE

NEW QUESTION 3

Which three are true about backup, restore, and recovery operations done without using Recovery Manager (RMAN)? (Choose three.)

- A. Backing up a database in NOARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in the MOUNT state.
- B. Backing up a database in ARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in MOUNT state.
- C. An Oracle database can be restored from backup files copied using O/S utilities.
- D. Oracle data file backups, copied using an O/S utility, can be added to the RMAN catalog as IMAGE COPIES.
- E. Backing up a database in NOARCHIVELOG mode using O/S utilities requires that the database instance be shut down.
- F. Oracle archive log backups, copied using an O/S utility, can be added to the RMAN catalog as a backup set.
- G. Backing up a database in ARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in OPEN state.

Answer: BDE

NEW QUESTION 4

A container database called CDB1 is OMF-enabled.

PDB_FILE_NAME_CONVERT is not configured in CDB1. PDB1 was unplugged from CDB1 earlier in the week. Examine this command, which will be executed in CDB1:

```
CREATE PLUGGABLE DATABASE pdb1  
USING '/u01/app/oracle/oradata/pdb1.xml' SOURCE_FILE_NAME_CONVERT =  
('/u01/app/oracle/oradata/', '/u02/app/oracle/oradata/');
```

Which two are true? (Choose two.)

- A. PDB1 data files already exist in the correct location.
- B. DBMS_PDB.CHECK_PLUG_COMPATIBILITY must be run in CDB1 before executing the command.
- C. PDB_FILE_NAME_CONVERT must be set before executing the command.
- D. /u01/app/oracle/oradata/pdb1.xml does not contain the current locations of data files for PDB1.
- E. PDB1 must be dropped from CDB1.

Answer: AE

NEW QUESTION 5

Which three are true in Oracle 19c and later releases? (Choose three.)

- A. If the password file location changes, then the new location is used automatically by the Oracle Server.
- B. Schema Only accounts can be granted administrator privileges.
- C. All the Oracle-supplied accounts are Schema Only accounts.
- D. Privilege Analysis is included in Oracle Enterprise Edition and no longer requires Database Vault.
- E. Unified Auditing can be configured to audit only events that are issued indirectly by an audited user.
- F. Unified Auditing can be configured to audit only events that are issued directly by an audited user.

Answer: BCD

NEW QUESTION 6

Which three are true about Recovery Manager (RMAN) in Oracle Database 19c and later releases? (Choose three.)

- A. It is only possible for RMAN to connect to a pluggable database as a target if an RMAN Virtual Private Catalog is used.
- B. It is always possible for RMAN to connect to a pluggable database as a target if any RMAN Catalog is used.
- C. A Virtual Private Catalog used to register a container database must be created in a pluggable database.
- D. A Virtual Private Catalog used to register a container database can be created in a pluggable database.
- E. It is always possible for RMAN to connect to a pluggable database as a target.
- F. A Virtual Private Catalog used to register a container database can be created in a non-container database.

Answer: DEF

NEW QUESTION 7

Which three can be done using Oracle Database Configuration Assistant (DBCA) starting from Oracle Database 19c? (Choose three.)

- A. cloning a remote container database in interactive mode
- B. cloning a remote pluggable database in silent mode
- C. relocating a remote pluggable database in interactive mode
- D. relocating a remote container database in silent mode
- E. cloning a remote container database in silent mode
- F. relocating a remote pluggable database in silent mode
- G. relocating a remote container database in interactive mode

Answer: BEF

NEW QUESTION 8

A user complains about poor database performance.

You want to verify if the user's session has waited for certain types of I/O activity. Which view displays all waits waited on by a session at least once?

- A. V\$SESSION_EVENT
- B. V\$SESSTAT
- C. V\$SESSION_WAIT
- D. V\$SESSION_WAIT_CLASS
- E. V\$SESSION

Answer: A

NEW QUESTION 9

Which three are true about managing memory components in an Oracle database instance? (Choose three.)

- A. With Automatic Shared Memory Management, the database instance can increase the Large Pool size by reducing the Shared Pool size.
- B. With Automatic Memory Management, the database instance can increase the System Global Area size by reducing the Program Global Area size.
- C. Automatically tuned and resized System Global Area components will always revert to their initial sizes after an instance restart.
- D. Automatic Memory Management must be used together with locking the System Global Area into physical memory.
- E. With Automatic Shared Memory Management, the database instance can increase the Program Global Area size by reducing the System Global Area size.
- F. On Line Transaction Processing systems often use less Program Global Area than Decision Support Systems.

Answer: AEF

NEW QUESTION 10

Which three are true about an application container?

- A. It must have an application root PDB.
- B. It can contain multiple applications.
- C. An application PDB can belong to multiple application containers.
- D. Two application containers can share an application seed PDB.
- E. It can contain a single application.
- F. It must have an application seed PDB.

Answer: BDE

NEW QUESTION 10

Which two are true about Oracle Database Configuration Assistant (DBCA) templates? (Choose two.)

- A. The General Purpose of Transaction Processing templates are most suitable when concurrency and recoverability are key criteria.
- B. Oracle DBCA templates can store only logical structure and not database files.
- C. New templates can only be created by modifying an existing user-created template.
- D. The Data Warehouse template is most suitable when transaction response time is the key criterion.
- E. Oracle DBCA templates can be used to create new databases and duplicate existing databases.

Answer: AE

NEW QUESTION 15

On the 10th of August, you implement an incremental database backup strategy and configure a recovery window of five days.

Level 0 backups are taken on the 10th, 17th, and 24th of August.

Differential level 1 incremental backups are taken daily between the level 0 backups. Today is the 26th of August.

Which backups will be obsolete?

- A. all backups prior to 10th of August
- B. all backups prior to 22nd of August
- C. all backups prior to 24th of August
- D. all backups prior to 20th of August
- E. all backups prior to 17th of August

Answer: C

NEW QUESTION 19

Which two are true about Rapid Home Provisioning (RHP), which has been available since Oracle 18c? (Choose two.)

- A. It is an Oracle Database service
- B. It cannot be used to upgrade Oracle Database homes.
- C. It can be used to provision applications.
- D. It can be used to patch Grid Infrastructure homes containing Oracle Restart.
- E. It can be used to provision middleware.

Answer: DE

NEW QUESTION 21

Examine this configuration:

- CDB1 is a container database.
- COMMON_USER_PREFIX is C##.
- PDB1 is a pluggable database contained in CDB1.
- APP1_ROOT is an application container contained in CDB1.
- APP1_PDB1 is an application PDB contained in APP1_ROOT.

You execute these commands successfully:

```
$ sqlplus sys/oracle_4U@localhost:1521/cdb1 as sysdba
```

```
SQL> CREATE USER c##user1 identified by oracle_4U container=all;
User created.
```

```
SQL> ALTER SESSION SET CONTAINER=pdb1;
Session altered.
```

```
SQL> CREATE USER p1_user1 identified by oracle_4U;
User Created.
```

```
SQL> ALTER SESSION SET CONTAINER=app1_root;
Session altered.
```

```
SQL> ALTER PLUGGABLE DATABASE APPLICATION app1_cdb1_app BEGIN INSTALL '1.0';
Session altered.
```

```
SQL> CREATE USER app1_user1 IDENTIFIED BY oracle_4U;
User Created.
```

```
SQL> ALTER PLUGGABLE DATABASE APPLICATION app1_cdb1_app END INSTALL '1.0';
Pluggable database altered.
```

Which two are true? (Choose two.)

- A. APP1_USER1 can be created in PDB1.
- B. APP1_USER1 can be created in CDB1.
- C. APP1_USER1 can have different privileges in each Application PDB contained in APP1_ROOT.
- D. C##_APP_USER1 can be created in CDB1.
- E. P1_USER1 can be created in CDB1.
- F. C##_USER1 will have the same privileges and roles granted in all PDBs in CDB1.

Answer: CF

NEW QUESTION 22

Examine this command:

```
$ rhpctl move database -sourcehome Oracle_home_path -destinationhome Oracle_home_path
```

For which two purposes can you use this command? (Choose two.)

- A. to switch an existing Oracle Database home to a newer release of Oracle software on the same server
- B. to switch to a read-only Oracle home
- C. to switch back to the previous Oracle home as part of a rollback operation
- D. to switch the Oracle Database home when using a centralized Rapid Home Provisioning server
- E. to switch to a patched Oracle Database home

Answer: CE

Explanation:

You can use the `rhpctl move gihome` command with the same syntax to switch from the current Oracle Grid Infrastructure home to a patched home. The `rhpctl` command enables you to switch from your current Oracle Grid Infrastructure or Oracle Database home to a patched Oracle home so that you can provision the new Oracle home as a gold image. You can also use the `rhpctl` command to switch back to the old Oracle home, if you want to roll back the operation.

NEW QUESTION 26

Which two are true about the character sets used in an Oracle database? (Choose two.)

- A. Single-byte character sets provide better performance than multibyte character sets.
- B. Unicode enables information from any language to be stored using a single character set.
- C. Unicode is the only supported character set for Oracle databases created using Database Configuration Assistant (DBCA).

- D. Single-byte character sets always use 7-bit encoding schemes.
- E. Multibyte character sets allow more efficient space utilization than single byte character sets.
- F. Single-byte character sets always use 8-bit encoding schemes.

Answer: AB

NEW QUESTION 30

Which four are true about RMAN backup sets? (Choose four.)

- A. A backup piece can belong to only one backup set.
- B. A data file can be split into multiple sections stored in different backup sets.
- C. A data file can be split into multiple sections stored in different backup pieces in the same backup set.
- D. Blocks from multiple data files can be contained in one backup piece,
- E. A backup set can contain only one backup piece.
- F. A backup set must be written to media.
- G. A backup set must be written to disk.
- H. Blocks from multiple data files can be contained in one backup set,

Answer: BEFH

NEW QUESTION 34

Which two are true about RMAN encryption? (Choose two.)

- A. RMAN encryption keys are stored in a database keystore.
- B. RMAN can encrypt the Oracle Database password file.
- C. Dual-mode encrypted backups can be restored only if both the password and the keystore used for encryption are available.
- D. The SET ENCRYPTION command overrides encryption settings specified by the CONFIGURE ENCRYPTION command.
- E. Password encryption can be persistently configured using the CONFIGURE ENCRYPTION command.

Answer: CD

NEW QUESTION 36

Which two are true about common objects? (Choose two.)

- A. They can be created only in CDB\$ROOT.
- B. They can be only metadata-linked in an application container.
- C. They can exist in user-defined schemas only in application containers.
- D. They can exist in CDB\$ROOT and an application root.
- E. They can be extended data-linked in CDB\$ROOT.
- F. They can be created only in an application root.

Answer: CF

NEW QUESTION 38

Which two are true about server-generated alerts? (Choose two.)

- A. Stateful alerts must be created by a DBA after resolving the problem.
- B. Stateless alerts can be purged manually from the alert history.
- C. Stateless alerts can be cleared manually.
- D. Stateless alerts are automatically cleared.
- E. Stateful alerts are purged automatically from the alert history.

Answer: BC

Explanation:

Except for the tablespace space usage metric, which is database related, the other metrics are instance related. Threshold alerts are also referred to as stateful alerts which are automatically cleared when an alert condition clears. Stateful alert appears in DBA_OUTSTANDING_ALERTS and when cleared go to DBA_ALERT_HISTORY. Other server-generated alerts correspond to specific database events such as ORA-* errors, "Snapshot too old" errors, Recovery Area Low on Free Space, Resumable Session Suspended. These are non threshold based alerts, also referred to as stateless alerts. Stateless alerts go directly to the History table. +++ Most alerts (such as "Out of Space") are cleared automatically when the cause of the problem disappears. However, other alerts (such as generic alert log errors) are sent to you for notification and must be acknowledged by you. After taking the corrective measures, you acknowledge an alert by clearing or purging it. Clearing an alert sends the alert to the Alert History which is accessible from Monitoring sub menu. Purging an alert removes it from the Alert History.

NEW QUESTION 40

Which four are true about performing Tablespace Point -In-Time Recovery (TSPITR) using Recovery Manager (RMAN)?

- A. It can be performed using an auxiliary instance managed by a DBA.
- B. It can be used to recover a truncated table.
- C. RMAN automatically adds any required tablespaces to the recovery set to make it self-contained.
- D. RMAN always includes tablespaces containing undo segments in the recovery set.
- E. It can be performed repeatedly until the correct time is found without using an RMAN catalog.
- F. flashback database must be enabled for it to work.
- G. It can be used to recover a dropped tablespace.
- H. It can be performed using an auxiliary instance managed by RMAN.

Answer: AEFH

NEW QUESTION 41

Which three are true about requirements for various FLASHBACK operations? (Choose three.)

- A. FLASHBACK transaction query requires undo to retrieve all versions of a row that existed between two points in time.
- B. FLASHBACK drop requires that the RECYCLEBIN parameter be set to ON.
- C. FLASHBACK version query requires that the RECYCLEBIN parameter be set to ON.
- D. FLASHBACK DATA ARCHIVE requires undo to store all versions of all rows of a table being tracked.
- E. FLASHBACK drop requires undo to retrieve all versions of a row that existed between two points in time.
- F. FLASHBACK version query requires undo to retrieve all versions of a row that existed between two points in time.

Answer: ABF

NEW QUESTION 46

Which two are true about instance recovery? (Choose two.)

- A. It is not possible if an archived log is missing.
- B. It is performed automatically after the database is opened; however, blocks requiring recovery are not available until they are recovered.
- C. Setting FAST_START_MTTR_TARGET to a lower value reduces instance recovery time by causing dirty buffers to be written to disk more frequently, thereby reducing the number of I/Os needed during instance recovery.
- D. It is performed by the Recovery Writer (RVWR) background process.
- E. Setting FAST_START_MTTR_TARGET to a higher value reduces instance recovery time by causing the log writer to write more frequently, thereby reducing the number of I/Os needed during instance recovery.
- F. It is performed automatically while the database remains in MOUNT state.
- G. Then the database is opened.

Answer: EF

NEW QUESTION 47

Which two are true about OS groups and users for OracleGrid Infrastructure and the Oracle Relational Database Management System (RDBMS)? (Choose two.)

- A. By default, members of the OSASM group can access Automatic Storage Management and RDBMS instances.
- B. The primary group for the Oracle Grid Infrastructure and Oracle Database owners must be the Oracle Inventory group.
- C. The Oracle Grid Infrastructure installation must be owned by the grid user.
- D. The Oracle Grid Infrastructure owner owns Oracle Restart and Oracle Automatic Storage Management binaries.
- E. The Oracle Grid Infrastructure owner must have OSOPER, OSBACKUPDBA, and OSKMDBA as secondary groups.
- F. The same OSDBA group must be used for Automatic Storage Management and the Oracle Database.

Answer: EF

NEW QUESTION 51

Examine this configuration:

- * 1. CDB1 is a container database running in archive log mode.
- * 2. Multiple uncommitted transactions are running in CDB1.
- * 3. Redo log groups 1 and 2 are inactive.
- * 4. Redo log group 3 is the current group.

All members of redo log group 3 are lost before it is archived. Examine these possible steps:

- * 1. SHUTDOWN ABORT
- * 2. STARTUP NOMOUNT
- * 3. STARTUP MOUNT
- * 4. ALTER DATABASE MOUNT
- * 5. RESTORE DATABASE
- * 6. RECOVER DATABASE NOREDO
- * 7. RECOVER DATABASE UNTIL AVAILABLE
- * 8. RESTORE ARCHIVELOG ALL
- * 9. ALTER DATABASE OPEN
- * 10. ALTER DATABASE OPEN RESETLOGS

Choose the minimum required steps in the correct order to recover the database.

- A. 1, 3, 5, 6, 10
- B. 1, 3, 5, 8, 6, 10
- C. 1, 3, 5, 6, 9
- D. 1, 3, 5, 6, 10
- E. 1, 2, 5, 7, 4, 10
- F. 1, 3, 5, 7, 10

Answer: D

NEW QUESTION 52

Automatic Shared Memory Management is disabled for one of your database instances.

Some SQL statements perform poorly due to excessive hard parse activity, thereby degrading performance. What would be your next step?

- A. Run the SQL Access Advisor.
- B. Run the Memory Advisor for the shared pool.
- C. Run the SQL Tuning Advisor.
- D. Run the Memory Advisor for the Program Global Area.
- E. Run the Memory Advisor for the System Global Area.

Answer: B

NEW QUESTION 56

Which three are true about Automatic Workload Repository (AWR)? (Choose three.)

- A. By default, AWR snapshots are taken every 60 minutes.
- B. Its collection level is determined by the value of the STATISTICS_LEVEL database parameter.
- C. By default, AWR snapshots are retained for 7 days.
- D. The taking of AWR snapshots can be disabled.
- E. AWR data is stored in the SYSTEM tablespace.

Answer: ABD

NEW QUESTION 59

Which two are true about the Oracle database methodology? (Choose two.)

- A. The Oracle Database time model should be used to find the database and instance areas most in need of tuning.
- B. Tuning activities should stop once the user is satisfied with performance.
- C. Tuning activities should stop once agreed service levels for performance have been met.
- D. The database instance memory should always be tuned before tuning any file systems.
- E. SQL statements should always be tuned before tuning any file systems.
- F. The alert log should be used to find the database and instance areas most in need of tuning.

Answer: CF

NEW QUESTION 61

Examine this configuration:

1. CDB1 is a container database running in ARCHIVELOG mode.
2. Controlfiles of CDB1 are multiplexed in
'/u01/app/oracle/oradata/CDB1/controlfile/controlfile01.ctl' and
'/u02/app/oracle/fast_recover_area/cdb1/CDB1/controlfile02.ctl'.
3. The only backup of CDB1 was taken when CONTROLFILE AUTOBACKUP was OFF
4. SNAPSHOT CONTROLFILE NAME is
'/u01/app/oracle/product/12.2.0.1/db_1/dbs/snapcf_cdb1.f'.

While CDB1 is open, '/u02/app/oracle/fast_recover_area/cdb1/CDB1/controlfile02.ctl' is accidentally deleted. To recover from this critical failure, you execute these commands:

```
$ rman target sys/oracle_4U@localhost:1521/cdb1

RMAN> SHUTDOWN ABORT
...
Oracle instance shut down

RMAN> STARTUP NOMOUNT

RMAN RESTORE CONTROLFILE FROM
'/u01/app/oracle/oradata/CDB1/controlfile/controlfile01.ctl';
```

What will be the outcome?

- A. It will create '\$ORACLE_HOME/dbs/cdb1/CDB1/controlfile02.ctl'
- B. It will create '/u01/app/oracle/oradata/CDB1/controlfile/controlfile02.ctl'.
- C. It will re-create '/u02/app/oracle/fast_recover_area/cdb1/CDB1/controlfile02.ctl'
- D. It will create '/u01/app/oracle/product/12.2.0.1/db_1/dbs/snapcf_cdb1control02.ctl'.
- E. It will fail because there is no autobackup of the controlfiles.

Answer: C

NEW QUESTION 64

Examine the command for creating pluggable database PDB2 in container database CDB2.

```
CREATE PLUGGABLE DATABASE pdb2
  ADMIN USER pdb2_adm
  IDENTIFIED BY 123pdb
  ROLES=(CONNECT);
```

Select three options, any one of which is required for it to execute successfully. (Choose three.)

- A. Add the FILE_NAME_CONVERT clause to the statement and set the PDB_FILE_NAME_CONVERT parameter.
- B. Add only the CREATE_FILE_DEST clause to the statement.
- C. Set only the PDB_FILE_NAME_CONVERT parameter.
- D. Set the PDB_FILE_NAME_CONVERT parameter and enable OMF.
- E. Enable only OMF.
- F. Add the FILE_NAME_CONVERT clause to the statement and enable Oracle Managed Files (OMF)

Answer: BDE

NEW QUESTION 68

Which two are true about the Automatic Database Diagnostic Monitor (ADDM)? (Choose two.)

- A. It analyzes a period of time corresponding to the 12 hours of activity.
- B. It runs automatically after each AWR snapshot.
- C. A DBA can run it manually.
- D. Results are written to the alert log.
- E. It analyzes a period of time corresponding to the last day of activity.

Answer: BC

NEW QUESTION 73

Examine this configuration:

* 1.The ORCL database data files are in Automatic Storage Management (Oracle ASM) disk group +DATA. * 2.ORCL uses disk group +FRAfor the Fast Recovery Area.

* 3. LISTENER is the listener for ORCL.

* 4. The database, listener, ASM instance, and ASM disk groups are managed by Oracle Restart. 5.All components are currently shut down.

You execute this command:

```
$ srvctl start database -d ORCL
```

What is the outcome?

- A. The ORCL database, the Oracle ASM instances, the +DATA and +FRA disk groups, and the LISTENERare started.
- B. Only the ORCL database instance is started.
- C. Only the ORCL database and the ASM instances are started.
- D. Only the ORCL database instance, the Oracle ASM instance, and the +DATA and +FRA disk groups are started.
- E. Only the ORCL database instance and the +DATA and +FRA disk groups are started.

Answer: D

NEW QUESTION 74

Examine this configuration:

- CDB1is a container database.
- PDB1andPDB2arepluggable databases inCDB1.
- PDB1andPDB2areOPENinREAD WRITEmode.

You execute these commands successfully:

```
$ export ORACLE_SID=CDB1
$ sqlplus / as sysdba
```

```
SQL> ALTER SESSION SET CONTAINER = PDB1;
Session altered.
```

```
SQL> SHUTDOWN IMMEDIATE
```

Which two are true? (Choose two.)

- A. Uncommitted transactions in PDB1 have been rolled back.
- B. PDB1 is closed.
- C. Uncommitted transactions in CDB1 and PDB1 have been rolled back.
- D. CDB1 is shut down.
- E. CDB1 is in MOUNT state

Answer: AB

NEW QUESTION 78

The USERS tablespace consists of data files 3 and 4 and must always be online in read/write mode.

Which two are true about using RMAN to perform an open database back up of this tablespace? (Choose two.)

- A. Backups must be doneincrementally.
- B. Backups must be contained in backup sets.
- C. Backups can be taken only if the database is in ARCHIVELOG mode.
- D. Backups can be done incrementally.
- E. The database must be registered in an RMAN catalog.
- F. Only consistent backups can becreated.

Answer: CE

NEW QUESTION 83

Which three are true about Audit policies In container databases (CDBs)?

- A. All audit records are written to the audit trail in CDB\$ROOT
- B. A common unified audit policy can be created at the application root level.
- C. A common unified audit policy can be created at the CDB level.
- D. An application PDB cannot have a local audit policy.
- E. Fine-grained auditing policies defined in an application root must be manually synchronized by each application PDB contained in the application root.
- F. Application-common unified audit policies defined In an application root must be manually synchronized by each application PDB contained in the application root.

Answer: DEF

NEW QUESTION 87

Which three actions are performed by the Oracle Preinstallation RPM, oracle-database-server-xxxx- preinstall, for Oracle Grid Infrastructure, where xxxx is the Oracle version and release? (Choose three.)

- A. performing checks to ensure minimum configuration requirements for Oracle Grid Infrastructure are met
- B. creating the oracle OS user
- C. creating the OSDBA (dba) group
- D. creating thte oralnventory (oinstall) group
- E. creating the grid OS user
- F. configuring the OS for Oracle Automatic Storage Management shared storage access

Answer: BCD

NEW QUESTION 91

Which three are true about transporting databases across platforms using Recovery Manager (RMAN) image copies? (Choose three.)

- A. By default, the transported database will use Oracle Managed Files (OMF)
- B. Data files can be converted on the destination system.
- C. Data files can be converted on the source system.
- D. A new DBID is automatically created for the transported database.
- E. Databases can be transported between systems with different endian formats.
- F. The password file is automatically converted by RMAN.

Answer: BCE

Explanation:

Password file is automatically converted by RMAN.

NEW QUESTION 95

Which four are true about a Recovery Manager (RMAN) duplication without a TARGET connection? (Choose four.)

- A. The NOREDO clause must be used if the backups of the database being duplicated were taken when the database was in NOARCHIVELOG mode.
- B. The UNDO TABLESPACE clause is always required when no connection exists to the TARGET instance.
- C. RMAN “pushes” the backups of the database to be duplicated over the network to the auxiliary instance.
- D. The NOREDO clause can be used if the backups of the database being duplicated were taken when the database was in ARCHIVELOG mode.
- E. RMAN SBT-based backups of the database to be duplicated can be used by the auxiliary instance.
- F. The UNDO TABLESPACE clause is always required when no connection exists to the recovery catalog and the TARGET database is closed.
- G. The UNDO TABLESPACE clause is always required when no connection exists to the recovery catalog and the TARGET database is opened.
- H. RMAN disk-based backups of the database to be duplicated can be used by the auxiliary instance.

Answer: ABGH

NEW QUESTION 100

For which two requirements can you use the USER_TABLESPACE clause with the CREATE PLUGGABLE DATABASE command? (Choose two.)

- A. to specify a default tablespace in a PDB cloned from another PDB in the same CDB.
- B. to exclude all tablespaces except SYSTEM, SYSAUX, and TEMP when plugging in a PDB
- C. to include specific user tablespaces only when relocating a PDB
- D. to specify the list of user tablespaces to include when moving a non-CDB to a PDB
- E. to exclude a temp tablespace when plugging in a PDB
- F. to specify the list of tablespaces to include when creating a PDB from the CDB seed

Answer: BD

NEW QUESTION 105

Which three are true about the SQL Tuning Advisor? (Choose three.)

- A. It checks each query being analyzed for stale statistics.
- B. It checks each query being analyzed for missing statistics.
- C. It only recommends syntactic changes to SQL statements.
- D. It can recommend semantic changes to SQL statements.
- E. It considers all SQL statements being analyzed by the advisor task as a group.
- F. It builds SQL profiles for each poorly performing SQL statement to prevent regressions.

Answer: ABF

NEW QUESTION 107

Examine these queries and their output:

```
SQL> select log_mode from v$database;
```

```
LOG_MODE
```

```
ARCHIVELOG
```

```
SQL> select property_name, property_value
       2 from database_properties where property_name like '%UNDO%';
```

```
PROPERTY_NAME          PROPERTY_VALUE
```

```
LOCAL_UNDO_ENABLED FALSE
```

```
SQL> select p.name, f.file#, t.name
       2 from v$containers p, v$datafile f, v$tablespace t
       3 where p.con_id=f.con_id
       4 and p.com_id=t.con_id
       5 and t.ts#=f.ts#
       6 order by 1, 2;
```

NAME	FILE#	NAME
CDB\$ROOT	1	SYSTEM
...		
PDB1	24	SYSTEM
...		
PDB2	16	SYSTEM

After a system crash, an instance restart and an attempted opening of the PDBs result in:

```
SQL> startup quiet
ORACLE instance started.
Database mounted.
Database opened.
SQL> alter pluggable database all open;
alter pluggable database all open
*
ERROR at line 1:
ORA-01157: cannot identify/lock data file 24 - see DBWR trace file
ORA-01110: data file 24:
'/u01/oradata/V122CDB1/516000726D464D04E054000C29704164/datafile/o1_mf_system_dmj30kld_.dbf'
```

Which two are true? (Choose two.)

- A. Data file 24 can be recovered while PDB2 is opened.
- B. Data file 24 must be recovered while the CDB is opened.
- C. Data file 24 can be recovered while CDB\$ROOT and PDB\$SEED are opened.
- D. Data file 24 cannot be recovered while the CDB is opened.
- E. Data file 24 must be recovered while PDB2 is closed.

Answer: AB

Explanation:

* 19c: PDB SYSTEM or UNDO Tablespace Recovery: The CDB and all other PDBs can be left opened. 1. Connect to PDB 2. Shutdown abort the PDB, if its not automatically done. sqlplus sys@sales_pdb as sysdba sql> SHUTDOWN ABORT; OR ALTER PLUGGABLE DATABASE CLOSE ABORT; rman target sys@slaes_pdb rman> restore database; rman> recover database; rman> alter pluggable database sales_pdb open;

NEW QUESTION 112

You have configured RMAN SBT channels to write backups to media. You then take an RMAN backup by using this command:

```
RMAN> BACKUP AS COMPRESSED BACKUPSET
      DATABASE
      KEEP UNTIL TIME 'SYSDATE + 730'
      RESTORE POINT 'OLD_CONFIGURATION';
```

Which three are true? (Choose three.)

- A. The restore point is a label for the system change number (SCN) that will be saved two years after the archival backup was taken.
- B. The data file backups in the self-contained archive backup are not considered obsolete for two years regardless of the retention policy.

- C. All archive logs created after this backup are kept for two years.
- D. The SPFILE is included in the self-contained archival backup.
- E. The control file is included in the self-contained archival backup.
- F. The restore point is a label for the system change number (SCN) before the archival backup was taken.

Answer: CDE

NEW QUESTION 117

You plan to install Oracle Grid Infrastructure for a Standalone Server and Oracle Database for the first time on a server. Examine this command and its outcome:

```
# id oracle
uid=54321 (oracle) gid=54321(oinstall) groups=54321(oinstall), 54322 (dba)
```

Which two are true? (Choose two.)

- A. oracle will be an owner of the Oracle Inventory.
- B. oracle must be the owner of every Oracle Database installation.
- C. oracle can own an OracleDatabase installation but not an Oracle Grid Infrastructure installation.
- D. oracle will be granted the SYSASM privilege when installing the Oracle Database software.
- E. The user account, oracle, and group, oinstall, can be used for all Oracle software installations.

Answer: CD

NEW QUESTION 120

Which two are true about diagnosing Oracle Database failure situations using Data Recovery Advisor? (Choose two.)

- A. Using the Data Recovery Advisor LIST FAILURE command always requires that the database for which failures are to be listed is in MOUNT state.
- B. A failure can be closed only when it has been repaired.
- C. Data Recovery Advisor can be used if a database is closed.
- D. The Data Recovery Advisor CHANGE FAILURE command can be used only to change failure priorities.
- E. Data Recovery Advisor can proactively check for failures.

Answer: DE

NEW QUESTION 125

Your container database, CDB1, has an application container, HR_ROOT, with an application PDB, HR_PDB1. You have the required privilege to clone HR_PDB1 to container database CDB2, which does not contain HR_ROOT. Which two are always true? (Choose two.)

- A. CDB1 and CDB2 must be in shared undo mode.
- B. A common user must exist in CDB2 with the CREATE PLUGGABLE DATABASE privilege.
- C. All transactions in HR_PDB1 of CDB1 must commit before the cloning process starts.
- D. Cloning HR_ROOT automatically clones HR_PDB1.
- E. The HR_PDB1 clone created in CDB2 will be in mount state when cloning ends.

Answer: BD

NEW QUESTION 127

Which two are true about changing the LOCAL_UNDO_ENABLED property to false in a CDB? (Choose two.)

- A. After the change, only a common user with the required privilege can create an undo tablespace in CDB\$ROOT.
- B. Any new PDB and existing PDBs are automatically configured to use the default undo tablespace in CDB\$ROOT.
- C. After the change, only one undo tablespace can exist in CDB\$ROOT.
- D. After the change, any user with the required privilege can create an undo tablespace in the PDBs.
- E. Undo tablespaces existing in PDBs must be dropped before the change.
- F. After the change, each existing PDB has to be reopened for the new undo mode to take effect.

Answer: BC

Explanation:

You can set a CDB in local UNDO mode either at CDB creation or by altering the CDB property. When the database property LOCAL_UNDO_ENABLE is FALSE, which is the default, there is only one UNDO tablespace that is created in the CDB root, and that is shared by all containers. When LOCAL_UNDO_ENABLE is TRUE, every container in the CDB uses local undo and each PDB must have its own local UNDO tablespace. To maintain ease of management and provisioning, UNDO tablespace creation happens automatically and does not require any action from the user. When a PDB is opened and an UNDO tablespace is not available, it is automatically created.

NEW QUESTION 132

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 1z0-083 Exam with Our Prep Materials Via below:

<https://www.certleader.com/1z0-083-dumps.html>