

Oracle

Exam Questions 1z0-083

Oracle Database Administration II



NEW QUESTION 1

Which four are true about duplicating a database using Recovery Manager (RMAN)? (Choose four.)

- A. Duplication can be done by having the auxiliary database instance pull backup sets from the target database instance.
- B. A connection to an auxiliary instance is always required.
- C. A subset of the target database can be duplicated.
- D. A new DBID is always created for the duplicated database.
- E. A connection to the recovery catalog instance is always required.
- F. A backup of the target database is always required.
- G. Duplication can be done by having the target database instance push copies to the auxiliary database instance.
- H. A connection to the target database instance is always required.

Answer: ABCG

Explanation:

A duplicate database is a copy of your target database. With the FOR STANDBY clause, it keeps the same unique database identifier (DBID); If FOR STANDBY not specified it creates a new DBID. The duplicate database can include the same content or only a subset from the source database. It can be in the same host or a separate host. The principal work of the duplication is performed by the auxiliary channels. These channels correspond to a server session on the auxiliary instance on the destination host for backup based duplication. For active database duplication the target channels perform the work of pushing data file copies to the auxiliary instance (if number of allocated target channels is greater than the number of allocated auxiliary channels).

NEW QUESTION 2

A container database (CDB) contains two pluggable databases PDB1 and PDB2.

The LOCAL_UNDO_ENABLED database property is set to FALSE in the CDB. Data file 24 of PDB2 was deleted and you need to restore and recover it.

The only RMAN backup that exists was created with the BACKUP DATABASE command while connected to CDB\$ROOT.

Which three are true? (Choose three.)

- A. Data file 24 can be recovered only while connected to PDB2.
- B. Data file 24 can be restored and recovered while connected to CDB\$ROOT.
- C. Data file 24 can be restored only while connected to CDB\$ROOT.
- D. Data file 24 can be restored only while connected to PDB2.
- E. Data file 24 can be recovered while connected to PDB2.
- F. Data file 24 can be recovered while connected to CDB\$ROOT.

Answer: BCF

NEW QUESTION 3

Which three are true about Database Point-in-Time Recovery? (Choose three.)

- A. The database must have FLASHBACK DATABASE ON to perform Database Point-in-Time Recovery.
- B. The database must be in MOUNT state when performing Database Point-in-Time Recovery.
- C. Database Point-in-Time Recovery is performed by the Managed Recovery Process (MRP)
- D. The Database must be in ARCHIVELOG mode.
- E. The target point for the recovery must be specified as a time or System Change Number (SCN).
- F. The database must be open RESETLOGS after Database Point-in-Time Recovery.

Answer: BDF

Explanation:

[https://docs.oracle.com/cd/B19306_01/backup.102/b14192/flashptr006.htm#:~:text=Database%20point%2Din%](https://docs.oracle.com/cd/B19306_01/backup.102/b14192/flashptr006.htm#:~:text=Database%20point%2Din%20time)

NEW QUESTION 4

Examine this configuration:

- > CDB1 is a container database.
- > PDB1 and PDB2 are pluggable databases in CDB1. You execute these commands successfully:

```
$ export ORACLE_SID=cdb1
```

```
$ sqlplus / as sysdba
```

```
SQL> SHUTDOWN IMMEDIATE
```

```
...
```

```
Oracle instance shut down.
```

```
SQL> STARTUP MOUNT
```

```
...
```

```
Database mounted.
```

Which two are true? (Choose two.)

- A. PDB1 and PDB2 are in MOUNT state.
- B. Redo logs are opened.
- C. PDB1 and PDB2 are in READ ONLY state.
- D. CDB\$ROOT is in MOUNT state.
- E. PDB\$SEED is in READ ONLY state.

Answer: BE

NEW QUESTION 5

Which two are true about gathering optimizer statistics? (Choose two.)

- A. Executing DBMS_STATS.GATHER_DATABASE_STATS while connected to CDB\$ROOT gathers object statistics in all open PDBs except PDB\$SEED.
- B. Executing DBMS_STATS.GATHER_DATABASE_STATS while connected to a PDB opened in read/write mode gathers object statistics for that PDB.
- C. Executing DBMS_STATS.GATHER_DATABASE_STATS while connected to CDB\$ROOT gathers object statistics only in CDB\$ROOT.
- D. System statistics can be gathered only while connected to CDB\$ROOT.
- E. Executing DBMS_STATS.GATHER_DATABASE_STATS while connected to CDB\$ROOT gathers object statistics in all open pluggable databases (PDBs)

Answer: BE

Explanation:

[https://mikedietrichde.com/2016/10/21/gather-fixed-objects-stats-in-pdb-as-well/#:~:text=Yes%2C%20you'll%](https://mikedietrichde.com/2016/10/21/gather-fixed-objects-stats-in-pdb-as-well/#:~:text=Yes%2C%20you'll%20)

NEW QUESTION 6

A database is configured in ARCHIVELOG mode.

Full RMAN backups are taken and no backup to trace has been taken of the control file. A media failure has occurred.

In which two scenarios is complete recovery possible? (Choose two.)

- A. when any archived log from, before, or after the most recent backup is corrupt.
- B. after losing all copies of the control file
- C. after losing an archived log from after the most recent backup
- D. after losing an archived log from before the most recent backup
- E. after losing the SYSTEM tablespace

Answer: DE

NEW QUESTION 7

Which three are true about backup, restore, and recovery operations done without using Recovery Manager (RMAN)? (Choose three.)

- A. Backing up a database in NOARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in the MOUNT state.
- B. Backing up a database in ARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in MOUNT state.
- C. An Oracle database can be restored from backup files copied using O/S utilities.
- D. Oracle data file backups, copied using an O/S utility, can be added to the RMAN catalog as IMAGE COPIES.
- E. Backing up a database in NOARCHIVELOG mode using O/S utilities requires that the database instance be shut down.
- F. Oracle archive log backups, copied using an O/S utility, can be added to the RMAN catalog as a backup set.
- G. Backing up a database in ARCHIVELOG mode using O/S utilities requires that the database instance be started and the database be in OPEN state.

Answer: BDE

NEW QUESTION 8

A container database called CDB1 is OMF-enabled.

PDB_FILE_NAME_CONVERT is not configured in CDB1. PDB1 was unplugged from CDB1 earlier in the week. Examine this command, which will be executed in CDB1:

```
CREATE PLUGGABLE DATABASE pdb1
```

```
USING '/u01/app/oracle/oradata/pdb1.xml' SOURCE_FILE_NAME_CONVERT =
```

```
(' /u01/app/oracle/oradata/', '/u02/app/oracle/oradata/');
```

Which two are true? (Choose two.)

- A. PDB1 data files already exist in the correct location.
- B. DBMS_PDB.CHECK_PLUG_COMPATIBILITY must be run in CDB1 before executing the command.
- C. PDB_FILE_NAME_CONVERT must be set before executing the command.
- D. /u01/app/oracle/oradata/pdb1.xml does not contain the current locations of data files for PDB1.
- E. PDB1 must be dropped from CDB1.

Answer: AE

NEW QUESTION 9

Which three are true about Recovery Manager (RMAN) in Oracle Database 19c and later releases? (Choose three.)

- A. It is only possible for RMAN to connect to a pluggable database as a target if an RMAN Virtual Private Catalog is used.
- B. It is always possible for RMAN to connect to a pluggable database as a target if any RMAN Catalog is used.
- C. A Virtual Private Catalog used to register a container database must be created in a pluggable database.
- D. A Virtual Private Catalog used to register a container database can be created in a pluggable database.
- E. It is always possible for RMAN to connect to a pluggable database as a target.
- F. A Virtual Private Catalog used to register a container database can be created in a non-container database.

Answer: DEF

NEW QUESTION 10

Examine this configuration:

- CDB1 is an Oracle Database 12c Release 2 database containing pluggable databases PDB\$SEED, PDB1, and PDB2.
- PDB\$SEED is open READ ONLY
- PDB1 is open READ WRITE

```
> PDB2isMOUNTED.  
> ORACLE_HOMEis/u01/app/oracle/product/18.1.0/dbhome_1.  
You execute these commands before upgrading the database to the current release:  
$ . oraenv  
ORACLE_SID = [cdb1] ? cdb1  
The Oracle base remains unchanged with value /u01/app/oracle  
  
$ $ORACLE_HOME/jdk/bin/java -jar preupgrade.jar TERMINAL TEXT
```

For which databases will fixup scripts be created?

- A. CDB1, PDB\$SEED, PDB1, and PDB2
- B. PDB\$SEED, PDB1, and PDB2 only
- C. CDB1 and PDB\$SEED only
- D. CDB1, PDB1, and PDB2 only
- E. CDB1, PDB\$SEED, and PDB1 only

Answer: E

NEW QUESTION 10

A user complains about poor database performance.

You want to verify if the user's session has waited for certain types of I/O activity. Which view displays all waits waited on by a session at least once?

- A. V\$SESSION_EVENT
- B. V\$SESSTAT
- C. V\$SESSION_WAIT
- D. V\$SESSION_WAIT_CLASS
- E. V\$SESSION

Answer: A

NEW QUESTION 13

Which three are true about opatchauto? (Choose three.)

- A. It performs a shutdown and then a restart of all processes in both Oracle Grid Infrastructure and Oracle Database home during the patching process.
- B. It must be invoked by a user with root user privileges.
- C. Patches are applied via opatchauto.
- D. Users must always input patch plans to opatchauto.
- E. It requires the Oracle Grid Infrastructure and Oracle Database instances to be shut down before being invoked.
- F. It applies patches in nonrolling mode by default.
- G. It is used to apply interim patches to Oracle Grid Infrastructure and Oracle Database home combinations.

Answer: ABC

NEW QUESTION 18

Which two are true about Oracle Database Configuration Assistant (DBCA) templates? (Choose two.)

- A. The General Purpose of Transaction Processing templates are most suitable when concurrency and recoverability are key criteria.
- B. Oracle DBCA templates can store only logical structure and not database files.
- C. New templates can only be created by modifying an existing user-created template.
- D. The Data Warehouse template is most suitable when transaction response time is the key criterion.
- E. Oracle DBCA templates can be used to create new databases and duplicate existing databases.

Answer: AE

NEW QUESTION 19

Which two are true about Rapid Home Provisioning (RHP), which has been available since Oracle 18c? (Choose two.)

- A. It is an Oracle Database service
- B. It cannot be used to upgrade Oracle Database homes.
- C. It can be used to provision applications.
- D. It can be used to patch Grid Infrastructure homes containing Oracle Restart.
- E. It can be used to provision middleware.

Answer: DE

NEW QUESTION 22

Your CDB has two regular PDBs as well as one application container with two application PDBs and an application seed

No changes have been made to the standard PDB\$SEED.

How many default temporary tablespaces can be assigned in the CDB?

- A. three
- B. eight
- C. seven
- D. six
- E. five

Answer: C

NEW QUESTION 25

Which three actions are performed by Database Upgrade Assistant (DBUA)? (Choose three.)

- A. It recompiles all stored PL/SQL code by using utlrlp.sql.
- B. It empties the RECYCLE BIN.
- C. It performs prerequisite checks to verify if the Oracle database is ready for upgrade.
- D. It sets all user tablespaces to “read-only” before starting the upgrade.
- E. It removes the AUDSYS schema and the AUDIT_ADMIN and AUDIT_VIEWER roles
- F. It increases tablespace size, if required, to meet upgrade requirements.

Answer: ACF

NEW QUESTION 27

Which two are true about flashback features in Oracle Database 19c and later releases? (Choose two.)

- A. Flashback logs are automatically purged when DB_FLASHBACK_RETENTION_TARGET is set lower than the time they have already been retained.
- B. Flashback logs are monitored and proactively deleted when beyond the retention period defined in DB_FLASHBACK_RETENTION_TARGET only after there is space pressure.
- C. Flashback logs are monitored and proactively deleted when beyond the retention period defined in DB_FLASHBACK_RETENTION_TARGET before there is space pressure.
- D. Flashback logs are monitored for being older than the retention period defined in DB_FLASHBACK_RETENTION_TARGET and can be deleted by an administrator written event trigger.
- E. Flashback logs are automatically purged whenever the value of DB_FLASHBACK_RETENTION_TARGET is changed.

Answer: BE

NEW QUESTION 30

Which two are true about Oracle Flashback features? (Choose two.)

- A. FLASHBACK QUERY can retrieve REDO records from ONLINE and ARCHIVED REDO LOG files.
- B. FLASHBACKVERSION QUERY can retrieve REDO records from ONLINE and ARCHIVED REDOLOG files.
- C. FLASHBACK TABLE can undrop a column.
- D. FLASHBACK DROP can undrop an index when undropping a table.
- E. After a database is restored from flashback logs using the FLASHBACKDATABASE command, it is sometimes rolled forward using redo logs.

Answer: DE

NEW QUESTION 32

Examine this command:

\$ rhpctl move database –sourcehome Oracle_home_path –destinationhome Oracle_home_path For which two purposes can you use this command? (Choose two.)

- A. to switch an existing Oracle Database home to a newer release of Oracle software on the same server
- B. to switch to a read-only Oracle home
- C. to switch back to the previous Oracle home as part of a rollback operation
- D. to switch the Oracle Database home when using a centralized Rapid Home Provisioning server
- E. to switch to a patched Oracle Database home

Answer: CE

Explanation:

You can use rhpctl move gihome command with the same syntax to switch from the current Oracle Grid Infrastructure home to a patched home. The rhpctl command enables you to switch from your current Oracle Grid Infrastructure or Oracle Database home to patched Oracle home so that you can provision the new Oracle home as gold image. You can also use the rhpctl command to switch back to the old Oracle home, if you want to roll back the operation.

NEW QUESTION 35

Which two are true about SQL Performance Analyzer (SPA)? (Choose two.)

- A. It is integrated with the SQL Access Advisor.
- B. It predicts the impact of system changes on SQL workload response time.
- C. It provides before and after execution statistics for each SQL statement in the analysis task
- D. It offers fine-grained analysis of all the SQL statements in the analysis task as a group.
- E. SQL statements that were originally run concurrently are run concurrently by SPA.

Answer: BD

NEW QUESTION 40

Which three are true about thresholds, metrics, and server-generated alerts? (Choose three.)

- A. All metrics are instance related.
- B. Cleared stateful alerts are displayed by querying DBA_ALERT_HISTORY.
- C. A space usage management alert is automatically cleared after the underlying problem is resolved.
- D. They are generated by SMON when a tablespace is 97% full.
- E. Metrics are statistical counts for a specific unit.
- F. STATISTICS_LEVEL must be set to ALL to generate alerts.

Answer: BCE

NEW QUESTION 42

Which two are true about RMAN encryption? (Choose two.)

- A. RMAN encryption keys are stored in a database keystore.
- B. RMAN can encrypt the Oracle Database password file.
- C. Dual-mode encrypted backups can be restored only if both the password and the keystore used for encryption are available.
- D. The SET ENCRYPTION command overrides encryption settings specified by the CONFIGURE ENCRYPTION command.
- E. Password encryption can be persistently configured using the CONFIGURE ENCRYPTION command.

Answer: CD

NEW QUESTION 45

Which two are true about RMAN duplexed backup sets? (Choose two.)

- A. A duplexed backup set uses the same number of SBT channels as a non-duplexed backup set for the same number of files.
- B. A non-duplexed backup set written to disk can be duplexed to disk by backing up the backup set that is already on disk.
- C. A non-duplexed backup set written to SBT can be duplexed to tape by backing up the backup set that is already on tape.
- D. A non-duplexed backup set written to disk can be duplexed to tape by backing up the backup set that is already on disk.
- E. A non-duplexed backup set written to SBT can be duplexed to disk by backing up the backup set that is already on tape.
- F. A duplexed backup set always uses twice as many SBT channels as a non-duplexed backup set for the same number of files.

Answer: DF

NEW QUESTION 46

Which two are true about server-generated alerts? (Choose two.)

- A. Stateful alerts must be created by a DBA after resolving the problem.
- B. Stateless alerts can be purged manually from the alert history.
- C. Stateless alerts can be cleared manually.
- D. Stateless alerts are automatically cleared.
- E. Stateful alerts are purged automatically from the alert history.

Answer: BC

Explanation:

Except for the tablespace space usage metric, which is database related, the other metrics are instance related. Threshold alerts are also referred to as stateful alerts which are automatically cleared when an alert condition clears. Stateful alert appears in DBA_OUTSTANDING_ALERTS and when cleared go to DBA_ALERT_HISTORY. Other server-generated alerts correspond to specific database events such as ORA-* errors, "Snapshot too old" errors, Recovery Area Low on Free Space, Resumable Session Suspended. These are non threshold based alerts, also referred to as stateless alerts. Stateless alerts go directly to the History table. +++ Most alerts (such as "Out of Space") are cleared automatically when the cause of the problem disappears. However, other alerts (such as generic alert log errors) are sent to you for notification and must be acknowledged by you. After taking the corrective measures, you acknowledge an alert by clearing or purging it. Clearing an alert sends the alert to the Alert History which is accessible from Monitoring sub menu. Purging an alert removes it from the Alert History.

NEW QUESTION 51

Oracle Managed Files (OMF) is enabled in a CDB and this command is successfully executed:

```
CREATE PLUGGABLE DATABASE appl
  AS APPLICATION CONTAINER
  ADMIN USER admin1 IDENTIFIED BY app_123 ROLES=(CONNECT);
```

Which three are true? (Choose three.)

- A. Application PDBs that are subsequently created in the APP1 application container will be cloned from APP1\$SEED.
- B. An application seed PDB is created for APP1.
- C. An application root PDB is created for APP1.
- D. A default service is created for the application root APP1.
- E. Application PDBs that are subsequently created in the APP1 application container will be cloned from PDB\$SEED.
- F. APP1 can never be unplugged.

Answer: ABE

NEW QUESTION 56

Which three are true about Automatic Workload Repository (AWR)? (Choose three.)

- A. By default, AWR snapshots are taken every 60 minutes.
- B. Its collection level is determined by the value of the STATISTICS_LEVEL database parameter.
- C. By default, AWR snapshots are retained for 7 days.
- D. The taking of AWR snapshots can be disabled.
- E. AWR data is stored in the SYSTEM tablespace.

Answer: ABD

NEW QUESTION 57

You must transport the UNIVERSITY tablespace from one database to another. The UNIVERSITY tablespace is currently open read/write. The source and destination platforms have different endian formats. Examine this list of actions:

- * 1. Make the UNIVERSITY tablespace read-only on the source system.
 - * 2. Export the UNIVERSITY tablespace metadata using EXPDP.
 - * 3. Convert the UNIVERSITY tablespace data files to the destination platform format using RMAN on the source system.
 - * 4. Copy the UNIVERSITY tablespace data files to the destination system.
 - * 5. Copy the Data Pump dump set to the destination system.
 - * 6. Convert the UNIVERSITY tablespace data files to the destination platform format using RMAN on the destination system.
 - * 7. Import the UNIVERSITY tablespace metadata using IMPDP.
 - * 8. Make the UNIVERSITY tablespace read/write on the destination system.
- Which is the minimum number of actions required, in the correct order, to transport the UNIVERSITY tablespace?

- A. 1, 2, 4, 5, 7, 8
- B. 1, 2, 4, 6, 7, 8
- C. 1, 2, 3, 4, 5, 7, 8
- D. 1, 2, 3, 4, 5, 6, 7, 8
- E. 2, 4, 5, 6, 7

Answer: B

NEW QUESTION 59

Examine this configuration:

- CDB1 is a container database.
- PDB1 and PDB2 are pluggable databases in CDB1.
- PDB1 and PDB2 are OPEN in READ WRITE mode.

You execute these commands successfully:

```
$ export ORACLE_SID=CDB1
$ sqlplus / as sysdba
```

```
SQL> ALTER SESSION SET CONTAINER = PDB1;
Session altered.
```

```
SQL> SHUTDOWN IMMEDIATE
```

Which two are true? (Choose two.)

- A. Uncommitted transactions in PDB1 have been rolled back.
- B. PDB1 is closed.
- C. Uncommitted transactions in CDB1 and PDB1 have been rolled back.
- D. CDB1 is shut down.
- E. CDB1 is in MOUNT state

Answer: AB

NEW QUESTION 64

Which three are true about Audit policies in container databases (CDBs)?

- A. All audit records are written to the audit trail in CDB\$ROOT
- B. A common unified audit policy can be created at the application root level.
- C. A common unified audit policy can be created at the CDB level.
- D. An application PDB cannot have a local audit policy.
- E. Fine-grained auditing policies defined in an application root must be manually synchronized by each application PDB contained in the application root.
- F. Application-common unified audit policies defined in an application root must be manually synchronized by each application PDB contained in the application root.

Answer: DEF

NEW QUESTION 69

Which three actions are performed by the Oracle Preinstallation RPM, oracle-database-server-xxxx- preinstall, for Oracle Grid Infrastructure, where xxxx is the Oracle version and release? (Choose three.)

- A. performing checks to ensure minimum configuration requirements for Oracle Grid Infrastructure are met
- B. creating the oracle OS user
- C. creating the OSDBA (dba) group
- D. creating the oraInventory (oinstall) group
- E. creating the grid OS user
- F. configuring the OS for Oracle Automatic Storage Management shared storage access

Answer: BCD

NEW QUESTION 71

Which two are true about unplugging an application container from a container database and plugging it into a different container database?

- A. It requires local undo mode in both container databases.
- B. It requires only local undo mode in the database where the application container will be unplugged.
- C. Plugging the application root into a different CDB plugs in all its application PDBs.
- D. Application PDBs in the application container must be unplugged before the application root is unplugged.
- E. Unplugging the application root from a CDB unplugs all its application PDBs.

F. The application root of an application container should be plugged into the other CDB before its application PDBs are plugged in.

Answer: DE

NEW QUESTION 72

Which three are true about transporting databases across platforms using Recovery Manager (RMAN) image copies? (Choose three.)

- A. By default, the transported database will use Oracle Managed Files (OMF)
- B. Data files can be converted on the destination system.
- C. Data files can be converted on the source system.
- D. A new DBID is automatically created for the transported database.
- E. Databases can be transported between systems with different endian formats.
- F. The password file is automatically converted by RMAN.

Answer: BCE

Explanation:

Password file is automatically converted by RMAN.

NEW QUESTION 74

Which three are true about upgrading Oracle Grid Infrastructure? (Choose three.)

- A. A direct upgrade can be performed only from the immediately preceding Oracle Grid Infrastructure version.
- B. The newer version is installed in a separate Oracle Grid Infrastructure home on the same server as the existing version.
- C. An existing Oracle base can be used.
- D. The upgrade process will automatically install all mandatory patches for the current version of Oracle Grid Infrastructure.
- E. Existing Oracle Database instances must be shut down before starting the upgrade.
- F. Only the grid user can perform the upgrade.

Answer: DEF

NEW QUESTION 75

For which two requirements can you use the USER_TABLESPACE clause with the CREATE PLUGGABLE DATABASE command? (Choose two.)

- A. to specify a default tablespace in a PDB cloned from another PDB in the same CDB.
- B. to exclude all tablespaces except SYSTEM, SYSAUX, and TEMP when plugging in a PDB
- C. to include specific user tablespaces only when relocating a PDB
- D. to specify the list of user tablespaces to include when moving a non-CDB to a PDB
- E. to exclude a temp tablespace when plugging in a PDB
- F. to specify the list of tablespaces to include when creating a PDB from the CDB seed

Answer: BD

NEW QUESTION 79

Which three are true about the SQL Tuning Advisor? (Choose three.)

- A. It checks each query being analyzed for stale statistics.
- B. It checks each query being analyzed for missing statistics.
- C. It only recommends syntactic changes to SQL statements.
- D. It can recommend semantic changes to SQL statements.
- E. It considers all SQL statements being analyzed by the advisor task as a group.
- F. It builds SQL profiles for each poorly performing SQL statement to prevent regressions.

Answer: ABF

NEW QUESTION 82

Which three are located by using environment variables? (Choose three.)

- A. the Optimal Flexible Architecture (OFA) compliant path to store Oracle software and configuration files.
- B. the location of Oracle Net Services configuration files
- C. the list of a disk group names to be mounted by an Oracle Automatic Storage Management (ASM) instance at startup
- D. default directories for temporary files used by temporary tablespaces
- E. the temporary disk space used by Oracle Installer during installation
- F. the maximum number of database files that can be opened by a database instance

Answer: ABE

NEW QUESTION 83

Which three are true about Oracle Grid Infrastructure for a Standalone Server?

- A. It includes both Oracle Restart and Oracle Automatic Storage Management (ASM) software.
- B. It creates one disk group during installation.
- C. It requires the operating system oracle_base environment variable to be predefined before installation.
- D. It requires Oracle ASM Filter Driver (ASMD) to manage Automatic Storage Management (ASM) disks
- E. It requires Oracle ASMLib to manage Automatic Storage Management (ASM) disks.
- F. Automatic Storage Management (ASM) requires that O/S groups OSASM and OSDBA be assigned as secondary groups for its installation owner.

Answer: ABD

NEW QUESTION 86

You plan to install Oracle Grid Infrastructure for a Standalone Server and Oracle Database for the first time on a server. Examine this command and its outcome:

```
# id oracle
uid=54321 (oracle) gid=54321(oinstall) groups=54321(oinstall), 54322 (dba)
```

Which two are true? (Choose two.)

- A. oracle will be an owner of the Oracle Inventory.
- B. oracle must be the owner of every Oracle Database installation.
- C. oracle can own an OracleDatabase installation but not an Oracle Grid Infrastructure installation.
- D. oracle will be granted the SYSASM privilege when installing the Oracle Database software.
- E. The user account, oracle, and group, oinstall, can be used for all Oracle software installations.

Answer: CD

NEW QUESTION 87

Which two are true about diagnosing Oracle Database failure situations using Data Recovery Advisor? (Choose two.)

- A. Using the Data Recovery Advisor LIST FAILURE command always requires that the database for which failures are to be listed is in MOUNT state.
- B. A failure can be closed only when it has been repaired.
- C. Data Recovery Advisor can be used if a database is closed.
- D. The Data Recovery Advisor CHANGE FAILURE command can be used only to change failure priorities.
- E. Data Recovery Advisor can proactively check for failures.

Answer: DE

NEW QUESTION 92

Which two are true about Oracle Optimizer Statistics, their use, and their collection? (Choose two.)

- A. The number of table rows is considered when evaluating the cost of accessing a table using an index.
- B. Index balanced B*Tree height is considered when evaluating the cost of using an index.
- C. The Statistics Advisor can help recommend the best way to gather statistics.
- D. Statistics collected using DBMS_STATS always yield the best optimizer result.
- E. The Statistics Advisor generates actions for all recommendations.

Answer: CD

NEW QUESTION 95

Which three methods can be used for heap table data migration after upgrading a database? (Choose three.)

- A. using Database Replay
- B. using SQL Developer
- C. using Oracle Data Pump
- D. using operating system file copy utilities
- E. using Database Upgrade Assistant
- F. using the CREATE TABLE AS SELECT SQL statement

Answer: DEF

NEW QUESTION 97

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

1z0-083 Practice Exam Features:

- * 1z0-083 Questions and Answers Updated Frequently
- * 1z0-083 Practice Questions Verified by Expert Senior Certified Staff
- * 1z0-083 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 1z0-083 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 1z0-083 Practice Test Here](#)