

Exam Questions 1z0-082

Oracle Database Administration I

<https://www.2passeasy.com/dumps/1z0-082/>



NEW QUESTION 1

Which three statements are true about the tools used to configure Oracle Net Services? (Choose three.)

- A. The Oracle Net Configuration Assistant is only used when running the Oracle installer
- B. Oracle Net Manager can be used to centrally configure listeners on any database server target
- C. The lsnrctl utility requires a listener.ora file to exist before it is started
- D. Oracle Net Manager can be used to locally configure naming methods on a database server
- E. Enterprise Manager Cloud Control can be used to centrally configure listeners on any managed database server
- F. Enterprise Manager Cloud Control can be used to centrally configure net service names for any databaseserver target

Answer: BDE

NEW QUESTION 2

Examine this command:

```
CREATE UNDO TABLESPACE undotbs01  
DATAFILE 'undotbs_01.dbf' SIZE 100M  
AUTOEXTEND ON;
```

Which two actions must you take to ensure UNDOTBS01 is used as the default UNDO tablespace? (Choose two.)

- A. Add the SEGMENT SPACE MANAGEMENT AUTO clause
- B. Set UNDO_TABLESPACE to UNDOTBS01
- C. Add the NOLOGGING clause
- D. Make certain that the database operates in automatic undo management mode
- E. Add the ONLINE clause

Answer: BD

NEW QUESTION 3

Which three statements are true about advanced connection options supported by Oracle Net for connection to Oracle Database instances? (Choose three.)

- A. Connect Time Failover requires the use of Transparent Application Failover (TAF)
- B. Source Routing requires the use of a name server
- C. Source Routing enables the use of Connection Manager (CMAN) which enables network traffic to be routed through a firewall
- D. Load Balancing can balance the number of connections to dispatchers when using a Shared Server configuration
- E. Load Balancing requires the use of a name server
- F. Connect Time Failover requires the connect string to have two or more listener addresses configured

Answer: BCF

NEW QUESTION 4

Which two statements are true about date/time functions in a session where NLS_DATE_FORMAT is set to DD-MON-YYYY HH24:MI:SS? (Choose two.)

- A. CURRENT_TIMESTAMP returns the same date and time as SYSDATE with additional details of fractional seconds
- B. SYSDATE can be queried only from the DUAL table
- C. CURRENT_DATE returns the current date and time as per the session time zone
- D. SYSDATE can be used in expressions only if the default date format is DD-MON-RR
- E. SYSDATE and CURRENT_DATE return the current date and time set for the operating system of the database server
- F. CURRENT_TIMESTAMP returns the same date as CURRENT_DATE

Answer: BC

NEW QUESTION 5

You execute this query:

```
SELECT TO_CHAR(NEXT_DAY(LAST_DAY(SYSDATE), 'MON'), 'dd "Monday for" fmMonth rrrr') What is the result?
```

- A. It executes successfully but does not return any result
- B. It returns the date for the first Monday of the next month
- C. It generates an error
- D. It returns the date for the last Monday of the current month

Answer: B

NEW QUESTION 6

You have been tasked to create a table for a banking application. One of the columns must meet three requirements:

- Be stored in a format supporting date arithmetic without using conversion functions
- Store a loan period of up to 10 years
- Be used for calculating interest for the number of days the loan remains unpaid Which data type should you use?

- A. INTERVAL YEAR TO MONTH
- B. INTERVAL DAY TO SECOND
- C. TIMESTAMP WITH LOCAL TIMEZONE
- D. TIMESTAMP
- E. TIMESTAMP WITH TIMEZONE

Answer: B

NEW QUESTION 7

Which two statements are true about the WHERE and HAVING clauses in a SELECT statement? (Choose two.)

- A. Aggregating functions and columns used in HAVING clauses must be specified in the SELECT list of a query
- B. WHERE and HAVING clauses can be used in the same statement only if applied to different table columns
- C. The HAVING clause can be used with aggregating functions in subqueries
- D. The WHERE clause can be used to exclude rows before dividing them into groups
- E. The WHERE clause can be used to exclude rows after dividing them into groups

Answer: CD

NEW QUESTION 8

You execute this command:

```
CREATE BIGFILE TABLESPACE big_tbs
    DATAFILE '/u01/oracle/data/big_f1.dbf'
    SIZE 20G;
```

Sufficient storage is available in filesystem /u01.

Which two statements are true about the BIG_TBS tablespace? (Choose two.)

- A. AUTOEXTEND is possible for the datafile
- B. It must be bigger than the largest SMALLFILE tablespace
- C. Additional data files may not be added
- D. It will be a dictionary-managed tablespace by default
- E. It will always have a 32K blocksize

Answer: AB

NEW QUESTION 9

Which three statements are true about GLOBAL TEMPORARY TABLES? (Choose three.)

- A. A TRUNCATE command issued in a session causes all rows in a GLOBAL TEMPORARY TABLE for the issuing session to be deleted.
- B. GLOBAL TEMPORARY TABLE rows inserted by a session are available to any other session whose user has been granted select on the table.
- C. GLOBAL TEMPORARY TABLE space allocation occurs at session start.
- D. Any GLOBAL TEMPORARY TABLE rows existing at session termination will be deleted.
- E. A GLOBAL TEMPORARY TABLE'S definition is available to multiple sessions.
- F. A DELETE command on a GLOBAL TEMPORARY TABLE cannot be rolled back.

Answer: BCF

NEW QUESTION 10

Which four statements are true regarding primary and foreign key constraints and the effect they can have on table data? (Choose four.)

- A. A table can have only one primary key but multiple foreign keys
- B. A table can have only one primary key and foreign key
- C. The foreign key columns and parent table primary key columns must have the same names
- D. It is possible for child rows that have a foreign key to remain in the child table at the time the parent row is deleted
- E. It is possible for child rows that have a foreign key to be deleted automatically from the child table at the time the parent row is deleted
- F. Only the primary key can be defined at the column and table level
- G. Primary key and foreign key constraints can be defined at both the column and table level

Answer: ACEG

NEW QUESTION 10

Examine the description of the BOOKS table:

Name	Null?	Type
TRANSACTION_ID	NOT NULL	VARCHAR2 (6)
TRANSACTION_DATE		DATE
AMOUNT		NUMBER (10, 2)
CUSTOMER_ID		VARCHAR2 (6)

The table has 100 rows.

Examine this sequence of statements issued in a new session:

```
INSERT INTO books VALUES ('ADV112', 'Adventures of Tom Sawyer', NULL, NULL); SAVEPOINT a;
DELETE FROM books; ROLLBACK TO SAVEPOINT a; ROLLBACK;
```

Which two statements are true? (Choose two.)

- A. The second ROLLBACK command does nothing
- B. The second ROLLBACK command replays the delete
- C. The first ROLLBACK command restores the 101 rows that were deleted, leaving the inserted row still to be committed
- D. The second ROLLBACK command undoes the insert
- E. The first ROLLBACK command restores the 101 rows that were deleted and commits the inserted row

Answer: DE

NEW QUESTION 11

The SALES_Q1 and USERS tablespaces exist in one of your databases and TEMP is a temporary tablespace. Segment creation is not deferred. You execute this command:

```
CREATE USER sales
  IDENTIFIED BY sales_123
  DEFAULT TABLESPACE sales_q1
  TEMPORARY TABLESPACE temp
  QUOTA 5M ON users;
```

Which three statements must be true so that the SALES user can create tables in SALES_Q1? (Choose three.)

- A. The sales user must have a quota on the TEMP tablespace
- B. The sales user must have a quota on the SALES_Q1 tablespace to hold the initial extents of all tables they plan to create in their schema
- C. The sales user must have been granted the CREATE SESSION privilege
- D. The sales user must have their quota on the users tablespace removed
- E. The sales user must have a quota on the SALES_Q1 tablespace to hold all the rows to be inserted into any table in their schema
- F. The sales user must have been granted the CREATE TABLE privilege

Answer: BDF

NEW QUESTION 16

The INVOICE table has a QTY_SOLD column of data type NUMBER and an INVOICE_DATE column of data type DATE. NLS_DATE_FORMAT is set to DD-MON-RR.

Which two are true about data type conversions involving these columns in query expressions? (Choose two.)

- A. CONCAT (qty_sold, invoice_date) : requires explicit conversion
- B. invoice_date = '15-march-2019' : uses implicit conversion
- C. invoice_date > '01-02-2019' : uses implicit conversion
- D. qty_sold BETWEEN '101' AND '110' : uses implicit conversion
- E. qty_sold = '0554982' uses implicit conversion

Answer: BD

NEW QUESTION 18

Examine this command and some partial output:

```
LSNRCTL> start LISTENER_1

Listening Endpoints Summary...
  (DESCRIPTION=(ADDRESS=PROTOCOL=tcp) (HOST=host01.abc.com) (PORT=1562)))
Services Summary...
Service "DB01.abc.com " has 1 instance(s).
  Instance "DB01", status UNKNOWN, has 1 handler(s) for this service...
The command completed successfully
```

Why does the DB01.abc.com service show unknown status?

- A. The service DB01.abc.com is dynamically registered
- B. The LOCAL_LISTENER database parameter is not set to a service name that refers to LISTENER_1
- C. The service DB01.abc.com is statically registered
- D. The listener is not listening on the default port 1521
- E. The SID_LIST_LISTENER section is not contained in the LISTENER.ORA file

Answer: B

NEW QUESTION 22

Which two statements are true about the SET VERIFY ON command? (Choose two.)

- A. It can be used only in SQL*Plus
- B. It displays values for variables used only in the WHERE clause of a query
- C. It can be used in SQL Developer and SQL*Plus
- D. It displays values for variables created by the DEFINE command
- E. It displays values for variables prefixed with &&

Answer: AD

NEW QUESTION 26

Which three statements are true about the Oracle join and ANSI join syntax? (Choose three.)

- A. The Oracle join syntax supports creation of a Cartesian product of two tables
- B. The Oracle join syntax performs better than the SQL:1999 compliant ANSI join syntax

- C. The SQL:1999 compliant ANSI join syntax supports natural joins
- D. The SQL:1999 compliant ANSI join syntax supports creation of a Cartesian product of two tables
- E. The Oracle join syntax only supports right outer joins
- F. The Oracle join syntax supports natural joins
- G. The Oracle join syntax performs less well than the SQL:1999 compliant ANSI join syntax

Answer: CDF

NEW QUESTION 28

Your database instance was shut down normally and then started in NOMOUNT state. You then execute this command:

ALTER DATABASE MOUNT;

Which two actions are performed? (Choose two.)

- A. The online redo logs are opened
- B. The online data files are opened
- C. The alert log records the execution details
- D. The Oracle background processes are started
- E. The initialization parameter file is read
- F. The control file is read

Answer: DF

NEW QUESTION 33

Which three statements are true regarding indexes? (Choose three.)

- A. A UNIQUE index can be altered to be non-unique
- B. A SELECT statement can access one or more indices without accessing any tables
- C. A table belonging to one user can have an index that belongs to a different user
- D. An update to a table can result in updates to any or all of the table's indexes
- E. When a table is dropped and is moved to the RECYCLE BIN, all indexes built on that table are permanently dropped
- F. An update to a table can result in no updates to any of the table's indexes

Answer: ADE

NEW QUESTION 36

Which statement is true about aggregate functions?

- A. Aggregate functions can be nested to any number of levels
- B. The AVG function implicitly converts NULLS to zero
- C. Aggregate functions can be used in any clause of a SELECT statement
- D. The MAX and MIN functions can be used on columns with character data types

Answer: A

NEW QUESTION 37

Which three statements are true about a self-join? (Choose three.)

- A. The ON clause must be used
- B. The query must use two different aliases for the table
- C. It must be an equi join
- D. It must be an inner join
- E. The ON clause can be used
- F. It can be an outer join

Answer: BDE

NEW QUESTION 42

Which two statements are true about trace files produced by the Oracle Database server? (Choose two.)

- A. They can be written by server processes
- B. Trace files are written to the Fast Recovery Area (FRA)
- C. They can be written by background processes
- D. All trace files contain error information that require contacting Oracle Support
- E. Trace file names are based on the database name concatenated with a sequential number

Answer: AC

NEW QUESTION 45

Which three statements are true about table data storage in an Oracle Database? (Choose three.)

- A. Data block headers contain their own Data Block Address (DBA)
- B. A table row piece can be chained across several database blocks
- C. Multiple row pieces from the same row may be stored in different database blocks
- D. Multiple row pieces from the same row may be stored in the same block
- E. Data block free space is always contiguous in the middle of the block
- F. Index block free space is always contiguous in the middle of the block

Answer: BCE

NEW QUESTION 50

In one of your databases, you create a user, HR, and then execute this command: GRANT CREATE SESSION TO hr WITH ADMIN OPTION;
 Which three actions can HR perform? (Choose three.)

- A. Revoke the CREATE SESSION privilege from other users
- B. Revoke the CREATE SESSION privilege from user HR
- C. Log in to the database instance
- D. Grant the CREATE SESSION privilege with ADMIN OPTION to other users
- E. Execute DDL statements in the HR schema
- F. Execute DML statements in the HR schema

Answer: ADE

NEW QUESTION 54

Which two statements are true about views used for viewing tablespace and datafile information? (Choose two.)

- A. Tablespace free space can be viewed in VTABLESPACE
- B. VTABLESPACE displays information that is contained in the controlfile about tablespaces
- C. VTABLESPACE displays information about tablespaces contained in the data dictionary
- D. Tablespace free space can be viewed in DBA_TABLESPACES
- E. A datafile can be renamed when the database is in MOUNT state and the new file name is displayed when querying DBA_DATA_FILES after the database is opened

Answer: BE

NEW QUESTION 58

Examine the description of the EMPLOYEES table:

Name	Null?	Type
-----	-----	-----
EMP_ID	NOT NULL	NUMBER
EMP_NAME		VARCHAR2 (40)
DEPT_ID		NUMBER (2)
SALARY		NUMBER (8, 2)
JOIN_DATE		DATE

Which query is valid?

- A. SELECT dept_id, AVG(MAX(salary)) FROM employees GROUP BY dept_id;
- B. SELECT dept_id, join_date, SUM(salary) FROM employees GROUP BY dept_id;
- C. SELECT dept_id, join_date, SUM(salary) FROM employees GROUP BY dept_id, join_date;
- D. SELECT dept_id, MAX(AVG(salary)) FROM employees GROUP BY dept_id;

Answer: B

NEW QUESTION 63

Which three statements are true about time zones, date data types, and timestamp data types in an Oracle database? (Choose three.)

- A. The CURRENT_TIMESTAMP function returns data without time zone information
- B. A TIMESTAMP WITH LOCAL TIMEZONE data type column is stored in the database using the time zone of the session that inserted the row
- C. A TIMESTAMP data type column contains information about year, month, and day
- D. The DBTIMEZONE function can return an offset from Universal Coordinated Time (UTC)
- E. The SESSIONTIMEZONE function can return an offset from Universal Coordinated Time (UTC)

Answer: ADE

NEW QUESTION 67

Examine the description of the SALES1 table:

Name	Null	Type
-----	-----	-----
SALES_ID	NOT NULL	NUMBER
STORE_ID	NOT NULL	NUMBER
ITEMS_ID		NUMBER
QUANTITY		NUMBER
SALES_DATE		DATE

SALES2 is a table with the same description as SALES1. Some sales data is duplicated in both tables.

You want to display the rows from the SALES1 table which are not present in the SALES2 table. Which set operator generates the required output?

- A. INTERSECT
- B. UNION ALL
- C. UNION
- D. SUBTRACT
- E. MINUS

Answer: E

NEW QUESTION 71

You want to write a query that prompts for two column names and the WHERE condition each time it is executed in a session but only prompts for the table name the first time it is executed.

The variables used in your query are never undefined in your session. Which query can be used?

- A. SELECT &&col1, &&col2FROM &tableWHERE &&condition = &&cond;
- B. SELECT &col1, &col2FROM &&tableWHERE &condition;
- C. SELECT &col1, &col2FROM "&table"WHERE &condition;
- D. SELECT '&&col1', '&&col2'FROM &tableWHERE '&&condition' = '&cond';
- E. SELECT &&col1, &&col2FROM &tableWHERE &&condition;

Answer: B

NEW QUESTION 73

Which two statements are true about the results of using the INTERSECT operator in compound queries? (Choose two.)

- A. Column names in each SELECT in the compound query can be different
- B. The number of columns in each SELECT in the compound query can be different
- C. Reversing the order of the intersected tables can sometimes affect the output
- D. INTERSECT returns rows common to both sides of the compound query
- E. INTERSECT ignores NULLs

Answer: AE

NEW QUESTION 75

In one of your databases, the user HR has the password HRMGR.

You want to connect to a database instance whose listener listens on port 1531 by using this statement: CONNECT HR/HRMGR@orcl

No name server is used.

Which statement is true about ORCL?

- A. It must be the value of the SERVICE_NAMES parameter on the client side
- B. It must resolve to a valid connect descriptor in the server's tnsnames.ora file
- C. It must resolve to a valid connect descriptor in the client's tnsnames.ora file
- D. It must be the name of the database to whose instance HR wishes to connect
- E. It must be the name of the server running the database to whose instance HR wishes to connect

Answer: E

NEW QUESTION 76

Examine the description of the CUSTOMERS table:

Name	Null?	Type
-----	-----	-----
CUST_ID	NOT NULL	VARCHAR2(6)
FIRST_NAME		VARCHAR2(50)
LAST_NAME	NOT NULL	VARCHAR2(50)
ADDRESS		VARCHAR2(50)
CITY		VARCHAR2(25)

You want to display details of all customers who reside in cities starting with the letter D followed by at least two characters.

Which query can be used?

- A. SELECT * FROM customers WHERE city LIKE 'D_%';
- B. SELECT * FROM customers WHERE city = '%D_%';
- C. SELECT * FROM customers WHERE city LIKE 'D_';
- D. SELECT * FROM customers WHERE city = 'D_%';

Answer: A

NEW QUESTION 78

Which three statements are true about external tables in Oracle 18c and later releases? (Choose three.)

- A. External table files can be used for other external tables in a different database
- B. The ORACLE_LOADER access driver can be used to unload data from a database into an external table
- C. The ORACLE_DATAPUMP access driver can be used to unload data from a database into an external table
- D. They cannot be partitioned

- E. The ORACLE_DATAPUMP access driver can be used to load data into a database from an external table
- F. They support UPDATES but not INSERTs and DELETES

Answer: ABF

NEW QUESTION 82

Which two statements are true about Enterprise Manager Database Express? (Choose two.)

- A. It is available only when the database is open
- B. It can be used to perform database recovery
- C. The same port number can be used for Database Express configurations for databases on different hosts
- D. It can be used to switch a database into ARCHIVELOGMODE
- E. The same port number can be used for multiple Database Express configurations for multiple databases on the same host

Answer: DE

NEW QUESTION 87

Which two statements are true about UNDO and REDO? (Choose two.)

- A. The generation of UNDO generates REDO
- B. DML modifies Oracle database objects and only generates UNDO
- C. The generation of REDO generates UNDO
- D. DML modifies Oracle database objects and only generates REDO

Answer: AC

NEW QUESTION 90

Evaluate these commands which execute successfully:

```
CREATE SEQUENCE ord_seq  
    INCREMENT BY 1  
    START WITH 1  
    MAXVALUE 100000  
    CYCLE  
    CACHE 5000;
```

```
CREATE TABLE ord_items (  
    ord_no      NUMBER(4) DEFAULT ord_seq.NEXTVAL NOT NULL,  
    item_no     NUMBER(3),  
    qty         NUMBER(3),  
    expiry_date DATE,  
    CONSTRAINT it_pk PRIMARY KEY (ord_no, item_no),  
    CONSTRAINT ord_fk FOREIGN KEY (ord_no) REFERENCES orders (ord_no));
```

Which two statements are true about the ORD_ITEMS table and the ORD_SEQ sequence? (Choose two.)

- A. If sequence ORD_SEQ is dropped then the default value for column ORD_NO will be NULL for rows inserted into ORD_ITEMS
- B. Any user inserting rows into table ORD_ITEMS must have been granted access to sequence ORD_SEQ
- C. Column ORD_NO gets the next number from sequence ORD_SEQ whenever a row is inserted into ORD_ITEMS and no explicit value is given for ORD_NO
- D. Sequence ORD_SEQ cycles back to 1 after every 5000 numbers and can cycle 20 times
- E. Sequence ORD_SEQ is guaranteed not to generate duplicate numbers

Answer: BE

NEW QUESTION 91

Which three statements are true about the Oracle Data Dictionary? (Choose three.)

- A. Data dictionary views are created by joins of dictionary base tables and DBA-defined tables
- B. The data dictionary is created and maintained by the database administrator
- C. Views with the same name but different prefixes, such as CDB, DBA, ALL and USER, reference the same base tables from the data dictionary
- D. Base tables can be queried directly
- E. It is owned by the SYSTEM user
- F. Usernames of all users including database administrators are stored in the data dictionary

Answer: CDF

NEW QUESTION 96

In which three situations does a new transaction always start? (Choose three.)

- A. when issuing a SELECT FOR UPDATE statement after a CREATE TABLE AS SELECT statement was issued in the same session
- B. when issuing a TRUNCATE statement after a SELECT statement was issued in the same session
- C. when issuing a CREATE TABLE statement after a SELECT statement was issued in the same session
- D. when issuing the first Data Manipulation Language (DML) statement after a COMMIT OR ROLLBACK statement was issued in the same session
- E. when issuing a CREATE INDEX statement after a CREATE TABLE statement completed successfully in the same session
- F. when issuing a DML statement after a DML statement failed in the same session

Answer: ADF

NEW QUESTION 100

Which three statements are true about the DESCRIBE command? (Choose three.)

- A. It displays the PRIMARY KEY constraint for any column or columns that have that constraint
- B. It can be used from SQL Developer
- C. It displays the NOT NULL constraint for any columns that have that constraint
- D. It can be used to display the structure of an existing view
- E. It displays all constraints that are defined for each column
- F. It can be used only from SQL *Plus

Answer: CDF

NEW QUESTION 105

A database is configured to use automatic undo management with temporary undo enabled. An UPDATE is executed on a temporary table. Where is the UNDO stored?

- A. in the undo tablespace
- B. in the SYSAUX tablespace
- C. in the SGA
- D. in the PGA
- E. in the temporary tablespace

Answer: A

NEW QUESTION 106

The ORCL database has RESUMABLE TIMEOUT = 7200 and DEFERRED_SEGMENT_CREATION = FALSE

User U1 has a 1 MB quota in tablespace DATA. U1 executes this command:

```
SQL> CREATE TABLE t1 AS
```

```
(SELECT object_name, sharing, created FROM dba_objects);
```

U1 complains that the command is taking too long to execute.

In the alert log, the database administrator (DBA) finds this: 2017-03-06T12:15:17.183438+05:30

statement in resumable session 'User U1(136), Session 1, Instance 1' was suspended due to ORA-01536: space quota exceeded for tablespace 'DATA'

Which are three actions any one of which the DBA could take to resume the session? (Choose three.)

- A. Add a data file to DATA
- B. Drop other U1 objects in DATA
- C. Increase U1's quota sufficiently in DATA
- D. Set DEFERRED_SEGMENT_CREATION to TRUE
- E. Grant UNLIMITED TABLESPACE to U1
- F. Set AUTOEXTEND ON for data files in DATA

Answer: CDF

NEW QUESTION 111

The SCOTT/TIGER user exists in two databases, BOSTON_DB and DALLAS_DB, in two different locations.

Each database has a tnsnames.ora file defining DALLAS_DB as a service name. Examine this command:

```
CREATE DATABASE LINK dblink1 CONNECT TO scott IDENTIFIED BY tiger USING 'dallas_db';
```

How do you execute the command so that only SCOTT in BOSTON_DB can access the SCOTT schema in DALLAS_DB?

- A. as SCOTT in DALLAS_DB
- B. as SCOTT in BOSTON_DB
- C. as SCOTT in BOSTON_DB and SYS in DALLAS_DB
- D. as SYS in both the databases
- E. as SCOTT in both the databases

Answer: D

NEW QUESTION 115

Your database instance is started with a PFILE.

Examine these parameters:

NAME	TYPE	VALUE
-----	-----	-----
memory_max_target	big integer	0
memory_target	big integer	0
sga_max_size	big integer	2G
sga_target	big integer	2G

You want to increase the size of the buffer cache.

Free memory is available to increase the size of the buffer cache. You execute the command:

```
SQL> ALTER SYSTEM SET DB_CACHE_SIZE=1024M;
```

What is the outcome?

- A. The value is changed only in the PFILE and takes effect at the next instance startup
- B. The value is changed for the current instance and in the PFILE
- C. It fails because the SCOPE clause is missing
- D. Change is applied to the current instance, but does not persist after instance restart

Answer: D

NEW QUESTION 116

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 1z0-082 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 1z0-082 Product From:

<https://www.2passeasy.com/dumps/1z0-082/>

Money Back Guarantee

1z0-082 Practice Exam Features:

- * 1z0-082 Questions and Answers Updated Frequently
- * 1z0-082 Practice Questions Verified by Expert Senior Certified Staff
- * 1z0-082 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 1z0-082 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year