

500-901 Dumps

Cisco Data Center Unified Computing Infrastructure Design

<https://www.certleader.com/500-901-dumps.html>



NEW QUESTION 1

You disassociated a Database Server Service Profile from your existing UCS C240 M4. Then, you associate a Web Server Service Profile to this UCS C240M4. The Database Server Service Profile contained a Scrub Policy enabled for Disk Scrub. The Web Server Service Profile contains a Scrub Policy disabled for Disk Scrub. What will happen after the reboot?

- A. The process will fail because the Service Profiles are fundamentally different
- B. The process will succeed, and server disk content will be preserved
- C. The process will fail because of the differences in the Scrub Policies
- D. The process will succeed, but server disk content will be lost

Answer: C

NEW QUESTION 2

You just installed a group of new Cisco UCS Servers in an ESX Cluster. Now, you want to deploy Nexus 1000v in this virtual environment. Which two statements regarding the scenario are true? (Choose two.)

- A. Nexus 1000v VEM will act as the Control Plane, while Nexus 1000v VSM acts as a remote line card
- B. Nexus 1000v VSM will act as the Control Plane, while Nexus 1000v VEM acts as a remote line card
- C. Nexus 1000v is not supported on ESX
- D. Nexus 1000v VSM is deployed in vCenter, Nexus 1000v VEM is deployed in each ESX Host
- E. Nexus 1000v VEM is deployed in vCenter, Nexus 1000v VSM is deployed in each ESX Host

Answer: BD

NEW QUESTION 3

Which statement is true regarding vNIC Templates and LAN Connectivity Policy?

- A. Network identities for LAN connectivity policy must be pool derived
- B. We can add VLANs to the vNIC template at any time
- C. WE do not need MAC address pool for vNIC Templates
- D. vNIC templates must be created first and then used as a part of the LAN Connectivity Policy

Answer: D

NEW QUESTION 4

Where can World Wide Node Name be defined?

- A. In neither vHBA template nor SAN connectivity policy
- B. In vHBA template only
- C. In SAN connectivity policy only
- D. In both, vHBA template or SAN connectivity policy

Answer: B

NEW QUESTION 5

Which three options can a virtual switch do? (Choose three.)

- A. VLAN tagging is done in UCS Manager
- B. Virtual Machines with a trunk port imposes the VLAN tag
- C. Impose the VLAN tag allocation
- D. Set IP Class-of-Service bits
- E. Allow physical switch to impose the VLAN tag

Answer: ABD

NEW QUESTION 6

An administrator needs to configure NPV between an edge fabric switch which will support application servers, and an upstream core switch. A Fiber Channel (FC) link exist between the two switchers. What two statements are true about roles on the edge fabric switch? (Choose two.)

- A. The port that connects to the core switch will be an NP port.
- B. The ports that connect to the servers will be F ports.
- C. The port that connects the switches is a TE port.
- D. The port that connects to the core switch will be an FP port
- E. The ports that connect to the servers will be N ports.

Answer: AB

NEW QUESTION 7

What is contained in Service Profiles?

- A. Management and server configurations
- B. Identity and state information for a logical server
- C. Application specific service requirements
- D. State information for a physical server

Answer: B

NEW QUESTION 8

Which is a gap of first generation hyperconverged solutions addressed by Cisco HyperFlex?

- A. Integrated networking configuration during deployment
- B. Support for GPUs
- C. Support for multiple hypervisors
- D. Integrated firewall for security monitoring

Answer: A

NEW QUESTION 9

What condition requires Inter VSAN Routing (IVR)?

- A. The targets are in the same Initiator Group.
- B. When the path between source and destination edge VSANs require the traffic to pass through several VSANs before reaching the destination.
- C. When using MDS 9000 series SAN Directors.
- D. Transit VSANs are integral to the IVR architecture and are always required.

Answer: B

NEW QUESTION 10

In the context of Cisco's unified Computing System, which three Cisco best practices are recommended when creating WWN pools? (Choose three.)

- A. All WWN must use "20" for the first octet
- B. Define a standard convention for WWNs agreed upon by all stakeholders for address blocks
- C. Select the default values presented by UCS Central
- D. Use Cisco's OUI (00:25:B5) for the 3rd to 5th octets in WWN
- E. Use the same hex value for 1st and 2nd octets in WWNN and WWPN
- F. Engage the security team to request WWNs

Answer: ADE

NEW QUESTION 10

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 500-901 Exam with Our Prep Materials Via below:

<https://www.certleader.com/500-901-dumps.html>