



**Cisco**

**Exam Questions 300-615**

Troubleshooting Cisco Data Center Infrastructure (DCIT)

## About Exambible

*[Your Partner of IT Exam](#)*

## Found in 1998

Exambible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, Exambible has its unique advantages that other companies could not achieve.

## Our Advances

### \* 99.9% Uptime

All examinations will be up to date.

### \* 24/7 Quality Support

We will provide service round the clock.

### \* 100% Pass Rate

Our guarantee that you will pass the exam.

### \* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

#### NEW QUESTION 1

A mission-critical server is connected to site A. Connectivity to this server is lost from site B because the MAC route is missing in the OTV VDC of the Nexus 7000 in site B due to MAC aging. Which action allows the flooding of the unknown unicast MAC on the Nexus 7000 in the OTV VDC?

- A. Use route-map to advertise this MAC statically and redistribute with ISIS.
- B. Unknown unicast flooding is not allowed.
- C. Use the otv flood mac <> command to selectively flood traffic for a given MAC.
- D. Use the otv isis bfd <> command to configure BFD protocol.

**Answer: B**

#### NEW QUESTION 2

Refer to the exhibit. The HSRP instance on both switches is showing as active. Which action resolves the issue?

- A. Configure the HSRP timers to be the same.
- B. Allow VLAN 100 between the switches.
- C. Configure the IP address of N9K-B on the same subnet as N9K-A.
- D. Configure preempt on only one of the switches.

**Answer: B**

#### NEW QUESTION 3

Refer to the exhibit. vPC between switch1 and switch2 is not working. Which two actions are needed to fix the problem? (Choose two.)

- A. Match vPC domain ID between the two devices.
- B. Configure IP address on the interface.
- C. Activate VLANs on the vPC.
- D. Configure vPC peer link and vPC peer keepalive correctly.
- E. Configure one of the switches as primary for the vPC.

**Answer: AC**

#### NEW QUESTION 4

A customer configures HSRP between two data centers that are interconnected with OTV. The configuration succeeds, but traffic between two ESXi virtual hosts on the same site is routed suboptimally through the OTV overlay. Which two actions optimize the traffic? (Choose two.)

- A. Disable first-hop redundancy.
- B. Filter HSRP traffic by using a Layer 3 VACL on the OTV edge devices.
- C. Filter HSRP by using a Layer 2 MAC-list on the ESXi vSwitch.
- D. Filter HSRP traffic by using a Layer 3 VACL on the ESXi vSwitch.
- E. Filter HSRP by using a Layer 2 MAC-list on the OTV edge devices.

**Answer: AB**

#### NEW QUESTION 5

An engineer removes a VMM domain from an endpoint group called EPG-1, but the distributed port group fails to be deleted. Which action must be taken to resolve the issue?

- A. Remove the port group manually.
- B. Migrate all virtual machines in the EPG-1 to different hypervisors.
- C. Remove the remaining EPGs from the VMM domain.
- D. Migrate all virtual machines in the EPG-1 to different port groups.

**Answer: C**

#### NEW QUESTION 6

Refer to the exhibit. HSRP adjacency fails to form between Nexus7K-1 and Nexus7K-2. Which action should be taken to solve the problem?

- A. Configure preempt on one of the switches in the HSRP group.
- B. Configure the same HSRP priority between the two switches.
- C. Configure the correct subnet mask on Nexus7K-1.
- D. Configure HSRP version 2 on Nexus7K-2.

**Answer: D**

#### NEW QUESTION 7

An attempt to use a global vNIC redundancy template pair results in a service profile that fails to apply. Which action resolves the issues?

- A. Create the peer names before creating the templates.
- B. Assign the secondary template first, and then set the peer name.
- C. Assign both templates simultaneously.
- D. Assign the primary template first, and then set the peer name.

**Answer:** D

#### NEW QUESTION 8

DRAG DROP

Drag and drop the Cisco UCS SNMP fault types from the left onto the correct issues on the right.

Select and Place:

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

#### NEW QUESTION 9

Cisco Unified Computing System Manager raises a critical error message that indicates that the system has overlapping Ethernet and FCoE VLANs. All of the Ethernet traffic on the overlapping VLANs drops. Which action resolves the issue?

- A. Modify the VLAN assignment to vNICs.
- B. Change the PIN groups on the vHBAs.
- C. Modify the FCoE VLAN.
- D. Set the FCoE VLAN as the native VLAN on server uplinks.

**Answer:** A

#### NEW QUESTION 10

A user reports that they cannot reach from a UCS server to an FC Storage array. Which command is used to test communication between an FCF and a target?

- A. fcroute
- B. traceroute
- C. fcping
- D. ping

**Answer:** C

#### NEW QUESTION 10

Refer to the exhibit. A new Cisco Nexus 5548 Switch connects to a network. SAN switching is configured on the switch. The switch fc2/10 NP uplink is shown in the exhibit. Which action ensures that fc2/10 is in an up state?

- A. Replace the SFP port module in fc2/10.
- B. Configure the admin port type E on the upstream switch that connects the port.
- C. Enable NPIV on the upstream switch that connects the port.
- D. Configure the BB\_credit buffers on the upstream switch that connects the port.

**Answer:** C

#### NEW QUESTION 14

A server fails to boot from the operating system after a RAID1 cluster migration. The RAID remains in an inactive state during and after a service profile association. Which action resolves the issue?

- A. Configure the SAN boot target in the service profile.
- B. Configure the SAN boot target to any configuration mode.
- C. Use a predefined local disk configuration policy.
- D. Remove the local disk configuration policy.

**Answer:** C

#### NEW QUESTION 16

One of Cisco Nexus Series interfaces has become errdisabled with the error message “DCX-No ACK in 100 PDUs”. What is the cause of this error?

- A. The host has not responded to the Control Sub-TLV DCBX exchanges of the switch.
- B. The acknowledgement number in the server response has not incremented for 100 exchanges.
- C. Cisco Discovery Protocol is disabled on the switch.
- D. LLDP is disabled on the switch.

**Answer:** B

#### NEW QUESTION 21

A fabric interconnect fails to start and the console displays the loader prompt. Which two actions resolve the issue? (Choose two.)

- A. Load an uncorrupt bootloader image.
- B. Load an uncorrupt kickstart image.
- C. Reconnect L1/L2 cables between the Fis.
- D. Reformat the fabric interconnect.
- E. Load the correct version of the boot image.

**Answer:** BE

#### NEW QUESTION 22

A network administrator attempts to install an application in the Cisco NX-OS Guest shell and receives an error that there is not enough space on the disk. Which command must the administrator run to increase the disk space available in the Guest shell?

- A. guestshell growdisk rootfs [size-in-MB]
- B. guestshell pvextend rootfs [size-in-MB]
- C. guestshell resize rootfs [size-in-MB]
- D. guestshell resize2fs rootfs [size-in-MB]

**Answer:** C

#### NEW QUESTION 23

An engineer is troubleshooting a custom AV pair that was created by a client on an external authentication server to map a read-only role for a specific security domain. Which AV pair solves the problem?

- A. shell:domains=Security\_Domain\_1//Read\_Role\_1|Read\_Role\_2
- B. shell:domains=Security\_Domain\_1/Write\_Role\_1|Read\_Role\_2
- C. shell=Security\_Domain\_1/Read\_Role\_1|Read\_Role\_2
- D. shell:domains=Security\_Domain\_1/Read\_Role\_1|Read\_Role\_2

**Answer:** A

#### NEW QUESTION 24

A server administrator attempts to change the Cisco IMC KVM certificate to one signed by a private CA, but the certificate is not being accepted. What can cause this process to fail?

- A. using a certificate with a password-protected private key
- B. RSA encryption being used in the generation of the certificate.
- C. AES encryption being used in the generation of the certificate.
- D. public IP address of the Cisco IMC not being included in the SAN.

**Answer:** A

#### NEW QUESTION 26

Refer to an exhibit. An engineer is troubleshooting an upgrade failure on a switch. Which action resolves the issue?

- A. Save the system image in NVRAM.
- B. Use the same system image as the kickstart image.
- C. Load a new system image.
- D. Reload the same system image.

**Answer:** C

#### NEW QUESTION 29

.....

## Relate Links

**100% Pass Your 300-615 Exam with Examible Prep Materials**

<https://www.examible.com/300-615-exam/>

## Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.examible.com/>