

300-710 Dumps

Securing Networks with Cisco Firepower (SNCF)

<https://www.certleader.com/300-710-dumps.html>



NEW QUESTION 1

What is a result of enabling Cisco FTD clustering?

- A. For the dynamic routing feature, if the master unit fails, the newly elected master unit maintains all existing connections.
- B. Integrated Routing and Bridging is supported on the master unit.
- C. Site-to-site VPN functionality is limited to the master unit, and all VPN connections are dropped if the master unit fails.
- D. All Firepower appliances can support Cisco FTD clustering.

Answer: C

NEW QUESTION 2

With Cisco Firepower Threat Defense software, which interface mode must be configured to passively receive traffic that passes through the appliance?

- A. inline set
- B. passive
- C. routed
- D. inline tap

Answer: B

NEW QUESTION 3

Which protocol establishes network redundancy in a switched Firepower device deployment?

- A. STP
- B. HSRP
- C. GLBP
- D. VRRP

Answer: A

NEW QUESTION 4

Which interface type allows packets to be dropped?

- A. passive
- B. inline
- C. ERSPAN
- D. TAP

Answer: B

NEW QUESTION 5

Which Cisco Firepower Threat Defense, which two interface settings are required when configuring a routed interface? (Choose two.)

- A. Redundant Interface
- B. EtherChannel
- C. Speed
- D. Media Type
- E. Duplex

Answer: CE

NEW QUESTION 6

Which two dynamic routing protocols are supported in Firepower Threat Defense without using FlexConfig? (Choose two.)

- A. EIGRP
- B. OSPF
- C. static routing
- D. IS-IS
- E. BGP

Answer: CE

NEW QUESTION 7

What are two application layer preprocessors? (Choose two.)

- A. CIFS
- B. IMAP
- C. SSL
- D. DNP3
- E. ICMP

Answer: BC

NEW QUESTION 8

Which two actions can be used in an access control policy rule? (Choose two.)

- A. Block with Reset
- B. Monitor
- C. Analyze
- D. Discover
- E. Block ALL

Answer: AB

NEW QUESTION 9

Which two routing options are valid with Cisco Firepower Threat Defense? (Choose two.)

- A. BGPv6
- B. ECMP with up to three equal cost paths across multiple interfaces
- C. ECMP with up to three equal cost paths across a single interface
- D. BGPv4 in transparent firewall mode
- E. BGPv4 with nonstop forwarding

Answer: AC

NEW QUESTION 10

Which object type supports object overrides?

- A. time range
- B. security group tag
- C. network object
- D. DNS server group

Answer: C

NEW QUESTION 10

Which Cisco Firepower rule action displays an HTTP warning page?

- A. Monitor
- B. Block
- C. Interactive Block
- D. Allow with Warning

Answer: C

NEW QUESTION 13

What is the result of specifying of QoS rule that has a rate limit that is greater than the maximum throughput of an interface?

- A. The rate-limiting rule is disabled.
- B. Matching traffic is not rate limited.
- C. The system rate-limits all traffic.
- D. The system repeatedly generates warnings.

Answer: B

NEW QUESTION 17

In which two places can thresholding settings be configured? (Choose two.)

- A. on each IPS rule
- B. globally, within the network analysis policy
- C. globally, per intrusion policy
- D. on each access control rule
- E. per preprocessor, within the network analysis policy

Answer: AC

NEW QUESTION 19

How many report templates does the Cisco Firepower Management Center support?

- A. 20
- B. 10
- C. 5
- D. unlimited

Answer: D

NEW QUESTION 21

Which report template field format is available in Cisco FMC?

- A. box lever chart
- B. arrow chart
- C. bar chart
- D. benchmark chart

Answer: C

NEW QUESTION 24

DRAG DROP

Drag and drop the steps to restore an automatic device registration failure on the standby Cisco FMC from the left into the correct order on the right. Not all options are used.

Select and Place:

- A. Mastered
- B. Not Mastered

Answer: A

NEW QUESTION 25

Which CLI command is used to generate firewall debug messages on a Cisco Firepower?

- A. system support firewall-engine-debug
- B. system support ssl-debug
- C. system support platform
- D. system support dump-table

Answer: A

NEW QUESTION 30

Which command is typed at the CLI on the primary Cisco FTD unit to temporarily stop running high-availability?

- A. configure high-availability resume
- B. configure high-availability disable
- C. system support network-options
- D. configure high-availability suspend

Answer: B

NEW QUESTION 35

A network engineer is configuring URL Filtering on Firepower Threat Defense. Which two port requirements on the Firepower Management Center must be validated to allow communication with the cloud service? (Choose two.)

- A. outbound port TCP/443
- B. inbound port TCP/80
- C. outbound port TCP/8080
- D. inbound port TCP/443
- E. outbound port TCP/80

Answer: AE

NEW QUESTION 38

Which limitation applies to Cisco Firepower Management Center dashboards in a multidomain environment?

- A. Child domains can view but not edit dashboards that originate from an ancestor domain.
- B. Child domains have access to only a limited set of widgets from ancestor domains.
- C. Only the administrator of the top ancestor domain can view dashboards.
- D. Child domains cannot view dashboards that originate from an ancestor domain.

Answer: D

NEW QUESTION 39

What is a behavior of a Cisco FMC database purge?

- A. User login and history data are removed from the database if the User Activity check box is selected.
- B. Data can be recovered from the device.
- C. The appropriate process is restarted.
- D. The specified data is removed from Cisco FMC and kept for two weeks.

Answer: C

NEW QUESTION 44

Which two packet captures does the FTD LINA engine support? (Choose two.)

- A. Layer 7 network ID
- B. source IP

- C. application ID
- D. dynamic firewall importing
- E. protocol

Answer: BE

NEW QUESTION 49

Which action should you take when Cisco Threat Response notifies you that AMP has identified a file as malware?

- A. Add the malicious file to the block list.
- B. Send a snapshot to Cisco for technical support.
- C. Forward the result of the investigation to an external threat-analysis engine.
- D. Wait for Cisco Threat Response to automatically block the malware.

Answer: A

NEW QUESTION 53

Which connector is used to integrate Cisco ISE with Cisco FMC for Rapid Threat Containment?

- A. pxGrid
- B. FTD RTC
- C. FMC RTC
- D. ISEGrid

Answer: A

NEW QUESTION 58

What is the maximum SHA level of filtering that Threat Intelligence Director supports?

- A. SHA-1024
- B. SHA-4096
- C. SHA-512
- D. SHA-256

Answer: D

NEW QUESTION 62

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 300-710 Exam with Our Prep Materials Via below:

<https://www.certleader.com/300-710-dumps.html>