

# Exam Questions AWS-Certified-Solutions-Architect-Professional

AWS-Certified-Solutions-Architect-Professional

<https://www.2passeasy.com/dumps/AWS-Certified-Solutions-Architect-Professional/>



#### NEW QUESTION 1

By default, Amazon Cognito maintains the last-written version of the data. You can override this behavior and resolve data conflicts programmatically. In addition, push synchronization allows you to use Amazon Cognito to send a silent notification to all devices associated with an identity to notify them that new data is available.

- A. get
- B. post
- C. pull
- D. push

**Answer:** D

**Explanation:** By default, Amazon Cognito maintains the last-written version of the data. You can override this behavior and resolve data conflicts programmatically. In addition, push synchronization allows you to use Amazon Cognito to send a silent push notification to all devices associated with an identity to notify them that new data is available.

Reference: <http://aws.amazon.com/cognito/faqs/>

#### NEW QUESTION 2

An IAM user is trying to perform an action on an object belonging to some other root account's bucket. Which of the below mentioned options will AWS S3 not verify?

- A. The object owner has provided access to the IAM user
- B. Permission provided by the parent of the IAM user on the bucket
- C. Permission provided by the bucket owner to the IAM user
- D. Permission provided by the parent of the IAM user

**Answer:** B

**Explanation:** If the IAM user is trying to perform some action on the object belonging to another AWS user's bucket, S3 will verify whether the owner of the IAM user has given sufficient permission to him. It also verifies the policy for the bucket as well as the policy defined by the object owner.

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/access-control-auth-workflow-object-operation.html>

#### NEW QUESTION 3

In the context of AWS IAM, identify a true statement about user passwords (login profiles).

- A. They must contain Unicode characters.
- B. They can contain any Basic Latin (ASCII) characters.
- C. They must begin and end with a forward slash (/).
- D. They cannot contain Basic Latin (ASCII) characters.

**Answer:** B

**Explanation:** The user passwords (login profiles) of IAM users can contain any Basic Latin (ASCII) characters. Reference:

<http://docs.aws.amazon.com/IAM/latest/UserGuide/LimitationsOnEntities.html>

#### NEW QUESTION 4

An organization is planning to host a Wordpress blog as well a Joomla CMS on a single instance launched with VPC. The organization wants to have separate domains for each application and assign them using Route 53. The organization may have about ten instances each with two applications as mentioned above. While launching the instance, the organization configured two separate network interfaces (primary + ENI) and wanted to have two elastic IPs for that instance. It was suggested to use a public IP from AWS instead of an elastic IP as the number of elastic IPs is restricted. What action will you recommend to the organization?

- A. I agree with the suggestion but will prefer that the organization should use separate subnets with each ENI for different public IPs.
- B. I do not agree as it is required to have only an elastic IP since an instance has more than one ENI and AWS does not assign a public IP to an instance with multiple ENIs.
- C. I do not agree as AWS VPC does not attach a public IP to an ENI; so the user has to use only an elastic IP only.
- D. I agree with the suggestion and it is recommended to use a public IP from AWS since the organization is going to use DNS with Route 53.

**Answer:** B

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. An Elastic Network Interface (ENI) is a virtual network interface that the user can attach to an instance in a VPC.

The user can attach up to two ENIs with a single instance. However, AWS cannot assign a public IP when there are two ENIs attached to a single instance. It is recommended to assign an elastic IP in this scenario. If the organization wants more than 5 EIPs they can request AWS to increase the number.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-eni.html>

#### NEW QUESTION 5

An organization has 4 people in the IT operations team who are responsible to manage the AWS infrastructure. The organization wants to setup that each user will have access to launch and manage an instance in a zone which the other user cannot modify. Which of the below mentioned options is the best solution to set this up?

- A. Create four AWS accounts and give each user access to a separate account.

- B. Create an IAM user and allow them permission to launch an instance of a different sizes only.
- C. Create four IAM users and four VPCs and allow each IAM user to have access to separate VPCs.
- D. Create a VPC with four subnets and allow access to each subnet for the indMdual IAM use

**Answer:** D

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC also work with IAM and the organization can create IAM users who have access to various VPC services. The organization can setup access for the IAM user who can modify the security groups of the VPC. The sample policy is given below:

```
{
"Version": "2012-10-17",
"Statement":
[
{ "Effect": "Allow", "Action": "ec2:RunInstances", "Resource":
["arn:aws:ec2:region::image/ami-*", "arn:aws:ec2:region:account:subnet/subnet-1a2b3c4d", "arn:aws:ec2:region:account:network-interface/*",
"arn:aws:ec2:region:account:volume/*", "arn:aws:ec2:region:account:key-pair/*", "arn:aws:ec2:region:account:security-group/sg-123abc123" ]
}
]
```

With this policy the user can create four subnets in separate zones and provide IAM user access to each subnet

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_IAM.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_IAM.html)

#### NEW QUESTION 6

A user is planning to host a web server as well as an app server on a single EC2 instance which is a part of the public subnet of a VPC. How can the user setup to have two separate public IPs and separate security groups for both the application as well as the web server?

- A. Launch VPC with two separate subnets and make the instance a part of both the subnets.
- B. Launch a VPC instance with two network interface
- C. Assign a separate security group and elastic IP to them.
- D. Launch a VPC instance with two network interface
- E. Assign a separate security group to each and AWS will assign a separate public IP to them.
- F. Launch a VPC with ELB such that it redirects requests to separate VPC instances of the public subne

**Answer:** B

**Explanation:** If you need to host multiple websites(with different IPs) on a single EC2 instance, the following is the suggested method from AWS.

Launch a VPC instance with two network interfaces

Assign elastic IPs from VPC EIP pool to those interfaces (Because, when the user has attached more than one network interface with an instance, AWS cannot assign public IPs to them.)

Assign separate Security Groups if separate Security Groups are needed

This scenario also helps for operating network appliances, such as firewalls or load balancers that have multiple private IP addresses for each network interface.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/MultipleIP.html>

#### NEW QUESTION 7

You have subscribed to the AWS Business and Enterprise support plan. Your business has a backlog of problems, and you need about 20 of your IAM users to open technical support cases. How many users can open technical support cases under the AWS Business and Enterprise support plan?

- A. 5 users
- B. 10 users
- C. Unlimited
- D. 1 user

**Answer:** C

**Explanation:** In the context of AWS support, the Business and Enterprise support plans allow an unlimited number of users to open technical support cases (supported by AWS Identity and Access Management (IAM)). Reference: <https://aws.amazon.com/premiumsupport/faqs/>

#### NEW QUESTION 8

How many g2.2xlarge on-demand instances can a user run in one region without taking any limit increase approval from AWS?

- A. 20
- B. 2
- C. 5
- D. 10

**Answer:** C

**Explanation:** Generally AWS EC2 allows running 20 on-demand instances and 100 spot instances at a time. This limit can be increased by requesting at <https://aws.amazon.com/contact-us/ec2-request>. Excluding certain types of instances, the limit is lower than mentioned above. For g2.2xlarge, the user can run only 5

on-demand instance at a time.

Reference: [http://docs.aws.amazon.com/general/latest/gr/aws\\_service\\_limits.html#limits\\_ec2](http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html#limits_ec2)

#### NEW QUESTION 9

IV|apMySite is setting up a web application in the AWS VPC. The organization has decided to use an AWS RDS instead of using its own DB instance for HA and DR requirements.

The organization also wants to secure RDS access. How should the web application be setup with RDS?

- A. Create a VPC with one public and one private subnet
- B. Launch an application instance in the public subnet while RDS is launched in the private subnet.
- C. Setup a public and two private subnets in different AZs within a VPC and create a subnet group
- D. Launch RDS with that subnet group.
- E. Create a network interface and attach two subnets to it
- F. Attach that network interface with RDS while launching a DB instance.
- G. Create two separate VPCs and launch a Web app in one VPC and RDS in a separate VPC and connect them with VPC peering.

**Answer:** B

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources, such as RDS into a virtual network that the user has defined. Subnets are segments of a VPC's IP address range that the user can designate to a group of VPC resources based on the security and operational needs.

A DB subnet group is a collection of subnets (generally private) that a user can create in a VPC and assign to the RDS DB instances. A DB subnet group allows the user to specify a particular VPC when creating the DB instances. Each DB subnet group should have subnets in at least two Availability Zones in a given region.

Reference: [http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER\\_VPC.html](http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_VPC.html)

#### NEW QUESTION 10

When does an AWS Data Pipeline terminate the AWS Data Pipeline-managed compute resources?

- A. AWS Data Pipeline terminates AWS Data Pipeline-managed compute resources every 2 hours.
- B. When the final activity that uses the resources is running
- C. AWS Data Pipeline terminates AWS Data Pipeline-managed compute resources every 12 hours.
- D. When the final activity that uses the resources has completed successfully or failed

**Answer:** D

**Explanation:** Compute resources will be provisioned by AWS Data Pipeline when the first activity for a scheduled time that uses those resources is ready to run, and those instances will be terminated when the final activity that uses the resources has completed successfully or failed.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

#### NEW QUESTION 10

The Principal element of an IAM policy refers to the specific entity that should be allowed or denied permission, whereas the resource translates to everyone except the specified entity.

- A. NotPrincipal
- B. Vendor
- C. Principal
- D. Action

**Answer:** A

**Explanation:** The element NotPrincipal that is included within your IAM policy statements allows you to specify an exception to a list of principals to whom the access to a specific resource is either allowed or denied. Use the NotPrincipal element to specify an exception to a list of principals. For example, you can deny access to all principals except the one named in the NotPrincipal element.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/reference\\_policies\\_elements.html#Principal](http://docs.aws.amazon.com/IAM/latest/UserGuide/reference_policies_elements.html#Principal)

#### NEW QUESTION 12

Doug has created a VPC with CIDR 10.201.0.0/16 in his AWS account. In this VPC he has created a public subnet with CIDR block 10.201.31.0/24. While launching a new EC2 from the console, he is not able to assign the private IP address 10.201.31.6 to this instance. Which is the most likely reason for this issue?

- A. Private address IP 10.201.31.6 is currently assigned to another interface.
- B. Private IP address 10.201.31.6 is reserved by Amazon for IP networking purposes.
- C. Private IP address 10.201.31.6 is blocked via ACLs in Amazon infrastructure as a part of platform security.
- D. Private IP address 10.201.31.6 is not part of the associated subnet's IP address range

**Answer:** A

**Explanation:** In Amazon VPC, you can assign any Private IP address to your instance as long as it is: Part of the associated subnet's IP address range Not reserved by Amazon for IP networking purposes Not currently assigned to another interface Reference: <http://aws.amazon.com/vpc/faqs/>

#### NEW QUESTION 17

The Statement element, of an AWS IAM policy, contains an array of individual statements. Each individual statement is a(n) block enclosed in braces { }.

- A. XML
- B. JavaScript
- C. JSON
- D. AJAX

**Answer:** C

**Explanation:** The Statement element, of an IAM policy, contains an array of individual statements. Each individual statement is a JSON block enclosed in braces { }.



Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage\\_ElementDescriptions.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html)

#### NEW QUESTION 18

If no explicit deny is found while applying IAM's Policy Evaluation Logic, the enforcement code looks for any instructions that would apply to the request.

- A. "cancel"
- B. "suspend"
- C. "allow"
- D. "valid"

**Answer:** C

**Explanation:** If an explicit deny is not found among the applicable policies for a specific request, IAM's Policy Evaluation Logic checks for any "allow" instructions to check if the request can be successfully completed.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage\\_EvaluationLogic.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_EvaluationLogic.html)

#### NEW QUESTION 20

An organization is hosting a scalable web application using AWS. The organization has configured ELB and Auto Scaling to make the application scalable. Which of the below mentioned statements is not required to be followed for ELB when the application is planning to host a web application on VPC?

- A. The ELB and all the instances should be in the same subnet.
- B. Configure the security group rules and network ACLs to allow traffic to be routed between the subnets in the VPC.
- C. The internet facing ELB should have a route table associated with the internet gateway.
- D. The internet facing ELB should be only in a public subnet

**Answer:** A

**Explanation:** Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Within this virtual private cloud, the user can launch AWS resources, such as an ELB, and EC2 instances. There are two ELBs available with VPC: internet facing and internal (private) ELB. For the internet facing ELB it is required that the ELB should be in a public subnet. After the user creates the public subnet, he should ensure to associate the route table of the public subnet with the internet gateway to enable the load balancer in the subnet to connect with the internet. The ELB and instances can be in a separate subnet. However, to allow communication between the instance and the

ELB the user must configure the security group rules and network ACLs to allow traffic to be routed between the subnets in his VPC.

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/CreateVPCForELB.html>

#### NEW QUESTION 25

An organization (account ID 123412341234) has configured the IAM policy to allow the user to modify his credentials. What will the below mentioned statement allow the user to perform?

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow", "Action": [ "iam:AddUserToGroup",
    "iam:RemoveUserFromGroup", "iam:GetGroup"
    ]!
    "Resource": "arn:aws:iam:: 123412341234:group/TestingGroup"
  ]
}
```

- A. Allow the IAM user to update the membership of the group called TestingGroup
- B. The IAM policy will throw an error due to an invalid resource name
- C. The IAM policy will allow the user to subscribe to any IAM group
- D. Allow the IAM user to delete the TestingGroup

**Answer:** A

**Explanation:** AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (account ID 123412341234) wants their users to manage their subscription to the groups, they should create a relevant policy for that. The below mentioned policy allows the respective IAM user to update the membership of the group called MarketingGroup.

```
{
  "Version": "2012-10-17",
  "Statement": [{
    "Effect": "Allow", "Action": [ "iam:AddUserToGroup",
    "iam:RemoveUserFromGroup", "iam:GetGroup"
    ]!
    "Resource": "arn:aws:iam:: 123412341234:group/ TestingGroup "
  ]
}
```

Reference:

<http://docs.aws.amazon.com/IAM/latest/UserGuide/Credentials-Permissions-examples.html#creds-policies-credentials>

#### NEW QUESTION 29

A user has configured EBS volume with PIOPS. The user is not experiencing the optimal throughput. Which of the following could not be factor affecting I/O performance of that EBS volume?

- A. EBS bandwidth of dedicated instance exceeding the PIOPS
- B. EBS volume size

- C. EC2 bandwidth
- D. Instance type is not EBS optimized

**Answer:** B

**Explanation:** If the user is not experiencing the expected IOPS or throughput that is provisioned, ensure that the EC2 bandwidth is not the limiting factor, the instance is EBS-optimized (or include 10 Gigabit network connectMty) and the instance type EBS dedicated bandwidth exceeds the IOPS more than he has provisioned.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-io-characteristics.html>

### NEW QUESTION 31

How can multiple compute resources be used on the same pipeline in AWS Data Pipeline?

- A. You can use multiple compute resources on the same pipeline by defining multiple cluster objects in your definition file and associating the cluster to use for each actMty via its runsOn field.
- B. You can use multiple compute resources on the same pipeline by defining multiple cluster definition files.
- C. You can use multiple compute resources on the same pipeline by defining multiple clusters for your actMty.
- D. You cannot use multiple compute resources on the same pipelin

**Answer:** A

**Explanation:** Multiple compute resources can be used on the same pipeline in AWS Data Pipeline by defining multiple cluster objects in your definition file and associating the cluster to use for each actMty via its runsOn field, which allows pipelines to combine AWS and on-premise resources, or to use a mix of instance types for their actMties.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

### NEW QUESTION 35

The two policies that you attach to an IAM role are the access policy and the trust policy. The trust policy identifies who can assume the role and grants the permission in the AWS Lambda account principal by adding the action.

- A. aws:AssumeAdmin
- B. lambda:InvokeAsync
- C. sts:|invokeAsync
- D. sts:AssumeRole

**Answer:** D

**Explanation:** The two policies that you attach to an IAM role are the access policy and the trust policy.

Remember that adding an account to the trust policy of a role is only half of establishing the trust relationship. By default, no users in the trusted accounts can assume the role until the administrator for that account grants the users the permission to assume the role by adding the Amazon Resource Name (ARN) of the role to an Allow element for the sts:AssumeRole action.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/id\\_roles\\_manage\\_modify.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/id_roles_manage_modify.html)

### NEW QUESTION 36

The MySecureData company has five branches across the globe. They want to expand their data centers such that their web server will be in the AWS and each branch would have their own database in the local data center. Based on the user login, the company wants to connect to the data center. How can MySecureData company implement this scenario with the AWS VPC?

- A. Create five VPCs with the public subnet for the app server and setup the VPN gateway for each VPN to connect them indMdually.
- B. Use the AWS VPN CloudHub to communicate with multiple VPN connections.
- C. Use the AWS CloudGateway to communicate with multiple VPN connections.
- D. It is not possible to connect different data centers from a single VPC.

**Answer:** B

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. If the organization has multiple VPN connections, he can provide secure communication between sites using the AWS VPN CloudHub.

The VPN CloudHub operates on a simple hub-and-spoke model that the user can use with or without a VPC. This design is suitable for customers with multiple branch offices and existing internet connections who would like to implement a convenient, potentially low-cost hub-and-spoke model for primary or backup connectMty between remote offices.

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPN\\_CloudHub.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPN_CloudHub.html)

### NEW QUESTION 38

Regarding Amazon SNS, you can send notification messages to mobile devices through any of the following supported push notification services, EXCEPT:

- A. Microsoft Windows Mobile Messaging (MWMM)
- B. Google Cloud Messaging for Android (GCM)
- C. Amazon Device Messaging (ADM)
- D. Apple Push Notification Service (APNS)

**Answer:** A

**Explanation:** In Amazon SNS, you have the ability to send notification messages directly to apps on mobile devices. Notification messages sent to a mobile

endpoint can appear in the mobile app as message alerts, badge updates, or even sound alerts. Microsoft Windows Mobile Messaging (MWMM) doesn't exist and is not supported by Amazon SNS.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePush.html>

#### NEW QUESTION 43

You want to define permissions for a role in an IAM policy. Which of the following configuration formats should you use?

- A. An XML document written in the IAM Policy Language
- B. An XML document written in a language of your choice
- C. A JSON document written in the IAM Policy Language
- D. A JSON document written in a language of your choice

**Answer: C**

**Explanation:** You define the permissions for a role in an IAM policy. An IAM policy is a JSON document written in the IAM Policy Language.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/id\\_roles\\_terms-and-concepts.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/id_roles_terms-and-concepts.html)

#### NEW QUESTION 47

Which of the following is NOT an advantage of using AWS Direct Connect?

- A. AWS Direct Connect provides users access to public and private resources by using two different connections while maintaining network separation between the public and private environments.
- B. AWS Direct Connect provides a more consistent network experience than Internet-based connections.
- C. AWS Direct Connect makes it easy to establish a dedicated network connection from your premises to AWS.
- D. AWS Direct Connect reduces your network cost

**Answer: A**

**Explanation:** AWS Direct Connect makes it easy to establish a dedicated network connection from your premises to AWS. Using AWS Direct Connect, you can establish private connectivity between AWS and your datacenter, office, or colocation environment, which in many cases can reduce your network costs, increase bandwidth throughput, and provide a more consistent network experience than Internet-based connections.

By using industry standard 802.1q VLANs, this dedicated connection can be partitioned into multiple virtual interfaces. This allows you to use the same connection to access public resources such as objects stored in Amazon S3 using public IP address space, and private resources such as Amazon EC2 instances running within an Amazon Virtual Private Cloud (VPC) using private IP space, while maintaining network separation between the public and private environments.

Reference: <http://aws.amazon.com/directconnect/#details>

#### NEW QUESTION 52

An organization is setting up an application on AWS to have both High Availability (HA) and Disaster Recovery (DR). The organization wants to have both Recovery point objective (RPO) and Recovery time objective (RTO) of 10 minutes. Which of the below mentioned service configurations does not help the organization achieve the said RPO and RTO?

- A. Take a snapshot of the data every 10 minutes and copy it to the other region.
- B. Use an elastic IP to assign to a running instance and use Route 53 to map the user's domain with that IP.
- C. Create ELB with multi-region routing to allow automated failover when required.
- D. Use an AMI copy to keep the AMI available in other region

**Answer: C**

**Explanation:** AWS provides an on demand, scalable infrastructure. AWS EC2 allows the user to launch On-Demand instances and the organization should create an AMI of the running instance. Copy the AMI to another region to enable Disaster Recovery (DR) in case of region failure. The organization should also use EBS for persistent storage and take a snapshot every 10 minutes to meet Recovery time objective (RTO). They should also setup an elastic IP and use it with Route 53 to route requests to the same IP.

When one of the instances fails the organization can launch new instances and assign the same EIP to a new instance to achieve High Availability (HA). The ELB works only for a particular region and does not route requests across regions.

Reference: [http://d36cz9buwru1tt.clooudfront.net/AWS\\_Disaster\\_Recovery.pdf](http://d36cz9buwru1tt.clooudfront.net/AWS_Disaster_Recovery.pdf)

#### NEW QUESTION 57

An organization is setting up a backup and restore system in AWS of their in premise system. The organization needs High Availability(HA) and Disaster Recovery(DR) but is okay to have a longer recovery time to save costs. Which of the below mentioned setup options helps achieve the objective of cost saving as well as DR in the most effective way?

- A. Setup pre-configured servers and create AMIs. Use EIP and Route 53 to quickly switch over to AWS from in premise.
- B. Setup the backup data on S3 and transfer data to S3 regularly using the storage gateway.
- C. Setup a small instance with AutoScaling; in case of DR start diverting all the load to AWS from on premise.
- D. Replicate on premise DB to EC2 at regular intervals and setup a scenario similar to the pilot light

**Answer: B**

**Explanation:** AWS has many solutions for Disaster Recovery(DR) and High Availability(HA). When the organization wants to have HA and DR but are okay to have a longer recovery time they should select the option backup and restore with S3. The data can be sent to S3 using either Direct Connect, Storage Gateway or over the internet.

The EC2 instance will pick the data from the S3 bucket when started and setup the environment. This process takes longer but is very cost effective due to the low pricing of S3. In all the other options, the EC2 instance might be running or there will be AMI storage costs.

Thus, it will be a costlier option. In this scenario the organization should plan appropriate tools to take a backup, plan the retention policy for data and setup

security of the data.

Reference: [http://d36cz9buwru1tt.cloudfront.net/AWS\\_Disaster\\_Recovery.pdf](http://d36cz9buwru1tt.cloudfront.net/AWS_Disaster_Recovery.pdf)

#### NEW QUESTION 62

Which of the following components of AWS Data Pipeline specifies the business logic of your data management?

- A. Task Runner
- B. Pipeline definition
- C. AWS Direct Connect
- D. Amazon Simple Storage Service (Amazon S3)

**Answer:** B

**Explanation:** A pipeline definition specifies the business logic of your data management.

Reference: <http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/what-is-datapipeline.html>

#### NEW QUESTION 67

What feature of the load balancing service attempts to force subsequent connections to a service to be redirected to the same node as long as it is online?

- A. Node balance
- B. Session retention
- C. Session multiplexing
- D. Session persistence

**Answer:** D

**Explanation:** Session persistence is a feature of the load balancing service. It attempts to force subsequent connections to a service to be redirected to the same node as long as it is online.

Reference:

<http://docs.rackspace.com/loadbalancers/api/v1.0/clb-devguide/content/Concepts-d1e233.html>

#### NEW QUESTION 69

In IAM, which of the following is true of temporary security credentials?

- A. Once you issue temporary security credentials, they cannot be revoked.
- B. None of these are correct.
- C. Once you issue temporary security credentials, they can be revoked only when the virtual MFA device is used.
- D. Once you issue temporary security credentials, they can be revoke

**Answer:** A

**Explanation:** Temporary credentials in IAM are valid throughout their defined duration of time and hence can't be revoked. However, because permissions are evaluated each time an AWS request is made using the credentials, you can achieve the effect of revoking the credentials by changing the permissions for the credentials even after they have been issued. Reference:

[http://docs.aws.amazon.com/IAM/latest/UserGuide/id\\_credentials\\_temp\\_control-access\\_disable-perms.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/id_credentials_temp_control-access_disable-perms.html)

#### NEW QUESTION 72

An organization has created 5 IAM users. The organization wants to give them the same login ID but different passwords. How can the organization achieve this?

- A. The organization should create each user in a separate region so that they have their own URL to login
- B. The organization should create a separate login ID but give the IAM users the same alias so that each one can login with their alias
- C. It is not possible to have the same login ID for multiple IAM users of the same account
- D. The organization should create various groups and add each user with the same login ID to different group
- E. The user can login with their own group ID

**Answer:** C

**Explanation:** AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Whenever the organization is creating an IAM user, there should be a unique ID for each user. It is not possible to have the same login ID for multiple users. The names of users, groups, roles, instance profiles must be alphanumeric, including the following common characters: plus (+), equal (=), comma (,), period (.), at (@), and dash (-).

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/Using\\_SettingUpUser.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_SettingUpUser.html)

#### NEW QUESTION 77

An organization is planning to setup a management network on the AWS VPC. The organization is trying to secure the webserver on a single VPC instance such that it allows the internet traffic as well as the back-end management traffic. The organization wants to make so that the back end management network interface can receive the SSH traffic only from a selected IP range, while the internet facing webserver will have an IP address which can receive traffic from all the internet IPs.

How can the organization achieve this by running web server on a single instance?

- A. It is not possible to have two IP addresses for a single instance.
- B. The organization should create two network interfaces with the same subnet and security group to assign separate IPs to each network interface.
- C. The organization should create two network interfaces with separate subnets so one instance can have two subnets and the respective security groups for



controlled access.

D. The organization should launch an instance with two separate subnets using the same network interface which allows to have a separate CIDR as well as security groups.

**Answer: C**

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. An Elastic Network Interface (ENI) is a virtual network interface that the user can attach to an instance in a VPC. The user can create a management network using two separate network interfaces. For the present scenario it is required that the secondary network interface on the instance handles the public facing traffic and the primary network interface handles the back-end management traffic and it is connected to a separate subnet in the VPC that has more restrictive access controls. The public facing interface, which may or may not be behind a load balancer, has an associated security group to allow access to the server from the internet while the private facing interface has an associated security group allowing SSH access only from an allowed range of IP addresses either within the VPC or from the internet, a private subnet within the VPC or a virtual private gateway.  
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-eni.html>

#### NEW QUESTION 81

An organization is purchasing licensed software. The software license can be registered only to a specific MAC Address. The organization is going to host the software in the AWS environment. How can the organization fulfil the license requirement as the MAC address changes every time an instance is started/stopped/terminated?

- A. It is not possible to have a fixed MAC address with AWS.
- B. The organization should use VPC with the private subnet and configure the MAC address with that subnet
- C. The organization should use VPC with an elastic network interface which will have a fixed MAC Address.
- D. The organization should use VPC since VPC allows to configure the MAC address for each EC2 instance.

**Answer: C**

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. An Elastic Network Interface (ENI) is a virtual network interface that the user can attach to an instance in a VPC. An ENI can include attributes such as: a primary private IP address, one or more secondary private IP addresses, one elastic IP address per private IP address, one public IP address, one or more security groups, a MAC address, a source/destination check flag, and a description. The user can create a network interface, attach it to an instance, detach it from an instance, and attach it to another instance. The attributes of a network interface follow the network interface as it is attached or detached from an instance and reattached to another instance. Thus, the user can maintain a fixed MAC using the network interface.  
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-eni.html>

#### NEW QUESTION 83

ExamKiller has three separate departments and each department has their own AWS accounts. The HR department has created a file sharing site where all the on roll employees' data is uploaded. The Admin department uploads data about the employee presence in the office to their DB hosted in the VPC. The Finance department needs to access data from the HR department to know the on roll employees to calculate the salary based on the number of days that an employee is present in the office.  
How can ExamKiller setup this scenario?

- A. It is not possible to configure VPC peering since each department has a separate AWS account.
- B. Setup VPC peering for the VPCs of Admin and Finance.
- C. Setup VPC peering for the VPCs of Finance and HR as well as between the VPCs of Finance and Admin.
- D. Setup VPC peering for the VPCs of Admin and HR

**Answer: C**

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. A VPC peering connection allows the user to route traffic between the peer VPCs using private IP addresses as if they are a part of the same network. This is helpful when one VPC from the same or different AWS account wants to connect with resources of the other VPC.  
Reference:  
<http://docs.aws.amazon.com/AmazonVPC/latest/PeeringGuide/peering-configurations-full-access.html#three-vpcs-full-access>

#### NEW QUESTION 88

An organization is undergoing a security audit. The auditor wants to view the AWS VPC configurations as the organization has hosted all the applications in the AWS VPC. The auditor is from a remote place and wants to have access to AWS to view all the VPC records.  
How can the organization meet the expectations of the auditor without compromising on the security of their AWS infrastructure?

- A. The organization should not accept the request as sharing the credentials means compromising on security.
- B. Create an IAM role which will have read only access to all EC2 services including VPC and assign that role to the auditor.
- C. Create an IAM user who will have read only access to the AWS VPC and share those credentials with the auditor.
- D. The organization should create an IAM user with VPC full access but set a condition that will not allow to modify anything if the request is from any IP other than the organization's data center.

**Answer: C**

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The VPC also works with IAM and the organization can create IAM users who have access to various VPC services. If an auditor wants to have access to the AWS VPC to verify the rules, the organization should be careful before sharing any data which can allow making updates to the AWS infrastructure. In this scenario it is recommended that the organization creates an IAM user who will have read only access to the VPC. Share the above mentioned credentials with the auditor as it cannot harm the organization. The sample policy is given below:

```
{
  "Effect": "Allow",
  "Action": [ "ec2:DescribeVpcs", "ec2:DescribeSubnets",
```

```
"ec2:DescribeInternetGateways", "ec2:DescribeCustomerGateways", "ec2:DescribeVpnGateways", "ec2:DescribeVpnConnections", "ec2:DescribeRouteTables",
"ec2:DescribeAddresses", "ec2:DescribeSecurityGroups", "ec2:DescribeNetworkAcls", "ec2:DescribeDhcpOptions", "ec2:DescribeTags", "ec2:DescribeInstances"
]!
"Resource": "*"
}
```

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_IANI.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_IANI.html)

#### NEW QUESTION 90

An organization is planning to create a secure scalable application with AWS VPC and ELB. The organization has two instances already running and each instance has an ENI attached to it in addition to a primary network interface. The primary network interface and additional ENI both have an elastic IP attached to it.

If those instances are registered with ELB and the organization wants ELB to send data to a particular EIP of the instance, how can they achieve this?

- A. The organization should ensure that the IP which is required to receive the ELB traffic is attached to a primary network interface.
- B. It is not possible to attach an instance with two ENIs with ELB as it will give an IP conflict error.
- C. The organization should ensure that the IP which is required to receive the ELB traffic is attached to an additional ENI.
- D. It is not possible to send data to a particular IP as ELB will send to any one EI

**Answer:** A

**Explanation:** Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Within this virtual private cloud, the user can launch AWS resources, such as an ELB, and EC2 instances. There are two ELBs available with VPC: internet facing and internal (private) ELB. For the internet facing ELB it is required that the ELB should be in a public subnet.

When the user registers a multi-homed instance (an instance that has an Elastic Network Interface (ENI) attached) with a load balancer, the load balancer will route the traffic to the IP address of the primary network interface (eth0).

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/gs-ec2VPC.html>

#### NEW QUESTION 94

A user is trying to create a PIOPS EBS volume with 3 GB size and 90 IOPS. Will AWS create the volume?

- A. No, since the PIOPS and EBS size ratio is less than 30
- B. Yes, since the ratio between EBS and IOPS is less than 30
- C. No, the EBS size is less than 4GB
- D. Yes, since PIOPS is higher than 100

**Answer:** C

**Explanation:** A Provisioned IOPS (SSD) volume can range in size from 4 GiB to 16 TiB and you can provision up to 20,000 IOPS per volume.

Reference: [http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html#EBSVolumeTypes\\_pio ps](http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html#EBSVolumeTypes_pio ps)

#### NEW QUESTION 96

A user has configured EBS volume with PIOPS. The user is not experiencing the optimal throughput. Which of the following could not be factor affecting I/O performance of that EBS volume?

- A. EBS bandwidth of dedicated instance exceeding the PIOPS
- B. EC2 bandwidth
- C. EBS volume size
- D. Instance type is not EBS optimized

**Answer:** C

**Explanation:** If the user is not experiencing the expected IOPS or throughput that is provisioned, ensure that the EC2 bandwidth is not the limiting factor, the instance is EBS-optimized (or include 10 Gigabit network

connectMty) and the instance type EBS dedicated bandwidth exceeds the IOPS more than he has provisioned.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-io-characteristics.html>

#### NEW QUESTION 97

If a single condition within an IAM policy includes multiple values for one key, it will be evaluated using a logical .

- A. OR
- B. NAND
- C. NOR
- D. AND

**Answer:** A

**Explanation:** If a single condition within an IAM policy includes multiple values for one key, it will be evaluated using a logical OR.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/reference\\_policies\\_elements.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/reference_policies_elements.html)

#### NEW QUESTION 98

Which of the following cache engines does Amazon ElastiCache support?

- A. Amazon ElastiCache supports Memcached and Redis.
- B. Amazon ElastiCache supports Redis and WinCache.
- C. Amazon ElastiCache supports Memcached and Hazelcast.
- D. Amazon ElastiCache supports Memcached onl

**Answer:** A

**Explanation:** The cache engines supported by Amazon ElastiCache are Memcached and Redis.  
Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/SelectEngine.html>

#### NEW QUESTION 102

You have been given the task to define multiple AWS Data Pipeline schedules for different actMties in the same pipeline. Which of the following would successfully accomplish this task?

- A. Creating multiple pipeline definition files
- B. Defining multiple pipeline definitions in your schedule objects file and associating the desired schedule to the correct actMty via its schedule field
- C. Defining multiple schedule objects in your pipeline definition file and associating the desired schedule to the correct actMty via its schedule field
- D. Defining multiple schedule objects in the schedule field

**Answer:** C

**Explanation:** To define multiple schedules for different actMties in the same pipeline, in AWS Data Pipeline, you should define multiple schedule objects in your pipeline definition file and associate the desired schedule to the correct actMty via its schedule field. As an example of this, it could allow you to define a pipeline in which log files are stored in Amazon S3 each hour to drive generation of an aggregate report once a day. Reference: <https://aws.amazon.com/datapipeline/faqs/>

#### NEW QUESTION 107

Which statement is NOT true about a stack which has been created in a Virtual Private Cloud (VPC) in AWS OpsWorks?

- A. Subnets whose instances cannot communicate with the Internet are referred to as public subnets.
- B. Subnets whose instances can communicate only with other instances in the VPC and cannot communicate directly with the Internet are referred to as private subnets.
- C. All instances in the stack should have access to any package repositories that your operating system depends on, such as the Amazon Linux or Ubuntu Linux repositories.
- D. Your app and custom cookbook repositories should be accessible for all instances in the stac

**Answer:** A

**Explanation:** In AWS OpsWorks, you can control user access to a stack's instances by creating it in a virtual private cloud (VPC). For example, you might not want users to have direct access to your stack's app servers or databases and instead require that all public traffic be channeled through an Elastic Load Balancer. A VPC consists of one or more subnets, each of which contains one or more instances. Each subnet has an associated routing table that directs outbound traffic based on its destination IP address.

Instances within a VPC can generally communicate with each other, regardless of their subnet. Subnets whose instances can communicate with the Internet are referred to as public subnets. Subnets whose instances can communicate only with other instances in the VPC and cannot communicate directly with the Internet are referred to as private subnets.

AWS OpsWorks requires the VPC to be configured so that every instance in the stack, including instances in private subnets, has access to the following endpoints:

The AWS OpsWorks service, <https://opsworks-instance-service.us-east-1.amazonaws.com> . Amazon S3

The package repositories for Amazon Linux or Ubuntu 12.04 LTS, depending on which operating system you specify.

Your app and custom cookbook repositories. Reference:

<http://docs.aws.amazon.com/opsworks/latest/userguide/workingstacks-vpc.html#workingstacks-vpc-basi> cs

#### NEW QUESTION 109

By default, temporary security credentials for an IAM user are valid for a maximum of 12 hours, but you can request a duration as long as hours.

- A. 24
- B. 36
- C. 10
- D. 48

**Answer:** B

**Explanation:** By default, temporary security credentials for an IAM user are valid for a maximum of 12 hours, but you can request a duration as short as 15 minutes or as long as 36 hours.

Reference: <http://docs.aws.amazon.com/STS/latest/UsingSTS/CreatingSessionTokens.html>

#### NEW QUESTION 114

One of the AWS account owners faced a major challenge in June as his account was hacked and the hacker deleted all the data from his AWS account. This resulted in a major blow to the business.

Which of the below mentioned steps would not have helped in preventing this action?

- A. Setup an MFA for each user as well as for the root account user.
- B. Take a backup of the critical data to offsite / on premise.
- C. Create an AMI and a snapshot of the data at regular intervals as well as keep a copy to separate regions.
- D. Do not share the AWS access and secret access keys with others as well do not store it inside programs, instead use IAM roles.



**Answer:** C

**Explanation:** AWS security follows the shared security model where the user is as much responsible as Amazon. If the user wants to have secure access to AWS while hosting applications on EC2, the first security rule to follow is to enable MFA for all users. This will add an added security layer. In the second step, the user should never give his access or secret access keys to anyone as well as store inside programs. The better solution is to use IAM roles. For critical data of the organization, the user should keep an offsite/ in premise backup which will help to recover critical data in case of security breach.

It is recommended to have AWS AMIs and snapshots as well as keep them at other regions so that they will help in the DR scenario. However, in case of a data security breach of the account they may not be very helpful as hacker can delete that.

Therefore, creating an AMI and a snapshot of the data at regular intervals as well as keep a copy to separate regions, would not have helped in preventing this action.

Reference: [http://media.amazonwebservices.com/pdf/AWS\\_Security\\_Whitepaper.pdf](http://media.amazonwebservices.com/pdf/AWS_Security_Whitepaper.pdf)

#### NEW QUESTION 117

With Amazon Elastic MapReduce (Amazon EMR) you can analyze and process vast amounts of data. The cluster is managed using an open-source framework called Hadoop.

You have set up an application to run Hadoop jobs. The application reads data from DynamoDB and generates a temporary file of 100 TBs.

The whole process runs for 30 minutes and the output of the job is stored to S3. Which of the below mentioned options is the most cost effective solution in this case?

- A. Use Spot Instances to run Hadoop jobs and configure them with EBS volumes for persistent data storage.
- B. Use Spot Instances to run Hadoop jobs and configure them with ephemeral storage for output file storage.
- C. Use an on demand instance to run Hadoop jobs and configure them with EBS volumes for persistent storage.
- D. Use an on demand instance to run Hadoop jobs and configure them with ephemeral storage for output file storage.

**Answer:** B

**Explanation:** AWS EC2 Spot Instances allow the user to quote his own price for the EC2 computing capacity. The user can simply bid on the spare Amazon EC2 instances and run them whenever his bid exceeds the current Spot Price. The Spot Instance pricing model complements the On-Demand and Reserved Instance pricing models, providing potentially the most cost-effective option for obtaining compute capacity, depending on the application. The only challenge with a Spot Instance is data persistence as the instance can be terminated whenever the spot price exceeds the bid price.

In the current scenario a Hadoop job is a temporary job and does not run for a longer period. It fetches data from a persistent DynamoDB. Thus, even if the instance gets terminated there will be no data loss and the job can be re-run. As the output files are large temporary files, it will be useful to store data on ephemeral storage for cost savings.

Reference: <http://aws.amazon.com/ec2/purchasing-options/spot-instances/>

#### NEW QUESTION 119

True or False : "In the context of Amazon ElastiCache, from the application's point of view, connecting to the cluster configuration endpoint is no different than connecting directly to an indMdual cache node."

- A. True, from the application's point of view, connecting to the cluster configuration endpoint is no different than connecting directly to an indMdual cache node since, each has a unique node identifier.
- B. True, from the application's point of view, connecting to the cluster configuration endpoint is no different than connecting directly to an indMdual cache node.
- C. False, you can connect to a cache node, but not to a cluster configuration endpoint.
- D. False, you can connect to a cluster configuration endpoint, but not to a cache nod

**Answer:** B

**Explanation:** This is true. From the application's point of view, connecting to the cluster configuration endpoint is no different than connecting directly to an indMdual cache node. In the process of connecting to cache nodes, the application resolves the configuration endpoint's DNS name. Because the configuration endpoint maintains CNAME entries for all of the cache nodes, the DNS name resolves to one of the nodes; the client can then connect to that node.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/AutoDiscovery.HowAutoDiscoveryWorks.html>

#### NEW QUESTION 123

An organization is setting up a highly scalable application using Elastic Beanstalk. They are using Elastic Load Balancing (ELB) as well as a Virtual Private Cloud (VPC) with public and private subnets. They have the following requirements:

- . All the EC2 instances should have a private IP
- . All the EC2 instances should receive data via the ELB's. Which of these will not be needed in this setup?

- A. Launch the EC2 instances with only the public subnet.
- B. Create routing rules which will route all inbound traffic from ELB to the EC2 instances.
- C. Configure ELB and NAT as a part of the public subnet only.
- D. Create routing rules which will route all outbound traffic from the EC2 instances through NA

**Answer:** A

**Explanation:** The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. If the organization wants the Amazon EC2 instances to have a private IP address, he should create a public and private subnet for VPC in each Availability Zone (this is an AWS Elastic Beanstalk requirement). The organization should add their public resources, such as ELB and NAT to the public subnet, and AWS Elastic Beanstalk will assign them unique elastic IP addresses (a static, public IP address). The organization should launch Amazon EC2 instances in a private subnet so that AWS Elastic Beanstalk assigns them non-routable private IP addresses. Now the organization should configure route tables with the following rules:

- . route all inbound traffic from ELB to EC2 instances
- . route all outbound traffic from EC2 instances through NAT

Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/AWSHowTo-vpc.html>



#### NEW QUESTION 125

An organization has created multiple components of a single application for compartmentalization. Currently all the components are hosted on a single EC2 instance. Due to security reasons the organization wants to implement two separate SSLs for the separate modules although it is already using VPC. How can the organization achieve this with a single instance?

- A. You have to launch two instances each in a separate subnet and allow VPC peering for a single IP.
- B. Create a VPC instance which will have multiple network interfaces with multiple elastic IP addresses.
- C. Create a VPC instance which will have both the ACL and the security group attached to it and have separate rules for each IP address.
- D. Create a VPC instance which will have multiple subnets attached to it and each will have a separate IP address.

**Answer:** B

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. With VPC the user can specify multiple private IP addresses for his instances. The number of network interfaces and private IP addresses that a user can specify for an instance depends on the instance type. With each network interface the organization can assign an EIP. This scenario helps when the user wants to host multiple websites on a single EC2 instance by using multiple SSL certificates on a single server and associating each certificate with a specific EIP address. It also helps in scenarios for operating network appliances, such as firewalls or load balancers that have multiple private IP addresses for each network interface.  
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/NIultipleIP.html>

#### NEW QUESTION 127

An organization is making software for the CIA in US

- A. CIA agreed to host the application on AWS but in a secure environment
- B. The organization is thinking of hosting the application on the AWS GovCloud region
- C. Which of the below mentioned difference is not correct when the organization is hosting on the AWS GovCloud in comparison with the AWS standard region?
- D. The billing for the AWS GovCloud will be in a different account than the Standard AWS account.
- E. GovCloud region authentication is isolated from Amazon.com.
- F. Physical and logical administrative access only to U.S. persons.
- G. persons.
- H. It is physically isolated and has logical network isolation from all the other region

**Answer:** A

**Explanation:** AWS GovCloud (US) is an isolated AWS region designed to allow U.S. government agencies and customers to move sensitive workloads into the cloud by addressing their specific regulatory and compliance requirements. The AWS GovCloud (US) Region adheres to the U.S. International Traffic in Arms Regulations (ITAR) requirements. It has added advantages, such as: Restricting physical and logical administrative access to U.S. persons only. There will be a separate AWS GovCloud (US) credentials, such as access key and secret access key than the standard AWS account. The user signs in with the IAM user name and password. The AWS GovCloud (US) Region authentication is completely isolated from Amazon.com. If the organization is planning to host on EC2 in AWS GovCloud then it will be billed to standard AWS account of organization since AWS GovCloud billing is linked with the standard AWS account and is not billed separately.  
Reference: <http://docs.aws.amazon.com/govcloud-us/latest/UserGuide/whatis.html>

#### NEW QUESTION 129

How does in-memory caching improve the performance of applications in ElastiCache?

- A. It improves application performance by deleting the requests that do not contain frequently accessed data.
- B. It improves application performance by implementing good database indexing strategies.
- C. It improves application performance by using a part of instance RAM for caching important data.
- D. It improves application performance by storing critical pieces of data in memory for low-latency access

**Answer:** D

**Explanation:** In Amazon ElastiCache, in-memory caching improves application performance by storing critical pieces of data in memory for low-latency access. Cached information may include the results of I/O-intensive database queries or the results of computationally intensive calculations.  
Reference: <http://aws.amazon.com/elasticache/faqs/#g4>

#### NEW QUESTION 131

A user is thinking to use EBS PIOPS volume. Which of the below mentioned options is a right use case for the PIOPS EBS volume?

- A. Analytics
- B. System boot volume
- C. MongoDB
- D. Log processing

**Answer:** C

**Explanation:** Provisioned IOPS volumes are designed to meet the needs of I/O-intensive workloads, particularly database workloads that are sensitive to storage performance and consistency in random access I/O throughput. Provisioned IOPS volumes are designed to meet the needs of I/O-intensive workloads, particularly database workloads, that are sensitive to storage performance and consistency in random access I/O throughput business applications, database workloads, such as NoSQL DB, RDBMS, etc. Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html>

#### NEW QUESTION 134

An organization is setting up a multi-site solution where the application runs on premise as well as on AWS to achieve the minimum recovery time objective (RTO).

Which of the below mentioned configurations will not meet the requirements of the multi-site solution scenario?

- A. Configure data replication based on RTO.
- B. Keep an application running on premise as well as in AWS with full capacity.
- C. Setup a single DB instance which will be accessed by both sites.
- D. Setup a weighted DNS service like Route 53 to route traffic across site

**Answer:** C

**Explanation:** AWS has many solutions for DR(Disaster recovery) and HA(High Availability). When the organization wants to have HA and DR with multi-site solution, it should setup two sites: one on premise and the other on AWS with full capacity. The organization should setup a weighted DNS service which can route traffic to both sites based on the weightage. When one of the sites fails it can route the entire load to another site. The organization would have minimal RTO in this scenario. If the organization setups a single DB instance, it will not work well in failover.

Instead they should have two separate DBs in each site and setup data replication based on RTO(recovery time objective )of the organization.

Reference: [http://d36cz9buwru1tt.cloudfront.net/AWS\\_Disaster\\_Recovery.pdf](http://d36cz9buwru1tt.cloudfront.net/AWS_Disaster_Recovery.pdf)

#### NEW QUESTION 136

In the context of policies and permissions in AWS IAM, the Condition element is .

- A. crucial while writing the IAM policies
- B. an optional element
- C. always set to null
- D. a mandatory element

**Answer:** B

**Explanation:** The Condition element (or Condition block) lets you specify conditions for when a policy is in effect. The Condition element is optional.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage\\_ElementDescriptions.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html)

#### NEW QUESTION 140

Which of the following is true while using an IAM role to grant permissions to applications running on Amazon EC2 instances?

- A. All applications on the instance share the same role, but different permissions.
- B. All applications on the instance share multiple roles and permissions.
- C. Multiple roles are assigned to an EC2 instance at a time.
- D. Only one role can be assigned to an EC2 instance at a time

**Answer:** D

**Explanation:** Only one role can be assigned to an EC2 instance at a time, and all applications on the instance share the same role and permissions.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/role-usecase-ec2app.html>

#### NEW QUESTION 141

When using string conditions within IAM, short versions of the available comparators can be used instead of the more verbose ones.

streql is the short version of the string condition.

- A. StringEqualsIgnoreCase
- B. StringNotEqualsIgnoreCase
- C. StringLikeStringEquals
- D. StringNotEquals

**Answer:** A

**Explanation:** When using string conditions within IAM, short versions of the available comparators can be used instead of the more verbose versions. For instance, streql is the short version of StringEqualsIgnoreCase that checks for the exact match between two strings ignoring their case.

Reference: <http://awsdocs.s3.amazonaws.com/SNS/20100331/sns-gsg-2010-03-31.pdf>

#### NEW QUESTION 143

Attempts, one of the three types of items associated with the schedule pipeline in the AWS Data Pipeline, provides robust data management.

Which of the following statements is NOT true about Attempts?

- A. Attempts provide robust data management.
- B. AWS Data Pipeline retries a failed operation until the count of retries reaches the maximum number of allowed retry attempts.
- C. An AWS Data Pipeline Attempt object compiles the pipeline components to create a set of actionable instances.
- D. AWS Data Pipeline Attempt objects track the various attempts, results, and failure reasons if applicable.

**Answer:** C

**Explanation:** Attempts, one of the three types of items associated with a schedule pipeline in AWS Data Pipeline, provides robust data management. AWS Data Pipeline retries a failed operation. It continues to do so until the task reaches the maximum number of allowed retry attempts. Attempt objects track the various attempts, results, and failure reasons if applicable. Essentially, it is the instance with a counter. AWS Data Pipeline performs retries using the same resources from the previous attempts, such as Amazon EMR clusters and EC2 instances.

Reference:

<http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/dp-how-tasks-scheduled.html>

#### NEW QUESTION 147

Select the correct statement about Amazon ElastiCache.

- A. It makes it easy to set up, manage, and scale a distributed in-memory cache environment in the cloud.
- B. It allows you to quickly deploy your cache environment only if you install software.
- C. It does not integrate with other Amazon Web Services.
- D. It cannot run in the Amazon Virtual Private Cloud (Amazon VPC) environmen

**Answer:** A

**Explanation:** ElastiCache is a web service that makes it easy to set up, manage, and scale a distributed in-memory cache environment in the cloud. It provides a high-performance, scalable, and cost-effective caching solution, while removing the complexity associated with deploying and managing a distributed cache environment. With ElastiCache, you can quickly deploy your cache environment, without having to provision hardware or install software.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/WhatIs.html>

#### NEW QUESTION 152

In Amazon RDS for PostgreSQL, you can provision up to 3TB storage and 30,000 IOPS per database instance. For a workload with 50% writes and 50% reads running on a cr1.8xlarge instance, you can realize over 25,000 IOPS for PostgreSQL. However, by provisioning more than this limit, you may be able to achieve:

- A. higher latency and lower throughput.
- B. lower latency and higher throughput.
- C. higher throughput only.
- D. higher latency onl

**Answer:** B

**Explanation:** You can provision up to 3TB storage and 30,000 IOPS per database instance. For a workload with 50% writes and 50% reads running on a cr1.8xlarge instance, you can realize over 25,000 IOPS for PostgreSQL. However, by provisioning more than this limit, you may be able to achieve lower latency and higher throughput. Your actual realized IOPS may vary from the amount you provisioned based on your database workload, instance type, and database engine choice.

Reference: <https://aws.amazon.com/rds/postgresql/>

#### NEW QUESTION 154

Which of the following cannot be done using AWS Data Pipeline?

- A. Create complex data processing workloads that are fault tolerant, repeatable, and highly available.
- B. Regularly access your data where it's stored, transform and process it at scale, and efficiently transfer the results to another AWS service.
- C. Generate reports over data that has been stored.
- D. Move data between different AWS compute and storage services as well as on-premise data sources at specified intervals.

**Answer:** C

**Explanation:** AWS Data Pipeline is a web service that helps you reliably process and move data between different AWS compute and storage services as well as on-premise data sources at specified intervals. With AWS Data Pipeline, you can regularly access your data where it's stored, transform and process it at scale, and efficiently transfer the results to another AWS.

AWS Data Pipeline helps you easily create complex data processing workloads that are fault tolerant, repeatable, and highly available. AWS Data Pipeline also allows you to move and process data that was previously locked up in on-premise data silos. Reference: <http://aws.amazon.com/datapipeline/>

#### NEW QUESTION 158

Identify an application that polls AWS Data Pipeline for tasks and then performs those tasks.

- A. A task executor
- B. A task deployer
- C. A task runner
- D. A task optimizer

**Answer:** C

**Explanation:** A task runner is an application that polls AWS Data Pipeline for tasks and then performs those tasks. You can either use Task Runner as provided by AWS Data Pipeline, or create a custom Task Runner application.

Task Runner is a default implementation of a task runner that is provided by AWS Data Pipeline. When Task Runner is installed and configured, it polls AWS Data Pipeline for tasks associated with pipelines that you have activated. When a task is assigned to Task Runner, it performs that task and reports its status back to AWS Data Pipeline. If your workflow requires non-default behavior, you'll need to implement that functionality in a custom task runner.

Reference:

<http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/dp-how-remote-taskrunner-client.html>

#### NEW QUESTION 161

Within an IAM policy, can you add an IfExists condition at the end of a Null condition?

- A. Yes, you can add an IfExists condition at the end of a Null condition but not in all Regions.
- B. Yes, you can add an IfExists condition at the end of a Null condition depending on the condition.

- C. No, you cannot add an IfExists condition at the end of a Null condition.
- D. Yes, you can add an IfExists condition at the end of a Null conditio

**Answer:** C

**Explanation:** Within an IAM policy, IfExists can be added to the end of any condition operator except the Null condition. It can be used to indicate that conditional comparison needs to happen if the policy key is present in the context of a request; otherwise, it can be ignored.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/reference\\_policies\\_elements.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/reference_policies_elements.html)

#### NEW QUESTION 164

Regarding Identity and Access Management (IAM), Which type of special account belonging to your application allows your code to access Google services programmatically?

- A. Service account
- B. Simple Key
- C. OAuth
- D. Code account

**Answer:** A

**Explanation:** A service account is a special Google account that can be used by applications to access Google services programmatically. This account belongs to your application or a virtual machine (VM), instead of to an individual end user. Your application uses the service account to call the Google API of a service, so that the users aren't directly involved.

A service account can have zero or more pairs of service account keys, which are used to authenticate to Google. A service account key is a public/private keypair generated by Google. Google retains the public key, while the user is given the private key.

Reference: <https://cloud.google.com/iam/docs/service-accounts>

#### NEW QUESTION 168

An organization is planning to use NoSQL DB for its scalable data needs. The organization wants to host an application securely in AWS VPC. What action can be recommended to the organization?

- A. The organization should setup their own NoSQL cluster on the AWS instance and configure route tables and subnets.
- B. The organization should only use a DynamoDB because by default it is always a part of the default subnet provided by AWS.
- C. The organization should use a DynamoDB while creating a table within the public subnet.
- D. The organization should use a DynamoDB while creating a table within a private subne

**Answer:** A

**Explanation:** The Amazon Virtual Private Cloud (Amazon VPC) allows the user to define a virtual networking environment in a private, isolated section of the Amazon Web Services (AWS) cloud. The user has complete control over the virtual networking environment. Currently VPC does not support DynamoDB. Thus, if the user wants to implement VPC, he has to setup his own NoSQL DB within the VPC. Reference:

[http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_Introduction.htm](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Introduction.htm)

#### NEW QUESTION 172

What happens when Dedicated instances are launched into a VPC?

- A. If you launch an instance into a VPC that has an instance tenancy of dedicated, you must manually create a Dedicated instance.
- B. If you launch an instance into a VPC that has an instance tenancy of dedicated, your instance is created as a Dedicated instance, only based on the tenancy of the instance.
- C. If you launch an instance into a VPC that has an instance tenancy of dedicated, your instance is automatically a Dedicated instance, regardless of the tenancy of the instance.
- D. None of these are tru

**Answer:** C

**Explanation:** If you launch an instance into a VPC that has an instance tenancy of dedicated, your instance is automatically a Dedicated instance, regardless of the tenancy of the instance.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/dedicated-instance.html>

#### NEW QUESTION 174

You create a VPN connection, and your VPN device supports Border Gateway Protocol (BGP). Which of the following should be specified to configure the VPN connection?

- A. Classless routing
- B. Classfull routing
- C. Dynamic routing
- D. Static routing

**Answer:** C

**Explanation:** If you create a VPN connection, you must specify the type of routing that you plan to use, which will depend upon on the make and model of your VPN devices. If your VPN device supports Border Gateway Protocol (BGP), you need to specify dynamic routing when you configure your VPN connection. If your device does not support BGP, you should specify static routing.



Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_VPN.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_VPN.html)

#### NEW QUESTION 179

An organization has developed an application which provides a smarter shopping experience. They need to show a demonstration to various stakeholders who may not be able to access the in premise application so they decide to host a demo version of the application on AWS. Consequently they will need a fixed elastic IP attached automatically to the instance when it is launched.

In this scenario which of the below mentioned options will not help assign the elastic IP automatically?

- A. Write a script which will fetch the instance metadata on system boot and assign the public IP using that metadata.
- B. Provide an elastic IP in the user data and setup a bootstrapping script which will fetch that elastic IP and assign it to the instance.
- C. Create a controlling application which launches the instance and assigns the elastic IP based on the parameter provided when that instance is booted.
- D. Launch instance with VPC and assign an elastic IP to the primary network interface

**Answer:** A

**Explanation:** EC2 allows the user to launch On-Demand instances. If the organization is using an application temporarily only for demo purposes the best way to assign an elastic IP would be:

Launch an instance with a VPC and assign an EIP to the primary network interface. This way on every instance start it will have the same IP Create a bootstrapping script and provide it some metadata, such as user data which can be used to assign an EIP Create a controller instance which can schedule the start and stop of the instance and provide an EIP as a parameter so that the controller instance can check the instance boot and assign an EIP

The instance metadata gives the current instance data, such as the public/private IP. It can be of no use for assigning an EIP.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/AESDG-chapter-instancedata.html>

#### NEW QUESTION 184

Can a Direct Connect link be connected directly to the Internet?

- A. Yes, this can be done if you pay for it.
- B. Yes, this can be done only for certain regions.
- C. Yes
- D. No

**Answer:** D

**Explanation:** AWS Direct Connect is a network service that provides an alternative to using the Internet to utilize AWS cloud service. Hence, a Direct Connect link cannot be connected to the Internet directly.

Reference: <http://aws.amazon.com/directconnect/faqs/>

#### NEW QUESTION 185

True or False: The Amazon ElastiCache clusters are not available for use in VPC at this time.

- A. TRUE
- B. True, but they are available only in the GovCloud.
- C. True, but they are available only on request.
- D. FALSE

**Answer:** D

**Explanation:** Amazon ElastiCache clusters can be run in an Amazon VPC. With Amazon VPC, you can define a virtual network topology and customize the network configuration to closely resemble a traditional network that you might operate in your own datacenter. You can now take advantage of the manageability, availability and scalability benefits of Amazon ElastiCache Clusters in your own isolated network. The same functionality of Amazon ElastiCache, including automatic failure detection, recovery, scaling, auto discovery, Amazon CloudWatch metrics, and software patching, are now available in Amazon VPC. Reference: <http://aws.amazon.com/about-aws/whats-new/2012/12/20/amazon-elasticache-announces-support-for-a-mazon-vpc/>

#### NEW QUESTION 189

In Amazon Redshift, how many slices does a dw2.8xlarge node have?

- A. 16
- B. 8
- C. 32
- D. 2

**Answer:** C

**Explanation:** The disk storage for a compute node in Amazon Redshift is dMded into a number of slices, equal to the number of processor cores on the node. For example, each DW1.XL compute node has two slices, and each DW2.8XL compute node has 32 slices.

Reference: [http://docs.aws.amazon.com/redshift/latest/dg/t\\_Distributing\\_data.html](http://docs.aws.amazon.com/redshift/latest/dg/t_Distributing_data.html)

#### NEW QUESTION 191

Identify a true statement about using an IAM role to grant permissions to applications running on Amazon EC2 instances.

- A. When AWS credentials are rotated, developers have to update only the root Amazon EC2 instance that uses their credentials.
- B. When AWS credentials are rotated, developers have to update only the Amazon EC2 instance on which the password policy was applied and which uses their

credentials.

- C. When AWS credentials are rotated, you don't have to manage credentials and you don't have to worry about long-term security risks.
- D. When AWS credentials are rotated, you must manage credentials and you should consider precautions for long-term security risks.

**Answer:** C

**Explanation:** Using IAM roles to grant permissions to applications that run on EC2 instances requires a bit of extra configuration. Because role credentials are temporary and rotated automatically, you don't have to manage credentials, and you don't have to worry about long-term security risks.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/role-usecase-ec2app.html>

#### NEW QUESTION 193

Out of the striping options available for the EBS volumes, which one has the following disadvantage: 'Doubles the amount of I/O required from the instance to EBS compared to RAID 0, because you're mirroring all writes to a pair of volumes, limiting how much you can stripe.'?

- A. Raid 1
- B. Raid 0
- C. RAID 1+0 (RAID 10)
- D. Raid 2

**Answer:** C

**Explanation:** RAID 1+0 (RAID 10) doubles the amount of I/O required from the instance to EBS compared to RAID 0, because you're mirroring all writes to a pair of volumes, limiting how much you can stripe.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/raid-config.html>

#### NEW QUESTION 197

In the context of IAM roles for Amazon EC2, which of the following NOT true about delegating permission to make API requests?

- A. You cannot create an IAM role.
- B. You can have the application retrieve a set of temporary credentials and use them.
- C. You can specify the role when you launch your instances.
- D. You can define which accounts or AWS services can assume the rol

**Answer:** A

**Explanation:** Amazon designed IAM roles so that your applications can securely make API requests from your instances, without requiring you to manage the security credentials that the applications use. Instead of creating and distributing your AWS credentials, you can delegate permission to make API requests using IAM roles as follows: Create an IAM role. Define which accounts or AWS services can assume the role. Define which API actions and resources the application can use after assuming the role. Specify the role when you launch your instances. Have the application retrieve a set of temporary credentials and use them.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/iam-roles-for-amazon-ec2.html>

#### NEW QUESTION 200

In the context of Amazon ElastiCache CLI, which of the following commands can you use to view all ElastiCache instance events for the past 24 hours?

- A. elasticache-events --duration 24
- B. elasticache-events --duration 1440
- C. elasticache-describe-events --duration 24
- D. elasticache describe-events --source-type cache-cluster --duration 1440

**Answer:** D

**Explanation:** In Amazon ElastiCache, the code "aws elasticache describe-events --source-type cache-cluster --duration 1440" is used to list the cache-cluster events for the past 24 hours (1440 minutes). Reference:

<http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/ECEvents.Viewing.html>

#### NEW QUESTION 205

When using Numeric Conditions within IAM, short versions of the available comparators can be used instead of the more verbose versions. Which of the following is the short version of the Numeric Condition "NumericLessThanEquals"?

- A. numlteq
- B. numlteql
- C. numltequals
- D. numeqql

**Answer:** A

**Explanation:** When using Numeric Conditions within IAM, short versions of the available comparators can be used instead of the more verbose versions. For instance, numlteq is the short version of NumericLessThanEquals.

Reference: <http://awsdocs.s3.amazonaws.com/SQS/2011-10-01/sqs-dg-2011-10-01.pdf>

#### NEW QUESTION 209

AWS has launched T2 instances which come with CPU usage credit. An organization has a requirement which keeps an instance running for 24 hours. However,

the organization has high usage only during 11 AM to 12 PM. The organization is planning to use a T2 small instance for this purpose. If the organization already has multiple instances running since Jan 2012, which of the below mentioned options should the organization implement while launching a T2 instance?

- A. The organization must migrate to the EC2-VPC platform first before launching a T2 instance.
- B. While launching a T2 instance the organization must create a new AWS account as this account does not have the EC2-VPC platform.
- C. Create a VPC and launch a T2 instance as part of one of the subnets of that VPC.
- D. While launching a T2 instance the organization must select EC2-VPC as the platform.

**Answer:** C

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. The user can create subnets as per the requirement within a VPC. The AWS account provides two platforms: EC2-CLASSIC and EC2-VPC, depending on when the user has created his AWS account and which regions he is using. If the user has created the AWS account after 2013-12-04, it supports only EC2-VPC. In this scenario, since the account is before the required date the supported platform will be EC2-CLASSIC. It is required that the organization creates a VPC as the T2 instances can be launched only as a part of VPC.  
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/vpc-migrate.html>

#### NEW QUESTION 210

In AWS IAM, which of the following predefined policy condition keys checks how long ago (in seconds) the MFA-validated security credentials making the request were issued using multi-factor authentication (MFA)?

- A. aws:MultiFactorAuthAge
- B. aws:MultiFactorAuthLast
- C. aws:MFAAge
- D. aws:MultiFactorAuthPrevious

**Answer:** A

**Explanation:** aws:MultiFactorAuthAge is one of the predefined keys provided by AWS that can be included within a Condition element of an IAM policy. The key allows to check how long ago (in seconds) the MFA-validated security credentials making the request were issued using Multi-Factor Authentication (MFA).  
Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage\\_ElementDescriptions.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_ElementDescriptions.html)

#### NEW QUESTION 214

A user is configuring MySQL RDS with PIOPS. What should be the minimum PIOPS that the user should provision?

- A. 1000
- B. 200
- C. 2000
- D. 500

**Answer:** A

**Explanation:** If a user is trying to enable PIOPS with MySQL RDS, the minimum size of storage should be 100 GB and the minimum PIOPS should be 1000.  
Reference: [http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER\\_PIOPS.html](http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_PIOPS.html)

#### NEW QUESTION 217

You are setting up some EBS volumes for a customer who has requested a setup which includes a RAID (redundant array of inexpensive disks). AWS has some recommendations for RAID setups. Which RAID setup is not recommended for Amazon EBS?

- A. RAID 1 only
- B. RAID 5 only
- C. RAID 5 and RAID 6
- D. RAID 0 only

**Answer:** C

**Explanation:** With Amazon EBS, you can use any of the standard RAID configurations that you can use with a traditional bare metal server, as long as that particular RAID configuration is supported by the operating system for your instance. This is because all RAID is accomplished at the software level. For greater I/O performance than you can achieve with a single volume, RAID 0 can stripe multiple volumes together; for on-instance redundancy, RAID 1 can mirror two volumes together. RAID 5 and RAID 6 are not recommended for Amazon EBS because the parity write operations of these RAID modes consume some of the IOPS available to your volumes.  
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/raid-config.html>

#### NEW QUESTION 219

What is the role of the PollForTask action when it is called by a task runner in AWS Data Pipeline?

- A. It is used to retrieve the pipeline definition.
- B. It is used to report the progress of the task runner to AWS Data Pipeline.
- C. It is used to receive a task to perform from AWS Data Pipeline.
- D. It is used to inform AWS Data Pipeline of the outcome when the task runner completes a task.

**Answer:** C

**Explanation:** Task runners call `PollForTask` to receive a task to perform from AWS Data Pipeline. If tasks are ready in the work queue, `PollForTask` returns a response immediately. If no tasks are available in the queue, `PollForTask` uses long-polling and holds on to a poll connection for up to 90 seconds, during which time any newly scheduled tasks are handed to the task agent. Your remote worker should not call `PollForTask` again on the same worker group until it receives a response, and this may take up to 90 seconds. Reference: [http://docs.aws.amazon.com/datapipeline/latest/APIReference/API\\_PollForTask.html](http://docs.aws.amazon.com/datapipeline/latest/APIReference/API_PollForTask.html)

#### NEW QUESTION 223

What is the average queue length recommended by AWS to achieve a lower latency for the 200 PIOPS EBS volume?

- A. 5
- B. 1
- C. 2
- D. 4

**Answer:** B

**Explanation:** The queue length is the number of pending I/O requests for a device. The optimal average queue length will vary for every customer workload, and this value depends on a particular application's sensitivity to IOPS and latency. If the workload is not delivering enough I/O requests to maintain the optimal average queue length, then the EBS volume might not consistently deliver the IOPS that have been provisioned. However, if the workload maintains an average queue length that is higher than the optimal value, then the per-request I/O latency will increase; in this case, the user should provision more IOPS for his volume. AWS recommends that the user should target an optimal average queue length of 1 for every 200 provisioned IOPS and tune that value based on his application requirements.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-workload-demand.html>

#### NEW QUESTION 225

Who is responsible for modifying the routing tables and networking ACLs in a VPC to ensure that a DB instance is reachable from other instances in the VPC?

- A. AWS administrators
- B. The owner of the AWS account
- C. Amazon
- D. The DB engine vendor

**Answer:** B

**Explanation:** You are in charge of configuring the routing tables of your VPC as well as the network ACLs rules needed to make your DB instances accessible from all the instances of your VPC that need to communicate with it.

Reference: <http://aws.amazon.com/rds/faqs/>

#### NEW QUESTION 228

An organization is planning to host a web application in the AWS VPC. The organization does not want to host a database in the public cloud due to statutory requirements. How can the organization setup in this scenario?

- A. The organization should plan the app server on the public subnet and database in the organization's data center and connect them with the VPN gateway.
- B. The organization should plan the app server on the public subnet and use RDS with the private subnet for a secure data operation.
- C. The organization should use the public subnet for the app server and use RDS with a storage gateway to access as well as sync the data securely from the local data center.
- D. The organization should plan the app server on the public subnet and database in a private subnet so it will not be in the public cloud.

**Answer:** A

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account.

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all the traffic of the VPN subnet. If the virtual private gateway is attached with VPC and the user deletes the VPC from the console it will first automatically detach the gateway and only then delete the VPC.

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_Subnets.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html)

#### NEW QUESTION 233

A user is trying to create a PIOPS EBS volume with 4000 IOPS and 100 GB size. AWS does not allow the user to create this volume. What is the possible root cause for this?

- A. PIOPS is supported for EBS higher than 500 GB size
- B. The maximum IOPS supported by EBS is 3000
- C. The ratio between IOPS and the EBS volume is higher than 30
- D. The ratio between IOPS and the EBS volume is lower than 50

**Answer:** C

**Explanation:** A Provisioned IOPS (SSD) volume can range in size from 4 GiB to 16 TiB and you can provision up to 20,000 IOPS per volume. The ratio of IOPS provisioned to the volume size requested should be a maximum of 30; for example, a volume with 3000 IOPS must be at least 100 GB.

Reference: [http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html#EBSVolumeTypes\\_piops](http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSVolumeTypes.html#EBSVolumeTypes_piops)



#### NEW QUESTION 236

A user is planning to host a Highly Available system on the AWS VPC. Which of the below mentioned statements is helpful in this scenario?

- A. Create VPC subnets in two separate availability zones and launch instances in different subnets.
- B. Create VPC with only one public subnet and launch instances in different AZs using that subnet.
- C. Create two VPCs in two separate zones and setup failover with ELB such that if one VPC fails it will divert traffic to another VPC.
- D. Create VPC with only one private subnet and launch instances in different AZs using that subne

**Answer:** A

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. The VPC is always specific to a region. The user can create a VPC which can span multiple Availability Zones by adding one or more subnets in each Availability Zone. Each subnet must reside entirely within one Availability Zone and cannot span across zones.

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_Subnets.html#VPCSubnet](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html#VPCSubnet)

#### NEW QUESTION 239

What is a possible reason you would need to edit claims issued in a SAML token?

- A. The NamelIdentifier claim cannot be the same as the username stored in AD.
- B. Authentication fails consistently.
- C. The NamelIdentifier claim cannot be the same as the claim URI.
- D. The NamelIdentifier claim must be the same as the username stored in A

**Answer:** A

**Explanation:** The two reasons you would need to edit claims issued in a SAML token are: The NamelIdentifier claim cannot be the same as the username stored in AD, and The app requires a different set of claim URIs.

Reference:

<https://azure.microsoft.com/en-us/documentation/articles/active-directory-saml-claims-customization/>

#### NEW QUESTION 241

What is the network performance offered by the c4.8xlarge instance in Amazon EC2?

- A. Very High but variable
- B. 20 Gigabit
- C. 5 Gigabit
- D. 10 Gigabit

**Answer:** D

**Explanation:** Networking performance offered by the c4.8xlarge instance is 10 Gigabit. Reference: <http://aws.amazon.com/ec2/instance-types/>

#### NEW QUESTION 246

An organization is setting up a web application with the JEE stack. The application uses the JBoss app server and |V|ySQL DB. The application has a logging module which logs all the actMties whenever a business function of the JEE application is called. The logging actMty takes some time due to the large size of the log file. If the application wants to setup a scalable infrastructure which of the below mentioned options will help achieve this setup?

- A. Host the log files on EBS with PIOPS which will have higher I/O.
- B. Host logging and the app server on separate sewers such that they are both in the same zone.
- C. Host logging and the app server on the same instance so that the network latency will be shorter.
- D. Create a separate module for logging and using SQS compartmentalize the module such that all calls to logging are asynchronous.

**Answer:** D

**Explanation:** The organization can always launch multiple EC2 instances in the same region across multiple AZs for HA and DR. The AWS architecture practice recommends compartmentalizing the functionality such that

they can both run in parallel without affecting the performance of the main application. In this scenario logging takes a longer time due to the large size of the log file. Thus, it is recommended that the organization should separate them out and make separate modules and make asynchronous calls among them. This way the application can scale as per the requirement and the performance will not bear the impact of logging.

Reference: <http://www.awsarchitectureblog.com/2014/03/aws-and-compartmentalization.html>

#### NEW QUESTION 248

You're trying to delete an SSL certificate from the IAM certificate store, and you're getting the message "Certificate: <certificate-id> is being used by CloudFront." Which of the following statements is probably the reason why you are getting this error?

- A. Before you can delete an SSL certificate you need to set up https on your server.
- B. Before you can delete an SSL certificate, you need to set up the appropriate access level in IAM
- C. Before you can delete an SSL certificate, you need to either rotate SSL certificates or revert from using a custom SSL certificate to using the default CloudFront certificate.
- D. You can't delete SSL certificates . You need to request it from AW

**Answer:** C

**Explanation:** CloudFront is a web service that speeds up distribution of your static and dynamic web content, for example, .html, .css, .php, and image files, to end users.

Every CloudFront web distribution must be associated either with the default CloudFront certificate or with a custom SSL certificate. Before you can delete an SSL certificate, you need to either rotate SSL certificates (replace the current custom SSL certificate with another custom SSL certificate) or revert from using a custom SSL certificate to using the default CloudFront certificate.

Reference: <http://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/Troubleshooting.html>

#### NEW QUESTION 252

A user has set the IAM policy where it denies all requests if a request is not from IP 10.10.10.1/32. The other policy says allow all requests between 5 PM to 7 PM. What will happen when a user is requesting access from IP 55.109.10.12/32 at 6 PM?

- A. It will deny access
- B. It is not possible to set a policy based on the time or IP
- C. IAM will throw an error for policy conflict
- D. It will allow access

**Answer:** A

**Explanation:** When a request is made, the AWS IAM policy decides whether a given request should be allowed or denied. The evaluation logic follows these rules:

By default, all requests are denied. (In general, requests made using the account credentials for resources in the account are always allowed.)

An explicit allow policy overrides this default.

An explicit deny policy overrides any allows.

In this case since there are explicit deny and explicit allow statements. Thus, the request will be denied since deny overrides allow.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage\\_EvaluationLogic.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/AccessPolicyLanguage_EvaluationLogic.html)

#### NEW QUESTION 257

Do you need to use Amazon Cognito to use the Amazon Mobile Analytics service?

- A. N
- B. However, it is recommend by AWS to use Amazon Cognito for security best practices.
- C. Ye
- D. You need to use it only if you have IAM root access.
- E. N
- F. You cannot use it at all, and you need to use AWS IAM accounts.
- G. Ye
- H. It is recommended by AWS to use Amazon Cognito to use Amazon Mobile Analytics servic

**Answer:** A

**Explanation:** You can initialize Amazon Mobile Analytics using AWS IAM accounts. AWS recommend using Amazon Cognito for security best practices.

Reference: <http://aws.amazon.com/mobileanalytics/faqs/>

#### NEW QUESTION 262

Which of the following AWS services can be used to define alarms to trigger on a certain actMty, such as actMty success, failure, or delay in AWS Data Pipeline?

- A. Amazon SES
- B. Amazon CodeDeploy
- C. Amazon SNS
- D. Amazon SQS

**Answer:** C

**Explanation:** In AWS Data Pipeline, you can define Amazon SNS alarms to trigger on actMties such as success, failure, or delay by creating an alarm object and referencing it in the onFail, onSuccess, or onLate slots of the actMty object.

Reference: <https://aws.amazon.com/datapipeline/faqs/>

#### NEW QUESTION 267

You want to use Amazon Redshift and you are planning to deploy dw1.8xlarge nodes. What is the minimum amount of nodes that you need to deploy with this kind of configuration?

- A. 1
- B. 4
- C. 3
- D. 2

**Answer:** D

**Explanation:** For a single-node configuration in Amazon Redshift, the only option available is the smallest of the two options. The 8XL extra-large nodes are only available in a multi-node configuration

Reference: <http://docs.aws.amazon.com/redshift/latest/mgmt/working-with-clusters.html>

#### NEW QUESTION 268

Mike is appointed as Cloud Consultant in ExamKiller.com. ExamKiller has the following VPCs set-up in the US East Region:

A VPC with CIDR block 10.10.0.0/16, a subnet in that VPC with CIDR block 10.10.1.0/24 A VPC with CIDR block 10.40.0.0/16, a subnet in that VPC with CIDR block 10.40.1.0/24

ExamKiller.com is trying to establish network connection between two subnets, a subnet with CIDR block 10.10.1.0/24 and another subnet with CIDR block 10.40.1.0/24. Which one of the following solutions should I recommend to ExamKiller.com?

- A. Create 2 Virtual Private Gateways and configure one with each VPC.
- B. Create 2 Internet Gateways, and attach one to each VPC.
- C. Create a VPC Peering connection between both VPCs.
- D. Create one EC2 instance in each subnet, assign Elastic IPs to both instances, and configure a set up Site-to-Site VPN connection between both EC2 instances.

**Answer: C**

**Explanation:** A VPC peering connection is a networking connection between two VPCs that enables you to route traffic between them using private IP addresses. EC2 instances in either VPC can communicate with each other as if they are within the same network. You can create a VPC peering connection between your own VPCs, or with a VPC in another AWS account within a single region.

AWS uses the existing infrastructure of a VPC to create a VPC peering connection; it is neither a gateway nor a VPN connection, and does not rely on a separate piece of physical hardware.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-peering.html>

#### NEW QUESTION 272

To get started using AWS Direct Connect, in which of the following steps do you configure Border Gateway Protocol (BGP)?

- A. Complete the Cross Connect
- B. Configure Redundant Connections with AWS Direct Connect
- C. Create a Virtual Interface
- D. Download Router Configuration

**Answer: C**

**Explanation:** In AWS Direct Connect, your network must support Border Gateway Protocol (BGP) and BGP MD5 authentication, and you need to provide a private Autonomous System Number (ASN) for that to connect to Amazon Virtual Private Cloud (VPC). To connect to public AWS products such as Amazon EC2 and Amazon S3, you will also need to provide a public ASN that you own (preferred) or a private ASN. You have to configure BGP in the Create a Virtual Interface step.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/getstarted.html#createvirtualinterface>

#### NEW QUESTION 273

Which of the following components of AWS Data Pipeline polls for tasks and then performs those tasks?

- A. Pipeline Definition
- B. Task Runner
- C. Amazon Elastic MapReduce (EMR)
- D. AWS Direct Connect

**Answer: B**

**Explanation:** Task Runner polls for tasks and then performs those tasks.

Reference: <http://docs.aws.amazon.com/datapipeline/latest/DeveloperGuide/what-is-datapipeline.html>

#### NEW QUESTION 277

A user is hosting a public website on AWS. The user wants to have the database and the app server on the AWS VPC. The user wants to setup a database that can connect to the Internet for any patch upgrade but cannot receive any request from the internet. How can the user set this up?

- A. Setup DB in a private subnet with the security group allowing only outbound traffic.
- B. Setup DB in a public subnet with the security group allowing only inbound data.
- C. Setup DB in a local data center and use a private gateway to connect the application with DB.
- D. Setup DB in a private subnet which is connected to the internet via NAT for outbound.

**Answer: D**

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. AWS provides two features that the user can use to increase security in VPC: security groups and network ACLs. When the user wants to setup both the DB and App on VPC, the user should make one public and one private subnet. The DB should be hosted in a private subnet and instances in that subnet cannot reach the internet. The user can allow an instance in his VPC to initiate outbound connections to the internet but prevent unsolicited inbound connections from the internet by using a Network Address Translation (NAT) instance.

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_Subnets.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html)

#### NEW QUESTION 280

An organization is setting up their website on AWS. The organization is working on various security measures to be performed on the AWS EC2 instances. Which of the below mentioned security mechanisms will not help the organization to avoid future data leaks and identify security weaknesses?

- A. Run penetration testing on AWS with prior approval from Amazon.
- B. Perform SQL injection for application testing.
- C. Perform a Code Check for any memory leaks.
- D. Perform a hardening test on the AWS instance

**Answer:** C

**Explanation:** AWS security follows the shared security model where the user is as much responsible as Amazon. Since Amazon is a public cloud it is bound to be targeted by hackers. If an organization is planning to host their application on AWS EC2, they should perform the below mentioned security checks as a measure to find any security weakness/data leaks:

Perform penetration testing as performed by attackers to find any vulnerability. The organization must take an approval from AWS before performing penetration testing

Perform hardening testing to find if there are any unnecessary ports open Perform SQL injection to find any DB security issues

The code memory checks are generally useful when the organization wants to improve the application performance.

Reference: <http://aws.amazon.com/security/penetration-testing/>

#### NEW QUESTION 281

In Amazon ElastiCache, the default cache port is:

- A. for Memcached 11210 and for Redis 6380.
- B. for Memcached 11211 and for Redis 6380.
- C. for Memcached 11210 and for Redis 6379.
- D. for Memcached 11211 and for Redis 6379.

**Answer:** D

**Explanation:** In Amazon ElastiCache, you can specify a new port number for your cache cluster, which by default is 11211 for Memcached and 6379 for Redis.

Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/GettingStarted.AuthorizeAccess.html>

#### NEW QUESTION 285

Which of the following cannot be used to manage Amazon ElastiCache and perform administrative tasks?

- A. AWS software development kits (SDKs)
- B. Amazon S3
- C. ElastiCache command line interface (CLI)
- D. AWS CloudWatch

**Answer:** D

**Explanation:** CloudWatch is a monitoring tool and doesn't give users access to manage Amazon ElastiCache. Reference:

<http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/WhatIs.Nlanaging.html>

#### NEW QUESTION 286

Which of the following statements is correct about AWS Direct Connect?

- A. Connections to AWS Direct Connect require double clad fiber for 1 gigabit Ethernet with Auto Negotiation enabled for the port.
- B. An AWS Direct Connect location provides access to Amazon Web Services in the region it is associated with.
- C. AWS Direct Connect links your internal network to an AWS Direct Connect location over a standard 50 gigabit Ethernet cable.
- D. To use AWS Direct Connect, your network must be colocated with a new AWS Direct Connect locatio

**Answer:** B

**Explanation:** AWS Direct Connect links your internal network to an AWS Direct Connect location over a standard 1 gigabit or 10 gigabit Ethernet fiber-optic cable. An AWS Direct Connect location provides access to Amazon Web Services in the region it is associated with, as well as access to other US regions. To use AWS Direct Connect, your network is colocated with an existing AWS Direct Connect location. Connections to AWS Direct Connect require single mode fiber, 1000BASE-LX (1310nm) for 1 gigabit Ethernet, or 10GBASE-LR (1310nm) for 10 gigabit Ethernet. Auto Negotiation for the port must be disabled.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/Welcome.html>

#### NEW QUESTION 289

Is there any way to own a direct connection to Amazon Web Services?

- A. No, AWS only allows access from the public Internet.
- B. No, you can create an encrypted tunnel to VPC, but you cannot own the connection.
- C. Yes, you can via Amazon Dedicated Connection.
- D. Yes, you can via AWS Direct Connec

**Answer:** D

**Explanation:** AWS Direct Connect links your internal network to an AWS Direct Connect location over a standard 1 gigabit or 10 gigabit Ethernet fiber-optic cable. One end of the cable is connected to your router, the other to an AWS Direct Connect router. With this connection in place, you can create virtual interfaces directly to the AWS cloud (for example, to Amazon Elastic Compute Cloud (Amazon EC2) and Amazon Simple Storage Service (Amazon S3)) and to Amazon Virtual Private Cloud (Amazon VPC), bypassing Internet service providers in your network path.

Reference: <http://docs.aws.amazon.com/directconnect/latest/UserGuide/Welcome.html>

#### NEW QUESTION 290

Identify a true statement about the statement ID (Sid) in IAM.



- A. You cannot expose the Sid in the IAM API.
- B. You cannot use a Sid value as a sub-ID for a policy document's ID for services provided by SQS and SNS.
- C. You can expose the Sid in the IAM API.
- D. You cannot assign a Sid value to each statement in a statement array.

**Answer:** A

**Explanation:** The Sid(statement ID) is an optional identifier that you provide for the policy statement. You can assign a Sid a value to each statement in a statement array. In IAM, the Sid is not exposed in the IAM API. You can't retrieve a particular statement based on this ID.  
Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/reference\\_policies\\_elements.html#Sid](http://docs.aws.amazon.com/IAM/latest/UserGuide/reference_policies_elements.html#Sid)

#### NEW QUESTION 293

In Amazon ElastiCache, which of the following statements is correct?

- A. When you launch an ElastiCache cluster into an Amazon VPC private subnet, every cache node is assigned a public IP address within that subnet.
- B. You cannot use ElastiCache in a VPC that is configured for dedicated instance tenancy.
- C. If your AWS account supports only the EC2-VPC platform, ElastiCache will never launch your cluster in a VPC.
- D. ElastiCache is not fully integrated with Amazon Virtual Private Cloud (VPC).

**Answer:** B

**Explanation:** The VPC must allow non-dedicated EC2 instances. You cannot use ElastiCache in a VPC that is configured for dedicated instance tenancy.  
Reference: <http://docs.aws.amazon.com/AmazonElastiCache/latest/UserGuide/AmazonVPC.EC.html>

#### NEW QUESTION 294

An organization has setup RDS with VPC. The organization wants RDS to be accessible from the internet. Which of the below mentioned configurations is not required in this scenario?

- A. The organization must enable the parameter in the console which makes the RDS instance publicly accessible.
- B. The organization must allow access from the internet in the RDS VPC security group,
- C. The organization must setup RDS with the subnet group which has an external IP.
- D. The organization must enable the VPC attributes DNS hostnames and DNS resolution.

**Answer:** C

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources, such as RDS into a virtual network that the user has defined. Subnets are segments of a VPC's IP address range that the user can designate to a group of VPC resources based on security and operational needs. A DB subnet group is a collection of subnets (generally private) that the user can create in a VPC and which the user assigns to the RDS DB instances. A DB subnet group allows the user to specify a particular VPC when creating DB instances. If the RDS instance is required to be accessible from the internet:

The organization must setup that the RDS instance is enabled with the VPC attributes, DNS hostnames and DNS resolution.

The organization must enable the parameter in the console which makes the RDS instance publicly accessible.

The organization must allow access from the internet in the RDS VPC security group. Reference:

[http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER\\_VPC.html](http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_VPC.html)

#### NEW QUESTION 295

An organization, which has the AWS account ID as Q99988887777, has created 50 IAM users. All the users are added to the same group examkiller. If the organization has enabled that each IAM user can login with the AWS console, which AWS login URL will the IAM users use??

- A. <https://Q99988887777.aws.amazon.com/examkiller/>
- B. <https://signin.aws.amazon.com/examkiller/>
- C. <https://examkiller.signin.aws.amazon.com/999988887777/console/>
- D. <https://999988887777.signin.aws.amazon.com/console/>

**Answer:** D

**Explanation:** AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Once the organization has created the IAM users, they will have a separate AWS console URL to login to the AWS console. The console login URL for the IAM user will be [https://AWS\\_Account\\_ID.signin.aws.amazon.com/console/](https://AWS_Account_ID.signin.aws.amazon.com/console/). It uses only the AWS account ID and does not depend on the group or user ID.  
Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/AccountAlias.html>

#### NEW QUESTION 300

Your company has recently extended its datacenter into a VPC on AWS to add burst computing capacity as needed. Members of your Network Operations Center need to be able to go to the AWS Management Console and administer Amazon EC2 instances as necessary. You don't want to create new IAM users for each NOC member and make those users sign in again to the AWS Management Console. Which option below will meet the needs for your NOC members?

- A. Use OAuth 2.0 to retrieve temporary AWS security credentials to enable your NOC members to sign in to the AWS Management Console.
- B. Use web Identity Federation to retrieve AWS temporary security credentials to enable your NOC members to sign in to the AWS IAM Management Console.
- C. Use your on-premises SAML 2.0-compliant identity provider (IDP) to grant the NOC members federated access to the AWS Management Console via the AWS single sign-on (SSO) endpoint.
- D. Use your on-premises SAML 2.0-compliant identity provider (IDP) to retrieve temporary security credentials to enable NOC members to sign in to the AWS Management Console.

**Answer:** D

#### NEW QUESTION 305

You're running an application on-premises due to its dependency on non-x86 hardware and want to use AWS for data backup. Your backup application is only able to write to POSIX-compatible block-based storage. You have 140TB of data and would like to mount it as a single folder on your file server. Users must be able to access portions of this data while the backups are taking place. What backup solution would be most appropriate for this use case?

- A. Use Storage Gateway and configure it to use Gateway Cached volumes.
- B. Configure your backup software to use S3 as the target for your data backups.
- C. Configure your backup software to use Glacier as the target for your data backups.
- D. Use Storage Gateway and configure it to use Gateway Stored volume

**Answer:** A

#### NEW QUESTION 306

To serve Web traffic for a popular product your chief financial officer and IT director have purchased 10 m1 large heavy utilization Reserved Instances (RIs) evenly spread across two availability zones. Route 53 is used to deliver the traffic to an Elastic Load Balancer (ELB). After several months, the product grows even more popular and you need additional capacity. As a result, your company purchases two C3.2xlarge medium utilization RIs. You register the two c3 2xlarge instances with your ELB and quickly find that the m1 large instances are at 100% of capacity and the c3 2xlarge instances have significant capacity that's unused. Which option is the most cost effective and uses EC2 capacity most effectively?

- A. Configure Autoscaling group and Launch Configuration with ELB to add up to 10 more on-demand m1 .large instances when triggered by Cloudwatc
- B. Shut off c3.2xlarge instances.
- C. Configure ELB with two c3.2xlarge instances and use on-demand Autoscaling group for up to two additional c3.2xlarge instance
- D. Shut off m1 .large instances.
- E. Route traffic to EC2 m1 .large and c3.2xlarge instances directly using Route 53 latency based routing and health check
- F. Shut off ELB.
- G. Use a separate ELB for each instance type and distribute load to ELBs with Route 53 weighted round robin.

**Answer:** B

#### NEW QUESTION 311

You have deployed a web application targeting a global audience across multiple AWS Regions under the domain name.example.com. You decide to use Route53 Latency-Based Routing to serve web requests to users from the region closest to the user. To provide business continuity in the event of server downtime you configure weighted record sets associated with two web servers in separate Availability Zones per region. During a DR test you notice that when you disable all web servers in one of the regions Route53 does not automatically direct all users to the other region. What could be happening? (Choose 2 answers)

- A. Latency resource record sets cannot be used in combination with weighted resource record sets.
- B. You did not setup an HTTP health check to one or more of the weighted resource record sets associated with the disabled web servers.
- C. The value of the weight associated with the latency alias resource record set in the region with the disabled servers is higher than the weight for the other region.
- D. One of the two working web servers in the other region did not pass its HTTP health check.
- E. You did not set "Evaluate Target Health" to "Yes" on the latency alias resource record set associated with example.com in the region where you disabled the servers.

**Answer:** BE

#### NEW QUESTION 312

.....

## THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual AWS-Certified-Solutions-Architect-Professional Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the AWS-Certified-Solutions-Architect-Professional Product From:

**<https://www.2passeasy.com/dumps/AWS-Certified-Solutions-Architect-Professional/>**

## Money Back Guarantee

### **AWS-Certified-Solutions-Architect-Professional Practice Exam Features:**

- \* AWS-Certified-Solutions-Architect-Professional Questions and Answers Updated Frequently
- \* AWS-Certified-Solutions-Architect-Professional Practice Questions Verified by Expert Senior Certified Staff
- \* AWS-Certified-Solutions-Architect-Professional Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* AWS-Certified-Solutions-Architect-Professional Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year