

ANS-C01 Dumps

AWS Certified Advanced Networking Specialty Exam

<https://www.certleader.com/ANS-C01-dumps.html>



NEW QUESTION 1

A network engineer needs to update a company's hybrid network to support IPv6 for the upcoming release of a new application. The application is hosted in a VPC in the AWS Cloud. The company's current AWS infrastructure includes VPCs that are connected by a transit gateway. The transit gateway is connected to the on-premises network by AWS Direct Connect and AWS Site-to-Site VPN. The company's on-premises devices have been updated to support the new IPv6 requirements.

The company has enabled IPv6 for the existing VPC by assigning a new IPv6 CIDR block to the VPC and by assigning IPv6 to the subnets for dual-stack support. The company has launched new Amazon EC2 instances for the new application in the updated subnets.

When updating the hybrid network to support IPv6 the network engineer must avoid making any changes to the current infrastructure. The network engineer also must block direct access to the instances' new IPv6 addresses from the internet. However, the network engineer must allow outbound internet access from the instances.

What is the MOST operationally efficient solution that meets these requirements?

- A. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- B. Create a new VPN connection that supports IPv6 connectivity
- C. Add an egress-only internet gateway
- D. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices
- E. Update the Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- F. Update the existing VPN connection to support IPv6 connectivity
- G. Add an egress-only internet gateway
- H. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- I. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- J. Create a new VPN connection that supports IPv6 connectivity
- K. Add an egress-only internet gateway
- L. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.
- M. Create a Direct Connect transit VIF and configure BGP peering with the AWS assigned IPv6 peering address
- N. Create a new VPN connection that supports IPv6 connectivity
- O. Add a NAT gateway
- P. Update any affected VPC security groups and route tables to provide connectivity within the VPC and between the VPC and the on-premises devices.

Answer: B

NEW QUESTION 2

A company is planning to use Amazon S3 to archive financial data. The data is currently stored in an on-premises data center. The company uses AWS Direct Connect with a Direct Connect gateway and a transit gateway to connect to the on-premises data center. The data cannot be transported over the public internet and must be encrypted in transit.

Which solution will meet these requirements?

- A. Create a Direct Connect public VIF
- B. Set up an IPsec VPN connection over the public VIF to access Amazon S3. Use HTTPS for communication.
- C. Create an IPsec VPN connection over the transit VIF
- D. Create a VPC and attach the VPC to the transit gateway
- E. In the VPC, provision an interface VPC endpoint for Amazon S3. Use HTTPS for communication.
- F. Create a VPC and attach the VPC to the transit gateway
- G. In the VPC, provision an interface VPC endpoint for Amazon S3. Use HTTPS for communication.
- H. Create a Direct Connect public VIF
- I. Set up an IPsec VPN connection over the public VIF to the transit gateway
- J. Create an attachment for Amazon S3. Use HTTPS for communication.

Answer: B

NEW QUESTION 3

A security team is performing an audit of a company's AWS deployment. The security team is concerned that two applications might be accessing resources that should be blocked by network ACLs and security groups. The applications are deployed across two Amazon Elastic Kubernetes Service (Amazon EKS) clusters that use the Amazon VPC Container Network Interface (CNI) plugin for Kubernetes. The clusters are in separate subnets within the same VPC and have a Cluster Autoscaler configured.

The security team needs to determine which POD IP addresses are communicating with which services throughout the VPC. The security team wants to limit the number of flow logs and wants to examine the traffic from only the two applications.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create VPC flow logs in the default format
- B. Create a filter to gather flow logs only from the EKS nodes. Include the srcaddr field and the dstaddr field in the flow logs.
- C. Create VPC flow logs in a custom format
- D. Set the EKS nodes as the resource. Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.
- E. Create VPC flow logs in a custom format
- F. Set the application subnets as resource
- G. Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.
- H. Create VPC flow logs in a custom format
- I. Create a filter to gather flow logs only from the EKS nodes. Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.

Answer: D

NEW QUESTION 4

A company has two on-premises data center locations. There is a company-managed router at each data center. Each data center has a dedicated AWS Direct Connect connection to a Direct Connect gateway through a private virtual interface. The router for the first location is advertising 110 routes to the Direct Connect gateway by using BGP, and the router for the second location is advertising 60 routes to the Direct Connect gateway by using BGP. The Direct Connect gateway is attached to a company VPC through a virtual private gateway.

A network engineer receives reports that resources in the VPC are not reachable from various locations in either data center. The network engineer checks the VPC route table and sees that the routes from the first data center location are not being populated into the route table. The network engineer must resolve this

issue in the most operationally efficient manner.
What should the network engineer do to meet these requirements?

- A. Remove the Direct Connect gateway, and create a new private virtual interface from each company router to the virtual private gateway of the VPC.
- B. Change the router configurations to summarize the advertised routes.
- C. Open a support ticket to increase the quota on advertised routes to the VPC route table.
- D. Create an AWS Transit Gateway
- E. Attach the transit gateway to the VPC, and connect the Direct Connect gateway to the transit gateway.

Answer: B

Explanation:

"If you advertise more than 100 routes each for IPv4 and IPv6 over the BGP session, the BGP session will go into an idle state with the BGP session DOWN." <https://docs.aws.amazon.com/directconnect/latest/UserGuide/limits.html>

NEW QUESTION 5

An international company provides early warning about tsunamis. The company plans to use IoT devices to monitor sea waves around the world. The data that is collected by the IoT devices must reach the company's infrastructure on AWS as quickly as possible. The company is using three operation centers around the world. Each operation center is connected to AWS through its own AWS Direct Connect connection. Each operation center is connected to the internet through at least two upstream internet service providers.

The company has its own provider-independent (PI) address space. The IoT devices use TCP protocols for reliable transmission of the data they collect. The IoT devices have both landline and mobile internet connectivity. The infrastructure and the solution will be deployed in multiple AWS Regions. The company will use Amazon Route 53 for DNS services.

A network engineer needs to design connectivity between the IoT devices and the services that run in the AWS Cloud.
Which solution will meet these requirements with the HIGHEST availability?

- A. Set up an Amazon CloudFront distribution with origin failover
- B. Create an origin group for each Region where the solution is deployed.
- C. Set up Route 53 latency-based routing
- D. Add latency alias record
- E. For the latency alias records, set the value of Evaluate Target Health to Yes.
- F. Set up an accelerator in AWS Global Accelerator
- G. Configure Regional endpoint groups and health checks.
- H. Set up Bring Your Own IP (BYOIP) addresses
- I. Use the same PI addresses for each Region where the solution is deployed.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/iot/automate-global-device-provisioning-with-aws-iot-core-and-amazon-route-53>

NEW QUESTION 6

An ecommerce company is hosting a web application on Amazon EC2 instances to handle continuously changing customer demand. The EC2 instances are part of an Auto Scaling group. The company wants to implement a solution to distribute traffic from customers to the EC2 instances. The company must encrypt all traffic at all stages between the customers and the application servers. No decryption at intermediate points is allowed.

Which solution will meet these requirements?

- A. Create an Application Load Balancer (ALB). Add an HTTPS listener to the ALB
- B. Configure the Auto Scaling group to register instances with the ALB's target group.
- C. Create an Amazon CloudFront distribution
- D. Configure the distribution with a custom SSL/TLS certificate
- E. Set the Auto Scaling group as the distribution's origin.
- F. Create a Network Load Balancer (NLB). Add a TCP listener to the NLB
- G. Configure the Auto Scaling group to register instances with the NLB's target group.
- H. Create a Gateway Load Balancer (GLB). Configure the Auto Scaling group to register instances with the GLB's target group.

Answer: C

Explanation:

To distribute traffic from customers to EC2 instances in an Auto Scaling group and encrypt all traffic at all stages between the customers and the application servers without decryption at intermediate points, the company should create a Network Load Balancer (NLB) with a TCP listener and configure the Auto Scaling group to register instances with the NLB's target group (Option C). This solution allows for end-to-end encryption of traffic without decryption at intermediate points.

NEW QUESTION 7

A company is running multiple workloads on Amazon EC2 instances in public subnets. In a recent incident, an attacker exploited an application vulnerability on one of the EC2 instances to gain access to the instance. The company fixed the application and launched a replacement EC2 instance that contains the updated application.

The attacker used the compromised application to spread malware over the internet. The company became aware of the compromise through a notification from AWS. The company needs the ability to identify when an application that is deployed on an EC2 instance is spreading malware.

Which solution will meet this requirement with the LEAST operational effort?

- A. Use Amazon GuardDuty to analyze traffic patterns by inspecting DNS requests and VPC flow logs.
- B. Use Amazon GuardDuty to deploy AWS managed decoy systems that are equipped with the most recent malware signatures.
- C. Set up a Gateway Load Balancer
- D. Run an intrusion detection system (IDS) appliance from AWS Marketplace on Amazon EC2 for traffic inspection.
- E. Configure Amazon Inspector to perform deep packet inspection of outgoing traffic.

Answer: A

Explanation:

This solution involves using Amazon GuardDuty to monitor network traffic and analyze DNS requests and VPC flow logs for suspicious activity. This will allow the company to identify when an application is spreading malware by monitoring the network traffic patterns associated with the instance. GuardDuty is a fully managed threat detection service that continuously monitors for malicious activity and unauthorized behavior in your AWS accounts and workloads. It requires minimal setup and configuration and can be integrated with other AWS services for automated remediation. This solution requires the least operational effort compared to the other options

NEW QUESTION 8

A banking company is successfully operating its public mobile banking stack on AWS. The mobile banking stack is deployed in a VPC that includes private subnets and public subnets. The company is using IPv4 networking and has not deployed or supported IPv6 in the environment. The company has decided to adopt a third-party service provider's API and must integrate the API with the existing environment. The service provider's API requires the use of IPv6.

A network engineer must turn on IPv6 connectivity for the existing workload that is deployed in a private subnet. The company does not want to permit IPv6 traffic from the public internet and mandates that the company's servers must initiate all IPv6 connectivity. The network engineer turns on IPv6 in the VPC and in the private subnets.

Which solution will meet these requirements?

- A. Create an internet gateway and a NAT gateway in the VP
- B. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT gateway.
- C. Create an internet gateway and a NAT instance in the VP
- D. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT instance.
- E. Create an egress-only Internet gateway in the VPAdd a route to the existing subnet route tables topointIPv6 traffic to the egress-only internet gateway.
- F. Create an egress-only internet gateway in the VP
- G. Configure a security group that denies all inbound traffi
- H. Associate the security group with the egress-only internet gateway.

Answer: C

NEW QUESTION 9

An IoT company sells hardware sensor modules that periodically send out temperature, humidity, pressure, and location data through the MQTT messaging protocol. The hardware sensor modules send this data to the company's on-premises MQTT brokers that run on Linux servers behind a load balancer. The hardware sensor modules have been hardcoded with public IP addresses to reach the brokers.

The company is growing and is acquiring customers across the world. The existing solution can no longer scale and is introducing additional latency because of the company's global presence. As a result, the company decides to migrate its entire infrastructure from on premises to the AWS Cloud. The company needs to migrate without reconfiguring the hardware sensor modules that are already deployed across the world. The solution also must minimize latency.

The company migrates the MQTT brokers to run on Amazon EC2 instances. What should the company do next to meet these requirements?

- A. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- B. Use Bring Your Own IP (BYOIP) from the on-premises network with the NLB.
- C. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- D. Create an AWS Global Accelerator accelerator in front of the NLUse Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator.
- E. Place the EC2 instances behind an Application Load Balancer (ALB). Configure TCP listener
- F. Create an AWS Global Accelerator accelerator in front of the AL
- G. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator
- H. Place the EC2 instances behind an Amazon CloudFront distributio
- I. Use Bring Your Own IP (BYOIP) from the on-premises network with CloudFront.

Answer: B

NEW QUESTION 10

A company's network engineer is designing an active-passive connection to AWS from two on-premises data centers. The company has set up AWS Direct Connect connections between the on-premises data centers and AWS. From each location, the company is using a transit VIF that connects to a Direct Connect gateway that is associated with a transit gateway.

The network engineer must ensure that traffic from AWS to the data centers is routed first to the primary data center. The traffic should be routed to the failover data center only in the case of an outage.

Which solution will meet these requirements?

- A. Set the BGP community tag for all prefixes from the primary data center to 7224:7100. Set the BGP community tag for all prefixes from the failover data center to 7224:7300
- B. Set the BGP community tag for all prefixes from the primary data center to 7224:7300. Set the BGP community tag for all prefixes from the failover data center to 7224:7100
- C. Set the BGP community tag for all prefixes from the primary data center to 7224:9300. Set the BGP community tag for all prefixes from the failover data center to 7224:9100
- D. Set the BGP community tag for all prefixes from the primary data center to 7224:9100. Set the BGP community tag for all prefixes from the failover data center to 7224:9300

Answer: B

NEW QUESTION 10

A company hosts an application on Amazon EC2 instances behind an Application Load Balancer (ALB). The company recently experienced a network security breach. A network engineer must collect and analyze logs that include the client IP address, target IP address, target port, and user agent of each user that accesses the application.

What is the MOST operationally efficient solution that meets these requirements?

- A. Configure the ALB to store logs in an Amazon S3 bucke
- B. Download the files from Amazon S3, and use a spreadsheet application to analyze the logs.
- C. Configure the ALB to push logs to Amazon Kinesis Data Stream
- D. Use Amazon Kinesis Data Analytics to analyze the logs.
- E. Configure Amazon Kinesis Data Streams to stream data from the ALB to Amazon OpenSearch Service (Amazon Elasticsearch Service). Use search operations in Amazon OpenSearch Service (Amazon Elasticsearch Service) to analyze the data.

- F. Configure the ALB to store logs in an Amazon S3 bucket
- G. Use Amazon Athena to analyze the logs in Amazon S3.

Answer: D

Explanation:

The most operationally efficient solution to collect and analyze logs that include the client IP address, target IP address, target port, and user agent of each user that accesses the application would be to configure the ALB to store logs in an Amazon S3 bucket and use Amazon Athena to analyze the logs in Amazon S3 (Option D). This solution allows for quick and easy analysis of log data without requiring manual download or manipulation of log files.

NEW QUESTION 12

All IP addresses within a 10.0.0.0/16 VPC are fully utilized with application servers across two Availability Zones. The application servers need to send frequent UDP probes to a single central authentication server on the Internet to confirm that is running up-to-date packages. The network is designed for application servers to use a single NAT gateway for internal access. Testing reveals that a few of the servers are unable to communicate with the authentication server.

- A. The NAT gateway does not support UDP traffic.
- B. The authentication server is not accepting traffic.
- C. The NAT gateway cannot allocate more ports.
- D. The NAT gateway is launched in a private subnet.

Answer: C

Explanation:

Ref:<https://docs.aws.amazon.com/vpc/latest/userguide/vpc-nat-gateway.html>

"A NAT gateway can support up to 55,000 simultaneous connections to each unique destination. This limit also applies if you create approximately 900 connections per second to a single destination (about 55,000 connections per minute). If the destination IP address, the destination port, or the protocol (TCP/UDP/ICMP) changes, you can create an additional 55,000 connections. For more than 55,000 connections, there is an increased chance of connection errors due to port allocation errors. These errors can be monitored by viewing the ErrorPortAllocation CloudWatch metric for your NAT gateway. For more information, see [Monitoring NAT Gateways Using Amazon CloudWatch](#)."

NEW QUESTION 14

A company is deploying a new application in the AWS Cloud. The company wants a highly available web server that will sit behind an Elastic Load Balancer. The load balancer will route requests to multiple target groups based on the URL in the request. All traffic must use HTTPS. TLS processing must be offloaded to the load balancer. The web server must know the user's IP address so that the company can keep accurate logs for security purposes. Which solution will meet these requirements?

- A. Deploy an Application Load Balancer with an HTTPS listener
- B. Use path-based routing rules to forward the traffic to the correct target group
- C. Include the X-Forwarded-For request header with traffic to the targets.
- D. Deploy an Application Load Balancer with an HTTPS listener for each domain
- E. Use host-based routing rules to forward the traffic to the correct target group for each domain
- F. Include the X-Forwarded-For request header with traffic to the targets.
- G. Deploy a Network Load Balancer with a TLS listener
- H. Use path-based routing rules to forward the traffic to the correct target group
- I. Configure client IP address preservation for traffic to the targets.
- J. Deploy a Network Load Balancer with a TLS listener for each domain
- K. Use host-based routing rules to forward the traffic to the correct target group for each domain
- L. Configure client IP address preservation for traffic to the targets.

Answer: A

Explanation:

An Application Load Balancer (ALB) can be used to route traffic to multiple target groups based on the URL in the request. The ALB can be configured with an HTTPS listener to ensure all traffic uses HTTPS. TLS processing can be offloaded to the ALB, which reduces the load on the web server. Path-based routing rules can be used to route traffic to the correct target group based on the URL in the request. The X-Forwarded-For request header can be included with traffic to the targets, which will allow the web server to know the user's IP address and keep accurate logs for security purposes.

NEW QUESTION 18

A company has developed an application on AWS that will track inventory levels of vending machines and initiate the restocking process automatically. The company plans to integrate this application with vending machines and deploy the vending machines in several markets around the world. The application resides in a VPC in the us-east-1 Region. The application consists of an Amazon Elastic Container Service (Amazon ECS) cluster behind an Application Load Balancer (ALB). The communication from the vending machines to the application happens over HTTPS.

The company is planning to use an AWS Global Accelerator accelerator and configure static IP addresses of the accelerator in the vending machines for application endpoint access. The application must be accessible only through the accelerator and not through a direct connection over the internet to the ALB endpoint.

Which solution will meet these requirements?

- A. Configure the ALB in a private subnet of the VPC
- B. Attach an internet gateway without adding routes in the subnet route tables to point to the internet gateway
- C. Configure the accelerator with endpoint groups that include the ALB endpoint
- D. Configure the ALB's security group to only allow inbound traffic from the internet on the ALB listener port.
- E. Configure the ALB in a private subnet of the VPC
- F. Configure the accelerator with endpoint groups that include the ALB endpoint
- G. Configure the ALB's security group to only allow inbound traffic from the internet on the ALB listener port.
- H. Configure the ALB in a public subnet of the VPC. Attach an internet gateway
- I. Add routes in the subnet route tables to point to the internet gateway
- J. Configure the accelerator with endpoint groups that include the ALB endpoint
- K. Configure the ALB's security group to only allow inbound traffic from the accelerator's IP addresses on the ALB listener port.
- L. Configure the ALB in a private subnet of the VPC
- M. Attach an internet gateway

- N. Add routes in the subnet route tables to point to the internet gateway
- O. Configure the accelerator with endpoint groups that include the ALB endpoint
- P. Configure the ALB's security group to only allow inbound traffic from the accelerator's IP addresses on the ALB listener port.

Answer: A

Explanation:

Please read the below link typically describing ELB integration with AWS Global accelerator (and the last line of the extract) - <https://docs.aws.amazon.com/global-accelerator/latest/dg/secure-vpc-connections.html> "When you add an internal Application Load Balancer or an Amazon EC2 instance endpoint in AWS Global Accelerator, you enable internet traffic to flow directly to and from the endpoint in Virtual Private Clouds (VPCs) by targeting it in a private subnet. The VPC that contains the load balancer or EC2 instance must have an internet gateway attached to it, to indicate that the VPC accepts internet traffic. However, you don't need public IP addresses on the load balancer or EC2 instance. You also don't need an associated internet gateway route for the subnet."

NEW QUESTION 19

You deploy an Amazon EC2 instance that runs a web server into a subnet in a VPC. An Internet gateway is attached, and the main route table has a default route (0.0.0.0/0) configured with a target of the Internet gateway.

The instance has a security group configured to allow as follows:

- > Protocol: TCP
- > Port: 80 inbound, nothing outbound

The Network ACL for the subnet is configured to allow as follows:

- > Protocol: TCP
- > Port: 80 inbound, nothing outbound

When you try to browse to the web server, you receive no response. Which additional step should you take to receive a successful response?

- A. Add an entry to the security group outbound rules for Protocol: TCP, Port Range: 80
- B. Add an entry to the security group outbound rules for Protocol: TCP, Port Range: 1024-65535
- C. Add an entry to the Network ACL outbound rules for Protocol: TCP, Port Range: 80
- D. Add an entry to the Network ACL outbound rules for Protocol: TCP, Port Range: 1024-65535

Answer: D

Explanation:

To enable the connection to a service running on an instance, the associated network ACL must allow both inbound traffic on the port that the service is listening on as well as allow outbound traffic from ephemeral ports. When a client connects to a server, a random port from the ephemeral port range (1024-65535) becomes the client's source port. The designated ephemeral port then becomes the destination port for return traffic from the service, so outbound traffic from the ephemeral port must be allowed in the network ACL. <https://aws.amazon.com/premiumsupport/knowledge-center/resolve-connection-sg-acl-inbound/>

NEW QUESTION 24

A bank built a new version of its banking application in AWS using containers that connect to an on-premises database over VPN connection. This application version requires users to also update their client application. The bank plans to deprecate the earlier client version. However, the company wants to keep supporting earlier clients through their on-premises version of the application to serve a small portion of the customers who haven't yet upgraded.

What design will allow the company to serve both newer and earlier clients in the MOST efficient way?

- A. Use an Amazon Route 53 multivalue answer routing policy to route older client traffic to the on-premises application version and the rest of the traffic to the new AWS based version.
- B. Use a Classic Load Balancer for the new application
- C. Route all traffic to the new application by using an Elastic Load Balancing (ELB) load balancer DN
- D. Define a user-agent-based rule on the backend servers to redirect earlier clients to the on-premises application.
- E. Use an Application Load Balancer for the new application
- F. Register both the new and earlier applications as separate target groups and use path-based routing to route traffic based on the application version.
- G. Use an Application Load Balancer for the new application
- H. Register both the new and earlier application backends as separate target group
- I. Use header-based routing to route traffic based on the application version.

Answer: D

NEW QUESTION 29

A company is deploying an application. The application is implemented in a series of containers in an Amazon Elastic Container Service (Amazon ECS) cluster. The company will use the Fargate launch type for its tasks. The containers will run workloads that require connectivity initiated over an SSL connection. Traffic must be able to flow to the application from other AWS accounts over private connectivity. The application must scale in a manageable way as more consumers use the application.

Which solution will meet these requirements?

- A. Choose a Gateway Load Balancer (GLB) as the type of load balancer for the ECS service
- B. Create a lifecycle hook to add new tasks to the target group from Amazon ECS as required to handle scaling
- C. Specify the GLB in the service definition
- D. Create a VPC peer for external AWS account
- E. Update the route tables so that the AWS accounts can reach the GLB.
- F. Choose an Application Load Balancer (ALB) as the type of load balancer for the ECS service
- G. Create path-based routing rules to allow the application to target the containers that are registered in the target group
- H. Specify the ALB in the service definition
- I. Create a VPC endpoint service for the ALB. Share the VPC endpoint service with other AWS accounts.
- J. Choose an Application Load Balancer (ALB) as the type of load balancer for the ECS service
- K. Create path-based routing rules to allow the application to target the containers that are registered in the target group
- L. Specify the ALB in the service definition
- M. Create a VPC peer for the external AWS account
- N. Update the route tables so that the AWS accounts can reach the ALB.
- O. Choose a Network Load Balancer (NLB) as the type of load balancer for the ECS service

- P. Specify the NLB in the service definitio
- Q. Create a VPC endpoint service for the NL
- R. Share the VPC endpoint service with other AWS accounts.

Answer: D

NEW QUESTION 33

Your security team implements a host-based firewall on all of your Amazon Elastic Compute Cloud (EC2) instances to block all outgoing traffic. Exceptions must be requested for each specific requirement. Until you request a new rule, you cannot access the instance metadata service. Which firewall rule should you request to be added to your instances to allow instance metadata access?

- A. Inbound; Protocol tcp; Source [Instance's EIP]; Destination 169.254.169.254
- B. Inbound; Protocol tcp; Destination 169.254.169.254; Destination port 80
- C. Outbound; Protocol tcp; Destination 169.254.169.254; Destination port 80
- D. Outbound; Protocol tcp; Destination 169.254.169.254; Destination port 443

Answer: C

Explanation:

<https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/instancedata-data-retrieval.html>

To view all categories of instance metadata from within a running instance, use the following URI.

<http://169.254.169.254/latest/meta-data/>

NEW QUESTION 38

A company hosts a web application on Amazon EC2 instances behind an Application Load Balancer (ALB). The ALB is the origin in an Amazon CloudFront distribution. The company wants to implement a custom authentication system that will provide a token for its authenticated customers. The web application must ensure that the GET/POST requests come from authenticated customers before it delivers the content. A network engineer must design a solution that gives the web application the ability to identify authorized customers. What is the MOST operationally efficient solution that meets these requirements?

- A. Use the ALB to inspect the authorized token inside the GET/POST request payload
- B. Use an AWS Lambda function to insert a customized header to inform the web application of an authenticated customer request.
- C. Integrate AWS WAF with the ALB to inspect the authorized token inside the GET/POST request payload
- D. Configure the ALB listener to insert a customized header to inform the web application of an authenticated customer request.
- E. Use an AWS Lambda@Edge function to inspect the authorized token inside the GET/POST request payload
- F. Use the Lambda@Edge function also to insert a customized header to inform the web application of an authenticated customer request.
- G. Set up an EC2 instance that has a third-party packet inspection tool to inspect the authorized token inside the GET/POST request payload
- H. Configure the tool to insert a customized header to inform the web application of an authenticated customer request.

Answer: C

NEW QUESTION 41

A network engineer needs to standardize a company's approach to centralizing and managing interface VPC endpoints for private communication with AWS services. The company uses AWS Transit Gateway for inter-VPC connectivity between AWS accounts through a hub-and-spoke model. The company's network services team must manage all Amazon Route 53 zones and interface endpoints within a shared services AWS account. The company wants to use this centralized model to provide AWS resources with access to AWS Key Management Service (AWS KMS) without sending traffic over the public internet. What should the network engineer do to meet these requirements?

- A. In the shared services account, create an interface endpoint for AWS KM
- B. Modify the interface endpoint by disabling the private DNS nam
- C. Create a private hosted zone in the shared services account with an alias record that points to the interface endpoint
- D. Associate the private hosted zone with the spoke VPCs in each AWS account.
- E. In the shared services account, create an interface endpoint for AWS KM
- F. Modify the interface endpoint by disabling the private DNS nam
- G. Create a private hosted zone in each spoke AWS account with an alias record that points to the interface endpoint
- H. Associate each private hosted zone with the shared services AWS account.
- I. In each spoke AWS account, create an interface endpoint for AWS KM
- J. Modify each interface endpoint by disabling the private DNS nam
- K. Create a private hosted zone in each spoke AWS account with an alias record that points to each interface endpoint
- L. Associate each private hosted zone with the shared services AWS account.
- M. In each spoke AWS account, create an interface endpoint for AWS KM
- N. Modify each interface endpoint by disabling the private DNS nam
- O. Create a private hosted zone in the shared services account with an alias record that points to each interface endpoint
- P. Associate the private hosted zone with the spoke VPCs in each AWS account.

Answer: A

NEW QUESTION 45

Your organization has a newly installed 1-Gbps AWS Direct Connect connection. You order the cross-connect from the Direct Connect location provider to the port on your router in the same facility. To enable the use of your first virtual interface, your router must be configured appropriately. What are the minimum requirements for your router?

- A. 1-Gbps Multi Mode Fiber Interface, 802.1Q VLAN, Peer IP Address, BGP Session with MD5.
- B. 1-Gbps Single Mode Fiber Interface, 802.1Q VLAN, Peer IP Address, BGP Session with MD5.
- C. IPsec Parameters, Pre-Shared key, Peer IP Address, BGP Session with MD5
- D. BGP Session with MD5, 802.1Q VLAN, Route-Map, Prefix List, IPsec encrypted GRE Tunnel

Answer: B

NEW QUESTION 50

A company has expanded its network to the AWS Cloud by using a hybrid architecture with multiple AWS accounts. The company has set up a shared AWS account for the connection to its on-premises data centers and the company offices. The workloads consist of private web-based services for internal use. These services run in different AWS accounts. Office-based employees consume these services by using a DNS name in an on-premises DNS zone that is named example.internal.

The process to register a new service that runs on AWS requires a manual and complicated change request to the internal DNS. The process involves many teams.

The company wants to update the DNS registration process by giving the service creators access that will allow them to register their DNS records. A network engineer must design a solution that will achieve this goal. The solution must maximize cost-effectiveness and must require the least possible number of configuration changes.

Which combination of steps should the network engineer take to meet these requirements? (Choose three.)

- A. Create a record for each service in its local private hosted zone (serviceA.account1.aws.example.internal). Provide this DNS record to the employees who need access.
- B. Create an Amazon Route 53 Resolver inbound endpoint in the shared account VPC
- C. Create a conditional forwarder for a domain named aws.example.internal on the on-premises DNS server
- D. Set the forwarding IP addresses to the inbound endpoint's IP addresses that were created.
- E. Create an Amazon Route 53 Resolver rule to forward any queries made to onprem.example.internal to the on-premises DNS servers.
- F. Create an Amazon Route 53 private hosted zone named aws.example.internal in the shared AWS account to resolve queries for this domain.
- G. Launch two Amazon EC2 instances in the shared AWS account
- H. Install BIND on each instance
- I. Create a DNS conditional forwarder on each BIND server to forward queries for each subdomain under aws.example.internal to the appropriate private hosted zone in each AWS account
- J. Create a conditional forwarder for a domain named aws.example.internal on the on-premises DNS server
- K. Set the forwarding IP addresses to the IP addresses of the BIND servers.
- L. Create a private hosted zone in the shared AWS account for each account that runs the service. Configure the private hosted zone to contain aws.example.internal in the domain (account1.aws.example.internal). Associate the private hosted zone with the VPC that runs the service and the shared account VPC.

Answer: ABD

Explanation:

To meet the requirements of updating the DNS registration process while maximizing cost-effectiveness and minimizing configuration changes, the network engineer should take the following steps:

- Create an Amazon Route 53 Resolver inbound endpoint in the shared account VPC. Create a conditional forwarder for a domain named aws.example.internal on the on-premises DNS servers. Set the forwarding IP addresses to the inbound endpoint's IP addresses that were created (Option B).
- Create an Amazon Route 53 private hosted zone named aws.example.internal in the shared AWS account to resolve queries for this domain (Option D).
- Create a record for each service in its local private hosted zone (serviceA.account1.aws.example.internal). Provide this DNS record to the employees who need access (Option A).

These steps will allow service creators to register their DNS records while keeping costs low and minimizing configuration changes.

NEW QUESTION 55

A company operates its IT services through a multi-site hybrid infrastructure. The company deploys resources on AWS in the us-east-1 Region and in the eu-west-2 Region. The company also deploys resources in its own data centers that are located in the United States (US) and in the United Kingdom (UK). In both AWS Regions, the company uses a transit gateway to connect 15 VPCs to each other. The company has created a transit gateway peering connection between the two transit gateways. The VPC CIDR blocks do not overlap with each other or with IP addresses used within the data centers. The VPC CIDR prefixes can also be aggregated either on a Regional level or for the company's entire AWS environment.

The data centers are connected to each other by a private WAN connection. IP routing information is exchanged dynamically through Interior BGP (iBGP) sessions. The data centers maintain connectivity to AWS through one AWS Direct Connect connection in the US and one Direct Connect connection in the UK. Each Direct Connect connection is terminated on a Direct Connect gateway and is associated with a local transit gateway through a transit VIF.

Traffic follows the shortest geographical path from source to destination. For example, packets from the UK data center that are targeted to resources in eu-west-2 travel across the local Direct Connect connection. In cases of cross-Region data transfers, such as from the UK data center to VPCs in us-east-1, the private WAN connection must be used to minimize costs on AWS. A network engineer has configured each transit gateway association on the Direct Connect gateway to advertise VPC-specific CIDR IP prefixes only from the local Region. The routes toward the other Region must be learned through BGP from the routers in the other data center in the original, non-aggregated form.

The company recently experienced a problem with cross-Region data transfers because of issues with its private WAN connection. The network engineer needs to modify the routing setup to prevent similar interruptions in the future. The solution cannot modify the original traffic routing goal when the network is operating normally.

Which modifications will meet these requirements? (Choose two.)

- A. Remove all the VPC CIDR prefixes from the list of subnets advertised through the local Direct Connect connection
- B. Add the company's entire AWS environment aggregate route to the list of subnets advertised through the local Direct Connect connection.
- C. Add the CIDR prefixes from the other Region VPCs and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connection
- D. Configure data center routers to make routing decisions based on the BGP communities received.
- E. Add the aggregate IP prefix for the other Region and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connection.
- F. Add the aggregate IP prefix for the company's entire AWS environment and the local VPC CIDR blocks to the list of subnets advertised through the local Direct Connect connection.
- G. Remove all the VPC CIDR prefixes from the list of subnets advertised through the local Direct Connect connection
- H. Add both Regional aggregate IP prefixes to the list of subnets advertised through the Direct Connect connection on both sides of the network
- I. Configure data center routers to make routing decisions based on the BGP communities received.

Answer: AD

NEW QUESTION 59

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your ANS-C01 Exam with Our Prep Materials Via below:

<https://www.certleader.com/ANS-C01-dumps.html>