

# Amazon

## Exam Questions AWS-SysOps

Amazon AWS Certified SysOps Administrator - Associate



#### NEW QUESTION 1

- (Topic 1)

A media company produces new video files on-premises every day with a total size of around 100GBS after compression All files have a size of 1 -2 GB and need to be uploaded to Amazon S3 every night in a fixed time window between 3am and 5am Current upload takes almost 3 hours, although less than half of the available bandwidth is used.

What step(s) would ensure that the file uploads are able to complete in the allotted time window?

- A. Increase your network bandwidth to provide faster throughput to S3
- B. Upload the files in parallel to S3
- C. Pack all files into a single archive, upload it to S3, then extract the files in AWS
- D. Use AWS Import/Export to transfer the video files

**Answer:** B

#### Explanation:

Reference:

<http://aws.amazon.com/importexport/faqs/>

#### NEW QUESTION 2

- (Topic 1)

A customer has a web application that uses cookie Based sessions to track logged in users It Is deployed on AWS using ELB and Auto Scaling The customer observes that when load increases. Auto Scaling launches new Instances but the load on the easting Instances does not decrease, causing all existing users to have a sluggish experience.

Which two answer choices independently describe a behavior that could be the cause of the sluggish user experience? Choose 2 answers

- A. ELB's normal behavior sends requests from the same user to the same backend instance
- B. ELB's behavior when sticky sessions are enabled causes ELB to send requests in the same session to the same backend instance
- C. A faulty browser is not honoring the TTL of the ELB DNS nam
- D. The web application uses long polling such as comet or websocket
- E. Thereby keeping a connection open to a web server tor a long time
- F. The web application uses long polling such as comet or websocket
- G. Thereby keeping a connection open to a web server for a long tim

**Answer:** BD

#### NEW QUESTION 3

- (Topic 1)

You have been asked to leverage Amazon VPC BC2 and SOS to implement an application that submits and receives millions of messages per second to a message queue. You want to ensure your application has sufficient bandwidth between your EC2 instances and SQS Which option will provide the most scalable solution for communicating between the application and SQS?

- A. Ensure the application instances are properly configured with an Elastic Load Balancer
- B. Ensure the application instances are launched in private subnets with the EBS-optimized option enabled
- C. Ensure the application instances are launched in public subnets with the associate-public-IP-address=true option enabled
- D. Launch application instances in private subnets with an Auto Scaling group and Auto Scaling triggers configured to watch the SQS queue size

**Answer:** B

#### Explanation:

Reference:

<http://www.cardinalpath.com/autoscaling-your-website-with-amazon-web-services-part-2/>

#### NEW QUESTION 4

- (Topic 1)

You need to design a VPC for a web-application consisting of an Elastic Load Balancer (ELB). a fleet of web/application servers, and an RDS database The entire Infrastructure must be distributed over 2 availability zones.

Which VPC configuration works while assuring the database is not available from the Internet?

- A. One public subnet for ELB one public subnet for the web-servers, and one private subnet for the database
- B. One public subnet for ELB two private subnets for the web-servers, two private subnets for RDS
- C. Two public subnets for ELB two private subnets for the web-servers and two private subnets for RDS
- D. Two public subnets for ELB two public subnets for the web-servers, and two public subnets for RDS

**Answer:** A

#### NEW QUESTION 5

- (Topic 1)

You have set up Individual AWS accounts for each project. You have been asked to make sure your AWS Infrastructure costs do not exceed the budget set per project for each month.

Which of the following approaches can help ensure that you do not exceed the budget each month?

- A. Consolidate your accounts so you have a single bill for all accounts and projects
- B. Set up auto scaling with CloudWatch alarms using SNS to notify you when you are running too many Instances in a given account
- C. Set up CloudWatch billing alerts for all AWS resources used by each project, with a notification occurring when the amount for each resource tagged to a particular project matches the budget allocated to the projec
- D. Set up CloudWatch billing alerts for all AWS resources used by each account, with email notifications when it hits 50%. 80% and 90% of its budgeted monthly spend

**Answer:** C

#### NEW QUESTION 6

- (Topic 1)

Your entire AWS infrastructure lives inside of one Amazon VPC. You have an Infrastructure monitoring application running on an Amazon instance in Availability Zone (AZ) A of the region, and another application instance running in AZ B. The monitoring application needs to make use of ICMP ping to confirm network reachability of the instance hosting the application.

Can you configure the security groups for these instances to only allow the ICMP ping to pass from the monitoring instance to the application instance and nothing else? If so, how?

- A. No. Two instances in two different AZ's can't talk directly to each other via ICMP ping as that protocol is not allowed across subnet (i.e. broadcast) boundaries.
- B. Yes. Both the monitoring instance and the application instance have to be a part of the same security group, and that security group needs to allow inbound ICMP.
- C. Yes, The security group for the monitoring instance needs to allow outbound ICMP and the application instance's security group needs to allow Inbound ICMP.
- D. Yes, Both the monitoring instance's security group and the application instance's security group need to allow both inbound and outbound ICMP ping packets since ICMP is not a connection-oriented protocol.

**Answer:** D

#### NEW QUESTION 7

- (Topic 1)

You run a web application where web servers on EC2 Instances are in an Auto Scaling group. Monitoring over the last 6 months shows that 6 web servers are necessary to handle the minimum load. During the day, up to 12 servers are needed. Five to six days per year, the number of web servers required might go up to 15.

What would you recommend to minimize costs while being able to provide high availability?

- A. 6 Reserved instances (heavy utilization), 6 Reserved instances (medium utilization), rest covered by On-Demand instances.
- B. 6 Reserved instances (heavy utilization), 6 On-Demand instances, rest covered by Spot Instances.
- C. 6 Reserved instances (heavy utilization), 6 Spot instances, rest covered by On-Demand instances.
- D. 6 Reserved instances (heavy utilization), 6 Reserved instances (medium utilization), rest covered by Spot instances.

**Answer:** B

#### NEW QUESTION 8

- (Topic 1)

You are currently hosting multiple applications in a VPC and have logged numerous port scans coming in from a specific IP address block. Your security team has requested that all access from the offending IP address block be denied for the next 24 hours.

Which of the following is the best method to quickly and temporarily deny access from the specified IP address block?

- A. Create an IAM policy to modify Windows Firewall settings on all hosts in the VPC to deny access from the IP address block.
- B. Modify the Network ACLs associated with all public subnets in the VPC to deny access from the IP address block.
- C. Add a rule to all of the VPC's Security Groups to deny access from the IP address block.
- D. Modify the Windows Firewall settings on all Amazon Machine Images (AMIs) that your organization uses in that VPC to deny access from the IP address block.

**Answer:** B

#### Explanation:

Reference:

[http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_SecurityGroups.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_SecurityGroups.html)

#### NEW QUESTION 9

- (Topic 1)

Which of the following are characteristics of Amazon VPC subnets?

Choose 2 answers.

- A. Each subnet maps to a single Availability Zone.
- B. A CIDR block mask of /25 is the smallest range supported.
- C. Instances in a private subnet can communicate with the internet only if they have an Elastic IP.
- D. By default, all subnets can route between each other, whether they are private or public.
- E. Each subnet spans at least 2 Availability zones to provide a high-availability environment.

**Answer:** CE

#### NEW QUESTION 10

- (Topic 1)

You have two Elastic Compute Cloud (EC2) instances inside a Virtual Private Cloud (VPC) in the same Availability Zone (AZ) but in different subnets. One instance is running a database and the other instance an application that will interface with the database. You want to confirm that they can talk to each other for your application to work properly.

Which two things do we need to confirm in the VPC settings so that these EC2 instances can communicate inside the VPC? Choose 2 answers.

- A. A network ACL that allows communication between the two subnets.
- B. Both instances are the same instance class and using the same Key-pair.
- C. That the default route is set to a NAT instance or internet Gateway (IGW) for them to communicate.
- D. Security groups are set to allow the application host to talk to the database on the right port/protocol.

**Answer:** AD

**NEW QUESTION 10**

- (Topic 1)

You are creating an Auto Scaling group whose Instances need to insert a custom metric into CloudWatch.

Which method would be the best way to authenticate your CloudWatch PUT request?

- A. Create an IAM role with the Put MetricData permission and modify the Auto Scaling launch configuration to launch instances in that role
- B. Create an IAM user with the PutMetricData permission and modify the Auto Scaling launch configuration to inject the userscredentials into the instance User Data
- C. Modify the appropriate Cloud Watch metric policies to allow the Put MetricData permission to instances from the Auto Scaling group
- D. Create an IAM user with the PutMetricData permission and put the credentials in a private repository and have applications on the server pull the credentials as needed

**Answer:** A

**NEW QUESTION 13**

- (Topic 1)

Which two AWS services provide out-of-the-box user configurable automatic backup-as-a-service and backup rotation options?

Choose 2 answers

- A. Amazon S3
- B. Amazon RDS
- C. Amazon EBS
- D. Amazon Red shift

**Answer:** BD

**NEW QUESTION 14**

- (Topic 1)

You are using ElastiCache Memcached to store session state and cache database queries in your infrastructure. You notice in CloudWatch that Evictions and GetMisses are both very high.

What two actions could you take to rectify this?

Choose 2 answers

- A. Increase the number of nodes in your cluster
- B. Tweak the max\_item\_size parameter
- C. Shrink the number of nodes in your cluster
- D. Increase the size of the nodes in the cluster

**Answer:** BD

**NEW QUESTION 18**

- (Topic 1)

You are attempting to connect to an instance in Amazon VPC without success. You have already verified that the VPC has an Internet Gateway (IGW), the instance has an associated Elastic IP (EIP), and correct security group rules are in place.

Which VPC component should you evaluate next?

- A. The configuration of a NAT instance
- B. The configuration of the Routing Table
- C. The configuration of the Internet Gateway (IGW)
- D. The configuration of SRC/DST checking

**Answer:** B

**Explanation:**

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/UserScenariosForVPC.html>

**NEW QUESTION 19**

- (Topic 1)

You have been asked to automate many routine systems administrator backup and recovery activities. Your current plan is to leverage AWS-managed solutions as much as possible and automate the rest with the AWS CLI and scripts.

Which task would be best accomplished with a script?

- A. Creating daily EBS snapshots with a monthly rotation of snapshots
- B. Creating daily RDS snapshots with a monthly rotation of snapshots
- C. Automatically detect and stop unused or underutilized EC2 instances
- D. Automatically add Auto Scaled EC2 instances to an Amazon Elastic Load Balancer

**Answer:** A

**NEW QUESTION 24**

- (Topic 1)

What are characteristics of Amazon S3? Choose 2 answers

- A. Objects are directly accessible via a URL
- B. S3 should be used to host a relational database
- C. S3 allows you to store objects of virtually unlimited size

- D. S3 allows you to store virtually unlimited amounts of data
- E. S3 offers Provisioned IOPS

**Answer:** AD

#### NEW QUESTION 27

- (Topic 2)

A user is planning to setup infrastructure on AWS for the Christmas sales. The user is planning to use Auto Scaling based on the schedule for proactive scaling. What advise would you give to the user?

- A. It is good to schedule now because if the user forgets later on it will not scale up
- B. The scaling should be setup only one week before Christmas
- C. Wait till end of November before scheduling the activity
- D. It is not advisable to use scheduled based scaling

**Answer:** C

#### Explanation:

Auto Scaling based on a schedule allows the user to scale the application in response to predictable load changes. The user can specify any date in the future to scale up or down during that period. As per Auto Scaling the user can schedule an action for up to a month in the future. Thus, it is recommended to wait until end of November before scheduling for Christmas.

#### NEW QUESTION 32

- (Topic 2)

A user is trying to connect to a running EC2 instance using SSH. However, the user gets a connection time out error. Which of the below mentioned options is not a possible reason for rejection?

- A. The access key to connect to the instance is wrong
- B. The security group is not configured properly
- C. The private key used to launch the instance is not correct
- D. The instance CPU is heavily loaded

**Answer:** A

#### Explanation:

If the user is trying to connect to a Linux EC2 instance and receives the connection time out error the probable reasons are: Security group is not configured with the SSH port The private key pair is not right The user name to login is wrong The instance CPU is heavily loaded, so it does not allow more connections

#### NEW QUESTION 35

- (Topic 2)

A user wants to disable connection draining on an existing ELB. Which of the below mentioned statements helps the user disable connection draining on the ELB?

- A. The user can only disable connection draining from CLI
- B. It is not possible to disable the connection draining feature once enabled
- C. The user can disable the connection draining feature from EC2 -> ELB console or from CLI
- D. The user needs to stop all instances before disabling connection draining

**Answer:** C

#### Explanation:

The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that inflight requests continue to be served. The user can enable or disable connection draining from the AWS EC2 console -> ELB or using CLI.

#### NEW QUESTION 38

- (Topic 2)

An organization is generating digital policy files which are required by the admins for verification. Once the files are verified they may not be required in the future unless there is some compliance issue. If the organization wants to save them in a cost effective way, which is the best possible solution?

- A. AWS RRS
- B. AWS S3
- C. AWS RDS
- D. AWS Glacier

**Answer:** D

#### Explanation:

Amazon S3 stores objects according to their storage class. There are three major storage classes: Standard, Reduced Redundancy and Glacier. Standard is for AWS S3 and provides very high durability. However, the costs are a little higher. Reduced redundancy is for less critical files. Glacier is for archival and the files which are accessed infrequently. It is an extremely low-cost storage service that provides secure and durable storage for data archiving and backup.

#### NEW QUESTION 39

- (Topic 2)



A user has created an ELB with the availability zone US-East-1A. The user wants to add more zones to ELB to achieve High Availability. How can the user add more zones to the existing ELB?

- A. It is not possible to add more zones to the existing ELB
- B. The only option is to launch instances in different zones and add to ELB
- C. The user should stop the ELB and add zones and instances as required
- D. The user can add zones on the fly from the AWS console

**Answer:** D

**Explanation:**

The user has created an Elastic Load Balancer with the availability zone and wants to add more zones to the existing ELB. The user can do so in two ways: From the console or CLI, add new zones to ELB; Launch instances in a separate AZ and add instances to the existing ELB.

#### NEW QUESTION 44

- (Topic 2)

A user has developed an application which is required to send the data to a NoSQL database. The user wants to decouple the data sending such that the application keeps processing and sending data but does not wait for an acknowledgement of DB. Which of the below mentioned applications helps in this scenario?

- A. AWS Simple Notification Service
- B. AWS Simple Workflow
- C. AWS Simple Queue Service
- D. AWS Simple Query Service

**Answer:** C

**Explanation:**

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. In this case, the user can use AWS SQS to send messages which are received from an application and sent to DB. The application can continue processing data without waiting for any acknowledgement from DB. The user can use SQS to transmit any volume of data without losing messages or requiring other services to always be available.

#### NEW QUESTION 47

- (Topic 2)

An organization is planning to create 5 different AWS accounts considering various security requirements. The organization wants to use a single payee account by using the consolidated billing option. Which of the below mentioned statements is true with respect to the above information?

- A. Master (Payee) account will get only the total bill and cannot see the cost incurred by each account
- B. Master (Payee) account can view only the AWS billing details of the linked accounts
- C. It is not recommended to use consolidated billing since the payee account will have access to the linked accounts
- D. Each AWS account needs to create an AWS billing policy to provide permission to the payee account

**Answer:** B

**Explanation:**

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account. The payee account will not have any other access than billing data of linked accounts.

#### NEW QUESTION 51

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/16. The user has created public and VPN only subnets along with hardware VPN access to connect to the user's datacenter. The user wants to make so that all traffic coming to the public subnet follows the organization's proxy policy. How can the user make this happen?

- A. Setting up a NAT with the proxy protocol and configure that the public subnet receives traffic from NAT
- B. Setting up a proxy policy in the internet gateway connected with the public subnet
- C. It is not possible to setup the proxy policy for a public subnet
- D. Setting the route table and security group of the public subnet which receives traffic from a virtual private gateway

**Answer:** D

**Explanation:**

The user can create subnets within a VPC. If the user wants to connect to VPC from his own data centre, he can setup public and VPN only subnets which uses hardware VPN access to connect with his data centre. When the user has configured this setup, it will update the main route table used with the VPN-only subnet, create a custom route table and associate it with the public subnet. It also creates an internet gateway for the public subnet. By default the internet traffic of the VPN subnet is routed to a virtual private gateway while the internet traffic of the public subnet is routed through the internet gateway. The user can set up the route and security group rules. These rules enable the traffic to come from the organization's network over the virtual private gateway to the public subnet to allow proxy settings on that public subnet.

**NEW QUESTION 56**

- (Topic 2)

A user has created a photo editing software and hosted it on EC2. The software accepts requests from the user about the photo format and resolution and sends a message to S3 to enhance the picture accordingly. Which of the below mentioned AWS services will help make a scalable software with the AWS infrastructure in this scenario?

- A. AWS Glacier
- B. AWS Elastic Transcoder
- C. AWS Simple Notification Service
- D. AWS Simple Queue Service

**Answer:** D

**Explanation:**

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can configure SQS, which will decouple the call between the EC2 application and S3. Thus, the application does not keep waiting for S3 to provide the data.

**NEW QUESTION 57**

- (Topic 2)

A user is planning to use AWS Cloud formation for his automatic deployment requirements. Which of the below mentioned components are required as a part of the template?

- A. Parameters
- B. Outputs
- C. Template version
- D. Resources

**Answer:** D

**Explanation:**

AWS Cloud formation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The template is a JSON-format, text-based file that describes all the AWS resources required to deploy and run an application. It can have option fields, such as Template Parameters, Output, Data tables, and Template file format version. The only mandatory value is Resource. The user can define the AWS services which will be used/ created by this template inside the Resource section

**NEW QUESTION 62**

- (Topic 2)

A user has setup a billing alarm using CloudWatch for \$200. The usage of AWS exceeded \$200 after some days. The user wants to increase the limit from \$200 to \$400? What should the user do?

- A. Create a new alarm of \$400 and link it with the first alarm
- B. It is not possible to modify the alarm once it has crossed the usage limit
- C. Update the alarm to set the limit at \$400 instead of \$200
- D. Create a new alarm for the additional \$200 amount

**Answer:** C

**Explanation:**

AWS CloudWatch supports enabling the billing alarm on the total AWS charges. The estimated charges are calculated and sent several times daily to CloudWatch in the form of metric data. This data will be stored for 14 days. This data also includes the estimated charges for every service in AWS used by the user, as well as the estimated overall AWS charges. If the user wants to increase the limit, the user can modify the alarm and specify a new threshold.

**NEW QUESTION 66**

- (Topic 2)

An organization is planning to use AWS for 5 different departments. The finance department is responsible to pay for all the accounts. However, they want the cost separation for each account to map with the right cost centre. How can the finance department achieve this?

- A. Create 5 separate accounts and make them a part of one consolidate billing
- B. Create 5 separate accounts and use the IAM cross account access with the roles for better management
- C. Create 5 separate IAM users and set a different policy for their access
- D. Create 5 separate IAM groups and add users as per the department's employees

**Answer:** A

**Explanation:**

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. Consolidated billing enables the organization to see a combined view of the AWS charges incurred by each account as well as obtain a detailed cost report for each of the individual AWS accounts associated with the paying account.

**NEW QUESTION 69**

- (Topic 2)

A user has created a VPC with CIDR 20.0.0.0/24. The user has created a public subnet with CIDR 20.0.0.0/25. The user is trying to create the private subnet with CIDR 20.0.0.128/25. Which of the below mentioned statements is true in this scenario?

- A. It will not allow the user to create the private subnet due to a CIDR overlap
- B. It will allow the user to create a private subnet with CIDR as 20.0.0.128/25
- C. This statement is wrong as AWS does not allow CIDR 20.0.0.0/25
- D. It will not allow the user to create a private subnet due to a wrong CIDR range

**Answer:** B

**Explanation:**

When the user creates a subnet in VPC, he specifies the CIDR block for the subnet. The CIDR block of a subnet can be the same as the CIDR block for the VPC (for a single subnet in the VPC., or a subset (to enable multiple subnets.. If the user creates more than one subnet in a VPC, the CIDR blocks of the subnets must not overlap. Thus, in this case the user has created a VPC with the CIDR block 20.0.0.0/24, which supports 256 IP addresses (20.0.0.0 to 20.0.0.255.. The user can break this CIDR block into two subnets, each supporting 128 IP addresses. One subnet uses the CIDR block 20.0.0.0/25 (for addresses 20.0.0.0 - 20.0.0.127. and the other uses the CIDR block 20.0.0.128/25 (for addresses 20.0.0.128 - 20.0.0.255..

#### NEW QUESTION 71

- (Topic 2)

An organization has setup consolidated billing with 3 different AWS accounts. Which of the below mentioned advantages will organization receive in terms of the AWS pricing?

- A. The consolidated billing does not bring any cost advantage for the organization
- B. All AWS accounts will be charged for S3 storage by combining the total storage of each account
- C. The EC2 instances of each account will receive a total of 750\*3 micro instance hours free
- D. The free usage tier for all the 3 accounts will be 3 years and not a single year

**Answer:** B

**Explanation:**

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS. accounts within a single organization by making a single paying account. For billing purposes, AWS treats all the accounts on the consolidated bill as one account. Some services, such as Amazon EC2 and Amazon S3 have volume pricing tiers across certain usage dimensions that give the user lower prices when he uses the service more.

#### NEW QUESTION 73

- (Topic 2)

A user has enabled the Multi AZ feature with the MS SQL RDS database server. Which of the below mentioned statements will help the user understand the Multi AZ feature better?

- A. In a Multi AZ, AWS runs two DBs in parallel and copies the data asynchronously to the replica copy
- B. In a Multi AZ, AWS runs two DBs in parallel and copies the data synchronously to the replica copy
- C. In a Multi AZ, AWS runs just one DB but copies the data synchronously to the standby replica
- D. AWS MS SQL does not support the Multi AZ feature

**Answer:** C

**Explanation:**

Amazon RDS provides high availability and failover support for DB instances using Multi-AZ deployments. In a Multi-AZ deployment, Amazon RDS automatically provisions and maintains a synchronous standby replica in a different Availability Zone. The primary DB instance is synchronously replicated across Availability Zones to a standby replica to provide data redundancy, eliminate I/O freezes, and minimize latency spikes during system backups. Running a DB instance with high availability can enhance availability during planned system maintenance, and help protect your databases against DB instance failure and Availability Zone disruption. Note that the high-availability feature is not a scaling solution for read-only scenarios; you cannot use a standby replica to serve read traffic. To service read-only traffic, you should use a read replica.

#### NEW QUESTION 76

- (Topic 2)

An organization is setting up programmatic billing access for their AWS account. Which of the below mentioned services is not required or enabled when the organization wants to use programmatic access?

- A. Programmatic access
- B. AWS bucket to hold the billing report
- C. AWS billing alerts
- D. Monthly Billing report

**Answer:** C

**Explanation:**

AWS provides an option to have programmatic access to billing. Programmatic Billing Access leverages the existing Amazon Simple Storage Service (Amazon S3. APIs. Thus, the user can build applications that reference his billing data from a CSV (comma-separated value. file stored in an Amazon S3 bucket. To enable programmatic access, the user has to first enable the monthly billing report. Then the user needs to provide an AWS bucket name where the billing CSV will be uploaded. The user should also enable the Programmatic access option.

#### NEW QUESTION 78

- (Topic 2)

A user has configured ELB with two EBS backed EC2 instances. The user is trying to understand the DNS access and IP support for ELB. Which of the below mentioned statements may not help the user understand the IP mechanism supported by ELB?

- A. The client can connect over IPV4 or IPV6 using Dualstack



- B. ELB DNS supports both IPV4 and IPV6
- C. Communication between the load balancer and back-end instances is always through IPV4
- D. The ELB supports either IPV4 or IPV6 but not both

**Answer:** D

**Explanation:**

Elastic Load Balancing supports both Internet Protocol version 6 (IPv6) and Internet Protocol version 4 (IPv4). Clients can connect to the user's load balancer using either IPv4 or IPv6 (in EC2-Classic DNS). However, communication between the load balancer and its back-end instances uses only IPv4. The user can use the Dualstack-prefixed DNS name to enable IPv6 support for communications between the client and the load balancers. Thus, the clients are able to access the load balancer using either IPv4 or IPv6 as their individual connectivity needs dictate.

#### NEW QUESTION 79

- (Topic 2)

An organization has added 3 of his AWS accounts to consolidated billing. One of the AWS accounts has purchased a Reserved Instance (RI) of a small instance size in the US-East-1a zone. All other AWS accounts are running instances of a small size in the same zone. What will happen in this case for the RI pricing?

- A. Only the account that has purchased the RI will get the advantage of RI pricing
- B. One instance of a small size and running in the US-East-1a zone of each AWS account will get the benefit of RI pricing
- C. Any single instance from all the three accounts can get the benefit of AWS RI pricing if they are running in the same zone and are of the same size
- D. If there are more than one instances of a small size running across multiple accounts in the same zone no one will get the benefit of RI

**Answer:** C

**Explanation:**

AWS consolidated billing enables the organization to consolidate payments for multiple Amazon Web Services (AWS) accounts within a single organization by making a single paying account. For billing purposes, consolidated billing treats all the accounts on the consolidated bill as one account. This means that all accounts on a consolidated bill can receive the hourly cost benefit of the Amazon EC2 Reserved Instances purchased by any other account. In this case only one Reserved Instance has been purchased by one account. Thus, only a single instance from any of the accounts will get the advantage of RI. AWS will implement the blended rate for each instance if more than one instance is running concurrently.

#### NEW QUESTION 81

- (Topic 2)

An organization (Account ID 123412341234) has attached the below mentioned IAM policy to a user. What does this policy statement entitle the user to perform?

```
"Statement": [
{
  "Sid": "AllowUsersAllActionsForCredentials",
  "Effect": "Allow",
  "Action": [
    "iam:*AccessKey*",
  ],
  "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
}]
```

- A. 0
- B. 0
- C. 0
- D. 0

**Answer:** A

**Explanation:**

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the organization (Account ID 123412341234) wants some of their users to manage keys (access and secret access keys) of all IAM users, the organization should set the below mentioned policy which entitles the IAM user to modify keys of all IAM users with CLI, SDK or API.

```
"Statement": [
{
  "Sid": "AllowUsersAllActionsForCredentials",
  "Effect": "Allow",
  "Action": [
    "iam:*AccessKey*",
  ],
  "Resource": ["arn:aws:iam:: 123412341234:user/${aws:username}"]
}]
```

#### NEW QUESTION 85

- (Topic 2)

A user has setup a web application on EC2. The user is generating a log of the application performance at every second. There are multiple entries for each second. If the user wants to send that data to CloudWatch every minute, what should he do?

- A. The user should send only the data of the 60th second as CloudWatch will map the receive data timezone with the sent data timezone
- B. It is not possible to send the custom metric to CloudWatch every minute
- C. Give CloudWatch the Min, Max, Sum, and SampleCount of a number of every minute

D. Calculate the average of one minute and send the data to CloudWatch

**Answer:** C

**Explanation:**

Amazon CloudWatch aggregates statistics according to the period length that the user has specified while getting data from CloudWatch. The user can publish as many data points as he wants with the same or similar time stamps. CloudWatch aggregates them by the period length when the user calls get statistics about those data points. CloudWatch records the average (sum of all items divided by the number of items. of the values received for every 1-minute period, as well as the number of samples, maximum value, and minimum value for the same time period. CloudWatch will aggregate all the data which have time stamps within a one-minute period.

#### NEW QUESTION 88

- (Topic 2)

A user has launched an EBS backed instance. The user started the instance at 9 AM in the morning. Between 9 AM to 10 AM, the user is testing some script. Thus, he stopped the instance twice and restarted it. In the same hour the user rebooted the instance once. For how many instance hours will AWS charge the user?

- A. 3 hours
- B. 4 hours
- C. 2 hours
- D. 1 hour

**Answer:** A

**Explanation:**

A user can stop/start or reboot an EC2 instance using the AWS console, the Amazon EC2 CLI or the Amazon EC2 API. Rebooting an instance is equivalent to rebooting an operating system. When the instance is rebooted AWS will not charge the user for the extra hours. In case the user stops the instance, AWS does not charge the running cost but charges only the EBS storage cost. If the user starts and stops the instance multiple times in a single hour, AWS will charge the user for every start and stop. In this case, since the instance was rebooted twice, it will cost the user for 3 instance hours.

#### NEW QUESTION 93

- (Topic 2)

A user is launching an EC2 instance in the US East region. Which of the below mentioned options is recommended by AWS with respect to the selection of the availability zone?

- A. Always select the US-East-1-a zone for HA
- B. Do not select the AZ; instead let AWS select the AZ
- C. The user can never select the availability zone while launching an instance
- D. Always select the AZ while launching an instance

**Answer:** B

**Explanation:**

When launching an instance with EC2, AWS recommends not to select the availability zone (AZ). AWS specifies that the default Availability Zone should be accepted. This is because it enables AWS to select the best Availability Zone based on the system health and available capacity. If the user launches additional instances, only then an Availability Zone should be specified. This is to specify the same or different AZ from the running instances.

#### NEW QUESTION 97

- (Topic 2)

An organization has created 50 IAM users. The organization has introduced a new policy which will change the access of an IAM user. How can the organization implement this effectively so that there is no need to apply the policy at the individual user level?

- A. Use the IAM groups and add users as per their role to different groups and apply policy to group
- B. The user can create a policy and apply it to multiple users in a single go with the AWS CLI
- C. Add each user to the IAM role as per their organization role to achieve effective policy setup
- D. Use the IAM role and implement access at the role level

**Answer:** A

**Explanation:**

With AWS IAM, a group is a collection of IAM users. A group allows the user to specify permissions for a collection of users, which can make it easier to manage the permissions for those users. A group helps an organization manage access in a better way; instead of applying at the individual level, the organization can apply at the group level which is applicable to all the users who are a part of that group.

#### NEW QUESTION 98

- (Topic 2)

An organization, which has the AWS account ID as 999988887777, has created 50 IAM users. All the users are added to the same group cloudacademy. If the organization has enabled that each IAM user can login with the AWS console, which AWS login URL will the IAM users use?

- A. [https:// 999988887777.signin.aws.amazon.com/console/](https://999988887777.signin.aws.amazon.com/console/)
- B. [https:// signin.aws.amazon.com/cloudacademy/](https://signin.aws.amazon.com/cloudacademy/)
- C. [https:// cloudacademy.signin.aws.amazon.com/999988887777/console/](https://cloudacademy.signin.aws.amazon.com/999988887777/console/)
- D. [https:// 999988887777.aws.amazon.com/ cloudacademy/](https://999988887777.aws.amazon.com/cloudacademy/)

**Answer:** A

**Explanation:**

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. Once the organization has created the IAM users, they will have a separate AWS console URL to login to the AWS console. The console login URL for the IAM user will be [https:// AWS\\_Account\\_ID.signin.aws.amazon.com/console/](https://AWS_Account_ID.signin.aws.amazon.com/console/). It uses only the AWS account ID and does not depend on the group or user ID.

#### NEW QUESTION 101

- (Topic 2)

An organization has created 50 IAM users. The organization wants that each user can change their password but cannot change their access keys. How can the organization achieve this?

- A. The organization has to create a special password policy and attach it to each user
- B. The root account owner has to use CLI which forces each IAM user to change their password on first login
- C. By default each IAM user can modify their passwords
- D. The root account owner can set the policy from the IAM console under the password policy screen

**Answer:** D

**Explanation:**

With AWS IAM, organizations can use the AWS Management Console to display, create, change or delete a password policy. As a part of managing the password policy, the user can enable all users to manage their own passwords. If the user has selected the option which allows the IAM users to modify their password, he does not need to set a separate policy for the users. This option in the AWS console allows changing only the password.

#### NEW QUESTION 102

- (Topic 2)

A user has a refrigerator plant. The user is measuring the temperature of the plant every 15 minutes. If the user wants to send the data to CloudWatch to view the data visually, which of the below mentioned statements is true with respect to the information given above?

- A. The user needs to use AWS CLI or API to upload the data
- B. The user can use the AWS Import Export facility to import data to CloudWatch
- C. The user will upload data from the AWS console
- D. The user cannot upload data to CloudWatch since it is not an AWS service metric

**Answer:** A

**Explanation:**

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. While sending the data the user has to include the metric name, namespace and timezone as part of the request.

#### NEW QUESTION 104

- (Topic 2)

A user has launched an EBS backed EC2 instance. What will be the difference while performing the restart or stop/start options on that instance?

- A. For restart it does not charge for an extra hour, while every stop/start it will be charged as a separate hour
- B. Every restart is charged by AWS as a separate hour, while multiple start/stop actions during a single hour will be counted as a single hour
- C. For every restart or start/stop it will be charged as a separate hour
- D. For restart it charges extra only once, while for every stop/start it will be charged as a separate hour

**Answer:** A

**Explanation:**

For an EC2 instance launched with an EBS backed AMI, each time the instance state is changed from stop to start/ running, AWS charges a full instance hour, even if these transitions happen multiple times within a single hour. Anyway, rebooting an instance AWS does not charge a new instance billing hour.

#### NEW QUESTION 107

- (Topic 3)

What would happen to an RDS (Relational Database Service) multi-Availability Zone deployment if the primary DB instance fails?

- A. The IP of the primary DB Instance is switched to the standby DB Instance
- B. A new DB instance is created in the standby availability zone
- C. The canonical name record (CNAME) is changed from primary to standby
- D. The RDS (Relational Database Service) DB instance reboot

**Answer:** D

**Explanation:**

Reference:  
[http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER\\_RebootInstance.html](http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_RebootInstance.html)

#### NEW QUESTION 111

- (Topic 3)

A user has configured ELB with Auto Scaling. The user suspended the Auto Scaling terminate process only for a while. What will happen to the availability zone

rebalancing process (AZRebalance. during this period?

- A. Auto Scaling will not launch or terminate any instances
- B. Auto Scaling will allow the instances to grow more than the maximum size
- C. Auto Scaling will keep launching instances till the maximum instance size
- D. It is not possible to suspend the terminate process while keeping the launch active

**Answer:** B

**Explanation:**

Auto Scaling performs various processes, such as Launch, Terminate, Availability Zone Rebalance (AZRebalance. etc. The AZRebalance process type seeks to maintain a balanced number of instances across Availability Zones within a region. If the user suspends the Terminate process, the AZRebalance process can cause the Auto Scaling group to grow up to ten percent larger than the maximum size. This is because Auto Scaling allows groups to temporarily grow larger than the maximum size during rebalancing activities. If Auto Scaling cannot terminate instances, the Auto Scaling group could remain up to ten percent larger than the maximum size until the user resumes the Terminate process type.

#### NEW QUESTION 114

- (Topic 3)

A user is trying to understand the CloudWatch metrics for the AWS services. It is required that the user should first understand the namespace for the AWS services. Which of the below mentioned is not a valid namespace for the AWS services?

- A. AWS/StorageGateway
- B. AWS/CloudTrail
- C. AWS/ElastiCache
- D. AWS/SWF

**Answer:** B

**Explanation:**

Amazon CloudWatch is basically a metrics repository. The AWS product puts metrics into this repository, and the user can retrieve the data or statistics based on those metrics. To distinguish the data for each service, the CloudWatch metric has a namespace. Namespaces are containers for metrics. All AWS services that provide the Amazon CloudWatch data use a namespace string, beginning with "AWS/". All the services which are supported by CloudWatch will have some namespace. CloudWatch does not monitor CloudTrail. Thus, the namespace "AWS/CloudTrail" is incorrect.

#### NEW QUESTION 118

- (Topic 3)

An organization has created a Queue named "modularqueue" with SQS. The organization is not performing any operations such as SendMessage, ReceiveMessage, DeleteMessage, GetQueueAttributes, SetQueueAttributes, AddPermission, and RemovePermission on the queue. What can happen in this scenario?

- A. AWS SQS sends notification after 15 days for inactivity on queue
- B. AWS SQS can delete queue after 30 days without notification
- C. AWS SQS marks queue inactive after 30 days
- D. AWS SQS notifies the user after 2 weeks and deletes the queue after 3 week

**Answer:** B

**Explanation:**

Amazon SQS can delete a queue without notification if one of the following actions hasn't been performed on it for 30 consecutive days: SendMessage, ReceiveMessage, DeleteMessage, GetQueueAttributes, SetQueueAttributes, AddPermission, and RemovePermission.

#### NEW QUESTION 121

- (Topic 3)

The CFO of a company wants to allow one of his employees to view only the AWS usage report page. Which of the below mentioned IAM policy statements allows the user to have access to the AWS usage report page?

- A. "Effect": "Allow", "Action": ["Describe"], "Resource": "Billing"
- B. "Effect": "Allow", "Action": ["AccountUsage"], "Resource": ""
- C. "Effect": "Allow", "Action": ["aws-portal:ViewUsage"], "Resource": ""
- D. "Effect": "Allow", "Action": ["aws-portal: ViewBilling"], "Resource": ""

**Answer:** C

**Explanation:**

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. If the CFO wants to allow only AWS usage report page access, the policy for that IAM user will be as given below:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "aws-portal:ViewUsage"
      ],
      "Resource": ""
    }
  ]
}
```



```
}  
}
```

**NEW QUESTION 126**

- (Topic 3)

A sys admin has enabled logging on ELB. Which of the below mentioned fields will not be a part of the log file name?

- A. Load Balancer IP
- B. EC2 instance IP
- C. S3 bucket name
- D. Random string

**Answer:** B

**Explanation:**

Elastic Load Balancing access logs capture detailed information for all the requests made to the load balancer. Elastic Load Balancing publishes a log file from each load balancer node at the interval that the user has specified. The load balancer can deliver multiple logs for the same period. Elastic Load Balancing creates log file names in the following format: "{Bucket}/{Prefix}/AWSLogs/{AWS AccountID}/elasticloadbalancing/{Region}/{Year}/{Month}/{Day}/{AWS Account ID}\_elasticloadbalancing\_{Region}\_{Load Balancer Name}\_{End Time}\_{Load Balancer IP}\_{Random String}.log"

**NEW QUESTION 127**

- (Topic 3)

When an EC2 instance that is backed by an S3-Dased AML is terminated, what happens to the data on the root volume?

- A. Data is automatically deleted
- B. Data is automatically saved as an EBS snapsho
- C. Data is unavailable until the instance is restarted
- D. Data is automatically saved as an EBS volum

**Answer:** A

**NEW QUESTION 132**

- (Topic 3)

You have a business-to-business web application running in a VPC consisting of an Elastic Load Balancer (ELB), web servers, application servers and a database. Your web application should only accept traffic from pre-defined customer IP addresses.

Which two options meet this security requirement? Choose 2 answers A. Configure web server VPC security groups to allow traffic from your customers' IPs

- A. Configure your web servers to filter traffic based on the ELB's "X-forwarded-for" header
- B. Configure ELB security groups to allow traffic from your customers' IPs and deny all outbound traffic
- C. Configure a VPC NACL to allow web traffic from your customers' IPs and deny all outbound traffic

**Answer:** AB

**NEW QUESTION 133**

- (Topic 3)

An organization has configured two single availability zones. The Auto Scaling groups are configured in separate zones. The user wants to merge the groups such that one group spans across multiple zones. How can the user configure this?

- A. Run the command as-join-auto-scaling-group to join the two groups
- B. Run the command as-update-auto-scaling-group to configure one group to span across zones and delete the other group
- C. Run the command as-copy-auto-scaling-group to join the two groups
- D. Run the command as-merge-auto-scaling-group to merge the groups

**Answer:** B

**Explanation:**

If the user has configured two separate single availability zone Auto Scaling groups and wants to merge them then he should update one of the groups and delete the other one. While updating the first group it is recommended that the user should increase the size of the minimum, maximum and desired capacity as a summation of both the groups.

**NEW QUESTION 135**

- (Topic 3)

A user has launched an RDS MySQL DB with the Multi AZ feature. The user has scheduled the scaling of instance storage during maintenance window. What is the correct order of events during maintenance window?

- Perform maintenance on standby
- Promote standby to primary
- Perform maintenance on original primary
- Promote original master back as primary

- A. 1, 2, 3, 4
- B. 1, 2, 3
- C. 2, 3, 1, 4

**Answer:** B

**Explanation:**



Running MySQL on the RDS DB instance as a Multi-AZ deployment can help the user reduce the impact of a maintenance event, as the Amazon will conduct maintenance by following the steps in the below mentioned order: Perform maintenance on standby Promote standby to primary Perform maintenance on original primary, which becomes the new standby.

**NEW QUESTION 136**

- (Topic 3)

A user has setup a CloudWatch alarm on the EC2 instance for CPU utilization. The user has setup to receive a notification on email when the CPU utilization is higher than 60%. The user is running a virus scan on the same instance at a particular time. The user wants to avoid receiving an email at this time. What should the user do?

- A. Remove the alarm
- B. Disable the alarm for a while using CLI
- C. Modify the CPU utilization by removing the email alert
- D. Disable the alarm for a while using the console

**Answer:** B

**Explanation:**

Amazon CloudWatch alarm watches a single metric over a time period that the user specifies and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. When the user has setup an alarm and it is known that for some unavoidable event the status may change to Alarm, the user can disable the alarm using the DisableAlarmActions API or from the command line `mon-disable-alarm-actions`.

**NEW QUESTION 138**

- (Topic 3)

A user has created a VPC with the public and private subnets using the VPC wizard. The VPC has CIDR 20.0.0.0/16. The public subnet uses CIDR 20.0.1.0/24. The user is planning to host a web server in the public subnet (port 80) and a DB server in the private subnet (port 3306). The user is configuring a security group for the public subnet (WebSecGrp) and the private subnet (DBSecGrp). Which of the below mentioned entries is required in the private subnet database security group (DBSecGrp)?

- A. Allow Inbound on port 3306 for Source Web Server Security Group (WebSecGr)
- B. Allow Inbound on port 3306 from source 20.0.0.0/16
- C. Allow Outbound on port 3306 for Destination Web Server Security Group (WebSecGr)
- D. Allow Outbound on port 80 for Destination NAT Instance IP

**Answer:** A

**Explanation:**

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet to host the web server and DB server respectively, the user should configure that the instances in the private subnet can receive inbound traffic from the public subnet on the DB port. Thus, configure port 3306 in Inbound with the source as the Web Server Security Group (WebSecGrp). The user should configure ports 80 and 443 for Destination 0.0.0.0/0 as the route table directs traffic to the NAT instance from the private subnet.

**NEW QUESTION 142**

- (Topic 3)

An organization has configured Auto Scaling with ELB. One of the instance health check returns the status as Impaired to Auto Scaling. What will Auto Scaling do in this scenario?

- A. Perform a health check until cool down before declaring that the instance has failed
- B. Terminate the instance and launch a new instance
- C. Notify the user using SNS for the failed state
- D. Notify ELB to stop sending traffic to the impaired instance

**Answer:** B

**Explanation:**

The Auto Scaling group determines the health state of each instance periodically by checking the results of the Amazon EC2 instance status checks. If the instance status description shows any other state other than "running" or the system status description shows impaired, Auto Scaling considers the instance to be unhealthy. Thus, it terminates the instance and launches a replacement.

**NEW QUESTION 143**

- (Topic 3)

A user wants to upload a complete folder to AWS S3 using the S3 Management console. How can the user perform this activity?

- A. Just drag and drop the folder using the flash tool provided by S3
- B. Use the Enable Enhanced Folder option from the S3 console while uploading objects
- C. The user cannot upload the whole folder in one go with the S3 management console
- D. Use the Enable Enhanced Uploader option from the S3 console while uploading objects

**Answer:** D

**Explanation:**

AWS S3 provides a console to upload objects to a bucket. The user can use the file upload screen to upload the whole folder in one go by clicking on the Enable Enhanced Uploader option. When the user uploads a folder, Amazon S3 uploads all the files and subfolders from the specified folder to the user's bucket. It then assigns a key value that is a combination of the uploaded file name and the folder name.

**NEW QUESTION 147**

- (Topic 3)

A user wants to find the particular error that occurred on a certain date in the AWS MySQL RDS DB. Which of the below mentioned activities may help the user to get the data easily?

- A. It is not possible to get the log files for MySQL RDS
- B. Find all the transaction logs and query on those records
- C. Direct the logs to the DB table and then query that table
- D. Download the log file to DynamoDB and search for the record

**Answer:** C

**Explanation:**

The user can view, download, and watch the database logs using the Amazon RDS console, the Command Line Interface (CLI) or the Amazon RDS API. For the MySQL RDS, the user can view the error log, slow query log, and general logs. The user can also view the MySQL logs easily by directing the logs to a database table in the main database and querying that table.

**NEW QUESTION 150**

- (Topic 3)

Which services allow the customer to retain run administrative privileges or the underlying EC2 instances? Choose 2 answers

- A. AWS Elastic Beanstalk
- B. Amazon Elastic Map Reduce
- C. Elastic Load Balancing
- D. Amazon Relational Database Service
- E. Amazon Elasti Cache

**Answer:** AB

**NEW QUESTION 151**

- (Topic 3)

A user has configured Auto Scaling with 3 instances. The user had created a new AMI after updating one of the instances. If the user wants to terminate two specific instances to ensure that Auto Scaling launches an instances with the new launch configuration, which command should he run?

- A. `as-delete-instance-in-auto-scaling-group <Instance ID> --no-decrement-desired-capacity`
- B. `as-terminate-instance-in-auto-scaling-group <Instance ID> --update-desired-capacity`
- C. `as-terminate-instance-in-auto-scaling-group <Instance ID> --decrement-desired-capacity`
- D. `as-terminate-instance-in-auto-scaling-group <Instance ID> --no-decrement-desired-capacity`

**Answer:** D

**Explanation:**

The Auto Scaling command `as-terminate-instance-in-auto-scaling-group <Instance ID>` will terminate the specific instance ID. The user is required to specify the parameter `--no-decrement-desired-capacity` to ensure that it launches a new instance from the launch config after terminating the instance. If the user specifies the parameter `--decrement-desired-capacity` then Auto Scaling will terminate the instance and decrease the desired capacity by 1.

**NEW QUESTION 153**

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. The user has not launched any instance manually and is trying to delete the VPC. What will happen in this scenario?

- A. It will not allow to delete the VPC as it has subnets with route tables
- B. It will not allow to delete the VPC since it has a running route instance
- C. It will terminate the VPC along with all the instances launched by the wizard
- D. It will not allow to delete the VPC since it has a running NAT instance

**Answer:** D

**Explanation:**

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the Internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance with an elastic IP. If the user is trying to delete the VPC it will not allow as the NAT instance is still running.

**NEW QUESTION 155**

- (Topic 3)

A user runs the command `dd if=/dev/zero of=/dev/xvdfbs=1M` on a fresh blank EBS volume attached to a Linux instance. Which of the below mentioned activities is the user performing with the command given above?

- A. Creating a file system on the EBS volume
- B. Mounting the device to the instance
- C. Pre warming the EBS volume
- D. Formatting the EBS volume

**Answer:** C

**Explanation:**

When the user creates a new EBS volume and is trying to access it for the first time it will encounter reduced IOPS due to wiping or initiating of the block storage. To avoid this as well as achieve the best performance it is required to pre warm the EBS volume. For a blank volume attached with a Linux OS, the “dd” command is used to write to all the blocks on the device. In the command “dd if=/dev/zero of=/dev/xvdfbs=1M” the parameter “if =import file” should be set to one of the Linux virtual devices, such as /dev/zero. The “of=output file” parameter should be set to the drive that the user wishes to warm. The “bs” parameter sets the block size of the write operation; for optimal performance, this should be set to 1 MB.

**NEW QUESTION 157**

- (Topic 3)

A user is trying to setup a security policy for ELB. The user wants ELB to meet the cipher supported by the client by configuring the server order preference in ELB security policy. Which of the below mentioned preconfigured policies supports this feature?

- A. ELBSecurity Policy-2014-01
- B. ELBSecurity Policy-2011-08
- C. ELBDefault Negotiation Policy
- D. ELBSample- OpenSSLDefault Cipher Policy

**Answer:** A

**Explanation:**

Elastic Load Balancing uses a Secure Socket Layer (SSL) negotiation configuration which is known as a Security Policy. It is used to negotiate the SSL connections between a client and the load balancer. If the load balancer is configured to support the Server Order Preference, then the load balancer gets to select the first cipher in its list that matches any one of the ciphers in the client's list. When the user verifies the preconfigured policies supported by ELB, the policy “ELBSecurity Policy-2014-01” supports server order preference.

**NEW QUESTION 160**

- (Topic 3)

A user is planning to use AWS services for his web application. If the user is trying to set up his own billing management system for AWS, how can he configure it?

- A. Set up programmatic billing acces
- B. Download and parse the bill as per the requirement
- C. It is not possible for the user to create his own billing management service with AWS
- D. Enable the AWS CloudWatch alarm which will provide APIs to download the alarm data
- E. Use AWS billing APIs to download the usage report of each service from the AWS billing console

**Answer:** A

**Explanation:**

AWS provides an option to have programmatic access to billing. Programmatic Billing Access leverages the existing Amazon Simple Storage Service (Amazon S3) APIs. Thus, the user can build applications that reference his billing data from a CSV (comma-separated value) file stored in an Amazon S3 bucket. AWS will upload the bill to the bucket every few hours and the user can download the bill CSV from the bucket, parse it and create a billing system as per the requirement.

**NEW QUESTION 164**

- (Topic 3)

A user is creating a Cloudformation stack. Which of the below mentioned limitations does not hold true for Cloudformation?

- A. One account by default is limited to 100 templates
- B. The user can use 60 parameters and 60 outputs in a single template
- C. The template, parameter, output, and resource description fields are limited to 4096 characters
- D. One account by default is limited to 20 stacks

**Answer:** A

**Explanation:**

AWS Cloudformation is an application management tool which provides application modelling, deployment, configuration, management and related activities. The limitations given below apply to the Cloudformation template and stack. There are no limits to the number of templates but each AWS CloudFormation account is limited to a maximum of 20 stacks by default. The Template, Parameter, Output, and Resource description fields are limited to 4096 characters. The user can include up to 60 parameters and 60 outputs in a template.

**NEW QUESTION 165**

- (Topic 3)

An organization is planning to create a user with IAM. They are trying to understand the limitations of IAM so that they can plan accordingly. Which of the below mentioned statements is not true with respect to the limitations of IAM?

- A. One IAM user can be a part of a maximum of 5 groups
- B. The organization can create 100 groups per AWS account
- C. One AWS account can have a maximum of 5000 IAM users
- D. One AWS account can have 250 roles

**Answer:** A

**Explanation:**

AWS Identity and Access Management is a web service which allows organizations to manage users and user permissions for various AWS services. The default maximums for each of the IAM entities is given below: Groups per AWS account: 100 Users per AWS account: 5000 Roles per AWS account: 250 Number of groups per user: 10 (that is, one user can be part of these many groups).

**NEW QUESTION 168**

- (Topic 3)

A user has launched an EC2 instance from an instance store backed AMI. If the user restarts the instance, what will happen to the ephemeral storage data?

- A. All the data will be erased but the ephemeral storage will stay connected
- B. All data will be erased and the ephemeral storage is released
- C. It is not possible to restart an instance launched from an instance store backed AMI
- D. The data is preserved

**Answer:** D

**Explanation:**

A user can reboot an EC2 instance using the AWS console, the Amazon EC2 CLI or the Amazon EC2 API. Rebooting an instance is equivalent to rebooting an operating system. However, it is recommended that the user use Amazon EC2 to reboot the instance instead of running the operating system reboot command from the instance. When an instance launched from an instance store backed AMI is rebooted all the ephemeral storage data is still preserved.

**NEW QUESTION 170**

- (Topic 3)

How can you secure data at rest on an EBS volume?

- A. Encrypt the volume using the S3 server-side encryption service
- B. Attach the volume to an instance using EC2's SSL interface
- C. Create an IAM policy that restricts read and write access to the volume
- D. Write the data randomly instead of sequentially
- E. Use an encrypted file system on top of the EBS volume

**Answer:** C

**Explanation:**

Reference:

[http://docs.aws.amazon.com/IAM/latest/UserGuide/policies\\_examples.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/policies_examples.html)

**NEW QUESTION 171**

- (Topic 3)

A user is trying to understand the detailed CloudWatch monitoring concept. Which of the below mentioned services provides detailed monitoring with CloudWatch without charging the user extra?

- A. AWS Auto Scaling
- B. AWS Route 53
- C. AWS EMR
- D. AWS SNS

**Answer:** B

**Explanation:**

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. Services, such as RDS, ELB, OpsWorks, and Route 53 can provide the monitoring data every minute without charging the user.

**NEW QUESTION 174**

- (Topic 3)

An application you maintain consists of multiple EC2 instances in a default tenancy VPC. This application has undergone an internal audit and has been determined to require dedicated hardware for one instance. Your compliance team has given you a week to move this instance to single-tenant hardware. Which process will have minimal impact on your application while complying with this requirement?

- A. Create a new VPC with tenancy=dedicated and migrate to the new VPC
- B. Use ec2-reboot-instances command line and set the parameter "dedicated=true"
- C. Right click on the instance, select properties and check the box for dedicated tenancy
- D. Stop the instance, create an AMI, launch a new instance with tenancy=dedicated, and terminate the old instance

**Answer:** A

**Explanation:**

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/CommandLineReference/ApiReference-cmd-CreateVpc.html>

**NEW QUESTION 177**

- (Topic 3)

When you put objects in Amazon S3, what is the indication that an object was successfully stored?



- A. Each S3 account has a special bucket named\_s3\_log
- B. Success codes are written to this bucket with a timestamp and checksu
- C. A success code is inserted into the S3 object metadat
- D. A HTTP 200 result code and MD5 checksum, taken together, indicate that the operation was successfu
- E. Amazon S3 is engineered for 99.999999999% durabilit
- F. Therefore there is no need to confirm that data was inserte

**Answer: B**

**Explanation:**

Reference:  
<http://docs.aws.amazon.com/AmazonS3/latest/API/RESTObjectPUT.html>

#### NEW QUESTION 181

- (Topic 3)

A user has created a subnet in VPC and launched an EC2 instance within it. The user has not selected the option to assign the IP address while launching the instance. The user has 3 elastic IPs and is trying to assign one of the Elastic IPs to the VPC instance from the console. The console does not show any instance in the IP assignment screen. What is a possible reason that the instance is unavailable in the assigned IP console?

- A. The IP address may be attached to one of the instances
- B. The IP address belongs to a different zone than the subnet zone
- C. The user has not created an internet gateway
- D. The IP addresses belong to EC2 Classic; so they cannot be assigned to VPC

**Answer: D**

**Explanation:**

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. When the user is launching an instance he needs to select an option which attaches a public IP to the instance. If the user has not selected the option to attach the public IP then it will only have a private IP when launched. If the user wants to connect to an instance from the internet he should create an elastic IP with VPC. If the elastic IP is a part of EC2 Classic it cannot be assigned to a VPC instance.

#### NEW QUESTION 184

- (Topic 3)

A user is trying to send custom metrics to CloudWatch using the PutMetricData APIs. Which of the below mentioned points should the user needs to take care while sending the data to CloudWatch?

- A. The size of a request is limited to 8KB for HTTP GET requests and 40KB for HTTP POST requests
- B. The size of a request is limited to 128KB for HTTP GET requests and 64KB for HTTP POST requests
- C. The size of a request is limited to 40KB for HTTP GET requests and 8KB for HTTP POST requests
- D. The size of a request is limited to 16KB for HTTP GET requests and 80KB for HTTP POST requests

**Answer: A**

**Explanation:**

With AWS CloudWatch, the user can publish data points for a metric that share not only the same time stamp, but also the same namespace and dimensions. CloudWatch can accept multiple data points in the same PutMetricData call with the same time stamp. The only thing that the user needs to take care of is that the size of a PutMetricData request is limited to 8KB for HTTP GET requests and 40KB for HTTP POST requests.

#### NEW QUESTION 187

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC wizard. Which of the below mentioned statements is not true in this scenario?

- A. The VPC will create a routing instance and attach it with a public subnet
- B. The VPC will create two subnets
- C. The VPC will create one internet gateway and attach it to VPC
- D. The VPC will launch one NAT instance with an elastic IP

**Answer: A**

**Explanation:**

A user can create a subnet with VPC and launch instances inside that subnet. If the user has created a public private subnet, the instances in the public subnet can receive inbound traffic directly from the internet, whereas the instances in the private subnet cannot. If these subnets are created with Wizard, AWS will create a NAT instance with an elastic IP. Wizard will also create two subnets with route tables. It will also create an internet gateway and attach it to the VPC.

#### NEW QUESTION 190

- (Topic 3)

A user is receiving a notification from the RDS DB whenever there is a change in the DB security group. The user does not want to receive these notifications for only a month. Thus, he does not want to delete the notification. How can the user configure this?

- A. Change the Disable button for notification to "Yes" in the RDS console
- B. Set the send mail flag to false in the DB event notification console
- C. The only option is to delete the notification from the console
- D. Change the Enable button for notification to "No" in the RDS console

**Answer: D**



**Explanation:**

Amazon RDS uses the Amazon Simple Notification Service to provide a notification when an Amazon RDS event occurs. Event notifications are sent to the addresses that the user has provided while creating the subscription. The user can easily turn off the notification without deleting a subscription by setting the Enabled radio button to No in the Amazon RDS console or by setting the Enabled parameter to false using the CLI or Amazon RDS API.

**NEW QUESTION 193**

- (Topic 3)

A user runs the command “dd if=/dev/xvdf of=/dev/null bs=1M” on an EBS volume created from a snapshot and attached to a Linux instance. Which of the below mentioned activities is the user performing with the step given above?

- A. Pre warming the EBS volume
- B. Initiating the device to mount on the EBS volume
- C. Formatting the volume
- D. Copying the data from a snapshot to the device

**Answer:** A

**Explanation:**

When the user creates an EBS volume and is trying to access it for the first time it will encounter reduced IOPS due to wiping or initiating of the block storage. To avoid this as well as achieve the best performance it is required to pre warm the EBS volume. For a volume created from a snapshot and attached with a Linux OS, the “dd” command pre warms the existing data on EBS and any restored snapshots of volumes that have been previously fully pre warmed. This command maintains incremental snapshots; however, because this operation is read-only, it does not pre warm unused space that has never been written to on the original volume. In the command “dd if=/dev/xvdf of=/dev/null bs=1M” , the parameter “if=input file” should be set to the drive that the user wishes to warm. The “of=output file” parameter should be set to the Linux null virtual device, /dev/null. The “bs” parameter sets the block size of the read operation; for optimal performance, this should be set to 1 MB.

**NEW QUESTION 194**

- (Topic 3)

A user is measuring the CPU utilization of a private data centre machine every minute. The machine provides the aggregate of data every hour, such as Sum of data”, “Min value”, “Max value, and “Number of Data points”.

The user wants to send these values to CloudWatch. How can the user achieve this?

- A. Send the data using the put-metric-data command with the aggregate-values parameter
- B. Send the data using the put-metric-data command with the average-values parameter
- C. Send the data using the put-metric-data command with the statistic-values parameter
- D. Send the data using the put-metric-data command with the aggregate –data parameter

**Answer:** C

**Explanation:**

AWS CloudWatch supports the custom metrics. The user can always capture the custom data and upload the data to CloudWatch using CLI or APIs. The user can publish the data to CloudWatch as single data points or as an aggregated set of data points called a statistic set using the command put-metric-data. When sending the aggregate data, the user needs to send it with the parameter statistic-values: `awscloudwatch put-metric-data --metric-name <Name> --namespace <Custom namespace> --timestamp <UTC Format> --statistic-values Sum=XX,Minimum=YY,Maximum=AA,SampleCount=BB --unit Milliseconds`

**NEW QUESTION 195**

- (Topic 3)

A user has created a VPC with public and private subnets using the VPC Wizard. The VPC has CIDR 20.0.0.0/16. The private subnet uses CIDR 20.0.0.0/24. Which of the below mentioned entries are required in the main route table to allow the instances in VPC to communicate with each other?

- A. Destination : 20.0.0.0/24 and Target : VPC
- B. Destination : 20.0.0.0/16 and Target : ALL
- C. Destination : 20.0.0.0/0 and Target : ALL
- D. Destination : 20.0.0.0/24 and Target : Local

**Answer:** D

**NEW QUESTION 198**

- (Topic 3)

An organization has configured Auto Scaling with ELB. There is a memory issue in the application which is causing CPU utilization to go above 90%. The higher CPU usage triggers an event for Auto Scaling as per the scaling policy. If the user wants to find the root cause inside the application without triggering a scaling activity, how can he achieve this?

- A. Stop the scaling process until research is completed
- B. It is not possible to find the root cause from that instance without triggering scaling
- C. Delete Auto Scaling until research is completed
- D. Suspend the scaling process until research is completed

**Answer:** D

**Explanation:**

Auto Scaling allows the user to suspend and then resume one or more of the Auto Scaling processes in the Auto Scaling group. This is very useful when the user wants to investigate a configuration problem or some other issue, such as a memory leak with the web application and then make changes to the application, without triggering the Auto Scaling process.

**NEW QUESTION 199**

- (Topic 3)

George has launched three EC2 instances inside the US-East-1a zone with his AWS account. Ray has launched two EC2 instances in the US-East-1a zone with his AWS account. Which of the below entioned statements will help George and Ray understand the availability zone (AZ. concept better?

- A. The instances of George and Ray will be running in the same data centre
- B. All the instances of George and Ray can communicate over a private IP with a minimal cost
- C. All the instances of George and Ray can communicate over a private IP without any cost
- D. The US-East-1a region of George and Ray can be different availability zones

**Answer:** D

**Explanation:**

Each AWS region has multiple, isolated locations known as Availability Zones. To ensure that the AWS resources are distributed across the Availability Zones for a region, AWS independently maps the Availability Zones to identifiers for each account. In this case the Availability Zone US-East-1a where George's EC2 instances are running might not be the same location as the US-East-1a zone of Ray's EC2 instances. There is no way for the user to coordinate the Availability Zones between accounts.

**NEW QUESTION 200**

- (Topic 3)

A user has configured an ELB to distribute the traffic among multiple instances. The user instances are facing some issues due to the back-end servers. Which of the below mentioned CloudWatch metrics helps the user understand the issue with the instances?

- A. HTTPCode\_Backend\_3XX
- B. HTTPCode\_Backend\_4XX
- C. HTTPCode\_Backend\_2XX
- D. HTTPCode\_Backend\_5XX

**Answer:** D

**Explanation:**

CloudWatch is used to monitor AWS as well as the custom services. For ELB, CloudWatch provides various metrics including error code by ELB as well as by back-end servers (instances.. It gives data for the count of the number of HTTP response codes generated by the back-end instances. This metric does not include any response codes generated by the load balancer. These metrics are: The 2XX class status codes represents successful actions The 3XX class status code indicates that the user agent requires action The 4XX class status code represents client errors The 5XX class status code represents back-end server errors

**NEW QUESTION 204**

- (Topic 3)

A user has created a VPC with two subnets: one public and one private. The user is planning to run the patch update for the instances in the private subnet. How can the instances in the private subnet connect to theinternet?

- A. Use the internet gateway with a private IP
- B. Allow outbound traffic in the security group for port 80 to allow internet updates
- C. The private subnet can never connect to the internet
- D. Use NAT with an elastic IP

**Answer:** D

**Explanation:**

A Virtual Private Cloud (VPC. is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside that subnet. If the user has created two subnets (one private and one public., he would need a Network Address Translation (NAT. instance with the elastic IP address. This enables the instances in the private subnet to send requests to the internet (for example, to perform software updates..

**NEW QUESTION 205**

- (Topic 3)

How can software determine the public and private IP addresses of the Amazon EC2 instance that it is running on?

- A. Query the local instance metadat
- B. Query the appropriate Amazon CloudWatch metri
- C. Query the local instance userdat
- D. Use ipconfig or ifconfig comman

**Answer:** B

**NEW QUESTION 208**

- (Topic 3)

A user has launched multiple EC2 instances for the purpose of development and testing in the same region. The user wants to find the separate cost for the production and development instances. How can the user find the cost distribution?

- A. The user should download the activity report of the EC2 services as it has the instance ID wise data
- B. It is not possible to get the AWS cost usage data of single region instances separately
- C. The user should use Cost Distribution Metadata and AWS detailed billing
- D. The user should use Cost Allocation Tags and AWS billing reports

**Answer:** D

**Explanation:**

AWS provides cost allocation tags to categorize and track the AWS costs. When the user applies tags to his AWS resources (such as Amazon EC2 instances or Amazon S3 buckets.), AWS generates a cost allocation report as a comma-separated value (CSV file) with the usage and costs aggregated by those tags. The user can apply tags which represent business categories (such as cost centres, application names, or instance type – Production/Dev. to organize usage costs across multiple services.

#### NEW QUESTION 211

- (Topic 3)

A user has created a queue named “awsmodule” with SQS. One of the consumers of queue is down for 3 days and then becomes available. Will that component receive message from queue?

- A. Yes, since SQS by default stores message for 4 days
- B. No, since SQS by default stores message for 1 day only
- C. No, since SQS sends message to consumers who are available that time
- D. Yes, since SQS will not delete message until it is delivered to all consumers

**Answer:** A

**Explanation:**

SQS allows the user to move data between distributed components of applications so they can perform different tasks without losing messages or requiring each component to be always available. Queues retain messages for a set period of time. By default, a queue retains messages for four days. However, the user can configure a queue to retain messages for up to 14 days after the message has been sent.

#### NEW QUESTION 212

- (Topic 3)

A user has hosted an application on EC2 instances. The EC2 instances are configured with ELB and Auto Scaling. The application server session time out is 2 hours. The user wants to configure connection draining to ensure that all in-flight requests are supported by ELB even though the instance is being deregistered. What time out period should the user specify for connection draining?

- A. 5 minutes
- B. 1 hour
- C. 30 minutes
- D. 2 hours

**Answer:** B

#### NEW QUESTION 215

- (Topic 3)

A user is configuring the Multi AZ feature of an RDS DB. The user came to know that this RDS DB does not use the AWS technology, but uses server mirroring to achieve HA. Which DB is the user using right now?

- A. My SQL
- B. Oracle
- C. MS SQL
- D. PostgreSQL

**Answer:** C

**Explanation:**

Amazon RDS provides high availability and failover support for DB instances using Multi AZ deployments. In a Multi AZ deployment, Amazon RDS automatically provisions and maintains a synchronous standby replica in a different Availability Zone. Multi AZ deployments for Oracle, PostgreSQL, and MySQL DB instances use Amazon technology, while SQL Server (MS SQL) DB instances use SQL Server Mirroring.

#### NEW QUESTION 219

- (Topic 3)

A user is trying to pre-warm a blank EBS volume attached to a Linux instance. Which of the below mentioned steps should be performed by the user?

- A. There is no need to pre-warm an EBS volume
- B. Contact AWS support to pre-warm
- C. Unmount the volume before pre-warming
- D. Format the device

**Answer:** C

**Explanation:**

When the user creates a new EBS volume or restores a volume from the snapshot, the back-end storage blocks are immediately allocated to the user EBS. However, the first time when the user is trying to access a block of the storage, it is recommended to either be wiped from the new volumes or instantiated from the snapshot (for restored volumes) before the user can access the block. This preliminary action takes time and can cause a 5 to 50 percent loss of IOPS for the volume when the block is accessed for the first time. To avoid this it is required to pre warm the volume. Pre-warming an EBS volume on a Linux instance requires that the user should unmount the blank device first and then write all the blocks on the device using a command, such as “dd”.

#### NEW QUESTION 224

- (Topic 3)

A sysadmin has created the below mentioned policy on an S3 bucket named cloudacademy. What does this policy define?

```
"Statement": [{
  "Sid": "Stmt1388811069831",
  "Effect": "Allow",
  "Principal": { "AWS": "*" },
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket" ],
  "Resource": [ "arn:aws:s3:::cloudacademy" ]
}]
```

- A. It will make the cloudacademy bucket as well as all its objects as public
- B. It will allow everyone to view the ACL of the bucket
- C. It will give an error as no object is defined as part of the policy while the action defines the rule about the object
- D. It will make the cloudacademy bucket as public

**Answer: D**

**Explanation:**

A sysadmin can grant permission to the S3 objects or the buckets to any user or make objects public using the bucket policy and user policy. Both use the JSON-based access policy language. Generally if the user is defining the ACL on the bucket, the objects in the bucket do not inherit it and vice versa. The bucket policy can be defined at the bucket level which allows the objects as well as the bucket to be public with a single policy applied to that bucket. In the sample policy the action says “S3:ListBucket” for effect Allow on Resource arn:aws:s3:::cloudacademy. This will make the cloudacademy bucket public.

```
"Statement": [{
  "Sid": "Stmt1388811069831",
  "Effect": "Allow",
  "Principal": { "AWS": "*" },
  "Action": [ "s3:GetObjectAcl", "s3:ListBucket" ],
  "Resource": [ "arn:aws:s3:::cloudacademy" ]
}]
```

#### NEW QUESTION 229

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16 using the wizard. The user has created a public subnet CIDR (20.0.0.0/24. and VPN only subnets CIDR (20.0.1.0/24. along with the VPN gateway (vgw-12345. to connect to the user's data centre. The user's data centre has CIDR 172.28.0.0/12. The user has also setup a NAT instance (i-123456. to allow traffic to the internet from the VPN subnet. Which of the below mentioned options is not a valid entry for the main route table in this scenario?

- A. Destination: 20.0.1.0/24 and Target: i-12345
- B. Destination: 0.0.0.0/0 and Target: i-12345
- C. Destination: 172.28.0.0/12 and Target: vgw-12345
- D. Destination: 20.0.0.0/16 and Target: local

**Answer: A**

**Explanation:**

The user can create subnets as per the requirement within a VPC. If the user wants to connect VPC from his own data centre, he can setup a public and VPN only subnet which uses hardware VPN access to connect with his data centre. When the user has configured this setup with Wizard, it will create a virtual private gateway to route all traffic of the VPN subnet. If the user has setup a NAT instance to route all the internet requests then all requests to the internet should be routed to it. All requests to the organization's DC will be routed to the VPN gateway. Here are the valid entries for the main route table in this scenario: Destination: 0.0.0.0/0 & Target: i-12345 (To route all internet traffic to the NAT Instance. Destination: 172.28.0.0/12 & Target: vgw-12345 (To route all the organization's data centre traffic to the VPN gateway. Destination: 20.0.0.0/16 & Target: local (To allow local routing in VPC.

#### NEW QUESTION 233

- (Topic 3)

A user has created an Auto Scaling group using CLI. The user wants to enable CloudWatch detailed monitoring for that group. How can the user configure this?

- A. When the user sets an alarm on the Auto Scaling group, it automatically enables detail monitoring
- B. By default detailed monitoring is enabled for Auto Scaling
- C. Auto Scaling does not support detailed monitoring
- D. Enable detail monitoring from the AWS console

**Answer: B**

**Explanation:**

CloudWatch is used to monitor AWS as well as the custom services. It provides either basic or detailed monitoring for the supported AWS products. In basic monitoring, a service sends data points to CloudWatch every five minutes, while in detailed monitoring a service sends data points to CloudWatch every minute. To enable detailed instance monitoring for a new Auto Scaling group, the user does not need to take any extra steps. When the user creates an Auto Scaling launch config as the first step for creating an Auto Scaling group, each launch configuration contains a flag named InstanceMonitoring.Enabled. The default value of this flag is true. Thus, the user does not need to set this flag if he wants detailed monitoring.

#### NEW QUESTION 237

- (Topic 3)

A user has configured ELB with two EBS backed instances. The user has stopped the instances for 1 week to save costs. The user restarts the instances after 1 week. Which of the below mentioned statements will help the user to understand the ELB and instance registration better?

- A. There is no way to register the stopped instances with ELB

- B. The user cannot stop the instances if they are registered with ELB
- C. If the instances have the same Elastic IP assigned after reboot they will be registered with ELB
- D. The instances will automatically get registered with ELB

**Answer: C**

**Explanation:**

Elastic Load Balancing registers the user's load balancer with his EC2 instance using the associated IP address. When the instances are stopped and started back they will have a different IP address. Thus, they will not get registered with ELB unless the user manually registers them. If the instances are assigned the same Elastic IP after reboot they will automatically get registered with ELB.

**NEW QUESTION 239**

- (Topic 3)

A user has created a VPC with CIDR 20.0.0.0/16. The user has created one subnet with CIDR 20.0.0.0/16 by mistake. The user is trying to create another subnet of CIDR 20.0.0.1/24. How can the user create the second subnet?

- A. There is no need to update the subnet as VPC automatically adjusts the CIDR of the first subnet based on the second subnet's CIDR
- B. The user can modify the first subnet CIDR from the console
- C. It is not possible to create a second subnet as one subnet with the same CIDR as the VPC has been created
- D. The user can modify the first subnet CIDR with AWS CLI

**Answer: D**

**Explanation:**

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances inside the subnet. The user can create a subnet with the same size of VPC. However, he cannot create any other subnet since the CIDR of the second subnet will conflict with the first subnet. The user cannot modify the CIDR of a subnet once it is created. Thus, in this case if required, the user has to delete the subnet and create new subnets.

**NEW QUESTION 242**

.....



## Thank You for Trying Our Product

### We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### AWS-SysOps Practice Exam Features:

- \* AWS-SysOps Questions and Answers Updated Frequently
- \* AWS-SysOps Practice Questions Verified by Expert Senior Certified Staff
- \* AWS-SysOps Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* AWS-SysOps Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
**[Order The AWS-SysOps Practice Test Here](#)**