

Amazon

Exam Questions AWS-Certified-Developer-Associate

Amazon AWS Certified Developer - Associate



NEW QUESTION 1

Which one of the following statements is NOT an advantage of DyanamoDB being built on Solid State Drives:

- A. serve high-scale request workloads
- B. low request pricing
- C. high I/O performance of WebApp on EC2 instance
- D. low-latency response times

Answer: C

Explanation:

In DynamoDB, SSDs help achieve design goals of predictable low-latency response times for storing and accessing data at any scale. The high I/O performance of SSDs also enables to serve high-scale request workloads cost efficiently, and to pass this efficiency along in low request pricing.

Reference: <http://aws.amazon.com/dynamodb/faqs/>

NEW QUESTION 2

A user is planning to make a mobile game which can be played online or offline and will be hosted on EC2.

The user wants to ensure that if someone breaks the highest score or they achieve some milestone they can inform all their colleagues through email. Which of the below mentioned AWS services helps achieve this goal?

- A. AWS Simple Workflow Service.
- B. AWS Simple Queue Service.
- C. Amazon Cognito
- D. AWS Simple Email Servic

Answer: D

Explanation:

Amazon Simple Email Service (Amazon SES) is a highly scalable and cost-effective email-sending service for businesses and developers. It integrates with other AWS services, making it easy to send emails from applications that are hosted on AWS.

Reference: <http://aws.amazon.com/ses/faqs/>

NEW QUESTION 3

Regarding Amazon SNS, when you want to subscribe to a topic and receive notifications to your email, in the Protocol drop-down box, you should select .

- A. Email
- B. Message
- C. SMTP
- D. IMAP

Answer: A

Explanation:

In Amazon SNS, when you want to subscribe to a topic and receive notifications to your email, select Email in the Protocol drop-down box. Enter an email address you can use to receive the notification in the Endpoint field.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SubscribeTopic.html>

NEW QUESTION 4

In DynamoDB, to get a detailed listing of secondary indexes on a table, you can use the action.

- A. DescribeTable
- B. BatchGetItem
- C. GetItem
- D. TableName

Answer: A

Explanation:

In DynamoDB, DescribeTable returns information about the table, including the current status of the table, when it was created, the primary key schema, and any indexes on the table.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SecondaryIndexes.html>

NEW QUESTION 5

When you create a table with a hash-and-range key, you must define one or more secondary indexes on that table.

- A. False, hash-range key is another name for secondary index
- B. False, it is optional
- C. True
- D. False, when you have Hash-Range key you cannot define Secondary index

Answer: B

Explanation:

When you create a table with a hash-and-range key in DynamoDB, you can also define one or more secondary indexes on that table.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/LSI.html>

NEW QUESTION 6

A user is accessing an EC2 instance on the SSH port for IP 10.20.30.40. Which one is a secure way to configure that the instance can be accessed only from this IP?

- A. In the security group, open port 22 for IP 1020.30.40/0
- B. In the security group, open port 22 for IP 10.20.30.40/32
- C. In the security group, open port 22 for IP 10.20.30.40/24
- D. In the security group, open port 22 for IP 10.20.30.40

Answer: B

Explanation:

In AWS EC2, while configuring a security group, the user needs to specify the IP address in CIDR notation. The CIDR IP range 10.20.30.40/32 says it is for a single IP 10.20.30.40. If the user specifies the IP as 10.20.30.40 only, the security group will not accept and ask it in a CIRD format.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-network-security.html>

NEW QUESTION 7

A user is planning to host a scalable dynamic web application on AWS. Which of the services may not be required by the user to achieve automated scalability?

- A. CloudWatch
- B. S3
- C. AutoScaling
- D. AWS EC2 instances

Answer: B

Explanation:

The user can achieve automated scaling by launching different EC2 instances and making them a part of an ELB. Cloudwatch will be used to monitor the resources and based on the scaling need it will trigger policies. AutoScaling is then used to scale up or down the instances.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/\NhatIsAutoScaling.html>

NEW QUESTION 8

Regarding Amazon SNS, you can send notification messages to mobile devices through any of the following supported push notification services, EXCEPT:

- A. Google Cloud Messaging for Android (GCM)
- B. Apple Push Notification Service (APNS)
- C. Amazon Device Messaging (ADM)
- D. Microsoft Windows Mobile Messaging (MWMM)

Answer: D

Explanation:

In Amazon SNS, you have the ability to send notification messages directly to apps on mobile devices. Notification messages sent to a mobile endpoint can appear in the mobile app as message alerts, badge updates, or even sound alerts. Microsoft Windows Mobile Messaging (MWMM) doesn't exist and is not supported by Amazon SNS.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SNSMobilePush.html>

NEW QUESTION 9

How many types of block devices does Amazon EC2 support?

- A. 5
- B. 1
- C. 2
- D. 4

Answer: C

Explanation:

Amazon EC2 supports 2 types of block devices. Reference:

<http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/block-device-mapping-concepts.html>

NEW QUESTION 10

Does AWS CloudFormation support Amazon EC2 tagging?

- A. It depends if the Amazon EC2 tagging has been defined in the template.
- B. No, it doesn't support Amazon EC2 tagging.
- C. No, CloudFormation doesn't support any tagging
- D. Yes, AWS CloudFormation supports Amazon EC2 tagging

Answer: D

Explanation:

In AWS CloudFormation, Amazon EC2 resources that support the tagging feature can also be tagged in an AWS template. The tag values can refer to template parameters, other resource names, resource attribute values (e.g. addresses), or values computed by simple functions (e.g., a concatenated list of strings).

Reference: <http://aws.amazon.com/cloudformation/faqs/>

NEW QUESTION 10

An online gaming site asked you if you can deploy a database that is a fast, highly scalable NoSQL database service in AWS for a new site that he wants to build. Which database should you recommend?

- A. Amazon Redshift
- B. Amazon SimpleDB
- C. Amazon DynamoDB
- D. Amazon RDS

Answer: C

Explanation:

Amazon DynamoDB is ideal for database applications that require very low latency and predictable performance at any scale but don't need complex querying capabilities like joins or transactions. Amazon DynamoDB is a fully-managed NoSQL database service that offers high performance, predictable throughput and low cost. It is easy to set up, operate, and scale.

With Amazon DynamoDB, you can start small, specify the throughput and storage you need, and easily scale your capacity requirements on the fly. Amazon DynamoDB automatically partitions data over a number of servers to meet your request capacity. In addition, DynamoDB automatically replicates your data synchronously across multiple Availability Zones within an AWS Region to ensure high-availability and data durability.

Reference: https://aws.amazon.com/running_databases/#dynamodb_anchor

NEW QUESTION 13

When should a user try to Force Detach an EBS volume?

- A. If the volume is stuck in a detaching state
- B. If the volume is not accessible from the instance
- C. If the volume is not unmounted and the user still wants to detach
- D. If the volume is a root volume

Answer: A

Explanation:

If an EBS volume stays in the detaching state, the user can force the detachment by clicking Force Detach. Forcing the detachment can lead to either data loss or a corrupted file system. The user should use this option only as a last resort to detach a volume from a failed instance or if he is detaching a volume with the intention of deleting it.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 14

A user wants to configure AutoScaling which scales up when the CPU utilization is above 70% and scales down when the CPU utilization is below 30%. How can the user configure AutoScaling for the above mentioned condition?

- A. Use AutoScaling with a schedule
- B. Configure ELB to notify AutoScaling on load increase or decrease
- C. Use dynamic AutoScaling with a policy
- D. Use AutoScaling by manually modifying the desired capacity during a condition

Answer: C

Explanation:

The user can configure the AutoScaling group to automatically scale up and then scale down based on the specified conditions. To configure this, the user must setup policies which will get triggered by the CloudWatch alarms.

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-scale-based-on-demand.html>

NEW QUESTION 15

A user has created an application which sends data to a log file. The server hosting the log files can be unavailable due to any reason. The user wants to make it so that whenever the log server is up it should be receiving the messages. Which of the below mentioned AWS services helps achieve this functionality?

- A. AWS Simple Workflow
- B. AWS Simple Task Service
- C. AWS Simple Notification Service
- D. AWS Simple Queue Service

Answer: D

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. The user can use SQS to transmit any volume of data without losing messages or requiring other services to always be available. Using SQS, the application has to just send the data to SQS and SQS transmits it to the log file whenever it is available.

Reference: <http://aws.amazon.com/sqs/>

NEW QUESTION 19

An account owner has created an IAM user with the name examkiller. The account owner wants to give EC2 access of only the US West region to that IAM user. How can the owner configure this?

- A. While creating a policy provide the region as a part of the resources
- B. Create an IAM user in the US West region and give access to EC2
- C. Create an IAM policy and define the region in the condition
- D. It is not possible to provide access based on the region

Answer: C

Explanation:

The IAM policy is never region specific. If the user wants to configure the region specific setting, he needs to provide conditions as part of the policy.
Reference: <http://awspolicygen.s3.amazonaws.com/policygen.html>

NEW QUESTION 24

In DynamoDB, the default table size is:

- A. 5 GB
- B. 1 GB
- C. 10 GB
- D. There is no table size

Answer: D

Explanation:

DynamoDB has seamless scalability with no table size limits and unlimited storage, so you shouldn't be worried about managing storage on the host or to provisioning more drive, as your data requirement changes.
Reference: <http://aws.amazon.com/dynamodb/>

NEW QUESTION 25

You want to have multiple versions of your application running at the same time, with all versions launched via AWS Elastic Beanstalk. Is this possible?

- A. N
- B. However if you have 2 AWS accounts this can be done
- C. N
- D. AWS Elastic Beanstalk is not designed to support multiple running environments
- E. Ye
- F. AWS Elastic Beanstalk is designed to support a number of multiple running environments
- G. Ye
- H. However AWS Elastic Beanstalk is designed to support only 2 multiple running environments

Answer: C

Explanation:

AWS Elastic Beanstalk is designed to support multiple running environments. As an example you could have one for integration testing, one for pre-production, and one for production, with each environment independently configured and running on its own separate AWS resources.
Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 28

When using Amazon SQS how much data can you store in a message?

- A. 8 KB
- B. 2 KB
- C. 16 KB
- D. 4 KB

Answer: A

Explanation:

With Amazon SQS version 2008-01-01, the maximum message size for both SOAP and Query requests is 8KB.
If you need to send messages to the queue that are larger than 8 KB, AWS recommends that you split the information into separate messages. Alternatively, you could use Amazon S3 or Amazon SimpleDB to hold the information and include the pointer to that information in the Amazon SQS message.
If you send a message that is larger than 8KB to the queue, you will receive a MessageTooLong error with HTTP code 400.
Reference: <https://aws.amazon.com/items/1343?externalID=1343>

NEW QUESTION 33

Which of the below mentioned options is not a best practice to securely manage the AWS access credentials?

- A. Enable MFA for privileged users
- B. Create individual IAM users
- C. Keep rotating your secure access credentials at regular intervals
- D. Create strong access key and secret access key and attach to the root account

Answer: D

Explanation:

It is a recommended approach to avoid using the access and secret access keys of the root account.
Thus, do not download or delete it. Instead make the IAM user as powerful as the root account and use its credentials. The user cannot generate their own access and secret access keys as they are always generated by AWS.
Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/IAMBestPractices.html>

NEW QUESTION 34

When you use the AWS Elastic Beanstalk console to deploy a new application you'll need to upload a source bundle and it should .

- A. Consist of a single .zip file

- B. Consist of a single .war file
- C. Consist of a single .zip file or .war file
- D. Consist of a folder with all files

Answer: C

Explanation:

When you use the AWS Elastic Beanstalk console to deploy a new application or an application version, you'll need to upload a source bundle. Your source bundle must meet the following requirements: Consist of a single .zip file or .war file

Not exceed 512 MB

Not include a parent folder or top-level directory (subdirectories are fine) Reference:

<http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.deployment.source.html>

NEW QUESTION 39

A user had defined an IAM policy similar to the one given below on a bucket:

```
{
"Version": "2012-10-17",
"Statement": [{
"Effect": "Allow",
"Principal": {
"AWS": "arn:aws:iam::12112112:user/test"
}
},
{
"Action": [ "s3:GetBucketLocation", "s3:ListBucket", "s3:GetObject" ],
"Resource": [ "arn:aws:s3:::examkiller" ]
}
]
```

What will this do?

- A. It will result in an error saying invalid policy statement
- B. It will create an IAM policy for the user test
- C. Allows the user test of the AWS account ID 12112112 to perform GetBucketLocation, ListBucket and GetObject on the bucket examkiller
- D. It will allow all the IAM users of the account ID 12112112 to perform GetBucketLocation, ListBucket and GetObject on bucket examkiller

Answer: C

Explanation:

The IAM policy allows to test a user in the account 12112112 to perform: s3:GetBucketLocation

s3:ListBucket s3:GetObject

Amazon S3 permissions on the examkiller bucket.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/access-policy-language-overview.html>

NEW QUESTION 40

How does Amazon SQS allow multiple readers to access the same message queue without losing messages or processing them many times?

- A. By identifying a user by his unique id
- B. By using unique cryptography
- C. Amazon SQS queue has a configurable visibility timeout.
- D. Multiple readers can't access the same message queue

Answer: C

Explanation:

Every Amazon SQS queue has a configurable visibility timeout. For the designated amount of time after a message is read from a queue, it will not be visible to any other reader. As long as the amount of time that it takes to process the message is less than the visibility timeout, every message will be processed and deleted. In the event that the component processing the message fails or becomes unavailable, the message will again become visible to any component reading the queue once the visibility timeout ends. This allows you to have many components all reading messages from the same queue, with each working to process different messages.

Reference: <https://aws.amazon.com/sqs/faqs/>

NEW QUESTION 41

A user is trying to understand AWS SNS. To which of the below mentioned end points is SNS unable to send a notification?

- A. AWS SES
- B. Email JSON
- C. AWS SQS
- D. HTTP

Answer: A

Explanation:

Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS can deliver notifications by SMS text message or email to the Amazon Simple Queue Service (SQS) queues or to any HTTP endpoint. The user can select one the following transports as part of the subscription requests: "HTTP", "HTTPS", "Email", "Email-JSON", "SQS", "and SMS".

Reference: <http://aws.amazon.com/sns/faqs/>

NEW QUESTION 45

What does Amazon SQS provide?

- A. An asynchronous message queue service.
- B. A Simple Query Service, managed directly by Amazon Web Services.
- C. None of these.
- D. A synchronous message queue service.

Answer: A

Explanation:

Amazon SQS stands for Simple Queue Services, and provides a cost-effective way to decouple the components of your application through an asynchronous message queue service

Reference: <http://aws.amazon.com/sqs/>

NEW QUESTION 46

A user is trying to create a list of IAM users with the AWS console. When the IAM users are created which of the below mentioned credentials will be enabled by default for the user?

- A. IAM access key and secret access key
- B. IAM X.509 certificates
- C. Nothin
- D. Everything is disabled by default
- E. IAM passwords

Answer: C

Explanation:

Newly created IAM users have no password and no access key (access key ID and secret access key). If the user needs to administer your AWS resources using the AWS Management Console, you can create a password for the user. If the user needs to interact with AWS programmatically (using the command line interface (CLI), the AWS SDK, or service-specific APIs), you can create an access key for that user. The credentials you create for users are what they use to uniquely identify themselves to AWS.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_WorkingWithGroupsAndUsers.html

NEW QUESTION 48

A root account owner is trying to setup an additional level of security for all his IAM users. Which of the below mentioned options is a recommended solution for the account owner?

- A. Enable access key and secret access key for all the IAM users
- B. Enable MFA for all IAM users
- C. Enable the password for all the IAM users
- D. Enable MFA for the root account

Answer: B

Explanation:

Multi-Factor Authentication adds an extra level of security for all the users. The user can enable MFA for all IAM users which ensures that each user has to provide an extra six digit code for authentication. Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_ManagingMFA.html

NEW QUESTION 51

Which of the below mentioned commands allows the user to share the AMI with his peers using the AWS EC2 CLI?

- A. ec2-share-image-public
- B. ec2-share-image-account
- C. ec2-share-image
- D. ec2-modify-image-attribute

Answer: D

Explanation:

A user can share an AMI with another user / peer using the command: ec2-modify-image-attribute

<AMI-ID> -| -a <AWS Account ID>

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/sharingamis-explicit.html>

NEW QUESTION 54

A user has created an EBS instance in the US-East-1a AZ. The user has a volume of 30 GB in the US-East-1 b zone. How can the user attach the volume to an instance?

- A. Since both the volume and the instance are in the same region, the user can attach the volume
- B. Use the volume migrate function to move the volume from one AZ to another and attach to the instance
- C. Take a snapshot of the volum
- D. Create a new volume in the USEast-1a and attach that to the instance
- E. Use the volume replicate function to create a new volume in the US-East-1a and attach that to the volume

Answer: C

Explanation:

If an EBS volume is not in the same AZ of an EC2 instance, it cannot be attached to the instance. The only option is to take a snapshot of the volume and create a new volume in the instance's AZ. Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSSnapshots.html>

NEW QUESTION 56

A user has created an RDS instance with MySQL. The user is using the HeidiSQL client to connect with the RDS DB. The client is unable to connect to DB from his home machine. What is a possible reason for the failure?

- A. The user has to open port 80 in the RDS security group to connect with RDS DNS
- B. The security group is not configured to allow a request from the user's IP on port 3306
- C. You can never connect to RDS from your desktop
- D. The user has to open port 22 in the RDS security group to connect with RDS DNS

Answer: B

Explanation:

If the user needs to connect to RDS then he has to open port 3306 in the RDS security group for his IP address.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 60

An orgAMzation has 10000 employees. The orgAMzation wants to give restricted AWS access to each employee. How can the orgAMzation achieve this?

- A. Create an IAM user for each employee and make them a part of the group
- B. It is not recommended to support 10000 users with IAM
- C. Use STS and create the users' run time
- D. Use Identity federation with SSO

Answer: D

Explanation:

Identity federation enables users from an existing directory to access resources within your AWS account, making it easier to manage your users by maintaining their identities in a single place. In this case, the federated user is the only solution since AWS does not allow creating more than 5000 IAM users. Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/LimitationsOnEntities.html>

NEW QUESTION 61

An orgAMzation has 20 employees. The orgAMzation wants to give all the users access to the orgAMzation AWS account. Which of the below mentioned options is the right solution?

- A. Share the root credentials with all the users
- B. Create an IAM user for each employee and provide access to them
- C. It is not advisable to give AWS access to so many users
- D. Use the IAM role to allow access based on STS

Answer: B

Explanation:

AWS Identity and Access Management is a web service that enables the AWS customers to manage users and user permissions in AWS. The IAM is targeted at orgAMzations with multiple users or systems that use AWS products such as Amazon EC2, Amazon RDS, and the AWS Management Console. With IAM, the orgAMzaiton can centrally manage users, security credentials such as access keys, and permissions that control which AWS resources users can access.

Reference: http://docs.aws.amazon.com/IAM/latest/UserGuide/IAM_Introduction.html

NEW QUESTION 62

Which Amazon service is not used by Elastic Beanstalk?

- A. Amazon S3
- B. Amazon ELB
- C. Auto scaling
- D. Amazon EMR

Answer: D

Explanation:

Elastic Beanstalk leverages AWS services such as Amazon Elastic Cloud Compute (Amazon EC2), Amazon Simple Storage Service (Amazon S3), Amazon Simple Notification Service (Amazon SNS), Elastic Load Balancing and Auto Scaling to deliver the same highly reliable, scalable, and cost-effective infrastructure that hundreds of thousands of businesses depend on today.

Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/Welcome.html>

NEW QUESTION 63

Which of the below mentioned options can be a good use case for storing content in AWS RRS?

- A. Storing mission critical data Files
- B. Storing infrequently used log files
- C. Storing a video file which is not reproducible
- D. Storing image thumbnails

Answer: D

Explanation:

AWS RRS provides the same functionality as AWS S3, but at a cheaper rate. It is ideally suited for non-mission, critical applications, such as files which can be reproduced.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/UsingRRS.html>

NEW QUESTION 65

AWS Elastic Beanstalk will change the health status of a web server environment tier to gray color when:

- A. AWS Elastic Beanstalk detects other problems with the environment that are known to make the application unavailable
- B. Your application hasn't responded to the application health check URL within the last one hour.
- C. Your application hasn't responded to the application health check URL within the last five minutes.
- D. Your application's health status is unknown because status is reported when the application is not in the ready state.

Answer: D

Explanation:

AWS Elastic Beanstalk will change the health status of a web server environment tier to gray color when your application's health status is unknown (because status is reported when the application is not in the ready state).

Reference: <http://docs.aws.amazon.com/elasticbeanstalk/latest/dg/using-features.healthstatus.html>

NEW QUESTION 68

A user is creating a snapshot of an EBS volume. Which of the below statements is incorrect in relation to the creation of an EBS snapshot?

- A. Its incremental
- B. It can be used to launch a new instance
- C. It is stored in the same AZ as the volume
- D. It is a point in time backup of the EBS volume

Answer: C

Explanation:

The EBS snapshots are a point in time backup of the EBS volume. It is an incremental snapshot, but is always specific to the region and never specific to a single AZ.

Hence the statement "It is stored in the same AZ as the volume" is incorrect.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSSnapshots.html>

NEW QUESTION 70

Which of the following groups is AWS Elastic Beanstalk best suited for?

- A. Those who want to deploy and manage their applications within minutes in the AWS cloud
- B. Those who want to privately store and manage Git repositories in the AWS cloud.
- C. Those who want to automate the deployment of applications to instances and to update the applications as required
- D. Those who want to model, visualize, and automate the steps required to release software

Answer: A

Explanation:

AWS Elastic Beanstalk is best suited for those groups who want to deploy and manage their applications within minutes in the AWS cloud. As a bonus, you don't even need experience with cloud computing to get started.

Reference: <https://aws.amazon.com/elasticbeanstalk/faqs/>

NEW QUESTION 72

You are using Amazon SQS and are getting a "Queue Deleted Recently" error. What is wrong?

- A. The message is too big
- B. You have incorrect permissions
- C. Another user has deleted the queue
- D. If you delete a queue, you need to wait for at least 60 seconds before creating a queue with the same name

Answer: D

Explanation:

If you delete a queue, you need to wait for at least 60 seconds before creating a queue with the same name. Please note that when you delete a queue, the deletion process takes up to 60 seconds. Requests you send to a recently deleted queue might succeed during the 60-second period. For example, a `SendMessage` request might succeed, but after 60 seconds the queue and that message you sent no longer exists.

Reference: <https://aws.amazon.com/items/1343?externalID=1343>

NEW QUESTION 76

A user has enabled serverside encryption with S3. The user downloads the encrypted object from S3. How can the user decrypt it?

- A. S3 does not support server side encryption
- B. S3 provides a server side key to decrypt the object
- C. The user needs to decrypt the object using their own private key
- D. S3 manages encryption and decryption automatically

Answer: D

Explanation:

If the user is using the server-side encryption feature, Amazon S3 encrypts the object data before saving it on disks in its data centres and decrypts it when the user downloads the objects. Thus, the user is free from the tasks of managing encryption, encryption keys, and related tools.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/UsingEncryption.html>

NEW QUESTION 81

A user has configured ELB with two instances running in separate AZs of the same region? Which of the below mentioned statements is true?

- A. Multi AZ instances will provide HA with ELB
- B. Multi AZ instances are not possible with a single ELB
- C. Multi AZ instances will provide scalability with ELB
- D. The user can achieve both HA and scalability with ELB

Answer: A

Explanation:

If a user is running two instances in separate AZs, it will provide HA with ELB since ELB will automatically stop routing the traffic to unhealthy instances and send it to healthy instances only.

NEW QUESTION 85

A user is trying to configure access with S3. Which of the following options is not possible to provide access to the S3 bucket / object?

- A. Define the policy for the IAM user
- B. Define the ACL for the object
- C. Define the policy for the object
- D. Define the policy for the bucket

Answer: C

Explanation:

Amazon S3 offers access policy options broadly categorized as resource-based policies and user policies.

Access policies, such as ACL and resource policy can be attached to the bucket. With the object the user can only have ACL and not an object policy. The user can also attach access policies to the IAM users in the account. These are called user policies.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/s3-access-control.html>

NEW QUESTION 87

A user has developed an application which is required to send the data to a NoSQL database. The user wants to decouple the data sending such that the application keeps processing and sending data but does not wait for an acknowledgement of DB. Which of the below mentioned applications helps in this scenario?

- A. AWS Simple Notification Service
- B. AWS Simple Workflow
- C. AWS Simple Query Service
- D. AWS Simple Queue Service

Answer: D

Explanation:

Amazon Simple Queue Service (SQS) is a fast, reliable, scalable, and fully managed message queuing service. SQS provides a simple and cost-effective way to decouple the components of an application. In this case, the user can use AWS SQS to send messages which are received from an application and sent to DB. The application can continue processing data without waiting for any acknowledgement from DB. The user can use SQS to transmit any volume of data without losing messages or requiring other services to always be available.

Reference: <http://aws.amazon.com/sqs/>

NEW QUESTION 89

A user is planning to use the AWS RDS with MySQL. Which of the below mentioned services the user is not going to pay?

- A. Data transfer
- B. RDS Cloudwatch metrics
- C. Data storage
- D. I/O requests per month

Answer: B

Explanation:

RDS charges the user on a pay as you go basis. It charges the user based on the instance type, number of hours that the instance is running, data transfer, storage cost as well for the I/O requests. The monitoring is free of cost.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 93

True or False: AWS CloudFormation allows you to create Microsoft Windows stacks.

- A. False, AWS CloudFormation does not support Microsoft Windows.
- B. False, Amazon doesn't support Microsoft Windows.
- C. False, you cannot create Windows stacks.
- D. True

Answer: D

Explanation:

AWS CloudFormation allows you to create Microsoft Windows stacks based on Amazon EC2 Windows Amazon Machine Images (AMIs) and provides you with the ability to install software, to use remote desktop to access your stack, and to update and configure your stack.

Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/cfn-windows-stacks.html>

NEW QUESTION 98

Which of the following solutions is not supported by DynamoDB:

- A. Hash secondary index
- B. Local secondary index
- C. Hash Primary Key
- D. Global secondary index

Answer: A

Explanation:

In DynamoDB, a secondary index is a data structure that contains a subset of attributes from a table, along with an alternate key to support Query operations. DynamoDB supports the following two types of secondary indexes:

Local secondary index is an index that has the same hash key as the table, but a different range key. A local secondary index is "local" in the sense that every partition of a local secondary index is scoped to a table partition that has the same hash key.

Global secondary index is an index with a hash and range key that can be different from those on the table. A global secondary index is considered "global" because queries on the index can span all of the data in a table, across all partitions.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

NEW QUESTION 103

The AWS console for DynamoDB enables you to do all the following operations, except:

- A. Set up alarms to monitor your table's capacity usage.
- B. Create, update, and delete tables.
- C. Import Data from other databases or from files.
- D. View your table's top monitoring metrics on real-time graphs from CloudWatc

Answer: C

Explanation:

The AWS console for DynamoDB enables you to do all the above operation but not Importing Data from other databases or from files and it is not possible to do it.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/ConsoleDynamoDB.html>

NEW QUESTION 104

An orgAMzation has created multiple components of a single application for compartmentalization. Currently all the components are hosted on a single EC2 instance. Due to security reasons the orgAMzation wants to implement two separate SSLs for the separate modules although it is already using VPC. How can the orgAMzation achieve this with a single instance?

- A. Create a VPC instance which will have both the ACL and the security group attached to it and have separate rules for each IP address.
- B. Create a VPC instance which will have multiple network interfaces with multiple elastic IP addresses.
- C. You have to launch two instances each in a separate subnet and allow VPC peering for a single IP.
- D. Create a VPC instance which will have multiple subnets attached to it and each will have a separate IP address.

Answer: B

Explanation:

A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. It enables the user to launch AWS resources into a virtual network that the user has defined. With VPC the user can specify multiple private IP addresses for his instances.

The number of network interfaces and private IP addresses that a user can specify for an instance depends on the instance type. With each network interface the orgAMzation can assign an EIP. This scenario helps when the user wants to host multiple websites on a single EC2 instance by using multiple SSL certificates on a single server and associating each certificate with a specific EIP address. It also helps in scenarios for operating network appliances, such as firewalls or load balancers that have multiple private IP addresses for each network interface.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/MultipleIP.html>

NEW QUESTION 105

A user has hosted a website on AWS and uses ELB to load balance the multiple instances. The user application does not have any cookie management. How can the user bind the session of the requestor with a particular instance?

- A. Bind the IP address with a sticky cookie
- B. Create a cookie at the application level to set at ELB
- C. Use session synchronization with ELB
- D. Let ELB generate a cookie for a specified duration

Answer: D

Explanation:

The key to manage the sticky session is determining how long the load balancer should route the user's request to the same application instance. If the application has its own session cookie, then the user can set the Elastic Load Balancing to create the session cookie to follow the duration specified by the application's session cookie. If the user's application does not have its own session cookie, then he can set the Elastic Load Balancing to create a session cookie by specifying his own stickiness duration. Reference: http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/US_StickySessions.html

NEW QUESTION 109

A user has enabled automated backup for an RDS instance. What is the longest duration for which the user can retain the automated backup?

- A. 25 days
- B. 15 days
- C. 45 days
- D. 35 days

Answer: D

Explanation:

Amazon RDS provides two different methods for backing up and restoring the Amazon DB instances: automated backups and DB snapshots. Automated backups automatically back up the DB instance during a specific, user-definable backup window, and keep the backups for a limited, user-specified period of time. The maximum period can be 35 days.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Overview.BackingUpAndRestoringAmazonRDSInstances.html>

NEW QUESTION 114

How can you peek at a message in Amazon SQS?

- A. Log the message ID and the receipt handle for your messages and correlate them to confirm when a message has been received and deleted
- B. Send the message to Amazon S3
- C. You can't
- D. Set up a CloudWatch alarm to auto send you the message

Answer: A

Explanation:

With version 2008-01-01, the PeekMessage action has been removed from Amazon SQS. This functionality was used mainly to debug small systems — specifically to confirm a message was successfully sent to the queue or deleted from the queue.

To do this with version 2008-01-01, you can log the message ID and the receipt handle for your messages and correlate them to confirm when a message has been received and deleted. Reference: <https://aws.amazon.com/items/1343?externalID=1343>

NEW QUESTION 116

In regard to DynamoDB, for which one of the following parameters does Amazon not charge you?

- A. Cost per provisioned write units
- B. Cost per provisioned read units
- C. Storage cost
- D. I/O usage within the same Region

Answer: D

Explanation:

In DynamoDB, you will be charged for the storage and the throughput you use rather than for the I/O which has been used.

Reference: <http://aws.amazon.com/dynamodb/pricing/>

NEW QUESTION 117

What is the maximum size for messages stored in SQS?

- A. 256KB
- B. 128KB
- C. 1024KB
- D. 64KB

Answer: A

Explanation:

By default, SQS queues allow you to send the largest supported payload size, currently 256KB. You can choose to specify a limit on how many bytes can be sent per payload, using the `MaximumMessageSize` attribute of the `SetQueueAttributes` method.

Reference: <http://aws.amazon.com/sqs/faqs/>

NEW QUESTION 118

A user is planning to host data with RDS. Which of the below mentioned databases is not supported by RDS?

- A. PostgreSQL
- B. SQLDB
- C. Oracle
- D. MS SQL

Answer: B

Explanation:

Amazon Relational Database Service (Amazon RDS) is a web service that makes it easier to set up, operate, and scale a relational database in the cloud. AWS RDS supports popular DBs, such as MySQL, PostgreSQL, MS SQL and Oracle. This means that the code, applications, and tools user is already using with existing databases can be used with Amazon RDS too. In short, it is a managed Relation Database offering from AWS which manages backups, software patching, automatic failure detection, and recovery of Database.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

NEW QUESTION 119

An EC2 instance has one additional EBS volume attached to it. How can a user attach the same volume to another running instance in the same AZ?

- A. Terminate the first instance and only then attach to the new instance
- B. Attach the volume as read only to the second instance
- C. Detach the volume first and attach to new instance
- D. No need to detach

E. Just select the volume and attach it to the new instance, it will take care of mapping internally

Answer: C

Explanation:

If an EBS volume is attached to a running EC2 instance, the user needs to detach the volume from the original instance and then attach it to a new running instance. The user doesn't need to stop / terminate the original instance.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

NEW QUESTION 120

Regarding Amazon SNS, to send messages to a queue through a topic, you must subscribe the queue to the Amazon SNS topic. You specify the queue by its .

- A. ARN
- B. Token
- C. Registration ID
- D. URL

Answer: A

Explanation:

In Amazon SNS, to send messages to a queue through a topic, you must subscribe the queue to the Amazon SNS topic. You specify the queue by its ARN.

Reference: <http://docs.aws.amazon.com/sns/latest/dg/SendMessageToSQS.html>

NEW QUESTION 121

To scale up the AWS resources using manual AutoScaling, which of the below mentioned parameters should the user change?

- A. Maximum capacity
- B. Desired capacity
- C. Preferred capacity
- D. Current capacity

Answer: B

Explanation:

The Manual Scaling as part of Auto Scaling allows the user to change the capacity of Auto Scaling group. The user can add / remove EC2 instances on the fly. To execute manual scaling, the user should modify the desired capacity. AutoScaling will adjust instances as per the requirements. If the user is trying to CLI, he can use command `as-set-desired-capacity <Auto Scaling Group Name> --desired-capacity <New Capacity>`

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/as-manual-scaling.html>

NEW QUESTION 124

A bucket owner has allowed another account's IAM users to upload or access objects in his bucket. The IAM user of Account A is trying to access an object created by the IAM user of account B. What will happen in this scenario?

- A. The bucket policy may not be created as S3 will give error due to conflict of Access Rights
- B. It is not possible to give permission to multiple IAM users
- C. AWS S3 will verify proper rights given by the owner of Account A, the bucket owner as well as by the IAM user B to the object
- D. It is not possible that the IAM user of one account accesses objects of the other IAM user

Answer: C

Explanation:

If a IAM user is trying to perform some action on an object belonging to another AWS user's bucket, S3 will verify whether the owner of the IAM user has given sufficient permission to him. It also verifies the policy for the bucket as well as the policy defined by the object owner.

Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/access-control-auth-workflow-object-operation.html>

NEW QUESTION 127

A user is launching an instance with EC2. Which of the below mentioned options does the user need to consider before launching an instance?

- A. Select the region where the instance is being launched.
- B. Select the instance type.
- C. All the options listed should be considered..
- D. Select the OS of the AM

Answer: C

Explanation:

Regarding Amazon EC2, when launching an instance, the user needs to select the region the instance would be launched from. While launching, the user needs to plan for the instance type and the OS of the instance.

Reference: http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-launch-instance_linux.html

NEW QUESTION 129

A user has created an EBS volume with 1000 IOPS. What is the average IOPS that the user will get for most of the year as per EC2 SLA if the instance is attached to the EBS optimized instance?

- A. 900
- B. 990

- C. 950
- D. 1000

Answer: A

Explanation:

As per AWS SLA if the instance is attached to an EBS-Optimized instance, then the Provisioned IOPS volumes are designed to deliver within 10% of the provisioned IOPS performance 99.9% of the time in a given year. Thus, if the user has created a volume of 1000 IOPS, the user will get a minimum 900 IOPS 99.9% time of the year.

Reference: <http://aws.amazon.com/ec2/faqs/>

NEW QUESTION 131

Which statements about DynamoDB are true? Choose 2 answers

- A. DynamoDB uses a pessimistic locking model
- B. DynamoDB uses optimistic concurrency control
- C. DynamoDB uses conditional writes for consistency
- D. DynamoDB restricts item access during reads
- E. DynamoDB restricts item access during writes

Answer: BC

NEW QUESTION 136

You have an environment that consists of a public subnet using Amazon VPC and 3 instances that are running in this subnet. These three instances can successfully communicate with other hosts on the Internet. You launch a fourth instance in the same subnet, using the same AMI and security group configuration you used for the others, but find that this instance cannot be accessed from the Internet. What should you do to enable internet access?

- A. Deploy a NAT instance into the public subnet.
- B. Modify the routing table for the public subnet
- C. Configure a publically routable IP Address In the host OS of the fourth instance.
- D. Assign an Elastic IP address to the fourth instanc

Answer: D

NEW QUESTION 138

Which of the following statements about SWF are true? Choose 3 answers

- A. SWF tasks are assigned once and never duplicated
- B. SWF requires an S3 bucket for workflow storage
- C. SWF workflow executions can last up to a year
- D. SWF triggers SNS notifications on task assignment
- E. SWF uses deciders and workers to complete tasks
- F. SWF requires atleast 1 EC2 instance per domain

Answer: ACE

NEW QUESTION 139

Company C has recently launched an online commerce site for bicycles on AWS. They have a "Product" DynamoDB table that stores details for each bicycle, such as, manufacturer, color, price, quantity and size to display in the online store. Due to customer demand, they want to include an image for each bicycle along with the existing details.

Which approach below provides the least impact to provisioned throughput on the "Product" table?

- A. Serialize the image and store it in multiple DynamoDB tables
- B. Create an "Images" DynamoDB table to store the Image with a foreign key constraint to the "Product" table
- C. Add an image data type to the "Product" table to store the images in binary format
- D. Store the images in Amazon S3 and add an S3 URL pointer to the "Product" table item for each image

Answer: D

NEW QUESTION 144

What is one key difference between an Amazon EBS-backed and an instance-store backed instance?

- A. Virtual Private Cloud requires EBS backed instances
- B. Amazon EBS-backed instances can be stopped and restarted
- C. Auto scaling requires using Amazon EBS-backed instances.
- D. Instance-store backed instances can be stopped and restarte

Answer: B

NEW QUESTION 147

A startup s photo-sharing site is deployed in a VPC. An ELB distributes web traffic across two subnets. ELB session stickiness is configured to use the AWS-generated session cookie, with a session TTL of 5 minutes. The webserver Auto Scaling Group is configured as: min-size=4, max-size=4.

The startups preparing for a public launch, by running load-testing software installed on a single EC2 instance running in us-west-2a. After 60 minutes of load-testing, the webserver logs show:

WEBSERVER LOGS	# of HTTP requests from load-tester	# of HTTP requests from private beta users
webserver #1 (subnet in us-west-2a):	19,210	434
webserver #2 (subnet in us-west-2a):	21,790	490
webserver #3 (subnet in us-west-2b):	0	410
webserver #4 (subnet in us-west-2b):	0	428

Which recommendations can help ensure load-testing HTTP requests are evenly distributed across the four webserver? Choose 2 answers

- A. Launch and run the load-tester EC2 instance from us-east-1 instead.
- B. Re-configure the load-testing software to re-resolve DNS for each web request.
- C. Use a 3rd-party load-testing service which offers globally-distributed test clients.
- D. Configure ELB and Auto Scaling to distribute across us-west-2a and us-west-2c.
- E. Configure ELB session stickiness to use the app-specific session cooki

Answer: BE

NEW QUESTION 152

In DynamoDB, what type of HTTP response codes indicate that a problem was found with the client request sent to the service?

- A. 5xx HTTP response code
- B. 200 HTTP response code
- C. 306 HTTP response code
- D. 4xx HTTP response code

Answer: D

NEW QUESTION 154

What item operation allows the retrieval of multiple items from a DynamoDB table in a single API call?

- A. GetItem
- B. BatchGetItem
- C. GetMultipleItems
- D. GetItemRange

Answer: B

NEW QUESTION 158

You are inserting 1000 new items every second in a DynamoDB table. Once an hour these items are analyzed and then are no longer needed. You need to minimize provisioned throughput, storage, and API calls.

Given these requirements, what is the most efficient way to manage these Items after the analysis?

- A. Retain the items in a single table
- B. Delete items indMdually over a 24 hour period
- C. Delete the table and create a new table per hour
- D. Create a new table per hour

Answer: C

NEW QUESTION 163

What AWS products and features can be deployed by Elastic Beanstalk? Choose 3 answers

- A. Auto scaling groups
- B. Route 53 hosted zones
- C. Elastic Load Balancers
- D. RDS Instances
- E. Elastic IP addresses
- F. SQS Queues

Answer: ACD

NEW QUESTION 164

How can software determine the public and private IP addresses of the Amazon EC2 instance that it is running on?

- A. Query the appropriate Amazon CloudWatch metric.
- B. Use ipconfig or ifconfig command.
- C. Query the local instance userdata.
- D. Query the local instance metadat

Answer: D

NEW QUESTION 165

An Amazon S3 bucket, "myawsbucket" is configured with website hosting in Tokyo region, what is the region-specific website endpoint?

- A. www.myawsbucket.ap-northeast-1.amazonaws.com
- B. myawsbucket.s3-website-ap-northeast-l.amazonawscom

- C. myawsbucket.amazonaws.com
- D. myawsbucket.tokyo.amazonaws.com

Answer: B

NEW QUESTION 169

Which of the following items are required to allow an application deployed on an EC2 instance to write data to a DynamoDB table? Assume that no security Keys are allowed to be stored on the EC2 instance. Choose 2 answers

- A. Create an IAM User that allows write access to the DynamoDB table.
- B. Add an IAM Role to a running EC2 instance.
- C. Add an IAM User to a running EC2 Instance.
- D. Launch an EC2 Instance with the IAM Role included in the launch configuration.
- E. Create an IAM Role that allows write access to the DynamoDB table.
- F. Launch an EC2 Instance with the IAM User included in the launch configuration.

Answer: DE

NEW QUESTION 171

Your application is trying to upload a 6 GB file to Simple Storage Service and receive a "Your proposed upload exceeds the maximum allowed object size." error message. What is a possible solution for this?

- A. None, Simple Storage Service objects are limited to 5 GB
- B. Use the multi-part upload API for this object
- C. Use the large object upload API for this object
- D. Contact support to increase your object size limit
- E. Upload to a different region

Answer: B

NEW QUESTION 174

What type of block cipher does Amazon S3 offer for server side encryption?

- A. Triple DES
- B. Advanced Encryption Standard
- C. Blowfish
- D. RC5

Answer: B

NEW QUESTION 179

A corporate web application is deployed within an Amazon VPC, and is connected to the corporate data center via IPsec VPN. The application must authenticate against the on-premise LDAP server. Once authenticated, logged-in users can only access an S3 keyspace specific to the user. Which two approaches can satisfy the objectives? Choose 2 answers

- A. The application authenticates against LDA
- B. The application then calls the IAM Security Service to login to IAM using the LDAP credential
- C. The application can use the IAM temporary credentials to access the appropriate S3 bucket.
- D. The application authenticates against LDAP, and retrieves the name of an IAM role associated with the use
- E. The application then calls the IAM Security Token Service to assume that IAM Rol
- F. The application can use the temporary credentials to access the appropriate S3 bucket.
- G. The application authenticates against IAM Security Token Service using the LDAP credential
- H. The application uses those temporary AWS security credentials to access the appropriate S3 bucket.
- I. Develop an identity broker which authenticates against LDAP, and then calls IAM Security Token Service to get IAM federated user credential
- J. The application calls the identity broker to get IAM federated user credentials with access to the appropriate S3 bucket.
- K. Develop an identity broker which authenticates against IAM Security Token Service to assume an IAM Role to get temporary AWS security credential
- L. The application calls the identity broker to get AWS temporary security credentials with access to the appropriate S3 bucket.

Answer: BD

NEW QUESTION 181

You attempt to store an object in the US-STANDARD region in Amazon S3, and receive a confirmation that it has been successfully stored. You then immediately make another API call and attempt to read this object. S3 tells you that the object does not exist. What could explain this behavior?

- A. US-STANDARD uses eventual consistency and it can take time for an object to be readable in a bucket
- B. Objects in Amazon S3 do not become visible until they are replicated to a second region.
- C. US-STANDARD imposes a 1 second delay before new objects are readable.
- D. You exceeded the bucket object limit, and once this limit is raised the object will be visible.

Answer: A

NEW QUESTION 182

You are writing to a DynamoDB table and receive the following exception: "ProvisionedThroughputExceededException". though according to your Cloudwatch metrics for the table, you are not exceeding your provisioned throughput. What could be an explanation for this?

- A. You haven't provisioned enough DynamoDB storage instances
- B. You're exceeding your capacity on a particular Range Key
- C. You're exceeding your capacity on a particular Hash Key
- D. You're exceeding your capacity on a particular Sort Key
- E. You haven't configured DynamoDB Auto Scaling triggers

Answer: C

NEW QUESTION 187

If an application is storing hourly log files from thousands of instances from a high traffic web site, which naming scheme would give optimal performance on S3?

- A. Sequential
- B. instanceID_log-HH-DD-NIM-YYYY
- C. instanceID_log-YYYY-NIM-DD-HH
- D. HH-DD-NINI-YYYY-log_instanceID
- E. YYYY-MM-DD-HH-log_instanceID

Answer: E

NEW QUESTION 189

Which of the following is chosen as the default region when making an API call with an AWS SDK?

- A. ap-northeast-1
- B. us-west-2
- C. us-east-1
- D. eu-west-1
- E. us-central-1

Answer: C

NEW QUESTION 190

Games-R-Us is launching a new game app for mobile devices. Users will log into the game using their existing Facebook account and the game will record player data and scoring information directly to a DynamoDB table.

What is the most secure approach for signing requests to the DynamoDB API?

- A. Create an IAM user with access credentials that are distributed with the mobile app to sign the requests
- B. Distribute the AWS root account access credentials with the mobile app to sign the requests
- C. Request temporary security credentials using web identity federation to sign the requests
- D. Establish cross account access between the mobile app and the DynamoDB table to sign the requests

Answer: C

NEW QUESTION 195

What happens, by default, when one of the resources in a CloudFormation stack cannot be created?

- A. Previously-created resources are kept but the stack creation terminates.
- B. Previously-created resources are deleted and the stack creation terminates.
- C. The stack creation continues, and the final results indicate which steps failed.
- D. CloudFormation templates are parsed in advance so stack creation is guaranteed to succeed

Answer: B

NEW QUESTION 198

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

AWS-Certified-Developer-Associate Practice Exam Features:

- * AWS-Certified-Developer-Associate Questions and Answers Updated Frequently
- * AWS-Certified-Developer-Associate Practice Questions Verified by Expert Senior Certified Staff
- * AWS-Certified-Developer-Associate Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * AWS-Certified-Developer-Associate Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The AWS-Certified-Developer-Associate Practice Test Here](#)