

ANS-C01 Dumps

AWS Certified Advanced Networking Specialty Exam

<https://www.certleader.com/ANS-C01-dumps.html>



NEW QUESTION 1

An IoT company sells hardware sensor modules that periodically send out temperature, humidity, pressure, and location data through the MQTT messaging protocol. The hardware sensor modules send this data to the company's on-premises MQTT brokers that run on Linux servers behind a load balancer. The hardware sensor modules have been hardcoded with public IP addresses to reach the brokers.

The company is growing and is acquiring customers across the world. The existing solution can no longer scale and is introducing additional latency because of the company's global presence. As a result, the company decides to migrate its entire infrastructure from on premises to the AWS Cloud. The company needs to migrate without reconfiguring the hardware sensor modules that are already deployed across the world. The solution also must minimize latency.

The company migrates the MQTT brokers to run on Amazon EC2 instances. What should the company do next to meet these requirements?

- A. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- B. Use Bring Your Own IP (BYOIP) from the on-premises network with the NLB.
- C. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- D. Create an AWS Global Accelerator accelerator in front of the NLB. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator.
- E. Place the EC2 instances behind an Application Load Balancer (ALB). Configure TCP listener
- F. Create an AWS Global Accelerator accelerator in front of the ALB
- G. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator
- H. Place the EC2 instances behind an Amazon CloudFront distributio
- I. Use Bring Your Own IP (BYOIP) from the on-premises network with CloudFront.

Answer: B

NEW QUESTION 2

A company has developed an application on AWS that will track inventory levels of vending machines and initiate the restocking process automatically. The company plans to integrate this application with vending machines and deploy the vending machines in several markets around the world. The application resides in a VPC in the us-east-1 Region. The application consists of an Amazon Elastic Container Service (Amazon ECS) cluster behind an Application Load Balancer (ALB). The communication from the vending machines to the application happens over HTTPS.

The company is planning to use an AWS Global Accelerator accelerator and configure static IP addresses of the accelerator in the vending machines for application endpoint access. The application must be accessible only through the accelerator and not through a direct connection over the internet to the ALB endpoint.

Which solution will meet these requirements?

- A. Configure the ALB in a private subnet of the VP
- B. Attach an internet gateway without adding routes in the subnet route tables to point to the internet gatewa
- C. Configure the accelerator with endpoint groups that include the ALB endpoint
- D. Configure the ALB's security group to only allow inbound traffic from the internet on the ALB listener port.
- E. Configure the ALB in a private subnet of the VP
- F. Configure the accelerator with endpoint groups that include the ALB endpoint
- G. Configure the ALB's security group to only allow inbound traffic from the internet on the ALB listener port.
- H. Configure the ALB in a public subnet of the VP. Attach an internet gatewa
- I. Add routes in the subnet route tables to point to the internet gatewa
- J. Configure the accelerator with endpoint groups that include the ALB endpoint
- K. Configure the ALB's security group to only allow inbound traffic from the accelerator's IP addresses on the ALB listener port.
- L. Configure the ALB in a private subnet of the VP
- M. Attach an internet gatewa
- N. Add routes in the subnet route tables to point to the internet gatewa
- O. Configure the accelerator with endpoint groups that include the ALB endpoint
- P. Configure the ALB's security group to only allow inbound traffic from the accelerator's IP addresses on the ALB listener port.

Answer: A

Explanation:

Please read the below link typically describing ELB integration with AWS Global accelerator (and the last line of the extract) - <https://docs.aws.amazon.com/global-accelerator/latest/dg/secure-vpc-connections.html> "When you add an internal Application Load Balancer or an Amazon EC2 instance endpoint in AWS Global Accelerator, you enable internet traffic to flow directly to and from the endpoint in Virtual Private Clouds (VPCs) by targeting it in a private subnet. The VPC that contains the load balancer or EC2 instance must have an internet gateway attached to it, to indicate that the VPC accepts internet traffic. However, you don't need public IP addresses on the load balancer or EC2 instance. You also don't need an associated internet gateway route for the subnet."

NEW QUESTION 3

A data analytics company has a 100-node high performance computing (HPC) cluster. The HPC cluster is for parallel data processing and is hosted in a VPC in the AWS Cloud. As part of the data processing workflow, the HPC cluster needs to perform several DNS queries to resolve and connect to Amazon RDS databases, Amazon S3 buckets, and on-premises data stores that are accessible through AWS Direct Connect. The HPC cluster can increase in size by five to seven times during the company's peak event at the end of the year.

The company is using two Amazon EC2 instances as primary DNS servers for the VPC. The EC2 instances are configured to forward queries to the default VPC resolver for Amazon Route 53 hosted domains and to the on-premises DNS servers for other on-premises hosted domain names. The company notices job failures and finds that DNS queries from the HPC cluster nodes failed when the nodes tried to resolve RDS and S3 bucket endpoints.

Which architectural change should a network engineer implement to provide the DNS service in the MOST scalable way?

- A. Scale out the DNS service by adding two additional EC2 instances in the VP
- B. Reconfigure half of the HPC cluster nodes to use these new DNS server
- C. Plan to scale out by adding additional EC2 instance-based DNS servers in the future as the HPC cluster size grows.
- D. Scale up the existing EC2 instances that the company is using as DNS server
- E. Change the instance size to the largest possible instance size to accommodate the current DNS load and the anticipated load in the future.
- F. Create Route 53 Resolver outbound endpoint
- G. Create Route 53 Resolver rules to forward queries to on-premises DNS servers for on premises hosted domain name
- H. Reconfigure the HPC cluster nodes to use the default VPC resolver instead of the EC2 instance-based DNS server
- I. Terminate the EC2 instances.
- J. Create Route 53 Resolver inbound endpoint
- K. Create rules on the on-premises DNS servers to forward queries to the default VPC resolve
- L. Reconfigure the HPC cluster nodes to forward all DNS queries to the on-premises DNS server

M. Terminate the EC2 instances.

Answer: C

NEW QUESTION 4

A company has its production VPC (VPC-A) in the eu-west-1 Region in Account 1. VPC-A is attached to a transit gateway (TGW-A) that is connected to an on-premises data center in Dublin, Ireland, by an AWS

Direct Connect transit VIF that is configured for an AWS Direct Connect gateway. The company also has a staging VPC (VPC-B) that is attached to another transit gateway (TGW-B) in the eu-west-2 Region in Account 2.

A network engineer must implement connectivity between VPC-B and the on-premises data center in Dublin. Which solutions will meet these requirements? (Choose two.)

- A. Configure inter-Region VPC peering between VPC-A and VPC-
- B. Add the required VPC peering route
- C. Add the VPC-B CIDR block in the allowed prefixes on the Direct Connect gateway association.
- D. Associate TGW-B with the Direct Connect gateway
- E. Advertise the VPC-B CIDR block under the allowed prefixes.
- F. Configure another transit VIF on the Direct Connect connection and associate TGW-
- G. Advertise the VPC-B CIDR block under the allowed prefixes.
- H. Configure inter-Region transit gateway peering between TGW-A and TGW-
- I. Add the peering routes in the transit gateway route table
- J. Add both the VPC-A and the VPC-B CIDR block under the allowed prefix list in the Direct Connect gateway association.
- K. Configure an AWS Site-to-Site VPN connection over the transit VIF to TGW-B as a VPN attachment.

Answer: BC

Explanation:

* B. Associate TGW-B with the Direct Connect gateway. Advertise the VPC-B CIDR block under the allowed prefixes. This will allow traffic from VPC-B to be sent over the Direct Connect connection to the on-premises data center via TGW-B. C. Configure another transit VIF on the Direct Connect connection and associate TGW-B. Advertise the VPC-B CIDR block under the allowed prefixes. This will enable the use of the Direct Connect connection for VPC-B's traffic by connecting TGW-B to the Direct Connect gateway.

NEW QUESTION 5

A software-as-a-service (SaaS) provider hosts its solution on Amazon EC2 instances within a VPC in the AWS Cloud. All of the provider's customers also have their environments in the AWS Cloud.

A recent design meeting revealed that the customers have IP address overlap with the provider's AWS deployment. The customers have stated that they will not share their internal IP addresses and that they do not want to connect to the provider's SaaS service over the internet.

Which combination of steps is part of a solution that meets these requirements? (Choose two.)

- A. Deploy the SaaS service endpoint behind a Network Load Balancer.
- B. Configure an endpoint service, and grant the customers permission to create a connection to the endpoint service.
- C. Deploy the SaaS service endpoint behind an Application Load Balancer.
- D. Configure a VPC peering connection to the customer VPC
- E. Route traffic through NAT gateways.
- F. Deploy an AWS Transit Gateway, and connect the SaaS VPC to i
- G. Share the transit gateway with the customer
- H. Configure routing on the transit gateway.

Answer: AB

Explanation:

NLB for creating the private link which solves the overlapping IP address issue and the SaaS service endpoint behind it. (the SaaS endpoint could be an ALB)
<https://aws.amazon.com/about-aws/whats-new/2021/09/application-load-balancer-aws-privatelink-static-ip>

NEW QUESTION 6

Your company runs an application for the US market in the us-east-1 AWS region. This application uses proprietary TCP and UDP protocols on Amazon Elastic Compute Cloud (EC2) instances. End users run a

real-time, front-end application on their local PCs. This front-end application knows the DNS hostname of the service.

You must prepare the system for global expansion. The end users must access the application with lowest latency.

How should you use AWS services to meet these requirements?

- A. Register the IP addresses of the service hosts as "A" records with latency-based routing policy in Amazon Route 53, and set a Route 53 health check for these hosts.
- B. Set the Elastic Load Balancing (ELB) load balancer in front of the hosts of the service, and register the ELB name of the main service host as an ALIAS record with a latency-based routing policy in Route 53.
- C. Set Amazon CloudFront in front of the host of the service, and register the CloudFront name of the main service as an ALIAS record in Route 53.
- D. Set the Amazon API gateway in front of the service, and register the API gateway name of the main service as an ALIAS record in Route 53.

Answer: B

NEW QUESTION 7

A customer has set up multiple VPCs for Dev, Test, Prod, and Management. You need to set up AWS Direct Connect to enable data flow from on-premises to each VPC. The customer has monitoring software running in the Management VPC that collects metrics from the instances in all the other VPCs. Due to budget requirements, data transfer charges should be kept at minimum.

Which design should be recommended?

- A. Create a total of four private VIFs, one for each VPC owned by the customer, and route traffic between VPCs using the Direct Connect link.
- B. Create a private VIF to the Management VPC, and peer this VPC to all other VPCs.
- C. Create a private VIF to the Management VPC, and peer this VPC to all other VPCs, enable source/destination NAT in the Management VPC.

D. Create a total of four private VIFs, and enable VPC peering between all VPCs.

Answer: D

Explanation:

- creating VPC peering is free of charge - traffic costs ~0.01€/GB for VPC peering (IN + OUT) and ~0.02€/GB for direct connect (OUT only). As the communication involved in monitoring will never have IN == OUT, then $0.01 * (IN + OUT)$ will always be lower than $0.02 * OUT$, ergo VPC peering will be cheaper

NEW QUESTION 8

A company has two AWS accounts one for Production and one for Connectivity. A network engineer needs to connect the Production account VPC to a transit gateway in the Connectivity account. The feature to auto accept shared attachments is not enabled on the transit gateway. Which set of steps should the network engineer follow in each AWS account to meet these requirements?

- A. * 1. In the Production account: Create a resource share in AWS Resource Access Manager for the transit gateway
- B. Provide the Connectivity account ID
- C. Enable the feature to allow external accounts* 2. In the Connectivity account: Accept the resource.* 3. In the Connectivity account: Create an attachment to the VPC subnets.* 4. In the Production account: Accept the attachment
- D. Associate a route table with the attachment.
- E. * 1. In the Production account: Create a resource share in AWS Resource Access Manager for the VPC subnet
- F. Provide the Connectivity account ID
- G. Enable the feature to allow external accounts.* 2. In the Connectivity account: Accept the resource.* 3. In the Production account: Create an attachment on the transit gateway to the VPC subnets.* 4. In the Connectivity account: Accept the attachment
- H. Associate a route table with the attachment.
- I. * 1. In the Connectivity account: Create a resource share in AWS Resource Access Manager for the VPC subnet
- J. Provide the Production account ID
- K. Enable the feature to allow external accounts.* 2. In the Production account: Accept the resource.* 3. In the Connectivity account: Create an attachment on the transit gateway to the VPC subnets.* 4. In the Production account: Accept the attachment
- L. Associate a route table with the attachment.
- M. * 1. In the Connectivity account: Create a resource share in AWS Resource Access Manager for the transit gateway
- N. Provide the Production account ID Enable the feature to allow external accounts.* 2. In the Production account: Accept the resource.* 3. In the Production account: Create an attachment to the VPC subnets.* 4. In the Connectivity account: Accept the attachment
- O. Associate a route table with the attachment.

Answer: A

Explanation:

step 1: In the Production account, create a resource share in AWS Resource Access Manager for the transit gateway and provide the Connectivity account ID. Enabling the feature to allow external accounts is also required to share resources between accounts. Step 2: In the Connectivity account, accept the shared resource. This action will allow the Production account to use the transit gateway in the Connectivity account. Step 3: In the Connectivity account, create an attachment to the VPC subnets. This attachment will enable communication between the VPC in the Production account and the transit gateway in the Connectivity account. Step 4: In the Production account, accept the attachment and associate a route table with the attachment. This will enable the VPC to route traffic through the transit gateway to other resources in the Connectivity account.

NEW QUESTION 9

A company is planning a migration of its critical workloads from an on-premises data center to Amazon EC2 instances. The plan includes a new 10 Gbps AWS Direct Connect dedicated connection from the on-premises data center to a VPC that is attached to a transit gateway. The migration must occur over encrypted paths between the on-premises data center and the AWS Cloud. Which solution will meet these requirements while providing the HIGHEST throughput?

- A. Configure a public VIF on the Direct Connect connection
- B. Configure an AWS Site-to-Site VPN connection to the transit gateway as a VPN attachment.
- C. Configure a transit VIF on the Direct Connect connection
- D. Configure an IPsec VPN connection to an EC2 instance that is running third-party VPN software.
- E. Configure MACsec for the Direct Connect connection
- F. Configure a transit VIF to a Direct Connect gateway that is associated with the transit gateway.
- G. Configure a public VIF on the Direct Connect connection
- H. Configure two AWS Site-to-Site VPN connections to the transit gateway
- I. Enable equal-cost multi-path (ECMP) routing.

Answer: C

Explanation:

<https://aws.amazon.com/blogs/networking-and-content-delivery/adding-macsec-security-to-aws-direct-connect-c>

NEW QUESTION 10

A company is building its website on AWS in a single VPC. The VPC has public subnets and private subnets in two Availability Zones. The website has static content such as images. The company is using Amazon S3 to store the content.

The company has deployed a fleet of Amazon EC2 instances as web servers in a private subnet. The EC2 instances are in an Auto Scaling group behind an Application Load Balancer. The EC2 instances will serve traffic, and they must pull content from an S3 bucket to render the webpages. The company is using AWS Direct Connect with a public VIF for on-premises connectivity to the S3 bucket.

A network engineer notices that traffic between the EC2 instances and Amazon S3 is routing through a NAT gateway. As traffic increases, the company's costs are increasing. The network engineer needs to change the connectivity to reduce the NAT gateway costs that result from the traffic between the EC2 instances and Amazon S3.

Which solution will meet these requirements?

- A. Create a Direct Connect private VIF
- B. Migrate the traffic from the public VIF to the private VIF.
- C. Create an AWS Site-to-Site VPN tunnel over the existing public VIF.
- D. Implement interface VPC endpoints for Amazon S3. Update the VPC route table.

E. Implement gateway VPC endpoints for Amazon S3. Update the VPC route table.

Answer: D

NEW QUESTION 10

An IoT company sells hardware sensor modules that periodically send out temperature, humidity, pressure, and location data through the MQTT messaging protocol. The hardware sensor modules send this data to the company's on-premises MQTT brokers that run on Linux servers behind a load balancer. The hardware sensor modules have been hardcoded with public IP addresses to reach the brokers.

The company is growing and is acquiring customers across the world. The existing solution can no longer scale and is introducing additional latency because of the company's global presence. As a result, the company decides to migrate its entire infrastructure from on premises to the AWS Cloud. The company needs to migrate without reconfiguring the hardware sensor modules that are already deployed across the world. The solution also must minimize latency.

The company migrates the MQTT brokers to run on Amazon EC2 instances. What should the company do next to meet these requirements?

- A. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- B. Use Bring Your Own IP (BYOIP) from the on-premises network with the NLB.
- C. Place the EC2 instances behind a Network Load Balancer (NLB). Configure TCP listener
- D. Create an AWS Global Accelerator accelerator in front of the NLB. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator.
- E. Place the EC2 instances behind an Application Load Balancer (ALB). Configure TCP listener
- F. Create an AWS Global Accelerator accelerator in front of the ALB
- G. Use Bring Your Own IP (BYOIP) from the on-premises network with Global Accelerator
- H. Place the EC2 instances behind an Amazon CloudFront distribution
- I. Use Bring Your Own IP (BYOIP) from the on-premises network with CloudFront.

Answer: B

NEW QUESTION 14

A company has expanded its network to the AWS Cloud by using a hybrid architecture with multiple AWS accounts. The company has set up a shared AWS account for the connection to its on-premises data centers and the company offices. The workloads consist of private web-based services for internal use. These services run in different AWS accounts. Office-based employees consume these services by using a DNS name in an on-premises DNS zone that is named example.internal.

The process to register a new service that runs on AWS requires a manual and complicated change request to the internal DNS. The process involves many teams.

The company wants to update the DNS registration process by giving the service creators access that will allow them to register their DNS records. A network engineer must design a solution that will achieve this goal. The solution must maximize cost-effectiveness and must require the least possible number of configuration changes.

Which combination of steps should the network engineer take to meet these requirements? (Choose three.)

- A. Create a record for each service in its local private hosted zone (serviceA.account1.aws.example.internal). Provide this DNS record to the employees who need access.
- B. Create an Amazon Route 53 Resolver inbound endpoint in the shared account VPC
- C. Create a conditional forwarder for a domain named aws.example.internal on the on-premises DNS server
- D. Set the forwarding IP addresses to the inbound endpoint's IP addresses that were created.
- E. Create an Amazon Route 53 Resolver rule to forward any queries made to onprem.example.internal to the on-premises DNS servers.
- F. Create an Amazon Route 53 private hosted zone named aws.example.internal in the shared AWS account to resolve queries for this domain.
- G. Launch two Amazon EC2 instances in the shared AWS account
- H. Install BIND on each instance
- I. Create a DNS conditional forwarder on each BIND server to forward queries for each subdomain under aws.example.internal to the appropriate private hosted zone in each AWS account
- J. Create a conditional forwarder for a domain named aws.example.internal on the on-premises DNS server
- K. Set the forwarding IP addresses to the IP addresses of the BIND servers.
- L. Create a private hosted zone in the shared AWS account for each account that runs the service. Configure the private hosted zone to contain aws.example.internal in the domain (account1.aws.example.internal). Associate the private hosted zone with the VPC that runs the service and the shared account VPC.

Answer: ABD

Explanation:

To meet the requirements of updating the DNS registration process while maximizing cost-effectiveness and minimizing configuration changes, the network engineer should take the following steps:

- Create an Amazon Route 53 Resolver inbound endpoint in the shared account VPC. Create a conditional forwarder for a domain named aws.example.internal on the on-premises DNS servers. Set the forwarding IP addresses to the inbound endpoint's IP addresses that were created (Option B).
- Create an Amazon Route 53 private hosted zone named aws.example.internal in the shared AWS account to resolve queries for this domain (Option D).
- Create a record for each service in its local private hosted zone (serviceA.account1.aws.example.internal). Provide this DNS record to the employees who need access (Option A).

These steps will allow service creators to register their DNS records while keeping costs low and minimizing configuration changes.

NEW QUESTION 18

A company is using Amazon Route 53 Resolver DNS Firewall in a VPC to block all domains except domains that are on an approved list. The company is concerned that if DNS Firewall is unresponsive, resources in the VPC might be affected if the network cannot resolve any DNS queries. To maintain application service level agreements, the company needs DNS queries to continue to resolve even if Route 53 Resolver does not receive a response from DNS Firewall.

Which change should a network engineer implement to meet these requirements?

- A. Update the DNS Firewall VPC configuration to disable fail open for the VPC.
- B. Update the DNS Firewall VPC configuration to enable fail open for the VPC.
- C. Create a new DHCP options set with parameter dns_firewall_fail_open=fals
- D. Associate the new DHCP options set with the VPC.
- E. Create a new DHCP options set with parameter dns_firewall_fail_open=tru
- F. Associate the new DHCP options set with the VPC.

Answer: B

NEW QUESTION 21

A company is deploying a non-web application on an AWS load balancer. All targets are servers located on-premises that can be accessed by using AWS Direct Connect. The company wants to ensure that the source IP addresses of clients connecting to the application are passed all the way to the end server. How can this requirement be achieved?

- A. Use a Network Load Balancer to automatically preserve the source IP address.
- B. Use a Network Load Balancer and enable the X-Forwarded-For attribute.
- C. Use a Network Load Balancer and enable the ProxyProtocol v2 attribute.
- D. Use an Application Load Balancer to automatically preserve the source IP address in the X-Forwarded-For header.

Answer: C

Explanation:

<https://docs.aws.amazon.com/elasticloadbalancing/latest/network/load-balancer-target-groups.html#proxy-protocol>

NEW QUESTION 22

A network engineer must provide additional safeguards to protect encrypted data at Application Load Balancers (ALBs) through the use of a unique random session key. What should the network engineer do to meet this requirement?

- A. Change the ALB security policy to a policy that supports TLS 1.2 protocol only
- B. Use AWS Key Management Service (AWS KMS) to encrypt session keys
- C. Associate an AWS WAF web ACL with the ALB
- D. and create a security rule to enforce forward secrecy (FS)
- E. Change the ALB security policy to a policy that supports forward secrecy (FS)

Answer: D

NEW QUESTION 25

A global company operates all its non-production environments out of three AWS Regions: eu-west-1, us-east-1, and us-west-1. The company hosts all its production workloads in two on-premises data centers. The company has 60 AWS accounts and each account has two VPCs in each Region. Each VPC has a virtual private gateway where two VPN connections terminate for resilient connectivity to the data centers. The company has 360 VPN tunnels to each data center, resulting in high management overhead. The total VPN throughput for each Region is 500 Mbps. The company wants to migrate the production environments to AWS. The company needs a solution that will simplify the network architecture and allow for future growth. The production environments will generate an additional 2 Gbps of traffic per Region back to the data centers. This traffic will increase over time. Which solution will meet these requirements?

- A. Set up an AWS Direct Connect connection from each data center to AWS in each Region
- B. Create and attach private VIFs to a single Direct Connect gateway
- C. Attach the Direct Connect gateway to all the VPC
- D. Remove the existing VPN connections that are attached directly to the virtual private gateways.
- E. Create a single transit gateway with VPN connections from each data center
- F. Share the transit gateway with each account by using AWS Resource Access Manager (AWS RAM). Attach the transit gateway to each VPC
- G. Remove the existing VPN connections that are attached directly to the virtual private gateways.
- H. Create a transit gateway in each Region with multiple newly commissioned VPN connections from each data center
- I. Share the transit gateways with each account by using AWS Resource Access Manager (AWS RAM). In each Region, attach the transit gateway to each VPC
- J. Remove the existing VPN connections that are attached directly to the virtual private gateways.
- K. Peer all the VPCs in each Region to a new VPC in each Region that will function as a centralized transit VPC
- L. Create new VPN connections from each data center to the transit VPC
- M. Terminate the original VPN connections that are attached to all the original VPC
- N. Retain the new VPN connection to the new transit VPC in each Region.

Answer: C

NEW QUESTION 30

A company has a hybrid cloud environment. The company's data center is connected to the AWS Cloud by an AWS Direct Connect connection. The AWS environment includes VPCs that are connected together in a hub-and-spoke model by a transit gateway. The AWS environment has a transit VIF with a Direct Connect gateway for on-premises connectivity.

The company has a hybrid DNS model. The company has configured Amazon Route 53 Resolver endpoints in the hub VPC to allow bidirectional DNS traffic flow. The company is running a backend application in one of the VPCs.

The company uses a message-oriented architecture and employs Amazon Simple Queue Service (Amazon SQS) to receive messages from other applications over a private network. A network engineer wants to use an interface VPC endpoint for Amazon SQS for this architecture. Client services must be able to access the endpoint service from on premises and from multiple VPCs within the company's AWS infrastructure.

Which combination of steps should the network engineer take to ensure that the client applications can resolve DNS for the interface endpoint? (Choose three.)

- A. Create the interface endpoint for Amazon SQS with the option for private DNS names turned on.
- B. Create the interface endpoint for Amazon SQS with the option for private DNS names turned off.
- C. Manually create a private hosted zone for sqs.us-east-1.amazonaws.com
- D. Add necessary records that point to the interface endpoint
- E. Associate the private hosted zones with other VPCs.
- F. Use the automatically created private hosted zone for sqs.us-east-1.amazonaws.com with previously created necessary records that point to the interface endpoint
- G. Associate the private hosted zones with other VPCs.
- H. Access the SQS endpoint by using the public DNS name sqs.us-east-1.amazonaws.com in VPCs and on premises.
- I. Access the SQS endpoint by using the private DNS name of the interface endpoint sqs.us-east-1.vpce.amazonaws.com in VPCs and on premises.

Answer: ADF

NEW QUESTION 31

A company has deployed a critical application on a fleet of Amazon EC2 instances behind an Application Load Balancer. The application must always be reachable on port 443 from the public internet. The application recently had an outage that resulted from an incorrect change to the EC2 security group. A network engineer needs to automate a way to verify the network connectivity between the public internet and the EC2 instances whenever a change is made to the security group. The solution also must notify the network engineer when the change affects the connection. Which solution will meet these requirements?

- A. Enable VPC Flow Logs on the elastic network interface of each EC2 instance to capture REJECT traffic on port 443. Publish the flow log records to a log group in Amazon CloudWatch Log
- B. Create a CloudWatch Logs metric filter for the log group for rejected traffi
- C. Create an alarm to notify the network engineer.
- D. Enable VPC Flow Logs on the elastic network interface of each EC2 instance to capture all traffic on port 443. Publish the flow log records to a log group in Amazon CloudWatch Log
- E. Create a CloudWatch Logs metric filter for the log group for all traffi
- F. Create an alarm to notify the network engineer
- G. Create a VPC Reachability Analyzer path on port 443. Specify the security group as the sourc
- H. Specify the EC2 instances as the destinatio
- I. Create an Amazon Simple Notification Service (Amazon SNS) topic to notify the network engineer when a change to the security group affects the connectio
- J. Create an AWS Lambda function to start Reachability Analyzer and to publish a message to the SNS topic in case the analyses fail Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke the Lambda function when a change to the security groupoccurs.
- K. Create a VPC Reachability Analyzer path on port 443. Specify the internet gateway of the VPC as the sourc
- L. Specify the EC2 instances as the destinatio
- M. Create an Amazon Simple Notification Service (Amazon SNS) topic to notify the network engineer when a change to the security group affects the connectio
- N. Create an AWS Lambda function to start Reachability Analyzer and to publish a message to the SNS topic in case the analyses fai
- O. Create an Amazon EventBridge (Amazon CloudWatch Events) rule to invoke the Lambda function when a change to the security group occurs.

Answer: C

NEW QUESTION 36

A software company offers a software-as-a-service (SaaS) accounting application that is hosted in the AWS Cloud The application requires connectivity to the company's on-premises network. The company has two redundant 10 GB AWS Direct Connect connections between AWS and its on-premises network to accommodate the growing demand for the application.

The company already has encryption between its on-premises network and the colocation. The company needs to encrypt traffic between AWS and the edge routers in the colocation within the next few months. The company must maintain its current bandwidth.

What should a network engineer do to meet these requirements with the LEAST operational overhead?

- A. Deploy a new public VIF with encryption on the existing Direct Connect connection
- B. Reroute traffic through the new public VIF.
- C. Create a virtual private gateway Deploy new AWS Site-to-Site VPN connections from on premises to the virtual private gateway Reroute traffic from the Direct Connect private VIF to the new VPNs.
- D. Deploy a new pair of 10 GB Direct Connect connections with MACse
- E. Configure MACsec on the edge router
- F. Reroute traffic to the new Direct Connect connection
- G. Decommission the original Direct Connect connections
- H. Deploy a new pair of 10 GB Direct Connect connections with MACse
- I. Deploy a new public VIF on the new Direct Connect connection
- J. Deploy two AWS Site-to-Site VPN connections on top of the new public VI
- K. Reroute traffic from the existing private VIF to the new Site-to-Site connection
- L. Decommission the original Direct Connect connections.

Answer: C

NEW QUESTION 41

A banking company is successfully operating its public mobile banking stack on AWS. The mobile banking stack is deployed in a VPC that includes private subnets and public subnets. The company is using IPv4 networking and has not deployed or supported IPv6 in the environment. The company has decided to adopt a third-party service provider's API and must integrate the API with the existing environment. The service provider's API requires the use of IPv6.

A network engineer must turn on IPv6 connectivity for the existing workload that is deployed in a private subnet. The company does not want to permit IPv6 traffic from the public internet and mandates that the company's servers must initiate all IPv6 connectivity. The network engineer turns on IPv6 in the VPC and in the private subnets.

Which solution will meet these requirements?

- A. Create an internet gateway and a NAT gateway in the VP
- B. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT gateway.
- C. Create an internet gateway and a NAT instance in the VP
- D. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT instance.
- E. Create an egress-only Internet gateway in the VPAdd a route to the existing subnet route tables topoint IPv6 traffic to the egress-only internet gateway.
- F. Create an egress-only internet gateway in the VP
- G. Configure a security group that denies all inbound traffi
- H. Associate the security group with the egress-only internet gateway.

Answer: C

NEW QUESTION 42

A company is planning to deploy many software-defined WAN (SD-WAN) sites. The company is using AWS Transit Gateway and has deployed a transit gateway in the required AWS Region. A network engineer needs to deploy the SD-WAN hub virtual appliance into a VPC that is connected to the transit gateway. The solution must support at least 5 Gbps of throughput from the SD-WAN hub virtual appliance to other VPCs that are attached to the transit gateway.

Which solution will meet these requirements?

- A. Create a new VPC for the SD-WAN hub virtual appliance
- B. Create two IPsec VPN connections between the SD-WAN hub virtual appliance and the transit gateway
- C. Configure BGP over the IPsec VPN connections
- D. Assign a new CIDR block to the transit gateway
- E. Create a new VPC for the SD-WAN hub virtual appliance
- F. Attach the new VPC to the transit gateway with a VPC attachment
- G. Add a transit gateway Connect attachment
- H. Create a Connect peer and specify the GRE and BGP parameter
- I. Create a route in the appropriate VPC for the SD-WAN hub virtual appliance to route to the transit gateway.
- J. Create a new VPC for the SD-WAN hub virtual appliance
- K. Attach the new VPC to the transit gateway with a VPC attachment
- L. Create two IPsec VPN connections between the SD-WAN hub virtual appliance and the transit gateway
- M. Configure BGP over the IPsec VPN connections.
- N. Assign a new CIDR block to the transit gateway
- O. Create a new VPC for the SD-WAN hub virtual appliance
- P. Attach the new VPC to the transit gateway with a VPC attachment
- Q. Add a transit gateway Connect attachment
- R. Create a Connect peer and specify the VXLAN and BGP parameter
- S. Create a route in the appropriate VPC for the SD-WAN hub virtual appliance to route to the transit gateway.

Answer: D

NEW QUESTION 43

A Network Engineer is provisioning a subnet for a load balancer that will sit in front of a fleet of application servers in a private subnet. There is limited IP space left in the VPC CIDR. The application has few users now but is expected to grow quickly to millions of users. What design will use the LEAST amount of IP space, while allowing for this growth?

- A. Use two /29 subnets for an Application Load Balancer in different Availability Zones.
- B. Use one /29 subnet for the Network Load Balance
- C. Add another VPC CIDR to the VPC to allow for future growth.
- D. Use two /28 subnets for a Network Load Balancer in different Availability Zones.
- E. Use one /28 subnet for an Application Load Balance
- F. Add another VPC CIDR to the VPC to allow for future growth.

Answer: C

NEW QUESTION 44

A bank built a new version of its banking application in AWS using containers that connect to an on-premises database over VPN connection. This application version requires users to also update their client application. The bank plans to deprecate the earlier client version. However, the company wants to keep supporting earlier clients through their on-premises version of the application to serve a small portion of the customers who haven't yet upgraded. What design will allow the company to serve both newer and earlier clients in the MOST efficient way?

- A. Use an Amazon Route 53 multivalue answer routing policy to route older client traffic to the on-premises application version and the rest of the traffic to the new AWS based version.
- B. Use a Classic Load Balancer for the new application
- C. Route all traffic to the new application by using an Elastic Load Balancing (ELB) load balancer DNS
- D. Define a user-agent-based rule on the backend servers to redirect earlier clients to the on-premises application.
- E. Use an Application Load Balancer for the new application
- F. Register both the new and earlier applications as separate target groups and use path-based routing to route traffic based on the application version.
- G. Use an Application Load Balancer for the new application
- H. Register both the new and earlier application backends as separate target group
- I. Use header-based routing to route traffic based on the application version.

Answer: D

NEW QUESTION 45

A company uses a hybrid architecture and has an AWS Direct Connect connection between its on-premises data center and AWS. The company has production applications that run in the on-premises data center. The company also has production applications that run in a VPC. The applications that run in the on-premises data center need to communicate with the applications that run in the VPC. The company is using corp.example.com as the domain name for the on-premises resources and is using an Amazon Route 53 private hosted zone for aws.example.com to host the VPC resources.

The company is using an open-source recursive DNS resolver in a VPC subnet and is using a DNS resolver in the on-premises data center. The company's on-premises DNS resolver has a forwarder that directs requests for the aws.example.com domain name to the DNS resolver in the VPC. The DNS resolver in the VPC has a forwarder that directs requests for the corp.example.com domain name to the DNS resolver in the on-premises data center. The company has decided to replace the open-source recursive DNS resolver with Amazon Route 53 Resolver endpoints.

Which combination of steps should a network engineer take to make this replacement? (Choose three.)

- A. Create a Route 53 Resolver rule to forward aws.example.com domain queries to the IP addresses of the outbound endpoint.
- B. Configure the on-premises DNS resolver to forward aws.example.com domain queries to the IP addresses of the inbound endpoint.
- C. Create a Route 53 Resolver inbound endpoint and a Route 53 Resolver outbound endpoint.
- D. Create a Route 53 Resolver rule to forward aws.example.com domain queries to the IP addresses of the inbound endpoint.
- E. Create a Route 53 Resolver rule to forward corp.example.com domain queries to the IP address of the on-premises DNS resolver.
- F. Configure the on-premises DNS resolver to forward aws.example.com queries to the IP addresses of the outbound endpoint.

Answer: BCE

Explanation:

To replace the open-source recursive DNS resolver with Amazon Route 53 Resolver endpoints in a hybrid architecture where on-premises applications need to communicate with applications running in a VPC, a network engineer should take the following steps:

- Create a Route 53 Resolver inbound endpoint and a Route 53 Resolver outbound endpoint. (Option C)

- Configure the on-premises DNS resolver to forward aws.example.com domain queries to the IP addresses of the inbound endpoint. (Option B)
- Create a Route 53 Resolver rule to forward corp.example.com domain queries to the IP address of the on-premises DNS resolver. (Option E)

These steps will allow for seamless replacement of the open-source recursive DNS resolver with Amazon Route 53 Resolver endpoints and enable communication between on-premises and VPC applications.

NEW QUESTION 46

A company is hosting an application on Amazon EC2 instances behind a Network Load Balancer (NLB). A solutions architect added EC2 instances in a second Availability Zone to improve the availability of the application. The solutions architect added the instances to the NLB target group.

The company's operations team notices that traffic is being routed only to the instances in the first Availability Zone.

What is the MOST operationally efficient solution to resolve this issue?

- A. Enable the new Availability Zone on the NLB
- B. Create a new NLB for the instances in the second Availability Zone
- C. Enable proxy protocol on the NLB
- D. Create a new target group with the instances in both Availability Zones

Answer: A

Explanation:

When adding instances in a new Availability Zone to an existing Network Load Balancer (NLB), it is important to ensure that the new Availability Zone is enabled on the NLB. This will allow traffic to be routed to instances in both Availability Zones. This can be done by editing the settings of the NLB and selecting the new Availability Zone from the list of available zones.

NEW QUESTION 50

A company uses AWS Direct Connect to connect its corporate network to multiple VPCs in the same AWS account and the same AWS Region. Each VPC uses its own private VIF and its own virtual LAN on the Direct Connect connection. The company has grown and will soon surpass the limit of VPCs and private VIFs for each connection.

What is the MOST scalable way to add VPCs with on-premises connectivity?

- A. Provision a new Direct Connect connection to handle the additional VPC
- B. Use the new connection to connect additional VPCs.
- C. Create virtual private gateways for each VPC that is over the service quot
- D. Use AWS Site-to-Site VPNto connect the virtual private gateways to the corporate network.
- E. Create a Direct Connect gateway, and add virtual private gateway associations to the VPC
- F. Configure a private VIF to connect to the corporate network.
- G. Create a transit gateway, and attach the VPC
- H. Create a Direct Connect gateway, and associate it with the transit gatewa
- I. Create a transit VIF to the Direct Connect gateway.

Answer: D

Explanation:

When a company requires connectivity to multiple VPCs over AWS Direct Connect, a scalable solution is to use a transit gateway. A transit gateway is a hub that can interconnect multiple VPCs and VPN connections. The VPCs can communicate with each other over the transitgateway, and on-premises networks can communicate with the VPCs through the Direct Connect gateway. This solution provides a central point of management and simplifies the configuration of network routing. By associating the Direct Connect gateway with the transit gateway, traffic between the VPCs and the on-premises network can be routed through the Direct Connect connection.

NEW QUESTION 54

A company is running multiple workloads on Amazon EC2 instances in public subnets. In a recent incident, an attacker exploited an application vulnerability on one of the EC2 instances to gain access to the instance. The company fixed the application and launched a replacement EC2 instance that contains the updated application.

The attacker used the compromised application to spread malware over the internet. The company became aware of the compromise through a notification from AWS. The company needs the ability to identify when an application that is deployed on an EC2 instance is spreading malware.

Which solution will meet this requirement with the LEAST operational effort?

- A. Use Amazon GuardDuty to analyze traffic patterns by inspecting DNS requests and VPC flow logs.
- B. Use Amazon GuardDuty to deploy AWS managed decoy systems that are equipped with the most recent malware signatures.
- C. Set up a Gateway Load Balance
- D. Run an intrusion detection system (IDS) appliance from AWS Marketplace on Amazon EC2 for traffic inspection.
- E. Configure Amazon Inspector to perform deep packet inspection of outgoing traffic.

Answer: A

Explanation:

This solution involves using Amazon GuardDuty to monitor network traffic and analyze DNS requests and VPC flow logs for suspicious activity. This will allow the company to identify when an application is spreading malware by monitoring the network traffic patterns associated with the instance. GuardDuty is a fully managed threat detection service that continuously monitors for malicious activity and unauthorized behavior in your AWS accounts and workloads. It requires minimal setup and configuration and can be integrated with other AWS services for automated remediation. This solution requires the least operational effort compared to the other options

NEW QUESTION 56

A network engineer is designing the architecture for a healthcare company's workload that is moving to the AWS Cloud. All data to and from the on-premises environment must be encrypted in transit. All traffic also must be inspected in the cloud before the traffic is allowed to leave the cloud and travel to the on-premises environment or to the internet.

The company will expose components of the workload to the internet so that patients can reserve appointments. The architecture must secure these components and protect them against DDoS attacks. The architecture also must provide protection against financial liability for services that scale out during a DDoS event.

Which combination of steps should the network engineer take to meet all these requirements for the workload? (Choose three.)

- A. Use Traffic Mirroring to copy all traffic to a fleet of traffic capture appliances.
- B. Set up AWS WAF on all network components.
- C. Configure an AWS Lambda function to create Deny rules in security groups to block malicious IP addresses.
- D. Use AWS Direct Connect with MACsec support for connectivity to the cloud.
- E. Use Gateway Load Balancers to insert third-party firewalls for inline traffic inspection.
- F. Configure AWS Shield Advanced and ensure that it is configured on all public assets.

Answer: DEF

Explanation:

To meet the requirements for the healthcare company's workload that is moving to the AWS Cloud, the network engineer should take the following steps:

- Use AWS Direct Connect with MACsec support for connectivity to the cloud to ensure that all data to and from the on-premises environment is encrypted in transit (Option D).
- Use Gateway Load Balancers to insert third-party firewalls for inline traffic inspection to inspect all traffic in the cloud before it is allowed to leave (Option E).
- Configure AWS Shield Advanced and ensure that it is configured on all public assets to secure components exposed to the internet against DDoS attacks and provide protection against financial liability for services that scale out during a DDoS event (Option F).

These steps will help ensure that all data is encrypted in transit, all traffic is inspected before leaving the cloud, and components exposed to the internet are secured against DDoS attacks.

NEW QUESTION 58

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your ANS-C01 Exam with Our Prep Materials Via below:

<https://www.certleader.com/ANS-C01-dumps.html>