

CompTIA

Exam Questions N10-008

CompTIA Network+Exam



NEW QUESTION 1

- (Exam Topic 1)

An engineer is configuring redundant network links between switches. Which of the following should the engineer enable to prevent network stability issues?

- A. 802.1Q
- B. STP
- C. Flow control
- D. CSMA/CD

Answer: B

NEW QUESTION 2

- (Exam Topic 1)

A network administrator is designing a new datacenter in a different region that will need to communicate to the old datacenter with a secure connection. Which of the following access methods would provide the BEST security for this new datacenter?

- A. Virtual network computing
- B. Secure Socket Shell
- C. In-band connection
- D. Site-to-site VPN

Answer: D

NEW QUESTION 3

- (Exam Topic 1)

Which of the following is the LARGEST MTU for a standard Ethernet frame?

- A. 1452
- B. 1492
- C. 1500
- D. 2304

Answer: C

NEW QUESTION 4

- (Exam Topic 1)

Which of the following can be used to centrally manage credentials for various types of administrative privileges on configured network devices?

- A. SSO
- B. TACACS+
- C. Zero Trust
- D. Separation of duties
- E. Multifactor authentication

Answer: B

NEW QUESTION 5

- (Exam Topic 1)

A technician is troubleshooting a wireless connectivity issue in a small office located in a high-rise building. Several APs are mounted in this office. The users report that the network connections frequently disconnect and reconnect throughout the day. Which of the following is the MOST likely cause of this issue?

- A. The AP association time is set too low
- B. EIRP needs to be boosted
- C. Channel overlap is occurring
- D. The RSSI is misreported

Answer: B

NEW QUESTION 6

- (Exam Topic 1)

Branch users are experiencing issues with videoconferencing. Which of the following will the company MOST likely configure to improve performance for these applications?

- A. Link Aggregation Control Protocol
- B. Dynamic routing
- C. Quality of service
- D. Network load balancer
- E. Static IP addresses

Answer: C

NEW QUESTION 7

- (Exam Topic 1)

An administrator is writing a script to periodically log the IPv6 and MAC addresses of all the devices on a network segment. Which of the following switch features will MOST likely be used to assist with this task?

- A. Spanning Tree Protocol
- B. Neighbor Discovery Protocol
- C. Link Aggregation Control Protocol
- D. Address Resolution Protocol

Answer: B

NEW QUESTION 8

- (Exam Topic 1)

A technician is connecting multiple switches to create a large network for a new office. The switches are unmanaged Layer 2 switches with multiple connections between each pair. The network is experiencing an extreme amount of latency. Which of the following is MOST likely occurring?

- A. Ethernet collisions
- B. A DDoS attack
- C. A broadcast storm
- D. Routing loops

Answer: C

NEW QUESTION 9

- (Exam Topic 1)

A technician is installing multiple UPS units in a major retail store. The technician is required to keep track of all changes to new and old equipment. Which of the following will allow the technician to record these changes?

- A. Asset tags
- B. A smart locker
- C. An access control vestibule
- D. A camera

Answer: A

NEW QUESTION 10

- (Exam Topic 1)

Which of the following provides redundancy on a file server to ensure the server is still connected to a LAN even in the event of a port failure on a switch?

- A. NIC teaming
- B. Load balancer
- C. RAID array
- D. PDUs

Answer: A

NEW QUESTION 10

- (Exam Topic 1)

A network technician is manually configuring the network settings for a new device and is told the network block is 192.168.0.0/20. Which of the following subnets should the technician use?

- A. 255.255.128.0
- B. 255.255.192.0
- C. 255.255.240.0
- D. 255.255.248.0

Answer: C

NEW QUESTION 15

- (Exam Topic 1)

A network administrator walks into a datacenter and notices an unknown person is following closely. The administrator stops and directs the person to the security desk. Which of the following attacks did the network administrator prevent?

- A. Evil twin
- B. Tailgating
- C. Piggybacking
- D. Shoulder surfing

Answer: B

NEW QUESTION 20

- (Exam Topic 1)

A website administrator is concerned the company's static website could be defaced by hackers or used as a pivot point to attack internal systems. Which of the following should a network security administrator recommend to assist with detecting these activities?

- A. Implement file integrity monitoring.
- B. Change the default credentials.
- C. Use SSL encryption.
- D. Update the web-server software.

Answer: C

NEW QUESTION 23

- (Exam Topic 1)

Which of the following connector types would have the MOST flexibility?

- A. SFP
- B. BNC
- C. LC
- D. RJ45

Answer: A

NEW QUESTION 25

- (Exam Topic 1)

A technician wants to deploy a new wireless network that comprises 30 WAPs installed throughout a three-story office building. All the APs will broadcast the same SSID for client access. Which of the following BEST describes this deployment?

- A. Extended service set
- B. Basic service set
- C. Unified service set
- D. Independent basic service set

Answer: B

NEW QUESTION 30

- (Exam Topic 1)

A network administrator is implementing OSPF on all of a company's network devices. Which of the following will MOST likely replace all the company's hubs?

- A. A Layer 3 switch
- B. A proxy server
- C. A NGFW
- D. A WLAN controller

Answer: A

NEW QUESTION 31

- (Exam Topic 1)

Which of the following types of devices can provide content filtering and threat protection, and manage multiple IPSec site-to-site connections?

- A. Layer 3 switch
- B. VPN headend
- C. Next-generation firewall
- D. Proxy server
- E. Intrusion prevention

Answer: C

NEW QUESTION 36

- (Exam Topic 1)

A technician is deploying a new switch model and would like to add it to the existing network monitoring software. The technician wants to know what metrics can be gathered from a given switch. Which of the following should the technician utilize for the switch?

- A. MIB
- B. Trap
- C. Syslog
- D. Audit log

Answer: A

NEW QUESTION 40

- (Exam Topic 1)

A network administrator needs to query the NSs for a remote application. Which of the following commands would BEST help the administrator accomplish this task?

- A. dig
- B. arp
- C. show interface
- D. hostname

Answer: A

NEW QUESTION 44

- (Exam Topic 1)

A technician receives feedback that some users are experiencing high amounts of jitter while using the wireless network. While troubleshooting the network, the

technician uses the ping command with the IP address of the default gateway and verifies large variations in latency. The technician thinks the issue may be interference from other networks and non-802.11 devices. Which of the following tools should the technician use to troubleshoot the issue?

- A. NetFlow analyzer
- B. Bandwidth analyzer
- C. Protocol analyzer
- D. Spectrum analyzer

Answer: D

NEW QUESTION 47

- (Exam Topic 1)

A systems administrator needs to improve WiFi performance in a densely populated office tower and use the latest standard. There is a mix of devices that use 2.4 GHz and 5 GHz. Which of the following should the systems administrator select to meet this requirement?

- A. 802.11ac
- B. 802.11ax
- C. 802.11g
- D. 802.11n

Answer: B

NEW QUESTION 50

- (Exam Topic 1)

A network device is configured to send critical events to a syslog server; however, the following alerts are not being received:

Severity 5 LINK-UPDOWN: Interface 1/1, changed state to down Severity 5 LINK-UPDOWN: Interface 1/3, changed state to down

Which of the following describes the reason why the events are not being received?

- A. The network device is not configured to log that level to the syslog server
- B. The network device was down and could not send the event
- C. The syslog server is not compatible with the network device
- D. The syslog server did not have the correct MIB loaded to receive the message

Answer: A

NEW QUESTION 53

- (Exam Topic 1)

Several WIFI users are reporting the inability to connect to the network. WLAN users on the guest network are able to access all network resources without any performance issues. The following table summarizes the findings after a site survey of the area in question:

Location	AP 1	AP 2	AP 3	AP 4
SSID	Corp1	Corp1	Corp1/Guest	Corp1/Guest
Channel	2	1	5	11
RSSI	-81dBm	-82dBm	-44dBm	-41dBm
Antenna type	Omni	Omni	Directional	Directional

Which of the following should a wireless technician do NEXT to troubleshoot this issue?

- A. Reconfigure the channels to reduce overlap
- B. Replace the omni antennas with directional antennas
- C. Update the SSIDs on all the APs
- D. Decrease power in AP 3 and AP 4

Answer: A

NEW QUESTION 55

- (Exam Topic 1)

A technician is assisting a user who cannot connect to a network resource. The technician first checks for a link light. According to troubleshooting methodology, this is an example of:

- A. using a bottom-to-top approach.
- B. establishing a plan of action.
- C. documenting a finding.
- D. questioning the obvious.

Answer: D

NEW QUESTION 57

- (Exam Topic 1)

A network technician is installing new software on a Windows-based server in a different geographical location. Which of the following would be BEST for the technician to use to perform this task?

- A. RDP
- B. SSH
- C. FTP
- D. DNS

Answer: A

NEW QUESTION 61

- (Exam Topic 1)

An IT director is setting up new disaster and HA policies for a company. Limited downtime is critical to operations. To meet corporate requirements, the director set up two different datacenters across the country that will stay current on data and applications. In the event of an outage, the company can immediately switch from one datacenter to another. Which of the following does this BEST describe?

- A. A warm site
- B. Data mirroring
- C. Multipathing
- D. Load balancing
- E. A hot site

Answer: E

NEW QUESTION 62

- (Exam Topic 1)

Access to a datacenter should be individually recorded by a card reader even when multiple employees enter the facility at the same time. Which of the following allows the enforcement of this policy?

- A. Motion detection
- B. Access control vestibules
- C. Smart lockers
- D. Cameras

Answer: B

Explanation:

The most effective security mechanism against physical intrusions due to stolen credentials would likely be a combination of several of these options. However, of the options provided, the most effective security mechanism would probably be an access control vestibule. An access control vestibule is a secure area that is located between the outer perimeter of a facility and the inner secure area. It is designed to provide an additional layer of security by requiring that individuals pass through a series of security checks before being allowed access to the secure area. This could include biometric authentication, access card readers, and motion detection cameras.

NEW QUESTION 63

- (Exam Topic 1)

A network administrator is configuring a load balancer for two systems. Which of the following must the administrator configure to ensure connectivity during a failover?

- A. VIP
- B. NAT
- C. APIPA
- D. IPv6 tunneling
- E. Broadcast IP

Answer: A

NEW QUESTION 67

- (Exam Topic 1)

A store owner would like to have secure wireless access available for both business equipment and patron use. Which of the following features should be configured to allow different wireless access through the same equipment?

- A. MIMO
- B. TKIP
- C. LTE
- D. SSID

Answer: D

NEW QUESTION 70

- (Exam Topic 1)

Which of the following routing protocols is used to exchange route information between public autonomous systems?

- A. OSPF
- B. BGP
- C. EGRIP
- D. RIP

Answer: B

NEW QUESTION 74

- (Exam Topic 1)

Which of the following BEST describes a network appliance that warns of unapproved devices that are accessing the network?

- A. Firewall
- B. AP

- C. Proxy server
- D. IDS

Answer: D

NEW QUESTION 76

- (Exam Topic 1)

A network engineer performs the following tasks to increase server bandwidth:

Connects two network cables from the server to a switch stack

Configure LACP on the switchports

Verifies the correct configurations on the switch interfaces

Which of the following needs to be configured on the server?

- A. Load balancing
- B. Multipathing
- C. NIC teaming
- D. Clustering

Answer: C

NEW QUESTION 78

- (Exam Topic 1)

Which of the following would need to be configured to ensure a device with a specific MAC address is always assigned the same IP address from DHCP?

- A. Scope options
- B. Reservation
- C. Dynamic assignment
- D. Exclusion
- E. Static assignment

Answer: B

NEW QUESTION 82

- (Exam Topic 1)

A technician needs to configure a Linux computer for network monitoring. The technician has the following information:

Linux computer details:

Interface	IP address	MAC address
eth0	10.1.2.24	A1:B2:C3:F4:E5:D6

Switch mirror port details:

Interface	IP address	MAC address
eth1	10.1.2.3	A1:B2:C3:D4:E5:F6

After connecting the Linux computer to the mirror port on the switch, which of the following commands should the technician run on the Linux computer?

- A. ifconfig eth0 promisc
- B. ifconfig eth1 up
- C. ifconfig eth0 10.1.2.3
- D. ifconfig eth1 hw ether A1:B2:C3:D4:E5:F6

Answer: A

NEW QUESTION 85

- (Exam Topic 1)

A network technician needs to ensure outside users are unable to telnet into any of the servers at the datacenter. Which of the following ports should be blocked when checking firewall configuration?

- A. 22
- B. 23
- C. 80
- D. 3389
- E. 8080

Answer: B

NEW QUESTION 89

- (Exam Topic 1)

At which of the following OSI model layers would a technician find an IP header?

- A. Layer 1
- B. Layer 2
- C. Layer 3
- D. Layer 4

Answer: C

NEW QUESTION 91

- (Exam Topic 1)

A branch of a company recently switched to a new ISP. The network engineer was given a new IP range to assign. The ISP assigned 196.26.4.0/26, and the branch gateway router now has the following configurations on the interface that peers to the ISP:

```
IP address:      196.26.4.30
Subnet mask:     255.255.255.224
Gateway:        196.24.4.1
```

The network engineer observes that all users have lost Internet connectivity. Which of the following describes the issue?

- A. The incorrect subnet mask was configured
- B. The incorrect gateway was configured
- C. The incorrect IP address was configured
- D. The incorrect interface was configured

Answer: A

NEW QUESTION 93

- (Exam Topic 1)

A technician is searching for a device that is connected to the network and has the device's physical network address. Which of the following should the technician review on the switch to locate the device's network port?

- A. IP route table
- B. VLAN tag
- C. MAC table
- D. QoS tag

Answer: C

NEW QUESTION 96

- (Exam Topic 1)

Which of the following would be BEST to use to detect a MAC spoofing attack?

- A. Internet Control Message Protocol
- B. Reverse Address Resolution Protocol
- C. Dynamic Host Configuration Protocol
- D. Internet Message Access Protocol

Answer: B

NEW QUESTION 97

- (Exam Topic 1)

Client devices cannot enter a network, and the network administrator determines the DHCP scope is exhausted. The administrator wants to avoid creating a new DHCP pool. Which of the following can the administrator perform to resolve the issue?

- A. Install load balancers
- B. Install more switches
- C. Decrease the number of VLANs
- D. Reduce the lease time

Answer: D

NEW QUESTION 98

- (Exam Topic 2)

A network administrator wants to improve the security of the management console on the company's switches and ensure configuration changes made can be correlated to the administrator who conformed them Which of the following should the network administrator implement?

- A. Port security
- B. Local authentication
- C. TACACS+
- D. Access control list

Answer: C

NEW QUESTION 102

- (Exam Topic 2)

Which of the following is a system that is installed directly on a server's hardware and abstracts the hardware from any guest machines?

- A. Storage array
- B. Type 1 hypervisor
- C. Virtual machine
- D. Guest QS

Answer: A

NEW QUESTION 105

- (Exam Topic 2)

There are two managed legacy switches running that cannot be replaced or upgraded. These switches do not support cryptographic functions, but they are password protected. Which of the following should a network administrator configure to BEST prevent unauthorized access?

- A. Enable a management access list
- B. Disable access to unnecessary services.
- C. Configure a stronger password for access
- D. Disable access to remote management
- E. Use an out-of-band access method.

Answer: A

NEW QUESTION 110

- (Exam Topic 2)

A small, family-run business uses a single SOHO router to provide Internet and WiFi to its employees. At the start of a new week, employees come in and find their usual WiFi network is no longer available, and there is a new wireless network to which they cannot connect. Given that information, which of the following should have been done to avoid this situation?

- A. The device firmware should have been kept current.
- B. Unsecure protocols should have been disabled.
- C. Parental controls should have been enabled
- D. The default credentials should have been changed

Answer: A

NEW QUESTION 115

- (Exam Topic 2)

A systems administrator is running a VoIP network and is experiencing jitter and high latency. Which of the following would BEST help the administrator determine the cause of these issues?

- A. Enabling RADIUS on the network
- B. Configuring SNMP traps on the network
- C. Implementing LDAP on the network
- D. Establishing NTP on the network

Answer: B

NEW QUESTION 117

- (Exam Topic 2)

To comply with industry requirements, a security assessment on the cloud server should identify which protocols and weaknesses are being exposed to attackers on the Internet. Which of the following tools is the MOST appropriate to complete the assessment?

- A. Use tcpdump and parse the output file in a protocol analyzer.
- B. Use an IP scanner and target the cloud WAN network addressing.
- C. Run netstat in each cloud server and retrieve the running processes.
- D. Use nmap and set the servers' public IPs as the targets.

Answer: D

NEW QUESTION 122

- (Exam Topic 2)

A network administrator is reviewing interface errors on a switch. Which of the following indicates that a switchport is receiving packets in excess of the configured MTU?

- A. CRC errors
- B. Giants
- C. Runts
- D. Flooding

Answer: B

NEW QUESTION 127

- (Exam Topic 2)

After a firewall replacement, some alarms and metrics related to network availability stopped updating on a monitoring system relying on SNMP. Which of the following should the network administrator do FIRST?

- A. Modify the device's MIB on the monitoring system.
- B. Configure syslog to send events to the monitoring system.
- C. Use port mirroring to redirect traffic to the monitoring system.
- D. Deploy SMB to transfer data to the monitoring system.

Answer: A

NEW QUESTION 132

- (Exam Topic 2)

An ARP request is broadcasted and sends the following request. "Who is 192.168.1.200? Tell 192.168.1.55"

At which of the following layers of the OSI model does this request operate?

- A. Application
- B. Data link
- C. Transport
- D. Network
- E. Session

Answer: B

NEW QUESTION 137

- (Exam Topic 2)

A network administrator decided to use SLAAC in an extensive IPv6 deployment to alleviate IP address management. The devices were properly connected into the LAN but autoconfiguration of the IP address did not occur as expected. Which of the following should the network administrator verify?

- A. The network gateway is configured to send router advertisements.
- B. A DHCP server is present on the same broadcast domain as the clients.
- C. The devices support dual stack on the network layer.
- D. The local gateway supports anycast routing.

Answer: A

NEW QUESTION 140

- (Exam Topic 2)

A firewall administrator is implementing a rule that directs HTTP traffic to an internal server listening on a non-standard socket Which of the following types of rules is the administrator implementing?

- A. NAT
- B. PAT
- C. STP
- D. SNAT
- E. ARP

Answer: D

NEW QUESTION 142

- (Exam Topic 2)

A network technician is installing an analog desk phone for a new receptionist After running a new phone line, the technician now needs to crimp on a new connector. Which of the following connectors would MOST likely be used in this case?

- A. DB9
- B. RJ11
- C. RJ45
- D. DB25

Answer: A

NEW QUESTION 144

- (Exam Topic 2)

A systems administrator is configuring a firewall using NAT with PAT. Which of the following would be BEST suited for the LAN interface?

- A. 172.15.0.0/18
- B. 172.18.0.0/10
- C. 172.23.0.0/16
- D. 172.28.0.0/8
- E. 172.32.0.0/14

Answer: C

NEW QUESTION 147

- (Exam Topic 2)

A rogue AP was found plugged in and providing Internet access to employees in the break room. Which of the following would be BEST to use to stop this from happening without physically removing the WAP?

- A. Password complexity
- B. Port security
- C. Wireless client isolation
- D. Secure SNMP

Answer: B

NEW QUESTION 148

- (Exam Topic 2)

A company wants to implement a large number of WAPs throughout its building and allow users to be able to move around the building without dropping their connections Which of the following pieces of equipment would be able to handle this requirement?

- A. A VPN concentrator

- B. A load balancer
- C. A wireless controller
- D. A RADIUS server

Answer: A

NEW QUESTION 152

- (Exam Topic 2)

Which of the following OSI model layers is where conversations between applications are established, coordinated, and terminated?

- A. Session
- B. Physical
- C. Presentation
- D. Data link

Answer: A

Explanation:

Reference: <https://www.techtarget.com/searchnetworking/definition/OSI#:~:text=The%20session%20layer,and%20termina>

NEW QUESTION 154

- (Exam Topic 2)

A wireless network was installed in a warehouse for employees to scan crates with a wireless handheld scanner. The wireless network was placed in the corner of the building near the ceiling for maximum coverage. However, users in the offices adjacent to the warehouse have noticed a large amount of signal overlap from the new network. Additionally, warehouse employees report difficulty connecting to the wireless network from the other side of the building; however, they have no issues when they are near the antenna. Which of the following is MOST likely the cause?

- A. The wireless signal is being refracted by the warehouse's windows
- B. The antenna's power level was set too high and is overlapping
- C. An omnidirectional antenna was used instead of a unidirectional antenna
- D. The wireless access points are using channels from the 5GHz spectrum

Answer: A

NEW QUESTION 157

- (Exam Topic 2)

Which of the following security devices would be BEST to use to provide mechanical access control to the MDF/IDF?

- A. A smart card
- B. A key fob
- C. An employee badge
- D. A door lock

Answer: B

NEW QUESTION 160

- (Exam Topic 2)

Which of the following technologies allows traffic to be sent through two different ISPs to increase performance?

- A. Fault tolerance
- B. Quality of service
- C. Load balancing
- D. Port aggregation

Answer: A

NEW QUESTION 163

- (Exam Topic 2)

At the destination host, which of the following OSI model layers will discard a segment with a bad checksum in the UDP header?

- A. Network
- B. Data link
- C. Transport
- D. Session

Answer: C

NEW QUESTION 168

- (Exam Topic 2)

A network technician is investigating an issue with handheld devices in a warehouse. Devices have not been connecting to the nearest APs, but they have been connecting to an AP on the far side of the warehouse. Which of the following is the MOST likely cause of this issue?

- A. The nearest APs are configured for 802.11g.
- B. An incorrect channel assignment is on the nearest APs.
- C. The power level is too high for the AP on the far side.
- D. Interference exists around the AP on the far side.

Answer: A

NEW QUESTION 172

- (Exam Topic 2)

A network technician has multimode fiber optic cable available in an existing IDF. Which of the following Ethernet standards should the technician use to connect the network switch to the existing fiber?

- A. 10GBaseT
- B. 1000BaseT
- C. 1000BaseSX
- D. 1000BaseLX

Answer: A

NEW QUESTION 176

- (Exam Topic 2)

A technician wants to install a WAP in the center of a room that provides service in a radius surrounding a radio. Which of the following antenna types should the AP utilize?

- A. Omni
- B. Directional
- C. Yagi
- D. Parabolic

Answer: A

NEW QUESTION 180

- (Exam Topic 2)

A company requires a disaster recovery site to have equipment ready to go in the event of a disaster at its main datacenter. The company does not have the budget to mirror all the live data to the disaster recovery site. Which of the following concepts should the company select?

- A. Cold site
- B. Hot site
- C. Warm site
- D. Cloud site

Answer: C

NEW QUESTION 181

- (Exam Topic 2)

Which of the following uses the destination IP address to forward packets?

- A. A bridge
- B. A Layer 2 switch
- C. A router
- D. A repeater

Answer: C

NEW QUESTION 184

- (Exam Topic 2)

A network technician was troubleshooting an issue for a user who was being directed to cloned websites that were stealing credentials. The URLs were correct for the websites but an incorrect IP address was revealed when the technician used ping on the user's PC. After checking the settings, the technician found the DNS server address was incorrect. Which of the following describes the issue?

- A. Rogue DHCP server
- B. Misconfigured HSRP
- C. DNS poisoning
- D. Exhausted IP scope

Answer: D

NEW QUESTION 189

- (Exam Topic 2)

A network technician needs to correlate security events to analyze a suspected intrusion. Which of the following should the technician use?

- A. SNMP
- B. Log review
- C. Vulnerability scanning
- D. SIEM

Answer: D

NEW QUESTION 190

- (Exam Topic 2)

A network administrator wants to analyze attacks directed toward the company's network. Which of the following must the network administrator implement to assist in this goal?

- A. A honeypot
- B. Network segmentation
- C. Antivirus
- D. A screened subnet

Answer: A

NEW QUESTION 194

- (Exam Topic 2)

A network engineer is designing a new secure wireless network. The engineer has been given the following requirements:

- * 1 Must not use plaintext passwords
- * 2 Must be certificate based
- * 3. Must be vendor neutral

Which of the following methods should the engineer select?

- A. TWP-RC4
- B. CCMP-AES
- C. EAP-TLS
- D. WPA2

Answer: C

NEW QUESTION 198

- (Exam Topic 2)

Which of the following policies is MOST commonly used for guest captive portals?

- A. AUP
- B. DLP
- C. BYOD
- D. NDA

Answer: A

NEW QUESTION 202

- (Exam Topic 2)

A corporation has a critical system that would cause unrecoverable damage to the brand if it was taken offline. Which of the following disaster recovery solutions should the corporation implement?

- A. Full backups
- B. Load balancing
- C. Hot site
- D. Snapshots

Answer: C

NEW QUESTION 203

- (Exam Topic 2)

A technician is troubleshooting a previously encountered issue. Which of the following should the technician reference to find what solution was implemented to resolve the issue?

- A. Standard operating procedures
- B. Configuration baseline documents
- C. Work instructions
- D. Change management documentation

Answer: A

NEW QUESTION 204

- (Exam Topic 2)

Which of the following cable types would MOST likely be used to provide high-speed network connectivity between nearby buildings?

- A. UTP
- B. Coaxial
- C. Fiber
- D. Cat 5
- E. Twinaxial

Answer: C

NEW QUESTION 208

- (Exam Topic 2)

A network technician is investigating an issue with a desktop that is not connecting to the network. The desktop was connecting successfully the previous day, and no changes were made to the environment. The technician locates the switchport where the device is connected and observes the LED status light on the switchport is not lit even though the desktop is turned on Other devices that are plugged into the switch are connecting to the network successfully Which of the

following is MOST likely the cause of the desktop not connecting?

- A. Transceiver mismatch
- B. VLAN mismatch
- C. Port security
- D. Damaged cable
- E. Duplex mismatch

Answer: C

NEW QUESTION 213

- (Exam Topic 2)

A user is having difficulty with video conferencing and is looking for assistance. Which of the following would BEST improve performance?

- A. Packet shaping
- B. Quality of service
- C. Port mirroring
- D. Load balancing

Answer: B

NEW QUESTION 214

- (Exam Topic 2)

A user reports a weak signal when walking 20ft (61 m) away from the WAP in one direction, but a strong signal when walking 20ft in the opposite direction The technician has reviewed the configuration and confirmed the channel type is correct There is no jitter or latency on the connection Which of the following would be the MOST likely cause of the issue?

- A. Antenna type
- B. Power levels
- C. Frequency
- D. Encryption type

Answer: A

NEW QUESTION 216

- (Exam Topic 2)

A voice engineer is troubleshooting a phone issue. When a call is placed, the caller hears echoes of the receiver's voice. Which of the following are the causes of this issue? (Choose two.)

- A. Jitter
- B. Speed mismatch
- C. QoS misconfiguration
- D. Protocol mismatch
- E. CRC errors
- F. Encapsulation errors

Answer: AC

NEW QUESTION 220

- (Exam Topic 2)

A network technician is configuring a new firewall for a company with the necessary access requirements to be allowed through the firewall. Which of the following would normally be applied as the LAST rule in the firewall?

- A. Secure SNMP
- B. Port security
- C. Implicit deny
- D. DHCP snooping

Answer: C

NEW QUESTION 221

- (Exam Topic 2)

A technician is troubleshooting a workstation's network connectivity and wants to confirm which switchport corresponds to the wall jack the PC is using Which of the following concepts would BEST help the technician?

- A. Consistent labeling
- B. Change management
- C. Standard work instructions
- D. Inventory management
- E. Network baseline

Answer: A

NEW QUESTION 225

- (Exam Topic 2)

Which of the following would be used to expedite MX record updates to authoritative NSs?

- A. UDP forwarding
- B. DNS caching
- C. Recursive lookup
- D. Time to live

Answer: D

NEW QUESTION 227

- (Exam Topic 2)

A network field technician is installing and configuring a secure wireless network. The technician performs a site survey. Which of the following documents would MOST likely be created as a result of the site survey?

- A. Physical diagram
- B. Heat map
- C. Asset list
- D. Device map

Answer: B

NEW QUESTION 229

- (Exam Topic 2)

A client moving into a new office wants the IP network set up to accommodate 412 network-connected devices that are all on the same subnet. The subnet needs to be as small as possible. Which of the following subnet masks should be used to achieve the required result?

- A. 255.255.0.0
- B. 255.255.252.0
- C. 255.255.254.0
- D. 255.255.255.0

Answer: C

NEW QUESTION 230

- (Exam Topic 2)

A packet is assigned a value to ensure it does not traverse a network indefinitely. Which of the following BEST represents this value?

- A. Zero Trust
- B. Planned obsolescence
- C. Time to live
- D. Caching

Answer: C

NEW QUESTION 234

- (Exam Topic 2)

Which of the following VPN configurations should be used to separate Internet and corporate traffic?

- A. Split-tunnel
- B. Remote desktop gateway
- C. Site-to-site
- D. Out-of-band management

Answer: A

NEW QUESTION 238

- (Exam Topic 2)

Given the following output:

```
192.168.22.1      00-13-5d-00-e6-23
192.168.22.15     00-15-88-00-58-00
192.168.22.10     00-13-5d-00-e6-23
192.168.22.100    00-13-5d-00-e6-23
```

Which of the following attacks is this MOST likely an example of?

- A. ARP poisoning
- B. VLAN hopping
- C. Rogue access point
- D. Amplified DoS

Answer: A

NEW QUESTION 240

- (Exam Topic 2)

A business is using the local cable company to provide Internet access. Which of the following types of cabling will the cable company MOST likely use from the demarcation point back to the central office?

- A. Multimode

- B. Cat 5e
- C. RG-6
- D. Cat 6
- E. 100BASE-T

Answer: C

NEW QUESTION 241

- (Exam Topic 2)

Which of the following attacks encrypts user data and requires a proper backup implementation to recover?

- A. DDoS
- B. Phishing
- C. Ransomware
- D. MAC spoofing

Answer: C

NEW QUESTION 245

- (Exam Topic 2)

Which of the following services can provide data storage, hardware options, and scalability to a third-party company that cannot afford new devices?

- A. SaaS
- B. IaaS
- C. PaaS
- D. DaaS

Answer: B

NEW QUESTION 250

- (Exam Topic 2)

Which of the following is used to provide networking capability for VMs at Layer 2 of the OSI model?

- A. VPN
- B. VRRP
- C. vSwitch
- D. VIP

Answer: C

NEW QUESTION 254

- (Exam Topic 2)

An IDS was installed behind the edge firewall after a network was breached. The network was then breached again even though the IDS logged the attack. Which of the following should be used in place of these devices to prevent future attacks?

- A. A network tap
- B. A proxy server
- C. A UTM appliance
- D. A content filter

Answer: C

NEW QUESTION 258

- (Exam Topic 2)

A network administrator is talking to different vendors about acquiring technology to support a new project for a large company. Which of the following documents will MOST likely need to be signed before information about the project is shared?

- A. BYOD policy
- B. NDA
- C. SLA
- D. MOU

Answer: C

NEW QUESTION 263

- (Exam Topic 2)

An IT technician suspects a break in one of the uplinks that provides connectivity to the core switch. Which of the following command-line tools should the technician use to determine where the incident is occurring?

- A. nslookup
- B. show config
- C. netstat
- D. show interface
- E. show counters

Answer: D

NEW QUESTION 264

- (Exam Topic 2)

A lab environment hosts Internet-facing web servers and other experimental machines, which technicians use for various tasks. A technician installs software on one of the web servers to allow communication to the company's file server, but it is unable to connect to it. Other machines in the building are able to retrieve files from the file server. Which of the following is the MOST likely reason the web server cannot retrieve the files, and what should be done to resolve the problem?

- A. The lab environment's IDS is blocking the network traffic. The technician can whitelist the new application in the IDS.
- B. The lab environment is located in the DMZ, and traffic to the LAN zone is denied by default.
- C. The technician can move the computer to another zone or request an exception from the administrator.
- D. The lab environment has lost connectivity to the company router, and the switch needs to be rebooted. The technician can get the key to the wiring closet and manually restart the switch.
- E. The lab environment is currently set up with hubs instead of switches, and the requests are getting bounced back. The technician can submit a request for upgraded equipment to management.

Answer: B

NEW QUESTION 265

- (Exam Topic 2)

An organization with one core and five distribution switches is transitioning from a star to a full-mesh topology. Which of the following is the number of additional network connections needed?

- A. 5
- B. 7
- C. 10
- D. 15

Answer: A

NEW QUESTION 267

- (Exam Topic 3)

Which of the following is most likely to have the HIGHEST latency while being the most accessible?

- A. Satellite
- B. DSL
- C. Cable
- D. 4G

Answer: A

NEW QUESTION 271

- (Exam Topic 3)

An ISP is providing Internet to a retail store and has terminated its point of connection using a standard Cat 6 pin-out. Which of the following terminations should the technician use when running a cable from the ISP's port to the front desk?

- A. F-type connector
- B. TIA/EIA-568-B
- C. LC
- D. SC

Answer: B

Explanation:

The termination that the technician should use when running a cable from the ISP's port to the front desk is B. TIA/EIA-568-B. This is a standard pin-out for Cat 6 cables that is used for Ethernet and other network physical layers¹. It specifies how to arrange the eight wires in an RJ45 connector, which is a common type of connector for network cables.

NEW QUESTION 276

- (Exam Topic 3)

Which of the following compromises internet-connected devices and makes them vulnerable to becoming part of a botnet? (Select TWO)

- A. Deauthentication attack
- B. Malware infection
- C. IP spoofing
- D. Firmware corruption
- E. Use of default credentials
- F. Dictionary attack

Answer: BF

NEW QUESTION 280

- (Exam Topic 3)

A company is utilizing multifactor authentication for data center access. Which of the following is the MOST effective security mechanism against physical intrusions due to stolen credentials?

- A. Biometrics security hardware
- B. Access card readers
- C. Access control vestibule
- D. Motion detection cameras

Answer: C

NEW QUESTION 282

- (Exam Topic 3)

A network technician needs to ensure the company's external mail server can pass reverse lookup checks. Which of the following records would the technician MOST likely configure? (Choose Correct option and give explanation directly from CompTIA Network+ Study guide or documents)

- A. PTR
- B. AAAA
- C. SPF
- D. CNAME

Answer: A

Explanation:

A PTR (Pointer) record is used to map an IP address to a domain name, which is necessary for reverse lookup checks. Reverse lookup checks are performed by external mail servers to verify the identity of the sender of the email. By configuring a PTR record, the network technician can ensure that the company's external mail server can pass these checks. According to the CompTIA Network+ Study Guide, "A PTR record is used to map an IP address to a domain name, and it is often used for email authentication."

NEW QUESTION 287

- (Exam Topic 3)

Which of the following BEST describes a North-South traffic flow?

- A. A public Internet user accessing a published web server
- B. A database server communicating with another clustered database server
- C. A Layer 3 switch advertising routes to a router
- D. A management application connecting to managed devices

Answer: D

NEW QUESTION 289

- (Exam Topic 3)

A network administrator is looking at switch features and is unsure whether to purchase a model with PoE. Which of the following devices that commonly utilize PoE should the administrator consider? (Select TWO)

- A. VoIP phones
- B. Cameras
- C. Printers
- D. Cable modems
- E. Laptops
- F. UPSs

Answer: AB

Explanation:

Power over Ethernet (PoE) is a technology that allows network-connected devices to receive power over the same Ethernet cables that are used for data transfer. PoE is commonly used to power devices such as VoIP phones and cameras, making it an ideal choice for network administrators looking for a cost-effective solution. PoE is not typically used for other devices such as printers, cable modems, laptops, and UPSs.

NEW QUESTION 292

- (Exam Topic 3)

Which of the following topologies requires the MOST connections when designing a network?

- A. Mesh
- B. Star
- C. Bus
- D. Ring

Answer: A

NEW QUESTION 294

- (Exam Topic 3)

A technician is installing the Wi-Fi infrastructure for legacy industrial machinery at a warehouse. The equipment only supports 802.11a and 802.11b standards. Speed of transmission is the top business requirement. Which of the following is the correct maximum speed for this scenario?

- A. 11Mbps
- B. 54Mbps
- C. 128Mbps
- D. 144Mbps

Answer: B

Explanation:

802.11b (Wi-Fi 1)
11 Mbps
100 meter maximum effective range
802.11a (Wi-Fi 2)

54 Mbps
50 meter maximum effective range

NEW QUESTION 299

- (Exam Topic 3)

When accessing corporate network resources, users are required to authenticate to each application they try to access. Which of the following concepts does this BEST represent?

- A. SSO
- B. Zero Trust
- C. VPN
- D. Role-based access control

Answer: B

NEW QUESTION 301

- (Exam Topic 3)

During a recent security audit, a contracted penetration tester discovered the organization uses a number of insecure protocols. Which of the following ports should be disallowed so only encrypted protocols are allowed? (Select TWO).

- A. 22
- B. 23
- C. 69
- D. 443
- E. 587
- F. 8080

Answer: BC

NEW QUESTION 302

- (Exam Topic 3)

A technician is assisting a user who cannot connect to a website. The technician attempts to ping the default gateway and DNS server of the workstation. According to troubleshooting methodology, this is an example of:

- A. a divide-and-conquer approach.
- B. a bottom-up approach.
- C. a top-to-bottom approach.
- D. implementing a solution.

Answer: B

NEW QUESTION 303

- (Exam Topic 3)

The power company notifies a network administrator that it will be turning off the power to the building over the weekend. Which of the following is the BEST solution to prevent the servers from going down?

- A. Redundant power supplies
- B. Uninterruptible power supply
- C. Generator
- D. Power distribution unit

Answer: A

NEW QUESTION 305

- (Exam Topic 3)

An international company is transferring its IT assets including a number of WAPs from the United States to an office in Europe for deployment. Which of the following considerations should the company research before Implementing the wireless hardware?

- A. WPA2 cipher
- B. Regulatory Impacts
- C. CDMA configuration
- D. 802.11 standards

Answer: B

Explanation:

When transferring IT assets, including wireless access points (WAPs), from one country to another, it's important to research the regulatory impacts of the move. Different countries have different regulations and compliance requirements for wireless devices, such as frequency bands, power levels, and encryption standards. Failing to comply with these regulations can result in fines or other penalties.

NEW QUESTION 309

- (Exam Topic 3)

After a critical power issue, the network team was not receiving UPS status notifications. The network team would like to be alerted on these status changes. Which of the following would be BEST to use for these notifications?

- A. Traps
- B. MB

- C. NetFlow
- D. Syslog

Answer: A

NEW QUESTION 310

- (Exam Topic 3)

A company streams video to multiple devices across a campus. When this happens, several users report a degradation of network performance. Which of the following would MOST likely address this issue?

- A. Enable IGMP snooping on the switches.
- B. Implement another DHCP server.
- C. Reconfigure port tagging for the video traffic.
- D. Change the SSID of the APs

Answer: A

NEW QUESTION 312

- (Exam Topic 3)

Which of the following needs to be tested to achieve a Cat 6a certification for a company's data cabling?

- A. RJ11
- B. LC ports
- C. Patch panel
- D. F-type connector

Answer: D

NEW QUESTION 315

- (Exam Topic 3)

Users are reporting poor wireless performance in some areas of an industrial plant. The wireless controller is measuring a low EIRP value compared to the recommendations noted on the most recent site survey. Which of the following should be verified or replaced for the EIRP value to meet the site survey's specifications? (Select TWO).

- A. AP transmit power
- B. Channel utilization
- C. Signal loss
- D. Update ARP tables
- E. Antenna gain
- F. AP association time

Answer: AE

Explanation:

➤ AP transmit power: You should check if your APs have sufficient power output and adjust them if needed. You should also make sure they are not exceeding regulatory limits for your region.

➤ Antenna gain: You should check if your antennas have adequate gain for your coverage area and replace them if needed. You should also make sure they are aligned properly and not obstructed by any objects.

In the scenario described, the wireless controller is measuring a low EIRP value compared to the recommendations noted in the most recent site survey. EIRP is the combination of the power transmitted by the access point and the antenna gain. Therefore, to increase the EIRP value to meet the site survey's specifications, the administrator should verify or replace the AP transmit power (option A) and the antenna gain (option E). This can be achieved by adjusting the transmit power settings on the AP or by replacing the AP's antenna with one that has a higher gain.

NEW QUESTION 316

- (Exam Topic 3)

Which of the following will reduce routing table lookups by performing packet forwarding decisions independently of the network layer header?

- A. MPLS
- B. mGRE
- C. EIGRP
- D. VRRP

Answer: A

Explanation:

Multiprotocol Label Switching, or MPLS, is a networking technology that routes traffic using the shortest path based on "labels," rather than network addresses, to handle forwarding over private wide area networks. As a scalable and protocol-independent solution, MPLS assigns labels to each data packet, controlling the path the packet follows. MPLS greatly improves the speed of traffic, so users don't experience downtime when connected to the network.

NEW QUESTION 319

- (Exam Topic 3)

Users in a branch can access an In-house database server, but it is taking too long to fetch records. The analyst does not know whether the issue is being caused by network latency. Which of the following will the analyst MOST likely use to retrieve the metrics that are needed to resolve this issue?

- A. SNMP
- B. Link state
- C. Syslog

- D. QoS
- E. Traffic shaping

Answer: A

NEW QUESTION 324

- (Exam Topic 3)

A network engineer needs to reduce the overhead of file transfers. Which of the following configuration changes would accomplish that goal?

- A. Link aggregation
- B. Jumbo frames
- C. Port security
- D. Flow control
- E. Lower FTP port

Answer: A

NEW QUESTION 329

- (Exam Topic 3)

A Wi-Fi network was originally configured to be able to handle interference from a microwave oven. The microwave oven was recently removed from the office. Now the network administrator wants to optimize the system to maximize the range of the signal. The main sources of signal degradation are the numerous cubicles and wooden walls between the WAP and the intended destination. Which of the following actions should the administrator take?

- A. Implement CDMA.
- B. Change from omni to directional.
- C. Change the SSID.
- D. Change the frequency.

Answer: D

Explanation:

- the microwave was already removed from the office
 - the signal is OK now
 - Notice that the question mentions "numerous cubicles and wooden walls" - meaning the signal now won't have the interference as before
 - KEY POINT: the admin wants to "maximize the range of the signal:"
- Manually change the frequency to 2.4 GHz for more reliable speeds and range. While 5 GHz gives you a stronger signal, it doesn't travel through walls or ceilings as well, so it doesn't give you the best range.
- "Microwave ovens: Older microwave ovens, which might not have sufficient shielding, can emit relatively high-powered signals in the 2.4GHz band, resulting in significant interference with WLAN devices operating in the 2.4GHz band."

NEW QUESTION 333

- (Exam Topic 3)

A newly installed VoIP phone is not getting the DHCP IP address it needs to connect to the phone system. Which of the following tasks needs to be completed to allow the phone to operate correctly?

- A. Assign the phone's switchport to the correct VLAN
- B. Statically assign the phone's gateway address.
- C. Configure a route on the VoIP network router.
- D. Implement a VoIP gateway

Answer: A

NEW QUESTION 334

- (Exam Topic 3)

A technician is troubleshooting a client's report about poor wireless performance. Using a client monitor, the technician notes the following information: Which of the following is MOST likely the cause of the issue?

- A. Channel overlap
- B. Poor signal
- C. Incorrect power settings
- D. Wrong antenna type

Answer: A

NEW QUESTION 335

- (Exam Topic 3)

An administrator would like to have two servers at different geographical locations provide fault tolerance and high performance while appearing as one URL to users. Which of the following should the administrator implement?

- A. Load balancing
- B. Multipathing
- C. NIC teaming
- D. Warm site

Answer: A

Explanation:

Load balancing is a technique that can be used to provide fault tolerance and high performance while appearing as one URL to users. It is achieved by distributing

the workload across multiple servers, which are usually located in different geographical locations. This allows for high performance and fault tolerance, as if one server fails, the other will take its place. Additionally, the multiple servers appear as one URL to the users, eliminating the need for the users to switch between servers.

NEW QUESTION 340

- (Exam Topic 3)

After HVAC failures caused network outages, the support team decides to monitor the temperatures of all the devices. The network administrator cannot find a command that will display this information. Which of the following will retrieve the necessary information?

- A. SNMP OID values
- B. NetFlow data export
- C. Network baseline configurations
- D. Security information and event management

Answer: A

Explanation:

The network administrator can use the Simple Network Management Protocol (SNMP) to monitor the temperatures of all the devices. SNMP is a widely-used protocol for managing and monitoring network devices, such as routers, switches, servers, and other networking equipment. SNMP allows network administrators to gather information about the performance and status of devices on the network, including temperature readings.

To retrieve the temperature information, the administrator will have to configure SNMP on the devices and configure SNMP manager software on their computer. Once the SNMP manager software is configured, it will be able to send SNMP requests to the devices and retrieve information such as temperature, voltage, fan speeds, etc. Many network devices have built-in SNMP support, and the administrator may also need to install SNMP agent software on the devices to enable SNMP monitoring.

The administrator can also use some specific command or tool like IPMI (Intelligent Platform Management Interface) or DCIM (Data Center Infrastructure Management) tools for monitoring the temperatures of all the devices.

NEW QUESTION 341

- (Exam Topic 3)

All packets arriving at an interface need to be fully analyzed. Which of the following features should be used to enable monitoring of the packets?

- A. LACP
- B. Flow control
- C. Port mirroring
- D. NetFlow exporter

Answer: C

Explanation:

Port mirroring is a feature that can be used to enable monitoring of all packets arriving at an interface. This feature is used to direct a copy of all traffic passing through the switch to a monitoring device, such as a network analyzer. This allows the switch to be monitored with the network analyzer in order to identify any malicious or suspicious activity. Additionally, port mirroring can be used to troubleshoot network issues, such as latency or poor performance.

NEW QUESTION 342

- (Exam Topic 3)

A systems operator is granted access to a monitoring application, configuration application, and timekeeping application. The operator is denied access to the financial and project management applications by the system's security configuration. Which of the following BEST describes the security principle in use?

- A. Network access control
- B. Least privilege
- C. Multifactor authentication
- D. Separation of duties

Answer: D

NEW QUESTION 345

- (Exam Topic 3)

Which of the following ports should be used to securely receive mail that is synchronized across multiple devices?

- A. 25
- B. 110
- C. 443
- D. 993

Answer: D

NEW QUESTION 349

- (Exam Topic 3)

A computer engineer needs to ensure that only a specific workstation can connect to port 1 on a switch. Which of the following features should the engineer configure on the switch interface?

- A. Port tagging
- B. Port security
- C. Port mirroring
- D. Port aggregation

Answer: B

Explanation:

Port security is a feature that can be configured on a switch interface to limit and identify the MAC addresses of workstations that are allowed to connect to that specific port. This can help ensure that only a specific workstation (or workstations) can connect to the interface. According to the CompTIA Network+ Study Manual, "Port security can be used to specify which MAC addresses are allowed to connect to a particular switch port. If a port security violation is detected, the switch can take a number of different actions, such as shutting down the port, sending an SNMP trap, or sending an email alert."

NEW QUESTION 353

- (Exam Topic 3)

SIMULATION


A network technician replaced a switch and needs to reconfigure it to allow the connected devices to connect to the correct networks.

INSTRUCTIONS

Click on the appropriate port(s) on Switch 1 and Switch 3 to verify or reconfigure the correct settings:

- Ensure each device accesses only its correctly associated network
- Disable all unused switch ports
- Require fault-tolerant connections between the switches
- Only make necessary changes to complete the above requirements

If at any time you would like to bring back the initial state of the simulation, please click the Reset All button.



Switch 3 - Port 8 Configuration

Status

Port ☒ Enabled
LACP ☐ Disabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000
Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

+

 Add VLAN

VLAN1

Port Tagging

UnTagged

Tagged

UnTagged

VLAN 1

VLAN 60

VLAN 90

VLAN 120

VLAN 150

VLAN 220

Reset to Default

Save

Close

Switch 3 - Port 7 Configuration

Status

Port ☒ Enabled

LACP ☐ Disabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

+ Add VLAN

VLAN1

Port Tagging

UnTagged

Tagged

UnTagged

VLAN 1

VLAN 60

VLAN 90

VLAN 120

VLAN 150

VLAN 220

Reset to Default

Save

Close

Switch 3 - Port 6 Configuration

Status

Port ☒ Enabled

LACP ☐ Disabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

+ Add VLAN

VLAN150

Port Tagging

UnTagged

Tagged

UnTagged

VLAN 1

VLAN 60

VLAN 90

VLAN 120

VLAN 150

VLAN 220

Reset to Default

Save

Close

Switch 3 - Port 4 Configuration

Status

Port ☒ Enabled

LACP ☐ Disabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

+ Add VLAN

VLAN1

Port Tagging

UnTagged

Tagged

UnTagged

VLAN 1

VLAN 60

VLAN 90

VLAN 120

VLAN 150

VLAN 220

Reset to Default

Save

Close

Switch 3 - Port 1 Configuration

Status

Port ☒ Enabled

LACP ☐ Disabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

+ Add VLAN

VLAN1

Port Tagging

UnTagged

Tagged

UnTagged

VLAN 1

VLAN 60

VLAN 90

VLAN 120

VLAN 150

VLAN 220

Reset to Default

Save

Close

Switch 1 - Port 7 Configuration

Status

Port ☒ Enabled

LACP ☒ Enabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

+ Add VLAN

VLAN60

Port Tagging

Tagged

VLAN90

Port Tagging

Tagged

VLAN120

Port Tagging

Tagged

VLAN150

Port Tagging

Tagged

VLAN220

Port Tagging

Tagged

Reset to Default

Save

Close

Switch 1 - Port 8 Configuration

Status

Port ☒ Enabled

LACP ☒ Enabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

+ Add VLAN

VLAN60

Port Tagging

Tagged

VLAN90

Port Tagging

Tagged

VLAN120

Port Tagging

Tagged

VLAN150

Port Tagging

Tagged

VLAN220

Port Tagging

Tagged

Reset to Default

Save

Close

Switch 1 - Port 6 Configuration

Status

Port ☒ Enabled

LACP ☒ Enabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

Add VLAN

VLAN60

Port Tagging

Tagged

VLAN120

Port Tagging

Tagged

VLAN150

Port Tagging

Tagged

Reset to Default

Save

Close

Switch 1 - Port 2 Configuration

Status

Port ☒ Enabled

LACP ☒ Enabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

Add VLAN

VLAN60

Port Tagging

Tagged

VLAN90

Port Tagging

Tagged

VLAN120

Port Tagging

Tagged

VLAN150

Port Tagging

Tagged

VLAN220

Port Tagging

Tagged

Reset to Default

Save

Close

Switch 1 - Port 1 Configuration

Status

Port ☒ Enabled

LACP ☒ Enabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

Add VLAN

VLAN60

Port Tagging

Tagged

VLAN90

Port Tagging

Tagged

VLAN120

Port Tagging

Tagged

VLAN150

Port Tagging

Tagged

VLAN220

Port Tagging

Tagged

Reset to Default

Save

Close

Switch 1 - Port 5 Configuration

Status

Port ☒ Enabled

LACP ☒ Enabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

Add VLAN

VLAN60

Port Tagging

Tagged

VLAN120

Port Tagging

Tagged

VLAN150

Port Tagging

Tagged

Reset to Default

Save

Close

Switch 1 - Port 4 Configuration

Status

Port ☒ Enabled

LACP ☐ Disabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

+ Add VLAN

VLAN90

Port Tagging

UnTagged

Tagged

UnTagged

VLAN 1

VLAN 60

VLAN 90

VLAN 120

VLAN 150

VLAN 220

Reset to Default

Save

Close

Switch 1 - Port 3 Configuration

Status

Port ☒ Enabled

LACP ☐ Disabled

Wired

Speed ☐ Auto ☐ 100 ☒ 1000

Duplex ☐ Auto ☐ Half ☒ Full

VLAN Configuration

+ Add VLAN

VLAN90

Port Tagging

UnTagged

Tagged

UnTagged

VLAN 1

VLAN 60

VLAN 90

VLAN 120


VLAN 150

VLAN 220

Reset to Default

Save

Close



The image shows a configuration window for 'Switch 3 - Port 2'. It has three main sections: 'Status', 'Wired', and 'VLAN Configuration'.
 - **Status:** 'Port' is a toggle switch set to 'Enabled'. 'LACP' is a toggle switch set to 'Disabled'.
 - **Wired:** 'Speed' has radio buttons for 'Auto', '100', and '1000' (selected). 'Duplex' has radio buttons for 'Auto', 'Half', and 'Full' (selected).
 - **VLAN Configuration:** There is an 'Add VLAN' button and a list of VLANs. A dropdown menu is open, showing 'VLAN 90' selected. Below the dropdown, there is a 'Port Tagging' section with a dropdown menu showing 'UnTagged', 'Tagged', and 'UnTagged' (the last one is highlighted in blue).
 At the bottom, there are three buttons: 'Reset to Default', 'Save', and 'Close'.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Switch 1 and Switch 2 is the only two switches that can be configured. Only switches linked together with there switch ports needs to be "tagged" and "LACP" needs to be enabled. The other ports must be untagged with no LACP enabled. You only need to assign the correct vlan via each port. 'Speed and Duplex' needs to be Speed=1000 and Duplex=Full, with is by default.

<https://resources.infosecinstitute.com/topic/what-are-tagged-and-untagged-ports/>

NEW QUESTION 354

- (Exam Topic 3)

A network technician 13 troubleshooting a specific port on a switch. Which of the following commands should the technician use to see the port configuration?

- A. show route
- B. show Interface
- C. show arp
- D. show port

Answer: B

Explanation:

To see the configuration of a specific port on a switch, the network technician should use the "show interface" command. This command provides detailed information about the interface, including the current configuration, status, and statistics for the interface.

NEW QUESTION 359

- (Exam Topic 3)

Users are reporting intermittent Wi-Fi connectivity in specific parts of a building. Which of the following should the network administrator check FIRST when troubleshooting this issue? (Select TWO).

- A. Site survey
- B. EIRP
- C. AP placement
- D. Captive portal
- E. SSID assignment
- F. AP association time

Answer: AC

Explanation:

This is a coverage issue. WAP placement and power need to be checked. Site survey should be done NEXT because it takes a while.

NEW QUESTION 361

- (Exam Topic 3)

An administrator is attempting to add a new system to monitoring but is unsuccessful. The administrator notices the system is similar to another one on the network; however, the new one has an updated OS version. Which of the following should the administrator consider updating?

- A. Management information bases
- B. System baseline
- C. Network device logs
- D. SNMP traps

Answer: A

NEW QUESTION 365

- (Exam Topic 3)

A company is reviewing ways to cut the overall cost of its IT budget. A network technician suggests removing various computer programs from the IT budget and only providing these programs on an as-needed basis. Which of the following models would meet this requirement?

- A. Multitenancy
- B. IaaS
- C. SaaS
- D. VPN

Answer: C

NEW QUESTION 367

- (Exam Topic 3)

Which of the following describes when an active exploit is used to gain access to a network?

- A. Penetration testing
- B. Vulnerability testing
- C. Risk assessment
- D. Posture assessment
- E. Baseline testing

Answer: A

Explanation:

Penetration testing is a type of security testing that is used to assess the security of a system or network by actively exploiting known vulnerabilities. It is used to simulate an attack on the system and identify any weaknesses that may be exploited by malicious actors. As stated in the CompTIA Security+ Study Guide, "penetration testing is a type of security assessment that attempts to gain unauthorized access to networks and systems by exploiting security vulnerabilities."

NEW QUESTION 370

- (Exam Topic 3)

A network administrator is investigating a network event that is causing all communication to stop. The network administrator is unable to use SSH to connect to the switch but is able to gain access using the serial console port. While monitoring port statistics, the administrator sees the following:

Total Rx (bps)	23,041,464	Total Tx (bps)	621,032
Unicast Rx (Pkts/sec)	102,465	Unicast Tx (Pkts/sec)	66
B/Mcast Rx (Pkts/sec)	21,456.465	B/Mcast Tx (Pkts/sec)	7
Utilization Rx	2.3%	Utilization Tx	0.06%

Which of the following is MOST likely causing the network outage?

- A. Duplicate IP address
- B. High collisions
- C. Asynchronous route
- D. Switch loop

Answer: B

NEW QUESTION 373

- (Exam Topic 3)

Which of the following is used to elect an STP root?

- A. A bridge ID
- B. A bridge protocol data unit
- C. Interface port priority
- D. A switch's root port

Answer: B

Explanation:

"Using special STP frames known as bridge protocol data units (BPDUs), switches communicate with other switches to prevent loops from happening in the first

place. Configuration BPDUs establish the topology, where one switch is elected root bridge and acts as the center of the STP universe. Each switch then uses the root bridge as a reference point to maintain a loop-free topology."

NEW QUESTION 378

- (Exam Topic 3)

A company is considering shifting its business to the cloud. The management team is concerned at the availability of the third-party cloud service. Which of the following should the management team consult to determine the promised availability of the cloud provider?

- A. Memorandum of understanding
- B. Business continuity plan
- C. Disaster recovery plan
- D. Service-level agreement

Answer: D

Explanation:

A Service-level agreement (SLA) is a document that outlines the responsibilities of a cloud service provider and the customer. It typically includes the agreed-upon availability of the cloud service provider, the expected uptime for the service, and the cost of any downtime or other service interruptions. Consulting the SLA is the best way for the management team to determine the promised availability of the cloud provider. Reference: CompTIA Cloud+ Study Guide, 6th Edition, page 28.

NEW QUESTION 381

- (Exam Topic 3)

Which of the following connectors and terminations are required to make a Cat 6 cable that connects from a PC to a non-capable MDIX switch? (Select TWO).

- A. T1A-568-A - TIA-568-B
- B. TIA-568-B - TIA-568-B
- C. RJ11
- D. RJ45
- E. F-type

Answer: AD

NEW QUESTION 385

- (Exam Topic 3)

Which of the following is a requirement when certifying a network cabling as Cat 7?

- A. Ensure the patch panel is certified for the same category.
- B. Limit 10Gb transmissions to 180ft (55m).
- C. Use F-type connectors on the network terminations.
- D. Ensure the termination standard is TIA/EIA-568-A.

Answer: D

Explanation:

Category 7 (Cat 7) is a cabling standard that supports 10GBASE-T Ethernet connections up to 100 meters (328 feet). In order for a cabling system to be certified as Cat 7, all components, including the patch panel, must meet the TIA/EIA-568-A standard. This standard requires the use of shielded cables with F-type connectors for the network terminations. Reference: CompTIA Network+ Study Manual, 8th Edition, page 158.

NEW QUESTION 386

- (Exam Topic 3)

To access production applications and data, developers must first connect remotely to a different server. From there, the developers are able to access production data. Which of the following does this BEST represent?

- A. A management plane
- B. A proxy server
- C. An out-of-band management device
- D. A site-to-site VPN
- E. A jump box

Answer: E

NEW QUESTION 389

- (Exam Topic 3)

A technician is connecting a Cat 6 Ethernet cable to a device that only has LC ports. Which of the following will the technician MOST likely use to accomplish this task?

- A. A bridge
- B. A media converter
- C. A repeater
- D. A router

Answer: B

NEW QUESTION 391

- (Exam Topic 3)

A network technician is having issues connecting an IoT sensor to the internet. The WLAN settings were enabled via a custom command line, and a proper IP address assignment was received on the wireless interface. However, when trying to connect to the internet, only HTTP redirections are being received when data

Is requested. Which of the following will point to the root cause of the Issue?

- A. Verifying if an encryption protocol mismatch exists.
- B. Verifying If a captive portal is active for the WLAN.
- C. Verifying the minimum RSSI for operation in the device's documentation
- D. Verifying EIRP power settings on the access point.

Answer: C

Explanation:

A captive portal is a web page that is displayed to a user before they can access the internet or other network resources. This is often used in public or guest networks to present users with a login or terms and conditions page before they can access the internet. If a captive portal is active on the WLAN, it would explain why the IoT sensor is only receiving HTTP redirections when trying to connect to the internet.

NEW QUESTION 394

- (Exam Topic 3)

A network administrator needs to run a single command-line tool capable of displaying routing table and multicast memberships. Which of the following would BEST help the administrator achieve the requirements?

- A. arp
- B. show route
- C. show config
- D. netstate

Answer: A

NEW QUESTION 399

- (Exam Topic 3)

Which of the following architectures is used for FTP?

- A. Client-server
- B. Service-oriented
- C. Connection-oriented
- D. Data-centric

Answer: A

Explanation:

FTP (File Transfer Protocol) is a client-server based protocol, meaning that the two computers involved communicate with each other in a request-response pattern. The client sends a request to the server and the server responds with the requested data. This type of architecture is known as client-server, and it is used for many different types of applications, including FTP. Other architectures, such as service-oriented, connection-oriented, and data-centric, are not used for FTP.

NEW QUESTION 401

- (Exam Topic 3)

A user reports that a new VoIP phone works properly but the computer that is connected to the phone cannot access any network resources. Which of the following MOST Likely needs to be configured correctly to provide network connectivity to the computer?

- A. Port duplex settings
- B. Port aggregation
- C. ARP settings
- D. VLAN tags
- E. MDIX settings

Answer: D

Explanation:

VLAN (virtual LAN) tags are used to identify packets as belonging to a particular VLAN. VLANs are used to segment a network into logical sub-networks, and each VLAN is assigned a unique VLAN tag. If the VLAN tag is not configured correctly, the computer may not be able to access network resources.

NEW QUESTION 404

- (Exam Topic 3)

A network technician is troubleshooting an area where the wireless connection to devices is poor. The technician theorizes that the signal-to-noise ratio in the area is causing the issue. Which of the following should the technician do NEXT?

- A. Run diagnostics on the relevant devices.
- B. Move the access point to a different location.
- C. Escalate the issue to the vendor's support team.
- D. Remove any electronics that might be causing interference.

Answer: D

NEW QUESTION 409

- (Exam Topic 3)

Which of the following types of datacenter architectures will MOST likely be used in a large SDN and can be extended beyond the datacenter? (Choose two.)

- A. iSCSI
- B. FCoE
- C. Three-tiered network

- D. Spine and leaf
- E. Top-of-rack switching

Answer: CD

NEW QUESTION 411

- (Exam Topic 3)

Which of the following must be functioning properly in order for a network administrator to create an accurate timeline during a troubleshooting process?

- A. NTP
- B. IP helper
- C. Syslog
- D. MySQL

Answer: A

NEW QUESTION 412

- (Exam Topic 3)

A network technician is planning a network scope. The web server needs to be within 12.31 69.1 to 12.31.69.29. Which of the following would meet this requirement?

- A. Lease time
- B. Range reservation
- C. DNS
- D. Superscope

Answer: A

NEW QUESTION 414

- (Exam Topic 3)

A company needs to virtualize a replica of its internal physical network without changing the logical topology and the way that devices behave and are managed. Which of the following technologies meets this requirement?

- A. NFV
- B. SDWAN
- C. VIP
- D. MPLS

Answer: A

Explanation:

Network Function Virtualization (NFV) is a technology that allows for the virtualization of a replica of a network's physical topology and the way it behaves without changing the logical topology and the way that devices are managed. NFV allows for the virtualization of network functions such as routers, firewalls, and switches, resulting in increased flexibility and scalability. This makes NFV an ideal technology for companies looking to virtualize a replica of their internal physical network.

NEW QUESTION 417

- (Exam Topic 3)

Which of the following describes the ability of a corporate IT department to expand its cloud-hosted VM environment with minimal effort?

- A. Scalability
- B. Load balancing
- C. Multitenancy
- D. Geo-redundancy

Answer: A

Explanation:

Scalability is the ability of a corporate IT department to expand its cloud-hosted virtual machine (VM) environment with minimal effort. This allows IT departments to quickly and easily scale up their cloud environment to meet increased demand. Scalability also allows for the efficient use of resources, as IT departments can quickly and easily scale up or down as needed.

NEW QUESTION 420

- (Exam Topic 3)

A network administrator is troubleshooting an issue with a new Internet connection. The ISP is asking detailed questions about the configuration of the router that the network administrator is troubleshooting. Which of the following commands is the network administrator using? (Select TWO.)

- A. tcpdump
- B. show config
- C. hostname
- D. show route
- E. netstate
- F. show ip arp

Answer: BD

Explanation:

"The show config command (or some variation of it) is used to examine the configuration of a network device. For example, on a Cisco router, the show running-

configuration command permits you to see the current configuration of the device, which is stored in the RAM of the device. To view the saved configuration that is loaded when the system is rebooted, you can use the show startup-configuration command."

"The show route command (or some variation of it) is used to view the routing table configuration of the network device. On a Cisco router, you can use show ip route to view the IPv4 routing table."

NEW QUESTION 425

- (Exam Topic 3)

A network administrator is adding a new switch to the network. Which of the following network hardening techniques would be BEST to use once the switch is in production?

- A. Disable unneeded ports
- B. Disable SSH service
- C. Disable MAC filtering
- D. Disable port security

Answer: A

NEW QUESTION 427

- (Exam Topic 3)

A corporate client is experiencing global system outages. The IT team has identified multiple potential underlying causes throughout the enterprise. Each team member has been assigned an area to trouble shoot. Which of the following approaches is being used?

- A. Divide-and-conquer
- B. Top-to-bottom
- C. Bottom-to-top
- D. Determine if anything changed

Answer: A

NEW QUESTION 430

- (Exam Topic 3)

A network engineer receives the following when connecting to a switch to configure a port:

```
telnet 10.1.200.1
Connecting to 10.1.200.1...Could not open connection to the host, on port 23: Connect failed.
```

Which of the following is the MOST likely cause for the failure?

- A. The network engineer is using the wrong protocol
- B. The network engineer does not have permission to configure the device
- C. SNMP has been secured with an ACL
- D. The switchport the engineer is trying to configure is down

Answer: D

NEW QUESTION 435

- (Exam Topic 3)

A technician is configuring a static IP address on a new device in a newly created subnet. The work order specifies the following requirements:

- The IP address should use the highest address available in the subnet.
- The default gateway needs to be set to 172.28.85.94.
- The subnet mask needs to be 255.255.255.224.

Which of the following addresses should the engineer apply to the device?

- A. 172.28.85.93
- B. 172.28.85.95
- C. 172.28.85.254
- D. 172.28.85.255

Answer: A

Explanation:

<https://www.tunnelsup.com/subnet-calculator/> IP Address: 172.28.85.95/27

Netmask: 255.255.255.224

Network Address: 172.28.85.64

Usable Host Range: 172.28.85.65 - 172.28.85.94

Broadcast Address: 172.28.85.95

NEW QUESTION 440

- (Exam Topic 3)

Users within a corporate network need to connect to the Internet, but corporate network policy does not allow direct connections. Which of the following is MOST likely to be used?

- A. Proxy server
- B. VPN client
- C. Bridge
- D. VLAN

Answer: A

NEW QUESTION 444

- (Exam Topic 3)

A new student is given credentials to log on to the campus Wi-Fi. The student stores the password in a laptop and is able to connect; however, the student is not able to connect with a phone when only a short distance from the laptop. Given the following information:

Signal strength	90%
Coverage	80%
Interference	15%
Number of connection attempts	10

Which of the following is MOST likely causing this connection failure?

- A. Transmission speed
- B. Incorrect passphrase
- C. Channel overlap
- D. Antenna cable attenuation/signal loss

Answer: B

NEW QUESTION 449

- (Exam Topic 3)

A company has multiple offices around the world. The computer rooms in some office locations are too warm. Dedicated sensors are in each room, but the process of checking each sensor takes a long time. Which of the following options can the company put in place to automate temperature readings with internal resources?

- A. Implement NetFlow.
- B. Hire a programmer to write a script to perform the checks
- C. Utilize ping to measure the response.
- D. Use SNMP with an existing collector server

Answer: D

Explanation:

SNMP (Simple Network Management Protocol) is a protocol that allows network devices to communicate with a management server. By using SNMP, the company can set up an SNMP agent on each sensor, which will report its temperature readings to an existing collector server. This will enable the company to monitor the temperatures of all their sensors in real-time without the need for manual checks. Additionally, SNMP's scalability means that even if the company adds more rooms or sensors, the existing system can be easily expanded to accommodate them.

NEW QUESTION 450

- (Exam Topic 3)

A network administrator would like to purchase a device that provides access ports to endpoints and has the ability to route between networks. Which of the following would be BEST for the administrator to purchase?

- A. An IPS
- B. A Layer 3 switch
- C. A router
- D. A wireless LAN controller

Answer: B

NEW QUESTION 454

- (Exam Topic 3)

A help desk technician is concerned that a client's network cable issues may be causing intermittent connectivity. Which of the following would help the technician determine if this is the issue?

- A. Run the show interface command on the switch
- B. Run the traceroute command on the server
- C. Run iperf on the technician's desktop
- D. Ping the client's computer from the router
- E. Run a port scanner on the client's IP address

Answer: A

Explanation:

To determine if a client's network cable issues may be causing intermittent connectivity, the help desk technician can run the show interface command on the switch. This command allows the technician to view the status and statistics of the various interfaces on the switch, including the physical link status and the number of transmitted and received packets. If the interface is experiencing a large number of errors or dropped packets, this could indicate a problem with the network cable or with the connection between the client's device and the switch.

"Cisco routers and switches have a show interfaces IOS command that provides interface statistics/status information, including link state (up/down), speed/duplex, send/receive traffic, cyclic redundancy checks (CRCs), and protocol packet and byte counts."

NEW QUESTION 456

- (Exam Topic 3)

A technician is troubleshooting reports that a networked printer is unavailable. The printer's IP address is configured with a DHCP reservation, but the address cannot be pinged from the print server in the same subnet. Which of the following is MOST likely the cause of the connectivity failure?

- A. Incorrect VLAN
- B. DNS failure
- C. DHCP scope exhaustion

D. Incorrect gateway

Answer: D

NEW QUESTION 457

- (Exam Topic 3)

The following DHCP scope was configured for a new VLAN dedicated to a large deployment of 325 IoT sensors:

```
DHCP network scope: 10.10.0.0/24
Exclusion range: 10.10.10.1-10.10.10.10
Gateway: 10.10.0.1
DNS: 10.10.0.2
DHCP option 66 (TFTP): 10.10.10.4
DHCP option 4 (NTP): 10.10.10.5
```

The first 244 IoT sensors were able to connect to the TFTP server, download the configuration file, and register to an IoT management system. The other sensors are being shown as offline. Which of the following should be performed to determine the MOST likely cause of the partial deployment of the sensors?

- A. Check the gateway connectivity to the TFTP server.
- B. Check the DHCP network scope.
- C. Check whether the NTP server is online.
- D. Check the IoT devices for a hardware failure.

Answer: B

NEW QUESTION 462

- (Exam Topic 3)

A technician is consolidating a topology with multiple SSIDs into one unique SSID deployment. Which of the following features will be possible after this new configuration?

- A. Seamless roaming
- B. Basic service set
- C. WPA
- D. MU-MIMO

Answer: A

NEW QUESTION 467

- (Exam Topic 3)

A network administrator wants to check all network connections and see the output in integer form. Which of the following commands should the administrator run on the command line?

- A. netstat
- B. netstat -a
- C. netstat —e
- D. netstat —n

Answer: A

NEW QUESTION 471

- (Exam Topic 3)

Which of the following is conducted frequently to maintain an updated list of a system's weaknesses?

- A. Penetration test
- B. Posture assessment
- C. Risk assessment
- D. Vulnerability scan

Answer: D

NEW QUESTION 472

- (Exam Topic 3)

A network client is trying to connect to the wrong TCP port. Which of the following responses would the client MOST likely receive?

- A. RST
- B. FIN
- C. ICMP Time Exceeded
- D. Redirect

Answer: A

NEW QUESTION 474

- (Exam Topic 3)

An engineer needs to verify the external record for SMTP traffic. The engineer logged in to the server and entered the nslookup command. Which of the following commands should the engineer send before entering the DNS name?

- A. set type=A
- B. is -d company-mail.com
- C. set domain=company.mail.com
- D. set querytype=Mx

Answer: D

NEW QUESTION 475

- (Exam Topic 3)

A network administrator is troubleshooting a connectivity performance issue. As part of the troubleshooting process, the administrator performs a traceout from the client to the server, and also from the server to the client. While comparing the outputs, the administrator notes they show different hops between the hosts. Which of the following BEST explains these findings?

- A. Asymmetric routing
- B. A routing loop
- C. A switch loop
- D. An incorrect gateway

Answer: C

NEW QUESTION 476

- (Exam Topic 3)

A Fortune 500 firm is deciding On the kind or data center equipment to install given its five-year budget Outlook. The Chief Information comparing equipment based on the life expectancy Of different models.

Which Of the following concepts BEST represents this metric?

- A. MTBF
- B. MTRR
- C. RPO
- D. RTO

Answer: A

NEW QUESTION 481

- (Exam Topic 3)

A technician notices that equipment is being moved around and misplaced in the server room, even though the room has locked doors and cabinets. Which of the following would be the BEST solution to identify who is responsible?

- A. Install motion detection
- B. Install cameras.
- C. Install tamper detection.
- D. Hire a security guard.

Answer: B

Explanation:

Installing cameras in the server room is the best solution to identify who is responsible for the equipment being moved and misplaced. Cameras provide a way to monitor the server room in real time and can be used to identify suspicious activity. Additionally, they provide a way to review past activity and allow you to review footage to determine who may be responsible for the misplacement of equipment.

NEW QUESTION 485

- (Exam Topic 3)

A network attack caused a network outage by wiping the configuration and logs of the border firewall. Which of the following sources, in an investigation to determine how the firewall was compromised, can provide the MOST detailed data?

- A. Syslog server messages
- B. MIB of the attacked firewall
- C. Network baseline reports
- D. NetFlow aggregate data

Answer: A

NEW QUESTION 489

- (Exam Topic 3)

A technician is consolidating a topology with multiple SSIDs into one unique SSID deployment. Which of the following features will be possible after this new configuration?

- A. Seamless roaming
- B. Basic service set
- C. WPA
- D. MU-MIMO

Answer: A

NEW QUESTION 494

- (Exam Topic 3)

A network administrator is setting up a new phone system and needs to define the location where VoIP phones can download configuration files. Which of the

following DHCP services can be used to accomplish this task?

- A. Scope options
- B. Exclusion ranges
- C. Lease time
- D. Relay

Answer: A

Explanation:

To define the location where VoIP phones can download configuration files, the network administrator can use scope options within the Dynamic Host Configuration Protocol (DHCP) service. Scope options are a set of values that can be configured within a DHCP scope, which defines a range of IP addresses that can be leased to clients on a network. One of the scope options that can be configured is the option for the location of the configuration file server, which specifies the URL or IP address of the server where the configuration files can be downloaded.
<https://pbxbook.com/voip/dhccpfg.html>

NEW QUESTION 497

- (Exam Topic 3)

During an annual review of policy documents, a company decided to adjust its recovery time frames. The company agreed that critical applications can be down for no more than six hours, and the acceptable amount of data loss is no more than two hours. Which of the following should be documented as the RPO?

- A. Two hours
- B. Four hours
- C. Six hours
- D. Eight hours

Answer: A

Explanation:

"RPO designates the variable amount of data that will be lost or will have to be re-entered during network downtime. RTO designates the amount of "real time" that can pass before the disruption begins to seriously and unacceptably impede the flow of normal business operations."

NEW QUESTION 501

- (Exam Topic 3)

An attacker targeting a large company was able to inject malicious A records into internal name resolution servers. Which of the following attack types was MOST likely used?

- A. DNS poisoning
- B. On-path
- C. IP spoofing
- D. Rogue DHCP

Answer: A

NEW QUESTION 504

- (Exam Topic 3)

A network administrator is installing a new server in the data center. The administrator is concerned the amount of traffic generated will exceed 1GB. and higher-throughput NiCs are not available for installation. Which of the following is the BEST solution for this issue?

- A. Install an additional NIC and configure LACP.
- B. Remove some of the applications from the server.
- C. Configure the NIC to use full duplex
- D. Configure port mirroring to send traffic to another server.
- E. Install a SSD to decrease data processing time.

Answer: A

NEW QUESTION 505

- (Exam Topic 3)

A company just migrated its email service to a cloud solution. After the migration, two-thirds of the internal users were able to connect to their mailboxes, but the connection fails for the other one-third of internal users. Users working externally are not reporting any issues. The network administrator identifies the following output collected from an internal host:

```
c:\user> nslookup newmail.company.com
```

Non-Authoritative answer:

Name: newmail.company.com

IPs: 3.219.13.186, 64.58.225.184, 184.168.131.243

Which of the following verification tasks should the network administrator perform NEXT?

- A. Check the firewall ACL to verify all required IP addresses are included.
- B. Verify the required router PAT rules are properly configured.
- C. Confirm the internal DNS server is replying to requests for the cloud solution.
- D. Validate the cloud console to determine whether there are unlicensed requests.

Answer: A

NEW QUESTION 507

- (Exam Topic 3)

An auditor assessing network best practices was able to connect a rogue switch into a network Jack and get network connectivity. Which of the following controls

would BEST address this risk?

- A. Activate port security on the switchports providing end user access.
- B. Deactivate Spanning Tree Protocol on network interfaces that are facing public areas.
- C. Disable Neighbor Resolution Protocol in the Layer 2 devices.
- D. Ensure port tagging is in place for network interfaces in guest areas

Answer: A

NEW QUESTION 512

- (Exam Topic 3)

A network administrator installed a new data and VoIP network. Users are now experiencing poor call quality when making calls. Which of the following should the administrator do to increase VoIP performance?

- A. Configure a voice VLAN.
- B. Configure LACP on all VoIP phones.
- C. Configure PoE on the network.
- D. Configure jumbo frames on the network.

Answer: A

Explanation:

"Benefits of Voice VLAN

It ensures that your VoIP (Voice over Internet Phone) devices do not have to contend directly with all the broadcasts and other traffic from the data VLAN. A voice VLAN can simplify network configuration in some circumstances."

<https://community.fs.com/blog/auto-voip-vs-voice-vlan-what-s-the-difference.html> Jumbo Frames

"When jumbo frames on a VoIP/UC network are enabled, it can cause the same kind of delay to your network transmissions."

"VoIP uses will always not benefit from jumbo frame, as VoIP like gaming, is latency and time sensitive. Jumbo Frame for Internet Purpose: You will not see any performance boost as the files that came across the internet does not support jumbo frame."

<https://www.ankmax.com/newsinfo/1358641.html#:~:text=VoIP%20uses%20will%20always%20not,does%20n>

"To summarize this general best practice guide, you should NOT enable jumbo frame feature as a general home user."

NEW QUESTION 516

- (Exam Topic 3)

A network engineer is monitoring a fiber uplink to a remote office and notes the uplink has been operating at 100% capacity for a long duration. Which of the following performance metrics is MOST likely to be impacted with sustained link saturation?

- A. Latency
- B. Jitter
- C. Speed
- D. Bandwidth

Answer: A

Explanation:

When a fiber uplink is operating at 100% capacity for an extended period of time, it can cause sustained link saturation. This can impact the network's performance by increasing latency. Latency is the time it takes for a packet to travel from the source to its destination. When there is link saturation, packets may have to wait in a queue before being transmitted, which increases the time it takes for them to reach their destination. As a result, users may experience delays or timeouts when accessing network resources.

Other metrics such as jitter, speed, and bandwidth are also important, but they are not as directly impacted by sustained link saturation as latency.

NEW QUESTION 518

- (Exam Topic 3)

Which of the following OSI model layers is where a technician would view UDP information?

- A. Physical
- B. Data link
- C. Network
- D. Transport

Answer: D

NEW QUESTION 521

- (Exam Topic 3)

Which of the following OSI model layers contains IP headers?

- A. Presentation
- B. Application
- C. Data link
- D. Network
- E. Transport

Answer: D

NEW QUESTION 526

- (Exam Topic 3)

A technician is investigating an issue with connectivity at customer's location. The technician confirms that users can access resources locally but not over the internet The technician theorizes that the local router has failed and investigates further. The technician's testing results show that the route is functional: however,

users still are unable to reach resources on the internal. Which of the following describes what the technician should do NEXT?

- A. Document the lessons learned
- B. Escalate the issue
- C. identify the symptoms.
- D. Question users for additional information

Answer: C

Explanation:

According to the CompTIA Network+ troubleshooting model123, this is the first step in troubleshooting a network problem. The technician should gather information about the current state of the network, such as error messages, device status, network topology, and user feedback. This can help narrow down the scope of the problem and eliminate possible causes.

NEW QUESTION 527

- (Exam Topic 3)

Which of the following issues are present with RIPv2? (Select TWO).

- A. Route poisoning
- B. Time to converge
- C. Scalability
- D. Unicast
- E. Adjacent neighbors
- F. Maximum transmission unit

Answer: BC

Explanation:

The disadvantages of RIP (Routing Information Protocol) include the following.

---Outdated, insecure, and slow. This is your parents' protocol. It was a thing before the Web was born.

---The more well-known problem of the 15 hop limitation in which data must travel

---Convergence time is terrible for information propagation in a network

---Metrics. It determines the number of hops from source to destination, and gives no regard to other factors when determining the best path for data to travel

---Overhead. A good example would be routing tables. These are broadcast at half-minute intervals to other routers regardless of whether the data has changed or not. It's essentially like those old cartoons where the town guard in the walled city cries out, '10 o' the clock and all is well!'. RIPv2 introduced more security and reduced broadcast traffic, which is relevant for some available answers here.

NEW QUESTION 531

- (Exam Topic 3)

An engineer recently decided to upgrade the firmware on a router. During the upgrade, the help desk received calls about a network outage, and a critical ticket was opened. The network manager would like to create a policy to prevent this from happening in the future. Which of the following documents should the manager create?

- A. Change management
- B. incident response
- C. Standard operating procedure
- D. System life cycle

Answer: A

NEW QUESTION 534

- (Exam Topic 3)

During a risk assessment which of the following should be considered when planning to mitigate high CPU utilization of a firewall?

- A. Recovery time objective
- B. Uninterruptible power supply
- C. NIC teaming
- D. Load balancing

Answer: D

Explanation:

The recovery time objective (RTO) is the maximum tolerable length of time that a computer, system, network or application can be down after a failure or disaster occurs. This does nothing to help with CPU utilization. Load balancing does this.

NEW QUESTION 538

- (Exam Topic 3)

Which of the following can be used to centrally manage credentials for various types of administrative privileges on configured network devices?

- A. SSO
- B. TACACS+
- C. Zero Trust
- D. Separation of duties
- E. Multifactor authentication

Answer: B

Explanation:

TACACS+ is used to authenticate users and authorize access to network resources. This protocol provides greater network security by encrypting the

authentication credentials and reducing the risk of unauthorized access. According to the CompTIA Network+ Study Manual, "TACACS+ is an authentication protocol used to centralize authentication and authorization for network devices. It is a more secure alternative to Telnet for handling logins and for granting privileges to users."

NEW QUESTION 539

- (Exam Topic 3)

An IT officer is installing a new WAP. Which of the following must the officer change to conned users securely to the WAP?

- A. AES encryption
- B. Channel to the highest frequency within the band
- C. TKIP encryption protocol
- D. Dynamic selection of the frequency

Answer: A

NEW QUESTION 544

- (Exam Topic 3)

A network administrator is decommissioning a server. Which of the following will the network administrator MOST likely consult?

- A. Onboarding and off boarding policies
- B. Business continuity plan
- C. Password requirements
- D. Change management documentation

Answer: D

NEW QUESTION 549

- (Exam Topic 3)

Which of the following provides guidance to an employee about restricting non-business access to the company's videoconferencing solution?

- A. Acceptable use policy
- B. Data loss prevention
- C. Remote access policy
- D. Standard operating procedure

Answer: A

Explanation:

An acceptable use policy (AUP) is a set of rules that outline the proper and improper use of an organization's resources, such as its videoconferencing solution. An AUP can provide guidance to employees about what is expected of them when using the organization's videoconferencing solution, including restricting non-business access to it.

NEW QUESTION 550

- (Exam Topic 3)

A network technician is troubleshooting an application issue. The technician is able to recreate the issue in a virtual environment. According to the troubleshooting methodology, which of the following actions will the technician most likely perform NEXT?

- A. Gather information from the initial report.
- B. Escalate the issue to a supervisor.
- C. Implement a solution to resolve the issue.
- D. Establish a theory of probable cause.

Answer: D

NEW QUESTION 551

- (Exam Topic 3)

Which of the following bandwidth management techniques uses buffers at the client side to prevent TCP retransmissions from occurring when the ISP starts to drop packets of specific types that exceed the agreed traffic rate?

- A. Traffic shaping
- B. Traffic policing
- C. Traffic marking
- D. Traffic prioritization

Answer: D

NEW QUESTION 552

- (Exam Topic 3)

AGRE tunnel has been configured between two remote sites. Which of the following features, when configured, ensures me GRE overhead does not affect payload?

- A. jumbo frames
- B. Auto medium-dependent Interface
- C. Interface crossover
- D. Collision detection

Answer: A

Explanation:

One of the features that can be configured to ensure that GRE overhead does not affect payload is A. jumbo frames. Jumbo frames are Ethernet frames that have a payload size larger than 1500 bytes, which is the standard maximum transmission unit (MTU) for Ethernet. By using jumbo frames, more data can be sent in each packet, reducing the overhead ratio and improving efficiency.

Auto medium-dependent interface (MDI), interface crossover, and collision detection are features related to Ethernet physical layer connectivity, but they do not affect GRE overhead or payload.

NEW QUESTION 556

- (Exam Topic 3)

Which of the following would be BEST to install to find and block any malicious users within a network?

- A. IDS
- B. IPS
- C. SCADA
- D. ICS

Answer: B

Explanation:

IPS takes action itself to block the attempted intrusion or otherwise remediate the incident. IDS is designed to only provide an alert about a potential incident, which enables a security operations center (SOC) analyst to investigate the event and determine whether it requires further action.

NEW QUESTION 557

- (Exam Topic 3)

Which of the following would be the MOST cost-effective recovery solution for a company's lower-priority applications?

- A. Warm site
- B. Cloud site
- C. Hot site
- D. Cold site

Answer: C

NEW QUESTION 560

- (Exam Topic 3)

A network administrator responds to a support ticket that was submitted by a customer who is having issues connecting to a website inside of the company network. The administrator verifies that the customer could not connect to a website using a URL. Which of the following troubleshooting steps would be BEST for the administrator to take?

- A. Check for certificate issues
- B. Contact the ISP
- C. Attempt to connect to the site via IP address
- D. Check the NTP configuration.

Answer: C

Explanation:

The best option for the administrator to take would be to attempt to connect to the site via IP address. This will help to determine if the issue is related to the website's DNS address or if the site itself is not accessible. Checking for certificate issues may be necessary, but this should be done after the administrator has attempted to connect to the site via IP address. Contacting the ISP is unnecessary since the issue is related to the website inside of the company network, and checking the NTP configuration is not relevant to this issue.

When a customer is having issues connecting to a website using a URL, one of the first troubleshooting steps a network administrator should take is attempting to connect to the site using the IP address of the website. This will help to determine if the issue is related to a DNS resolution problem or a connectivity problem. If the administrator is able to connect to the website using the IP address, then the issue may be related to a DNS problem. However, if the administrator is still unable to connect, then the issue may be related to a connectivity problem. In either case, further troubleshooting steps will be necessary. Checking for certificate issues or NTP configuration, and contacting the ISP would not be the BEST initial steps in this scenario.

NEW QUESTION 565

- (Exam Topic 3)

Which of the following can be used to store various types of devices and provide contactless delivery to users?

- A. Asset tags
- B. Biometrics
- C. Access control vestibules
- D. Smart lockers

Answer: C

NEW QUESTION 570

- (Exam Topic 3)

Which of the following BEST describes a split-tunnel client-to-server VPN connection?

- A. The client sends all network traffic down the VPN tunnel
- B. The client has two different IP addresses that can be connected to a remote site from two different ISPs to ensure availability
- C. The client sends some network traffic down the VPN tunnel and other traffic to the local gateway.
- D. The client connects to multiple remote sites at the same time

Answer: C

Explanation:

In a split-tunnel VPN, the client can access both the local network and the remote network simultaneously, with some network traffic sent through the VPN tunnel and other traffic sent to the local gateway. This approach allows for more efficient use of bandwidth and reduces the load on the VPN server. It also allows the client to continue accessing local resources while connected to the remote network.

NEW QUESTION 574

- (Exam Topic 3)

A security engineer is installing a new IDS on the network. The engineer has asked a network administrator to ensure all traffic entering and leaving the router interface is available for the IDS. Which of the following should the network administrator do?

- A. Install a network tap for the IDS
- B. Configure ACLs to route traffic to the IDS.
- C. Install an additional NIC into the IDS
- D. Install a loopback adapter for the IDS.
- E. Add an additional route on the router for the IDS.

Answer: A

Explanation:

a network tap is a way of connecting an IDS out of band, which means it does not interfere with the normal network traffic. A network tap allows you to view a copy of the network traffic transmitted over the media being tapped.

NEW QUESTION 579

- (Exam Topic 3)

A client who shares office space and an IT closet with another company recently reported connectivity issues throughout the network. Multiple third-party vendors regularly perform on-site maintenance in the shared IT closet. Which of the following security techniques would BEST secure the physical networking equipment?

- A. Disabling unneeded switchports
- B. Implementing role-based access
- C. Changing the default passwords
- D. Configuring an access control list

Answer: A

NEW QUESTION 583

- (Exam Topic 3)

A network technician was hired to harden the security of a network. The technician is required to enable encryption and create a password for AP security through the web browser. Which of the following would BEST support these requirements?

- A. ESP
- B. WPA2
- C. IPSec
- D. ACL

Answer: B

NEW QUESTION 584

- (Exam Topic 3)

A user reports that a new VoIP phone works properly, but the computer that is connected to the phone cannot access any network resources. Which of the following MOST likely needs to be configured correctly to provide network connectivity to the computer?

- A. Port duplex settings
- B. Port aggregation
- C. ARP settings
- D. VLAN tags
- E. MDIX settings

Answer: A

NEW QUESTION 585

- (Exam Topic 3)

A network is experiencing extreme latency when accessing a particular website. Which of the following commands will BEST help identify the issue?

- A. ipconfig
- B. netstat
- C. tracert
- D. ping

Answer: C

NEW QUESTION 587

- (Exam Topic 3)

A network administrator needs to provide evidence to confirm that recent network outages were caused by increased traffic generated by a recently released application. Which of the following actions will BEST support the administrator's response?

- A. Generate a network baseline report for comparison.
- B. Export the firewall traffic logs.
- C. Collect the router's NetFlow data.
- D. Plot interface statistics for dropped packets.

Answer: C

NEW QUESTION 589

- (Exam Topic 3)

An administrator is investigating reports of network slowness in a building. While looking at the uplink interface statistics in the switch's CLI, the administrator discovers the uplink is at 100% utilization. However, the administrator is unsure how to identify what traffic is causing the saturation. Which of the following tools should the administrator utilize to identify the source and destination addresses of the traffic?

- A. SNMP
- B. Traps
- C. Syslog
- D. NetFlow

Answer: D

Explanation:

To identify the source and destination addresses of the traffic causing network saturation, the network administrator should use a network protocol analyzer that supports the NetFlow protocol. NetFlow is a network protocol that collects IP traffic information as it enters or exits an interface and sends it to a NetFlow collector for analysis. This data includes the source and destination addresses of the traffic, the ports used, and the number of bytes and packets transferred.

Therefore, the correct answer is option D, NetFlow.

Reference: CompTIA Network+ Study Guide, Exam N10-007, Fourth Edition, by Todd Lammle (Chapter 6: Network Devices)

NEW QUESTION 592

- (Exam Topic 3)

A network security engineer locates an unapproved wireless bridge connected to the corporate LAN that is broadcasting a hidden SSID, providing unauthenticated access to internal resources. Which of the following types of attacks BEST describes this finding?

- A. Rogue access point Most Voted
- B. Evil twin
- C. ARP spoofing
- D. VLAN hopping

Answer: A

Explanation:

A rogue access point is an illegitimate access point plugged into a network to create a bypass from outside into the legitimate network. By contrast, an evil twin is a copy of a legitimate access point.

NEW QUESTION 597

- (Exam Topic 3)

A small office is running WiFi 4 APs, and neighboring offices do not want to increase the throughput to associated devices. Which of the following is the MOST cost-efficient way for the office to increase network performance?

- A. Add another AP.
- B. Disable the 2.4GHz radios.
- C. Enable channel bonding.
- D. Upgrade to WiFi 5.

Answer: C

Explanation:

Channel bonding is a practice commonly used in IEEE 802.11 implementations in which two adjacent channels within a given frequency band are combined to increase throughput between two or more wireless devices. Channel bonding is also known as Ethernet bonding, but it is used heavily in Wi-Fi implementations. It has become a very popular technique in the world of Wi-Fi because its increased throughput provides for more functionality within Wi-Fi deployments. Channel bonding is also known as NIC bonding. Source- <https://www.techopedia.com/definition/2999/channel-bonding>

NEW QUESTION 598

- (Exam Topic 3)

At which of the following OSI model layers does routing occur?

- A. Data link
- B. Transport
- C. Physical
- D. Network

Answer: D

NEW QUESTION 602

- (Exam Topic 3)

A technician wants to monitor and provide traffic segmentation across the network. The technician would like to assign each department a specific identifier. Which of the following will the technician MOST likely use?

- A. Flow control

- B. Traffic shaping
- C. VLAN tagging
- D. Network performance baselines

Answer: C

Explanation:

To monitor and provide traffic segmentation across the network, a technician may use the concept of VLANs (Virtual Local Area Networks). VLANs are a way of dividing a single physical network into multiple logical networks, each with its own unique identifier or "tag."

By assigning each department a specific VLAN identifier, the technician can segment the network traffic and ensure that the different departments' traffic is kept separate from one another. This can help to improve network security, performance, and scalability, as well as allowing for better monitoring and control of the network traffic.

To implement VLANs, the technician will need to configure VLAN tagging on the network devices, such as switches and routers, and assign each department's devices to the appropriate VLAN. The technician may also need to configure VLAN trunking to allow the different VLANs to communicate with each other.

By using VLANs, the technician can effectively monitor and segment the network traffic, providing better control and visibility into the network.

NEW QUESTION 605

- (Exam Topic 3)

Which of the following can be used to validate domain ownership by verifying the presence of pre-agreed content contained in a DNS record?

- A. SOA
- B. SRV
- C. AAA
- D. TXT

Answer: D

Explanation:

"One final usage of the TXT resource record is how some cloud service providers, such as Azure, validate ownership of custom domains. You are provided with data to include in your TXT record, and once that is created, the domain is verified and able to be used. The thought is that if you control the DNS, then you own the domain name."

NEW QUESTION 607

- (Exam Topic 3)

While waking from the parking lot to an access-controlled door an employee sees an authorized user open the door. Then the employee notices that another person catches the door before it closes and goes inside. Which of the following attacks is taking place?

- A. Tailgating
- B. Piggybacking
- C. Shoulder surfing
- D. Phishing

Answer: A

Explanation:

The difference between piggybacking and tailgating is that with piggybacking, the person is willfully and intentionally letting you in. In this particular case, the person caught the door before it closed, so it is tailgating.

NEW QUESTION 611

- (Exam Topic 3)

Which of the following layers of the OSI model receives data from the application layer and converts it into syntax that is readable by other devices on the network?

- A. Layer 1
- B. Layer 3
- C. Layer 6
- D. Layer 7

Answer: C

NEW QUESTION 612

- (Exam Topic 3)

Which of the following compromises internet-connected devices and makes them vulnerable to becoming part of a botnet? (Select TWO).

- A. Deauthentication attack
- B. Malware infection
- C. IP spoofing
- D. Firmware corruption
- E. Use of default credentials
- F. Dictionary attack

Answer: BE

NEW QUESTION 617

- (Exam Topic 3)

A network technician is attempting to increase throughput by configuring link port aggregation between a Gigabit Ethernet distribution switch and a Fast Ethernet access switch. Which of the following is the BEST choice concerning speed and duplex for all interfaces that are participating in the link aggregation?

- A. Half duplex and 1GB speed

- B. Full duplex and 1GB speed
- C. Half duplex and 100MB speed
- D. Full duplex and 100MB speed

Answer: B

Explanation:

The best choice for configuring link port aggregation between a Gigabit Ethernet distribution switch and a Fast Ethernet access switch is to use full duplex and 1GB speed for all interfaces that are participating in the link aggregation. This will allow for maximum throughput, as the full duplex connection will enable simultaneous sending and receiving of data, and the 1GB speed will ensure that the data is transferred quickly.

According to the CompTIA Network+ Study Guide, "Full-duplex Ethernet allows the network adapter to transmit and receive data simultaneously, which can result in double the bandwidth of half-duplex Ethernet." Additionally, the official text states, "Ethernet and Fast Ethernet use different speeds for data transmission, with Ethernet being 1,000 megabits (1 gigabit) per second and Fast Ethernet being 100 megabits per second."

NEW QUESTION 618

- (Exam Topic 3)

A company rents out a large event space and includes wireless internet access for each tenant. Tenants reserve a two-hour window from the company each week, which includes a tenant-specific SSID. However, all users share the company's network hardware.

Wireless encryption	WPA2
Captive portal	Disabled
AP isolation	Enabled
Subnet mask	255.255.255.0
DNS server	10.0.0.1
Default gateway	10.1.10.1
DHCP scope begin	10.1.10.10
DHCP scope end	10.1.10.150
DHCP lease time	24 hours

The network support team is receiving complaints from tenants that some users are unable to connect to the wireless network. Upon investigation, the support teams discover a pattern indicating that after a tenant with a particularly large attendance ends its sessions, tenants throughout the day are unable to connect. The following settings are common to all network configurations:

Which of the following actions would MOST likely reduce this issue? (Select TWO).

- A. Change to WPA encryption
- B. Change the DNS server to 10.1.10.1.
- C. Change the default gateway to 10.0.0.1.
- D. Change the DHCP scope end to 10.1.10.250
- E. Disable AP isolation
- F. Change the subnet mask to 255.255.255.192.
- G. Reduce the DHCP lease time to four hours.

Answer: DG

NEW QUESTION 621

- (Exam Topic 3)

A technician needs to configure a routing protocol for an internet-facing edge router. Which of the following routing protocols will the technician MOST likely use?

- A. BGP
- B. RIPv2
- C. OSPF
- D. EIGRP

Answer: A

NEW QUESTION 625

- (Exam Topic 3)

A network technician reviews an entry on the syslog server and discovers the following message from a switch:

SPANNING-TREE Port 1/1 BLOCKED

Which of the following describes the issue?

- A. A loop was discovered, and the impact was mitigated.
- B. An incorrectly pinned cable was disconnected.
- C. The link-local address on the port is incorrect.
- D. The port was shut down, and it needs to be reactivated.

Answer: A

NEW QUESTION 628

- (Exam Topic 3)

A technician knows the MAC address of a device and is attempting to find the device's IP address. Which of the following should the technician look at to find the IP address? (Select TWO).

- A. ARP table
- B. DHCP leases
- C. IP route table
- D. DNS cache

- E. MAC address table
- F. STP topology

Answer: BE

NEW QUESTION 632

- (Exam Topic 3)

A network technician receives a report about a performance issue on a client PC that is connected to port 1/3 on a network switch. The technician observes the following configuration output from the switch:

1/1	Client PC	Connected	Full	1000
1/2	Client PC	Connected	Full	1000
1/3	Client PC	Connected	Full	10

Which of the following is a cause of the issue on port 1/3?

- A. Speed
- B. Duplex
- C. Errors
- D. VLAN

Answer: A

NEW QUESTION 636

- (Exam Topic 3)

Which of the following is used to provide disaster recovery capabilities to spin up an critical devices using internet resources?

- A. Cloud site
- B. Hot site
- C. Cold site
- D. Warm site

Answer: A

NEW QUESTION 638

- (Exam Topic 3)

An IT administrator received an assignment with the following objectives

- Conduct a total scan within the company's network tor all connected hosts
- Detect all the types of operating systems running on all devices
- Discover all services offered by hosts on the network
- Find open ports and detect security risks.

Which of the following command-line tools can be used to achieve these objectives?

- A. nmap
- B. arp
- C. netatat
- D. tcpdump

Answer: A

Explanation:

Nmap (Network Mapper) is a free and open source command line tool that can be used to scan a network for all connected hosts, detect the types of operating systems running on all devices, discover all services offered by hosts on the network, find open ports, and detect security risks. Nmap is commonly used by system administrators and security professionals to audit a network's security and identify possible vulnerabilities. Nmap can be used to discover active hosts, scan ports, fingerprint operating systems, detect running services, and more. Reference: CompTIA Network+ Study Manual, 8th Edition, page 592.

NEW QUESTION 643

- (Exam Topic 3)

Which of the following records can be used to track the number of changes on a DNS zone?

- A. SOA
- B. SRV
- C. PTR
- D. NS

Answer: A

Explanation:

The DNS 'start of authority' (SOA) record stores important information about a domain or zone such as the email address of the administrator, when the domain was last updated, and how long the server should wait between refreshes. All DNS zones need an SOA record in order to conform to IETF standards. SOA records are also important for zone transfers.

NEW QUESTION 648

- (Exam Topic 3)

A network administrator is designing a wireless network. The administrator must ensure a rented office space has a sufficient signal. Reducing exposure to the wireless network is important, but it is secondary to the primary objective. Which of the following would MOST likely facilitate the correct accessibility to the Wi-Fi network?

- A. Polarization
- B. Channel utilization
- C. Channel bonding
- D. Antenna type
- E. MU-MIMO

Answer: B

NEW QUESTION 651

- (Exam Topic 3)

Which of the following is the MOST cost-effective alternative that provides proper cabling and supports gigabit Ethernet devices?

- A. Twisted cable with a minimum Cat 5e certification
- B. Multimode fiber with an SC connector
- C. Twinaxial cabling using an F-type connector
- D. Cable termination using TIA/EIA-568-B

Answer: A

Explanation:

twisted cable with a minimum Cat 5e certification is the MOST cost-effective alternative that provides proper cabling and supports gigabit Ethernet devices.

NEW QUESTION 654

- (Exam Topic 3)

An employee reports to a network administrator that internet access is not working. Which of the following should the administrator do FIRST?

- A. Establish a theory of probable cause.
- B. Identify symptoms.
- C. Determine if anything has changed.
- D. Ask the user to restart the computer.

Answer: C

Explanation:

When a user reports that internet access is not working, it is important to first determine if there have been any recent changes to the network or the user's computer that could have caused the issue. This could include changes to the network configuration, the installation of new software or hardware, or other events that could have impacted the user's ability to access the internet. By determining if anything has changed, the administrator can narrow down the possible causes of the issue and focus on addressing the most likely cause.

NEW QUESTION 655

- (Exam Topic 3)

A network engineer is investigating reports of poor network performance. Upon reviewing a report, the engineer finds hundreds of CRC errors on an interface. Which of the following is the MOST likely cause of these errors?

- A. A bad wire on the Cat 5e cable
- B. The wrong VLAN assignment to the switchport
- C. A misconfigured QoS setting on the router
- D. Both sides of the switch trunk set to full duplex

Answer: A

NEW QUESTION 659

- (Exam Topic 3)

Due to a surge in business, a company is onboarding an unusually high number of salespeople. The salespeople are assigned desktops that are wired to the network. The last few salespeople to be onboarded are able to access corporate materials on the network but not sales-specific resources. Which of the following is MOST likely the cause?

- A. The switch was configured with port security.
- B. Newly added machines are running into DHCP conflicts.
- C. The IPS was not configured to recognize the new users.
- D. Recently added users were assigned to the wrong VLAN

Answer: D

NEW QUESTION 663

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

N10-008 Practice Exam Features:

- * N10-008 Questions and Answers Updated Frequently
- * N10-008 Practice Questions Verified by Expert Senior Certified Staff
- * N10-008 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * N10-008 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The N10-008 Practice Test Here](#)