

## AWS-Solution-Architect-Associate Dumps

### AWS Certified Solutions Architect - Associate

<https://www.certleader.com/AWS-Solution-Architect-Associate-dumps.html>



**NEW QUESTION 1**

You are trying to launch an EC2 instance, however the instance seems to go into a terminated status immediately. What would probably not be a reason that this is happening?

- A. The AMI is missing a required part.
- B. The snapshot is corrupt.
- C. You need to create storage in EBS first.
- D. You've reached your volume limit

**Answer:** C

**Explanation:** Amazon EC2 provides a virtual computing environments, known as an instance.

After you launch an instance, AWS recommends that you check its status to confirm that it goes from the pending status to the running status, the not terminated status.

The following are a few reasons why an Amazon EBS-backed instance might immediately terminate: You've reached your volume limit.

The AMI is missing a required part. The snapshot is corrupt. Reference:

[http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/Using\\_InstanceStraightToTerminated.html](http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/Using_InstanceStraightToTerminated.html)

**NEW QUESTION 2**

In Amazon EC2 Container Service components, what is the name of a logical grouping of container instances on which you can place tasks?

- A. A cluster
- B. A container instance
- C. A container
- D. A task definition

**Answer:** A

**Explanation:** Amazon ECS contains the following components:

A Cluster is a logical grouping of container instances that you can place tasks on.

A Container instance is an Amazon EC2 instance that is running the Amazon ECS agent and has been registered into a cluster.

A Task definition is a description of an application that contains one or more container definitions. A Scheduler is the method used for placing tasks on container instances.

A Service is an Amazon ECS service that allows you to run and maintain a specified number of instances of a task definition simultaneously.

A Task is an instantiation of a task definition that is running on a container instance. A Container is a Linux container that was created as part of a task.

Reference: <http://docs.aws.amazon.com/AmazonECS/latest/developerguide/Welcome.html>

**NEW QUESTION 3**

Can a user get a notification of each instance start / terminate configured with Auto Scaling?

- A. Yes, if configured with the Launch Config
- B. Yes, always
- C. Yes, if configured with the Auto Scaling group
- D. No

**Answer:** C

**Explanation:** The user can get notifications using SNS if he has configured the notifications while creating the Auto Scaling group.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/GettingStartedTutorial.html>

**NEW QUESTION 4**

To specify a resource in a policy statement, in Amazon EC2, can you use its Amazon Resource Name (ARN)?

- A. Yes, you can.
- B. No, you can't because EC2 is not related to ARN.
- C. No, you can't because you can't specify a particular Amazon EC2 resource in an IAM policy.
- D. Yes, you can but only for the resources that are not affected by the action

**Answer:** A

**Explanation:** Some Amazon EC2 API actions allow you to include specific resources in your policy that can be created or modified by the action. To specify a resource in the statement, you need to use its Amazon Resource Name (ARN).

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ec2-ug.pdf>

**NEW QUESTION 5**

After you recommend Amazon Redshift to a client as an alternative solution to paying data warehouses to analyze his data, your client asks you to explain why you are recommending Redshift. Which of the following would be a reasonable response to his request?

- A. It has high performance at scale as data and query complexity grows.
- B. It prevents reporting and analytic processing from interfering with the performance of OLTP workloads.
- C. You don't have the administrative burden of running your own data warehouse and dealing with setup, durability, monitoring, scaling, and patching.
- D. All answers listed are a reasonable response to his QUESTION

**Answer:** D

**Explanation:** Amazon Redshift delivers fast query performance by using columnar storage technology to improve I/O efficiency and parallelizing queries across multiple nodes. Redshift uses standard PostgreSQL JDBC and ODBC drivers, allowing you to use a wide range of familiar SQL clients. Data load speed scales linearly with cluster size, with integrations to Amazon S3, Amazon DynamoDB, Amazon Elastic MapReduce, Amazon Kinesis or any SSH-enabled host.

AWS recommends Amazon Redshift for customers who have a combination of needs, such as: High performance at scale as data and query complexity grows  
Desire to prevent reporting and analytic processing from interfering with the performance of OLTP workloads

Large volumes of structured data to persist and query using standard SQL and existing BI tools  
Desire to the administrative burden of running one's own data warehouse and dealing with setup, durability, monitoring, scaling and patching

Reference: [https://aws.amazon.com/running\\_databases/#redshift\\_anchor](https://aws.amazon.com/running_databases/#redshift_anchor)

#### NEW QUESTION 6

A user is launching an EC2 instance in the US East region. Which of the below mentioned options is recommended by AWS with respect to the selection of the availability zone?

- A. Always select the AZ while launching an instance
- B. Always select the US-East-1-a zone for HA
- C. Do not select the AZ; instead let AWS select the AZ
- D. The user can never select the availability zone while launching an instance

**Answer:** C

**Explanation:** When launching an instance with EC2, AWS recommends not to select the availability zone (AZ). AWS specifies that the default Availability Zone should be accepted. This is because it enables AWS to select the best Availability Zone based on the system health and available capacity. If the user launches additional instances, only then an Availability Zone should be specified. This is to specify the same or different AZ from the running instances.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-regions-availability-zones.html>

#### NEW QUESTION 7

A user is storing a large number of objects on AWS S3. The user wants to implement the search functionality among the objects. How can the user achieve this?

- A. Use the indexing feature of S3.
- B. Tag the objects with the metadata to search on that.
- C. Use the query functionality of S3.
- D. Make your own DB system which stores the S3 metadata for the search functionalit

**Answer:** D

**Explanation:** In Amazon Web Services, AWS S3 does not provide any query facility. To retrieve a specific object the user needs to know the exact bucket / object key. In this case it is recommended to have an own DB system which manages the S3 metadata and key mapping.

Reference: [http://media.amazonwebservices.com/AWS\\_Storage\\_Options.pdf](http://media.amazonwebservices.com/AWS_Storage_Options.pdf)

#### NEW QUESTION 8

After setting up a Virtual Private Cloud (VPC) network, a more experienced cloud engineer suggests that to achieve low network latency and high network throughput you should look into setting up a placement group. You know nothing about this, but begin to do some research about it and are especially curious about its limitations. Which of the below statements is wrong in describing the limitations of a placement group?

- A. Although launching multiple instance types into a placement group is possible, this reduces the likelihood that the required capacity will be available for your launch to succeed.
- B. A placement group can span multiple Availability Zones.
- C. You can't move an existing instance into a placement group.
- D. A placement group can span peered VPCs

**Answer:** B

**Explanation:** A placement group is a logical grouping of instances within a single Availability Zone. Using placement groups enables applications to participate in a low-latency, 10 Gbps network. Placement groups are recommended for applications that benefit from low network latency, high network throughput, or both. To provide the lowest latency, and the highest packet-per-second network performance for your placement group, choose an instance type that supports enhanced networking.

Placement groups have the following limitations:

The name you specify for a placement group a name must be unique within your AWS account. A placement group can't span multiple Availability Zones.

Although launching multiple instance types into a placement group is possible, this reduces the likelihood that the required capacity will be available for your launch to succeed. We recommend using the same instance type for all instances in a placement group.

You can't merge placement groups. Instead, you must terminate the instances in one placement group, and then relaunch those instances into the other placement group.

A placement group can span peered VPCs; however, you will not get full-bisection bandwidth between instances in peered VPCs. For more information about VPC peering connections, see VPC Peering in the Amazon VPC User Guide.

You can't move an existing instance into a placement group. You can create an AM from your existing instance, and then launch a new instance from the AMI into a placement group.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/placement-groups.html>

#### NEW QUESTION 9

What is a placement group in Amazon EC2?

- A. It is a group of EC2 instances within a single Availability Zone.

- B. It the edge location of your web content.
- C. It is the AWS region where you run the EC2 instance of your web content.
- D. It is a group used to span multiple Availability Zone

**Answer:** A

**Explanation:** A placement group is a logical grouping of instances within a single Availability Zone. Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/placement-groups.html>

#### NEW QUESTION 10

True or false? A VPC contains multiple subnets, where each subnet can span multiple Availability Zones.

- A. This is true only if requested during the set-up of VPC.
- B. This is true.
- C. This is false.
- D. This is true only for US region

**Answer:** C

**Explanation:** A VPC can span several Availability Zones. In contrast, a subnet must reside within a single Availability Zone. Reference: <https://aws.amazon.com/vpc/faqs/>

#### NEW QUESTION 10

You are looking at ways to improve some existing infrastructure as it seems a lot of engineering resources are being taken up with basic management and monitoring tasks and the costs seem to be excessive.

You are thinking of deploying Amazon ElastiCache to help. Which of the following statements is true in regards to ElastiCache?

- A. You can improve load and response times to user actions and queries however the cost associated with scaling web applications will be more.
- B. You can't improve load and response times to user actions and queries but you can reduce the cost associated with scaling web applications.
- C. You can improve load and response times to user actions and queries however the cost associated with scaling web applications will remain the same.
- D. You can improve load and response times to user actions and queries and also reduce the cost associated with scaling web applications.

**Answer:** D

**Explanation:** Amazon ElastiCache is a web service that makes it easy to deploy and run Memcached or Redis protocol-compliant server nodes in the cloud. Amazon ElastiCache improves the performance of web applications by allowing you to retrieve information from a fast, managed, in-memory caching system, instead of relying entirely on slower disk-based databases. The service simplifies and offloads the management, monitoring and operation of in-memory cache environments, enabling your engineering resources to focus on developing applications. Using Amazon ElastiCache, you can not only improve load and response times to user actions and queries, but also reduce the cost associated with scaling web applications. Reference: <https://aws.amazon.com/elasticache/faqs/>

#### NEW QUESTION 12

Do Amazon EBS volumes persist independently from the running life of an Amazon EC2 instance?

- A. Yes, they do but only if they are detached from the instance.
- B. No, you cannot attach EBS volumes to an instance.
- C. No, they are dependent.
- D. Yes, they d

**Answer:** D

**Explanation:** An Amazon EBS volume behaves like a raw, unformatted, external block device that you can attach to a single instance. The volume persists independently from the running life of an Amazon EC2 instance. Reference: <http://docs.amazonaws.com/AWSEC2/latest/UserGuide/Storage.html>

#### NEW QUESTION 15

Your supervisor has asked you to build a simple file synchronization service for your department. He doesn't want to spend too much money and he wants to be notified of any changes to files by email. What do you think would be the best Amazon service to use for the email solution?

- A. Amazon SES
- B. Amazon CloudSearch
- C. Amazon SWF
- D. Amazon AppStream

**Answer:** A

**Explanation:** File change notifications can be sent via email to users following the resource with Amazon Simple Email Service (Amazon SES), an easy-to-use, cost-effective email solution. Reference: [http://media.amazonaws.com/architecturecenter/AWS\\_ac\\_ra\\_filesync\\_08.pdf](http://media.amazonaws.com/architecturecenter/AWS_ac_ra_filesync_08.pdf)

#### NEW QUESTION 16

Your manager has just given you access to multiple VPN connections that someone else has recently set up between all your company's offices. She needs you to make sure that the communication between the VPNs is secure. Which of the following services would be best for providing a low-cost hub-and-spoke model for primary or backup connectivity between these remote offices?

- A. Amazon CloudFront
- B. AWS Direct Connect
- C. AWS CloudHSM
- D. AWS VPN CloudHub

**Answer:** D

**Explanation:** If you have multiple VPN connections, you can provide secure communication between sites using the AWS VPN CloudHub. The VPN CloudHub operates on a simple hub-and-spoke model that you can use with or without a VPC. This design is suitable for customers with multiple branch offices and existing Internet connections who would like to implement a convenient, potentially low-cost hub-and-spoke model for primary or backup connectivity between these remote offices.

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPN\\_CloudHub.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPN_CloudHub.html)

#### NEW QUESTION 17

Amazon EC2 provides a . It is an HTTP or HTTPS request that uses the HTTP verbs GET or POST.

- A. web database
- B. .net framework
- C. Query API
- D. C library

**Answer:** C

**Explanation:** Amazon EC2 provides a Query API. These requests are HTTP or HTTPS requests that use the HTTP verbs GET or POST and a Query parameter named Action.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/APIReference/making-api-requests.html>

#### NEW QUESTION 22

Does Amazon DynamoDB support both increment and decrement atomic operations?

- A. Only increment, since decrement are inherently impossible with DynamoDB's data model.
- B. No, neither increment nor decrement operations.
- C. Yes, both increment and decrement operations.
- D. Only decrement, since increment are inherently impossible with DynamoDB's data model

**Answer:** C

**Explanation:** Amazon DynamoDB supports increment and decrement atomic operations.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/APISummary.html>

#### NEW QUESTION 25

An organization has three separate AWS accounts, one each for development, testing, and production. The organization wants the testing team to have access to certain AWS resources in the production account. How can the organization achieve this?

- A. It is not possible to access resources of one account with another account.
- B. Create the IAM roles with cross account access.
- C. Create the IAM user in a test account, and allow it access to the production environment with the IAM policy.
- D. Create the IAM users with cross account access

**Answer:** B

**Explanation:** An organization has multiple AWS accounts to isolate a development environment from a testing or production environment. At times the users from one account need to access resources in the other account, such as promoting an update from the development environment to the production environment. In this case the IAM role with cross account access will provide a solution. Cross account access lets one account share access to their resources with users in the other AWS accounts.

Reference: [http://media.amazonwebservices.com/AWS\\_Security\\_Best\\_Practices.pdf](http://media.amazonwebservices.com/AWS_Security_Best_Practices.pdf)

#### NEW QUESTION 28

You need to migrate a large amount of data into the cloud that you have stored on a hard disk and you decide that the best way to accomplish this is with AWS Import/Export and you mail the hard disk to AWS. Which of the following statements is incorrect in regards to AWS Import/Export?

- A. It can export from Amazon S3
- B. It can Import to Amazon Glacier
- C. It can export from Amazon Glacier.
- D. It can Import to Amazon EBS

**Answer:** C

**Explanation:** AWS Import/Export supports: Import to Amazon S3  
Export from Amazon S3 Import to Amazon EBS Import to Amazon Glacier



AWS Import/Export does not currently support export from Amazon EBS or Amazon Glacier. Reference:  
<https://docs.aws.amazon.com/AWSImportExport/latest/DG/whatisdisk.html>

**NEW QUESTION 30**

A user wants to use an EBS-backed Amazon EC2 instance for a temporary job. Based on the input data, the job is most likely to finish within a week. Which of the following steps should be followed to terminate the instance automatically once the job is finished?

- A. Configure the EC2 instance with a stop instance to terminate it.
- B. Configure the EC2 instance with ELB to terminate the instance when it remains idle.
- C. Configure the CloudWatch alarm on the instance that should perform the termination action once the instance is idle.
- D. Configure the Auto Scaling schedule actMty that terminates the instance after 7 day

**Answer:** C

**Explanation:** Auto Scaling can start and stop the instance at a pre-defined time. Here, the total running time is unknown. Thus, the user has to use the CloudWatch alarm, which monitors the CPU utilization. The user can create an alarm that is triggered when the average CPU utilization percentage has been lower than 10 percent

for 24 hours, signaling that it is idle and no longer in use. When the utilization is below the threshold limit, it will terminate the instance as a part of the instance action.

Reference: <http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/UsingAlarmActions.html>

**NEW QUESTION 35**

An Elastic IP address (EIP) is a static IP address designed for dynamic cloud computing. With an EIP, you can mask the failure of an instance or software by rapidly remapping the address to another instance in your account. Your EIP is associated with your AWS account, not a particular EC2 instance, and it remains associated with your account until you choose to explicitly release it. By default how many EIPs is each AWS account limited to on a per region basis?

- A. 1
- B. 5
- C. Unlimited
- D. 10

**Answer:** B

**Explanation:** By default, all AWS accounts are limited to 5 Elastic IP addresses per region for each AWS account, because public (IPv4) Internet addresses are a scarce public resource. AWS strongly encourages you to use an EIP primarily for load balancing use cases, and use DNS hostnames for all other inter-node communication.

If you feel your architecture warrants additional EIPs, you would need to complete the Amazon EC2 Elastic IP Address Request Form and give reasons as to your need for additional addresses. Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/elastic-ip-addresses-eip.html#using-instance-addressing-limit>

**NEW QUESTION 36**

In Amazon EC2, partial instance-hours are billed .

- A. per second used in the hour
- B. per minute used
- C. by combining partial segments into full hours
- D. as full hours

**Answer:** D

**Explanation:** Partial instance-hours are billed to the next hour. Reference: <http://aws.amazon.com/ec2/faqs/>

**NEW QUESTION 41**

You are setting up a VPC and you need to set up a public subnet within that VPC. Which following requirement must be met for this subnet to be considered a public subnet?

- A. Subnet's traffic is not routed to an internet gateway but has its traffic routed to a virtual private gateway.
- B. Subnet's traffic is routed to an internet gateway.
- C. Subnet's traffic is not routed to an internet gateway.
- D. None of these answers can be considered a public subne

**Answer:** B

**Explanation:** A virtual private cloud (VPC) is a virtual network dedicated to your AWS account. It is logically isolated from other virtual networks in the AWS cloud. You can launch your AWS resources, such as Amazon EC2 instances, into your VPC. You can configure your VPC: you can select its IP address range, create subnets, and configure route tables, network gateways, and security settings.

A subnet is a range of IP addresses in your VPC. You can launch AWS resources into a subnet that you select. Use a public subnet for resources that must be connected to the internet, and a private subnet for resources that won't be connected to the Internet.

If a subnet's traffic is routed to an internet gateway, the subnet is known as a public subnet.

If a subnet doesn't have a route to the internet gateway, the subnet is known as a private subnet.

If a subnet doesn't have a route to the internet gateway, but has its traffic routed to a virtual private gateway, the subnet is known as a VPN-only subnet.

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_Subnets.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Subnets.html)

**NEW QUESTION 42**

While using the EC2 GET requests as URLs, the is the URL that serves as the entry point for the web service.

- A. token
- B. endpoint
- C. action
- D. None of these

**Answer:** B

**Explanation:** The endpoint is the URL that serves as the entry point for the web service.

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/using-query-api.html>

**NEW QUESTION 43**

You have been asked to build a database warehouse using Amazon Redshift. You know a little about it, including that it is a SQL data warehouse solution, and uses industry standard ODBC and JDBC connections and PostgreSQL drivers. However you are not sure about what sort of storage it uses for database tables. What sort of storage does Amazon Redshift use for database tables?

- A. InnoDB Tables
- B. NDB data storage
- C. Columnar data storage
- D. NDB CLUSTER Storage

**Answer:** C

**Explanation:** Amazon Redshift achieves efficient storage and optimum query performance through a combination of massively parallel processing, columnar data storage, and very efficient, targeted data compression encoding schemes.

Columnar storage for database tables is an important factor in optimizing analytic query performance because it drastically reduces the overall disk I/O requirements and reduces the amount of data you need to load from disk.

Reference: [http://docs.aws.amazon.com/redshift/latest/dg/c\\_columnar\\_storage\\_disk\\_mem\\_mgmnt.html](http://docs.aws.amazon.com/redshift/latest/dg/c_columnar_storage_disk_mem_mgmnt.html)

**NEW QUESTION 47**

Which of the below mentioned options is not available when an instance is launched by Auto Scaling with EC2 Classic?

- A. Public IP
- B. Elastic IP
- C. Private DNS
- D. Private IP

**Answer:** B

**Explanation:** Auto Scaling supports both EC2 classic and EC2-VPC. When an instance is launched as a part of EC2 classic, it will have the public IP and DNS as well as the private IP and DNS.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/GettingStartedTutorial.html>

**NEW QUESTION 52**

You have been given a scope to deploy some AWS infrastructure for a large organisation. The requirements are that you will have a lot of EC2 instances but may need to add more when the average utilization of your Amazon EC2 fleet is high and conversely remove them when CPU utilization is low. Which AWS services would be best to use to accomplish this?

- A. Auto Scaling, Amazon CloudWatch and AWS Elastic Beanstalk
- B. Auto Scaling, Amazon CloudWatch and Elastic Load Balancing.
- C. Amazon CloudFront, Amazon CloudWatch and Elastic Load Balancing.
- D. AWS Elastic Beanstalk , Amazon CloudWatch and Elastic Load Balancing

**Answer:** B

**Explanation:** Auto Scaling enables you to follow the demand curve for your applications closely, reducing the need to manually provision Amazon EC2 capacity in advance. For example, you can set a condition to add new

Amazon EC2 instances in increments to the Auto Scaling group when the average utilization of your Amazon EC2 fleet is high; and similarly, you can set a condition to remove instances in the same increments when CPU utilization is low. If you have predictable load changes, you can set a schedule through Auto Scaling to plan your scaling activities. You can use Amazon CloudWatch to send alarms to trigger scaling activities and Elastic Load Balancing to help distribute traffic to your instances within Auto Scaling groups. Auto Scaling enables you to run your Amazon EC2 fleet at optimal utilization. Reference:

<http://aws.amazon.com/autoscaling/>

**NEW QUESTION 54**

You are building infrastructure for a data warehousing solution and an extra request has come through that there will be a lot of business reporting queries running all the time and you are not sure if your current DB instance will be able to handle it. What would be the best solution for this?

- A. DB Parameter Groups
- B. Read Replicas
- C. Multi-AZ DB Instance deployment
- D. Database Snapshots

**Answer:**

B

**Explanation:** Read Replicas make it easy to take advantage of MySQL's built-in replication functionality to elastically scale out beyond the capacity constraints of a single DB Instance for read-heavy database workloads. There are a variety of scenarios where deploying one or more Read Replicas for a given source DB Instance may make sense. Common reasons for deploying a Read Replica include:

Scaling beyond the compute or I/O capacity of a single DB Instance for read-heavy database workloads. This excess read traffic can be directed to one or more Read Replicas.

Serving read traffic while the source DB Instance is unavailable. If your source DB Instance cannot take I/O requests (e.g. due to I/O suspension for backups or scheduled maintenance), you can direct read traffic to your Read Replica(s). For this use case, keep in mind that the data on the Read Replica may be "stale" since the source DB Instance is unavailable.

Business reporting or data warehousing scenarios; you may want business reporting queries to run against a Read Replica, rather than your primary, production DB Instance.

Reference: <https://aws.amazon.com/rds/faqs/>

#### NEW QUESTION 56

In DynamoDB, could you use IAM to grant access to Amazon DynamoDB resources and API actions?

- A. In DynamoDB there is no need to grant access
- B. Depended to the type of access
- C. No
- D. Yes

**Answer:** D

**Explanation:** Amazon DynamoDB integrates with AWS Identity and Access Management (IAM). You can use AWS IAM to grant access to Amazon DynamoDB resources and API actions. To do this, you first write an AWS IAM policy, which is a document that explicitly lists the permissions you want to grant. You then attach that policy to an AWS IAM user or role.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/UsingIAMWithDDB.html>

#### NEW QUESTION 59

Your EBS volumes do not seem to be performing as expected and your team leader has requested you look into improving their performance. Which of the following is not a true statement relating to the performance of your EBS volumes?

- A. Frequent snapshots provide a higher level of data durability and they will not degrade the performance of your application while the snapshot is in progress.
- B. General Purpose (SSD) and Provisioned IOPS (SSD) volumes have a throughput limit of 128 MB/s per volume.
- C. There is a relationship between the maximum performance of your EBS volumes, the amount of I/O you are drMng to them, and the amount of time it takes for each transaction to complete.
- D. There is a 5 to 50 percent reduction in IOPS when you first access each block of data on a newly created or restored EBS volume

**Answer:** A

**Explanation:** Several factors can affect the performance of Amazon EBS volumes, such as instance configuration, I/O characteristics, workload demand, and storage configuration.

Frequent snapshots provide a higher level of data durability, but they may slightly degrade the performance of your application while the snapshot is in progress. This trade off becomes critical when you have data that changes rapidly. Whenever possible, plan for snapshots to occur during off-peak times in order to minimize workload impact.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSPerformance.html>

#### NEW QUESTION 61

You've created your first load balancer and have registered your EC2 instances with the load balancer. Elastic Load Balancing routinely performs health checks on all the registered EC2 instances and automatically distributes all incoming requests to the DNS name of your load balancer across your registered, healthy EC2 instances. By default, the load balancer uses the \_ protocol for checking the health of your instances.

- A. HTTPS
- B. HTTP
- C. ICMP
- D. IPv6

**Answer:** B

**Explanation:** In Elastic Load Balancing a health configuration uses information such as protocol, ping port, ping path (URL), response timeout period, and health check interval to determine the health state of the instances registered with the load balancer.

Currently, HTTP on port 80 is the default health check. Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/TerminologyandKeyConcepts.html>

#### NEW QUESTION 66

is a fast, filexible, fully managed push messaging service.

- A. Amazon SNS
- B. Amazon SES
- C. Amazon SQS
- D. Amazon FPS

**Answer:** A



**Explanation:** Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, fully managed push messaging service. Amazon SNS makes it simple and cost-effective to push to mobile devices such as iPhone, iPad, Android, Kindle Fire, and internet connected smart devices, as well as pushing to other distributed services.

Reference: [http://aws.amazon.com/sns/?nc1=h\\_I2\\_as](http://aws.amazon.com/sns/?nc1=h_I2_as)

#### NEW QUESTION 69

As AWS grows, most of your clients' main concerns seem to be about security, especially when all of their competitors also seem to be using AWS. One of your clients asks you whether having a competitor who hosts their EC2 instances on the same physical host would make it easier for the competitor to hack into the client's data. Which of the following statements would be the best choice to put your client's mind at rest?

- A. Different instances running on the same physical machine are isolated from each other via a 256-bit Advanced Encryption Standard (AES-256).
- B. Different instances running on the same physical machine are isolated from each other via the Xen hypervisor and via a 256-bit Advanced Encryption Standard (AES-256).
- C. Different instances running on the same physical machine are isolated from each other via the Xen hypervisor.
- D. Different instances running on the same physical machine are isolated from each other via IAM permissions.

**Answer:** C

**Explanation:** Amazon Elastic Compute Cloud (EC2) is a key component in Amazon's Infrastructure as a Service (IaaS), providing resizable computing capacity using server instances in AWS's data centers. Amazon EC2 is designed to make web-scale computing easier by enabling you to obtain and configure capacity with minimal friction.

You create and launch instances, which are collections of platform hardware and software. Different instances running on the same physical machine are isolated from each other via the Xen hypervisor.

Amazon is active in the Xen community, which provides awareness of the latest developments. In addition, the AWS firewall resides within the hypervisor layer, between the physical network interface and the instance's virtual interface. All packets must pass through this layer, thus an instance's neighbors have no more access to that instance than any other host on the Internet and can be treated as if they are on separate physical hosts. The physical RAM is separated using similar mechanisms.

Reference: <http://d0.awsstatic.com/whitepapers/Security/AWS%20Security%20Whitepaper.pdf>

#### NEW QUESTION 74

You need to set up a complex network infrastructure for your organization that will be reasonably easy to deploy, replicate, control, and track changes on. Which AWS service would be best to use to help you accomplish this?

- A. AWS Import/Export
- B. AWS CloudFormation
- C. Amazon Route 53
- D. Amazon CloudWatch

**Answer:** B

**Explanation:** AWS CloudFormation is a service that helps you model and set up your Amazon Web Services resources so that you can spend less time managing those resources and more time focusing on your applications that run in AWS. You create a template that describes all the AWS resources that you want (like Amazon EC2 instances or Amazon RDS DB instances), and AWS CloudFormation takes care of provisioning and configuring those resources for you. You don't need to manually create and configure AWS resources

and figure out what's dependent on what. AWS CloudFormation handles all of that.

Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/Welcome.html>

#### NEW QUESTION 79

You have just been given a scope for a new client who has an enormous amount of data (petabytes) that he constantly needs analysed. Currently he is paying a huge amount of money for a data warehousing company to do this for him and is wondering if AWS can provide a cheaper solution. Do you think AWS has a solution for this?

- A. Yes
- B. Amazon SimpleDB
- C. No
- D. Not presently
- E. Yes
- F. Amazon Redshift
- G. Yes
- H. Your choice of relational AMIs on Amazon EC2 and EBS

**Answer:** C

**Explanation:** Amazon Redshift is a fast, fully managed, petabyte-scale data warehouse service that makes it simple and cost-effective to efficiently analyze all your data using your existing business intelligence tools. You can start small for just \$0.25 per hour with no commitments or upfront costs and scale to a petabyte or more for \$1,000 per terabyte per year, less than a tenth of most other data warehousing solutions. Amazon Redshift delivers fast query performance by using columnar storage technology to improve I/O efficiency and parallelizing queries across multiple nodes. Redshift uses standard PostgreSQL JDBC and ODBC drivers, allowing you to use a wide range of familiar SQL clients. Data load speed scales linearly with cluster size, with integrations to Amazon S3, Amazon DynamoDB, Amazon Elastic MapReduce, Amazon Kinesis or any SSH-enabled host.

Reference: [https://aws.amazon.com/running\\_databases/#redshift\\_anchor](https://aws.amazon.com/running_databases/#redshift_anchor)

#### NEW QUESTION 82

In an experiment, if the minimum size for an Auto Scaling group is 1 instance, which of the following statements holds true when you terminate the running instance?

- A. Auto Scaling must launch a new instance to replace it.
- B. Auto Scaling will raise an alarm and send a notification to the user for action.
- C. Auto Scaling must configure the schedule actMty that terminates the instance after 5 days.
- D. Auto Scaling will terminate the experimen

**Answer:** A

**Explanation:** If the minimum size for an Auto Scaling group is 1 instance, when you terminate the running instance, Auto Scaling must launch a new instance to replace it.

Reference: [http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AS\\_Concepts.html](http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AS_Concepts.html)

#### NEW QUESTION 87

In Amazon EC2, while sharing an Amazon EBS snapshot, can the snapshots with AWS IV|arketplace product codes be public?

- A. Yes, but only for US-based providers.
- B. Yes, they can be public.
- C. No, they cannot be made public.
- D. Yes, they are automatically made public by the syste

**Answer:** C

**Explanation:** Snapshots with AWS Marketplace product codes can't be made public. Reference:

[http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/ebs-modifying-snapshot-permissions.ht ml](http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/ebs-modifying-snapshot-permissions.html)

#### NEW QUESTION 89

An organization has created an application which is hosted on the AWS EC2 instance. The application stores images to S3 when the end user uploads to it. The organization does not want to store the AWS secure credentials required to access the S3 inside the instance. Which of the below mentioned options is a possible solution to avoid any security threat?

- A. Use the IAM based single sign between the AWS resources and the organization application.
- B. Use the IAM role and assign it to the instance.
- C. Since the application is hosted on EC2, it does not need credentials to access S3.
- D. Use the X.509 certificates instead of the access and the secret access key

**Answer:** B

**Explanation:** The AWS IAM role uses temporary security credentials to access AWS services. Once the role is assigned to an instance, it will not need any security credentials to be stored on the instance. Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/iam-roles-for-amazon-ec2.html>

#### NEW QUESTION 93

You are running PostgreSQL on Amazon RDS and it seems to be all running smoothly deployed in one availability zone. A database administrator asks you if DB instances running PostgreSQL support Multi-AZ deployments. What would be a correct response to this QUESTION ?

- A. Yes.
- B. Yes but only for small db instances.
- C. No.
- D. Yes but you need to request the service from AW

**Answer:** A

**Explanation:** Amazon RDS supports DB instances running several versions of PostgreSQL. Currently we support PostgreSQL versions 9.3.1, 9.3.2, and 9.3.3.

You can create DB instances and DB snapshots, point-in-time restores and backups.

DB instances running PostgreSQL support Multi-AZ deployments, Provisioned IOPS, and can be created inside a VPC. You can also use SSL to connect to a DB instance running PostgreSQL.

You can use any standard SQL client application to run commands for the instance from your client computer. Such applications include pgAdmin, a popular Open Source administration and development tool for PostgreSQL, or psql, a command line utility that is part of a PostgreSQL installation. In order to deliver a managed service experience, Amazon RDS does not provide host access to DB instances, and it restricts access to certain system procedures and tables that require advanced prMleges. Amazon RDS supports access to databases on a DB instance using any standard SQL client application. Amazon RDS does not allow direct host access to a DB instance via Telnet or Secure Shell (SSH).

Reference: [http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP\\_PostgreSQL.html](http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP_PostgreSQL.html)

#### NEW QUESTION 95

Which of the following AWS CLI commands is syntactically incorrect?

- 1. \$ aws ec2 describe-instances
- 2. \$ aws ec2 start-instances --instance-ids i-1348636c
- 3. \$ aws sns publish --topic-arn arn:aws:sns:us-east-1:546419318123:OperationsError -message "Script Failure"
- 4. \$ aws sqs receive-message --queue-url https://queue.amazonaws.com/546419318123/Test

- A. 3
- B. 4
- C. 2
- D. 1

**Answer:** A

**Explanation:** The following CLI command is missing a hyphen before "-message".

aws sns publish --topic-arn arn:aws:sns:us-east-1:546419318123:OperationsError -message "Script Failure"

It has been added below in red

aws sns publish --topic-arn arn:aws:sns:us-east-1:546419318123:OperationsError ---message "Script Failure"

Reference: <http://aws.amazon.com/cji/>

#### NEW QUESTION 99

An organization has developed a mobile application which allows end users to capture a photo on their mobile device, and store it inside an application. The application internally uploads the data to AWS S3. The organization wants each user to be able to directly upload data to S3 using their Google ID. How will the mobile app allow this?

- A. Use the AWS Web identity federation for mobile applications, and use it to generate temporary security credentials for each user.
- B. It is not possible to connect to AWS S3 with a Google ID.
- C. Create an IAM user every time a user registers with their Google ID and use IAM to upload files to S3.
- D. Create a bucket policy with a condition which allows everyone to upload if the login ID has a Google part to it.

**Answer:** A

**Explanation:** For Amazon Web Services, the Web identity federation allows you to create cloud-backed mobile apps that use public identity providers, such as login with Facebook, Google, or Amazon. It will create temporary security credentials for each user, which will be authenticated by the AWS services, such as S3.

Reference: <http://docs.aws.amazon.com/STS/latest/UsingSTS/CreatingWIF.html>

#### NEW QUESTION 100

You are architecting an auto-scalable batch processing system using video processing pipelines and Amazon Simple Queue Service (Amazon SQS) for a customer. You are unsure of the limitations of SQS and need to find out. What do you think is a correct statement about the limitations of Amazon SQS?

- A. It supports an unlimited number of queues but a limited number of messages per queue for each user but automatically deletes messages that have been in the queue for more than 4 weeks.
- B. It supports an unlimited number of queues and unlimited number of messages per queue for each user but automatically deletes messages that have been in the queue for more than 4 days.
- C. It supports an unlimited number of queues but a limited number of messages per queue for each user but automatically deletes messages that have been in the queue for more than 4 days.
- D. It supports an unlimited number of queues and unlimited number of messages per queue for each user but automatically deletes messages that have been in the queue for more than 4 weeks.

**Answer:** B

**Explanation:** Amazon Simple Queue Service (Amazon SQS) is a messaging queue service that handles message or workflows between other components in a system.

Amazon SQS supports an unlimited number of queues and unlimited number of messages per queue for each user. Please be aware that Amazon SQS automatically deletes messages that have been in the queue for more than 4 days.

Reference: <http://aws.amazon.com/documentation/sqs/>

#### NEW QUESTION 102

An online gaming site asked you if you can deploy a database that is a fast, highly scalable NoSQL database service in AWS for a new site that he wants to build. Which database should you recommend?

- A. Amazon DynamoDB
- B. Amazon RDS
- C. Amazon Redshift
- D. Amazon SimpleDB

**Answer:** A

**Explanation:** Amazon DynamoDB is ideal for database applications that require very low latency and predictable performance at any scale but don't need complex querying capabilities like joins or transactions. Amazon DynamoDB is a fully-managed NoSQL database service that offers high performance, predictable throughput and low cost. It is easy to set up, operate, and scale.

With Amazon DynamoDB, you can start small, specify the throughput and storage you need, and easily scale your capacity requirements on the fly. Amazon DynamoDB automatically partitions data over a number of servers to meet your request capacity. In addition, DynamoDB automatically replicates your data synchronously across multiple Availability Zones within an AWS Region to ensure high-availability and data durability.

Reference: [https://aws.amazon.com/running\\_databases/#dynamodb\\_anchor](https://aws.amazon.com/running_databases/#dynamodb_anchor)

#### NEW QUESTION 106

You have been doing a lot of testing of your VPC Network by deliberately failing EC2 instances to test whether instances are failing over properly. Your customer who will be paying the AWS bill for all this asks you if he being charged for all these instances. You try to explain to him how the billing works on EC2 instances to the best of your knowledge. What would be an appropriate response to give to the customer in regards to this?

- A. Billing commences when Amazon EC2 AM instance is completely up and billing ends as soon as the instance starts to shutdown.
- B. Billing only commences only after 1 hour of uptime and billing ends when the instance terminates.
- C. Billing commences when Amazon EC2 initiates the boot sequence of an AM instance and billing ends when the instance shuts down.
- D. Billing commences when Amazon EC2 initiates the boot sequence of an AM instance and billing ends as soon as the instance starts to shutdown.

**Answer:** C

**Explanation:** Billing commences when Amazon EC2 initiates the boot sequence of an AM instance. Billing ends when the instance shuts down, which could occur through a web services command, by running "shutdown -h", or through instance failure.

Reference: <http://aws.amazon.com/ec2/faqs/#Billing>

#### NEW QUESTION 108

You log in to IAM on your AWS console and notice the following message. "Delete your root access keys." Why do you think IAM is requesting this?

- A. Because the root access keys will expire as soon as you log out.
- B. Because the root access keys expire after 1 week.
- C. Because the root access keys are the same for all users.
- D. Because they provide unrestricted access to your AWS resource

**Answer:** D

**Explanation:** In AWS an access key is required in order to sign requests that you make using the command-line interface (CLI), using the AWS SDKs, or using direct API calls. Anyone who has the access key for your root account has unrestricted access to all the resources in your account, including billing information. One of the best ways to protect your account is to not have an access key for your root account. We recommend that unless you must have a root access key (this is very rare), that you do not generate one. Instead, AWS best practice is to create one or more AWS Identity and Access Management (IAM) users, give them the necessary permissions, and use IAM users for everyday interaction with AWS.

Reference:

<http://docs.aws.amazon.com/general/latest/gr/aws-access-keys-best-practices.html#root-password>

#### NEW QUESTION 112

Your company has been storing a lot of data in Amazon Glacier and has asked for an inventory of what is in there exactly. So you have decided that you need to download a vault inventory. Which of the following statements is incorrect in relation to Vault Operations in Amazon Glacier?

- A. You can use Amazon Simple Notification Service (Amazon SNS) notifications to notify you when the job completes.
- B. A vault inventory refers to the list of archives in a vault.
- C. You can use Amazon Simple Queue Service (Amazon SQS) notifications to notify you when the job completes.
- D. Downloading a vault inventory is an asynchronous operatio

**Answer:** C

**Explanation:** Amazon Glacier supports various vault operations.

A vault inventory refers to the list of archives in a vault. For each archive in the list, the inventory provides archive information such as archive ID, creation date, and size. Amazon Glacier updates the vault inventory approximately once a day, starting on the day the first archive is uploaded to the vault. A vault inventory must exist for you to be able to download it.

Downloading a vault inventory is an asynchronous operation. You must first initiate a job to download the inventory. After receiving the job request, Amazon Glacier prepares your inventory for download. After the job completes, you can download the inventory data.

Given the asynchronous nature of the job, you can use Amazon Simple Notification Service (Amazon SNS) notifications to notify you when the job completes. You can specify an Amazon SNS topic for each individual job request or configure your vault to send a notification when specific vault events occur. Amazon Glacier prepares an inventory for each vault periodically, every 24 hours. If there have been no archive additions or deletions to the vault since the last inventory, the inventory date is not updated. When you initiate a job for a vault inventory, Amazon Glacier returns the last inventory it generated, which is a point-in-time snapshot and not real-time data. You might not find it useful to retrieve vault inventory for each archive upload. However, suppose you maintain a database on the client-side associating metadata about the archives you upload to Amazon Glacier. Then, you might find the vault inventory useful to reconcile information in your database with the actual vault inventory.

Reference: <http://docs.aws.amazon.com/amazonglacier/latest/dev/working-with-vaults.html>

#### NEW QUESTION 113

You are in the process of building an online gaming site for a client and one of the requirements is that it must be able to process vast amounts of data easily. Which AWS Service would be very helpful in processing all this data?

- A. Amazon S3
- B. AWS Data Pipeline
- C. AWS Direct Connect
- D. Amazon EMR

**Answer:** D

**Explanation:** Managing and analyzing high data volumes produced by online games platforms can be difficult. The back-end infrastructures of online games can be challenging to maintain and operate. Peak usage periods, multiple players, and high volumes of write operations are some of the most common problems that operations teams face.

Amazon Elastic MapReduce (Amazon EMR) is a service that processes vast amounts of data easily. Input data can be retrieved from web server logs stored on Amazon S3 or from player data stored in Amazon DynamoDB tables to run analytics on player behavior, usage patterns, etc. Those results can be stored again on Amazon S3, or inserted in a relational database for further analysis with classic business intelligence tools.

Reference: [http://media.amazonwebservices.com/architecturecenter/AWS\\_ac\\_ra\\_games\\_10.pdf](http://media.amazonwebservices.com/architecturecenter/AWS_ac_ra_games_10.pdf)

#### NEW QUESTION 117

You need to change some settings on Amazon Relational Database Service but you do not want the database to reboot immediately which you know might happen depending on the setting that you change. Which of the following will cause an immediate DB instance reboot to occur?

- A. You change storage type from standard to PIOPS, and Apply Immediately is set to true.
- B. You change the DB instance class, and Apply Immediately is set to false.
- C. You change a static parameter in a DB parameter group.
- D. You change the backup retention period for a DB instance from 0 to a nonzero value or from a nonzero value to 0, and Apply Immediately is set to false.



**Answer:** A

**Explanation:** A DB instance outage can occur when a DB instance is rebooted, when the DB instance is put into a state that prevents access to it, and when the database is restarted. A reboot can occur when you manually reboot your DB instance or when you change a DB instance setting that requires a reboot before it can take effect.

A DB instance reboot occurs immediately when one of the following occurs:

You change the backup retention period for a DB instance from 0 to a nonzero value or from a nonzero value to 0 and set Apply Immediately to true.

You change the DB instance class, and Apply Immediately is set to true.

You change storage type from standard to PIOPS, and Apply Immediately is set to true.

A DB instance reboot occurs during the maintenance window when one of the following occurs:

You change the backup retention period for a DB instance from 0 to a nonzero value or from a nonzero value to 0, and Apply Immediately is set to false.

You change the DB instance class, and Apply Immediately is set to false. Reference:

[http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP\\_Troubleshooting.Security](http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP_Troubleshooting.Security)

#### NEW QUESTION 118

What does the following policy for Amazon EC2 do?

```
{
  "Statement": [{
    "Effect": "Allow", "Action": "ec2:Describe*", "Resource": "*"
  }]
}
```

A. Allow users to use actions that start with "Describe" over all the EC2 resources.

B. Share an AMI with a partner

C. Share an AMI within the account

D. Allow a group to only be able to describe, run, stop, start, and terminate instances

**Answer:** A

**Explanation:** You can use IAM policies to control the actions that your users can perform against your EC2 resources. For instance, a policy with the following statement will allow users to perform actions whose name start with "Describe" against all your EC2 resources.

```
{
  "Statement": [{
    "Effect": "Allow", "Action": "ec2:Describe*", "Resource": "*"
  }]
}
```

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/UsingIAM.html>

#### NEW QUESTION 123

A major customer has asked you to set up his AWS infrastructure so that it will be easy to recover in the case of a disaster of some sort. Which of the following is important when thinking about being able to quickly launch resources in AWS to ensure business continuity in case of a disaster?

A. Create and maintain AMIs of key servers where fast recovery is required.

B. Regularly run your servers, test them, and apply any software updates and configuration changes.

C. All items listed here are important when thinking about disaster recovery.

D. Ensure that you have all supporting custom software packages available in AWS

**Answer:** C

**Explanation:** In the event of a disaster to your AWS infrastructure you should be able to quickly launch resources in Amazon Web Services (AWS) to ensure business continuity.

The following are some key steps you should have in place for preparation:

1. Set up Amazon EC2 instances to replicate or mirror data.

2. Ensure that you have all supporting custom software packages available in AWS.

3. Create and maintain AMIs of key servers where fast recovery is required.

4. Regularly run these servers, test them, and apply any software updates and configuration changes.

5. Consider automating the provisioning of AWS resources.

Reference: [http://d36cz9buwru1tt.cloudfront.net/AWS\\_Disaster\\_Recovery.pdf](http://d36cz9buwru1tt.cloudfront.net/AWS_Disaster_Recovery.pdf)

#### NEW QUESTION 125

What does Amazon DynamoDB provide?

A. A predictable and scalable MySQL database

B. A fast and reliable PL/SQL database cluster

C. A standalone Cassandra database, managed by Amazon Web Services

D. A fast, highly scalable managed NoSQL database service

**Answer:** D

**Explanation:** Amazon DynamoDB is a managed NoSQL database service offered by Amazon. It automatically manages tasks like scalability for you while it provides high availability and durability for your data, allowing you to concentrate in other aspects of your application.

Reference: check link - [https://aws.amazon.com/running\\_databases/](https://aws.amazon.com/running_databases/)

#### NEW QUESTION 128

What would be the best way to retrieve the public IP address of your EC2 instance using the CLI?

- A. Using tags
- B. Using traceroute
- C. Using ipconfig
- D. Using instance metadata

**Answer:** D

**Explanation:** To determine your instance's public IP address from within the instance, you can use instance metadata. Use the following command to access the public IP address: For Linux use, \$ curl <http://169.254.169.254/latest/meta-data/public-ipv4>, and for Windows use, \$ wget <http://169.254.169.254/latest/meta-data/public-ipv4>.  
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-instance-addressing.htm>

### NEW QUESTION 133

You need to measure the performance of your EBS volumes as they seem to be under performing. You have come up with a measurement of 1,024 KB I/O but your colleague tells you that EBS volume performance is measured in IOPS. How many IOPS is equal to 1,024 KB I/O?

- A. 16
- B. 256
- C. 8
- D. 4

**Answer:** D

**Explanation:** Several factors can affect the performance of Amazon EBS volumes, such as instance configuration, I/O characteristics, workload demand, and storage configuration.

IOPS are input/output operations per second. Amazon EBS measures each I/O operation per second (that is 256 KB or smaller) as one IOPS. I/O operations that are larger than 256 KB are counted in 256 KB capacity units. For example, a 1,024 KB I/O operation would count as 4 IOPS.

When you provision a 4,000 IOPS volume and attach it to an EBS-optimized instance that can provide the necessary bandwidth, you can transfer up to 4,000 chunks of data per second (provided that the I/O does not exceed the 128 MB/s per volume throughput limit of General Purpose (SSD) and Provisioned IOPS (SSD) volumes).

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/EBSPerformance.html>

### NEW QUESTION 137

Having set up a website to automatically be redirected to a backup website if it fails, you realize that there are different types of failovers that are possible. You need all your resources to be available the majority of the time. Using Amazon Route 53 which configuration would best suit this requirement?

- A. Active-active failover.
- B. Non
- C. Route 53 can't failover.
- D. Active-passive failover.
- E. Active-active-passive and other mixed configuration

**Answer:** A

**Explanation:** You can set up a variety of failover configurations using Amazon Route 53 alias: weighted, latency, geolocation routing, and failover resource record sets.

Active-active failover: Use this failover configuration when you want all of your resources to be available the majority of the time. When a resource becomes unavailable, Amazon Route 53 can detect that it's unhealthy and stop including it when responding to queries.

Active-passive failover: Use this failover configuration when you want a primary group of resources to be available the majority of the time and you want a secondary group of resources to be on standby in case all of the primary resources become unavailable. When responding to queries, Amazon Route 53 includes only the healthy primary resources. If all of the primary resources are unhealthy, Amazon Route 53 begins to include only the healthy secondary resources in response to DNS queries.

Active-active-passive and other mixed configurations: You can combine alias and non-alias resource record sets to produce a variety of Amazon Route 53 behaviors.

Reference: <http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/dns-failover.html>

### NEW QUESTION 139

True or False: In Amazon Route 53, you can create a hosted zone for a top-level domain (TLD).

- A. FALSE
- B. False, Amazon Route 53 automatically creates it for you.
- C. True, only if you send an XML document with a CreateHostedZoneRequest element for TLD.
- D. TRUE

**Answer:** A

**Explanation:** In Amazon Route 53, you cannot create a hosted zone for a top-level domain (TLD).

Reference: [http://docs.aws.amazon.com/Route53/latest/APIReference/API\\_CreateHostedZone.html](http://docs.aws.amazon.com/Route53/latest/APIReference/API_CreateHostedZone.html)

### NEW QUESTION 142

You decide that you need to create a number of Auto Scaling groups to try and save some money as you have noticed that at certain times most of your EC2 instances are not being used. By default, what is the maximum number of Auto Scaling groups that AWS will allow you to create?

- A. 12

- B. Unlimited
- C. 20
- D. 2

**Answer:** C

**Explanation:** Auto Scaling is an AWS service that allows you to increase or decrease the number of EC2 instances within your application's architecture. With Auto Scaling, you create collections of EC2 instances, called Auto Scaling groups. You can create these groups from scratch, or from existing EC2 instances that are already in production.

Reference: [http://docs.aws.amazon.com/general/latest/gr/aws\\_service\\_limits.htm#limits\\_autoscaling](http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.htm#limits_autoscaling)

#### NEW QUESTION 145

A user needs to run a batch process which runs for 10 minutes. This will only be run once, or at maximum twice, in the next month, so the processes will be temporary only. The process needs 15 X-Large instances. The process downloads the code from S3 on each instance when it is launched, and then generates a temporary log file. Once the instance is terminated, all the data will be lost. Which of the below mentioned pricing models should the user choose in this case?

- A. Spot instance.
- B. Reserved instance.
- C. On-demand instance.
- D. EBS optimized instanc

**Answer:** A

**Explanation:** In Amazon Web Services, the spot instance is useful when the user wants to run a process temporarily. The spot instance can terminate the instance if the other user outbids the existing bid. In this case all storage is temporary and the data is not required to be persistent. Thus, the spot instance is a good option to save money.

Reference: <http://aws.amazon.com/ec2/purchasing-options/spot-instances/>

#### NEW QUESTION 150

You have been storing massive amounts of data on Amazon Glacier for the past 2 years and now start to wonder if there are any limitations on this. What is the correct answer to your QUESTION ?

- A. The total volume of data is limited but the number of archives you can store are unlimited.
- B. The total volume of data is unlimited but the number of archives you can store are limited.
- C. The total volume of data and number of archives you can store are unlimited.
- D. The total volume of data is limited and the number of archives you can store are limite

**Answer:** C

**Explanation:** An archive is a durably stored block of information. You store your data in Amazon Glacier as archives. You may upload a single file as an archive, but your costs will be lower if you aggregate your data. TAR and ZIP are common formats that customers use to aggregate multiple files into a single file before uploading to Amazon Glacier.

The total volume of data and number of archives you can store are unlimited. Individual Amazon Glacier archives can range in size from 1 byte to 40 terabytes.

The largest archive that can be uploaded in a single upload request is 4 gigabytes.

For items larger than 100 megabytes, customers should consider using the Multipart upload capability. Archives stored in Amazon Glacier are immutable, i.e. archives can be uploaded and deleted but cannot be edited or overwritten.

Reference: <https://aws.amazon.com/glacier/faqs/>

#### NEW QUESTION 152

You are setting up your first Amazon Virtual Private Cloud (Amazon VPC) so you decide to use the VPC wizard in the AWS console to help make it easier for you. Which of the following statements is correct regarding instances that you launch into a default subnet via the VPC wizard?

- A. Instances that you launch into a default subnet receive a public IP address and 10 private IP addresses.
- B. Instances that you launch into a default subnet receive both a public IP address and a private IP address.
- C. Instances that you launch into a default subnet don't receive any ip addresses and you need to define them manually.
- D. Instances that you launch into a default subnet receive a public IP address and 5 private IP addresse

**Answer:** B

**Explanation:** Instances that you launch into a default subnet receive both a public IP address and a private IP address. Instances in a default subnet also receive both public and private DNS hostnames. Instances that you launch into a nondefault subnet in a default VPC don't receive a public IP address or a DNS hostname. You can change your subnet's default public IP addressing behavior.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/default-vpc.html>

#### NEW QUESTION 155

A user has configured ELB with two EBS backed EC2 instances. The user is trying to understand the DNS access and IP support for ELB. Which of the below mentioned statements may not help the user understand the IP mechanism supported by ELB?

- A. The client can connect over IPV4 or IPV6 using Dualstack
- B. Communication between the load balancer and back-end instances is always through IPV4
- C. ELB DNS supports both IPV4 and IPV6
- D. The ELB supports either IPV4 or IPV6 but not both

**Answer:** D

**Explanation:** Elastic Load Balancing supports both Internet Protocol version 6 (IPv6) and Internet Protocol version 4 (IPv4). Clients can connect to the user's load balancer using either IPv4 or IPv6 (in EC2-Classic) DNS. However, communication between the load balancer and its back-end instances uses only IPv4. The user can use the Dualstack-prefixed DNS name to enable IPv6 support for communications between the client and the load balancers. Thus, the clients are able to access the load balancer using either IPv4 or IPv6 as their individual connectivity needs dictate.

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/UserScenariosForEC2.html>

#### NEW QUESTION 157

Does AWS CloudFormation support Amazon EC2 tagging?

- A. Yes, AWS CloudFormation supports Amazon EC2 tagging
- B. No, CloudFormation doesn't support any tagging
- C. No, it doesn't support Amazon EC2 tagging.
- D. It depends if the Amazon EC2 tagging has been defined in the template

**Answer:** A

**Explanation:** In AWS CloudFormation, Amazon EC2 resources that support the tagging feature can also be tagged in an AWS template. The tag values can refer to template parameters, other resource names, resource attribute values (e.g. addresses), or values computed by simple functions (e.g., a concatenated list of strings).

Reference: <http://aws.amazon.com/cloudformation/faqs/>

#### NEW QUESTION 159

An existing client comes to you and says that he has heard that launching instances into a VPC (virtual private cloud) is a better strategy than launching instances into a EC2-classic which he knows is what you currently do. You suspect that he is correct and he has asked you to do some research about this and get back to him. Which of the following statements is true in regards to what ability launching your instances into a VPC instead of EC2-Classic gives you?

- A. All of the things listed here.
- B. Change security group membership for your instances while they're running
- C. Assign static private IP addresses to your instances that persist across starts and stops
- D. Define network interfaces, and attach one or more network interfaces to your instances

**Answer:** A

**Explanation:** By launching your instances into a VPC instead of EC2-Classic, you gain the ability to: Assign static private IP addresses to your instances that persist across starts and stops Assign multiple IP addresses to your instances

Define network interfaces, and attach one or more network interfaces to your instances Change security group membership for your instances while they're running

Control the outbound traffic from your instances (egress filtering) in addition to controlling the inbound traffic to them (ingress filtering)

Add an additional layer of access control to your instances in the form of network access control lists (ACL)

Run your instances on single-tenant hardware

Reference: [http://media.amazonwebservices.com/AWS\\_Cloud\\_Best\\_Practices.pdf](http://media.amazonwebservices.com/AWS_Cloud_Best_Practices.pdf)

#### NEW QUESTION 164

Amazon S3 allows you to set per-file permissions to grant read and/or write access. However you have decided that you want an entire bucket with 100 files already in it to be accessible to the public. You don't want to go through 100 files individually and set permissions. What would be the best way to do this?

- A. Move the bucket to a new region
- B. Add a bucket policy to the bucket.
- C. Move the files to a new bucket.
- D. Use Amazon EBS instead of S3

**Answer:** B

**Explanation:** Amazon S3 supports several mechanisms that give you flexibility to control who can access your data as well as how, when, and where they can access it. Amazon S3 provides four different access control mechanisms: AWS Identity and Access Management (IAM) policies, Access Control Lists (ACLs), bucket policies, and query string authentication. IAM enables organizations to create and manage multiple users under a single AWS account. With IAM policies, you can grant IAM users fine-grained control to your Amazon S3 bucket or objects. You can use ACLs to selectively add (grant) certain permissions on individual objects.

Amazon S3 bucket policies can be used to add or deny permissions across some or all of the objects within a single bucket.

With Query string authentication, you have the ability to share Amazon S3 objects through URLs that are valid for a specified period of time.

Reference: <http://aws.amazon.com/s3/details/#security>

#### NEW QUESTION 166

A user is accessing an EC2 instance on the SSH port for IP 10.20.30.40. Which one is a secure way to configure that the instance can be accessed only from this IP?

- A. In the security group, open port 22 for IP 10.20.30.40
- B. In the security group, open port 22 for IP 10.20.30.40/32
- C. In the security group, open port 22 for IP 10.20.30.40/24
- D. In the security group, open port 22 for IP 10.20.30.40/0

**Answer:** B

**Explanation:** In AWS EC2, while configuring a security group, the user needs to specify the IP address in CIDR notation. The CIDR IP range 10.20.30.40/32 says



it is for a single IP 10.20.30.40. If the user specifies the IP as 10.20.30.40 only, the security group will not accept and ask it in a CIDR format.  
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-network-security.html>

**NEW QUESTION 170**

Which of the following statements is true of creating a launch configuration using an EC2 instance?

- A. The launch configuration can be created only using the Query APIs.
- B. Auto Scaling automatically creates a launch configuration directly from an EC2 instance.
- C. A user should manually create a launch configuration before creating an Auto Scaling group.
- D. The launch configuration should be created manually from the AWS CL

**Answer: B**

**Explanation:** You can create an Auto Scaling group directly from an EC2 instance. When you use this feature, Auto Scaling automatically creates a launch configuration for you as well.

Reference:

<http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/create-lc-with-instanceID.html>

**NEW QUESTION 174**

You need to set up a high level of security for an Amazon Relational Database Service (RDS) you have just built in order to protect the confidential information stored in it. What are all the possible security groups that RDS uses?

- A. DB security groups, VPC security groups, and EC2 security groups.
- B. DB security groups only.
- C. EC2 security groups only.
- D. VPC security groups, and EC2 security group

**Answer: A**

**Explanation:** A security group controls the access to a DB instance. It does so by allowing access to IP address ranges or Amazon EC2 instances that you specify.

Amazon RDS uses DB security groups, VPC security groups, and EC2 security groups. In simple terms, a DB security group controls access to a DB instance that is not in a VPC, a VPC security group controls access to a DB instance inside a VPC, and an Amazon EC2 security group controls access to an EC2 instance and can be used with a DB instance.

Reference: <http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/Welcome.html>

**NEW QUESTION 176**

You have been using T2 instances as your CPU requirements have not been that intensive. However you now start to think about larger instance types and start looking at M and IV|3 instances. You are a little confused as to the differences between them as they both seem to have the same ratio of CPU and memory. Which statement below is incorrect as to why you would use one over the other?

- A. M3 instances are less expensive than M1 instances.
- B. IV|3 instances are configured with more swap memory than M instances.
- C. IV|3 instances provide better, more consistent performance than M instances for most use-cases.
- D. M3 instances also offer SSD-based instance storage that delivers higher I/O performance

**Answer: B**

**Explanation:** Amazon EC2 allows you to set up and configure everything about your instances from your operating system up to your applications. An Amazon Machine Image (AMI) is simply a packaged-up environment that includes all the necessary bits to set up and boot your instance.

M1 and M3 Standard instances have the same ratio of CPU and memory, some reasons below as to why you would use one over the other.

IV|3 instances provide better, more consistent performance than M instances for most use-cases. M3 instances also offer SSD-based instance storage that delivers higher I/O performance.

M3 instances are also less expensive than M1 instances. Due to these reasons, we recommend M3 for applications that require general purpose instances with a balance of compute, memory, and network resources.

However, if you need more disk storage than what is provided in M3 instances, you may still find M1 instances useful for running your applications.

Reference: <https://aws.amazon.com/ec2/faqs/>

**NEW QUESTION 181**

You have set up an Elastic Load Balancer (ELB) with the usual default settings, which route each request independently to the application instance with the smallest load. However, someone has asked you to bind a user's session to a specific application instance so as to ensure that all requests coming from the user during the session will be sent to the same application instance. AWS has a feature to do this. What is it called?

- A. Connection draining
- B. Proxy protocol
- C. Tagging
- D. Sticky session

**Answer: D**

**Explanation:** An Elastic Load Balancer(ELB) by default, routes each request independently to the application instance with the smallest load. However, you can use the sticky session feature (also known as session affinity), which enables the load balancer to bind a user's session to a specific application instance. This ensures that all requests coming from the user during the session will be sent to the same application instance. The key to managing the sticky session is determining how long your load balancer should consistently route the user's request to the same application instance. If your application has its own session cookie, then you can set Elastic Load Balancing to create the session cookie to follow the duration specified by the application's

session cookie. If your application does not have its own session cookie, then you can set Elastic Load Balancing to create a session cookie by specifying your own stickiness duration. You can associate stickiness duration for only HTTP/HTTPS load balancer listeners.

An application instance must always receive and send two cookies: A cookie that defines the stickiness duration and a special Elastic Load Balancing cookie named AWSELB, that has the mapping to the application instance.

Reference: <http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/TerminologyandKeyConcepts.html#session-stickiness>

#### NEW QUESTION 185

A user has created an application which will be hosted on EC2. The application makes calls to DynamoDB to fetch certain data. The application is using the DynamoDB SDK to connect with from the EC2 instance. Which of the below mentioned statements is true with respect to the best practice for security in this scenario?

- A. The user should create an IAM user with DynamoDB access and use its credentials within the application to connect with DynamoDB
- B. The user should attach an IAM role with DynamoDB access to the EC2 instance
- C. The user should create an IAM role, which has EC2 access so that it will allow deploying the application
- D. The user should create an IAM user with DynamoDB and EC2 acces
- E. Attach the user with the application so that it does not use the root account credentials

**Answer:** B

**Explanation:** With AWS IAM a user is creating an application which runs on an EC2 instance and makes requests to AWS, such as DynamoDB or S3 calls. Here it is recommended that the user should not create an IAM user and pass the user's credentials to the application or embed those credentials inside the application. Instead, the user should use roles for EC2 and give that role access to DynamoDB /S3. When the roles are attached to EC2, it will give temporary security credentials to the application hosted on that EC2, to connect with DynamoDB / S3.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/Using\\_WorkingWithGroupsAndUsers.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_WorkingWithGroupsAndUsers.html)

#### NEW QUESTION 188

After setting up several database instances in Amazon Relational Database Service (Amazon RDS) you decide that you need to track the performance and health of your databases. How can you do this?

- A. Subscribe to Amazon RDS events to be notified when changes occur with a DB instance, DB snapshot, DB parameter group, or DB security group.
- B. Use the free Amazon CloudWatch service to monitor the performance and health of a DB instance.
- C. All of the items listed will track the performance and health of a database.
- D. View, download, or watch database log files using the Amazon RDS console or Amazon RDS API
- E. You can also query some database log files that are loaded into database tables.

**Answer:** C

**Explanation:** Amazon Relational Database Service (Amazon RDS) is a web service that makes it easier to set up, operate, and scale a relational database in the cloud. It provides cost-efficient, resizable capacity for an industry-standard relational database and manages common database administration tasks.

There are several ways you can track the performance and health of a database or a DB instance. You can:

Use the free Amazon CloudWatch service to monitor the performance and health of a DB instance. Subscribe to Amazon RDS events to be notified when changes occur with a DB instance, DB snapshot, DB parameter group, or DB security group.

View, download, or watch database log files using the Amazon RDS console or Amazon RDS APIs. You can also query some database log files that are loaded into database tables.

Use the AWS CloudTrail service to record AWS calls made by your AWS account. The calls are recorded in log files and stored in an Amazon S3 bucket.

Reference: [http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP\\_Monitoring.html](http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/CHAP_Monitoring.html)

#### NEW QUESTION 192

A user has attached 1 EBS volume to a VPC instance. The user wants to achieve the best fault tolerance of data possible. Which of the below mentioned options can help achieve fault tolerance?

- A. Attach one more volume with RAID 1 configuration.
- B. Attach one more volume with RAID 0 configuration.
- C. Connect multiple volumes and stripe them with RAID 6 configuration.
- D. Use the EBS volume as a root devic

**Answer:** A

**Explanation:** The user can join multiple provisioned IOPS volumes together in a RAID 1 configuration to achieve better fault tolerance. RAID 1 does not provide a write performance improvement; it requires more bandwidth than non-RAID configurations since the data is written simultaneously to multiple volumes.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/raid-config.html>

#### NEW QUESTION 195

A user has created a subnet in VPC and launched an EC2 instance within it. The user has not selected the option to assign the IP address while launching the instance. The user has 3 elastic IPs and is trying to assign one of the Elastic IPs to the VPC instance from the console. The console does not show any instance in the IP assignment screen. What is a possible reason that the instance is unavailable in the assigned IP console?

- A. The IP address may be attached to one of the instances
- B. The IP address belongs to a different zone than the subnet zone
- C. The user has not created an internet gateway
- D. The IP addresses belong to EC2 Classic; so they cannot be assigned to VPC

**Answer:** D

**Explanation:** A Virtual Private Cloud (VPC) is a virtual network dedicated to the user's AWS account. A user can create a subnet with VPC and launch instances

inside that subnet. When the user is launching an instance he needs to select an option which attaches a public IP to the instance. If the user has not selected the option to attach the public IP then it will only have a private IP when launched. If the user wants to connect to an instance from the internet he should create an elastic IP with VPC. If the elastic IP is a part of EC2 Classic it cannot be assigned to a VPC instance.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/GettingStartedGuide/LaunchInstance.html>

#### NEW QUESTION 200

A user is aware that a huge download is occurring on his instance. He has already set the Auto Scaling policy to increase the instance count when the network I/O increases beyond a certain limit. How can the user ensure that this temporary event does not result in scaling?

- A. The network I/O are not affected during data download
- B. The policy cannot be set on the network I/O
- C. There is no way the user can stop scaling as it is already configured
- D. Suspend scaling

**Answer:** D

**Explanation:** The user may want to stop the automated scaling processes on the Auto Scaling groups either to perform manual operations or during emergency situations. To perform this, the user can suspend one or more scaling processes at any time. Once it is completed, the user can resume all the suspended processes. Reference: [http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AS\\_Concepts.html](http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/AS_Concepts.html)

#### NEW QUESTION 201

Select a true statement about Amazon EC2 Security Groups (EC2-Classic).

- A. After you launch an instance in EC2-Classic, you can't change its security groups.
- B. After you launch an instance in EC2-Classic, you can change its security groups only once.
- C. After you launch an instance in EC2-Classic, you can only add rules to a security group.
- D. After you launch an instance in EC2-Classic, you cannot add or remove rules from a security group

**Answer:** A

**Explanation:** After you launch an instance in EC2-Classic, you can't change its security groups. However, you can add rules to or remove rules from a security group, and those changes are automatically applied to all instances that are associated with the security group.

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/using-network-security.html>

#### NEW QUESTION 204

Which one of the following answers is not a possible state of Amazon CloudWatch Alarm?

- A. INSUFFICIENT\_DATA
- B. ALARM
- C. OK
- D. STATUS\_CHECK\_FAILED

**Answer:** D

**Explanation:** Amazon CloudWatch Alarms have three possible states: OK: The metric is within the defined threshold ALARM: The metric is outside of the defined threshold

INSUFFICIENT\_DATA: The alarm has just started, the metric is not available, or not enough data is available for the metric to determine the alarm state

Reference: <http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/AlarmThatSendsEmail.html>

#### NEW QUESTION 205

An accountant asks you to design a small VPC network for him and, due to the nature of his business, just needs something where the workload on the network will be low, and dynamic data will be accessed infrequently. Being an accountant, low cost is also a major factor. Which EBS volume type would best suit his requirements?

- A. Magnetic
- B. Any, as they all perform the same and cost the same.
- C. General Purpose (SSD)
- D. Magnetic or Provisioned IOPS (SSD)

**Answer:** A

**Explanation:** You can choose between three EBS volume types to best meet the needs of their workloads: General Purpose (SSD), Provisioned IOPS (SSD), and Magnetic. General Purpose (SSD) is the new, SSD-backed, general purpose EBS volume type that we recommend as the default choice for customers. General Purpose (SSD) volumes are suitable for a broad range of workloads, including small to medium sized databases, development and test environments, and boot volumes. Provisioned IOPS (SSD) volumes offer storage with consistent and low-latency performance, and are designed for I/O intensive applications such as large relational or NoSQL databases. Magnetic volumes provide the lowest cost per gigabyte of all EBS volume types. Magnetic volumes are ideal for workloads where data is accessed infrequently, and applications where the lowest storage cost is important.

Reference: <https://aws.amazon.com/ec2/faqs/>

#### NEW QUESTION 206

A user is planning to launch a scalable web application. Which of the below mentioned options will not affect the latency of the application?

- A. Region.
- B. Provisioned IOPS.
- C. Availability Zone.
- D. Instance siz

**Answer:** C

**Explanation:** In AWS, the instance size decides the I/O characteristics. The provisioned IOPS ensures higher throughput, and lower latency. The region does affect the latency; latency will always be less when the instance is near to the end user. Within a region the user uses any AZ and this does not affect the latency. The AZ is mainly for fault toleration or HA.

Reference: [http://media.amazonwebservices.com/AWS\\_Security\\_Best\\_Practices.pdf](http://media.amazonwebservices.com/AWS_Security_Best_Practices.pdf)

#### NEW QUESTION 207

Which of the following strategies can be used to control access to your Amazon EC2 instances?

- A. DB security groups
- B. IAM policies
- C. None of these
- D. EC2 security groups

**Answer:** D

**Explanation:** IAM policies allow you to specify what actions your IAM users are allowed to perform against your EC2 Instances. However, when it comes to access control, security groups are what you need in order to define and control the way you want your instances to be accessed, and whether or not certain kind of communications are allowed or not.

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/UsingIAM.html>

#### NEW QUESTION 208

A user has launched one EC2 instance in the US East region and one in the US West region. The user has launched an RDS instance in the US East region. How can the user configure access from both the EC2 instances to RDS?

- A. It is not possible to access RDS of the US East region from the US West region
- B. Configure the US West region's security group to allow a request from the US East region's instance and configure the RDS security group's ingress rule for the US East EC2 group
- C. Configure the security group of the US East region to allow traffic from the US West region's instance and configure the RDS security group's ingress rule for the US East EC2 group
- D. Configure the security group of both instances in the ingress rule of the RDS security group

**Answer:** C

**Explanation:** The user cannot authorize an Amazon EC2 security group if it is in a different AWS Region than the RDS DB instance. The user can authorize an IP range or specify an Amazon EC2 security group in the same region that refers to an IP address in another region. In this case allow IP of US West inside US East's security group and open the RDS security group for US East region.

Reference: [http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER\\_WorkingWithSecurityGroups.html](http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_WorkingWithSecurityGroups.html)

#### NEW QUESTION 212

In Amazon EC2, if your EBS volume stays in the detaching state, you can force the detachment by clicking .

- A. Force Detach
- B. Detach Instance
- C. AttachVolume
- D. AttachInstance

**Answer:** A

**Explanation:** If your volume stays in the detaching state, you can force the detachment by clicking Force Detach. Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/ebs-detaching-volume.html>

#### NEW QUESTION 213

Do you need to shutdown your EC2 instance when you create a snapshot of EBS volumes that serve as root devices?

- A. No, you only need to shutdown an instance before deleting it.
- B. Yes
- C. No, the snapshot would turn off your instance automatically.
- D. No

**Answer:** B

**Explanation:** Yes, to create a snapshot for Amazon EBS volumes that serve as root devices, you should stop the instance before taking the snapshot.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-creating-snapshot.html>

#### NEW QUESTION 215



An organization has a statutory requirement to protect the data at rest for data stored in EBS volumes. Which of the below mentioned options can the organization use to achieve data protection?

- A. Data replication.
- B. Data encryption.
- C. Data snapshot.
- D. All the options listed her

**Answer:** D

**Explanation:** For protecting the Amazon EBS data at REST, the user can use options, such as Data Encryption (Windows / Linux / third party based), Data Replication (AWS internally replicates data for redundancy), and Data Snapshot (for point in time backup).

Reference: [http://media.amazonwebservices.com/AWS\\_Security\\_Best\\_Practices.pdf](http://media.amazonwebservices.com/AWS_Security_Best_Practices.pdf)

#### NEW QUESTION 218

Which IAM role do you use to grant AWS Lambda permission to access a DynamoDB Stream?

- A. Dynamic role
- B. Invocation role
- C. Execution role
- D. Event Source role

**Answer:** C

**Explanation:** You grant AWS Lambda permission to access a DynamoDB Stream using an IAM role known as the "execution role".

Reference: <http://docs.aws.amazon.com/lambda/latest/dg/intro-permission-model.htm>

#### NEW QUESTION 223

Name the disk storage supported by Amazon Elastic Compute Cloud (EC2).

- A. None of these
- B. Amazon AppStream store
- C. Amazon SNS store
- D. Amazon Instance Store

**Answer:** D

**Explanation:** Amazon EC2 supports the following storage options: Amazon Elastic Block Store (Amazon EBS) Amazon EC2 Instance Store Amazon Simple Storage Service (Amazon S3)

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/Storage.html>

#### NEW QUESTION 227

You are signed in as root user on your account but there is an Amazon S3 bucket under your account that you cannot access. What is a possible reason for this?

- A. An IAM user assigned a bucket policy to an Amazon S3 bucket and didn't specify the root user as a principal
- B. The S3 bucket is full.
- C. The S3 bucket has reached the maximum number of objects allowed.
- D. You are in the wrong availability zone

**Answer:** A

**Explanation:** With IAM, you can centrally manage users, security credentials such as access keys, and permissions that control which AWS resources users can access.

In some cases, you might have an IAM user with full access to IAM and Amazon S3. If the IAM user assigns a bucket policy to an Amazon S3 bucket and doesn't specify the root user as a principal, the root user is denied access to that bucket. However, as the root user, you can still access the bucket by modifying the bucket policy to allow root user access.

Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/iam-troubleshooting.html#testing2>

#### NEW QUESTION 228

A user is observing the EC2 CPU utilization metric on CloudWatch. The user has observed some interesting patterns while filtering over the 1 week period for a particular hour. The user wants to zoom that data point to a more granular period. How can the user do that easily with CloudWatch?

- A. The user can zoom a particular period by selecting that period with the mouse and then releasing the mouse
- B. The user can zoom a particular period by specifying the aggregation data for that period
- C. The user can zoom a particular period by double clicking on that period with the mouse
- D. The user can zoom a particular period by specifying the period in the Time Range

**Answer:** A

**Explanation:** Amazon CloudWatch provides the functionality to graph the metric data generated either by the AWS services or the custom metric to make it easier for the user to analyse. The AWS CloudWatch console provides the option to change the granularity of a graph and zoom in to see data over a shorter time period. To zoom, the user has to click in the graph details pane, drag on the graph area for selection, and then release the mouse button.

Reference: [http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/zoom\\_in\\_on\\_graph.html](http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/zoom_in_on_graph.html)

**NEW QUESTION 231**

A scope has been handed to you to set up a super fast gaming server and you decide that you will use Amazon DynamoDB as your database. For efficient access to data in a table, Amazon DynamoDB creates and maintains indexes for the primary key attributes. A secondary index is a data structure that contains a subset of attributes from a table, along with an alternate key to support Query operations. How many types of secondary indexes does DynamoDB support?

- A. 2
- B. 16
- C. 4
- D. As many as you need

**Answer:** A

**Explanation:** DynamoDB supports two types of secondary indexes:

Local secondary index — an index that has the same hash key as the table, but a different range key. A local secondary index is "local" in the sense that every partition of a local secondary index is scoped to a table partition that has the same hash key.

Global secondary index — an index with a hash and range key that can be different from those on the table. A global secondary index is considered "global" because queries on the index can span all of the data in a table, across all partitions.

Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/SecondaryIndexes.html>

**NEW QUESTION 233**

Select the correct statement: Within Amazon EC2, when using Linux instances, the device name /dev/sda1 is .

- A. reserved for EBS volumes
- B. recommended for EBS volumes
- C. recommended for instance store volumes
- D. reserved for the root device

**Answer:** D

**Explanation:** Within Amazon EC2, when using a Linux instance, the device name /dev/sda1 is reserved for the root device.

Reference: [http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/device\\_naming.html](http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/device_naming.html)

**NEW QUESTION 237**

You need to set up security for your VPC and you know that Amazon VPC provides two features that you can use to increase security for your VPC: security groups and network access control lists (ACLs). You have already looked into security groups and you are now trying to understand ACLs. Which statement below is incorrect in relation to ACLs?

- A. Supports allow rules and deny rules.
- B. Is stateful: Return traffic is automatically allowed, regardless of any rules.
- C. Processes rules in number order when deciding whether to allow traffic.
- D. Operates at the subnet level (second layer of defense).

**Answer:** B

**Explanation:** Amazon VPC provides two features that you can use to increase security for your VPC:

Security groups—Act as a firewall for associated Amazon EC2 instances, controlling both inbound and outbound traffic at the instance level

Network access control lists (ACLs)—Act as a firewall for associated subnets, controlling both inbound and outbound traffic at the subnet level

Security groups are stateful: (Return traffic is automatically allowed, regardless of any rules) Network ACLs are stateless: (Return traffic must be explicitly allowed by rules)

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_Security.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Security.html)

**NEW QUESTION 240**

A user comes to you and wants access to Amazon CloudWatch but only wants to monitor a specific LoadBalancer. Is it possible to give him access to a specific set of instances or a specific LoadBalancer?

- A. No because you can't use IAM to control access to CloudWatch data for specific resources.
- B. Yes
- C. You can use IAM to control access to CloudWatch data for specific resources.
- D. No because you need to be Sysadmin to access CloudWatch data.
- E. Yes
- F. Any user can see all CloudWatch data and needs no access right

**Answer:** A

**Explanation:** Amazon CloudWatch integrates with AWS Identity and Access Management (IAM) so that you can

specify which CloudWatch actions a user in your AWS Account can perform. For example, you could create an IAM policy that gives only certain users in your organization permission to use GetMetricStatistics. They could then use the action to retrieve data about your cloud resources.

You can't use IAM to control access to CloudWatch data for specific resources. For example, you can't give a user access to CloudWatch data for only a specific set of instances or a specific LoadBalancer. Permissions granted using IAM cover all the cloud resources you use with CloudWatch. In addition, you can't use IAM roles with the Amazon CloudWatch command line tools.

Using Amazon CloudWatch with IAM doesn't change how you use CloudWatch. There are no changes to CloudWatch actions, and no new CloudWatch actions related to users and access control.

Reference: <http://docs.aws.amazon.com/AmazonCloudWatch/latest/DeveloperGuide/UsingIAM.html>

**NEW QUESTION 241**

You have multiple VPN connections and want to provide secure communication between sites using the AWS VPN CloudHub. Which statement is the most accurate in describing what you must do to set this up correctly?

- A. Create a virtual private gateway with multiple customer gateways, each with unique Border Gateway Protocol (BGP) Autonomous System Numbers (ASNs)
- B. Create a virtual private gateway with multiple customer gateways, each with a unique set of keys
- C. Create a virtual public gateway with multiple customer gateways, each with a unique Private subnet
- D. Create a virtual private gateway with multiple customer gateways, each with unique subnet id

**Answer:** A

**Explanation:** If you have multiple VPN connections, you can provide secure communication between sites using the AWS VPN CloudHub. The VPN CloudHub operates on a simple hub-and-spoke model that you can use with or without a VPC. This design is suitable for customers with multiple branch offices and existing Internet connections who'd like to implement a convenient, potentially low-cost hub-and-spoke model for primary or backup connectivity between these remote offices.

To use the AWS VPN CloudHub, you must create a virtual private gateway with multiple customer gateways, each with unique Border Gateway Protocol (BGP) Autonomous System Numbers (ASNs). Customer gateways advertise the appropriate routes (BGP prefixes) over their VPN connections. These routing advertisements are received and re-advertised to each BGP peer, enabling each site to send data to and receive data from the other sites. The routes for each spoke must have unique ASNs and the sites must not have overlapping IP ranges. Each site can also send and receive data from the VPC as if they were using a standard VPN connection.

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPN\\_CloudHub.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPN_CloudHub.html)

**NEW QUESTION 246**

Which one of the below is not an AWS Storage Service?

- A. Amazon S3
- B. Amazon Glacier
- C. Amazon CloudFront
- D. Amazon EBS

**Answer:** C

**Explanation:** AWS Storage Services are: Amazon S3

Amazon Glacier Amazon EBS

AWS Storage Gateway

Reference: <https://console.aws.amazon.com/console>

**NEW QUESTION 247**

You are very concerned about security on your network because you have multiple programmers testing APIs and SDKs and you have no idea what is happening. You think CloudTrail may help but are not sure what it does. Which of the following statements best describes the AWS service CloudTrail?

- A. With AWS CloudTrail you can get a history of AWS API calls and related events for your account.
- B. With AWS CloudTrail you can get a history of IAM users for your account.
- C. With AWS CloudTrail you can get a history of S3 logfiles for your account.
- D. With AWS CloudTrail you can get a history of CloudFormation JSON scripts used for your account

**Answer:** A

**Explanation:** With AWS CloudTrail, you can get a history of AWS API calls for your account, including API calls made via the AWS Management Console, the AWS SDKs, the command line tools, and higher-level AWS services. You can also identify which users and accounts called AWS APIs for services that support CloudTrail, the source IP address the calls were made from, and when the calls occurred.

You can identify which users and accounts called AWS for services that support CloudTrail, the source IP address the calls were made from, and when the calls occurred. You can integrate CloudTrail into applications using the API, automate trail creation for your organization, check the status of your trails, and control how administrators turn CloudTrail logging on and off.

Reference: [http://docs.aws.amazon.com/awscloudtrail/latest/userguide/what\\_is\\_cloud\\_trail\\_top\\_level.html](http://docs.aws.amazon.com/awscloudtrail/latest/userguide/what_is_cloud_trail_top_level.html)

**NEW QUESTION 251**

After setting up an EC2 security group with a cluster of 20 EC2 instances, you find an error in the security group settings. You quickly make changes to the security group settings. When will the changes to the settings be effective?

- A. The settings will be effective immediately for all the instances in the security group.
- B. The settings will be effective only when all the instances are restarted.
- C. The settings will be effective for all the instances only after 30 minutes.
- D. The settings will be effective only for the new instances added to the security group

**Answer:** A

**Explanation:** Amazon Redshift applies changes to a cluster security group immediately. So if you have associated the cluster security group with a cluster, inbound cluster access rules in the updated cluster security group apply immediately.

Reference: <http://docs.aws.amazon.com/redshift/latest/mgmt/working-with-security-groups.html>

**NEW QUESTION 255**

You have a lot of data stored in the AWS Storage Gateway and your manager has come to you asking about how the billing is calculated, specifically the Virtual Tape Shelf usage. What would be a correct response to this?

- A. You are billed for the virtual tape data you store in Amazon Glacier and are billed for the size of the virtual tape.
- B. You are billed for the virtual tape data you store in Amazon Glacier and billed for the portion of virtual tape capacity that you use, not for the size of the virtual tape.
- C. You are billed for the virtual tape data you store in Amazon S3 and billed for the portion of virtual tape capacity that you use, not for the size of the virtual tape.
- D. You are billed for the virtual tape data you store in Amazon S3 and are billed for the size of the virtual tape.

**Answer:** B

**Explanation:** The AWS Storage Gateway is a service connecting an on-premises software appliance with cloud-based storage to provide seamless and secure integration between an organization's on-premises IT environment and AWS's storage infrastructure.

AWS Storage Gateway billing is as follows. Volume storage usage (per GB per month):

You are billed for the Cached volume data you store in Amazon S3. You are only billed for volume capacity you use, not for the size of the volume you create.

Snapshot Storage usage (per GB per month): You are billed for the snapshots your gateway stores in Amazon S3. These snapshots are stored and billed as Amazon EBS snapshots. Snapshots are incremental backups, reducing your storage charges. When taking a new snapshot, only the data that has changed since your last snapshot is stored.

Virtual Tape Library usage (per GB per month):

You are billed for the virtual tape data you store in Amazon S3. You are only billed for the portion of virtual tape capacity that you use, not for the size of the virtual tape.

Virtual Tape Shelf usage (per GB per month):

You are billed for the virtual tape data you store in Amazon Glacier. You are only billed for the portion of virtual tape capacity that you use, not for the size of the virtual tape.

Reference: <https://aws.amazon.com/storagegateway/faqs/>

#### NEW QUESTION 258

You are configuring a new VPC for one of your clients for a cloud migration project, and only a public VPN will be in place. After you created your VPC, you created a new subnet, a new internet gateway, and attached your internet gateway to your VPC. When you launched your first instance into your VPC, you realized that you aren't able to connect to the instance, even if it is configured with an elastic IP. What should be done to access the instance?

- A. A route should be created as 0.0.0.0/0 and your internet gateway as target.
- B. Attach another ENI to the instance and connect via new ENI.
- C. A NAT instance should be created and all traffic should be forwarded to NAT instance.
- D. A NACL should be created that allows all outbound traffi

**Answer:** A

**Explanation:** All traffic should be routed via Internet Gateway. So, a route should be created with 0.0.0.0/0 as a source, and your Internet Gateway as your target.

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_Scenario1.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Scenario1.html)

#### NEW QUESTION 263

A user is currently building a website which will require a large number of instances in six months, when a demonstration of the new site will be given upon launch. Which of the below mentioned options allows the user to procure the resources beforehand so that they need not worry about infrastructure availability during the demonstration?

- A. Procure all the instances as reserved instances beforehand.
- B. Launch all the instances as part of the cluster group to ensure resource availability.
- C. Pre-warm all the instances one month prior to ensure resource availability.
- D. Ask AWS now to procure the dedicated instances in 6 month

**Answer:** A

**Explanation:** Amazon Web Services has massive hardware resources at its data centers, but they are finite. The best way for users to maximize their access to these resources is by reserving a portion of the computing capacity that they require. This can be done through reserved instances. With reserved instances, the user literally reserves the computing capacity in the Amazon Web Services cloud.

Reference: [http://media.amazonwebservices.com/AWS\\_Building\\_Fault\\_Tolerant\\_Applications.pdf](http://media.amazonwebservices.com/AWS_Building_Fault_Tolerant_Applications.pdf)

#### NEW QUESTION 266

You receive a bill from AWS but are confused because you see you are incurring different costs for the exact same storage size in different regions on Amazon S3. You ask AWS why this is so. What response would you expect to receive from AWS?

- A. We charge less in different time zones.
- B. We charge less where our costs are less.
- C. This will balance out next bill.
- D. It must be a mistak

**Answer:** B

**Explanation:** Amazon S3 is storage for the internet. It's a simple storage service that offers software developers a highly-scalable, reliable, and low-latency data storage infrastructure at very low costs.

AWS charges less where their costs are less.

For example, their costs are lower in the US Standard Region than in the US West (Northern California) Region.

Reference: <https://aws.amazon.com/s3/faqs/>



**NEW QUESTION 268**

You are setting up some EBS volumes for a customer who has requested a setup which includes a RAID (redundant array of inexpensive disks). AWS has some recommendations for RAID setups. Which RAID setup is not recommended for Amazon EBS?

- A. RAID 5 only
- B. RAID 5 and RAID 6
- C. RAID 1 only
- D. RAID 1 and RAID 6

**Answer:** B

**Explanation:** With Amazon EBS, you can use any of the standard RAID configurations that you can use with a traditional bare metal server, as long as that particular RAID configuration is supported by the operating system for your instance. This is because all RAID is accomplished at the software level. For greater I/O performance than you can achieve with a single volume, RAID 0 can stripe multiple volumes together; for on-instance redundancy, RAID 1 can mirror two volumes together.

RAID 5 and RAID 6 are not recommended for Amazon EBS because the parity write operations of these RAID modes consume some of the IOPS available to your volumes.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/raid-config.html>

**NEW QUESTION 269**

You receive the following request from a client to quickly deploy a static website for them, specifically on AWS. The requirements are low-cost, reliable, online storage, and a reliable and cost-effective way to route customers to the website, as well as a way to deliver content with low latency and high data transfer speeds so that visitors to his website don't experience unnecessary delays. What do you think would be the minimum AWS services that could fulfill the client's request?

- A. Amazon Route 53, Amazon CloudFront and Amazon VPC.
- B. Amazon S3, Amazon Route 53 and Amazon RDS
- C. Amazon S3, Amazon Route 53 and Amazon CloudFront
- D. Amazon S3 and Amazon Route 53.

**Answer:** C

**Explanation:** You can easily and inexpensively use AWS to host a website that uses client-side technologies (such as HTML, CSS, and JavaScript) and does not require server-side technologies (such as PHP and ASP.NET). This type of site is called a static website, and is used to display content that does not change frequently. Before you create and deploy a static website, you must plan your architecture to ensure that it meets your requirements. Amazon S3, Amazon Route 53, and Amazon CloudFront would be required in this instance.

Reference: <http://docs.aws.amazon.com/gettingstarted/latest/swl/website-hosting-intro.html>

**NEW QUESTION 270**

What is the network performance offered by the c4.8xlarge instance in Amazon EC2?

- A. 20 Gigabit
- B. 10 Gigabit
- C. Very High but variable
- D. 5 Gigabit

**Answer:** B

**Explanation:** Networking performance offered by the c4.8xlarge instance is 10 Gigabit. Reference: <http://aws.amazon.com/ec2/instance-types/>

**NEW QUESTION 271**

Doug has created a VPC with CIDR 10.201.0.0/16 in his AWS account. In this VPC he has created a public subnet with CIDR block 10.201.31.0/24. While launching a new EC2 from the console, he is not able to assign the private IP address 10.201.31.6 to this instance. Which is the most likely reason for this issue?

- A. Private IP address 10.201.31.6 is blocked via ACLs in Amazon infrastructure as a part of platform security.
- B. Private address IP 10.201.31.6 is currently assigned to another interface.
- C. Private IP address 10.201.31.6 is not part of the associated subnet's IP address range.
- D. Private IP address 10.201.31.6 is reserved by Amazon for IP networking purpose

**Answer:** B

**Explanation:** In Amazon VPC, you can assign any Private IP address to your instance as long as it is: Part of the associated subnet's IP address range  
Not reserved by Amazon for IP networking purposes  
Not currently assigned to another interface  
Reference: <http://aws.amazon.com/vpc/faqs/>

**NEW QUESTION 276**

You need to create a JSON-formatted text file for AWS CloudFormation. This is your first template and the only thing you know is that the templates include several major sections but there is only one that is required for it to work. What is the only section required?

- A. Mappings
- B. Outputs
- C. Resources
- D. Conditions

**Answer:** C

**Explanation:** AWS CloudFormation is a service that helps you model and set up your Amazon Web Services resources so that you can spend less time managing those resources and more time focusing on your applications that run in AWS. You create a template that describes all the AWS resources that you want (like Amazon EC2 instances or Amazon RDS DB instances), and AWS CloudFormation takes care of provisioning and configuring those resources for you. A template is a JSON-formatted text file that describes your AWS infrastructure. Templates include several major sections. The Resources section is the only section that is required. The first character in the template must be an open brace ({), and the last character must be a closed brace (}). The following template fragment shows the template structure and sections.  
Reference: <http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/template-anatomy.html>

**NEW QUESTION 280**

You are planning and configuring some EBS volumes for an application. In order to get the most performance out of your EBS volumes, you should attach them to an instance with enough to support your volumes.

- A. Redundancy
- B. Storage
- C. Bandwidth
- D. Memory

**Answer:** C

**Explanation:** When you plan and configure EBS volumes for your application, it is important to consider the configuration of the instances that you will attach the volumes to. In order to get the most performance out of your EBS volumes, you should attach them to an instance with enough bandwidth to support your volumes, such as an EBS-optimized instance or an instance with 10 Gigabit network connectMty. This is especially important when you use General Purpose (SSD) or Provisioned IOPS (SSD) volumes, or when you stripe multiple volumes together in a RAID configuration.  
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/ebs-ec2-config.html>

**NEW QUESTION 283**

Can a single EBS volume be attached to multiple EC2 instances at the same time?

- A. Yes
- B. No
- C. Only for high-performance EBS volumes.
- D. Only when the instances are located in the US region

**Answer:** B

**Explanation:** You can't attach an EBS volume to multiple EC2 instances. This is because it is equivalent to using a single hard drive with many computers at the same time.  
Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/AmazonEBS.html>

**NEW QUESTION 285**

How long does an AWS free usage tier EC2 last for?

- A. Forever
- B. 12 Months upon signup
- C. 1 Month upon signup
- D. 6 Months upon signup

**Answer:** B

**Explanation:** The AWS free usage tier will expire 12 months from the date you sign up. When your free usage expires or if your application use exceeds the free usage tiers, you simply pay the standard, pay-as-you-go service rates.  
Reference: <http://aws.amazon.com/free/faqs/>

**NEW QUESTION 289**

A user is hosting a website in the US West-1 region. The website has the highest client base from the Asia-Pacific (Singapore / Japan) region. The application is accessing data from S3 before serving it to client. Which of the below mentioned regions gives a better performance for S3 objects?

- A. Japan
- B. Singapore
- C. US East
- D. US West-1

**Answer:** D

**Explanation:** Access to Amazon S3 from within Amazon EC2 in the same region is fast. In this aspect, though the client base is Singapore, the application is being hosted in the US West-1 region. Thus, it is recommended that S3 objects be stored in the US-West-1 region.  
Reference: [http://media.amazonwebservices.com/AWS\\_Storage\\_Options.pdf](http://media.amazonwebservices.com/AWS_Storage_Options.pdf)

**NEW QUESTION 292**

Which of the following statements is true of tagging an Amazon EC2 resource?

- A. You don't need to specify the resource identifier while terminating a resource.
- B. You can terminate, stop, or delete a resource based solely on its tags.
- C. You can't terminate, stop, or delete a resource based solely on its tags.
- D. You don't need to specify the resource identifier while stopping a resource.

**Answer:** C

**Explanation:** You can assign tags only to resources that already exist. You can't terminate, stop, or delete a resource based solely on its tags; you must specify the resource identifier.

Reference: [http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/Using\\_Tags.html](http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/Using_Tags.html)

#### NEW QUESTION 294

You have been setting up an Amazon Virtual Private Cloud (Amazon VPC) for your company, including setting up subnets. Security is a concern, and you are not sure which is the best security practice for securing subnets in your VPC. Which statement below is correct in describing the protection of AWS resources in each subnet?

- A. You can use multiple layers of security, including security groups and network access control lists (ACL).
- B. You can only use access control lists (ACL).
- C. You don't need any security in subnets.
- D. You can use multiple layers of security, including security groups, network access control lists (ACL) and CloudHSM.

**Answer:** A

**Explanation:** A subnet is a range of IP addresses in your VPC. You can launch AWS resources into a subnet that you select. Use a public subnet for resources that must be connected to the Internet, and a private subnet for resources that won't be connected to the Internet.

To protect the AWS resources in each subnet, you can use multiple layers of security, including security groups and network access control lists (ACL).

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_Introduction.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Introduction.html)

#### NEW QUESTION 296

You have been asked to tighten up the password policies in your organization after a serious security breach, so you need to consider every possible security measure. Which of the following is not an account password policy for IAM Users that can be set?

- A. Force IAM users to contact an account administrator when the user has allowed his or her password to expire.
- B. A minimum password length.
- C. Force IAM users to contact an account administrator when the user has entered his password incorrectly.
- D. Prevent IAM users from reusing previous password

**Answer:** C

**Explanation:** IAM users need passwords in order to access the AWS Management Console. (They do not need passwords if they will access AWS resources programmatically by using the CLI, AWS SDKs, or the APIs.)

You can use a password policy to do these things: Set a minimum password length.

Require specific character types, including uppercase letters, lowercase letters, numbers, and non-alphanumeric characters. Be sure to remind your users that passwords are case sensitive. Allow all IAM users to change their own passwords.

Require IAM users to change their password after a specified period of time (enable password expiration). Prevent IAM users from reusing previous passwords.

Force IAM users to contact an account administrator when the user has allowed his or her password to expire.

Reference: [http://docs.aws.amazon.com/IAM/latest/UserGuide/Using\\_ManagingPasswordPolicies.html](http://docs.aws.amazon.com/IAM/latest/UserGuide/Using_ManagingPasswordPolicies.html)

#### NEW QUESTION 297

Your organization is in the business of architecting complex transactional databases. For a variety of reasons, this has been done on EBS. What is AWS's recommendation for customers who have architected databases using EBS for backups?

- A. Backups to Amazon S3 be performed through the database management system.
- B. Backups to AWS Storage Gateway be performed through the database management system.
- C. If you take regular snapshots no further backups are required.
- D. Backups to Amazon Glacier be performed through the database management system

**Answer:** A

**Explanation:** Data stored in Amazon EBS volumes is redundantly stored in multiple physical locations as part of normal operation of those services and at no additional charge.

However, Amazon EBS replication is stored within the same availability zone, not across multiple zones; therefore, it is highly recommended that you conduct regular snapshots to Amazon S3 for long-term data durability.

For customers who have architected complex transactional databases using EBS, it is recommended that backups to Amazon S3 be performed through the database management system so that distributed transactions and logs can be checkpointed.

AWS does not perform backups of data that are maintained on virtual disks attached to running instances on Amazon EC2.

Reference: <http://d0.awsstatic.com/whitepapers/Security/AWS%20Security%20Whitepaper.pdf>

#### NEW QUESTION 301

You have three Amazon EC2 instances with Elastic IP addresses in the US East (Virginia) region, and you want to distribute requests across all three IPs evenly for users for whom US East (Virginia) is the appropriate region.

How many EC2 instances would be sufficient to distribute requests in other regions?

- A. 3
- B. 9

- C. 2  
D. 1

**Answer:** D

**Explanation:** If your application is running on Amazon EC2 instances in two or more Amazon EC2 regions, and if you have more than one Amazon EC2 instance in one or more regions, you can use latency-based routing to route traffic to the correct region and then use weighted resource record sets to route traffic to instances within the region based on weights that you specify.

For example, suppose you have three Amazon EC2 instances with Elastic IP addresses in the US East (Virginia) region and you want to distribute requests across all three IPs evenly for users for whom US East (Virginia) is the appropriate region. Just one Amazon EC2 instance is sufficient in the other regions, although you can apply the same technique to many regions at once.

Reference: <http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/Tutorials.html>

#### NEW QUESTION 306

A user has created a CloudFormation stack. The stack creates AWS services, such as EC2 instances, ELB, AutoScaling, and RDS. While creating the stack it created EC2, ELB and AutoScaling but failed to create RDS. What will CloudFormation do in this scenario?

- A. Rollback all the changes and terminate all the created services  
B. It will wait for the user's input about the error and correct the mistake after the input  
C. CloudFormation can never throw an error after launching a few services since it verifies all the steps before launching  
D. It will warn the user about the error and ask the user to manually create RDS

**Answer:** A

**Explanation:** AWS CloudFormation is an application management tool which provides application modeling, deployment, configuration, management and related activities. The AWS CloudFormation stack is a collection of AWS resources which are created and managed as a single unit when AWS CloudFormation instantiates a template. If any of the services fails to launch, CloudFormation will rollback all the changes and terminate or delete all the created services.

Reference: <http://aws.amazon.com/cloudformation/faqs/>

#### NEW QUESTION 309

In Amazon EC2, what is the limit of Reserved Instances per Availability Zone each month?

- A. 5  
B. 20  
C. 50  
D. 10

**Answer:** B

**Explanation:** There are 20 Reserved Instances per Availability Zone in each month.

Reference: [http://docs.aws.amazon.com/general/latest/gr/aws\\_service\\_limits.html](http://docs.aws.amazon.com/general/latest/gr/aws_service_limits.html)

#### NEW QUESTION 311

You have just finished setting up an advertisement server in which one of the obvious choices for a service was Amazon Elastic Map Reduce (EMR) and are now troubleshooting some weird cluster states that you are seeing. Which of the below is not an Amazon EMR cluster state?

- A. STARTING  
B. STOPPED  
C. RUNNING  
D. WAITING

**Answer:** B

**Explanation:** Amazon Elastic Map Reduce (EMR) is a web service that enables businesses, researchers, data analysts, and developers to easily and cost-effectively process vast amounts of data.

Amazon EMR historically referred to an Amazon EMR cluster (and all processing steps assigned to it) as a "cluster". Every cluster has a unique identifier that starts with "j-".

The different cluster states of an Amazon EMR cluster are listed below. STARTING — The cluster provisions, starts, and configures EC2 instances.

BOOTSTRAPPING — Bootstrap actions are being executed on the cluster. RUNNING — A step for the cluster is currently being run.

WAITING — The cluster is currently active, but has no steps to run. TERMINATING - The cluster is in the process of shutting down. TERMINATED - The cluster was shut down without error. TERMINATED\_WITH\_ERRORS - The cluster was shut down with errors.

Reference: <https://aws.amazon.com/elasticmapreduce/faqs/>

#### NEW QUESTION 314

Is it possible to get a history of all EC2 API calls made on your account for security analysis and operational troubleshooting purposes?

- A. Yes, by default, the history of your API calls is logged.  
B. Yes, you should turn on the CloudTrail in the AWS console.  
C. No, you can only get a history of VPC API calls.  
D. No, you cannot store history of EC2 API calls on Amazon.

**Answer:** B

**Explanation:** To get a history of all EC2 API calls (including VPC and EBS) made on your account, you simply turn on CloudTrail in the AWS Management



Console.

Reference: <https://aws.amazon.com/ec2/faqs/>

#### NEW QUESTION 315

After moving an E-Commerce website for a client from a dedicated server to AWS you have also set up auto scaling to perform health checks on the instances in your group and replace instances that fail these checks. Your client has come to you with his own health check system that he wants you to use as it has proved to be very useful prior to his site running on AWS. What do you think would be an appropriate response to this given all that you know about auto scaling?

- A. It is not possible to implement your own health check system
- B. You need to use AWS's health check system.
- C. It is not possible to implement your own health check system due to compatibility issues.
- D. It is possible to implement your own health check system and then send the instance's health information directly from your system to Cloud Watch.
- E. It is possible to implement your own health check system and then send the instance's health information directly from your system to Cloud Watch but only in the US East (
- F. Virginia) region.

**Answer:** C

**Explanation:** Auto Scaling periodically performs health checks on the instances in your group and replaces instances that fail these checks. By default, these health checks use the results of EC2 instance status checks to determine the health of an instance. If you use a load balancer with your Auto Scaling group, you can optionally choose to include the results of Elastic Load Balancing health checks.

Auto Scaling marks an instance unhealthy if the calls to the Amazon EC2 action `DescribeInstanceStatus` returns any other state other than running, the system status shows impaired, or the calls to Elastic Load Balancing action `DescribeInstanceHealth` returns `OutOfService` in the instance state field.

After an instance is marked unhealthy because of an Amazon EC2 or Elastic Load Balancing health check, it is scheduled for replacement.

You can customize the health check conducted by your Auto Scaling group by specifying additional checks or by having your own health check system and then sending the instance's health information directly from your system to Auto Scaling.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/healthcheck.html>

#### NEW QUESTION 320

When does the billing of an Amazon EC2 system begin?

- A. It starts when the Status column for your distribution changes from Creating to Deployed.
- B. It starts as soon as you click the create instance option on the main EC2 console.
- C. It starts when your instance reaches 720 instance hours.
- D. It starts when Amazon EC2 initiates the boot sequence of an AM instance.

**Answer:** D

**Explanation:** Billing commences when Amazon EC2 initiates the boot sequence of an AM instance. Billing ends when the instance terminates, which could occur through a web services command, by running `"shutdown -h"`, or through instance failure. When you stop an instance, Amazon shuts it down but doesn't charge hourly usage for a stopped instance, or data transfer fees, but charges for the storage for any Amazon EBS volumes.

Reference: <http://aws.amazon.com/ec2/faqs/>

#### NEW QUESTION 324

You have just discovered that you can upload your objects to Amazon S3 using Multipart Upload API. You start to test it out but are unsure of the benefits that it would provide. Which of the following is not a benefit of using multipart uploads?

- A. You can begin an upload before you know the final object size.
- B. Quick recovery from any network issues.
- C. Pause and resume object uploads.
- D. It's more secure than normal uploads.

**Answer:** D

**Explanation:** Multipart upload in Amazon S3 allows you to upload a single object as a set of parts. Each part is a contiguous portion of the object's data. You can upload these object parts independently and in any order.

If transmission of any part fails, you can re-transmit that part without affecting other parts. After all parts of your object are uploaded, Amazon S3 assembles these parts and creates the object. In general, when

your object size reaches 100 MB, you should consider using multipart uploads instead of uploading the object in a single operation.

Using multipart upload provides the following advantages:

Improved throughput—You can upload parts in parallel to improve throughput.

Quick recovery from any network issues—Smaller part size minimizes the impact of restarting a failed upload due to a network error.

Pause and resume object uploads—You can upload object parts over time. Once you initiate a multipart upload there is no expiry; you must explicitly complete or abort the multipart upload.

Begin an upload before you know the final object size—You can upload an object as you are creating it. Reference:

<http://docs.aws.amazon.com/AmazonS3/latest/dev/uploadobjusingmpu.html>

#### NEW QUESTION 326

What is the data model of DynamoDB?

- A. Since DynamoDB is schema-less, there is no data model.
- B. "Items", with Keys and one or more Attribute; and "Attribute", with Name and Value.
- C. "Table", a collection of Items; "Items", with Keys and one or more Attribute; and "Attribute", with Name and Value.
- D. "Database", which is a set of "Tables", which is a set of "Items", which is a set of "Attributes".

**Answer:** C

**Explanation:** The data model of DynamoDB is: "Table", a collection of Items; "Items", with Keys and one or more Attribute; "Attribute", with Name and Value.  
Reference: <http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/DataModel.html>

#### NEW QUESTION 327

A gaming company comes to you and asks you to build them infrastructure for their site. They are not sure how big they will be as with all start ups they have limited money and big ideas. What they do tell you is that if the game becomes successful, like one of their previous games, it may rapidly grow to millions of users and generate tens (or even hundreds) of thousands of writes and reads per second. After considering all of this, you decide that they need a fully managed NoSQL database service that provides fast and predictable performance with seamless scalability. Which of the following databases do you think would best fit their needs?

- A. Amazon DynamoDB
- B. Amazon Redshift
- C. Any non-relational database.
- D. Amazon SimpleDB

**Answer:** A

**Explanation:** Amazon DynamoDB is a fully managed NoSQL database service that provides fast and predictable performance with seamless scalability. Amazon DynamoDB enables customers to offload the administrative burdens of operating and scaling distributed databases to AWS, so they don't have to worry about hardware provisioning, setup and configuration, replication, software patching, or cluster scaling. Today's web-based applications generate and consume massive amounts of data. For example, an online game might start out with only a few thousand users and a light database workload consisting of 10 writes per second and 50 reads per second. However, if the game becomes successful, it may rapidly grow to millions of users and generate tens (or even hundreds) of thousands of writes and reads per second. It may also create terabytes or more of data per day. Developing your applications against Amazon DynamoDB enables you to start small and simply dial-up your request capacity for a table as your requirements scale, without incurring downtime. You pay highly cost-efficient rates for the request capacity you provision, and let Amazon DynamoDB do the work over partitioning your data and traffic over sufficient server capacity to meet your needs. Amazon DynamoDB does the database management and administration, and you simply store and request your data. Automatic replication and failover provides built-in fault tolerance, high availability, and data durability. Amazon DynamoDB gives you the peace of mind that your database is fully managed and can grow with your application requirements.  
Reference: <http://aws.amazon.com/dynamodb/faqs/>

#### NEW QUESTION 332

Mike is appointed as Cloud Consultant in Netcrak Inc. Netcrak has the following VPCs set-up in the US East Region:  
A VPC with CIDR block 10.10.0.0/16, a subnet in that VPC with CIDR block 10.10.1.0/24 A VPC with CIDR block 10.40.0.0/16, a subnet in that VPC with CIDR block 10.40.1.0/24  
Netcrak Inc is trying to establish network connection between two subnets, a subnet with CIDR block 10.10.1.0/24 and another subnet with CIDR block 10.40.1.0/24. Which one of the following solutions should Mke recommend to Netcrak Inc?

- A. Create 2 Virtual Private Gateways and configure one with each VPC.
- B. Create one EC2 instance in each subnet, assign Elastic IPs to both instances, and configure a set up Site-to-Site VPN connection between both EC2 instances.
- C. Create a VPC Peering connection between both VPCs.
- D. Create 2 Internet Gateways, and attach one to each VP

**Answer:** C

**Explanation:** A VPC peering connection is a networking connection between two VPCs that enables you to route traffic between them using private IP addresses. EC2 instances in either VPC can communicate with each other as if they are within the same network. You can create a VPC peering connection between your own VPCs, or with a VPC in another AWS account within a single region. AWS uses the existing infrastructure of a VPC to create a VPC peering connection; it is neither a gateway nor a VPN connection, and does not rely on a separate piece of physical hardware.  
Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-peering.html>

#### NEW QUESTION 334

You're trying to delete an SSL certificate from the IAM certificate store, and you're getting the message "Certificate: <certificate-id> is being used by CloudFront." Which of the following statements is probably the reason why you are getting this error?

- A. Before you can delete an SSL certificate, you need to either rotate SSL certificates or revert from using a custom SSL certificate to using the default CloudFront certificate.
- B. You can't delete SSL certificates . You need to request it from AWS.
- C. Before you can delete an SSL certificate, you need to set up the appropriate access level in IAM
- D. Before you can delete an SSL certificate you need to set up https on your serve

**Answer:** A

**Explanation:** CloudFront is a web service that speeds up distribution of your static and dynamic web content, for example, .html, .css, .php, and image files, to end users. Every CloudFront web distribution must be associated either with the default CloudFront certificate or with a custom SSL certificate. Before you can delete an SSL certificate, you need to either rotate SSL certificates (replace the current custom SSL certificate with another custom SSL certificate) or revert from using a custom SSL certificate to using the default CloudFront certificate.  
Reference: <http://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/Troubleshooting.html>

#### NEW QUESTION 337

You need to set up security for your VPC and you know that Amazon VPC provides two features that you can use to increase security for your VPC: Security

groups and network access control lists (ACLs). You start to look into security groups first. Which statement below is incorrect in relation to security groups?

- A. Are stateful: Return traffic is automatically allowed, regardless of any rules.
- B. Evaluate all rules before deciding whether to allow traffic.
- C. Support allow rules and deny rules.
- D. Operate at the instance level (first layer of defense).

**Answer:** C

**Explanation:** Amazon VPC provides two features that you can use to increase security for your VPC:

Security groups—Act as a firewall for associated Amazon EC2 instances, controlling both inbound and outbound traffic at the instance level and supports allow rules only.

Network access control lists (ACLs)—Act as a firewall for associated subnets, controlling both inbound and outbound traffic at the subnet level and supports allow rules and deny rules.

Reference: [http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC\\_Security.html](http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/VPC_Security.html)

#### NEW QUESTION 340

In relation to AWS CloudHSM, High-availability (HA) recovery is hands-off resumption by failed HA group members.

Prior to the introduction of this function, the HA feature provided redundancy and performance, but required that a failed/lost group member be reinstated.

- A. automatically
- B. periodically
- C. manually
- D. continuously

**Answer:** C

**Explanation:** In relation to AWS CloudHSM, High-availability (HA) recovery is hands-off resumption by failed HA group members.

Prior to the introduction of this function, the HA feature provided redundancy and performance, but required that a failed/lost group member be manually reinstated.

Reference: <http://docs.aws.amazon.com/cloudhsm/latest/userguide/ha-best-practices.html>

#### NEW QUESTION 345

You have created a Route 53 latency record set from your domain to a machine in Northern Virginia and a similar record to a machine in Sydney.

When a user located in U S visits your domain he will be routed to:

- A. Northern Virginia
- B. Sydney
- C. Both, Northern Virginia and Sydney
- D. Depends on the Weighted Resource Record Sets

**Answer:** A

**Explanation:** If your application is running on Amazon EC2 instances in two or more Amazon EC2 regions, and if you have more than one Amazon EC2 instance in one or more regions, you can use latency-based routing to route traffic to the correct region and then use weighted resource record sets to route traffic to instances within the region based on weights that you specify.

For example, suppose you have three Amazon EC2 instances with Elastic IP addresses in the US East (Virginia) region and you want to distribute requests across all three IPs evenly for users for whom US East (Virginia) is the appropriate region. Just one Amazon EC2 instance is sufficient in the other regions, although you can apply the same technique to many regions at once.

Reference: <http://docs.aws.amazon.com/Route53/latest/DeveloperGuide/Tutorials.html>

#### NEW QUESTION 350

Any person or application that interacts with AWS requires security credentials. AWS uses these credentials to identify who is making the call and whether to allow the requested access. You have just set up a VPC network for a client and you are now thinking about the best way to secure this network. You set up a security group called vpcsecuritygroup. Which following statement is true in respect to the initial settings that will be applied to this security group if you choose to use the default settings for this group?

- A. Allow all inbound traffic and allow no outbound traffic.
- B. Allow no inbound traffic and allow all outbound traffic.
- C. Allow inbound traffic on port 80 only and allow all outbound traffic.
- D. Allow all inbound traffic and allow all outbound traffic

**Answer:** B

**Explanation:** Amazon VPC provides advanced security features such as security groups and network access control lists to enable inbound and outbound filtering at the instance level and subnet level.

AWS assigns each security group a unique ID in the form sg-xxxxxxx. The following are the initial settings for a security group that you create:

Allow no inbound traffic Allow all outbound traffic

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-network-security.html>

#### NEW QUESTION 351

You are using Amazon SES as an email solution but are unsure of what its limitations are. Which statement below is correct in regards to that?

- A. New Amazon SES users who have received production access can send up to 1,000 emails per 24-hour period, at a maximum rate of 10 emails per second.
- B. Every Amazon SES sender has a the same set of sending limits



- C. Sending limits are based on messages rather than on recipients  
D. Every Amazon SES sender has a unique set of sending limits

**Answer:** D

**Explanation:** Amazon Simple Email Service (Amazon SES) is a highly scalable and cost-effective email-sending service for businesses and developers. Amazon SES eliminates the complexity and expense of building an in-house email solution or licensing, installing, and operating a third-party email service for this type of email communication.

Every Amazon SES sender has a unique set of sending limits, which are calculated by Amazon SES on an ongoing basis:

Sending quota — the maximum number of emails you can send in a 24-hour period. Maximum send rate — the maximum number of emails you can send per second.

New Amazon SES users who have received production access can send up to 10,000 emails per 24-hour period, at a maximum rate of 5 emails per second.

Amazon SES automatically adjusts these limits upward, as long as you send high-quality email. If your existing quota is not adequate for your needs and the system has not automatically increased your quota, you can submit an SES Sending Quota Increase case at any time.

Sending limits are based on recipients rather than on messages. You can check your sending limits at any time by using the Amazon SES console.

Note that if your email is detected to be of poor or QUESTION able quality (e.g., high complaint rates, high bounce rates, spam, or abusive content), Amazon SES might temporarily or permanently reduce your permitted send volume, or take other action as AWS deems appropriate.

Reference: <https://aws.amazon.com/ses/faqs/>

### NEW QUESTION 352

Amazon Elastic Load Balancing is used to manage traffic on a fleet of Amazon EC2 instances, distributing traffic to instances across all availability zones within a region. Elastic Load Balancing has all the advantages of an on-premises load balancer, plus several security benefits.

Which of the following is not an advantage of ELB over an on-premise load balancer?

- A. ELB uses a four-tier, key-based architecture for encryption.  
B. ELB offers clients a single point of contact, and can also serve as the first line of defense against attacks on your network.  
C. ELB takes over the encryption and decryption work from the Amazon EC2 instances and manages it centrally on the load balancer.  
D. ELB supports end-to-end traffic encryption using TLS (previously SSL) on those networks that use secure HTTP (HTTPS) connections.

**Answer:** A

**Explanation:** Amazon Elastic Load Balancing is used to manage traffic on a fleet of Amazon EC2 instances, distributing traffic to instances across all availability zones within a region. Elastic Load Balancing has all the advantages of an on-premises load balancer, plus several security benefits:

Takes over the encryption and decryption work from the Amazon EC2 instances and manages it centrally on the load balancer

Offers clients a single point of contact, and can also serve as the first line of defense against attacks on your network

When used in an Amazon VPC, supports creation and management of security groups associated with your Elastic Load Balancing to provide additional networking and security options

Supports end-to-end traffic encryption using TLS (previously SSL) on those networks that use secure HTTP (HTTPS) connections. When TLS is used, the TLS server certificate used to terminate client connections can be managed centrally on the load balancer, rather than on every individual instance. Reference:

<http://d0.awsstatic.com/whitepapers/Security/AWS%20Security%20Whitepaper.pdf>

### NEW QUESTION 353

You have been asked to build AWS infrastructure for disaster recovery for your local applications and within that you should use an AWS Storage Gateway as part of the solution. Which of the following best describes the function of an AWS Storage Gateway?

- A. Accelerates transferring large amounts of data between the AWS cloud and portable storage devices .  
B. A web service that speeds up distribution of your static and dynamic web content.  
C. Connects an on-premises software appliance with cloud-based storage to provide seamless and secure integration between your on-premises IT environment and AWS's storage infrastructure.  
D. Is a storage service optimized for infrequently used data, or "cold data."

**Answer:** C

**Explanation:** AWS Storage Gateway connects an on-premises software appliance with cloud-based storage to provide seamless integration with data security features between your on-premises IT environment and the Amazon Web Services (AWS) storage infrastructure. You can use the service to store data in the AWS cloud for scalable and cost-effective storage that helps maintain data security. AWS Storage Gateway offers both volume-based and tape-based storage solutions:

Volume gateways Gateway-cached volumes Gateway-stored volumes

Gateway-virtual tape library (VTL)

Reference:

[http://media.amazonwebservices.com/architecturecenter/AWS\\_ac\\_ra\\_disasterrecovery\\_07.pdf](http://media.amazonwebservices.com/architecturecenter/AWS_ac_ra_disasterrecovery_07.pdf)

### NEW QUESTION 356

An organization has a statutory requirement to protect the data at rest for the S3 objects. Which of the below mentioned options need not be enabled by the organization to achieve data security?

- A. MFA delete for S3 objects  
B. Client side encryption  
C. Bucket versioning  
D. Data replication

**Answer:** D

**Explanation:** AWS S3 provides multiple options to achieve the protection of data at REST. The options include Permission (Policy), Encryption (Client and Server Side), Bucket Versioning and MFA based delete. The user can enable any of these options to achieve data protection. Data replication is an internal facility by AWS where S3 replicates each object across all the Availability Zones and the organization need not enable it in this case.

Reference: [http://media.amazonwebservices.com/AWS\\_Security\\_Best\\_Practices.pdf](http://media.amazonwebservices.com/AWS_Security_Best_Practices.pdf)



**NEW QUESTION 357**

In Amazon CloudFront, if you use Amazon EC2 instances and other custom origins with CloudFront, it is recommended to .

- A. not use Elastic Load Balancing
- B. restrict Internet communication to private instances while allowing outgoing traffic
- C. enable access key rotation for CloudWatch metrics
- D. specify the URL of the load balancer for the domain name of your origin server

**Answer:** D

**Explanation:** In Amazon CloudFront, you should use an Elastic Load Balancing load balancer to handle traffic across multiple Amazon EC2 instances and to isolate your application from changes to Amazon EC2 instances. When you create your CloudFront distribution, specify the URL of the load balancer for the domain name of your origin server.

Reference: <http://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/CustomOriginBestPractices.html>

**NEW QUESTION 359**

What is the time period with which metric data is sent to CloudWatch when detailed monitoring is enabled on an Amazon EC2 instance?

- A. 15 minutes
- B. 5 minutes
- C. 1 minute
- D. 45 seconds

**Answer:** C

**Explanation:** By default, Amazon EC2 metric data is automatically sent to CloudWatch in 5-minute periods. However, you can, enable detailed monitoring on an Amazon EC2 instance, which sends data to CloudWatch in 1-minute periods

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-cloudwatch.html>

**NEW QUESTION 363**

A government client needs you to set up secure cryptographic key storage for some of their extremely confidential data. You decide that the AWS CloudHSM is the best service for this. However, there seem to be a few pre-requisites before this can happen, one of those being a security group that has certain ports open. Which of the following is correct in regards to those security groups?

- A. A security group that has port 22 (for SSH) or port 3389 (for RDP) open to your network.
- B. A security group that has no ports open to your network.
- C. A security group that has only port 3389 (for RDP) open to your network.
- D. A security group that has only port 22 (for SSH) open to your network.

**Answer:** A

**Explanation:** AWS CloudHSM provides secure cryptographic key storage to customers by making hardware security modules (HSMs) available in the AWS cloud. AWS CloudHSM requires the following environment before an HSM appliance can be provisioned. A virtual private cloud (VPC) in the region where you want the AWS CloudHSM service.

One private subnet (a subnet with no Internet gateway) in the VPC. The HSM appliance is provisioned into this subnet.

One public subnet (a subnet with an Internet gateway attached). The control instances are attached to this subnet.

An AWS Identity and Access Management (IAM) role that delegates access to your AWS resources to AWS CloudHSM.

An EC2 instance, in the same VPC as the HSM appliance, that has the SafeNet client software installed. This instance is referred to as the control instance and is used to connect to and manage the HSM appliance.

A security group that has port 22 (for SSH) or port 3389 (for RDP) open to your network. This security group is attached to your control instances so you can access them remotely.

**NEW QUESTION 368**

Which of the following features are provided by Amazon EC2?

- A. Exadata Database Machine, Optimized Storage Management, Flashback Technology, and Data Warehousing
- B. Instances, Amazon Machine Images (AMIs), Key Pairs, Amazon EBS Volumes, Firewall, Elastic IP address, Tags, and Virtual Private Clouds (VPCs)
- C. Real Application Clusters (RAC), ElastiCache Machine Images (EMIs), Data Warehousing, Flashback Technology, Dynamic IP address
- D. Exadata Database Machine, Real Application Clusters (RAC), Data Guard, Table and Index Partitioning, and Data Pump Compression

**Answer:** B

**Explanation:** Amazon EC2 provides the following features:

- Virtual computing environments, known as instances;
- Pre-configured templates for your instances, known as Amazon Machine Images (AMIs), that package the bits you need for your server (including the operating system and additional software)
- Various configurations of CPU, memory, storage, and networking capacity for your instances, known as instance types
- Secure login information for your instances using key pairs (AWS stores the public key, and you store the private key in a secure place)
- Storage volumes for temporary data that's deleted when you stop or terminate your instance, known as instance store volumes
- Persistent storage volumes for your data using Amazon Elastic Block Store (Amazon EBS), known as Amazon EBS volumes
- Multiple physical locations for your resources, such as instances and Amazon EBS volumes, known as regions and Availability Zones
- A firewall that enables you to specify the protocols, ports, and source IP ranges that can reach your instances using security groups
- Static IP addresses for dynamic cloud computing, known as Elastic IP addresses

- Metadata, known as tags, that you can create and assign to your Amazon EC2 resources
- Virtual networks you can create that are logically isolated from the rest of the AWS cloud, and that you can optionally connect to your own network, known as virtual private clouds (VPCs).

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/concepts.html>

**NEW QUESTION 372**

A friend tells you he is being charged \$100 a month to host his WordPress website, and you tell him you can move it to AWS for him and he will only pay a fraction of that, which makes him very happy. He then tells you he is being charged \$50 a month for the domain, which is registered with the same people that set it up, and he asks if it's possible to move that to AWS as well. You tell him you aren't sure, but will look into it. Which of the following statements is true in regards to transferring domain names to AWS?

- A. You can't transfer existing domains to AWS.
- B. You can transfer existing domains into Amazon Route 53's management.
- C. You can transfer existing domains via AWS Direct Connect.
- D. You can transfer existing domains via AWS Import/Export

**Answer:** B

**Explanation:** With Amazon Route 53, you can create and manage your public DNS records with the AWS Management Console or with an easy-to-use API. If you need a domain name, you can find an available name and register it using Amazon Route 53. You can also transfer existing domains into Amazon Route 53's management.

Reference: <http://aws.amazon.com/route53/>

**NEW QUESTION 376**

Are penetration tests allowed as long as they are limited to the customer's instances?

- A. Yes, they are allowed but only for selected regions.
- B. No, they are never allowed.
- C. Yes, they are allowed without any permission.
- D. Yes, they are allowed but only with approval.

**Answer:** D

**Explanation:** Penetration tests are allowed after obtaining permission from AWS to perform them. Reference: <http://aws.amazon.com/security/penetration-testing/>

**NEW QUESTION 377**

A user has created an ELB with the availability zone US-East-1A. The user wants to add more zones to ELB to achieve High Availability. How can the user add more zones to the existing ELB?

- A. The user should stop the ELB and add zones and instances as required
- B. The only option is to launch instances in different zones and add to ELB
- C. It is not possible to add more zones to the existing ELB
- D. The user can add zones on the fly from the AWS console

**Answer:** D

**Explanation:** The user has created an Elastic Load Balancer with the availability zone and wants to add more zones to the existing ELB. The user can do so in two ways:

From the console or CLI, add new zones to ELB;

Launch instances in a separate AZ and add instances to the existing ELB. Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/enable-disable-az.html>

**NEW QUESTION 381**

What happens to data on an ephemeral volume of an EBS-backed EC2 instance if it is terminated or if it fails?

- A. Data is automatically copied to another volume.
- B. The volume snapshot is saved in S3.
- C. Data persists.
- D. Data is delete

**Answer:** D

**Explanation:** Any data on the instance store volumes persists as long as the instance is running, but this data is deleted when the instance is terminated or if it fails (such as if an underlying drive has issues). After an instance store-backed instance fails or terminates, it cannot be restored.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/RootDeviceStorage.html>

**NEW QUESTION 382**

A user is sending bulk emails using AWS SES. The emails are not reaching some of the targeted audience because they are not authorized by the ISPs. How can the user ensure that the emails are all delivered?

- A. Send an email using DKIMI with SES.
- B. Send an email using SMTP with SES.
- C. Open a ticket with AWS support to get it authorized with the ISP.

D. Authorize the ISP by sending emails from the development account

**Answer:** A

**Explanation:** Domain Keys Identified Mail (DKIM) is a standard that allows senders to sign their email messages and ISPs, and use those signatures to verify that those messages are legitimate and have not been modified by a third party in transit.

Reference: <http://docs.aws.amazon.com/ses/latest/DeveloperGuide/dkim.html>

#### NEW QUESTION 385

In AWS CloudHSM, in addition to the AWS recommendation that you use two or more HSM appliances in a high-availability configuration to prevent the loss of keys and data, you can also perform a remote backup/restore of a Luna SA partition if you have purchased a:

- A. Luna Restore HSM.
- B. Luna Backup HSM.
- C. Luna HSM.
- D. Luna SA HSM.

**Answer:** B

**Explanation:** In AWS CloudHSM, you can perform a remote backup/restore of a Luna SA partition if you have purchased a Luna Backup HSM.

Reference: <http://docs.aws.amazon.com/cloudhsm/latest/userguide/cloud-hsm-backup-restore.html>

#### NEW QUESTION 386

Content and IVMedia Server is the latest requirement that you need to meet for a client.

The client has been very specific about his requirements such as low latency, high availability, durability, and access control. Potentially there will be millions of views on this server and because of "spiky" usage patterns, operations teams will need to provision static hardware, network, and management resources to support the maximum expected need. The Customer base will be initially low but is expected to grow and become more geographically distributed.

Which of the following would be a good solution for content distribution?

- A. Amazon S3 as both the origin server and for caching
- B. AWS Storage Gateway as the origin server and Amazon EC2 for caching
- C. AWS CloudFront as both the origin server and for caching
- D. Amazon S3 as the origin server and Amazon CloudFront for caching

**Answer:** D

**Explanation:** As your customer base grows and becomes more geographically distributed, using a high-performance edge cache like Amazon CloudFront can provide substantial improvements in latency, fault tolerance, and cost.

By using Amazon S3 as the origin server for the Amazon CloudFront distribution, you gain the advantages of fast in-network data transfer rates, simple publishing/caching workflow, and a unified security framework.

Amazon S3 and Amazon CloudFront can be configured by a web service, the AWS Management Console, or a host of third-party management tools.

Reference: [http://media.amazonwebservices.com/architecturecenter/AWS\\_ac\\_ra\\_media\\_02.pdf](http://media.amazonwebservices.com/architecturecenter/AWS_ac_ra_media_02.pdf)

#### NEW QUESTION 387

An EC2 instance is connected to an ENI (Elastic Network Interface) in one subnet. What happens when you attach an ENI of a different subnet to this EC2 instance?

- A. The EC2 instance follows the rules of the older subnet
- B. The EC2 instance follows the rules of both the subnets
- C. Not possible, cannot be connected to 2 ENIs
- D. The EC2 instance follows the rules of the newer subnet

**Answer:** B

**Explanation:** AWS allows you create an elastic network interface (ENI), attach an ENI to an EC2 instance, detach an ENI from an EC2 instance and attach this ENI to another EC2 instance. The attributes of a network traffic follow the ENI which is attached to an EC2 instance or detached from an EC2 instance. When you move an ENI from one EC2 instance to another, network traffic is redirected to the new EC2 instance. You can create and attach additional ENIs to an EC2 instance.

Attaching multiple network interfaces (ENIs) to an EC2 instance is useful to: Create a management network.

Use network and security appliances in your VPC.

Create dual-homed instances with workloads/roles on distinct subnets Create a low-budget, high-availability solution.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-eni.html>

#### NEW QUESTION 392

Which one of the below doesn't affect Amazon CloudFront billing?

- A. Distribution Type
- B. Data Transfer Out
- C. Dedicated IP SSL Certificates
- D. Requests

**Answer:** A

**Explanation:** Amazon CloudFront is a web service for content delivery. CloudFront delivers your content using a global network of edge locations and works

seamlessly with Amazon S3 which durably stores the original and definitive versions of your files.  
Amazon CloudFront billing is mainly affected by Data Transfer Out  
Edge Location Traffic Distribution Requests  
Dedicated IP SSL Certificates  
Reference: <http://calculator.s3.amazonaws.com/index.html>

**NEW QUESTION 394**

Your company has multiple IT departments, each with their own VPC. Some VPCs are located within the same AWS account, and others in a different AWS account. You want to peer together all VPCs to enable the IT departments to have full access to each others' resources. There are certain limitations placed on VPC peering. Which of the following statements is incorrect in relation to VPC peering?

- A. Private DNS values cannot be resolved between instances in peered VPCs.
- B. You can have up to 3 VPC peering connections between the same two VPCs at the same time.
- C. You cannot create a VPC peering connection between VPCs in different regions.
- D. You have a limit on the number active and pending VPC peering connections that you can have per VPC.

**Answer:** B

**Explanation:** To create a VPC peering connection with another VPC, you need to be aware of the following limitations and rules:

You cannot create a VPC peering connection between VPCs that have matching or overlapping CIDR blocks.

You cannot create a VPC peering connection between VPCs in different regions.

You have a limit on the number active and pending VPC peering connections that you can have per VPC. VPC peering does not support transitive peering relationships; in a VPC peering connection, your VPC will not have access to any other VPCs that the peer VPC may be peered with. This includes VPC peering connections that are established entirely within your own AWS account.

You cannot have more than one VPC peering connection between the same two VPCs at the same time. The Maximum Transmission Unit (MTU) across a VPC peering connection is 1500 bytes.

A placement group can span peered VPCs; however, you will not get full-bisection bandwidth between instances in peered VPCs.

Unicast reverse path forwarding in VPC peering connections is not supported.

You cannot reference a security group from the peer VPC as a source or destination for ingress or egress rules in your security group. Instead, reference CIDR blocks of the peer VPC as the source or destination of your security group's ingress or egress rules.

Private DNS values cannot be resolved between instances in peered VPCs. Reference:

<http://docs.aws.amazon.com/AmazonVPC/latest/PeeringGuide/vpc-peering-overview.html#vpc-peering-limitations>

**NEW QUESTION 398**

A company wants to review the security requirements of Glacier. Which of the below mentioned statements is true with respect to the AWS Glacier data security?

- A. All data stored on Glacier is protected with AES-256 serverside encryption.
- B. All data stored on Glacier is protected with AES-128 serverside encryption.
- C. The user can set the serverside encryption flag to encrypt the data stored on Glacier.
- D. The data stored on Glacier is not encrypted by default

**Answer:** A

**Explanation:** For Amazon Web Services, all the data stored on Amazon Glacier is protected using serverside encryption. AWS generates separate unique encryption keys for each Amazon Glacier archive, and encrypts it using AES-256. The encryption key then encrypts itself using AES-256 with a master key that is stored in a secure location.

Reference: [http://media.amazonwebservices.com/AWS\\_Security\\_Best\\_Practices.pdf](http://media.amazonwebservices.com/AWS_Security_Best_Practices.pdf)

**NEW QUESTION 401**

You are architecting a highly-scalable and reliable web application which will have a huge amount of content. You have decided to use CloudFront as you know it will speed up distribution of your static and dynamic web content and know that Amazon CloudFront integrates with Amazon CloudWatch metrics so that you can monitor your web application. Because you live in Sydney you have chosen the Asia Pacific (Sydney) region in the AWS console. However you have set up this up but no CloudFront metrics seem to be appearing in the CloudWatch console. What is the most likely reason from the possible choices below for this?

- A. Metrics for CloudWatch are available only when you choose the same region as the application you are monitoring.
- B. You need to pay for CloudWatch for it to become active.
- C. Metrics for CloudWatch are available only when you choose the US East (N. Virginia)
- D. Virginia)
- E. Metrics for CloudWatch are not available for the Asia Pacific region as yet

**Answer:** C

**Explanation:** CloudFront is a global service, and metrics are available only when you choose the US East (N. Virginia) region in the AWS console. If you choose another region, no CloudFront metrics will appear in the CloudWatch console.

Reference:

<http://docs.aws.amazon.com/AmazonCloudFront/latest/DeveloperGuide/monitoring-using-cloudwatch.html>

**NEW QUESTION 404**

A friend wants you to set up a small BitTorrent storage area for him on Amazon S3. You tell him it is highly unlikely that AWS would allow such a thing in their infrastructure. However you decide to investigate. Which of the following statements best describes using BitTorrent with Amazon S3?

- A. Amazon S3 does not support the BitTorrent protocol because it is used for pirated software.
- B. You can use the BitTorrent protocol but only for objects that are less than 100 GB in size.
- C. You can use the BitTorrent protocol but you need to ask AWS for specific permissions first.
- D. You can use the BitTorrent protocol but only for objects that are less than 5 GB in size



**Answer:** D

**Explanation:** BitTorrent is an open, peer-to-peer protocol for distributing files. You can use the BitTorrent protocol to retrieve any publicly-accessible object in Amazon S3.

Amazon S3 supports the BitTorrent protocol so that developers can save costs when distributing content at high scale. Amazon S3 is useful for simple, reliable storage of any data. The default distribution mechanism for Amazon S3 data is via client/server download. In client/server distribution, the entire object is transferred point-to-point from Amazon S3 to every authorized user who requests that object. While client/server delivery is appropriate for a wide variety of use cases, it is not optimal for everybody. Specifically, the costs of client/server distribution increase linearly as the number of users downloading objects increases. This can make it expensive to distribute popular objects.

BitTorrent addresses this problem by recruiting the very clients that are downloading the object as distributors themselves: Each client downloads some pieces of the object from Amazon S3 and some from other clients, while simultaneously uploading pieces of the same object to other interested "peers." The benefit for publishers is that for large, popular files the amount of data actually supplied by Amazon S3 can be substantially lower than what it would have been sewing the same clients via client/server download. Less data transferred means lower costs for the publisher of the object.

Reference: <http://docs.aws.amazon.com/AmazonS3/latest/dev/S3Torrent.html>

#### NEW QUESTION 409

After a major security breach your manager has requested a report of all users and their credentials in AWS. You discover that in IAM you can generate and download a credential report that lists all users in your account and the status of their various credentials, including passwords, access keys, MFA devices, and signing certificates. Which following statement is incorrect in regards to the use of credential reports?

- A. Credential reports are downloaded XML files.
- B. You can get a credential report using the AWS Management Console, the AWS CLI, or the IAM API.
- C. You can use the report to audit the effects of credential lifecycle requirements, such as password rotation.
- D. You can generate a credential report as often as once every four hour

**Answer:** A

**Explanation:** To access your AWS account resources, users must have credentials.

You can generate and download a credential report that lists all users in your account and the status of their various credentials, including passwords, access keys, MFA devices, and signing certificates. You can get a credential report using the AWS Management Console, the AWS CLI, or the IAM API.

You can use credential reports to assist in your auditing and compliance efforts. You can use the report to audit the effects of credential lifecycle requirements, such as password rotation. You can provide the report to an external auditor, or grant permissions to an auditor so that he or she can download the report directly. You can generate a credential report as often as once every four hours. When you request a report, IAM first checks whether a report for the account has been generated within the past four hours. If so, the most recent report is downloaded. If the most recent report for the account is more than four hours old, or if there are no previous reports for the account, IAM generates and downloads a new report.

Credential reports are downloaded as comma-separated values (CSV) files.

You can open CSV files with common spreadsheet software to perform analysis, or you can build an application that consumes the CSV files programmatically and performs custom analysis. Reference: <http://docs.aws.amazon.com/IAM/latest/UserGuide/credential-reports.html>

#### NEW QUESTION 410

In the most recent company meeting, your CEO focused on the fact that everyone in the organization needs to make sure that all of the infrastructure that is built is truly scalable. Which of the following statements is incorrect in reference to scalable architecture?

- A. A scalable service is capable of handling heterogeneity.
- B. A scalable service is resilient.
- C. A scalable architecture won't be cost effective as it grows.
- D. Increasing resources results in a proportional increase in performanc

**Answer:** C

**Explanation:** In AWS it is critical to build a scalable architecture in order to take advantage of a scalable infrastructure. The cloud is designed to provide conceptually infinite scalability. However, you cannot leverage all that scalability in infrastructure if your architecture is not scalable. Both have to work together. You will have to identify the monolithic components and bottlenecks in your architecture, identify the areas where you cannot leverage the on-demand provisioning capabilities in your architecture, and work to refactor your application, in order to leverage the scalable infrastructure and take advantage of the cloud.

Characteristics of a truly scalable application:

Increasing resources results in a proportional increase in performance A scalable service is capable of handling heterogeneity

A scalable service is operationally efficient A scalable service is resilient

A scalable service should become more cost effective when it grows (Cost per unit reduces as the number of units increases)

Reference: [http://media.amazonwebservices.com/AWS\\_Cloud\\_Best\\_Practices.pdf](http://media.amazonwebservices.com/AWS_Cloud_Best_Practices.pdf)

#### NEW QUESTION 413

A user has defined an AutoScaling termination policy to first delete the instance with the nearest billing hour. AutoScaling has launched 3 instances in the US-East-1A region and 2 instances in the US-East-1 B region. One of the instances in the US-East-1B region is running nearest to the billing hour. Which instance will AutoScaling terminate first while executing the termination action?

- A. Random Instance from US-East-1A
- B. Instance with the nearest billing hour in US-East-1 B
- C. Instance with the nearest billing hour in US-East-1A
- D. Random instance from US-East-1B

**Answer:** C

**Explanation:** Even though the user has configured the termination policy, before AutoScaling selects an instance to terminate, it first identifies the Availability Zone that has more instances than the other Availability Zones used by the group. Within the selected Availability Zone, it identifies the instance that matches the specified termination policy.

Reference: <http://docs.aws.amazon.com/AutoScaling/latest/DeveloperGuide/us-termination-policy.html>

**NEW QUESTION 415**

A user has configured a website and launched it using the Apache web server on port 80. The user is using ELB with the EC2 instances for Load Balancing. What should the user do to ensure that the EC2 instances accept requests only from ELB?

- A. Configure the security group of EC2, which allows access to the ELB source security group
- B. Configure the EC2 instance so that it only listens on the ELB port
- C. Open the port for an ELB static IP in the EC2 security group
- D. Configure the security group of EC2, which allows access only to the ELB listener

**Answer:** A

**Explanation:** When a user is configuring ELB and registering the EC2 instances with it, ELB will create a source security group. If the user wants to allow traffic only from ELB, he should remove all the rules set for the other requests and open the port only for the ELB source security group.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/using-elb-security-groups.html>

**NEW QUESTION 416**

A user is planning a highly available application deployment with EC2. Which of the below mentioned options will not help to achieve HA?

- A. Elastic IP address
- B. PIOPS
- C. AMI
- D. Availability Zones

**Answer:** B

**Explanation:** In Amazon Web Service, the user can achieve HA by deploying instances in multiple zones. The elastic IP helps the user achieve HA when one of the instances is down but still keeps the same URL. The AM helps launching the new instance. The PIOPS is for the performance of EBS and does not help for HA. Reference: [http://media.amazonwebservices.com/AWS\\_Web\\_Hosting\\_Best\\_Practices.pdf](http://media.amazonwebservices.com/AWS_Web_Hosting_Best_Practices.pdf)

**NEW QUESTION 421**

After deploying a new website for a client on AWS, he asks if you can set it up so that if it fails it can be automatically redirected to a backup website that he has stored on a dedicated server elsewhere. You are wondering whether Amazon Route 53 can do this. Which statement below is correct in regards to Amazon Route 53?

- A. Amazon Route 53 can't help detect an outage
- B. You need to use another service.
- C. Amazon Route 53 can help detect an outage of your website and redirect your end users to alternate locations.
- D. Amazon Route 53 can help detect an outage of your website but can't redirect your end users to alternate locations.
- E. Amazon Route 53 can't help detect an outage of your website, but can redirect your end users to alternate locations.

**Answer:** B

**Explanation:** With DNS Failover, Amazon Route 53 can help detect an outage of your website and redirect your end users to alternate locations where your application is operating properly.

Reference:

<http://aws.amazon.com/about-aws/whats-new/2013/02/11/announcing-dns-failover-for-route-53/>

**NEW QUESTION 423**

While creating a network in the VPC, which of the following is true of a NAT device?

- A. You have to administer the NAT Gateway Service provided by AWS.
- B. You can choose to use any of the three kinds of NAT devices offered by AWS for special purposes.
- C. You can use a NAT device to enable instances in a private subnet to connect to the Internet.
- D. You are recommended to use AWS NAT instances over NAT gateways, as the instances provide better availability and bandwidth.

**Answer:** C

**Explanation:** You can use a NAT device to enable instances in a private subnet to connect to the Internet (for example, for software updates) or other AWS services, but prevent the Internet from initiating connections with the instances. AWS offers two kinds of NAT devices u a NAT gateway or a NAT instance. We recommend NAT gateways, as they provide better availability and bandwidth over NAT instances. The NAT Gateway service is also a managed service that does not require your administration efforts. A NAT instance is launched from a NAT AM. You can choose to use a NAT instance for special purposes.

Reference: <http://docs.aws.amazon.com/AmazonVPC/latest/UserGuide/vpc-nat.html>

**NEW QUESTION 425**

All Amazon EC2 instances are assigned two IP addresses at launch. Which are those?

- A. 2 Elastic IP addresses
- B. A private IP address and an Elastic IP address
- C. A public IP address and an Elastic IP address
- D. A private IP address and a public IP address

**Answer:** D

**Explanation:** In Amazon EC2-Classical every instance is given two IP Addresses: a private IP address and a public IP address

Reference:

<http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-instance-addressing.html#differences>

#### NEW QUESTION 426

You want to establish a dedicated network connection from your premises to AWS in order to save money by transferring data directly to AWS rather than through your internet service provider. You are sure there must be some other benefits beyond cost savings. Which of the following would not be considered a benefit if you were to establish such a connection?

- A. Elasticity
- B. Compatibility with all AWS services.
- C. Private connectMty to your Amazon VPC.
- D. Everything listed is a benefi

**Answer:** D

**Explanation:** AWS Direct Connect makes it easy to establish a dedicated network connection from your premises to AWS.

Using AWS Direct Connect, you can establish private connectMty between AWS and your datacenter, office, or colocation environment, which in many cases can reduce your network costs, increase bandwidth throughput, and provide a more consistent network experience than internet-based connections.

You could expect the following benefits if you use AWS Direct Connect. Reduced bandwidth costs

Consistent network performance Compatibility with all AWS services Private connectMty to your Amazon VPC Elasticity

Simplicity

Reference: <http://aws.amazon.com/directconnect/>

#### NEW QUESTION 429

You can seamlessly join an EC2 instance to your directory domain. What connectMty do you need to be able to connect remotely to this instance?

- A. You must have IP connectMty to the instance from the network you are connecting from.
- B. You must have the correct encryption keys to connect to the instance remotely.
- C. You must have enough bandwidth to connect to the instance.
- D. You must use MFA authentication to be able to connect to the instance remotel

**Answer:** A

**Explanation:** You can seamlessly join an EC2 instance to your directory domain when the instance is launched using the Amazon EC2 Simple Systems Manager. If you need to manually join an EC2 instance to your domain, you must launch the instance in the proper region and security group or subnet, then join the instance to the domain. To be able to connect remotely to these instances, you must have IP connectMty to the instances from the network you are connecting from. In most cases, this requires that an Internet gateway be attached to your VPC and that the instance has a public IP address.

Reference: [http://docs.aws.amazon.com/directoryservice/latest/admin-guide/join\\_a\\_directory.html](http://docs.aws.amazon.com/directoryservice/latest/admin-guide/join_a_directory.html)

#### NEW QUESTION 432

George has launched three EC2 instances inside the US-East-1a zone with his AWS account. Ray has launched two EC2 instances in the US-East-1a zone with his AWS account. Which of the below mentioned statements will help George and Ray understand the availability zone (AZ) concept better?

- A. All the instances of George and Ray can communicate over a private IP with a minimal cost
- B. The US-East-1a region of George and Ray can be different availability zones
- C. All the instances of George and Ray can communicate over a private IP without any cost
- D. The instances of George and Ray will be running in the same data centre

**Answer:** B

**Explanation:** Each AWS region has multiple, isolated locations known as Availability Zones. To ensure that the AWS resources are distributed across the Availability Zones for a region, AWS independently maps the Availability Zones to identifiers for each account. In this case the Availability Zone US-East-1a where George's EC2 instances are running might not be the same location as the US-East-1a zone of Ray's EC2 instances. There is no way for the user to coordinate the Availability Zones between accounts.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/using-regions-availability-zones.html>

#### NEW QUESTION 435

You are in the process of moving your friend's WordPress site onto AWS to try and save him some money, and you have told him that he should probably also move his domain name. He asks why he can't leave his domain name where it is and just have his infrastructure on AWS. What would be an incorrect response to his question ?

- A. Route 53 offers low query latency for your end users.
- B. Route 53 is designed to automatically answer queries from the optimal location depending on network conditions.
- C. The globally distributed nature of AWS's DNS servers helps ensure a consistent ability to route your end users to your application.
- D. Route 53 supports Domain Name System Security Extensions (DNSSEC).

**Answer:** D

**Explanation:** Amazon Route 53 provides highly available and scalable Domain Name System (DNS), domain name registration, and health-checking web services.

Route 53 is built using AWS's highly available and reliable infrastructure. The globally distributed nature of our DNS servers helps ensure a consistent ability to route your end users to your application by circumventing any internet or network related issues. Route 53 is designed to provide the level of dependability required by important applications. Using a global anycast network of DNS servers around the world, Route 53 is designed to automatically answer queries from

the optimal location depending on network conditions. As a result, the service offers low query latency for your end users.

Amazon Route 53 does not support Domain Name System Security Extensions (DNSSEC) at this time. Reference: <https://aws.amazon.com/route53/faqs/>

**NEW QUESTION 439**

Can you encrypt EBS volumes?

- A. Yes, you can enable encryption when you create a new EBS volume using the AWS Management Console, API, or CLI.
- B. No, you should use a third-party software to perform raw block-level encryption of an EBS volume.
- C. Yes, but you must use a third-party API for encrypting data before it's loaded on EBS.
- D. Yes, you can encrypt with the special "ebs\_encrypt" command through Amazon API

**Answer:** A

**Explanation:** With Amazon EBS encryption, you can now create an encrypted EBS volume and attach it to a supported instance type. Data on the volume, disk I/O, and snapshots created from the volume are then all encrypted. The encryption occurs on the servers that host the EC2 instances, providing encryption of data as it moves between EC2 instances and EBS storage. EBS encryption is based on the industry standard AES-256 cryptographic algorithm.

To get started, simply enable encryption when you create a new EBS volume using the AWS Management Console, API, or CLI. Amazon EBS encryption is available for all the latest EC2 instances in all commercially available AWS regions.

Reference:

<https://aws.amazon.com/about-aws/whats-new/2014/05/21/Amazon-EBS-encryption-now-available/>

**NEW QUESTION 441**

In Amazon EC2, you are billed instance-hours when .

- A. your EC2 instance is in a running state
- B. the instance exits from Amazon S3 console
- C. your instance still exits the EC2 console
- D. EC2 instances stop

**Answer:** A

**Explanation:** You are billed instance-hours as long as your EC2 instance is in a running state. Reference: <http://aws.amazon.com/ec2/faqs/>

**NEW QUESTION 442**

A user has created an ELB with Auto Scaling. Which of the below mentioned offerings from ELB helps the user to stop sending new requests traffic from the load balancer to the EC2 instance when the instance is being deregistered while continuing in-flight requests?

- A. ELB sticky session
- B. ELB deregistration check
- C. ELB auto registration Off
- D. ELB connection draining

**Answer:** D

**Explanation:** The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that in-flight requests continue to be served.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/config-conn-drain.html>

**NEW QUESTION 445**

A user is running a webserver on EC2. The user wants to receive the SMS when the EC2 instance utilization is above the threshold limit. Which AWS services should the user configure in this case?

- A. AWS CloudWatch + AWS SQS.
- B. AWS CloudWatch + AWS SNS.
- C. AWS CloudWatch + AWS SES.
- D. AWS EC2 + AWS Cloudwatch

**Answer:** B

**Explanation:** Amazon SNS makes it simple and cost-effective to push to mobile devices, such as iPhone, iPad, Android, Kindle Fire, and internet connected smart devices, as well as pushing to other distributed services. In this case, the user can configure that Cloudwatch sends an alarm on when the threshold is crossed to SNS which will trigger an SMS.

Reference: <http://aws.amazon.com/sns/>

**NEW QUESTION 450**

You have some very sensitive data stored on AWS S3 and want to try every possible alternative to keeping it secure in regards to access control. What are the mechanisms available for access control on AWS S3?

- A. (IAM) policies, Access Control Lists (ACLs), bucket policies, and query string authentication.
- B. (IAM) policies, Access Control Lists (ACLs) and bucket policies.
- C. Access Control Lists (ACLs), bucket policies, and query string authentication
- D. (IAM) policies, Access Control Lists (ACLs), bucket policies, query string authentication and encryption.



**Answer:** A

**Explanation:** Amazon S3 supports several mechanisms that give you flexibility to control who can access your data as well as how, when, and where they can access it.

Amazon S3 provides four different access control mechanisms:

AWS Identity and Access Management (IAM) policies, Access Control Lists (ACLs), bucket policies, and query string authentication.

IAM enables organizations to create and manage multiple users under a single AWS account. With IAM policies, you can grant IAM users fine-grained control to your Amazon S3 bucket or objects. You can use ACLs to selectively add (grant) certain permissions on individual objects.

Amazon S3 bucket policies can be used to add or deny permissions across some or all of the objects within a single bucket.

With Query string authentication, you have the ability to share Amazon S3 objects through URLs that are valid for a specified period of time.

#### NEW QUESTION 451

Your manager has come to you saying that he is very confused about the bills he is receiving from AWS as he is getting different bills for every user and needs you to look into making it more understandable. Which of the following would be the best solution to meet his request?

- A. AWS Billing Aggregation
- B. Consolidated Billing
- C. Deferred Billing
- D. Aggregated Billing

**Answer:** B

**Explanation:** Consolidated Billing enables you to consolidate payment for multiple AWS accounts within your company by designating a single paying account. Consolidated Billing enables you to see a combined view of AWS costs incurred by all accounts, as well as obtain a detailed cost report for each of the individual AWS accounts associated with your "Paying Account". Consolidated Billing is offered at no additional charge. Reference: <https://aws.amazon.com/billing/faqs/>

#### NEW QUESTION 455

A user is planning to host a mobile game on EC2 which sends notifications to active users on either high score or the addition of new features. The user should get this notification when he is online on his mobile device. Which of the below mentioned AWS services can help achieve this functionality?

- A. AWS Simple Notification Service.
- B. AWS Simple Email Service.
- C. AWS Mobile Communication Service.
- D. AWS Simple Queue Service.

**Answer:** A

**Explanation:** Amazon Simple Notification Service (Amazon SNS) is a fast, flexible, and fully managed push messaging service. Amazon SNS makes it simple and cost-effective to push to mobile devices, such as iPhone, iPad, Android, Kindle Fire, and internet connected smart devices, as well as pushing to other distributed services.

Reference: <http://aws.amazon.com/sns>

#### NEW QUESTION 456

You have written a CloudFormation template that creates 1 Elastic Load Balancer fronting 2 EC2 Instances. Which section of the template should you edit so that the DNS of the load balancer is returned upon creation of the stack?

- A. Resources
- B. Outputs
- C. Parameters
- D. Mappings

**Answer:** B

**Explanation:** You can use AWS CloudFormation's sample templates or create your own templates to describe the AWS resources, and any associated dependencies or runtime parameters, required to run your application.

Reference:

<http://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/outputs-section-structure.html>

#### NEW QUESTION 460

You have been asked to set up a database in AWS that will require frequent and granular updates. You know that you will require a reasonable amount of storage space but are not sure of the best option. What is the recommended storage option when you run a database on an instance with the above criteria?

- A. Amazon S3
- B. Amazon EBS
- C. AWS Storage Gateway
- D. Amazon Glacier

**Answer:** B

**Explanation:** Amazon EBS provides durable, block-level storage volumes that you can attach to a running Amazon EC2 instance. You can use Amazon EBS as a primary storage device for data that requires frequent and granular updates. For example, Amazon EBS is the recommended storage option when you run a database on an instance.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/Storage.html>

**NEW QUESTION 465**

You have been asked to set up monitoring of your network and you have decided that Cloudwatch would be the best service to use. Amazon CloudWatch monitors your Amazon Web Services (AWS) resources and the applications you run on AWS in real-time. You can use CloudWatch to collect and track metrics, which are the variables you want to measure for your resources and applications. Which of the following items listed can AWS Cloudwatch monitor?

- A. Log files your applications generate.
- B. All of the items listed on this page.
- C. System-wide visibility into resource utilization, application performance, and operational health.
- D. Custom metrics generated by your applications and services .

**Answer:** B

**Explanation:** Amazon CloudWatch can monitor AWS resources such as Amazon EC2 instances, Amazon DynamoDB tables, and Amazon RDS DB instances, as well as custom metrics generated by your applications and services, and any log files your applications generate. You can use Amazon CloudWatch to gain system-wide visibility into resource utilization, application performance, and operational health. You can use these insights to react and keep your application running smoothly.

Reference: <http://aws.amazon.com/cloudwatch/>

**NEW QUESTION 468**

A user has hosted an application on EC2 instances. The EC2 instances are configured with ELB and Auto Scaling. The application server session time out is 2 hours. The user wants to configure connection draining to ensure that all in-flight requests are supported by ELB even though the instance is being deregistered. What time out period should the user specify for connection draining?

- A. 1 hour
- B. 30 minutes
- C. 5 minutes
- D. 2 hours

**Answer:** A

**Explanation:** The Elastic Load Balancer connection draining feature causes the load balancer to stop sending new requests to the back-end instances when the instances are deregistering or become unhealthy, while ensuring that in-flight requests continue to be served. The user can specify a maximum time of 3600 seconds (1 hour) for the load balancer to keep the connections alive before reporting the instance as deregistered. If the user does not specify the maximum timeout period, by default, the load balancer will close the connections to the deregistering instance after 300 seconds.

Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/config-conn-drain.html>

**NEW QUESTION 470**

You need to quickly set up an email-sending service because a client needs to start using it in the next hour. Amazon Simple Email Service (Amazon SES) seems to be the logical choice but there are several options available to set it up. Which of the following options to set up SES would best meet the needs of the client?

- A. Amazon SES console
- B. AWS CloudFormation
- C. SMTP Interface
- D. AWS Elastic Beanstalk

**Answer:** A

**Explanation:** Amazon SES is an outbound-only email-sending service that provides an easy, cost-effective way for you to send email.

There are several ways that you can send an email by using Amazon SES. You can use the Amazon SES console, the Simple Mail Transfer Protocol (SMTP) interface, or you can call the Amazon SES API. Amazon SES console—This method is the quickest way to set up your system

Reference: <http://docs.aws.amazon.com/ses/latest/DeveloperGuide/Welcome.html>

**NEW QUESTION 475**

Which of the following statements is NOT true about using Elastic IP Address (EIP) in EC2-Classic and EC2-VPC platforms?

- A. In the EC2-VPC platform, the Elastic IP Address (EIP) does not remain associated with the instance when you stop it.
- B. In the EC2-Classic platform, stopping the instance disassociates the Elastic IP Address (EIP) from it.
- C. In the EC2-VPC platform, if you have attached a second network interface to an instance, when you disassociate the Elastic IP Address (EIP) from that instance, a new public IP address is not assigned to the instance automatically; you'll have to associate an EIP with it manually.
- D. In the EC2-Classic platform, if you disassociate an Elastic IP Address (EIP) from the instance, the instance is automatically assigned a new public IP address within a few minutes.

**Answer:** A

**Explanation:** In the EC2-Classic platform, when you associate an Elastic IP Address (EIP) with an instance, the instance's current public IP address is released to the EC2-Classic public IP address pool. If you disassociate an EIP from the instance, the instance is automatically assigned a new public IP address within a few minutes. In addition, stopping the instance also disassociates the EIP from it.

But in the EC2-VPC platform, when you associate an EIP with an instance in a default Virtual Private Cloud (VPC), or an instance in which you assigned a public IP to the eth0 network interface during launch, its current public IP address is released to the EC2-VPC public IP address pool. If you disassociate an EIP from the instance, the instance is automatically assigned a new public IP address within a few minutes. However, if you have attached a second network interface to the instance, the instance is not automatically assigned a new public IP address; you'll have to associate an EIP with it manually. The EIP remains associated with the instance when you stop it.

Reference: <http://docs.aws.amazon.com/AWSEC2/latest/UserGuide/elastic-ip-addresses-eip.html>

**NEW QUESTION 480**

You have a Business support plan with AWS. One of your EC2 instances is running Microsoft Windows Server 2008 R2 and you are having problems with the software. Can you receive support from AWS for this software?

- A. Yes
- B. No, AWS does not support any third-party software.
- C. No, Microsoft Windows Server 2008 R2 is not supported.
- D. No, you need to be on the enterprise support plan

**Answer:** A

**Explanation:** Third-party software support is available only to AWS Support customers enrolled for Business or Enterprise Support. Third-party support applies only to software running on Amazon EC2 and does not extend to assisting with on-premises software. An exception to this is a VPN tunnel configuration running supported devices for Amazon VPC.

Reference: <https://aws.amazon.com/premiumsupport/features/>

**NEW QUESTION 483**

After deciding that EMR will be useful in analysing vast amounts of data for a gaming website that you are architecting you have just deployed an Amazon EMR Cluster and wish to monitor the cluster performance. Which of the following tools cannot be used to monitor the cluster performance?

- A. Kinesis
- B. Ganglia
- C. CloudWatch Metrics
- D. Hadoop Web Interfaces

**Answer:** A

**Explanation:** Amazon EMR provides several tools to monitor the performance of your cluster. Hadoop Web Interfaces

Every cluster publishes a set of web interfaces on the master node that contain information about the cluster. You can access these web pages by using an SSH tunnel to connect them on the master node. For more information, see [View Web Interfaces Hosted on Amazon EMR Clusters](#).

CloudWatch Metrics

Every cluster reports metrics to CloudWatch. CloudWatch is a web service that tracks metrics, and which you can use to set alarms on those metrics. For more information, see [Monitor Metrics with CloudWatch](#). Ganglia

Ganglia is a cluster monitoring tool. To have this available, you have to install Ganglia on the cluster when you launch it. After you've done so, you can monitor the cluster as it runs by using an SSH tunnel to connect to the Ganglia UI running on the master node. For more information, see [Monitor Performance with Ganglia](#).

Reference:

<http://docs.aws.amazon.com/ElasticMapReduce/latest/DeveloperGuide/emr-troubleshoot-tools.html>

**NEW QUESTION 488**

A user has launched one EC2 instance in the US West region. The user wants to access the RDS instance launched in the US East region from that EC2 instance. How can the user configure the access for that EC2 instance?

- A. Configure the IP range of the US West region instance as the ingress security rule of RDS
- B. It is not possible to access RDS of the US East region from the US West region
- C. Open the security group of the US West region in the RDS security group's ingress rule
- D. Create an IAM role which has access to RDS and launch an instance in the US West region with it

**Answer:** A

**Explanation:** The user cannot authorize an Amazon EC2 security group if it is in a different AWS Region than the RDS DB instance. The user can authorize an IP range or specify an Amazon EC2 security group in the same region that refers to an IP address in another region.

Reference: [http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER\\_WorkingWithSecurityGroups.html](http://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/USER_WorkingWithSecurityGroups.html)

**NEW QUESTION 490**

You need to create a load balancer in a VPC network that you are building. You can make your load balancer internal (private) or internet-facing (public). When you make your load balancer internal, a DNS name will be created, and it will contain the private IP address of the load balancer. An internal load balancer is not exposed to the internet. When you make your load balancer internet-facing, a DNS name will be created with the public IP address. If you want the Internet-facing load balancer to be connected to the Internet, where must this load balancer reside?

- A. The load balancer must reside in a subnet that is connected to the internet using the internet gateway.
- B. The load balancer must reside in a subnet that is not connected to the internet.
- C. The load balancer must not reside in a subnet that is connected to the internet.
- D. The load balancer must be completely outside of your VPC

**Answer:** A

**Explanation:** When you create an internal Elastic Load Balancer in a VPC, you need to select private subnets that are in the same Availability Zone as your instances. If the VPC Elastic Load Balancer is to be public facing, you need to create the Elastic Load Balancer in a public subnet. A subnet is a public subnet if it is attached to an Internet Gateway (IGW) with a defined route to that gateway. Selecting more than one public subnet increases the availability of your Elastic Load Balancer.

NB - Elastic Load Balancers in EC2-Classic are always Internet-facing load balancers. Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/elb-internet-facing-load-balancers.html>

**NEW QUESTION 493**

Can you move a Reserved Instance from one Availability Zone to another?

- A. Yes, but each Reserved Instance is associated with a specific Region that cannot be changed.  
B. Yes, only in US-West-2.  
C. Yes, only in US-East-1.  
D. No

**Answer:** A

**Explanation:** Each Reserved Instance is associated with a specific Region, which is fixed for the lifetime of the reservation and cannot be changed. Each reservation can, however, be used in any of the available AZs within the associated Region.

Reference: <https://aws.amazon.com/rds/faqs/>

#### NEW QUESTION 497

An application hosted at the EC2 instance receives an HTTP request from ELB. The same request has an X-Forwarded-For header, which has three IP addresses. Which system's IP will be a part of this header?

- A. Previous Request IP address.  
B. Client IP address.  
C. All of the answers listed here.  
D. Load Balancer IP address

**Answer:** C

**Explanation:** When a user sends a request to ELB over HTTP/HTTPS, the request header log at the instance will only receive the IP of ELB. This is because ELB is the interceptor between the EC2 instance and the client request. To get the client IP, use the header X-Forwarded-For in header. The client IP address in the X-Forwarded-For request header is followed by the IP addresses of each successive proxy that passes along the request. The last IP address is the IP address that connects to the back-end application instance. e.g. if the HTTP request already has a header when it reaches the Load Balancer, the IP address from which the request came is appended at the end of the header followed by the IP address of the Load Balancer. In such cases, the X-Forwarded-For request header takes the following form:

X-Forwarded-For: clientIPAddress, previousRequestIPAddress, LoadBalancerIPAddress. Reference:

<http://docs.aws.amazon.com/ElasticLoadBalancing/latest/DeveloperGuide/TerminologyandKeyConcepts.html>

#### NEW QUESTION 502

You need to develop and run some new applications on AWS and you know that Elastic Beanstalk and CloudFormation can both help as a deployment mechanism for a broad range of AWS resources. Which of the following statements best describes the differences between Elastic Beanstalk and CloudFormation?

- A. Elastic Beanstalk uses Elastic load balancing and CloudFormation doesn't.  
B. CloudFormation is faster in deploying applications than Elastic Beanstalk.  
C. Elastic Beanstalk is faster in deploying applications than CloudFormation.  
D. CloudFormation is much more powerful than Elastic Beanstalk, because you can actually design and script custom resources

**Answer:** D

**Explanation:** These services are designed to complement each other. AWS Elastic Beanstalk provides an environment to easily develop and run applications in the cloud. It is integrated with developer tools and provides a one-stop experience for you to manage the lifecycle of your applications. AWS CloudFormation is a convenient deployment mechanism for a broad range of AWS resources. It supports the infrastructure needs of many different types of applications such as existing enterprise applications, legacy applications, applications built using a variety of AWS resources and container-based solutions (including those built using AWS Elastic Beanstalk).

AWS CloudFormation introduces two new concepts: The template, a JSON-format, text-based file that describes all the AWS resources you need to deploy to run your application and the stack, the set of AWS resources that are created and managed as a single unit when AWS CloudFormation instantiates a template.

Reference: <http://aws.amazon.com/cloudformation/faqs/>

#### NEW QUESTION 507

You need to set up a security certificate for a client's e-commerce website as it will use the HTTPS protocol. Which of the below AWS services do you need to access to manage your SSL server certificate?

- A. AWS Directory Service  
B. AWS Identity & Access Management  
C. AWS CloudFormation  
D. Amazon Route 53

**Answer:** B

**Explanation:** AWS Identity and Access Management (IAM) is a web service that enables Amazon Web Services (AWS) customers to manage users and user permissions in AWS.

All your SSL server certificates are managed by AWS Identity and Access management (IAM). Reference:

<http://docs.aws.amazon.com/IAM/latest/UserGuide/ManagingServerCerts.html>

#### NEW QUESTION 509

When controlling access to Amazon EC2 resources, each Amazon EBS Snapshot has a attribute that controls which AWS accounts can use the snapshot.

- A. createVolumePermission  
B. LaunchPermission  
C. SharePermission  
D. RequestPermission



**Answer:** A

**Explanation:** Each Amazon EBS Snapshot has a createVolumePermission attribute that you can set to one or more AWS Account IDs to share the AM with those AWS Accounts. To allow several AWS Accounts to use a particular EBS snapshot, you can use the snapshots's createVolumePermission attribute to include a list of the accounts that can use it.

Reference: <http://docs.amazonwebservices.com/AWSEC2/latest/UserGuide/UsingIAM.html>

#### NEW QUESTION 511

A 3-tier e-commerce web application is current deployed on-premises and will be migrated to AWS for greater scalability and elasticity The web server currently shares read-only data using a network distributed file system The app server tier uses a clustering mechanism for discovery and shared session state that depends on I P multicast The database tier uses shared-storage clustering to provide database fail over capability, and uses several read slaves for scaling Data on all sewers and the distributed file system directory is backed up weekly to off-site tapes Which AWS storage and database architecture meets the requirements of the application?

- A. Web sewers: store read-only data in 53, and copy from 53 to root volume at boot tim
- B. App servers: share state using a combination of DynamoDB and IP unicas
- C. Database: use RDS with multi-AZ deployment and one or more read replica
- D. Backup: web servers, app servers, and database backed up weekly to Glacier using snapshots.
- E. Web sewers: store read-only data in an EC2 NFS server, mount to each web server at boot tim
- F. App servers: share state using a combination of DynamoDB and IP multicas
- G. Database: use RDS with multi-AZ deployment and one or more Read Replica
- H. Backup: web and app servers backed up weekly via AM Is, database backed up via DB snapshots.
- I. Web servers: store read-only data in 53, and copy from 53 to root volume at boot tim
- J. App servers: share state using a combination of DynamoDB and IP unicas
- K. Database: use RDS with multi-AZ deployment and one or more Read Replica
- L. Backup: web and app servers backed up weekly viaAM Is, database backed up via DB snapshots.
- M. Web servers: store read-only data in 53, and copy from 53 to root volume at boot tim
- N. App servers: share state using a combination of DynamoDB and IP unicas
- O. Database: use RDS with multi-AZ deploymen
- P. Backup: web and app sewers backed up weekly via ANI Is, database backed up via DB snapshots.

**Answer:** C

**Explanation:** Amazon RDS Multi-AZ deployments provide enhanced availability and durability for Database (DB) Instances, making them a natural fit for production database workloads. When you provision a Multi-AZ DB Instance, Amazon RDS automatically creates a primary DB Instance and synchronously replicates the data to a standby instance in a different Availability Zone (AZ). Each AZ runs on its own physically distinct, independent infrastructure, and is engineered to be highly reliable. In case of an infrastructure failure (for example, instance hardware failure, storage failure, or network disruption), Amazon RDS performs an automatic failover to the standby, so that you can resume database operations as soon as the failover is complete. Since the endpoint for your DB Instance remains the same after a failover, your application can resume database operation without the need for manual administrative intervention.

Benefits

Enhanced Durability

Multi-AZ deployments for the MySQL, Oracle, and PostgreSQL engines utilize synchronous physical replication to keep data on the standby up-to-date with the primary. Multi-AZ deployments for the SQL Server engine use synchronous logical replication to achieve the same result, employing SQL Server-native Mrroring technology. Both approaches safeguard your data in the event of a DB Instance failure or loss of an Availability Zone.

If a storage volume on your primary fails in a Multi-AZ deployment, Amazon RDS automatically initiates a failover to the up-to-date standby. Compare this to a Single-AZ deployment: in case of a Single-AZ database failure, a user-initiated point-in-time-restore operation will be required. This operation can take several hours to complete, and any data updates that occurred after the latest restorable time (typically within the last five minutes) will not be available.

Amazon Aurora employs a highly durable, SSD-backed virtualized storage layer purpose-built for database workloads. Amazon Aurora automatically replicates your volume six ways, across three Availability Zones. Amazon Aurora storage is fault-tolerant, transparently handling the loss of up to two copies of data without affecting database write availability and up to three copies without affecting read availability. Amazon Aurora storage is also self-healing. Data blocks and disks are continuously scanned for errors and replaced automatically.

Increased Availability

You also benefit from enhanced database availability when running Multi-AZ deployments. If an Availability Zone failure or DB Instance failure occurs, your availability impact is limited to the time automatic failover takes to complete: typically under one minute for Amazon Aurora and one to two minutes for other database engines (see the RDS FAQ for details).

The availability benefits of Multi-AZ deployments also extend to planned maintenance and backups.

In the case of system upgrades like OS patching or DB Instance scaling, these operations are applied first on the standby, prior to the automatic failover. As a result, your availability impact is, again, only the time required for automatic fail over to complete.

Unlike Single-AZ deployments, 1/0 actMty is not suspended on your primary during backup for Multi-AZ deployments for the MySQL, Oracle, and PostgreSQL engines, because the backup is taken from the standby. However, note that you may still experience elevated latencies for a few minutes during backups for Mu|ti-AZ deployments.

On instance failure in Amazon Aurora deployments, Amazon RDS uses RDS Multi-AZ technology to automate failover to one of up to 15 Amazon Aurora Replicas you have created in any of three Availability Zones. If no Amazon Aurora Replicas have been provisioned, in the case of a failure, Amazon RDS will attempt to create a new Amazon Aurora DB instance for you automatically.

No Administrative Intervention

DB Instance failover is fully automatic and requires no administrative intervention. Amazon RDS monitors the health of your primary and standbys, and initiates a failover automatically in response to a variety of failure conditions.

Failover conditions

Amazon RDS detects and automatically recovers from the most common failure scenarios for Multi-AZ deployments so that you can resume database operations as quickly as possible without administrative intervention. Amazon RDS automatically performs a failover in the event of any of the following:

Loss of availability in primary Availability Zone Loss of network connectMty to primary Compute unit failure on primary

Storage failure on primary

Note: When operations such as DB Instance scaling or system upgrades like OS patching are initiated for Multi-AZ deployments, for enhanced availability, they are applied first on the standby prior to an automatic failover. As a result, your availability impact is limited only to the time required for automatic failover to complete.

Note that Amazon RDS Multi-AZ deployments do not failover automatically in response to database operations such as long running queries, deadlocks or database corruption errors.

#### NEW QUESTION 512

.....

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your AWS-Solution-Architect-Associate Exam with Our Prep Materials Via below:**

<https://www.certleader.com/AWS-Solution-Architect-Associate-dumps.html>