



Amazon-Web-Services

Exam Questions ANS-C01

AWS Certified Advanced Networking Specialty Exam

About Exambible

Your Partner of IT Exam

Found in 1998

Exambible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, Exambible has its unique advantages that other companies could not achieve.

Our Advances

* 99.9% Uptime

All examinations will be up to date.

* 24/7 Quality Support

We will provide service round the clock.

* 100% Pass Rate

Our guarantee that you will pass the exam.

* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

NEW QUESTION 1

A company has deployed Amazon EC2 instances in private subnets in a VPC. The EC2 instances must initiate any requests that leave the VPC, including requests to the company's on-premises data center over an AWS Direct Connect connection. No resources outside the VPC can be allowed to open communications directly to the EC2 instances.

The on-premises data center's customer gateway is configured with a stateful firewall device that filters for incoming and outgoing requests to and from multiple VPCs. In addition, the company wants to use a single IP match rule to allow all the communications from the EC2 instances to its data center from a single IP address.

Which solution will meet these requirements with the LEAST amount of operational overhead?

- A. Create a VPN connection over the Direct Connect connection by using the on-premises firewall
- B. Use the firewall to block all traffic from on premises to AWS
- C. Allow a stateful connection from the EC2 instances to initiate the requests.
- D. Configure the on-premises firewall to filter all requests from the on-premises network to the EC2 instance
- E. Allow a stateful connection if the EC2 instances in the VPC initiate the traffic.
- F. Deploy a NAT gateway into a private subnet in the VPC where the EC2 instances are deployed
- G. Specify the NAT gateway type as private
- H. Configure the on-premises firewall to allow connections from the IP address that is assigned to the NAT gateway.
- I. Deploy a NAT instance into a private subnet in the VPC where the EC2 instances are deployed. Configure the on-premises firewall to allow connections from the IP address that is assigned to the NAT instance.

Answer: C

NEW QUESTION 2

A network engineer needs to standardize a company's approach to centralizing and managing interface VPC endpoints for private communication with AWS services. The company uses AWS Transit Gateway for inter-VPC connectivity between AWS accounts through a hub-and-spoke model. The company's network services team must manage all Amazon Route 53 zones and interface endpoints within a shared services AWS account. The company wants to use this centralized model to provide AWS resources with access to AWS Key Management Service (AWS KMS) without sending traffic over the public internet.

What should the network engineer do to meet these requirements?

- A. In the shared services account, create an interface endpoint for AWS KMS
- B. Modify the interface endpoint by disabling the private DNS name
- C. Create a private hosted zone in the shared services account with an alias record that points to the interface endpoint
- D. Associate the private hosted zone with the spoke VPCs in each AWS account.
- E. In the shared services account, create an interface endpoint for AWS KMS
- F. Modify the interface endpoint by disabling the private DNS name
- G. Create a private hosted zone in each spoke AWS account with an alias record that points to the interface endpoint
- H. Associate each private hosted zone with the shared services AWS account.
- I. In each spoke AWS account, create an interface endpoint for AWS KMS
- J. Modify each interface endpoint by disabling the private DNS name
- K. Create a private hosted zone in each spoke AWS account with an alias record that points to each interface endpoint
- L. Associate each private hosted zone with the shared services AWS account.
- M. In each spoke AWS account, create an interface endpoint for AWS KMS
- N. Modify each interface endpoint by disabling the private DNS name
- O. Create a private hosted zone in the shared services account with an alias record that points to each interface endpoint
- P. Associate the private hosted zone with the spoke VPCs in each AWS account.

Answer: A

NEW QUESTION 3

A company is planning to use Amazon S3 to archive financial data. The data is currently stored in an on-premises data center. The company uses AWS Direct Connect with a Direct Connect gateway and a transit gateway to connect to the on-premises data center. The data cannot be transported over the public internet and must be encrypted in transit.

Which solution will meet these requirements?

- A. Create a Direct Connect public VIF
- B. Set up an IPsec VPN connection over the public VIF to access Amazon S3. Use HTTPS for communication.
- C. Create an IPsec VPN connection over the transit VIF
- D. Create a VPC and attach the VPC to the transit gateway
- E. In the VPC, provision an interface VPC endpoint for Amazon S3. Use HTTPS for communication.
- F. Create a VPC and attach the VPC to the transit gateway
- G. In the VPC, provision an interface VPC endpoint for Amazon S3. Use HTTPS for communication.
- H. Create a Direct Connect public VIF
- I. Set up an IPsec VPN connection over the public VIF to the transit gateway
- J. Create an attachment for Amazon S3. Use HTTPS for communication.

Answer: B

Explanation:

<https://docs.aws.amazon.com/vpn/latest/s2svpn/private-ip-dx.html>

An IPsec VPN connection over the transit VIF can encrypt traffic between the on-premises network and AWS without using public IP addresses or the internet. A VPC endpoint for Amazon S3 can enable private access to S3 buckets within the same region. HTTPS can provide additional encryption for communication.

NEW QUESTION 4

A company has an AWS Direct Connect connection between its on-premises data center in the United States (US) and workloads in the us-east-1 Region. The connection uses a transit VIF to connect the data center to a transit gateway in us-east-1.

The company is opening a new office in Europe with a new on-premises data center in England. A Direct Connect connection will connect the new data center with some workloads that are running in a single VPC in the eu-west-2 Region. The company needs to connect the US data center and us-east-1 with the Europe data center and eu-west-2. A network engineer must establish full connectivity between the data centers and Regions with the lowest possible latency.

How should the network engineer design the network architecture to meet these requirements?

- A. Connect the VPC in eu-west-2 with the Europe data center by using a Direct Connect gateway and a private VIF
- B. Associate the transit gateway in us-east-1 with the same Direct Connect gateway
- C. Enable SiteLink for the transit VIF and the private VIF.
- D. Connect the VPC in eu-west-2 to a new transit gateway
- E. Connect the Europe data center to the new transit gateway by using a Direct Connect gateway and a new transit VIF
- F. Associate the transit gateway in us-east-1 with the same Direct Connect gateway
- G. Enable SiteLink for both transit VIF
- H. Peer the two transit gateways.
- I. Connect the VPC in eu-west-2 to a new transit gateway
- J. Connect the Europe data center to the new transit gateway by using a Direct Connect gateway and a new transit VIF
- K. Create a new Direct Connect gateway
- L. Associate the transit gateway in us-east-1 with the new Direct Connect gateway
- M. Enable SiteLink for both transit VIF
- N. Peer the two transit gateways.
- O. Connect the VPC in eu-west-2 with the Europe data center by using a Direct Connect gateway and a private VIF
- P. Create a new Direct Connect gateway
- Q. Associate the transit gateway in us-east-1 with the new Direct Connect gateway
- R. Enable SiteLink for the transit VIF and the private VIF.

Answer: C

NEW QUESTION 5

A company has deployed a web application on AWS. The web application uses an Application Load Balancer (ALB) across multiple Availability Zones. The targets of the ALB are AWS Lambda functions. The web application also uses Amazon CloudWatch metrics for monitoring.

Users report that parts of the web application are not loading properly. A network engineer needs to troubleshoot the problem. The network engineer enables access logging for the ALB.

What should the network engineer do next to determine which errors the ALB is receiving?

- A. Send the logs to Amazon CloudWatch Log
- B. Review the ALB logs in CloudWatch Insights to determine which error messages the ALB is receiving.
- C. Configure the Amazon S3 bucket destination
- D. Use Amazon Athena to determine which error messages the ALB is receiving.
- E. Configure the Amazon S3 bucket destination
- F. After Amazon CloudWatch Logs pulls the ALB logs from the S3 bucket automatically, review the logs in CloudWatch Logs to determine which error messages the ALB is receiving.
- G. Send the logs to Amazon CloudWatch Log
- H. Use the Amazon Athena CloudWatch Connector to determine which error messages the ALB is receiving.

Answer: B

Explanation:

Access logs is an optional feature of Elastic Load Balancing that is disabled by default. After you enable access logs for your load balancer, Elastic Load Balancing captures the logs and stores them in the Amazon S3 bucket that you specify as compressed files. You can disable access logs at any time. <https://docs.aws.amazon.com/elasticloadbalancing/latest/application/load-balancer-access-logs.html>

NEW QUESTION 6

A real estate company is building an internal application so that real estate agents can upload photos and videos of various properties. The application will store these photos and videos in an Amazon S3 bucket as objects and will use Amazon DynamoDB to store corresponding metadata. The S3 bucket will be configured to publish all PUT events for new object uploads to an Amazon Simple Queue Service (Amazon SQS) queue.

A compute cluster of Amazon EC2 instances will poll the SQS queue to find out about newly uploaded objects. The cluster will retrieve new objects, perform proprietary image and video recognition and classification update metadata in DynamoDB and replace the objects with new watermarked objects. The company does not want public IP addresses on the EC2 instances.

Which networking design solution will meet these requirements MOST cost-effectively as application usage increases?

- A. Place the EC2 instances in a public subnet
- B. Disable the Auto-assign Public IP option while launching the EC2 instance
- C. Create an internet gateway
- D. Attach the internet gateway to the VPC
- E. In the public subnet's route table, add a default route that points to the internet gateway.
- F. Place the EC2 instances in a private subnet
- G. Create a NAT gateway in a public subnet in the same Availability Zone
- H. Create an internet gateway
- I. Attach the internet gateway to the VPC
- J. In the public subnet's route table, add a default route that points to the internet gateway
- K. Place the EC2 instances in a private subnet
- L. Create an interface VPC endpoint for Amazon SQS
- M. Create gateway VPC endpoints for Amazon S3 and DynamoDB.
- N. Place the EC2 instances in a private subnet
- O. Create a gateway VPC endpoint for Amazon SQS. Create interface VPC endpoints for Amazon S3 and DynamoDB.

Answer: C

NEW QUESTION 7

A software-as-a-service (SaaS) provider hosts its solution on Amazon EC2 instances within a VPC in the AWS Cloud. All of the provider's customers also have their environments in the AWS Cloud.

A recent design meeting revealed that the customers have IP address overlap with the provider's AWS deployment. The customers have stated that they will not share their internal IP addresses and that they do not want to connect to the provider's SaaS service over the internet.

Which combination of steps is part of a solution that meets these requirements? (Choose two.)

- A. Deploy the SaaS service endpoint behind a Network Load Balancer.
- B. Configure an endpoint service, and grant the customers permission to create a connection to the endpoint service.
- C. Deploy the SaaS service endpoint behind an Application Load Balancer.
- D. Configure a VPC peering connection to the customer VPC
- E. Route traffic through NAT gateways.
- F. Deploy an AWS Transit Gateway, and connect the SaaS VPC to it
- G. Share the transit gateway with the customer
- H. Configure routing on the transit gateway.

Answer: AB

Explanation:

NLB for creating the private link which solves the overlapping IP address issue and the SaaS service endpoint behind it. (the SaaS endpoint could be an ALB)
<https://aws.amazon.com/about-aws/whats-new/2021/09/application-load-balancer-aws-privatelink-static-ip>

NEW QUESTION 8

Your company runs an application for the US market in the us-east-1 AWS region. This application uses proprietary TCP and UDP protocols on Amazon Elastic Compute Cloud (EC2) instances. End users run a real-time, front-end application on their local PCs. This front-end application knows the DNS hostname of the service. You must prepare the system for global expansion. The end users must access the application with lowest latency. How should you use AWS services to meet these requirements?

- A. Register the IP addresses of the service hosts as “A” records with latency-based routing policy in Amazon Route 53, and set a Route 53 health check for these hosts.
- B. Set the Elastic Load Balancing (ELB) load balancer in front of the hosts of the service, and register the ELB name of the main service host as an ALIAS record with a latency-based routing policy in Route 53.
- C. Set Amazon CloudFront in front of the host of the service, and register the CloudFront name of the main service as an ALIAS record in Route 53.
- D. Set the Amazon API gateway in front of the service, and register the API gateway name of the main service as an ALIAS record in Route 53.

Answer: B

NEW QUESTION 9

A customer has set up multiple VPCs for Dev, Test, Prod, and Management. You need to set up AWS Direct Connect to enable data flow from on-premises to each VPC. The customer has monitoring software running in the Management VPC that collects metrics from the instances in all the other VPCs. Due to budget requirements, data transfer charges should be kept at minimum. Which design should be recommended?

- A. Create a total of four private VIFs, one for each VPC owned by the customer, and route traffic between VPCs using the Direct Connect link.
- B. Create a private VIF to the Management VPC, and peer this VPC to all other VPCs.
- C. Create a private VIF to the Management VPC, and peer this VPC to all other VPCs, enable source/destination NAT in the Management VPC.
- D. Create a total of four private VIFs, and enable VPC peering between all VPCs.

Answer: D

Explanation:

- creating VPC peering is free of charge - traffic costs ~0.01€/GB for VPC peering (IN + OUT) and ~0.02€/GB for direct connect (OUT only). As the communication involved in monitoring will never have IN == OUT, then $0.01 * (IN + OUT)$ will always be lower than $0.02 * OUT$, ergo VPC peering will be cheaper

NEW QUESTION 10

A global company runs business applications in the us-east-1 Region inside a VPC. One of the company's regional offices in London uses a virtual private gateway for an AWS Site-to-Site VPN connection to the VPC. The company has configured a transit gateway and has set up peering between the VPC and other VPCs that various departments in the company use.

Employees at the London office are experiencing latency issues when they connect to the business applications.

What should a network engineer do to reduce this latency?

- A. Create a new Site-to-Site VPN connection
- B. Set the transit gateway as the target gateway
- C. Enable acceleration on the new Site-to-Site VPN connection
- D. Update the VPN device in the London office with the new connection details.
- E. Modify the existing Site-to-Site VPN connection by setting the transit gateway as the target gateway. Enable acceleration on the existing Site-to-Site VPN connection.
- F. Create a new transit gateway in the eu-west-2 (London) Region
- G. Peer the new transit gateway with the existing transit gateway
- H. Modify the existing Site-to-Site VPN connection by setting the new transit gateway as the target gateway.
- I. Create a new AWS Global Accelerator standard accelerator that has an endpoint of the Site-to-Site VPN connection
- J. Update the VPN device in the London office with the new connection details.

Answer: A

Explanation:

Enabling acceleration for a Site-to-Site VPN connection uses AWS Global Accelerator to route traffic from the on-premises network to an AWS edge location that is closest to the customer gateway device¹. AWS Global Accelerator optimizes the network path, using the congestion-free AWS global network to route traffic to the endpoint that provides the best application performance². Setting the transit gateway as the target gateway enables connectivity between the on-premises network and multiple VPCs that are attached to the transit gateway³.

NEW QUESTION 10

An AWS CloudFormation template is being used to create a VPC peering connection between two existing operational VPCs, each belonging to a different AWS account. All necessary components in the 'Remote' (receiving) account are already in place.

The template below creates the VPC peering connection in the Originating account. It contains these components:

AWSTemplateFormation Version: 2010-09-09 Parameters:

Originating VPCId: Type: String RemoteVPCId: Type: String

RemoteVPCAccountId: Type: String Resources:

newVPCPeeringConnection:

Type: 'AWS::EC2::VPCPeeringConnection'

Properties:

VpcId: !Ref OriginatingVPCId PeerVpcId: !Ref RemoteVPCId PeerOwnerId: !Ref RemoteVPCAccountId

Which additional AWS CloudFormation components are necessary in the Originating account to create an operational cross-account VPC peering connection with AWS CloudFormation? (Select two.)

A. Resources:NewEC2SecurityGroup:Type: AWS::EC2::SecurityGroup

B. Resources:NetworkInterfaceToRemoteVPC:Type: "AWS::EC2NetworkInterface"

C. Resources:newEC2Route:Type: AWS::EC2::Route

D. Resources:VPCGatewayToRemoteVPC:Type: "AWS::EC2::VPCGatewayAttachment"

E. Resources:newVPCPeeringConnection:Type: 'AWS::EC2VPCPeeringConnection'PeerRoleArn: !Ref PeerRoleArn

Answer: CE

Explanation:

https://docs.aws.amazon.com/AWSCloudFormation/latest/UserGuide/AWS_EC2.html

NEW QUESTION 14

A company is deploying a non-web application on an AWS load balancer. All targets are servers located on-premises that can be accessed by using AWS Direct Connect. The company wants to ensure that the source IP addresses of clients connecting to the application are passed all the way to the end server.

How can this requirement be achieved?

A. Use a Network Load Balancer to automatically preserve the source IP address.

B. Use a Network Load Balancer and enable the X-Forwarded-For attribute.

C. Use a Network Load Balancer and enable the ProxyProtocol v2 attribute.

D. Use an Application Load Balancer to automatically preserve the source IP address in the X-Forwarded-For header.

Answer: C

Explanation:

<https://docs.aws.amazon.com/elasticloadbalancing/latest/network/load-balancer-target-groups.html#proxy-protocol>

NEW QUESTION 18

A company has a hybrid cloud environment. The company's data center is connected to the AWS Cloud by an AWS Direct Connect connection. The AWS environment includes VPCs that are connected together in a hub-and-spoke model by a transit gateway. The AWS environment has a transit VIF with a Direct Connect gateway for on-premises connectivity.

The company has a hybrid DNS model. The company has configured Amazon Route 53 Resolver endpoints in the hub VPC to allow bidirectional DNS traffic flow. The company is running a backend application in one of the VPCs.

The company uses a message-oriented architecture and employs Amazon Simple Queue Service (Amazon SQS) to receive messages from other applications over a private network. A network engineer wants to use an interface VPC endpoint for Amazon SQS for this architecture. Client services must be able to access the endpoint service from on premises and from multiple VPCs within the company's AWS infrastructure.

Which combination of steps should the network engineer take to ensure that the client applications can resolve DNS for the interface endpoint? (Choose three.)

A. Create the interface endpoint for Amazon SQS with the option for private DNS names turned on.

B. Create the interface endpoint for Amazon SQS with the option for private DNS names turned off.

C. Manually create a private hosted zone for sqs.us-east-1.amazonaws.co

D. Add necessary records that point to the interface endpoint

E. Associate the private hosted zones with other VPCs.

F. Use the automatically created private hosted zone for sqs.us-east-1.amazonaws.com with previously created necessary records that point to the interface endpoint

G. Associate the private hosted zones with other VPCs.

H. Access the SQS endpoint by using the public DNS name sqs.us-east-1.amazonaws.com in VPCs and on premises.

I. Access the SQS endpoint by using the private DNS name of the interface endpoint.sqs.us-east-1.vpce.amazonaws.com in VPCs and on premises.

Answer: ADF

NEW QUESTION 23

A banking company is successfully operating its public mobile banking stack on AWS. The mobile banking stack is deployed in a VPC that includes private subnets and public subnets. The company is using IPv4 networking and has not deployed or supported IPv6 in the environment. The company has decided to adopt a third-party service provider's API and must integrate the API with the existing environment. The service provider's API requires the use of IPv6.

A network engineer must turn on IPv6 connectivity for the existing workload that is deployed in a private subnet. The company does not want to permit IPv6 traffic from the public internet and mandates that the company's servers must initiate all IPv6 connectivity. The network engineer turns on IPv6 in the VPC and in the private subnets.

Which solution will meet these requirements?

A. Create an internet gateway and a NAT gateway in the VP

B. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT gateway.

C. Create an internet gateway and a NAT instance in the VP

D. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT instance.

E. Create an egress-only Internet gateway in the VPAdd a route to the existing subnet route tables to point IPv6 traffic to the egress-only internet gateway.

F. Create an egress-only internet gateway in the VP

G. Configure a security group that denies all inbound traffic

H. Associate the security group with the egress-only internet gateway.

Answer: C

NEW QUESTION 28

A company's network engineer is designing an active-passive connection to AWS from two on-premises data centers. The company has set up AWS Direct Connect connections between the on-premises data centers and AWS. From each location, the company is using a transit VIF that connects to a Direct Connect gateway that is associated with a transit gateway.

The network engineer must ensure that traffic from AWS to the data centers is routed first to the primary data center. The traffic should be routed to the failover data center only in the case of an outage.

Which solution will meet these requirements?

- A. Set the BGP community tag for all prefixes from the primary data center to 7224:7100. Set the BGP community tag for all prefixes from the failover data center to 7224:7300
- B. Set the BGP community tag for all prefixes from the primary data center to 7224:7300. Set the BGP community tag for all prefixes from the failover data center to 7224:7100
- C. Set the BGP community tag for all prefixes from the primary data center to 7224:9300. Set the BGP community tag for all prefixes from the failover data center to 7224:9100
- D. Set the BGP community tag for all prefixes from the primary data center to 7224:9100. Set the BGP community tag for all prefixes from the failover data center to 7224:9300

Answer: B

NEW QUESTION 29

A company has been using an outdated application layer protocol for communication among applications. The company decides not to use this protocol anymore and must migrate all applications to support a new protocol. The old protocol and the new protocol are TCP-based, but the protocols use different port numbers. After several months of work, the company has migrated dozens of applications that run on Amazon EC2 instances and in containers. The company believes that all the applications have been migrated, but the company wants to verify this belief. A network engineer needs to verify that no application is still using the old protocol.

Which solution will meet these requirements without causing any downtime?

- A. Use Amazon Inspector and its Network Reachability rules packag
- B. Wait until the analysis has finished running to find out which EC2 instances are still listening to the old port.
- C. Enable Amazon GuardDut
- D. Use the graphical visualizations to filter for traffic that uses the port of the old protoco
- E. Exclude all internet traffic to filter out occasions when the same port is used as an ephemeral port.
- F. Configure VPC flow logs to be delivered into an Amazon S3 bucke
- G. Use Amazon Athena to query the data and to filter for the port number that is used by the old protocol.
- H. Inspect all security groups that are assigned to the EC2 instances that host the application
- I. Remove the port of the old protocol if that port is in the list of allowed port
- J. Verify that the applications are operating properly after the port is removed from the security groups.

Answer: C

Explanation:

Configuring VPC flow logs to be delivered into an Amazon S3 bucket would enable capture of information about the IP traffic going to and from network interfaces within the VPC3. Using Amazon Athena to query the data and to filter for the port number that is used by the old protocol would enable identification of applications that are still using the old protocol.

NEW QUESTION 33

A company uses a 4 Gbps AWS Direct Connect dedicated connection with a link aggregation group (LAG) bundle to connect to five VPCs that are deployed in the us-east-1 Region. Each VPC serves a different business unit and uses its own private VIF for connectivity to the on-premises environment. Users are reporting slowness when they access resources that are hosted on AWS.

A network engineer finds that there are sudden increases in throughput and that the Direct Connect connection becomes saturated at the same time for about an hour each business day. The company wants to know which business unit is causing the sudden increase in throughput. The network engineer must find out this information and implement a solution to resolve the problem.

Which solution will meet these requirements?

- A. Review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observe
- B. Create a new 10 Gbps dedicated connectio
- C. Shift traffic from the existing dedicated connection to the new dedicated connection.
- D. Review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observe
- E. Upgrade the bandwidth of the existing dedicated connection to 10 Gbps.
- F. Review the Amazon CloudWatch metrics for ConnectionBpsIngress and ConnectionPpsEgress to determine which VIF is sending the highest throughput during the period in which slowness is observe
- G. Upgrade the existing dedicated connection to a 5 Gbps hosted connection.
- H. Review the Amazon CloudWatch metrics for ConnectionBpsIngress and ConnectionPpsEgress to determine which VIF is sending the highest throughput during the period in which slowness is observed.Create a new 10 Gbps dedicated connectio
- I. Shift traffic from the existing dedicated connection to the new dedicated connection.

Answer: A

Explanation:

To meet the requirements of finding out which business unit is causing the sudden increase in throughput and resolving the problem, the network engineer should review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observed (Option B). After identifying the VIF that is causing the issue, they can upgrade the bandwidth of the existing dedicated connection to 10 Gbps to resolve the problem (Option B).

NEW QUESTION 37

A company wants to improve visibility into its AWS environment. The AWS environment consists of multiple VPCs that are connected to a transit gateway. The transit gateway connects to an on-premises data center through an AWS Direct Connect gateway and a pair of redundant Direct Connect connections that use transit VIFs. The company must receive notification each time a new route is advertised to AWS from on premises over Direct Connect. What should a network engineer do to meet these requirements?

- A. Enable Amazon CloudWatch metrics on Direct Connect to track the received route
- B. Configure a CloudWatch alarm to send notifications when routes change.
- C. Onboard Transit Gateway Network Manager to Amazon CloudWatch Logs Insight
- D. Use Amazon EventBridge (Amazon CloudWatch Events) to send notifications when routes change.
- E. Configure an AWS Lambda function to periodically check the routes on the Direct Connect gateway and to send notifications when routes change.
- F. Enable Amazon CloudWatch Logs on the transit VIFs to track the received route
- G. Create a metric filter Set an alarm on the filter to send notifications when routes change.

Answer: B

Explanation:

<https://docs.aws.amazon.com/network-manager/latest/cloudwan/cloudwan-cloudwatch-events.html>

To receive notification each time a new route is advertised to AWS from on premises over Direct Connect, a network engineer should onboard Transit Gateway Network Manager to Amazon CloudWatch Logs Insights and use Amazon EventBridge (Amazon CloudWatch Events) to send notifications when routes change (Option B). This solution allows for real-time monitoring of route changes and automatic notification when new routes are advertised.

NEW QUESTION 39

A company has multiple AWS accounts. Each account contains one or more VPCs. A new security guideline requires the inspection of all traffic between VPCs. The company has deployed a transit gateway that provides connectivity between all VPCs. The company also has deployed a shared services VPC with Amazon EC2 instances that include IDS services for stateful inspection. The EC2 instances are deployed across three Availability Zones. The company has set up VPC associations and routing on the transit gateway. The company has migrated a few test VPCs to the new solution for traffic inspection. Soon after the configuration of routing, the company receives reports of intermittent connections for traffic that crosses Availability Zones. What should a network engineer do to resolve this issue?

- A. Modify the transit gateway VPC attachment on the shared services VPC by enabling cross-Availability Zone load balancing.
- B. Modify the transit gateway VPC attachment on the shared services VPC by enabling appliance mode support.
- C. Modify the transit gateway by selecting VPN equal-cost multi-path (ECMP) routing support.
- D. Modify the transit gateway by selecting multicast support.

Answer: B

Explanation:

To resolve the issue of intermittent connections for traffic that crosses Availability Zones after configuring routing for traffic inspection between VPCs using a transit gateway and EC2 instances with IDS services in a shared services VPC, a network engineer should modify the transit gateway VPC attachment on the shared services VPC by enabling appliance mode support (Option B). This will ensure that traffic is routed to the same EC2 instance for stateful inspection and prevent intermittent connections.

NEW QUESTION 42

A company is hosting an application on Amazon EC2 instances behind a Network Load Balancer (NLB). A solutions architect added EC2 instances in a second Availability Zone to improve the availability of the application. The solutions architect added the instances to the NLB target group. The company's operations team notices that traffic is being routed only to the instances in the first Availability Zone. What is the MOST operationally efficient solution to resolve this issue?

- A. Enable the new Availability Zone on the NLB
- B. Create a new NLB for the instances in the second Availability Zone
- C. Enable proxy protocol on the NLB
- D. Create a new target group with the instances in both Availability Zones

Answer: A

Explanation:

When adding instances in a new Availability Zone to an existing Network Load Balancer (NLB), it is important to ensure that the new Availability Zone is enabled on the NLB. This will allow traffic to be routed to instances in both Availability Zones. This can be done by editing the settings of the NLB and selecting the new Availability Zone from the list of available zones.

NEW QUESTION 43

A company recently migrated its Amazon EC2 instances to VPC private subnets to satisfy a security compliance requirement. The EC2 instances now use a NAT gateway for internet access. After the migration, some long-running database queries from private EC2 instances to a publicly accessible third-party database no longer receive responses. The database query logs reveal that the queries successfully completed after 7 minutes but that the client EC2 instances never received the response. Which configuration change should a network engineer implement to resolve this issue?

- A. Configure the NAT gateway timeout to allow connections for up to 600 seconds.
- B. Enable enhanced networking on the client EC2 instances.
- C. Enable TCP keepalive on the client EC2 instances with a value of less than 300 seconds.
- D. Close idle TCP connections through the NAT gateway.

Answer: C

Explanation:

When a TCP connection is idle for a long time, it may be terminated by network devices, including the NAT gateway. By enabling TCP keepalive, the client EC2 instances can periodically send packets to the third-party database to indicate that the connection is still active, preventing it from being terminated prematurely.

NEW QUESTION 44

A retail company is running its service on AWS. The company's architecture includes Application Load Balancers (ALBs) in public subnets. The ALB target groups are configured to send traffic to backend Amazon EC2 instances in private subnets. These backend EC2 instances can call externally hosted services over the internet by using a NAT gateway.

The company has noticed in its billing that NAT gateway usage has increased significantly. A network engineer needs to find out the source of this increased usage.

Which options can the network engineer use to investigate the traffic through the NAT gateway? (Choose two.)

- A. Enable VPC flow logs on the NAT gateway's elastic network interface
- B. Publish the logs to a log group in Amazon CloudWatch Log
- C. Use CloudWatch Logs Insights to query and analyze the logs.
- D. Enable NAT gateway access log
- E. Publish the logs to a log group in Amazon CloudWatch Log
- F. Use CloudWatch Logs Insights to query and analyze the logs.
- G. Configure Traffic Mirroring on the NAT gateway's elastic network interface
- H. Send the traffic to an additional EC2 instance
- I. Use tools such as tcpdump and Wireshark to query and analyze the mirrored traffic.
- J. Enable VPC flow logs on the NAT gateway's elastic network interface
- K. Publish the logs to an Amazon S3 bucket
- L. Create a custom table for the S3 bucket in Amazon Athena to describe the log structure
- M. Use Athena to query and analyze the logs.
- N. Enable NAT gateway access log
- O. Publish the logs to an Amazon S3 bucket
- P. Create a custom table for the S3 bucket in Amazon Athena to describe the log structure
- Q. Use Athena to query and analyze the logs.

Answer: AD

Explanation:

To investigate the increased usage of a NAT gateway in a VPC architecture with ALBs and backend EC2 instances, a network engineer can use the following options:

➤ Enable VPC flow logs on the NAT gateway's elastic network interface and publish the logs to a log group in Amazon CloudWatch Logs. Use CloudWatch Logs Insights to query and analyze the logs.

(Option A)

➤ Enable VPC flow logs on the NAT gateway's elastic network interface and publish the logs to an Amazon S3 bucket. Create a custom table for the S3 bucket in Amazon Athena to describe the log structure and use Athena to query and analyze the logs. (Option D)

These options allow for detailed analysis of traffic through the NAT gateway to identify the source of increased usage.

NEW QUESTION 49

An ecommerce company is hosting a web application on Amazon EC2 instances to handle continuously changing customer demand. The EC2 instances are part of an Auto Scaling group. The company wants to implement a solution to distribute traffic from customers to the EC2 instances. The company must encrypt all traffic at all stages between the customers and the application servers. No decryption at intermediate points is allowed.

Which solution will meet these requirements?

- A. Create an Application Load Balancer (ALB). Add an HTTPS listener to the ALB
- B. Configure the Auto Scaling group to register instances with the ALB's target group.
- C. Create an Amazon CloudFront distribution
- D. Configure the distribution with a custom SSL/TLS certificate
- E. Set the Auto Scaling group as the distribution's origin.
- F. Create a Network Load Balancer (NLB). Add a TCP listener to the NLB
- G. Configure the Auto Scaling group to register instances with the NLB's target group.
- H. Create a Gateway Load Balancer (GLB). Configure the Auto Scaling group to register instances with the GLB's target group.

Answer: C

Explanation:

To distribute traffic from customers to EC2 instances in an Auto Scaling group and encrypt all traffic at all stages between the customers and the application servers without decryption at intermediate points, the company should create a Network Load Balancer (NLB) with a TCP listener and configure the Auto Scaling group to register instances with the NLB's target group (Option C). This solution allows for end-to-end encryption of traffic without decryption at intermediate points.

NEW QUESTION 54

A company is migrating an existing application to a new AWS account. The company will deploy the application in a single AWS Region by using one VPC and multiple Availability Zones. The application will run on Amazon EC2 instances. Each Availability Zone will have several EC2 instances. The EC2 instances will be deployed in private subnets.

The company's clients will connect to the application by using a web browser with the HTTPS protocol. Inbound connections must be distributed across the Availability Zones and EC2 instances. All connections from the same client session must be connected to the same EC2 instance. The company must provide end-to-end encryption for all connections between the clients and the application by using the application SSL certificate.

Which solution will meet these requirements?

- A. Create a Network Load Balance
- B. Create a target group
- C. Set the protocol to TCP and the port to 443 for the target group
- D. Turn on session affinity (sticky sessions). Register the EC2 instances as target
- E. Create a listener
- F. Set the protocol to TCP and the port to 443 for the listener
- G. Deploy SSL certificates to the EC2 instances.
- H. Create an Application Load Balance
- I. Create a target group
- J. Set the protocol to HTTP and the port to 80 for the target group
- K. Turn on session affinity (sticky sessions) with an application-based cookie policy

- L. Register the EC2 instances as target
- M. Create an HTTPS listener
- N. Set the default action to forward to the target group
- O. Use AWS Certificate Manager (ACM) to create a certificate for the listener.
- P. Create a Network Load Balance
- Q. Create a target group
- R. Set the protocol to TLS and the port to 443 for the target group
- S. Turn on session affinity (sticky sessions). Register the EC2 instances as target
- T. Create a listener
 - . Set the protocol to TLS and the port to 443 for the listener
 - . Use AWS Certificate Manager (ACM) to create a certificate for the application.
 - . Create an Application Load Balance
 - . Create a target group
 - . Set the protocol to HTTPS and the port to 443 for the target group
 - . Turn on session affinity (sticky sessions) with an application-based cookie policy
 - . Register the EC2 instances as target
 - . Create an HTTP listener
 - . Set the port to 443 for the listener
 - . Set the default action to forward to the target group.

Answer: A

NEW QUESTION 55

.....

Relate Links

100% Pass Your ANS-C01 Exam with ExamBible Prep Materials

<https://www.exambible.com/ANS-C01-exam/>

Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>