

Exam Questions 350-801

Implementing and Operating Cisco Collaboration Core Technologies

<https://www.2passeasy.com/dumps/350-801/>



NEW QUESTION 1

A Cisco Unity Connection Administrator must set a voice mailbox so that it can be accessed from a secondary device. Which configuration on the voice mailbox makes this change?

- A. Attempt Forward routing rule
- B. Alternate Extensions
- C. Alternate Names
- D. Mobile User

Answer: A

NEW QUESTION 2

An engineer with troubleshoots poor voice quality on multiple calls. After looking at packet captures, the engineer notices high levels of jitter. Which two areas does the engineer check to prevent jitter? (Choose two.)

- A. The network meets bandwidth requirements.
- B. MTP is enabled on the SIP trunk to Cisco Unified Border Element.
- C. Cisco UBE manages voice traffic, not data traffic.
- D. All devices use wired connections instead of wireless connections.
- E. Voice packets are classified and marked.

Answer: AE

Explanation:

Reference: <https://www.cisco.com/c/en/us/support/docs/voice/voice-quality/20371-troubleshoot-qos-voice.html>

NEW QUESTION 3

Multiple route patterns match a number. How does Cisco Unified Communications Managers determine which pattern to use?

- A. the one that comes first in numerical order
- B. the one with the longest match
- C. the one with the closest match
- D. the one that discards everything PreDot

Answer: C

Explanation:

Reference: <https://www.cisco.com/c/en/us/support/docs/voice-unified-communications/unified-communications-manager-callmanager/13920-call-routing.html#bcr>

NEW QUESTION 4

An engineer must extend the corporate phone system to mobile users connecting through the internet with their own devices. One requirement is to keep that as simple as possible for end users. Which infrastructure element achieves these goals?

- A. Cisco Express Mobility
- B. Cisco Expressway-C and Expressway-E
- C. Cisco Unified Border Element
- D. Cisco Unified Instant Messaging and Presence

Answer: C

NEW QUESTION 5

Which issue causes slips on a PRI?

- A. incorrect clock source
- B. incorrect encapsulation
- C. incorrectly configured time zone
- D. change in the line code

Answer: A

NEW QUESTION 6

Calls are being delivered to the end user in the globalized format. Where does an engineer configure the calling number into a localized format?

- A. route pattern
- B. service parameters
- C. IP phone
- D. gateway

Answer: C

NEW QUESTION 7

An administrator recently upgraded a Cisco Webex DX80 through its web interface but discovered the next morning that the unit has received to its previous version. What must the administrator do to prevent this from happening again?

- A. Assign a phone security profile with secure SIP.
- B. Set the prepare cluster for rollback to pre-8-0 enterprise parameter to true.
- C. Confirm the phone load name in the phone configuration.
- D. Assign a universal device template to the phone.

Answer: C

NEW QUESTION 8

What field is configured to change the caller ID information on a SIP route pattern?

- A. Route Partition
- B. Called Party Transformation Mask
- C. Calling Party Transformation Mask
- D. Connected Line ID Presentation

Answer: D

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/admin/10_0_1/ccmcfg/CUCM_BK_C95ABA82_00_admin-guide-100/CUCM_BK_C95ABA82_00_admin-guide-100_chapter_0100111.pdf

NEW QUESTION 9

Where is the default for Maximum Session Bit Rate for a region configured?

- A. Service Parameter Configuration
- B. Enterprise Phone Configuration
- C. Enterprise Parameters Configuration
- D. Region Configuration

Answer: A

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/admin/9_1_1/ccmcfg/CUCM_BK_A34970C5_00_admin-guide-91/CUCM_BK_A34970C5_00_admin-guide-91_chapter_0111.html

NEW QUESTION 10

When a user dials a number with a phone that is registered to the Cisco Unified Communications Manager, what is the default timeout before the number is sent?

- A. 15 seconds
- B. 5 seconds
- C. 10 seconds
- D. 3 seconds

Answer: C

Explanation:

Reference: <https://www.cisco.com/c/en/us/support/docs/voice-unified-communications/unified-communications-manager-callmanager/13920-call-routing.html>

NEW QUESTION 10

Which protocols does Cisco IM and Presence use to authenticate Jabber?

- A. XMPP
- B. SOAP
- C. TCP
- D. LDAP
- E. QBE

Answer: AB

NEW QUESTION 11

How many DNS SRV entries can be defined in the SIP trunk destination address field in Cisco Unified Communications Manager?

- A. 1
- B. 8
- C. 16
- D. 4

Answer: C

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/admin/11_5_1/sysConfig/CUCM_BK_SE5DAF88_00_cucm-system-configuration-guide-1151/CUCM_BK_SE5DAF88_00_cucm-system-configuration-guide1151_chapter_01110.html

NEW QUESTION 12

A present redundancy group is deployed, and an engineer with ID012345678 initiates a manual fallback. Which statement about Cisco Server Recovery Manager is true?

- A. disconnects all users that had been failed over, and the users must log in again.
- B. disconnects all users that had been failed over
- C. restarts critical on the secondary node
- D. restarts the Cisco Presence Engine

Answer: B

NEW QUESTION 13

A collaboration engineer must configure Cisco Unified Border Element to support up to five concurrent outbound calls across an Ethernet link with a bandwidth of 160 kb to the Internet Telephony Service Provider. Which set of commands allows the engineer to complete the task without compromising voice quality?

- A. dial-peer voice 1 voip translation-profile outgoing Strip9 max-conn 5 destination-pattern 91[2-9]..[2-9].....\$session protocol sipv2 session target ipv4:142.45.10.1 dtmf-relay rtp-nte sip-notify sip-kpml
- B. dial-peer voice 1 voip translation-profile outgoing Strip9 max-conn 5 destination-pattern 91[2-9]..[2-9].....\$ session protocol sipv2 session target ipv4:142.45.10.1 dtmf-relay rtp-nte sip-notify sip-kpml codec ilbc mode 20
- C. dial-peer voice 1 voip translation-profile outgoing Strip9 max-conn 5 destination-pattern 91[2-9]..[2-9].....\$ session protocol sipv2 session target ipv4:142.45.10.1 dtmf-relay rtp-nte sip-notify sip-kpml codec aacld
- D. dial-peer voice 1 voip translation-profile outgoing Strip9 max-conn 5 destination-pattern 91[2-9]..[2-9].....\$ session protocol sipv2 session target ipv4:142.45.10.1 dtmf-relay rtp-nte sip-notify sip-kpml codec mp4a-latm

Answer: B

NEW QUESTION 18

A customer is deploying a SIP IOS gateway for a customer who requires that in-band DTMF relay is first priority and out-of-band DTMF relay is second priority. Which IOS entry sets the required priority?

- A. dtmf-relay rtp-nte sip-notify B.dtmf-relay cisco-rtp
- B. sip-notify dtmf-relay rtp-nte
- C. dtmf-relay sip-kpml cisco-rtp

Answer: A

NEW QUESTION 21

How does Cisco Unified Communications Manager perform a digit analysis on-hook versus off-hook for an outbound call from a Cisco IP phone that is registered to Cisco Unified CM?

- A. On-hook, Unified CM performs a digit-by-digit analysis, off-hook, Unified GM considers all digits were dialed and does not wait for additional digits.
- B. On-hook, Unified CM considers all digits were dialed and does not wait for additional digits, off-hook, Unified CM performs a digit-by-digit analysis.
- C. On-hook, by pressing the digits and entering "#" to process the call, Unified CM performs a digit-by-digit analysis; off-hoo
- D. Unified CM analyzes all digits as a string.
- E. On-hook, no digit analysis is performed, off-hoo
- F. Unified CM requires the "*" to start the digit analysis.

Answer: C

NEW QUESTION 22

A Cisco TelePresence SX80 suddenly has issues displaying main video to a display over HDMI. Which command can you use from the SX80 admin CLI to check the video output status to the monitor?

- A. xStatus Video Output
- B. xCommand Video Status
- C. xConfiguration Video Output
- D. xStatus HDMI Output

Answer: C

NEW QUESTION 24

You are adding regions in Cisco Unified Communications Manager. Which codec(s) are selected when a call is placed if you set up the max audio bit rate to use 8 kbps?

- A. G.729
- B. G 729 and G.711ulaw
- C. G.711ulaw and G 711alaw
- D. G.722

Answer: A

NEW QUESTION 26

An incoming off-net call to a user fails. An engineer notices that the off-net call is G.711, but the phone accepts only G.729. Which media resource on a Cisco Unified Border Element and Cisco Unified Communications Manager must the engineer configure to manage the codec negotiation?

- A. transcoder
- B. CFB
- C. MOH
- D. MTP

Answer: A

NEW QUESTION 28

Which transport protocol does the application layer protocol SNMP use?

- A. XML
- B. UDP
- C. SIP
- D. HTTP

Answer: B

Explanation:

Reference: <https://www.geeksforgeeks.org/simple-network-management-protocol-snmp/>

NEW QUESTION 33

Which protocol does Cisco Prime Collaboration Assurance use to poll the health status of different systems in the Collaboration environment?

- A. SIP
- B. SNMP
- C. SCCP
- D. SMTP

Answer: B

Explanation:

Reference: https://www.cisco.com/c/en/us/products/collateral/cloud-systems-management/prime-collaboration/guide-c07-736946.html#_Toc446633083

NEW QUESTION 35

When a remote office location is set up with limited bandwidth resources, which codec carries the most voice calls?

- A. G.711
- B. G.722
- C. G.723
- D. G.729

Answer: D

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/srnd/collab10/collab10/media.html

NEW QUESTION 36

Which two DNS records must be created to configure Service Discovery for or premises Jabber? (Choose two.)

- A. _cisco-uds._tls.cisco.com pointing to the IP address of Cisco Unified Communications Manager
- B. _cuplogin._tcp.cisco.com pointing to a record of IM&P
- C. _cuplogin._tls.cisco.com pointing to the IP address of IM&P
- D. _cisco-uds._tcp.cisco.com pointing to a record of Cisco Unified CM
- E. _xmpp._tls.cisco.com pointing to a record of IM&P

Answer: AB

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/jabber/Windows/9_7/CJAB_BK_C606D8A9_00_cisco-jabber-dns-configuration-guide/CJAB_BK_C606D8A9_00_cisco-jabber-dns-configuration-guide_chapter_010.html

NEW QUESTION 40

An engineer is designing a high availability and failover solution for two Cisco Unified Border Element routers. The first router (cube1.ab?.com) takes 60% of the calls and the second router (cube2.abc.com) takes 40% of the calls. Assume all DNS A records have been created. Which two SRV records are needed for a load balanced solution? (Choose two.)

- A. _sip._udp.abc.com 60 IN SRV 2 60 cube1.abc.com
- B. _sip._udp.abc.com 60 IN SRV 60 1 cube1.abc.com
- C. _sip._udp.abc.com 60 IN SRV 1 40 cube2.abc.com
- D. _sip._udp.abc.com 60 IN SRV 3 60 cube2.abc.com
- E. _sip._udp.abc.com 60 IN SRV 1 60 cube1.abc.com

Answer: CE

NEW QUESTION 42

Why would we not include an end user's PC device in a QoS trust boundary?

- A. The end user could incorrectly tag their traffic to bypass firewalls.
- B. The end user may incorrectly tag their traffic to be prioritized over other network traffic.
- C. There is no reason not to include an end user's PC device in a QoS trust boundary.
- D. The end user could incorrectly tag their traffic to advertise their PC as a default gateway.

Answer: B

NEW QUESTION 47

A DTMF mismatch is occurring between an MGCP gateway registered FXS port and a Cisco Unified Communications Manager SIP trunk. Which media resource can be leveraged to interwork this mismatch?

- A. Conference Bridge
- B. Trusted Relay Point
- C. Media Termination Point
- D. Annunciator

Answer: C

NEW QUESTION 49

Which packet delay is the maximum supported between Cisco Unified Communications Manager nodes for clustering over WAN deployments?

- A. 150 ms round trip
- B. 510 ms round trip
- C. 40 ms round trip
- D. 80 ms round trip

Answer: D

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/srnd/collab11/collab11/callpros.html

NEW QUESTION 52

Refer to the exhibit.

```
dial-peer voice 10 voip
  destination-pattern 1...
  session target ipv4:10.1.1.1
  no vad
```

An engineer configures a VoIP dial peer on a Cisco gateway. Which codec is used?

- A. G.711ulaw
- B. No codec is used (missing codec command).
- C. G.711alaw
- D. G.729r8

Answer: A

Explanation:

Reference: <https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/voice/dialpeer/configuration/15-mt/vd-15-mt-book/vd-dp-cfg-examp.pdf>

NEW QUESTION 56

Due to provider requirements, outgoing calls from the Enterprise to the PSTN must start with channel 1. Which ISDN command changes the channel selection an IOS to meet this requirement?

- A. isdn bchan-number-order decending
- B. isdn bchan-number-order ascending
- C. isdn protocol-emulate network
- D. isdn incoming-voice voice

Answer: B

NEW QUESTION 60

Which wildcard must an engineer configure to match a whole domain in SIP route patterns?

- A. .
- B. !
- C. @
- D. *

Answer: D

Explanation:

Reference: https://www.cisco.com/c/en/us/td/docs/voice_ip_comm/cucm/admin/10_0_1/ccmcf/CUCM_BK_C95ABA82_00_admin-guide-100/CUCM_BK_C95ABA82_00_admin-guide-100_chapter_0100111.html

NEW QUESTION 65

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 350-801 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 350-801 Product From:

<https://www.2passeasy.com/dumps/350-801/>

Money Back Guarantee

350-801 Practice Exam Features:

- * 350-801 Questions and Answers Updated Frequently
- * 350-801 Practice Questions Verified by Expert Senior Certified Staff
- * 350-801 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 350-801 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year