



**Oracle**

**Exam Questions 1z0-808**

Java SE 8 Programmer I

### NEW QUESTION 1

Given:

```
public static void main(String[] args) {
    String ta = "A ";
    ta = ta.concat("B ");
    String tb = "C ";
    ta = ta.concat(tb);
    ta.replace('C', 'D');
    ta = ta.concat(tb);
    System.out.println(ta);
}
```

What is the result?

- A. ABCD
- B. ACD
- C. ACDD
- D. ABD
- E. ABDC

**Answer: C**

### NEW QUESTION 2

Given the code fragment:

```
public static void main(String[] args) {
    int ans;
    try {
        int num = 10;
        int div = 0;
        ans = num / div;
    } catch (ArithmeticException ae) {
        ans = 0; // line n1
    } catch (Exception e) {
        System.out.println("Invalid calculation");
    }
    System.out.println("Answer = " + ans); // line n2
}
```

What is the result?

- A. Answer = 0
- B. Invalid calculation
- C. Compilation fails only at line n1.
- D. Compilation fails only at line n2.
- E. Compilation fails at line n1 and line2.

**Answer: C**

**Explanation:**

```
1
2 public class Test {
3     public static void main(String[] args) {
4         int ans;
5         try {
6             int num = 10;
7             int div = 0;
8             ans = num / div;
9         } catch (ArithmeticException ae) {
10            ans = 0;
11        } catch (Exception e) {
12            System.out.println("Invalid calculation");
13        }
14        System.out.println("Answer = " + ans); //line n2
15    }
16 }
17
```

✖ variable ans might not have been initialized

### NEW QUESTION 3

Given the code fragments:

Person.java:

```
public class Person {
    String name;
    int age;

    public Person(String n, int a) {
        name = n;
        age = a;
    }

    public String getName() {
        return name;
    }

    public int getAge() {
        return age;
    }
}
```

Test.java:

```
public static void checkAge(List<Person> list, Predicate<Person> predicate) {
    for (Person p : list) {
        if (predicate.test(p)) {
            System.out.println(p.name + " ");
        }
    }
}

public static void main(String[] args) {
    List<Person> iList = Arrays.asList(new Person("Hank", 45),
                                       new Person("Charlie", 40),
                                       new Person("Smith", 38));

    //line n1
}
```

Which code fragment, when inserted at line n1, enables the code to print Hank?

- A `checkAge (iList, ( ) -> p. get Age ( ) > 40);`
- B `checkAge(iList, Person p -> p.getAge( ) > 40);`
- C `checkAge (iList, p -> p.getAge ( ) > 40);`
- D `checkAge(iList, (Person p) -> { p.getAge() > 40; });`

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: C

#### NEW QUESTION 4

Given the code fragment:

```
public static void main (String[] args) {
    String[] arr = ("Hi", "How", "Are", "You");
    List<String> arrList = new ArrayList<>(Arrays.asList(arr));
    if (arrList.removeIf((String s) -> (return s.length() <= 2;))) {
        System.out.println(s + "removed")
    }
}
```

What is the result?

- A. Compilation fails.
- B. Hi removed
- C. An UnsupportedOperationException is thrown at runtime.
- D. The program compiles, but it prints nothing.

**Answer:** A

#### NEW QUESTION 5

Given the code fragment:

```
public static void main(String[] args) {
    int data[] = {2010, 2013, 2014, 2015, 2014};
    int key = 2014;
    int count = 0;
    for (int e: data) {
        if (e != key) {
            continue;
            count++;
        }
    }
    System.out.print(count + " Found");
}
```

What is the result?

- A. Compilation fails.
- B. 0 Found
- C. 1 Found
- D. 3 Found

**Answer:** A

#### NEW QUESTION 6

Which two class definitions fail to compile? (Choose two.)

A

```
abstract class A3 {
    private static int i;
    public void doStuff(){}
    public A3(){}
}
```

B

```
final class A1 {
    public A1(){}
}
```

C

```
private class A2 {
    private static int i;
    private A2(){}
}
```

D

```
class A4 {
    protected static final int i = 10;
    private A4() {}
}
```

E

```
final abstract class A5 {
    protected static int i;
    void doStuff(){}
    abstract void doIt();
}
```

A. Option A

- B. Option B
- C. Option C
- D. Option D
- E. Option E

**Answer:** CD

#### NEW QUESTION 7

Given the code fragment:

```
int n [] [] = {{1, 3}, {2, 4}};
for (int i = n.length-1; i >= 0; i--) {
    for (int y : n[i]) {
        System.out.print (y);
    }
}
```

What is the result?

- A. 1324
- B. 2313
- C. 3142
- D. 4231

**Answer:** D

#### NEW QUESTION 8

Given the code fragment:

```
public static void main(String[] args) {
    int ii = 0;
    int jj = 7;
    for (ii = 0; ii < jj - 1; ii = ii + 2) {
        System.out.print(ii + " ");
    }
}
```

What is the result?

- A. 2 4
- B. 0 2 4 6
- C. 0 2 4
- D. Compilation fails

**Answer:** C

#### NEW QUESTION 9

Given:

```
public class App {
    int count;
    public static void displayMsg() {
        System.out.println("Welcome Visit Count: " + count++); // line n1
    }
    public static void main(String[] args) {
        App.displayMsg();
        displayMsg(); // line n2
    }
}
```

What is the result?

- A. Welcome Visit Count:0Welcome Visit Count: 1
- B. Compilation fails at line n2.
- C. Compilation fails at line n1.
- D. Welcome Visit Count:0Welcome Visit Count: 0

**Answer:** C

**Explanation:**

```

1
2 public class App {
3     int count;
4     public static void displayMsg() {
5         System.out.println("Welcome Visit Count: " + count ++); //line n1
6     }
7     public static void main(String[] args) {
8         App.displayMsg();
9         displayMsg();
10    }
11 }
12

```

**NEW QUESTION 10**

Which two statements are true about Java byte code? (Choose two.)

- A. It can be serialized across network.
- B. It can run on any platform that has a Java compiler.
- C. It can run on any platform.
- D. It has ".java" extension.
- E. It can run on any platform that has the Java Runtime Environment.

**Answer: AE**

**NEW QUESTION 10**

Given the code fragment:

```

public static void main(String[] args) {
    LocalDate date = LocalDate.of(2012, 1, 30);
    date.plusDays(10);
    System.out.println(date);
}

```

What is the result?

- A. 2012-02-10 00:00
- B. 2012-01-30
- C. 2012-02-10
- D. A DateTimeException is thrown at runtime.

**Answer: B**

**Explanation:**

```

Main.java  saved
1 import java.time.LocalDate;
2 import java.time.Month;
3
4 public class Main {
5     public static void main(String[] args) {
6         LocalDate date = LocalDate.of(2012, 1, 30);
7         date.plusDays(10);
8         System.out.println(date);
9     }
10 }

```

```

java version "1.8.0_31"
Java(TM) SE Runtime Environment (build 1.8.0_31-b13)
Java HotSpot(TM) 64-Bit Server VM (build 25.31-b07, mixed mode)
> javac -classpath ./run_dir/junit-4.12.jar:./run_dir/hamcrest-core-1.3.jar:./run_dir/json-simple-1.1.1.jar -d . Main.java
> java -classpath ./run_dir/junit-4.12.jar:./run_dir/hamcrest-core-1.3.jar:./run_dir/json-simple-1.1.1.jar Main
2012-01-30

```

**NEW QUESTION 13**

Given the code fragment:

```
public class Employee {
    String name;
    boolean contract;
    double salary;
    Employee() {
        // line n1
    }
    public String toString(){
        return name + ":" + contract + ":" + salary;
    }
    public static void main(String[] args) {
        Employee e = new Employee();
        // line n2
        System.out.print(e);
    }
}
```

Which two modifications, when made independently, enable the code to print Joe:true: 100.0? (Choose two.)

- A) Replace line n2 with:  
e.name = "Joe";  
e.contract = true;  
e.salary = 100;
- B) Replace line n2 with:  
this.name = "Joe";  
this.contract = true;  
this.salary = 100;
- C) Replace line n1 with:  
this.name = new String("Joe");  
this.contract = new Boolean(true);  
this.salary = new Double(100);
- D) Replace line n1 with:  
name = "Joe";  
contract = TRUE;  
salary = 100.0f;
- E) Replace line n1 with:  
this("Joe", true, 100);

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

**Answer:** AC

#### NEW QUESTION 18

Given:

```
class A {
    public void test() {
        System.out.println("A ");
    }
}

class B extends A {
    public void test() {
        System.out.println("B ");
    }
}

public class C extends A {
    public void test() {
        System.out.println("C ");
    }
}

public static void main(String[] args) {
    A b1 = new A();
    A b2 = new C();
    A b3 = (B) b2;           //line n1
    b1 = (A) b2;           //line n2
    b1.test();
    b3.test();
}
}
```

What is the result?

- A. AB
- B. AC
- C. CC
- D. A ClassCastException is thrown only at line n1.
- E. A ClassCastException is thrown only at line n2.

**Answer:** D

#### NEW QUESTION 21

Which statement is true about Java byte code?

- A. It can run on any platform.
- B. It can run on any platform only if it was compiled for that platform.
- C. It can run on any platform that has the Java Runtime Environment.
- D. It can run on any platform that has a Java compiler.
- E. It can run on any platform only if that platform has both the Java Runtime Environment and a Java compiler.

**Answer:** D

#### Explanation:

Java bytecodes help make "write once, run anywhere" possible. You can compile your program into bytecodes on any platform that has a Java compiler. The bytecodes can then be run on any implementation of the Java VM. That means that as long as a computer has a Java VM, the same program written in the Java programming language can run on Windows 2000, a Solaris workstation, or on an iMac.

#### NEW QUESTION 22

Given:

Base.java:

```
class Base {
    public void test(){
        System.out.println("Base ");
    }
}
```

DerivedA.java:

```
class DerivedA extends Base {
    public void test(){
        System.out.println("DerivedA ");
    }
}
```

DerivedB.java:

```
class DerivedB extends DerivedA {
    public void test(){
        System.out.println("DerivedB ");
    }
    public static void main(String[] args) {
        Base b1 = new DerivedB();
        Base b2 = new DerivedA();
        Base b3 = new DerivedB();
        Base b4 = b3;
        b1 = (Base) b2;
        b1.test();
        b4.test();
    }
}
```

What is the result?

- A. BaseDerivedA
- B. BaseDerivedB
- C. DerivedBDerivedB
- D. DerivedBDerivedA
- E. A ClassCastException is thrown at runtime.

**Answer:** D

### NEW QUESTION 23

Given:

```
class Test {
    int a1;

    public static void doProduct(int a) {
        a = a * a;
    }

    public static void doString(String s) {
        s.concat(" " + s);
    }

    public static void main(String[] args) {
        Test item = new Test();
        item.a1 = 11;
        String sb = "Hello";
        Integer i = 10;
        doProduct(i);
        doString(sb);
        doProduct(item.a1);
        System.out.println(i + " " + sb + " " + item.a1);
    }
}
```

What is the result?

- A. 10 Hello Hello 11

- B. 10 Hello Hello 121
- C. 100 Hello 121
- D. 100 Hello Hello 121
- E. 10 Hello 11

**Answer: E**

#### NEW QUESTION 25

Given the code fragment:

```
public static void main(String[] args) {
    LocalDate date = LocalDate.of(2012, 1, 30);
    date.plusDays(10);
    System.out.println(date);
}
```

What is the result?

- A. 2012-02-10
- B. 2012-01-30
- C. 2012-02-10 00:00
- D. A DateTimeException is thrown at runtime.

**Answer: C**

#### NEW QUESTION 30

Given:

```
public class Triangle {
    static double area;
    int b = 2, h = 3;
    public static void main(String[] args) {
        double p, b, h; //line n1
        if (area == 0) {
            b = 3;
            h = 4;
            p = 0.5;
            area = p * b * h; //line n2
        }
        System.out.println("Area is " + area);
    }
}
```

What is the result?

- A. Area is 6.0
- B. Area is 3.0
- C. Compilation fails at line n1
- D. Compilation fails at line n2.

**Answer: D**

#### NEW QUESTION 34

Given this class:

```
public class Rectangle {
    private double length;
    private double height;
    private double area;

    public void setLength(double length) {
        this.length = length;
    }
    public void setHeight(double height) {
        this.height = height;
    }
    public void setArea() {
        area = length*height;
    }
}
```

Which two changes would encapsulate this class and ensure that the area field is always equal to length \* height whenever the Rectangle class is used?

- A. Call the setArea method at the end of the setHeight method.
- B. Call the setArea method at the beginning of the setHeight method.
- C. Call the setArea method at the end of the setLength method.
- D. Call the setArea method at the beginning of the setLength method.
- E. Change the setArea method to private.
- F. Change the area field to public.

**Answer:** AE

#### NEW QUESTION 38

Which statement is true about the switch statement?

- A. It must contain the default section.
- B. The break statement, at the end of each case block, is optional.
- C. Its case label literals can be changed at runtime.
- D. Its expression must evaluate to a collection of values.

**Answer:** B

#### NEW QUESTION 42

Which two statements are true? (Choose two.)

- A. Error class is unextendable.
- B. Error class is extendable.
- C. Error is a RuntimeException.
- D. Error is an Exception.
- E. Error is a Throwable.

**Answer:** BC

#### NEW QUESTION 45

Given the code fragment:

```
LocalDate date1 = LocalDate.now();
LocalDate date2 = LocalDate.of(6, 20, 2014 );
LocalDate date3 = LocalDate.parse("2014-06-20", DateTimeFormatter.ISO_DATE);
System.out.println("date1 = " + date1);
System.out.println("date2 = " + date2);
System.out.println("date3 = " + date3);
```

Assume that the system date is June 20, 2014. What is the result?

- A
  - date1 = 2014-06-20
  - date2 = 2014-06-20
  - date3 = 2014-06-20
- B
  - date1 = 06/20/2014
  - date2 = 2014-06-20
  - date3 = Jun 20, 2014
- C Compilation fails.
- D An exception is thrown at runtime.

- A. Option A
- B. Option B
- C. Option C
- D. Option D

**Answer:** A

#### NEW QUESTION 47

.....

## About ExamBible

### *Your Partner of IT Exam*

## Found in 1998

ExamBible is a company specialized on providing high quality IT exam practice study materials, especially Cisco CCNA, CCDA, CCNP, CCIE, Checkpoint CCSE, CompTIA A+, Network+ certification practice exams and so on. We guarantee that the candidates will not only pass any IT exam at the first attempt but also get profound understanding about the certificates they have got. There are so many alike companies in this industry, however, ExamBible has its unique advantages that other companies could not achieve.

## Our Advances

### \* 99.9% Uptime

All examinations will be up to date.

### \* 24/7 Quality Support

We will provide service round the clock.

### \* 100% Pass Rate

Our guarantee that you will pass the exam.

### \* Unique Gurantee

If you do not pass the exam at the first time, we will not only arrange FULL REFUND for you, but also provide you another exam of your claim, ABSOLUTELY FREE!

### NEW QUESTION 1

Given:

```
public static void main(String[] args) {
    String ta = "A ";
    ta = ta.concat("B ");
    String tb = "C ";
    ta = ta.concat(tb);
    ta.replace('C', 'D');
    ta = ta.concat(tb);
    System.out.println(ta);
}
```

What is the result?

- A. ABCD
- B. ACD
- C. ACDD
- D. ABD
- E. ABDC

**Answer: C**

### NEW QUESTION 2

Given the code fragment:

```
public static void main(String[] args) {
    int ans;
    try {
        int num = 10;
        int div = 0;
        ans = num / div;
    } catch (ArithmeticException ae) {
        ans = 0; // line n1
    } catch (Exception e) {
        System.out.println("Invalid calculation");
    }
    System.out.println("Answer = " + ans); // line n2
}
```

What is the result?

- A. Answer = 0
- B. Invalid calculation
- C. Compilation fails only at line n1.
- D. Compilation fails only at line n2.
- E. Compilation fails at line n1 and line2.

**Answer: C**

**Explanation:**

```
1
2 public class Test {
3     public static void main(String[] args) {
4         int ans;
5         try {
6             int num = 10;
7             int div = 0;
8             ans = num / div;
9         } catch (ArithmeticException ae) {
10            ans = 0;
11        } catch (Exception e) {
12            System.out.println("Invalid calculation");
13        }
14        System.out.println("Answer = " + ans); //line n2
15    }
16 }
17
```

✘ variable ans might not have been initialized

### NEW QUESTION 3

Given the code fragments:

Person.java:

```
public class Person {
    String name;
    int age;

    public Person(String n, int a) {
        name = n;
        age = a;
    }

    public String getName() {
        return name;
    }

    public int getAge() {
        return age;
    }
}
```

Test.java:

```
public static void checkAge(List<Person> list, Predicate<Person> predicate) {
    for (Person p : list) {
        if (predicate.test(p)) {
            System.out.println(p.name + " ");
        }
    }
}

public static void main(String[] args) {
    List<Person> iList = Arrays.asList(new Person("Hank", 45),
                                       new Person("Charlie", 40),
                                       new Person("Smith", 38));

    //line n1
}
```

Which code fragment, when inserted at line n1, enables the code to print Hank?

- A `checkAge (iList, ( ) -> p. get Age ( ) > 40);`
- B `checkAge(iList, Person p -> p.getAge( ) > 40);`
- C `checkAge (iList, p -> p.getAge ( ) > 40);`
- D `checkAge(iList, (Person p) -> { p.getAge() > 40; });`

- A. Option A
- B. Option B
- C. Option C
- D. Option D

**Answer: C**

#### NEW QUESTION 4

Given the code fragment:

```
public static void main (String[] args) {
    String[] arr = ("Hi", "How", "Are", "You");
    List<String> arrList = new ArrayList<>(Arrays.asList(arr));
    if (arrList.removeIf((String s) -> (return s.length() <= 2;))) {
        System.out.println(s + "removed")
    }
}
```

What is the result?

- A. Compilation fails.
- B. Hi removed
- C. An UnsupportedOperationException is thrown at runtime.
- D. The program compiles, but it prints nothing.

**Answer:** A

#### NEW QUESTION 5

Given the code fragment:

```
public static void main(String[] args) {
    int data[] = {2010, 2013, 2014, 2015, 2014};
    int key = 2014;
    int count = 0;
    for (int e: data) {
        if (e != key) {
            continue;
            count++;
        }
    }
    System.out.print(count + " Found");
}
```

What is the result?

- A. Compilation fails.
- B. 0 Found
- C. 1 Found
- D. 3 Found

**Answer:** A

#### NEW QUESTION 6

Which two class definitions fail to compile? (Choose two.)

A

```
abstract class A3 {
    private static int i;
    public void doStuff(){}
    public A3(){}
}
```

B

```
final class A1 {
    public A1(){}
}
```

C

```
private class A2 {
    private static int i;
    private A2(){}
}
```

D

```
class A4 {
    protected static final int i = 10;
    private A4() {}
}
```

E

```
final abstract class A5 {
    protected static int i;
    void doStuff(){}
    abstract void doIt();
}
```

A. Option A

- B. Option B
- C. Option C
- D. Option D
- E. Option E

**Answer:** CD

#### NEW QUESTION 7

Given the code fragment:

```
int n [] [] = {{1, 3}, {2, 4}};
for (int i = n.length-1; i >= 0; i--) {
    for (int y : n[i]) {
        System.out.print (y);
    }
}
```

What is the result?

- A. 1324
- B. 2313
- C. 3142
- D. 4231

**Answer:** D

#### NEW QUESTION 8

Given the code fragment:

```
public static void main(String[] args) {
    int ii = 0;
    int jj = 7;
    for (ii = 0; ii < jj - 1; ii = ii + 2) {
        System.out.print(ii + " ");
    }
}
```

What is the result?

- A. 2 4
- B. 0 2 4 6
- C. 0 2 4
- D. Compilation fails

**Answer:** C

#### NEW QUESTION 9

Given:

```
public class App {
    int count;
    public static void displayMsg() {
        System.out.println("Welcome Visit Count: " + count++); // line n1
    }
    public static void main(String[] args) {
        App.displayMsg();
        displayMsg(); // line n2
    }
}
```

What is the result?

- A. Welcome Visit Count:0Welcome Visit Count: 1
- B. Compilation fails at line n2.
- C. Compilation fails at line n1.
- D. Welcome Visit Count:0Welcome Visit Count: 0

**Answer:** C

**Explanation:**

```

1
2 public class App {
3     int count;
4     public static void displayMsg() {
5         System.out.println("Welcome Visit Count: " + count ++); //line n1
6     }
7     public static void main(String[] args) {
8         App.displayMsg();
9         displayMsg();
10    }
11 }
12

```

**NEW QUESTION 10**

Which two statements are true about Java byte code? (Choose two.)

- A. It can be serialized across network.
- B. It can run on any platform that has a Java compiler.
- C. It can run on any platform.
- D. It has ".java" extension.
- E. It can run on any platform that has the Java Runtime Environment.

**Answer: AE**

**NEW QUESTION 10**

Given the code fragment:

```

public static void main(String[] args) {
    LocalDate date = LocalDate.of(2012, 1, 30);
    date.plusDays(10);
    System.out.println(date);
}

```

What is the result?

- A. 2012-02-10 00:00
- B. 2012-01-30
- C. 2012-02-10
- D. A DateTimeException is thrown at runtime.

**Answer: B**

**Explanation:**

```

Main.java  saved
1 import java.time.LocalDate;
2 import java.time.Month;
3
4 public class Main {
5     public static void main(String[] args) {
6         LocalDate date = LocalDate.of(2012, 1, 30);
7         date.plusDays(10);
8         System.out.println(date);
9     }
10 }

```

```

java version "1.8.0_31"
Java(TM) SE Runtime Environment (build 1.8.0_31-b13)
Java HotSpot(TM) 64-Bit Server VM (build 25.31-b07, mixed mode)
> javac -classpath ./run_dir/junit-4.12.jar:./run_dir/hamcrest-core-1.3.jar:./run_dir/json-simple-1.1.1.jar -d . Main.java
> java -classpath ./run_dir/junit-4.12.jar:./run_dir/hamcrest-core-1.3.jar:./run_dir/json-simple-1.1.1.jar Main
2012-01-30

```

**NEW QUESTION 13**

Given the code fragment:

```
public class Employee {
    String name;
    boolean contract;
    double salary;
    Employee() {
        // line n1
    }
    public String toString(){
        return name + ":" + contract + ":" + salary;
    }
    public static void main(String[] args) {
        Employee e = new Employee();
        // line n2
        System.out.print(e);
    }
}
```

Which two modifications, when made independently, enable the code to print Joe:true: 100.0? (Choose two.)

- A) Replace line n2 with:  
e.name = "Joe";  
e.contract = true;  
e.salary = 100;
- B) Replace line n2 with:  
this.name = "Joe";  
this.contract = true;  
this.salary = 100;
- C) Replace line n1 with:  
this.name = new String("Joe");  
this.contract = new Boolean(true);  
this.salary = new Double(100);
- D) Replace line n1 with:  
name = "Joe";  
contract = TRUE;  
salary = 100.0f;
- E) Replace line n1 with:  
this("Joe", true, 100);

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

**Answer:** AC

#### NEW QUESTION 18

Given:

```
class A {
    public void test() {
        System.out.println("A ");
    }
}

class B extends A {
    public void test() {
        System.out.println("B ");
    }
}

public class C extends A {
    public void test() {
        System.out.println("C ");
    }
}

public static void main(String[] args) {
    A b1 = new A();
    A b2 = new C();
    A b3 = (B) b2;           //line n1
    b1 = (A) b2;           //line n2
    b1.test();
    b3.test();
}
}
```

What is the result?

- A. AB
- B. AC
- C. CC
- D. A ClassCastException is thrown only at line n1.
- E. A ClassCastException is thrown only at line n2.

**Answer:** D

#### NEW QUESTION 21

Which statement is true about Java byte code?

- A. It can run on any platform.
- B. It can run on any platform only if it was compiled for that platform.
- C. It can run on any platform that has the Java Runtime Environment.
- D. It can run on any platform that has a Java compiler.
- E. It can run on any platform only if that platform has both the Java Runtime Environment and a Java compiler.

**Answer:** D

#### Explanation:

Java bytecodes help make "write once, run anywhere" possible. You can compile your program into bytecodes on any platform that has a Java compiler. The bytecodes can then be run on any implementation of the Java VM. That means that as long as a computer has a Java VM, the same program written in the Java programming language can run on Windows 2000, a Solaris workstation, or on an iMac.

#### NEW QUESTION 22

Given:

Base.java:

```
class Base {
    public void test(){
        System.out.println("Base ");
    }
}
```

DerivedA.java:

```
class DerivedA extends Base {
    public void test(){
        System.out.println("DerivedA ");
    }
}
```

DerivedB.java:

```
class DerivedB extends DerivedA {
    public void test(){
        System.out.println("DerivedB ");
    }
    public static void main(String[] args) {
        Base b1 = new DerivedB();
        Base b2 = new DerivedA();
        Base b3 = new DerivedB();
        Base b4 = b3;
        b1 = (Base) b2;
        b1.test();
        b4.test();
    }
}
```

What is the result?

- A. BaseDerivedA
- B. BaseDerivedB
- C. DerivedBDerivedB
- D. DerivedBDerivedA
- E. A ClassCastException is thrown at runtime.

**Answer:** D

### NEW QUESTION 23

Given:

```
class Test {
    int a1;

    public static void doProduct(int a) {
        a = a * a;
    }

    public static void doString(String s) {
        s.concat(" " + s);
    }

    public static void main(String[] args) {
        Test item = new Test();
        item.a1 = 11;
        String sb = "Hello";
        Integer i = 10;
        doProduct(i);
        doString(sb);
        doProduct(item.a1);
        System.out.println(i + " " + sb + " " + item.a1);
    }
}
```

What is the result?

- A. 10 Hello Hello 11

- B. 10 Hello Hello 121
- C. 100 Hello 121
- D. 100 Hello Hello 121
- E. 10 Hello 11

**Answer: E**

#### NEW QUESTION 25

Given the code fragment:

```
public static void main(String[] args) {  
    LocalDate date = LocalDate.of(2012, 1, 30);  
    date.plusDays(10);  
    System.out.println(date);  
}
```

What is the result?

- A. 2012-02-10
- B. 2012-01-30
- C. 2012-02-10 00:00
- D. A DateTimeException is thrown at runtime.

**Answer: C**

#### NEW QUESTION 30

Given:

```
public class Triangle {  
    static double area;  
    int b = 2, h = 3;  
    public static void main(String[] args) {  
        double p, b, h; //line n1  
        if (area == 0) {  
            b = 3;  
            h = 4;  
            p = 0.5;  
            area = p * b * h; //line n2  
        }  
        System.out.println("Area is " + area);  
    }  
}
```

What is the result?

- A. Area is 6.0
- B. Area is 3.0
- C. Compilation fails at line n1
- D. Compilation fails at line n2.

**Answer: D**

#### NEW QUESTION 34

Given this class:

```
public class Rectangle {  
    private double length;  
    private double height;  
    private double area;  
  
    public void setLength(double length) {  
        this.length = length;  
    }  
    public void setHeight(double height) {  
        this.height = height;  
    }  
    public void setArea() {  
        area = length*height;  
    }  
}
```

Which two changes would encapsulate this class and ensure that the area field is always equal to length \* height whenever the Rectangle class is used?

- A. Call the setArea method at the end of the setHeight method.
- B. Call the setArea method at the beginning of the setHeight method.
- C. Call the setArea method at the end of the setLength method.
- D. Call the setArea method at the beginning of the setLength method.
- E. Change the setArea method to private.
- F. Change the area field to public.

**Answer:** AE

#### NEW QUESTION 38

Which statement is true about the switch statement?

- A. It must contain the default section.
- B. The break statement, at the end of each case block, is optional.
- C. Its case label literals can be changed at runtime.
- D. Its expression must evaluate to a collection of values.

**Answer:** B

#### NEW QUESTION 42

Which two statements are true? (Choose two.)

- A. Error class is unextendable.
- B. Error class is extendable.
- C. Error is a RuntimeException.
- D. Error is an Exception.
- E. Error is a Throwable.

**Answer:** BC

#### NEW QUESTION 45

Given the code fragment:

```
LocalDate date1 = LocalDate.now();
LocalDate date2 = LocalDate.of(6, 20, 2014 );
LocalDate date3 = LocalDate.parse("2014-06-20", DateTimeFormatter.ISO_DATE);
System.out.println("date1 = " + date1);
System.out.println("date2 = " + date2);
System.out.println("date3 = " + date3);
```

Assume that the system date is June 20, 2014. What is the result?

- A
  - date1 = 2014-06-20
  - date2 = 2014-06-20
  - date3 = 2014-06-20
- B
  - date1 = 06/20/2014
  - date2 = 2014-06-20
  - date3 = Jun 20, 2014
- C Compilation fails.
- D An exception is thrown at runtime.

- A. Option A
- B. Option B
- C. Option C
- D. Option D

**Answer:** A

#### NEW QUESTION 47

.....

## Relate Links

**100% Pass Your 1z0-808 Exam with ExamBible Prep Materials**

<https://www.exambible.com/1z0-808-exam/>

## Contact us

We are proud of our high-quality customer service, which serves you around the clock 24/7.

Viste - <https://www.exambible.com/>