

Amazon-Web-Services

Exam Questions ANS-C01

AWS Certified Advanced Networking Specialty Exam



NEW QUESTION 1

A network engineer must develop an AWS CloudFormation template that can create a virtual private gateway, a customer gateway, a VPN connection, and static routes in a route table. During testing of the template, the network engineer notes that the CloudFormation template has encountered an error and is rolling back. What should the network engineer do to resolve the error?

- A. Change the order of resource creation in the CloudFormation template.
- B. Add the DependsOn attribute to the resource declaration for the virtual private gateway.
- C. Specify the route table entry resource.
- D. Add a wait condition in the template to wait for the creation of the virtual private gateway.
- E. Add the DependsOn attribute to the resource declaration for the route table entry.
- F. Specify the virtual private gateway resource.

Answer: D

NEW QUESTION 2

A data analytics company has a 100-node high performance computing (HPC) cluster. The HPC cluster is for parallel data processing and is hosted in a VPC in the AWS Cloud. As part of the data processing workflow, the HPC cluster needs to perform several DNS queries to resolve and connect to Amazon RDS databases, Amazon S3 buckets, and on-premises data stores that are accessible through AWS Direct Connect. The HPC cluster can increase in size by five to seven times during the company's peak event at the end of the year.

The company is using two Amazon EC2 instances as primary DNS servers for the VPC. The EC2 instances are configured to forward queries to the default VPC resolver for Amazon Route 53 hosted domains and to the on-premises DNS servers for other on-premises hosted domain names. The company notices job failures and finds that DNS queries from the HPC cluster nodes failed when the nodes tried to resolve RDS and S3 bucket endpoints.

Which architectural change should a network engineer implement to provide the DNS service in the MOST scalable way?

- A. Scale out the DNS service by adding two additional EC2 instances in the VPC.
- B. Reconfigure half of the HPC cluster nodes to use these new DNS servers.
- C. Plan to scale out by adding additional EC2 instance-based DNS servers in the future as the HPC cluster size grows.
- D. Scale up the existing EC2 instances that the company is using as DNS servers.
- E. Change the instance size to the largest possible instance size to accommodate the current DNS load and the anticipated load in the future.
- F. Create Route 53 Resolver outbound endpoint.
- G. Create Route 53 Resolver rules to forward queries to on-premises DNS servers for on-premises hosted domain names.
- H. Reconfigure the HPC cluster nodes to use the default VPC resolver instead of the EC2 instance-based DNS server.
- I. Terminate the EC2 instances.
- J. Create Route 53 Resolver inbound endpoint.
- K. Create rules on the on-premises DNS servers to forward queries to the default VPC resolver.
- L. Reconfigure the HPC cluster nodes to forward all DNS queries to the on-premises DNS server.
- M. Terminate the EC2 instances.

Answer: C

NEW QUESTION 3

A company is planning to use Amazon S3 to archive financial data. The data is currently stored in an on-premises data center. The company uses AWS Direct Connect with a Direct Connect gateway and a transit gateway to connect to the on-premises data center. The data cannot be transported over the public internet and must be encrypted in transit.

Which solution will meet these requirements?

- A. Create a Direct Connect public VIF.
- B. Set up an IPsec VPN connection over the public VIF to access Amazon S3. Use HTTPS for communication.
- C. Create an IPsec VPN connection over the transit VIF.
- D. Create a VPC and attach the VPC to the transit gateway.
- E. In the VPC, provision an interface VPC endpoint for Amazon S3. Use HTTPS for communication.
- F. Create a VPC and attach the VPC to the transit gateway.
- G. In the VPC, provision an interface VPC endpoint for Amazon S3. Use HTTPS for communication.
- H. Create a Direct Connect public VIF.
- I. Set up an IPsec VPN connection over the public VIF to the transit gateway.
- J. Create an attachment for Amazon S3. Use HTTPS for communication.

Answer: B

Explanation:

<https://docs.aws.amazon.com/vpn/latest/s2svpn/private-ip-dx.html>

An IPsec VPN connection over the transit VIF can encrypt traffic between the on-premises network and AWS without using public IP addresses or the internet2. A VPC endpoint for Amazon S3 can enable private access to S3 buckets within the same region. HTTPS can provide additional encryption for communication.

NEW QUESTION 4

A company has deployed a web application on AWS. The web application uses an Application Load Balancer (ALB) across multiple Availability Zones. The targets of the ALB are AWS Lambda functions. The web application also uses Amazon CloudWatch metrics for monitoring.

Users report that parts of the web application are not loading properly. A network engineer needs to troubleshoot the problem. The network engineer enables access logging for the ALB.

What should the network engineer do next to determine which errors the ALB is receiving?

- A. Send the logs to Amazon CloudWatch Log.
- B. Review the ALB logs in CloudWatch Insights to determine which error messages the ALB is receiving.
- C. Configure the Amazon S3 bucket destination.
- D. Use Amazon Athena to determine which error messages the ALB is receiving.
- E. Configure the Amazon S3 bucket destination.
- F. After Amazon CloudWatch Logs pulls the ALB logs from the S3 bucket automatically, review the logs in CloudWatch Logs to determine which error messages the ALB is receiving.

- G. Send the logs to Amazon CloudWatch Log
- H. Use the Amazon Athena CloudWatch Connector to determine which error messages the ALB is receiving.

Answer: B

Explanation:

Access logs is an optional feature of Elastic Load Balancing that is disabled by default. After you enable access logs for your load balancer, Elastic Load Balancing captures the logs and stores them in the Amazon S3 bucket that you specify as compressed files. You can disable access logs at any time. <https://docs.aws.amazon.com/elasticloadbalancing/latest/application/load-balancer-access-logs.html>

NEW QUESTION 5

A company has hundreds of VPCs on AWS. All the VPCs access the public endpoints of Amazon S3 and AWS Systems Manager through NAT gateways. All the traffic from the VPCs to Amazon S3 and Systems Manager travels through the NAT gateways. The company's network engineer must centralize access to these services and must eliminate the need to use public endpoints.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create a central egress VPC that has private NAT gateway
- B. Connect all the VPCs to the central egress VPC by using AWS Transit Gateway
- C. Use the private NAT gateways to connect to Amazon S3 and Systems Manager by using private IP addresses.
- D. Create a central shared services VPC
- E. In the central shared services VPC, create interface VPC endpoints for Amazon S3 and Systems Manager to access
- F. Ensure that private DNS is turned off
- G. Connect all the VPCs to the central shared services VPC by using AWS Transit Gateway
- H. Create an Amazon Route 53 forwarding rule for each interface VPC endpoint
- I. Associate the forwarding rules with all the VPC
- J. Forward DNS queries to the interface VPC endpoints in the shared services VPC.
- K. Create a central shared services VPC. In the central shared services VPC, create interface VPC endpoints for Amazon S3 and Systems Manager to access
- L. Ensure that private DNS is turned off
- M. Connect all the VPCs to the central shared services VPC by using AWS Transit Gateway
- N. Create an Amazon Route 53 private hosted zone with a full service endpoint name for Amazon S3 and Systems Manager
- O. Associate the private hosted zones with all the VPC
- P. Create an alias record in each private hosted zone with the full AWS service endpoint pointing to the interface VPC endpoint in the shared services VPC.
- Q. Create a central shared services VPC
- R. In the central shared services VPC, create interface VPC endpoints for Amazon S3 and Systems Manager to access
- S. Connect all the VPCs to the central shared services VPC by using AWS Transit Gateway
- T. Ensure that private DNS is turned on for the interface VPC endpoints and that the transit gateway is created with DNS support turned on.

Answer: B

Explanation:

Interface VPC endpoints enable private connectivity between VPCs and supported AWS services without requiring an internet gateway, NAT device, VPN connection, or AWS Direct Connect connection. Interface VPC endpoints are powered by AWS PrivateLink, a technology that enables private access to AWS services. Amazon S3 and AWS Systems Manager support interface VPC endpoints. By turning off private DNS, the interface VPC endpoints can be accessed by using their private IP addresses. By using Amazon Route 53 forwarding rules, DNS queries can be resolved to the interface VPC endpoints in the shared services VPC.

NEW QUESTION 6

A real estate company is building an internal application so that real estate agents can upload photos and videos of various properties. The application will store these photos and videos in an Amazon S3 bucket as objects and will use Amazon DynamoDB to store corresponding metadata. The S3 bucket will be configured to publish all PUT events for new object uploads to an Amazon Simple Queue Service (Amazon SQS) queue.

A compute cluster of Amazon EC2 instances will poll the SQS queue to find out about newly uploaded objects. The cluster will retrieve new objects, perform proprietary image and video recognition and classification, update metadata in DynamoDB, and replace the objects with new watermarked objects. The company does not want public IP addresses on the EC2 instances.

Which networking design solution will meet these requirements MOST cost-effectively as application usage increases?

- A. Place the EC2 instances in a public subnet
- B. Disable the Auto-assign Public IP option while launching the EC2 instance
- C. Create an internet gateway
- D. Attach the internet gateway to the VPC
- E. In the public subnet's route table, add a default route that points to the internet gateway.
- F. Place the EC2 instances in a private subnet
- G. Create a NAT gateway in a public subnet in the same Availability Zone
- H. Create an internet gateway
- I. Attach the internet gateway to the VPC
- J. In the public subnet's route table, add a default route that points to the internet gateway
- K. Place the EC2 instances in a private subnet
- L. Create an interface VPC endpoint for Amazon SQS
- M. Create gateway VPC endpoints for Amazon S3 and DynamoDB.
- N. Place the EC2 instances in a private subnet
- O. Create a gateway VPC endpoint for Amazon SQS. Create interface VPC endpoints for Amazon S3 and DynamoDB.

Answer: C

NEW QUESTION 7

A company is deploying third-party firewall appliances for traffic inspection and NAT capabilities in its VPC. The VPC is configured with private subnets and public subnets. The company needs to deploy the firewall appliances behind a load balancer.

Which architecture will meet these requirements MOST cost-effectively?

- A. Deploy a Gateway Load Balancer with the firewall appliances as target
- B. Configure the firewall appliances with a single network interface in a private subnet

- C. Use a NAT gateway to send the traffic to the internet after inspection.
- D. Deploy a Gateway Load Balancer with the firewall appliances as target
- E. Configure the firewall appliances with two network interfaces: one network interface in a private subnet and another network interface in a public subnet
- F. Use the NAT functionality on the firewall appliances to send the traffic to the internet after inspection.
- G. Deploy a Network Load Balancer with the firewall appliances as target
- H. Configure the firewall appliances with a single network interface in a private subnet
- I. Use a NAT gateway to send the traffic to the internet after inspection.
- J. Deploy a Network Load Balancer with the firewall appliances as target
- K. Configure the firewall appliances with two network interfaces: one network interface in a private subnet and another network interface in a public subnet
- L. Use the NAT functionality on the firewall appliances to send the traffic to the internet after inspection.

Answer: B

NEW QUESTION 8

A company's network engineer is designing a hybrid DNS solution for an AWS Cloud workload. Individual teams want to manage their own DNS hostnames for their applications in their development environment. The solution must integrate the application-specific hostnames with the centrally managed DNS hostnames from the on-premises network and must provide bidirectional name resolution. The solution also must minimize management overhead. Which combination of steps should the network engineer take to meet these requirements? (Choose three.)

- A. Use an Amazon Route 53 Resolver inbound endpoint.
- B. Modify the DHCP options set by setting a custom DNS server value.
- C. Use an Amazon Route 53 Resolver outbound endpoint.
- D. Create DNS proxy servers.
- E. Create Amazon Route 53 private hosted zones.
- F. Set up a zone transfer between Amazon Route 53 and the on-premises DNS.

Answer: ABE

NEW QUESTION 9

A network engineer needs to set up an Amazon EC2 Auto Scaling group to run a Linux-based network appliance in a highly available architecture. The network engineer is configuring the new launch template for the Auto Scaling group. In addition to the primary network interface the network appliance requires a second network interface that will be used exclusively by the application to exchange traffic with hosts over the internet. The company has set up a Bring Your Own IP (BYOIP) pool that includes an Elastic IP address that should be used as the public IP address for the second network interface. How can the network engineer implement the required architecture?

- A. Configure the two network interfaces in the launch template
- B. Define the primary network interface to be created in one of the private subnets
- C. For the second network interface, select one of the public subnets
- D. Choose the BYOIP pool ID as the source of public IP addresses.
- E. Configure the primary network interface in a private subnet in the launch template
- F. Use the user data option to run a cloud-init script after boot to attach the second network interface from a subnet with auto-assign public IP addressing enabled.
- G. Create an AWS Lambda function to run as a lifecycle hook of the Auto Scaling group when an instance is launching
- H. In the Lambda function, assign a network interface to an AWS Global Accelerator endpoint.
- I. During creation of the Auto Scaling group, select subnets for the primary network interface
- J. Use the user data option to run a cloud-init script to allocate a second network interface and to associate an Elastic IP address from the BYOIP pool.

Answer: D

Explanation:

During creation of the Auto Scaling group, select subnets for the primary network interface. Use the user data option to run a cloud-init script to allocate a second network interface and to associate an Elastic IP address from the BYOIP pool. This solution meets all of the requirements stated in the question. The primary network interface can be configured in a private subnet during creation of the Auto Scaling group. The user data option can be used to run a cloud-init script that will allocate a second network interface and associate an Elastic IP address from the BYOIP pool with it.

NEW QUESTION 10

A software-as-a-service (SaaS) provider hosts its solution on Amazon EC2 instances within a VPC in the AWS Cloud. All of the provider's customers also have their environments in the AWS Cloud. A recent design meeting revealed that the customers have IP address overlap with the provider's AWS deployment. The customers have stated that they will not share their internal IP addresses and that they do not want to connect to the provider's SaaS service over the internet. Which combination of steps is part of a solution that meets these requirements? (Choose two.)

- A. Deploy the SaaS service endpoint behind a Network Load Balancer.
- B. Configure an endpoint service, and grant the customers permission to create a connection to the endpoint service.
- C. Deploy the SaaS service endpoint behind an Application Load Balancer.
- D. Configure a VPC peering connection to the customer VPC
- E. Route traffic through NAT gateways.
- F. Deploy an AWS Transit Gateway, and connect the SaaS VPC to it
- G. Share the transit gateway with the customer
- H. Configure routing on the transit gateway.

Answer: AB

Explanation:

NLB for creating the private link which solves the overlapping IP address issue and the SaaS service endpoint behind it. (the SaaS endpoint could be an ALB)
<https://aws.amazon.com/about-aws/whats-new/2021/09/application-load-balancer-aws-privatelink-static-ip>

NEW QUESTION 10

A customer has set up multiple VPCs for Dev, Test, Prod, and Management. You need to set up AWS Direct Connect to enable data flow from on-premises to each VPC. The customer has monitoring software running in the Management VPC that collects metrics from the instances in all the other VPCs. Due to budget requirements, data transfer charges should be kept at minimum. Which design should be recommended?

- A. Create a total of four private VIFs, one for each VPC owned by the customer, and route traffic between VPCs using the Direct Connect link.
- B. Create a private VIF to the Management VPC, and peer this VPC to all other VPCs.
- C. Create a private VIF to the Management VPC, and peer this VPC to all other VPCs, enable source/destination NAT in the Management VPC.
- D. Create a total of four private VIFs, and enable VPC peering between all VPCs.

Answer: D

Explanation:

- creating VPC peering is free of charge - traffic costs ~0.01€/GB for VPC peering (IN + OUT) and ~0.02€/GB for direct connect (OUT only). As the communication involved in monitoring will never have IN == OUT, then $0.01 * (IN + OUT)$ will always be lower than $0.02 * OUT$, ergo VPC peering will be cheaper

NEW QUESTION 11

A company has two AWS accounts one for Production and one for Connectivity. A network engineer needs to connect the Production account VPC to a transit gateway in the Connectivity account. The feature to auto accept shared attachments is not enabled on the transit gateway. Which set of steps should the network engineer follow in each AWS account to meet these requirements?

- A. * 1. In the Production account: Create a resource share in AWS Resource Access Manager for the transit gateway
- B. Provide the Connectivity account ID
- C. Enable the feature to allow external accounts* 2. In the Connectivity account: Accept the resource.* 3. In the Connectivity account: Create an attachment to the VPC subnets.* 4. In the Production account: Accept the attachment
- D. Associate a route table with the attachment.
- E. * 1. In the Production account: Create a resource share in AWS Resource Access Manager for the VPC subnet
- F. Provide the Connectivity account ID
- G. Enable the feature to allow external accounts.* 2. In the Connectivity account: Accept the resource.* 3. In the Production account: Create an attachment on the transit gateway to the VPC subnets.* 4. In the Connectivity account: Accept the attachment
- H. Associate a route table with the attachment.
- I. * 1. In the Connectivity account: Create a resource share in AWS Resource Access Manager for the VPC subnet
- J. Provide the Production account ID
- K. Enable the feature to allow external accounts.* 2. In the Production account: Accept the resource.* 3. In the Connectivity account: Create an attachment on the transit gateway to the VPC subnets.* 4. In the Production account: Accept the attachment
- L. Associate a route table with the attachment.
- M. * 1. In the Connectivity account: Create a resource share in AWS Resource Access Manager for the transit gateway
- N. Provide the Production account ID Enable the feature to allow external accounts.* 2. In the Production account: Accept the resource.* 3. In the Production account: Create an attachment to the VPC subnets.* 4. In the Connectivity account: Accept the attachment
- O. Associate a route table with the attachment.

Answer: A

Explanation:

step 1: In the Production account, create a resource share in AWS Resource Access Manager for the transit gateway and provide the Connectivity account ID. Enabling the feature to allow external accounts is also required to share resources between accounts. Step 2: In the Connectivity account, accept the shared resource. This action will allow the Production account to use the transit gateway in the Connectivity account. Step 3: In the Connectivity account, create an attachment to the VPC subnets. This attachment will enable communication between the VPC in the Production account and the transit gateway in the Connectivity account. Step 4: In the Production account, accept the attachment and associate a route table with the attachment. This will enable the VPC to route traffic through the transit gateway to other resources in the Connectivity account.

NEW QUESTION 16

You deploy an Amazon EC2 instance that runs a web server into a subnet in a VPC. An Internet gateway is attached, and the main route table has a default route (0.0.0.0/0) configured with a target of the Internet gateway.

The instance has a security group configured to allow as follows:

- > Protocol: TCP
- > Port: 80 inbound, nothing outbound

The Network ACL for the subnet is configured to allow as follows:

- > Protocol: TCP
- > Port: 80 inbound, nothing outbound

When you try to browse to the web server, you receive no response. Which additional step should you take to receive a successful response?

- A. Add an entry to the security group outbound rules for Protocol: TCP, Port Range: 80
- B. Add an entry to the security group outbound rules for Protocol: TCP, Port Range: 1024-65535
- C. Add an entry to the Network ACL outbound rules for Protocol: TCP, Port Range: 80
- D. Add an entry to the Network ACL outbound rules for Protocol: TCP, Port Range: 1024-65535

Answer: D

Explanation:

To enable the connection to a service running on an instance, the associated network ACL must allow both inbound traffic on the port that the service is listening on as well as allow outbound traffic from ephemeral ports. When a client connects to a server, a random port from the ephemeral port range (1024-65535) becomes the client's source port. The designated ephemeral port then becomes the destination port for return traffic from the service, so outbound traffic from the ephemeral port must be allowed in the network ACL.<https://aws.amazon.com/premiumsupport/knowledge-center/resolve-connection-sg-acl-inbound/>

NEW QUESTION 19

A company uses a 1 Gbps AWS Direct Connect connection to connect its AWS environment to its

on-premises data center. The connection provides employees with access to an application VPC that is hosted on AWS. Many remote employees use a company-provided VPN to connect to the data center. These employees are reporting slowness when they access the application during business hours. On-premises users have started to report similar slowness while they are in the office.

The company plans to build an additional application on AWS. On-site and remote employees will use the additional application. After the deployment of this additional application, the company will need 20% more bandwidth than the company currently uses. With the increased usage, the company wants to add resiliency to the AWS connectivity. A network engineer must review the current implementation and must make improvements within a limited budget. What should the network engineer do to meet these requirements MOST cost-effectively?

- A. Set up a new 1 Gbps Direct Connect dedicated connection to accommodate the additional traffic load from remote employees and the additional application
- B. Create a link aggregation group (LAG).
- C. Deploy an AWS Site-to-Site VPN connection to the application VPC
- D. Configure the on-premises routing for the remote employees to connect to the Site-to-Site VPN connection.
- E. Deploy Amazon Workspaces into the application VPC and instruct the remote employees to connect to Workspaces.
- F. Replace the existing 1 Gbps Direct Connect connection with two new 2 Gbps Direct Connect hosted connections
- G. Create an AWS Client VPN endpoint in the application VPC
- H. Instruct the remote employees to connect to the Client VPN endpoint.

Answer: A

Explanation:

Setting up a new 1 Gbps Direct Connect dedicated connection to accommodate the additional traffic load from remote employees and the additional application would provide more bandwidth and lower latency than a VPN connection over the public internet¹. Creating a link aggregation group (LAG) with the existing and new Direct Connect connections would provide resiliency and redundancy for the AWS connectivity².

NEW QUESTION 21

A global company runs business applications in the us-east-1 Region inside a VPC. One of the company's regional offices in London uses a virtual private gateway for an AWS Site-to-Site VPN connection to the VPC. The company has configured a transit gateway and has set up peering between the VPC and other VPCs that various departments in the company use.

Employees at the London office are experiencing latency issues when they connect to the business applications. What should a network engineer do to reduce this latency?

- A. Create a new Site-to-Site VPN connection
- B. Set the transit gateway as the target gateway
- C. Enable acceleration on the new Site-to-Site VPN connection
- D. Update the VPN device in the London office with the new connection details.
- E. Modify the existing Site-to-Site VPN connection by setting the transit gateway as the target gateway. Enable acceleration on the existing Site-to-Site VPN connection.
- F. Create a new transit gateway in the eu-west-2 (London) Region
- G. Peer the new transit gateway with the existing transit gateway
- H. Modify the existing Site-to-Site VPN connection by setting the new transit gateway as the target gateway.
- I. Create a new AWS Global Accelerator standard accelerator that has an endpoint of the Site-to-Site VPN connection
- J. Update the VPN device in the London office with the new connection details.

Answer: A

Explanation:

Enabling acceleration for a Site-to-Site VPN connection uses AWS Global Accelerator to route traffic from the on-premises network to an AWS edge location that is closest to the customer gateway device¹. AWS Global Accelerator optimizes the network path, using the congestion-free AWS global network to route traffic to the endpoint that provides the best application performance². Setting the transit gateway as the target gateway enables connectivity between the on-premises network and multiple VPCs that are attached to the transit gateway³.

NEW QUESTION 26

A global delivery company is modernizing its fleet management system. The company has several business units. Each business unit designs and maintains applications that are hosted in its own AWS account in separate application VPCs in the same AWS Region. Each business unit's applications are designed to get data from a central shared services VPC.

The company wants the network connectivity architecture to provide granular security controls. The architecture also must be able to scale as more business units consume data from the central shared services VPC in the future.

Which solution will meet these requirements in the MOST secure manner?

- A. Create a central transit gateway
- B. Create a VPC attachment to each application VPC
- C. Provide full mesh connectivity between all the VPCs by using the transit gateway.
- D. Create VPC peering connections between the central shared services VPC and each application VPC in each business unit's AWS account.
- E. Create VPC endpoint services powered by AWS PrivateLink in the central shared services VPC and create VPC endpoints in each application VPC.
- F. Create a central transit VPC with a VPN appliance from AWS Marketplace
- G. Create a VPN attachment from each VPC to the transit VPC
- H. Provide full mesh connectivity among all the VPCs.

Answer: C

Explanation:

Option C provides a secure and scalable solution using VPC endpoint services powered by AWS PrivateLink. AWS PrivateLink enables private connectivity between VPCs and services without exposing the data to the public internet or using a VPN connection. By creating VPC endpoints in each application VPC, the company can securely access the central shared services VPC without the need for complex network configurations. Furthermore, PrivateLink supports cross-account connectivity, which makes it a scalable solution as more business units consume data from the central shared services VPC in the future.

NEW QUESTION 31

A company has deployed a software-defined WAN (SD-WAN) solution to interconnect all of its offices. The company is migrating workloads to AWS and needs to extend its SD-WAN solution to support connectivity to these workloads.

A network engineer plans to deploy AWS Transit Gateway Connect and two SD-WAN virtual appliances to provide this connectivity. According to company

policies, only a single SD-WAN virtual appliance can handle traffic from AWS workloads at a given time. How should the network engineer configure routing to meet these requirements?

- A. Add a static default route in the transit gateway route table to point to the secondary SD-WAN virtual appliance
- B. Add routes that are more specific to point to the primary SD-WAN virtual appliance.
- C. Configure the BGP community tag 7224:7300 on the primary SD-WAN virtual appliance for BGP routes toward the transit gateway.
- D. Configure the AS_PATH prepend attribute on the secondary SD-WAN virtual appliance for BGP routes toward the transit gateway.
- E. Disable equal-cost multi-path (ECMP) routing on the transit gateway for Transit Gateway Connect.

Answer: A

NEW QUESTION 34

A company is using Amazon Route 53 Resolver DNS Firewall in a VPC to block all domains except domains that are on an approved list. The company is concerned that if DNS Firewall is unresponsive, resources in the VPC might be affected if the network cannot resolve any DNS queries. To maintain application service level agreements, the company needs DNS queries to continue to resolve even if Route 53 Resolver does not receive a response from DNS Firewall. Which change should a network engineer implement to meet these requirements?

- A. Update the DNS Firewall VPC configuration to disable fail open for the VPC.
- B. Update the DNS Firewall VPC configuration to enable fail open for the VPC.
- C. Create a new DHCP options set with parameter dns_firewall_fail_open=fals
- D. Associate the new DHCP options set with the VPC.
- E. Create a new DHCP options set with parameter dns_firewall_fail_open=tru
- F. Associate the new DHCP options set with the VPC.

Answer: B

NEW QUESTION 38

A company is deploying an application. The application is implemented in a series of containers in an Amazon Elastic Container Service (Amazon ECS) cluster. The company will use the Fargate launch type for its tasks. The containers will run workloads that require connectivity initiated over an SSL connection. Traffic must be able to flow to the application from other AWS accounts over private connectivity. The application must scale in a manageable way as more consumers use the application.

Which solution will meet these requirements?

- A. Choose a Gateway Load Balancer (GLB) as the type of load balancer for the ECS servic
- B. Create a lifecycle hook to add new tasks to the target group from Amazon ECS as required to handle scalin
- C. Specify the GLB in the service definitio
- D. Create a VPC peer for external AWS account
- E. Update the route tables so that the AWS accounts can reach the GLB.
- F. Choose an Application Load Balancer (ALB) as the type of load balancer for the ECS servic
- G. Create path-based routing rules to allow the application to target the containers that are registered in the target grou
- H. Specify the ALB in the service definitio
- I. Create a VPC endpoint service for the ALB Share the VPC endpoint service with other AWS accounts.
- J. Choose an Application Load Balancer (ALB) as the type of load balancer for the ECS servic
- K. Create path-based routing rules to allow the application to target the containers that are registered in the target grou
- L. Specify the ALB in the service definitio
- M. Create a VPC peer for the external AWS account
- N. Update the route tables so that the AWS accounts can reach the ALB.
- O. Choose a Network Load Balancer (NLB) as the type of load balancer for the ECS servic
- P. Specify the NLB in the service definitio
- Q. Create a VPC endpoint service for the NL
- R. Share the VPC endpoint service with other AWS accounts.

Answer: D

NEW QUESTION 43

A company has created three VPCs: a production VPC, a nonproduction VPC, and a shared services VPC. The production VPC and the nonproduction VPC must each have communication with the shared services VPC. There must be no communication between the production VPC and the nonproduction VPC. A transit gateway is deployed to facilitate communication between VPCs.

Which route table configurations on the transit gateway will meet these requirements?

- A. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for only the shared services VP
- B. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.
- C. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes for each VP
- D. Create an additional route table with only the shared services VPC attachment associated with propagated routes from each VPC.
- E. Configure a route table with all the VPC attachments associated with propagated routes for only the shared services VPC
- F. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.
- G. Configure a route table with the production and nonproduction VPC attachments associated with propagated routes disable
- H. Create an additional route table with only the shared services VPC attachment associated with propagated routes from the production and nonproduction VPCs.

Answer: A

NEW QUESTION 47

A company manages resources across VPCs in multiple AWS Regions. The company needs to connect to the resources by using its internal domain name. A network engineer needs to apply the aws.example.com DNS suffix to all resources.

What must the network engineer do to meet this requirement?

- A. Create an Amazon Route 53 private hosted zone for aws.example.com in each Region that has resource
- B. Associate the private hosted zone with that Region's VP
- C. In the appropriate private hosted zone, create DNS records for the resources in each Region.

- D. Create one Amazon Route 53 private hosted zone for aws.example.co
- E. Configure the private hosted zone to allow zone transfers with every VPC.
- F. Create one Amazon Route 53 private hosted zone for example.co
- G. Create a single resource record for aws.example.com in the private hosted zone
- H. Apply a multivalued answer routing policy to the record
- I. Add all VPC resources as separate values in the routing policy.
- J. Create one Amazon Route 53 private hosted zone for aws.example.co
- K. Associate the private hosted zone with every VPC that has resources
- L. In the private hosted zone, create DNS records for all resources.

Answer: D

Explanation:

Creating one private hosted zone for aws.example.com and associating it with every VPC that has resources would enable DNS resolution for all resources by using their internal domain name. Creating an alias record in each private hosted zone with the full AWS service endpoint pointing to the interface VPC endpoint in the shared services VPC would enable private connectivity to Amazon S3 and AWS Systems Manager without using public endpoints.

NEW QUESTION 50

A company is using a NAT gateway to allow internet connectivity for private subnets in a VPC in the us-west-2 Region. After a security audit, the company needs to remove the NAT gateway.

In the private subnets, the company has resources that use the unified Amazon CloudWatch agent. A network engineer must create a solution to ensure that the unified CloudWatch agent continues to work after the removal of the NAT gateway.

Which combination of steps should the network engineer take to meet these requirements? (Choose three.)

- A. Validate that private DNS is enabled on the VPC by setting the enableDnsHostnames VPC attribute and the enableDnsSupport VPC attribute to true.
- B. Create a new security group with an entry to allow outbound traffic that uses the TCP protocol on port 443 to destination 0.0.0.0/0
- C. Create a new security group with entries to allow inbound traffic that uses the TCP protocol on port 443 from the IP prefixes of the private subnets.
- D. Create the following interface VPC endpoints in the VPC: com.amazonaws.us-west-2.logs and com.amazonaws.us-west-2.monitoring
- E. Associate the new security group with the endpoint network interfaces.
- F. Create the following interface VPC endpoint in the VPC: com.amazonaws.us-west-2.cloudwatch. Associate the new security group with the endpoint network interfaces.
- G. Associate the VPC endpoint or endpoints with route tables that the private subnets use.

Answer: BDF

NEW QUESTION 51

A company is using an AWS Site-to-Site VPN connection from the company's on-premises data center to a virtual private gateway in the AWS Cloud. Because of congestion, the company is experiencing availability and performance issues as traffic travels across the internet before the traffic reaches AWS. A network engineer must reduce these issues for the connection as quickly as possible with minimum administration effort.

Which solution will meet these requirements?

- A. Edit the existing Site-to-Site VPN connection by enabling acceleration
- B. Stop and start the VPN service on the customer gateway for the new setting to take effect.
- C. Configure a transit gateway in the same AWS Region as the existing virtual private gateway
- D. Create a new accelerated Site-to-Site VPN connection
- E. Connect the new connection to the transit gateway by using a VPN attachment
- F. Update the customer gateway device to use the new Site-to-Site VPN connection
- G. Delete the existing Site-to-Site VPN connection
- H. Create a new accelerated Site-to-Site VPN connection
- I. Connect the new Site-to-Site VPN connection to the existing virtual private gateway
- J. Update the customer gateway device to use the new Site-to-Site VPN connection
- K. Delete the existing Site-to-Site VPN connection.
- L. Create a new AWS Direct Connect connection with a private VIF between the on-premises data center and the AWS Cloud
- M. Update the customer gateway device to use the new Direct Connect connection
- N. Delete the existing Site-to-Site VPN connection.

Answer: B

NEW QUESTION 52

A company hosts an application on Amazon EC2 instances behind an Application Load Balancer (ALB). The company recently experienced a network security breach. A network engineer must collect and analyze logs that include the client IP address, target IP address, target port, and user agent of each user that accesses the application.

What is the MOST operationally efficient solution that meets these requirements?

- A. Configure the ALB to store logs in an Amazon S3 bucket
- B. Download the files from Amazon S3, and use a spreadsheet application to analyze the logs.
- C. Configure the ALB to push logs to Amazon Kinesis Data Stream
- D. Use Amazon Kinesis Data Analytics to analyze the logs.
- E. Configure Amazon Kinesis Data Streams to stream data from the ALB to Amazon OpenSearch Service (Amazon Elasticsearch Service). Use search operations in Amazon OpenSearch Service (Amazon Elasticsearch Service) to analyze the data.
- F. Configure the ALB to store logs in an Amazon S3 bucket
- G. Use Amazon Athena to analyze the logs in Amazon S3.

Answer: D

Explanation:

The most operationally efficient solution to collect and analyze logs that include the client IP address, target IP address, target port, and user agent of each user that accesses the application would be to configure the ALB to store logs in an Amazon S3 bucket and use Amazon Athena to analyze the logs in Amazon S3 (Option D). This solution allows for quick and easy analysis of log data without requiring manual download or manipulation of log files.

NEW QUESTION 55

A network engineer must provide additional safeguards to protect encrypted data at Application Load Balancers (ALBs) through the use of a unique random session key.

What should the network engineer do to meet this requirement?

- A. Change the ALB security policy to a policy that supports TLS 1.2 protocol only
- B. Use AWS Key Management Service (AWS KMS) to encrypt session keys
- C. Associate an AWS WAF web ACL with the ALB
- D. and create a security rule to enforce forward secrecy (FS)
- E. Change the ALB security policy to a policy that supports forward secrecy (FS)

Answer: D

NEW QUESTION 59

A company has a hybrid cloud environment. The company's data center is connected to the AWS Cloud by an AWS Direct Connect connection. The AWS environment includes VPCs that are connected together in a hub-and-spoke model by a transit gateway. The AWS environment has a transit VIF with a Direct Connect gateway for on-premises connectivity.

The company has a hybrid DNS model. The company has configured Amazon Route 53 Resolver endpoints in the hub VPC to allow bidirectional DNS traffic flow. The company is running a backend application in one of the VPCs.

The company uses a message-oriented architecture and employs Amazon Simple Queue Service (Amazon SQS) to receive messages from other applications over a private network. A network engineer wants to use an interface VPC endpoint for Amazon SQS for this architecture. Client services must be able to access the endpoint service from on premises and from multiple VPCs within the company's AWS infrastructure.

Which combination of steps should the network engineer take to ensure that the client applications can resolve DNS for the interface endpoint? (Choose three.)

- A. Create the interface endpoint for Amazon SQS with the option for private DNS names turned on.
- B. Create the interface endpoint for Amazon SQS with the option for private DNS names turned off.
- C. Manually create a private hosted zone for sqs.us-east-1.amazonaws.co
- D. Add necessary records that point to the interface endpoint
- E. Associate the private hosted zones with other VPCs.
- F. Use the automatically created private hosted zone for sqs.us-east-1.amazonaws.com with previously created necessary records that point to the interface endpoint
- G. Associate the private hosted zones with other VPCs.
- H. Access the SQS endpoint by using the public DNS name sqs.us-east-1.amazonaws.com in VPCs and on premises.
- I. Access the SQS endpoint by using the private DNS name of the interface endpoint.sqs.us-east-1.vpc.amazonaws.com in VPCs and on premises.

Answer: ADF

NEW QUESTION 60

A company has two on-premises data center locations. There is a company-managed router at each data center. Each data center has a dedicated AWS Direct Connect connection to a Direct Connect gateway through a private virtual interface. The router for the first location is advertising 110 routes to the Direct Connect gateway by using BGP, and the router for the second location is advertising 60 routes to the Direct Connect gateway by using BGP. The Direct Connect gateway is attached to a company VPC through a virtual private gateway.

A network engineer receives reports that resources in the VPC are not reachable from various locations in either data center. The network engineer checks the VPC route table and sees that the routes from the first data center location are not being populated into the route table. The network engineer must resolve this issue in the most operationally efficient manner.

What should the network engineer do to meet these requirements?

- A. Remove the Direct Connect gateway, and create a new private virtual interface from each company router to the virtual private gateway of the VPC.
- B. Change the router configurations to summarize the advertised routes.
- C. Open a support ticket to increase the quota on advertised routes to the VPC route table.
- D. Create an AWS Transit Gateway
- E. Attach the transit gateway to the VPC, and connect the Direct Connect gateway to the transit gateway.

Answer: B

Explanation:

"If you advertise more than 100 routes each for IPv4 and IPv6 over the BGP session, the BGP session will go into an idle state with the BGP session DOWN." <https://docs.aws.amazon.com/directconnect/latest/UserGuide/limits.html>

NEW QUESTION 63

An organization is using a VPC endpoint for Amazon S3. When the security group rules for a set of instances were initially configured, access was restricted to allow traffic only to the IP addresses of the Amazon S3 API endpoints in the region from the published JSON file. The application was working properly, but now is logging a growing number of timeouts when connecting with Amazon S3. No internet gateway is configured for the VPC.

Which solution will fix the connectivity failures with the LEAST amount of effort?

- A. Create a Lambda function to update the security group based on AmazonIPSpaceChanged notifications.
- B. Update the VPC routing to direct Amazon S3 prefix-list traffic to the VPC endpoint using the route table APIs.
- C. Update the application server's outbound security group to use the prefix-list for Amazon S3 in the same region.
- D. Create an additional VPC endpoint for Amazon S3 in the same route table to scale the concurrent connections to Amazon.

Answer: C

Explanation:

<https://aws.amazon.com/blogs/aws/subscribe-to-aws-public-ip-address-changes-via-amazon-sns/>

NEW QUESTION 64

A banking company is successfully operating its public mobile banking stack on AWS. The mobile banking stack is deployed in a VPC that includes private subnets and public subnets. The company is using IPv4 networking and has not deployed or supported IPv6 in the environment. The company has decided to adopt a third-party service provider's API and must integrate the API with the existing environment. The service provider's API requires the use of IPv6.

A network engineer must turn on IPv6 connectivity for the existing workload that is deployed in a private subnet. The company does not want to permit IPv6 traffic from the public internet and mandates that the company's servers must initiate all IPv6 connectivity. The network engineer turns on IPv6 in the VPC and in the private subnets.

Which solution will meet these requirements?

- A. Create an internet gateway and a NAT gateway in the VP
- B. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT gateway.
- C. Create an internet gateway and a NAT instance in the VP
- D. Add a route to the existing subnet route tables to point IPv6 traffic to the NAT instance.
- E. Create an egress-only Internet gateway in the VPAdd a route to the existing subnet route tables to point IPv6 traffic to the egress-only internet gateway.
- F. Create an egress-only internet gateway in the VP
- G. Configure a security group that denies all inbound traffic
- H. Associate the security group with the egress-only internet gateway.

Answer: C

NEW QUESTION 67

A company hosts a web application on Amazon EC2 instances behind an Application Load Balancer (ALB). The ALB is the origin in an Amazon CloudFront distribution. The company wants to implement a custom authentication system that will provide a token for its authenticated customers. The web application must ensure that the GET/POST requests come from authenticated customers before it delivers the content. A network engineer must design a solution that gives the web application the ability to identify authorized customers.

What is the MOST operationally efficient solution that meets these requirements?

- A. Use the ALB to inspect the authorized token inside the GET/POST request payload
- B. Use an AWS Lambda function to insert a customized header to inform the web application of an authenticated customer request.
- C. Integrate AWS WAF with the ALB to inspect the authorized token inside the GET/POST request payload
- D. Configure the ALB listener to insert a customized header to inform the web application of an authenticated customer request.
- E. Use an AWS Lambda@Edge function to inspect the authorized token inside the GET/POST request payload
- F. Use the Lambda@Edge function also to insert a customized header to inform the web application of an authenticated customer request.
- G. Set up an EC2 instance that has a third-party packet inspection tool to inspect the authorized token inside the GET/POST request payload
- H. Configure the tool to insert a customized header to inform the web application of an authenticated customer request.

Answer: C

NEW QUESTION 72

An international company provides early warning about tsunamis. The company plans to use IoT devices to monitor sea waves around the world. The data that is collected by the IoT devices must reach the company's infrastructure on AWS as quickly as possible. The company is using three operation centers around the world. Each operation center is connected to AWS through its own AWS Direct Connect connection. Each operation center is connected to the internet through at least two upstream internet service providers.

The company has its own provider-independent (PI) address space. The IoT devices use TCP protocols for reliable transmission of the data they collect. The IoT devices have both landline and mobile internet connectivity. The infrastructure and the solution will be deployed in multiple AWS Regions. The company will use Amazon Route 53 for DNS services.

A network engineer needs to design connectivity between the IoT devices and the services that run in the AWS Cloud.

Which solution will meet these requirements with the HIGHEST availability?

- A. Set up an Amazon CloudFront distribution with origin failover
- B. Create an origin group for each Region where the solution is deployed.
- C. Set up Route 53 latency-based routing
- D. Add latency alias records
- E. For the latency alias records, set the value of Evaluate Target Health to Yes.
- F. Set up an accelerator in AWS Global Accelerator
- G. Configure Regional endpoint groups and health checks.
- H. Set up Bring Your Own IP (BYOIP) addresses
- I. Use the same PI addresses for each Region where the solution is deployed.

Answer: B

Explanation:

<https://aws.amazon.com/blogs/iot/automate-global-device-provisioning-with-aws-iot-core-and-amazon-route-53>

NEW QUESTION 77

A company is deploying a new application in the AWS Cloud. The company wants a highly available web server that will sit behind an Elastic Load Balancer. The load balancer will route requests to multiple target groups based on the URL in the request. All traffic must use HTTPS. TLS processing must be offloaded to the load balancer. The web server must know the user's IP address so that the company can keep accurate logs for security purposes.

Which solution will meet these requirements?

- A. Deploy an Application Load Balancer with an HTTPS listener
- B. Use path-based routing rules to forward the traffic to the correct target group
- C. Include the X-Forwarded-For request header with traffic to the targets.
- D. Deploy an Application Load Balancer with an HTTPS listener for each domain
- E. Use host-based routing rules to forward the traffic to the correct target group for each domain
- F. Include the X-Forwarded-For request header with traffic to the targets.
- G. Deploy a Network Load Balancer with a TLS listener
- H. Use path-based routing rules to forward the traffic to the correct target group
- I. Configure client IP address preservation for traffic to the targets.
- J. Deploy a Network Load Balancer with a TLS listener for each domain
- K. Use host-based routing rules to forward the traffic to the correct target group for each domain
- L. Configure client IP address preservation for traffic to the targets.

Answer: A

Explanation:

An Application Load Balancer (ALB) can be used to route traffic to multiple target groups based on the URL in the request. The ALB can be configured with an HTTPS listener to ensure all traffic uses HTTPS. TLS processing can be offloaded to the ALB, which reduces the load on the web server. Path-based routing rules can be used to route traffic to the correct target group based on the URL in the request. The X-Forwarded-For request header can be included with traffic to the targets, which will allow the web server to know the user's IP address and keep accurate logs for security purposes.

NEW QUESTION 79

A company's network engineer needs to design a new solution to help troubleshoot and detect network anomalies. The network engineer has configured Traffic Mirroring. However, the mirrored traffic is overwhelming the Amazon EC2 instance that is the traffic mirror target. The EC2 instance hosts tools that the company's security team uses to analyze the traffic. The network engineer needs to design a highly available solution that can scale to meet the demand of the mirrored traffic.

Which solution will meet these requirements?

- A. Deploy a Network Load Balancer (NLB) as the traffic mirror target
- B. Behind the NLB
- C. Deploy a fleet of EC2 instances in an Auto Scaling group
- D. Use Traffic Mirroring as necessary.
- E. Deploy an Application Load Balancer (ALB) as the traffic mirror target
- F. Behind the ALB, deploy a fleet of EC2 instances in an Auto Scaling group
- G. Use Traffic Mirroring only during non-business hours.
- H. Deploy a Gateway Load Balancer (GLB) as the traffic mirror target
- I. Behind the GLB
- J. Deploy a fleet of EC2 instances in an Auto Scaling group
- K. Use Traffic Mirroring as necessary.
- L. Deploy an Application Load Balancer (ALB) with an HTTPS listener as the traffic mirror target
- M. Behind the ALB
- N. Deploy a fleet of EC2 instances in an Auto Scaling group
- O. Use Traffic Mirroring only during active events or business hours.

Answer: A

NEW QUESTION 82

A company's network engineer builds and tests network designs for VPCs in a development account. The company needs to monitor the changes that are made to network resources and must ensure strict compliance with network security policies. The company also needs access to the historical configurations of network resources.

Which solution will meet these requirements?

- A. Create an Amazon EventBridge (Amazon CloudWatch Events) rule with a custom pattern to monitor the account for change
- B. Configure the rule to invoke an AWS Lambda function to identify noncompliant resource
- C. Update an Amazon DynamoDB table with the changes that are identified.
- D. Create custom metrics from Amazon CloudWatch log
- E. Use the metrics to invoke an AWS Lambda function to identify noncompliant resource
- F. Update an Amazon DynamoDB table with the changes that are identified.
- G. Record the current state of network resources by using AWS Config
- H. Create rules that reflect the desired configuration setting
- I. Set remediation for noncompliant resources.
- J. Record the current state of network resources by using AWS Systems Manager Inventory
- K. Use Systems Manager State Manager to enforce the desired configuration settings and to carry out remediation for noncompliant resources.

Answer: C

Explanation:

Recording the current state of network resources by using AWS Config would enable auditing and assessment of resource configurations and compliance. Creating rules that reflect the desired configuration settings would enable evaluation of whether the network resources comply with network security policies. Setting remediation for noncompliant resources would enable automatic correction of undesired configurations.

NEW QUESTION 87

A company deploys a new web application on Amazon EC2 instances. The application runs in private subnets in three Availability Zones behind an Application Load Balancer (ALB). Security auditors require encryption of all connections. The company uses Amazon Route 53 for DNS and uses AWS Certificate Manager (ACM) to automate SSL/TLS certificate provisioning. SSL/TLS connections are terminated on the ALB.

The company tests the application with a single EC2 instance and does not observe any problems. However, after production deployment, users report that they can log in but that they cannot use the application. Every new web request restarts the login process.

What should a network engineer do to resolve this issue?

- A. Modify the ALB listener configuration
- B. Edit the rule that forwards traffic to the target group
- C. Change the rule to enable group-level stickiness
- D. Set the duration to the maximum application session length.
- E. Replace the ALB with a Network Load Balancer
- F. Create a TLS listener
- G. Create a new target group with the protocol type set to TLS Register the EC2 instance
- H. Modify the target group configuration by enabling the stickiness attribute.
- I. Modify the ALB target group configuration by enabling the stickiness attribute
- J. Use an application-based cookie
- K. Set the duration to the maximum application session length.
- L. Remove the ALB
- M. Create an Amazon Route 53 rule with a failover routing policy for the application name
- N. Configure ACM to issue certificates for each EC2 instance.

Answer: C

NEW QUESTION 90

A company has been using an outdated application layer protocol for communication among applications. The company decides not to use this protocol anymore and must migrate all applications to support a new protocol. The old protocol and the new protocol are TCP-based, but the protocols use different port numbers. After several months of work, the company has migrated dozens of applications that run on Amazon EC2 instances and in containers. The company believes that all the applications have been migrated, but the company wants to verify this belief. A network engineer needs to verify that no application is still using the old protocol.

Which solution will meet these requirements without causing any downtime?

- A. Use Amazon Inspector and its Network Reachability rules packag
- B. Wait until the analysis has finished running to find out which EC2 instances are still listening to the old port.
- C. Enable Amazon GuardDut
- D. Use the graphical visualizations to filter for traffic that uses the port of the old protoco
- E. Exclude all internet traffic to filter out occasions when the same port is used as an ephemeral port.
- F. Configure VPC flow logs to be delivered into an Amazon S3 bucke
- G. Use Amazon Athena to query the data and to filter for the port number that is used by the old protocol.
- H. Inspect all security groups that are assigned to the EC2 instances that host the application
- I. Remove the port of the old protocol if that port is in the list of allowed port
- J. Verify that the applications are operating properly after the port is removed from the security groups.

Answer: C

Explanation:

Configuring VPC flow logs to be delivered into an Amazon S3 bucket would enable capture of information about the IP traffic going to and from network interfaces within the VPC3. Using Amazon Athena to query the data and to filter for the port number that is used by the old protocol would enable identification of applications that are still using the old protocol.

NEW QUESTION 94

A Network Engineer is provisioning a subnet for a load balancer that will sit in front of a fleet of application servers in a private subnet. There is limited IP space left in the VPC CIDR. The application has few users now but is expected to grow quickly to millions of users.

What design will use the LEAST amount of IP space, while allowing for this growth?

- A. Use two /29 subnets for an Application Load Balancer in different Availability Zones.
- B. Use one /29 subnet for the Network Load Balance
- C. Add another VPC CIDR to the VPC to allow for future growth.
- D. Use two /28 subnets for a Network Load Balancer in different Availability Zones.
- E. Use one /28 subnet for an Application Load Balance
- F. Add another VPC CIDR to the VPC to allow for future growth.

Answer: C

NEW QUESTION 98

A company uses a 4 Gbps AWS Direct Connect dedicated connection with a link aggregation group (LAG) bundle to connect to five VPCs that are deployed in the us-east-1 Region. Each VPC serves a different business unit and uses its own private VIF for connectivity to the on-premises environment. Users are reporting slowness when they access resources that are hosted on AWS.

A network engineer finds that there are sudden increases in throughput and that the Direct Connect connection becomes saturated at the same time for about an hour each business day. The company wants to know which business unit is causing the sudden increase in throughput. The network engineer must find out this information and implement a solution to resolve the problem.

Which solution will meet these requirements?

- A. Review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observe
- B. Create a new 10 Gbps dedicated connectio
- C. Shift traffic from the existing dedicated connection to the new dedicated connection.
- D. Review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observe
- E. Upgrade the bandwidth of the existing dedicated connection to 10 Gbps.
- F. Review the Amazon CloudWatch metrics for ConnectionBpsIngress and ConnectionPpsEgress to determine which VIF is sending the highest throughput during the period in which slowness is observe
- G. Upgrade the existing dedicated connection to a 5 Gbps hosted connection.
- H. Review the Amazon CloudWatch metrics for ConnectionBpsIngress and ConnectionPpsEgress to determine which VIF is sending the highest throughput during the period in which slowness is observed.Create a new 10 Gbps dedicated connectio
- I. Shift traffic from the existing dedicated connection to the new dedicated connection.

Answer: A

Explanation:

To meet the requirements of finding out which business unit is causing the sudden increase in throughput and resolving the problem, the network engineer should review the Amazon CloudWatch metrics for VirtualInterfaceBpsEgress and VirtualInterfaceBpsIngress to determine which VIF is sending the highest throughput during the period in which slowness is observed (Option B). After identifying the VIF that is causing the issue, they can upgrade the bandwidth of the existing dedicated connection to 10 Gbps to resolve the problem (Option B).

NEW QUESTION 99

A company has deployed an application in a VPC that uses a NAT gateway for outbound traffic to the internet. A network engineer notices a large quantity of suspicious network traffic that is traveling from the VPC over the internet to IP addresses that are included on a deny list. The network engineer must implement a solution to determine which AWS resources are generating the suspicious traffic. The solution must minimize cost and administrative overhead.

Which solution will meet these requirements?

- A. Launch an Amazon EC2 instance in the VP
- B. Use Traffic Mirroring by specifying the NAT gateway as the source and the EC2 instance as the destinatio

- C. Analyze the captured traffic by using open-source tools to identify the AWS resources that are generating the suspicious traffic.
- D. Use VPC flow log
- E. Launch a security information and event management (SIEM) solution in the VP
- F. Configure the SIEM solution to ingest the VPC flow log
- G. Run queries on the SIEM solution to identify the AWS resources that are generating the suspicious traffic.
- H. Use VPC flow log
- I. Publish the flow logs to a log group in Amazon CloudWatch Log
- J. Use CloudWatch Logs Insights to query the flow logs to identify the AWS resources that are generating the suspicious traffic.
- K. Configure the VPC to stream the network traffic directly to an Amazon Kinesis data stream
- L. Send the data from the Kinesis data stream to an Amazon Kinesis Data Firehose delivery stream to store the data in Amazon S3. Use Amazon Athena to query the data to identify the AWS resources that are generating the suspicious traffic.

Answer: C

NEW QUESTION 101

A company has multiple AWS accounts. Each account contains one or more VPCs. A new security guideline requires the inspection of all traffic between VPCs. The company has deployed a transit gateway that provides connectivity between all VPCs. The company also has deployed a shared services VPC with Amazon EC2 instances that include IDS services for stateful inspection. The EC2 instances are deployed across three Availability Zones. The company has set up VPC associations and routing on the transit gateway. The company has migrated a few test VPCs to the new solution for traffic inspection. Soon after the configuration of routing, the company receives reports of intermittent connections for traffic that crosses Availability Zones. What should a network engineer do to resolve this issue?

- A. Modify the transit gateway VPC attachment on the shared services VPC by enabling cross-Availability Zone load balancing.
- B. Modify the transit gateway VPC attachment on the shared services VPC by enabling appliance mode support.
- C. Modify the transit gateway by selecting VPN equal-cost multi-path (ECMP) routing support.
- D. Modify the transit gateway by selecting multicast support.

Answer: B

Explanation:

To resolve the issue of intermittent connections for traffic that crosses Availability Zones after configuring routing for traffic inspection between VPCs using a transit gateway and EC2 instances with IDS services in a shared services VPC, a network engineer should modify the transit gateway VPC attachment on the shared services VPC by enabling appliance mode support (Option B). This will ensure that traffic is routed to the same EC2 instance for stateful inspection and prevent intermittent connections.

NEW QUESTION 106

An organization is replacing a tape backup system with a storage gateway. there is currently no connectivity to AWS. Initial testing is needed. What connection option should the organization use to get up and running at minimal cost?

- A. Use an internet connection.
- B. Set up an AWS VPN connection.
- C. Provision an AWS Direct Connection private virtual interface.
- D. Provision a Direct Connect public virtual interface.

Answer: A

NEW QUESTION 111

A security team is performing an audit of a company's AWS deployment. The security team is concerned that two applications might be accessing resources that should be blocked by network ACLs and security groups. The applications are deployed across two Amazon Elastic Kubernetes Service (Amazon EKS) clusters that use the Amazon VPC Container Network Interface (CNI) plugin for Kubernetes. The clusters are in separate subnets within the same VPC and have a Cluster Autoscaler configured.

The security team needs to determine which POD IP addresses are communicating with which services throughout the VPC. The security team wants to limit the number of flow logs and wants to examine the traffic from only the two applications.

Which solution will meet these requirements with the LEAST operational overhead?

- A. Create VPC flow logs in the default format
- B. Create a filter to gather flow logs only from the EKS nodes. Include the srcaddr field and the dstaddr field in the flow logs.
- C. Create VPC flow logs in a custom format
- D. Set the EKS nodes as the resource. Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.
- E. Create VPC flow logs in a custom format
- F. Set the application subnets as resource
- G. Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.
- H. Create VPC flow logs in a custom format
- I. Create a filter to gather flow logs only from the EKS nodes. Include the pkt-srcaddr field and the pkt-dstaddr field in the flow logs.

Answer: D

NEW QUESTION 112

A retail company is running its service on AWS. The company's architecture includes Application Load Balancers (ALBs) in public subnets. The ALB target groups are configured to send traffic to backend Amazon EC2 instances in private subnets. These backend EC2 instances can call externally hosted services over the internet by using a NAT gateway.

The company has noticed in its billing that NAT gateway usage has increased significantly. A network engineer needs to find out the source of this increased usage.

Which options can the network engineer use to investigate the traffic through the NAT gateway? (Choose two.)

- A. Enable VPC flow logs on the NAT gateway's elastic network interface
- B. Publish the logs to a log group in Amazon CloudWatch Log
- C. Use CloudWatch Logs Insights to query and analyze the logs.
- D. Enable NAT gateway access log

- E. Publish the logs to a log group in Amazon CloudWatch Log
- F. Use CloudWatch Logs Insights to query and analyze the logs.
- G. Configure Traffic Mirroring on the NAT gateway's elastic network interface
- H. Send the traffic to an additional EC2 instance
- I. Use tools such as tcpdump and Wireshark to query and analyze the mirrored traffic.
- J. Enable VPC flow logs on the NAT gateway's elastic network interface
- K. Publish the logs to an Amazon S3 bucket
- L. Create a custom table for the S3 bucket in Amazon Athena to describe the log structure
- M. Use Athena to query and analyze the logs.
- N. Enable NAT gateway access log
- O. Publish the logs to an Amazon S3 bucket
- P. Create a custom table for the S3 bucket in Amazon Athena to describe the log structure
- Q. Use Athena to query and analyze the logs.

Answer: AD

Explanation:

To investigate the increased usage of a NAT gateway in a VPC architecture with ALBs and backend EC2 instances, a network engineer can use the following options:

➤ Enable VPC flow logs on the NAT gateway's elastic network interface and publish the logs to a log group in Amazon CloudWatch Logs. Use CloudWatch Logs Insights to query and analyze the logs.

(Option A)

➤ Enable VPC flow logs on the NAT gateway's elastic network interface and publish the logs to an Amazon S3 bucket. Create a custom table for the S3 bucket in Amazon Athena to describe the log structure and use Athena to query and analyze the logs. (Option D)

These options allow for detailed analysis of traffic through the NAT gateway to identify the source of increased usage.

NEW QUESTION 113

A network engineer has deployed an Amazon EC2 instance in a private subnet in a VPC. The VPC has no public subnet. The EC2 instance hosts application code that sends messages to an Amazon Simple Queue Service (Amazon SQS) queue. The subnet has the default network ACL with no modification applied. The EC2 instance has the default security group with no modification applied.

The SQS queue is not receiving messages.

Which of the following are possible causes of this problem? (Choose two.)

- A. The EC2 instance is not attached to an IAM role that allows write operations to Amazon SQS.
- B. The security group is blocking traffic to the IP address range used by Amazon SQS
- C. There is no interface VPC endpoint configured for Amazon SQS
- D. The network ACL is blocking return traffic from Amazon SQS
- E. There is no route configured in the subnet route table for the IP address range used by Amazon SQS

Answer: CE

NEW QUESTION 118

A government contractor is designing a multi-account environment with multiple VPCs for a customer. A network security policy requires all traffic between any two VPCs to be transparently inspected by a third-party appliance.

The customer wants a solution that features AWS Transit Gateway. The setup must be highly available across multiple Availability Zones, and the solution needs to support automated failover. Furthermore, asymmetric routing is not supported by the inspection appliances.

Which combination of steps is part of a solution that meets these requirements? (Choose two.)

- A. Deploy two clusters that consist of multiple appliances across multiple Availability Zones in a designated inspection VPC
- B. Connect the inspection VPC to the transit gateway by using a VPC attachment
- C. Create a target group, and register the appliances with the target group
- D. Create a Network Load Balancer (NLB), and set it up to forward to the newly created target group
- E. Configure a default route in the inspection VPC's transit gateway subnet toward the NLB.
- F. Deploy two clusters that consist of multiple appliances across multiple Availability Zones in a designated inspection VPC
- G. Connect the inspection VPC to the transit gateway by using a VPC attachment
- H. Create a target group, and register the appliances with the target group
- I. Create a Gateway Load Balancer, and set it up to forward to the newly created target group
- J. Configure a default route in the inspection VPC's transit gateway subnet toward the Gateway Load Balancer endpoint.
- K. Configure two route tables on the transit gateway
- L. Associate one route table with all the attachments of the application VPC
- M. Associate the other route table with the inspection VPC's attachments
- N. Propagate all VPC attachments into the inspection route table
- O. Define a static default route in the application route table
- P. Enable appliance mode on the attachment that connects the inspection VPC.
- Q. Configure two route tables on the transit gateway
- R. Associate one route table with all the attachments of the application VPC
- S. Associate the other route table with the inspection VPC's attachments
- T. Propagate all VPC attachments into the application route table
- . Define a static default route in the inspection route table
- . Enable appliance mode on the attachment that connects the inspection VPC.
- . Configure one route table on the transit gateway
- . Associate the route table with all the VPC
- . Propagate all VPC attachments into the route table
- . Define a static default route in the route table.

Answer: BC

NEW QUESTION 123

A company is running multiple workloads on Amazon EC2 instances in public subnets. In a recent incident, an attacker exploited an application vulnerability on one of the EC2 instances to gain access to the instance. The company fixed the application and launched a replacement EC2 instance that contains the updated application.

The attacker used the compromised application to spread malware over the internet. The company became aware of the compromise through a notification from AWS. The company needs the ability to identify when an application that is deployed on an EC2 instance is spreading malware.

Which solution will meet this requirement with the LEAST operational effort?

- A. Use Amazon GuardDuty to analyze traffic patterns by inspecting DNS requests and VPC flow logs.
- B. Use Amazon GuardDuty to deploy AWS managed decoy systems that are equipped with the most recent malware signatures.
- C. Set up a Gateway Load Balance
- D. Run an intrusion detection system (IDS) appliance from AWS Marketplace on Amazon EC2 for traffic inspection.
- E. Configure Amazon Inspector to perform deep packet inspection of outgoing traffic.

Answer: A

Explanation:

This solution involves using Amazon GuardDuty to monitor network traffic and analyze DNS requests and VPC flow logs for suspicious activity. This will allow the company to identify when an application is spreading malware by monitoring the network traffic patterns associated with the instance. GuardDuty is a fully managed threat detection service that continuously monitors for malicious activity and unauthorized behavior in your AWS accounts and workloads. It requires minimal setup and configuration and can be integrated with other AWS services for automated remediation. This solution requires the least operational effort compared to the other options

NEW QUESTION 125

Your security team implements a host-based firewall on all of your Amazon Elastic Compute Cloud (EC2) instances to block all outgoing traffic. Exceptions must be requested for each specific requirement. Until you request a new rule, you cannot access the instance metadata service. Which firewall rule should you request to be added to your instances to allow instance metadata access?

- A. Inbound; Protocol tcp; Source [Instance's EIP]; Destination 169.254.169.254
- B. Inbound; Protocol tcp; Destination 169.254.169.254; Destination port 80
- C. Outbound; Protocol tcp; Destination 169.254.169.254; Destination port 80
- D. Outbound; Protocol tcp; Destination 169.254.169.254; Destination port 443

Answer: C

Explanation:

<https://docs.aws.amazon.com/AWSEC2/latest/UserGuide/instancedata-data-retrieval.html>

To view all categories of instance metadata from within a running instance, use the following URI.

<http://169.254.169.254/latest/meta-data/>

NEW QUESTION 130

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

ANS-C01 Practice Exam Features:

- * ANS-C01 Questions and Answers Updated Frequently
- * ANS-C01 Practice Questions Verified by Expert Senior Certified Staff
- * ANS-C01 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * ANS-C01 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The ANS-C01 Practice Test Here](#)