

Exam Questions 1z0-083

Oracle Database Administration II

<https://www.2passeasy.com/dumps/1z0-083/>



NEW QUESTION 1

Which two are true about RMAN backups when using a media manager to write backups to tape when there are only two tape drives? (Choose two.)

- A. SBT tape compression can be used even if no RMAN compression is configured.
- B. Any backup set written to the SBT device in this configuration can contain a maximum of two backup pieces.
- C. Any backup written to the SBT device in this configuration can contain a maximum of two backup sets.
- D. SBT tape compression and RMAN backup compression should be used in parallel.
- E. The SBT device should be configured to use PARALLELISM 2 to allow both tape drive to be used simultaneously.

Answer: DE

NEW QUESTION 2

A database is configured in ARCHIVELOG mode.

Full RMAN backups are taken and no backup to trace has been taken of the control file. A media failure has occurred.

In which two scenarios is complete recovery possible? (Choose two.)

- A. when any archived log from, before, or after the most recent backup is corrupt.
- B. after losing all copies of the control file
- C. after losing an archived log from after the most recent backup
- D. after losing an archived log from before the most recent backup
- E. after losing the SYSTEM tablespace

Answer: DE

NEW QUESTION 3

Which three are true in Oracle 19c and later releases? (Choose three.)

- A. If the password file location changes, then the new location is used automatically by the Oracle Server.
- B. Schema Only accounts can be granted administrator privileges.
- C. All the Oracle-supplied accounts are Schema Only accounts.
- D. Privilege Analysis is included in Oracle Enterprise Edition and no longer requires Database Vault.
- E. Unified Auditing can be configured to audit only events that are issued indirectly by an audited user.
- F. Unified Auditing can be configured to audit only events that are issued directly by an audited user.

Answer: BCD

NEW QUESTION 4

A user complains about poor database performance.

You want to verify if the user's session has waited for certain types of I/O activity. Which view displays all waits waited on by a session at least once?

- A. V\$SESSION_EVENT
- B. V\$SESSTAT
- C. V\$SESSION_WAIT
- D. V\$SESSION_WAIT_CLASS
- E. V\$SESSION

Answer: A

NEW QUESTION 5

On the 10th of August, you implement an incremental database backup strategy and configure a recovery window of five days.

Level 0 backups are taken on the 10th, 17th, and 24th of August.

Differential level 1 incremental backups are taken daily between the level 0 backups. Today is the 26th of August.

Which backups will be obsolete?

- A. all backups prior to 10th of August
- B. all backups prior to 22nd of August
- C. all backups prior to 24th of August
- D. all backups prior to 20th of August
- E. all backups prior to 17th of August

Answer: C

NEW QUESTION 6

Which two are true about duplicating pluggable databases (PDBs) with RMAN? (Choose two.)

- A. Two or more PDBs can be duplicated with the same RMAN DUPLICATE command.
- B. All tablespaces belonging to a PDB must be duplicated when duplicating the PDB.
- C. The auxiliary instance is automatically created with ENABLE_PLUGGABLE_DATABASE = TRUE.
- D. A user with SYSDBA or SYSBACKUP must be logged in with RMAN to the PDB to duplicate it.
- E. CDB\$ROOT and PDB\$SEED are automatically duplicated.

Answer: CD

NEW QUESTION 7

Examine this command:

\$ rhpctl move database –sourcehome Oracle_home_path –destinationhome Oracle_home_path For which two purposes can you use this command? (Choose two.)

- A. to switch an existing Oracle Database home to a newer release of Oracle software on the same server
- B. to switch to a read-only Oracle home
- C. to switch back to the previous Oracle home as part of a rollback operation
- D. to switch the Oracle Database home when using a centralized Rapid Home Provisioning server
- E. to switch to a patched Oracle Database home

Answer: CE

Explanation:

You can use rhpctl move gihome command with the same syntax to switch from the current Oracle Grid Infrastructure home to a patched home. The rhpctl command enables you to switch from your current Oracle Grid Infrastructure or Oracle Database home to patched Oracle home so that you can provision the new Oracle home as gold image. You can also use the rhpctl command to switch back to the old Oracle home, if you want to roll back the operation.

NEW QUESTION 8

Which two are true about RMAN encryption? (Choose two.)

- A. RMAN encryption keys are stored in a database keystore.
- B. RMAN can encrypt the Oracle Database password file.
- C. Dual-mode encrypted backups can be restored only if both the password and the keystore used for encryption are available.
- D. The SET ENCRYPTION command overrides encryption settings specified by the CONFIGURE ENCRYPTION command.
- E. Password encryption can be persistently configured using the CONFIGURE ENCRYPTION command.

Answer: CD

NEW QUESTION 9

Which two are true about RMAN duplexed backup sets? (Choose two.)

- A. A duplexed backup set uses the same number of SBT channels as a non-duplexed backup set for the same number of files.
- B. A non-duplexed backup set written to disk can be duplexed to disk by backing up the backup set that is already on disk.
- C. A non-duplexed backup set written to SBT can be duplexed to tape by backing up the backup set that is already on tape.
- D. A non-duplexed backup set written to disk can be duplexed to tape by backing up the backup set that is already on disk.
- E. A non-duplexed backup set written to SBT can be duplexed to disk by backing up the backup set that is already on tape.
- F. A duplexed backup set always uses twice as many SBT channels as a non-duplexed backup set for the same number of files.

Answer: DF

NEW QUESTION 10

Which four are true about performing Tablespace Point -In-Time Recovery (TSPITR) using Recovery Manager (RMAN)?

- A. It can be performed using an auxiliary instance managed by a DBA.
- B. It can be used to recover a truncated table.
- C. RMAN automatically adds any required tablespaces to the recovery set to make it self-contained.
- D. RMAN always includes tablespaces containing undo segments in the recovery set.
- E. It can be performed repeatedly until the correct time is found without using an RMAN catalog.
- F. flashback database must be enabled for it to work.
- G. It can be used to recover a dropped tablespace.
- H. It can be performed using an auxiliary instance managed by RMAN.

Answer: AEFH

NEW QUESTION 10

Which three are true about requirements for various FLASHBACK operations? (Choose three.)

- A. FLASHBACK transaction query requires undo to retrieve all versions of a row that existed between two points in time.
- B. FLASHBACK drop requires that the RECYCLEBIN parameter be set to ON.
- C. FLASHBACK version query requires that the RECYCLEBIN parameter be set to ON.
- D. FLASHBACK DATA ARCHIVE requires undo to store all versions of all rows of a table being tracked.
- E. FLASHBACK drop requires undo to retrieve all versions of a row that existed between two points in time.
- F. FLASHBACK version query requires undo to retrieve all versions of a row that existed between two points in time.

Answer: ABF

NEW QUESTION 15

Which two are true about instance recovery? (Choose two.)

- A. It is not possible if an archived log is missing.
- B. It is performed automatically after the database is opened; however, blocks requiring recovery are not available until they are recovered.
- C. Setting FAST_START_MTTR_TARGET to a lower value reduces instance recovery time by causing dirty buffers to be written to disk more frequently, thereby reducing the number of I/Os needed during instance recovery.
- D. It is performed by the Recovery Writer (RVWR) background process.
- E. Setting FAST_START_MTTR_TARGET to a higher value reduces instance recovery time by causing the log writer to write more frequently, thereby reducing the number of I/Os needed during instance recovery.
- F. It is performed automatically while the database remains in MOUNT state.
- G. Then the database is opened.

Answer: EF

NEW QUESTION 18

Automatic Shared Memory Management is disabled for one of your database instances. SomeSQL statements perform poorly due to excessive hard parse activity, thereby degrading performance. What would be your next step?

- A. Run the SQL Access Advisor.
- B. Run the Memory Advisor for the shared pool.
- C. Run the SQL Tuning Advisor.
- D. Run theMemory Advisor for the Program Global Area.
- E. Run the Memory Advisor for the System Global Area.

Answer: B

NEW QUESTION 19

Oracle Managed Files (OMF) is enabled in a CDB and thiscommand is successfully executed:

```
CREATE PLUGGABLE DATABASE app1
  AS APPLICATION CONTAINER
  ADMIN USER admin1 IDENTIFIED BY app_123 ROLES=(CONNECT);
```

Which three are true? (Choose three.)

- A. Application PDBs that are subsequently created in the APP1 application container will be cloned from APP1\$SEED.
- B. An application seed PDB is created for APP1.
- C. An application root PDB is created for APP1.
- D. A default service is created for the application root APP1.
- E. Application PDBs that are subsequently created in the APP1 application container will be cloned from PDB\$SEED.
- F. APP1 can never be unplugged.

Answer: ABE

NEW QUESTION 20

YourSALES_ROOTApplication container has two application PDBs. TheSALES_APPApplication has a common table,FIN.REVENUE, in the two PDBs. Examine this query and its output:

```
SELECT containers_default, container_map, table_name
  FROM dba_tables WHERE owner='FIN';
```

CONTAINERS_DEFAULT	CONTAINER_MAP	CONTAINER_MAP_OBJECT	TABLE_NAME
NO	YES	NO	REVENUE
NO	NO	YES	MAPTABLE

Which two are true? (Choose two.)

- A. The CONTAINERS clause cannot be used in queries on the REVENUEtable.
- B. The REVENUE table must be a list-partitioned table.
- C. The MAPTABLE tables defines a logical partition key on a commonly used column for the REVENUE table.
- D. The MAPTABLE table is a metadata-linked table.
- E. A container map exists for theREVENUE table, but is not enabled.
- F. The REVENUE table partitions are not pruned across the PDBs automatically.

Answer: CE

NEW QUESTION 25

Which three are true In Oracle 19c and later releases?

- A. Tablespaces always remain In read/write mode during transportable tablespace operations.
- B. Simultaneous data pump jobs can be limited at thepluggable database (PDB) level.
- C. Tablespaces never remain In read/write mode during transportable tablespace operations.
- D. An ordinary data pump export of a table with encrypted columns will always encrypt the same columns when imported.
- E. A transportable data pump import can leave a plugged-in tablespace in read-only mode.
- F. A transportable data pump import can leave a plugged-in tablespace In read/write mode.

Answer: ADE

NEW QUESTION 26

A database is configured in ARCHIVELOG mode.

A full RMAN backup exists but no control file backup to trace has been taken. A mediafailure has occurred. In which two scenarios is incomplete recovery required? (Choose two.)

- A. after losing a SYSAUX tablespace data file
- B. after losing all members of an INACTIVE online redo log group
- C. after losing all members of the CURRENT onlineredo log group
- D. after losing all copies of the control file
- E. after losing an UNDO tablespace that is in use

Answer: BD

NEW QUESTION 31

Which three are true about the SQL Tuning Advisor? (Choose three.)

- A. It checks each query being analyzed for stale statistics.
- B. It checks each query being analyzed for missing statistics.
- C. It only recommends syntactic changes to SQL statements.
- D. It can recommend semantic changes to SQL statements.
- E. It considers all SQL statements being analyzed by the advisor task as a group.
- F. It builds SQL profiles for each poorly performing SQL statement to prevent regressions.

Answer: ABF

NEW QUESTION 33

Which two are true about the execution of operating system scripts starting from Oracle Database 19c? (Choose two.)

- A. oraInstRoot.sh can be executed automatically by the Database installer by using sudo or root credentials.
- B. root.sh can be executed automatically by the Database Installer only if it is provided with root credentials.
- C. The sudo password can be specified in a response file.
- D. root.sh can be executed automatically by the Database installer only by using sudo credentials.
- E. The sudo password must be specified in a response file.
- F. The root password cannot be specified in a response file.

Answer: AF

NEW QUESTION 37

Which three are true about Oracle Grid Infrastructure for a Standalone Server?

- A. It includes both Oracle Restart and Oracle Automatic Storage Management (ASM) software.
- B. It creates one disk group during installation.
- C. It requires the operating system oracle_base environment variable to be predefined before installation.
- D. It requires Oracle ASM Filter Driver (ASMD) to manage Automatic Storage Management (ASM) disks.
- E. It requires Oracle ASMLib to manage Automatic Storage Management (ASM) disks.
- F. Automatic Storage Management (ASM) requires that O/S groups OSASM and OSDBA be assigned as secondary groups for its installation owner.

Answer: ABD

NEW QUESTION 39

You are managing this configuration:

- CDB1 is a container database.
- PDB1 and PDB2 are two pluggable databases in CDB1.
- USER1.EMP is a table in PDB1 and USER2.DEPT is a table in PDB2.

CDB1 user SYS executes these commands after connecting successfully to PDB2:

```
SQL> ALTER SESSION SET CONTAINER=pdb1;  
Session altered.
```

```
SQL> INSERT INTO user1.emp VALUES(100, 'Alan', 1);  
1 row created.
```

```
SQL> INSERT INTO user1.emp VALUES(101, 'Ben', 1);  
1 row created.
```

```
SQL> ALTER SESSION SET CONTAINER=pdb2;  
Session altered.
```

```
SQL> INSERT INTO user2.dept VALUES(1, 'IT');
```

Which two are true? (Choose two.)

- A. The inserts on USER1.EMP remain uncommitted when the session connected to PDB2.
- B. The inserts on USER1.EMP were committed when the session inserted a row into USER2.DEPT.
- C. The insert on USER2.DEPT fails because of the active transaction in the parent container.
- D. The insert on USER2.DEPT is a recursive autonomous transaction by the child session and is committed.
- E. The inserts on USER1.EMP were rolled back when the session connected to PDB2.
- F. The insert on USER2.DEPT is uncommitted.
- G. The inserts on USER1.EMP were committed when the session connected to PDB2.

Answer: FG

NEW QUESTION 42

Which two are true about diagnosing Oracle Database failure situations using Data Recovery Advisor? (Choose two.)

- A. Using the Data Recovery Advisor LIST FAILURE command always requires that the database for which failures are to be listed is in MOUNT state.

- B. A failure can be closed only when it has been repaired.
- C. Data Recovery Advisor can be used if a database is closed.
- D. The Data Recovery Advisor CHANGE FAILURE command can be used only to change failure priorities.
- E. Data Recovery Advisor can proactively check for failures.

Answer: DE

NEW QUESTION 47

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 1z0-083 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 1z0-083 Product From:

<https://www.2passeasy.com/dumps/1z0-083/>

Money Back Guarantee

1z0-083 Practice Exam Features:

- * 1z0-083 Questions and Answers Updated Frequently
- * 1z0-083 Practice Questions Verified by Expert Senior Certified Staff
- * 1z0-083 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 1z0-083 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year