

1Y0-230 Dumps

Citrix NetScaler 12 Essentials and Unified Gateway

<https://www.certleader.com/1Y0-230-dumps.html>



NEW QUESTION 1

Scenario: A NetScaler Gateway provides ICA Proxy to an internal XenDesktop site in an environment. The security team wants the Citrix Administrator to configure the NetScaler to block client drives if the client device fails a security scan.

Which NetScaler feature allows the administrator to satisfy the security team's requirements without making changes to the XenDesktop configuration?

- A. Traffic Policy
- B. Smart Access
- C. SmartControl
- D. Authorization Policy

Answer: D

NEW QUESTION 2

A Citrix Administrator needs to configure single sign-on to a StoreFront server using an external, secure single URL.

Which type of virtual server can the administrator use to meet this requirement?

- A. Load Balancing
- B. Content Switching
- C. VPN
- D. Unified Gateway

Answer: D

NEW QUESTION 3

Which setting can a Citrix Administrator use to reduce server load, improve response time and increase the number of SSL transactions per second on a SSL virtual server created with default settings?

- A. Session Reuse
- B. SSLv3
- C. Session Timeout
- D. SSLv2 Redirect

Answer: C

NEW QUESTION 4

Which two options would provide an end-to-end encryption data, while allowing the NetScaler to optimize the responses? (Choose two.)

- A. HTTP protocol for the virtual server
- B. SSL Bridge protocol for the virtual server
- C. HTTP protocol for the services
- D. SSL protocol for the virtual server
- E. SSL protocol for the services
- F. SSL Bridge protocol for the services

Answer: AB

NEW QUESTION 5

Scenario: A Citrix Administrator is concerned about the amount of health checks the NetScaler is sending the back-end resources. The administrator would like to find a way to remove health checks from specific bound services.

How can the administrator accomplish this?

- A. Use reverse condition monitoring.
- B. Use Service Groups to minimize health checks.
- C. Unbind the current monitor.
- D. Use the No-Monitor Option.

Answer: C

NEW QUESTION 6

Scenario: A Citrix Administrator is evaluating the following policies in an environment.

Policy A:	Priority 2	Bound at the Global Default level
Policy B:	Priority 15	Bound at the User level
Policy C:	Priority 18	Bound at the Group level
Policy D:	priority 7	Bound at the Virtual Server Level

Which policy will take effect in the event of a policy conflict?

- A. Policy B
- B. Policy A
- C. Policy D
- D. Policy C

Answer: D

NEW QUESTION 7

Scenario: A Citrix Administrator needs to create local user accounts for other administrators with limited privileges. The other administrators will need only:

-Read-only access

-The ability to enable and disable services and servers

Which built-in Command Policy permission level can the administrator use?

- A. Network
- B. Operator
- C. Sysadmin
- D. Read-Only

Answer: B

NEW QUESTION 8

Which two components need to be configured for SmartAccess? (Choose two.)

- A. Configuration logging
- B. XenDesktop policies
- C. XML Trust
- D. StoreFront server groups

Answer: CD

NEW QUESTION 9

Which three pieces of information are required for a NetScaler Unified Gateway deployment? (Choose three.)

- A. Valid SSL Certificates
- B. Secondary Authentication for the Unified Gateway
- C. Enterprise license or higher
- D. Content Switching virtual server
- E. Multiple IP addresses for User Access

Answer: ACD

NEW QUESTION 10

A Citrix Administrator needs to configure a NetScaler high availability (HA) pair with both NetScalers in different subnets.

What does the administrator need to do for the HA pair to work in different subnets?

- A. Configure Sync VLAN
- B. Turn on HA Monitoring on all Interfaces
- C. Turn on Fail-safe Mode
- D. Turn on Independent Network Configuration (INC) mode

Answer: D

NEW QUESTION 10

TCP multiplexing is a technique that enables the reuse of existing TCP connections

Which NetScaler hardware or software platform offers a Multi-Tenant solution?

- A. VPX
- B. CPX
- C. MPX
- D. SDX

Answer: D

NEW QUESTION 12

Scenario: A Citrix Administrator configured the “-denySSLReneg” Parameter using the below command on NetScaler to enhance security.

set ssl parameter -denySSLReneg <option>

Which two options can the administrator use to complete the command (Choose two.)

- A. NO
- B. NONSECURE
- C. ALL
- D. HIGHSECURE
- E. FRONTEND_CLIENT

Answer: AB

NEW QUESTION 14

Which three statements are true when comparing a Simple Access Control List (ACL) to an Extended ACL? (Choose three.)

- A. Extended ACLs have priorities
- B. Simple ACLs can be modified
- C. Extended ACLs apply first
- D. Simple ACLs can be based on the Source and Destination IP address
- E. Simple ACLs can bridge traffic

- F. Simple ACLs are based on the Source IP address only
- G. Simple ACLs apply first

Answer: ADG

NEW QUESTION 19

Which NetScaler Access Control List (ACL) command can a Citrix Administrator use to bridge traffic originating from 192.168.10.200?

- A. add ns acl
- B. add ns simpleacl
- C. add ns acl6
- D. add ns simpleacl6

Answer: D

NEW QUESTION 20

Which two options should a Citrix Administrator consider when adding a secondary device in a high availability (HA) pair? (Choose two.)

- A. The Independent Network Configuration (INC) mode should be enabled.
- B. Both the devices should have different SNIP addresses.
- C. The nsroot password should be the same on both nodes.
- D. HA Monitoring should be disabled on all the unused interfaces.
- E. Configure the HA status of the Primary Node as STAYPRIMARY.

Answer: CD

NEW QUESTION 24

Scenario: A NetScaler has two interfaces as 1/1 and 1/2 with MAC-based Forwarding enabled. Below are the specifications:

-Interface 1/1 and IP 192.168.10.10 is bound to VLAN 10.

-On Interface 1/2 VLAN 20 and VLAN 30 are tagged.

-VLAN 20 is bound to IP 192.168.20.10 and VLAN 30 is bound to 192.168.30.10 The NetScaler receives a packet for VIP 192.168.30.30 on interface 1/1.

Which interface of NetScaler will send a reply back in this environment?

- A. Interface 1/1
- B. NetScaler will drop the packet received on interface 1/1
- C. Interface 1/2
- D. Netscaler will reply on interfaces 1/1 and 1/2

Answer: D

NEW QUESTION 27

Scenario: A Citrix Administrator manages an environment that has an externally accessible website. The administrator would like to provide end-to-end encryption and use features such as caching and compression on the NetScaler.

Which setting in SSL offload should the administrator configure to meet this requirement?

- A. SSL_TCP front-end, TCP back-end
- B. SSL front-end, HTTP back-end
- C. SSL_TCP front-end, SSL_TCP back-end
- D. SSL front-end, SSL back-end

Answer: C

NEW QUESTION 31

Scenario: A Citrix Administrator entered the command-line interface commands below to prevent IP address 10.10.100 from accessing the NetScaler on port 80.

```
add simpleacl rule1 DENY- srcIP 10.10.10.100 -TTL 600 add simpleacl rule2 DENY- srcIP 10.10.10.100 -destPort 80 add ns acl rule1 DENY- srcIP 10.10.10.100-priority 10
```

```
add ns acl rule2 DENY- srcIP 10.10.10.100-priority 100 apply ns acls
```

Which Access Control List (ACL) will the NetScaler use to deny the IP address?

- A. add ns acl rule1 DENY-srcIP 10.10.10.100-priority 10
- B. add simpleacl rule1 DENY- srcIP 10.10.10.100 -TTL 600
- C. add simpleacl rule2 DENY- srcIP 10.10.10.100 -destPort 80
- D. add ns acl rule2 DENY- srcIP 10.10.10.100-priority 100

Answer: B

NEW QUESTION 34

Scenario: Client connects to certain virtual servers are abnormally high. A Citrix Administrator needs to be alerted whatever the connections pass a certain threshold.

How can the administrator use NetScaler Management and Analytics System (MAS) to accomplish this requirement?

- A. Configure SMTP Reporting on the NetScaler MAS by adding the threshold and email address.
- B. Configure specific alerts for virtual servers using NetScaler MAS.
- C. Configure TCP Insight on the NetScaler MAS.
- D. Configure Network Reporting on the NetScaler MAS by setting the threshold and email address.

Answer: D

NEW QUESTION 39

A Citrix Administrator receives user complaints about latency while accessing an application that is being load-balanced on the NetScaler. Which tool can the administrator use to gather information regarding Response time, Client latency and Server-side processing time?

- A. aaad.debug
- B. WAN Insight
- C. NetScaler Management and Analytics System (MAS)
- D. HDX Insight

Answer: D

NEW QUESTION 41

After creating and correctly configuring a custom user monitor, from where do the monitor probes originate by default?

- A. Subnet IP address
- B. NetScaler IP address
- C. Mapped IP address
- D. Virtual IP address

Answer: B

NEW QUESTION 46

To which three bind points can a Citrix Administrator bind a session policy, to enable Clientless access? (Choose three.)

- A. Group
- B. Service
- C. Service Group
- D. User
- E. Virtual server

Answer: BDE

NEW QUESTION 50

Which two actions must be true for a client to connect to a SSL offload virtual server without any SSL errors? (Choose two.)

- A. The Root Certificate is installed on the client's device
- B. The Server Certificate is bound to the load-balancing virtual server
- C. The Server Certificate is from a private certificate authority (CA)
- D. The Root Certificate is installed on the NetScaler

Answer: AC

NEW QUESTION 54

What are two pre-requisites for configuring SmartAccess policies on a NetScaler Gateway virtual server? (Choose two.)

- A. Universal License
- B. Pre- or Post-Endpoint Analysis configuration policy
- C. Smart card configuration policy
- D. Standard License

Answer: AB

Explanation: Make sure the Prerequisites are completed. This includes: ICA Only unchecked, Gateway Universal licenses installed, Callback URL configured at StoreFront, and Trust XML enabled on Delivery Controllers.

If you are using a Preauthentication Policy to run an Endpoint Analysis scan: References:

NEW QUESTION 59

Which mode on the NetScaler can a Citrix Administrator utilize to avoid asymmetrical packet flows and multiple route/ARP lookups?

- A. USNIP
- B. Layer 3
- C. MAC-based Forwarding
- D. Layer 2

Answer: C

Explanation: MAC-based forwarding can be used to avoid multiple-route/ARP lookups and to avoid asymmetrical packet flows.

NEW QUESTION 60

Which three steps can a Citrix Administrator take to integrate an existing CERT-based authentication policy on an existing NetScaler Gateway platform? (Choose three.)

- A. Create a CERT authentication policy and bind it to the NetScaler Gateway virtual server

- B. Enable client authentication on the SSL parameters of the virtual server
- C. Bind the existing CERT authentication policy to the NetScaler Gateway virtual server
- D. Enable the two-factor option on the existing CERT authentication profile
- E. Change the client certificate to Mandatory on the SSL parameters of the virtual server

Answer: ACD

NEW QUESTION 62

Scenario: A Citrix Administrator is deploying a NetScaler device and would like to add the NTP server to this appliance. Currently, the NTP service is configured at 192.168.55.54.

Which command-line interface command can the administrator use to complete this task?

- A. Add ntp server 192.168.55.54
- B. Add server ntp 192.168.55.54
- C. Add servicegroup NTP UDP
- D. Add service NTP 192.168.55.54 UDP 123

Answer: A

NEW QUESTION 64

A Citrix Administrator needs to create a customized blacklist of IP addresses to supplement the Webroot reputation check, and in order to have stricter access through NetScaler.

How can the administrator create this blacklist?

- A. Create several extended Access Control List policies.
- B. Create a data set for IPv4 address matching.
- C. Enable MAC-based Forwarding.
- D. Create several simple Access Control List policies.

Answer: A

NEW QUESTION 66

Scenario: A Citrix Administrator was notified that all contractor user IDs will start with the prefix “con.” Currently SmartControl is used to restrict access to peripherals.

Which expression can the administrator use to accomplish this requirement?

- A. HTTP.REQ.USERNAME.CONTAINS(“con”).NOT
- B. HTTP.REQ.USER.IS_MEMBER_OF(“con”).NOT
- C. HTTP.REQ.USE
- D. IS_MEMBER-OF (“con”)
- E. HTTP.REQ.USERNAME.CONTAINS (“con”)

Answer: C

Explanation: Reference <https://support.citrix.com/article/CTX200261>

NEW QUESTION 71

A Citrix Administrator needs to customize the user experience for users connecting with the NetScaler Gateway plug-in.

Which three options can the administrator configure in this customization, using session and traffic policies? (Choose three.)

- A. The level of user access to the applications
- B. Single sign-on
- C. Split tunneling
- D. The domains to which users are allowed access
- E. Authentication methods

Answer: CDE

NEW QUESTION 72

A Citrix Administrator receives complaints from some users that authentication for the NetScaler Gateway site fails.

Which tool can the administrator use to find data regarding time of failure and a list of users facing this issue?

- A. Gateway Insight
- B. Security Insight
- C. Web Insight
- D. HDX Insight

Answer: D

NEW QUESTION 76

Scenario: A Citrix Administrator created a rewrite policy to add a custom footer for a NetScaler Gateway login page. However, the administrator is NOT able to see the changes on the login page.

Which step can the administrator perform next to see the changes on the login page?

- A. Restart the NetScaler
- B. Edit the vpn/gateway_login_view.js file

- C. Make changes to rc.netscaler
- D. Disable the Rewrite and Responder feature

Answer: B

NEW QUESTION 81

Which three Unified Gateway elements can be configured by the Unified Gateway Wizard? (Choose three.)

- A. Responder policy for HTTP to HTTPS redirect
- B. A primary and any optional secondary authentication configuration
- C. The Unified Gateway primary virtual server
- D. Rewrite policy for HTTP to HTTPS redirect
- E. An SSL Server Certificate for the Unified Gateway virtual server

Answer: BCE

NEW QUESTION 82

A Citrix Administrator is configuring a NetScaler high availability (HA) pair and needs to ensure that one NetScaler is UP and primary at all times to ensure the business websites are always available.

What does the administrator need to do ensure that the NetScalers still handle web traffic in the event that both nodes become unavailable or fail a health check?

- A. Disable HA Fail-safe mode on the Secondary NetScaler.
- B. Configure HA Fail-safe mode on each NetScaler independently.
- C. Disable HA Fail-safe mode on the Primary NetScaler only.
- D. Configure HA Fail-safe mode on the Primary NetScaler only.

Answer: D

NEW QUESTION 86

Scenario: User authentication is failing through the NetScaler. A Citrix Administrator checked the Authentication, Authorization and Auditing (AAA) policy, action and virtual server and verified that the correct configuration was in place. The administrator bypassed the NetScaler and the authentication worked.

Which NetScaler utility can the administrator use to troubleshoot the access issue?

- A. nslog file
- B. aaad.debug
- C. nscon message
- D. Dashboard

Answer: B

NEW QUESTION 87

Scenario: A Citrix Administrator needs to build policies that control the selection of XenApp applications to which a user has access. The administrator would like for the policy decisions to be made by leveraging the HDX settings.

Which type of policy would enable this requirement?

- A. Traffic
- B. SmartControl
- C. Authorization
- D. SmartAccess

Answer: D

NEW QUESTION 92

Scenario: A Citrix Administrator is running applications on thousands of load-balanced back-end servers in a large infrastructure. It is difficult to track and troubleshoot problems due to the large volume of traffic received.

Which feature of NetScaler Management and Analytics System (MAS) can the administrator configure to monitor and troubleshoot in detail for an environment of this size?

- A. AppFlow Analytics
- B. Application Security Analytics
- C. Application Performance Analytics
- D. Advanced Analytics with Telemetry Node installed

Answer: D

NEW QUESTION 94

Scenario: A Citrix Administrator notices user sessions are disconnecting and reconnecting more often this week than last week, signaling a problem.

The administrator troubleshoots this issue and prepares to resolve it using persistence. However, the following considerations apply in the environment:

- It is a multi-proxy environment behind the NetScaler.
- USIP mode is enabled and applied to the services.
- The session timeout is very short.
- All users connect from the same location.

The Administrator can use persistence based on the setting to resolve this issue. (Choose the correct option to complete the sentence.)

- A. HTTP Cookies
- B. Proximity
- C. SSL Session IDs

D. Subnet IP

Answer: A

NEW QUESTION 95

Scenario: A NetScaler MPX appliance has become unresponsive while using the GUI. A Citrix Administrator needs to restart the appliance and force a core dump for analysis.

What can the administrator do to accomplish this?

- A. Use the NMI button on the back of the appliance.
- B. Connect to the USB port to issue a restart command.
- C. Use the reset button on the front of the appliance.
- D. Turn off the appliance using the power button.

Answer: A

NEW QUESTION 97

What are three possible policy results in a Default (Advanced) policy configuration? (Choose three.)

- A. Drop
- B. Bridge
- C. True
- D. False
- E. Undefined

Answer: ABE

NEW QUESTION 100

A Citrix Administrator needs to configure a policy where users will be downgraded to 'ICA Proxy Only' from 'Full VPN' in the event a user fails to meet Endpoint Analysis requirements.

Which configuration is required to satisfy this requirement?

- A. Quarantine Group with nFactor authentication
- B. Quarantine Group with two-factor authentication, using LDAP as primary authentication
- C. Quarantine Group with no Active Directory membership
- D. Quarantine Group with regular Active Directory membership

Answer: A

NEW QUESTION 104

Scenario: A Citrix Administrator needs to add 10 new servers to an existing server farm. The new servers are configured to serve the same applications and connections and are twice the capacity of the existing servers. The administrator wants to ensure that they are being fully utilized. Currently in the environment, the default load-balancing method is being used.

To ensure that only the 10 new servers are receiving twice the connections of the old servers without changing the load balancing to the rest of the environment, the administrator needs to add a weight of to the services attached to the servers. (Choose the correct option to complete the sentence.)

- A. 2; new
- B. 2; old
- C. 50; old
- D. 50; new

Answer: B

NEW QUESTION 107

Scenario: A Citrix Administrator suspects an attack on a load-balancing virtual server. The administrator needs to restrict access to the load-balancing virtual server (192.168.100.25) for 10 minutes.

Which Access Control List (ACL) will help to accomplish this requirement?

- A. add ns acl rule1 DENY –destIP 192.168.100.25- TTL 600000
- B. add simpleacl rule1 DENY- srcIP 192.168.100.25- TTL 600
- C. add ns acl rule1 DENY –destIP 192.168.100.25- TTL 600
- D. add simpleacl rule1 DENY- srcIP 192.168.100.25- TTL 600000

Answer: C

NEW QUESTION 109

A Citrix Administrator needs to generate AppFlow data for internal ICA connections.

Which two connection methods could the administrator use to route internal ICA connections through NetScaler without modifying the existing network routing? (Choose two.)

- A. Policy-based Routing
- B. ICA Proxy
- C. SOCKS proxy
- D. Transparent Mode

Answer: AD

NEW QUESTION 111

Scenario: A Citrix Administrator is performing a disaster recovery test and decided to fail over the NetScaler high availability (HA) pair appliances. The administrator noticed that the failover is NOT working as expected in item text, and the Secondary NetScaler is NOT taking over as Primary. The administrator suspects that networking issues may be causing the failure. What could be the cause of this issue with the NetScalers?

- A. HA monitoring is enabled on a disabled interface of the Primary Node
- B. HA monitoring is enabled on an interface of the Secondary Node that shows as ENABLED, DOWN
- C. Independent network configuration (INC) mode is enabled
- D. HA heartbeats are only seen on some enabled interfaces of the Secondary Node

Answer: D

NEW QUESTION 115

Scenario: Users belong to three Authentication, Authorization and Auditing (AAA) groups: Corporate, Finance and Software.

Show aaa groups:

```
>show aaa group
```

```
1) GroupName: Corporate
```

```
2) GroupName: Finance
```

```
3) GroupName: Software Done
```

```
>show aaa group Corporate GroupName: Corporate Weight: 0
```

```
Authorization Policy: pol_1, Type: Classic, Priority: 0
```

```
> add authorization policy pol_1 ns_true ALLOW
```

```
> bind aaa group Corporate -policy pol_1
```

The user is being denied resources while aaad.debug shows: Group 'corporate' being extracted for user User1

Why is the user being denied access?

- A. The Authorization policy is NOT configured properly.
- B. The group attribute is NOT configured in the LDAP policy.
- C. AAA group names are NOT the same as those in Active Directory/
- D. LDAP Base DN is incorrect.

Answer: D

NEW QUESTION 120

Which NetScaler mode is commonly referred to as 'inline mode'?

- A. One-Arm Mode
- B. Use Source IP (USIP)
- C. MAC-based Forwarding
- D. Two-Arm Mode

Answer: D

Explanation: In an inline mode (also called two-arm mode) setup, you connect the NetScaler appliance to the network through multiple VLANs.

NEW QUESTION 123

Scenario: A Citrix Administrator needs to integrate LDAP for NetScaler system administration using the current Active Directory groups. The administrator created the group on the NetScaler, exactly matching the group name in LDAP.

What can the administrator add next to complete the configuration of the LDAP?

- A. Users to the group on the NetScaler
- B. An AAA action to the group
- C. A command policy to the group to specify the permission level
- D. A nested group to the new group

Answer: C

NEW QUESTION 125

Scenario: A Citrix Administrator created four session policies and applied them to the bind points below.

Policy A: Split tunnel ON priority 10 bound at the Virtual Server level

Policy B: Split tunnel OFF priority 20 bound at the Group level

Policy C: Split tunnel NOT configured priority 30 bound at the Global level

Policy D: Split tunnel ON priority 6 bound at the Group level

Which policy will take precedence?

- A. Policy C
- B. Policy D
- C. Policy A
- D. Policy B

Answer: A

NEW QUESTION 127

Scenario: A Citrix Administrator deployed a NetScaler in one-arm mode. Currently, the VLANs 20, 30 and 40 are tagged on the interface with the option of 'tagall' on the interface.

What is true regarding the VLANs, when 'tagall' is enabled on the interface?

- A. VLANS 1, 20, 30, 40 and HA packets are tagged on the interface
- B. VLANS 20, 30 and 40 are tagged on the interface
- C. VLANS 20, 30, 40 and HA packets are tagged on the interface
- D. VLANS 1, 20, 30 and 40 are tagged on the interface

Answer: B

NEW QUESTION 128

Which two deployment methods does remote desktop protocol (RDP) proxy support? (Choose two.)

- A. ICA proxy
- B. Two hops
- C. Optimal Gateway
- D. CVPN

Answer: AD

NEW QUESTION 132

Scenario: A Citrix Administrator is configuring a new Authentication, Authorization and Auditing (AAA) virtual server, and the status is DOWN. The administrator has made the following configurations:

Add lbvserver lb_vsrv_www HTTP 10.107.149.229.80- persistenceType NONOE -cltTimeout 180- authn401 ON -authnVsName SAML_SP

Bind vserver lb_vsrv_www_ssl Red_srv Bind lb vserver lb_vsrv_www_ssl Blue_srv

Add authentication vserver SAML_SP SSL 10.107.149.230.443- AuthenticationDomain citrix.lab How can the administrator finish the installation to change the status of the virtual server to UP?

- A. Bind the Certificate to the virtual server SAML_SP.
- B. The LDAP server is NOT bound to the virtual server SAML_SP.
- C. Services are NOT bound to the virtual server SAML_SP.
- D. An AAA policy is NOT bound to the virtual server SAML_SP.

Answer: B

NEW QUESTION 133

Which three services can the StoreFront monitor probe to determine the state of the StoreFront server? (Choose three.)

- A. Default Domain
- B. Discovery
- C. Authentication
- D. Subscription
- E. Account

Answer: BCE

NEW QUESTION 135

Scenario: A Junior Citrix Administrator needs to create a Content Switching virtual server on a NetScaler high availability (HA) pair. The NSIP addresses are 192.168.20.10 and 192.168.20.11. The junior administrator connects to NSIP address 192.168.20.10 and saves the changes.

The following day, a Senior Citrix Administrator tries to test the new Content Switching virtual server, but it is NOT working. The senior administrator connects to the HA pair and everything the junior administrator configured is gone.

Why did the NetScalers lose the newly added configurations?

- A. The NetScaler appliances are NOT at the same firmware version
- B. The junior administrator connected to the NSIP of the secondary NetScaler in the HA pair
- C. Both NetScalers in the HA pair restarted overnight, losing the configuration
- D. The junior administrator made the changes and did NOT force a failover to save the configuration

Answer: C

NEW QUESTION 137

Scenario: IT administrators working from remote locations, need to connect securely to internal Windows servers to manage the servers.

Below are the connection requirements:

The remote client devices must be locked down, preventing installation of any additional software

Users must authenticate at NetScaler Gateway and NetScaler Gateway must perform Single Sign-on to the Windows servers

Connection capabilities (for example, client drive mapping) must be controlled by NetScaler Gateway Which connection method can a Citrix Administrator configure to meet these requirements?

- A. RDP Proxy
- B. Clientless VPN
- C. Full VPN
- D. Micro VPN

Answer: A

NEW QUESTION 140

How can a Citrix Administrator configure session policies for the Authentication, Authorization and Auditing Traffic Management (AAA-TM) sessions if the authentication virtual server is specified in a Unified Gateway setup?

- A. The session policies can be defined only for the NetScaler Gateway virtual server.

- B. The AAA-TM session policies are bound to the virtual server.
- C. The AAA-TM sessions inherit the NetScaler Gateway session policies.
- D. The AAA-TM policies need to be bound as default global.

Answer: B

NEW QUESTION 142

In which two ways can a Citrix Administrator configure SmartAccess? (Choose two.)

- A. Enable Workspace Control within StoreFront.
- B. Update XML Service Trust to set-BrokerSite-TrustRequestsSentToTheXMLServicePort \$True
- C. Update the XML Service trust in the XenDesktop database manually.
- D. Ensure that the SmartAccess filter name on the Delivery Group matches the NetScaler Gateway policies.

Answer: BD

NEW QUESTION 147

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 1Y0-230 Exam with Our Prep Materials Via below:

<https://www.certleader.com/1Y0-230-dumps.html>