

1z0-074 Dumps

Upgrade Oracle DBA 11g/12c to 12cR2

<https://www.certleader.com/1z0-074-dumps.html>



NEW QUESTION 1

You create a refreshable copy PDB,PDB_COPY, from thePDB_ORGPDB by using theREFRESH MODE EVERY 5 MINUTESclause. What happens every five minutes?

- A. An automatic refresh is done providedPDB_COPYis closed; otherwise the refresh is deferred and attempted again after five minutes.
- B. PDB_COPYis automatically closed provided there is no ongoing transaction inPDB_ORGand then reopened as read-only after the refresh is complete.
- C. PDB_COPY'Sstate is automatically changed to read-write and back to read-only after the refresh is complete.
- D. PDB_COPY'Sstate is automatically changed to read-only and then reopened as read-write after the refresh is complete.
- E. An automatic refresh is done providedPDB_COPYis in read-only mode; otherwise the refresh is deferred and attempted again after five minutes.

Answer: E

NEW QUESTION 2

Which statement is true about transportable tablespaces?

- A. The tablespace data file or data files to be plugged in to the target database cannot have a different block size than any of the source database's data file or files.
- B. They cannot be dictionary-managed tablespaces
- C. The source tablespace can be encrypted
- D. They can be administrative tablespaces such asSYSTEMorSYSAUX

Answer: A

NEW QUESTION 3

Identify two operations for which thebkup_apiutility can be used. (Choose two.)

- A. to define the retention period for backups
- B. to define which system files are backed up
- C. to define which database configuration files are backed up
- D. to define the cycle period for backups
- E. to define the frequency of automatic backups

Answer: AD

NEW QUESTION 4

In which situation can the optimizer choose a hash join?

- A. when a non-equi join is used and the join column in at least one of the tables is a primary key
- B. when a non-equi join is used and the join column for both tables is a primary key
- C. when a non-equi join is used between a table and a sorted hash cluster
- D. when an equality operator is used
- E. when any self-join is done

Answer: D

NEW QUESTION 5

In your CDB1 container database, theDB_CREATE_FILE_DESTparameter is set to'/u01/app/oracle/oradata'.

CDB1has an application container calledREGIONS_APP.

There are no seeds forREGIONS_APPand there are no other application containers. You plan to execute this command.

```
CREATE PLUGGABLE DATABASE AS SEED ADMIN USER seed_adm IDENTIFIED BY admin_123;
```

What must you do for the command to execute successfully?

- A. Set the current container toREGIONS_APP
- B. Set the current container toCDB1
- C. Add theFILE_NAME_CONVERTclause to the command
- D. Add theCREATE_FILE_DESTclause to the command
- E. Set thePDB_FILE_NAME_CONVERTparameter to'/u01/app/oracle/oradata'

Answer: E

NEW QUESTION 6

Which statement is true about Trace File Analyzer (TFA) Collector?

- A. TFA collects diagnostic data only for Oracle 12c Release 2 databases or later versions.
- B. If TFA is installed on any cluster node, it automatically collects diagnostic data on all other cluster nodes.
- C. It can be used to collect diagnostic data for predefined events, and can be configured to automatically collect data for other events.
- D. In Oracle 12c Release 2, TFA installation can be done only while executingroot.sh.
- E. It is used to collect diagnostic data only for ORA-600, ORA-7445, and ORA-4031 events.

Answer: D

NEW QUESTION 7

Examine these statements:

```
SQL> SELECT VALIDATE_CONVERSION('200 00:00:00' AS INTERVAL DAY TO
SECOND) FROM DUAL;

SQL> SELECT VALIDATE_CONVERSION('P1Y2M' AS INTERVAL YEAR TO MONTH)
FROM DUAL;

SQL> SELECT VALIDATE_CONVERSION('July 20, 1969, 20:18' AS DATE,
'MONTH dd, YYYY, HH24:MI', 'NLS_DATE_LANGUAGE = American') FROM
DUAL;
```

Which statement is true?

- A. Statements 2 and 3 will validate the conversion
- B. Only statement 3 will validate the conversion
- C. Only statement 1 will validate the conversion
- D. Statement 1 will return an error
- E. All the statements will validate the conversion

Answer: B

NEW QUESTION 8

Which two statements are true about FLEX ASM? (Choose two.)

- A. A database instance on any node can connect to an ASM instance on any node.
- B. A separate ASM network is required.
- C. It is impossible to connect to a database instance on one node if the database password file for the same database is corrupt on another node in the cluster.
- D. Database instances that depend on an ASM instance that is terminated fail over to a node that has a surviving ASM instance.
- E. Database instances that depend on an ASM instance that is terminated connect to a surviving ASM instance.

Answer: DE

NEW QUESTION 9

In which four situations does the RMAN DUPLICATE command use the "pull" method? (Choose four.)

- A. when the USING BACKUPSET clause is used
- B. when the SET ENCRYPTION clause is added before the DUPLICATE command
- C. when the SECTION SIZE clause is used
- D. when the number of auxiliary channels allocated is less than the number of target channels allocated
- E. when the USING COMPRESSED BACKUPSET clause is used
- F. when no auxiliary channels are allocated
- G. when IMAGE COPIES are used for the DUPLICATE operation

Answer: ACDE

NEW QUESTION 10

In an Oracle 12c Release 2 database, USER1 has CREATE SESSION, CREATE PROCEDURE, and CREATE FUNCTION privileges. Examine these commands:

```

$ sqlplus / as sysdba

SQL> REVOKE INHERIT PRIVILEGES ON USER sys FROM user1;

SQL> CONNECT user1/oracle

SQL> CREATE OR REPLACE PROCEDURE create_user AUTHID CURRENT_USER AS
PRAGMA AUTONOMOUS_TRANSACTION;
BEGIN
DBMS_OUTPUT.PUT_LINE('The result is: ');
EXECUTE IMMEDIATE 'CREATE USER testdba IDENTIFIED BY oracle';
EXECUTE IMMEDIATE 'GRANT SYSDBA TO testdba';
EXCEPTION
WHEN OTHERS THEN
NULL;
END;
/

SQL> CREATE OR REPLACE FUNCTION add_num(num1 IN NUMBER, num2 IN NUMBER)
RETURN NUMBER AUTHID CURRENT_USER
AS
BEGIN
create_user;
RETURN (num1+num2);
END;
/

```

SYSEXECUTEs this command:

```
SQL> SELECT add_num(1,2) FROM DUAL;
```

What is the result?

- A. An error is returned
- B. The message "The result is 3" only is displayed
- C. TESTDBA is created with the SYSDBA privilege only
- D. Only "3" is displayed
- E. TESTDBA is created with the SYSDBA privilege and the message "The result is 3" is displayed

Answer: C

NEW QUESTION 10

Which two statements are true about the In-Memory (IM) column store? (Choose two.)

- A. It may be used for columns in Index Organized Tables (IOTs)
- B. It may be used for columns in clustered tables
- C. IM area size is not controlled by Oracle Automatic Memory Management
- D. IM area size can be set at the CDB and PDB levels
- E. IM area size can be increased or decreased dynamically
- F. It is not used for partitioned tables

Answer: AE

NEW QUESTION 14

U1.T1 is in a tablespace TBS_UNCOMP which has no default compression and U1.T2 is in a tablespace, TBS_CMP with default compression for query low. You execute commands:

```
SQL> EXEC DBMS_REDEFINITION.START_REDEF_TABLE (uname=>
'u1',orig_table => 't1', int_table => 't2',options_flag =>
DBMS_REDEFINITION.CONST_USE_PK, enable_rollback => TRUE);
PL/SQL procedure successfully completed.

SQL> EXEC DBMS_REDEFINITION.SYNC_INTERIM_TABLE (uname => 'u',
orig_table => 't1', int_table => 't2');
PL/SQL procedure successfully completed.

SQL> EXEC DBMS_REDEFINITION.FINISH_REDEF_TABLE (uname => 'u1',
orig_table => 't1', int_table => 't2');
PL/SQL procedure successfully completed.

SQL> EXEC DBMS_REDEFINITION.ROLLBACK (uname => 'u1', orig_table =>
't1', int_table => 't2');
PL/SQL procedure successfully completed.
```

Which three statements are true? (Choose three.)

- A. The primary key constraints on T1 are dropped
- B. T1 is in the TBS_UNCOMP tablespace
- C. T1 is in the TBS_CMP tablespace
- D. T1 is in compressed format
- E. T1 is in uncompressed format
- F. All indexes on T1 remain valid

Answer: ACE

NEW QUESTION 19

A multi-tenant container database (CDB) contains three PDBs.

Which three are prerequisites for performing a cross-platform transport of any of the PDBs? (Choose three.)

- A. The CDB should be in MOUNT state.
- B. The source and target platforms must have the same endianness.
- C. The COMPATIBLE parameter must be set to 12.2 or greater in the CDB.
- D. The source PDBs must be closed for a cross-platform PDB backup.
- E. Flashback database must be enabled for the CDB.
- F. The CDB must use Automatic Memory Management.

Answer: BCD

NEW QUESTION 24

Which three statements are true about the deferred invalidation clause in DDL statements? (Choose three.)

- A. It defers invalidating dependent cursor when possible.
- B. It cannot be used for bitmap index creation.
- C. The CURSOR_INVALIDATION parameter always overrides the deferred invalidation clause.
- D. It always overrides the CURSOR_INVALIDATION setting.
- E. It cannot be used for creating a secondary index on index organized tables

Answer: ACE

NEW QUESTION 27

You want to restrict PGA usage to 200 MB for a set of database users' sessions as part of your organization's security requirements for combating denial of service (DOS) attacks.

Which statement is true about limiting PGA usage for those users' sessions?

- A. You can limit their PGA usage by setting SORT_AREA_SIZE to 200 MB.
- B. You cannot limit PGA for a set of database user sessions.
- C. You can limit their PGA usage by setting PGA_AGGREGATE_LIMIT to 200 MB.
- D. You can limit their PGA usage by setting PGA_AGGREGATE_TARGET to 200 MB.
- E. You can limit their PGA usage by setting the SESSION_PGA_LIMIT directive by using Database Resource Manager

Answer: C

NEW QUESTION 31

Identify a situation where performance profiles can be used for application containers.

- A. to specify the total number of parallel execution servers available
- B. to specify the maximum time, in seconds, that a parallel statement can wait in the parallel statement queue before it is timed out
- C. to specify the maximum percentage of the parallel execution server pool that a particular application container can use
- D. to enforce a limit on the number of I/Os issued per second
- E. to enforce a limit on I/O throughput per second

Answer: A

NEW QUESTION 35

Which three statements are true about the Automatic Database Diagnostic Monitor (ADDM)? (Choose three.)

- A. It analyzes only those memory components of the database instance that are impacting performance.
- B. It determines the segments on which waits are occurring when the database has a high number of buffer busy waits.
- C. It analyzes the performance of the database instance based on the latest two AWR snapshots.
- D. It determines SQL statements that are performing poorly.
- E. It recommends implementing SQL profiles to generate better execution plans.
- F. It analyzes only the components and waits that are impacting database performance.

Answer: BCD

NEW QUESTION 36

Which two statements are true about a PDB lockdown profile? (Choose two.)

- A. It is created by a local user with the SYSDBA privilege in each PDB where it needs to be applied.
- B. It is created by a common user with the SYSDBA privilege in CDB\$ROOT.
- C. It is created by a common user with the SYSDBA privilege in each PDB where it needs to be applied.
- D. It is enabled by default on creation.
- E. It is enabled by using the PDB_LOCKDOWN parameter in each PDBs where it needs to be applied.
- F. It is enabled in PDBs only after the CDB to which the PDBs belong is restarted.

Answer: BC

NEW QUESTION 37

From which two failure scenarios can a database be restored and recovered with the REPAIR DATABASE command? (Choose two.)

- A. loss of ARCHIVELOGS
- B. loss of a redo log member
- C. loss of a noncritical data file
- D. loss of all copies of the control file
- E. loss of a critical data file such as SYSTEM, SYSAUX or UNDO
- F. loss of SPFILE

Answer: DE

NEW QUESTION 41

Which statement is true about the Automatic Diagnostic Repository (ADR)?

- A. Space used by the ADR can be limited to a user-specified value.
- B. Space used by the ADR is limited based only on the retention period.
- C. The retention period for the ADR is set based on the space limit specified.
- D. When the ADR reaches the space limit, it deletes incident dumps and metadata before deleting old core dumps.
- E. Manual purging of all types of ADR files is allowed.

Answer: E

NEW QUESTION 44

Which three database objects can have columns stored in the In-Memory (IM) column store? (Choose three.)

- A. subpartitions
- B. clustered tables
- C. materialized views
- D. index-organized tables
- E. heap tables
- F. any SYS owned objects

Answer: BDF

NEW QUESTION 45

You receive complaints about poor performance in an Oracle 12c database while long running queries execute.

You must obtain statistics such as elapsed time, CPU time, number of reads and writes, I/O wait time, and other wait times for each step of each execution plan to help diagnose the problem during query execution.
How would you achieve this?

- A. by viewing Active Reports for that time period
- B. by enabling SQL trace for each query
- C. by running the Automatic Workload Repository (AWR) report for that time period
- D. by running the Active Session History (ASH) report for that time period
- E. by enabling tracing for sessions that run these queries

Answer: E

NEW QUESTION 47

You create a new application container, SALES_APP, with application PDBs, SALES1_PDB, and SALES2_PDB. You want to install the NEW_APP application in SALES1_PDB and SALES2_PDB by using:

```
ALTER PLUGGABLE DATABASE APPLICATION BEGIN INSTALL;
ALTER PLUGGABLE DATABASE APPLICATION END INSTALL;
ALTER PLUGGABLE DATABASE APPLICATION SYNC;
```

Where should you execute these statements?

- A. All the statements should be executed in the application root.
- B. All the statements should be executed in the application seed.
- C. All the statements should be executed in the SALES1_PDB and SALES2_PDB application containers.
- D. BEGIN/END INSTALL statements should be executed in the application root and the SYNC statement in SALES1_PDB and SALES2_PDB.
- E. BEGIN/END INSTALL statements should be executed in the CDB root and the SYNC statement in the application root.

Answer: AD

NEW QUESTION 50

One of your databases supports an OLTP workload.

If a better plan is discovered for a statement, then you want that plan to be used. Which two can cause better plans to be used for a statement? (Choose two.)

- A. adaptive cursor sharing
- B. using literals in SQL statements
- C. SQL Access Advisor
- D. SQL Performance Analyzer
- E. adaptive execution plans

Answer: CE

NEW QUESTION 55

Identify four prerequisites for issuing the RMAN RECOVER TABLE command starting from ORACLE Database 12c Release 2.

- A. The COMPATIBLE parameter must be set to 12.0 or greater.
- B. The database must be in ARCHIVELOG mode.
- C. FLASHBACK DATABASE must be enabled.
- D. RMAN must use a recovery catalog.
- E. The database must be in the READ WRITE state.
- F. RMAN can recover the table only from a backupset.
- G. An export dump file of the table must be available.
- H. There must be sufficient space to start the auxiliary instance.

Answer: ABEF

NEW QUESTION 60

Identify two types of files that are generated by the Pre-Upgrade Information tool as part of the database upgrade prerequisite checks? (Choose two.)

- A. expdp scripts to export database objects belonging to the SYS schema
- B. a log file containing a list of pre-upgrade patches to be applied
- C. RMAN database backup scripts
- D. a log file with tool recommendations and requirements
- E. pre- and post-upgrade fixup scripts

Answer: DE

NEW QUESTION 61

QUERY_REWRITE_INTEGRITY and QUERY_REWRITE_ENABLED are set to TRUSTED and TRUE respectively in an Oracle 12c Release 2 database.

You create the SALES_EVAL real-time materialized view (MV) on the SALES, CUSTOMERS, and PRODUCT tables, which supports COMPLETE REFRESH by executing these statements.

```
SQL> CREATE MATERIALIZED VIEW SALES_EVAL
      BUILD IMMEDIATE
      REFRESH COMPLETE
      ENABLE QUERY REWRITE
      AS SELECT c.cust_id, sum(s.amount_sold)
      AS dollars,
      p.prod_id, sum(s.quantity_sold) as quantity
      FROM sales s, customers c, products p
      WHERE c.cust_id=s.cust_id AND s.prod_id = p.prod_id
      GROUP BY c.cust_id, p.prod_id;

SQL> SELECT c.cust_last_name,
      sum(s.quantity_sold) as quantity
      FROM sales s, customers c, products p
      WHERE c.cust_id = s.cust_id AND s.prod_id = p.prod_id
      GROUP BY c.cust_last_name, p.prod;
```

There is a constraint on the PRODUCT table with ENABLE, NOVALIDATE, and RELY attributes. No updates have been done to SALES, CUSTOMERS, or PRODUCTS since the MV was created. From where are rows returned and why?

- A. from the SALES_EVAL MV because the QUERY_REWRITE_ENABLED setting permits rewrites on unverified constraints if the table is not stale
- B. from the SALES, CUSTOMERS, and PRODUCTS tables because QUERY_REWRITE_INTEGRITY is set to TRUSTED
- C. from the SALES, CUSTOMERS, and PRODUCT tables because the column in the GROUP BY clause is different from the SALES_EVAL MV definition
- D. from the SALES, CUSTOMERS, and PRODUCT tables because the columns used in the SELECT list are different from the SALES_EVAL MV definition
- E. from the SALES_EVAL MV because the WHERE clause in the query and in the SALES_EVAL definition are the same

Answer: E

NEW QUESTION 66

In a Database Cloud Service (DBCS) environment, which pre-created user has sudo privileges to run certain root commands?

- A. grid
- B. oracle
- C. opc
- D. nobody
- E. oinstall

Answer: C

NEW QUESTION 67

You log in to the ORCL database as SYSTEM and successfully execute these two blocks of code:

```

BEGIN
    DBMS_REDACT.ADD_POLICY (object_schema => 'HR',
        object_name => 'EMP'
        policy_name => 'REDACT_EMP',
        column_name => 'SALARY',
        function_type => DBMS_REDACT.FULL,
        expression => '1=1');
END;

BEGIN
    DBMS_REDACT.ALTER_POLICY (object_schema => 'HR',
        object_name => 'EMP',
        policy_name => 'REDACT_EMP',
        action => DBMS_REDACT.ADD_COLUMN,
        column_name => 'LAST_NAME',
        expression => 'SYS_CONTEXT(''USERENV'', ''SESSION_USER'')!
        ='' SCOTT''');
END;

```

The SCOTT user has the SELECT privilege on HR.EMP.
Which statement is true about queries by non-DBA users with the SELECT privilege on HR.EMP?

- A. All their queries display blanks for LAST_NAME and the true contents of the SALARY column.
- B. Only SCOTT'S queries display the true contents of the SALARY column and blanks for LAST_NAME.
- C. All their queries display blanks for LAST_NAME and zeroes for SALARY.
- D. Only SCOTT'S queries display the true contents of the SALARY and LAST_NAME columns.
- E. Only SCOTT'S queries display zero for SALARY and the true contents of the LAST_NAME column.

Answer: A

NEW QUESTION 69

In a database on an Oracle Exadata Database machine, a DBA executes this command: SQL> exec DBMS_INMEMORY_ADMIN.ENABLE_FASTSTART ('fs_tbs');
What is the result?

- A. All columns for all tables in the FS_TBStablespace are loaded into the In-Memory column store.
- B. Any data in the In-Memory column store is copied in compressed columnar format to the FS_TBS tablespace.
- C. Any data in the In-Memory column store is copied in uncompressed columnar format to the FS_TBS tablespace.
- D. Any data in the In-Memory column store is copied in row major format to the FS_TBStablespace.

Answer: A

NEW QUESTION 72

ACDB, CDB1, has a LOCATIONS application container. NORTH_PDB and SOUTH_PDB are two application PDBs in LOCATIONS. Both application PDBs are synchronized with the application installed in the LOCATIONS root... In CDB2, you create a remote clone, LOC_R, of the LOCATIONS application root.
You want to query data across the LOCATIONS application PDBs created in CDB1 and CDB2. How can you do this?

- A. by creating a proxy PDB in LOCATIONS_ROOT in CDB1, referencing LOC_R
- B. by creating a proxy PDB in CDB1 root, referencing LOC_R
- C. by using private database links created in CDB1 and CDB2
- D. by using public database links created in CDB1 and CDB2
- E. by creating a proxy PDB in CDB2 root, referencing LOC_R

Answer: E

NEW QUESTION 73

APP1 is an application container that has an application seed and two application PDBs, APP_PDB1 and APP_PDB2. 1.1 is the current version of the application. You execute this block in the application root:

```
ALTER PLUGGABLE DATABASE APPLICATION app1
BEGIN UPGRADE '1.0' TO '1.5';

CREATE ROLE role1;

ALTER PLUGGABLE DATABASE APPLICATION app1
END UPGRADE TO '1.5';
```

What is the outcome?

- A. An error is thrown because the version number should be sequential, either 1.1 or 2.0.
- B. An error is thrown because the CONTAINER=ALL clause is missing.
- C. An error is thrown because the ## prefix is missing in the role name.
- D. A common role is created only in the application root.
- E. A common role is created only in the application root and application seed.
- F. A common role is created in the application root, application seed, APP_PDB1, and APP_PDB2.

Answer: D

NEW QUESTION 77

The In-Memory compression level is set to MEMCOMPRESS FOR QUERY HIGH. For what purpose is this optimized?

- A. for parallel query performance only
- B. for query performance and space saving
- C. for query performance and space saving with greater bias toward space saving
- D. for query performance only
- E. for space saving only

Answer: B

NEW QUESTION 80

You plan to execute this command:

```
CREATE TABLE sales
(
  prod_id          NUMBER(3),
  annual_sale_amt  NUMBER(10, 2),
  country          VARCHAR2(4),
  channel          VARCHAR2(1)
)
PARTITION BY LIST(country, channel)
(
  PARTITION p1 VALUES (('USA', 'D'), ('CA', 'D')),
  PARTITION p2 VALUES (('USA', 'I'), ('CA', 'I'))
);
```

Which statement is true and why?

- A. It creates partitions P1 and P2 where COUNTRY is a single column partition key and CHANNEL is a subpartition key.
- B. It returns an error because only one set of multiple values can be specified for each partition.
- C. It returns an error because only a single column key can be used for a list-partitioned table.
- D. It returns an error because the AUTOMATIC option must be specified.
- E. It creates partitions P1 and P2 where COUNTRY and CHANNEL are multi-column partition keys.

Answer: E

NEW QUESTION 84

Your CDB is in ARCHIVELOG mode and has an application container with a container PDB. A backup exists for the CDB. When you connect to the container PDB and try to execute a query, you get an error that a SYSTEM data file is missing in the container PDB. You want to use the RMAN RESTORE DATABASE and RECOVER DATABASE commands to perform the recovery.

Examine these actions:

1. Connect to CDB\$ROOT and execute SHUTDOWN ABORT and STARTUP MOUNT.

2. Connect to the application container and execute SHUTDOWN ABORT.

3. Connect to the application container and execute ALTER PLUGGABLE DATABASE CLOSE ABORT. Which option correctly lists the actions that you must execute before performing the recovery?

- A. 1 and 3

- B. 1 and 2
- C. only 2
- D. only 3

Answer: A

NEW QUESTION 86

Which two statements are true about a band join? (Choose two.)

- A. The optimizer always uses the smaller of the two row sources to build a hash table on the join key.
- B. It returns rows for SQL statements that contain an equijoin.
- C. It is a non-equijoin in which the key values in one data set must fall within the specified range of the second data set.
- D. For each row in the first row source, Oracle probes the second row source for matching rows and joins them.
- E. The SQL runtime engine avoids unnecessary scanning of rows that fall outside the defined ranges.

Answer: CE

NEW QUESTION 91

TheEMP_CDB1andEMP_CDB2CDBs are in ARCHIVELOG mode. Oracle Managed Files is enabled in both CDBs. EMP_CDB1has a PDB,EMP_PDB1.

InEMP_CDB2, you log in as theSYSuser. You plan to execute this statement:

CREATE PLUGGABLE DATABASE emp_pdb2 FROM emp_pdb1@emp_link RELOCATE; Which two statements are true? (Choose two.)

- A. TheAVAILABILITY MAXclause should be added to the command to ensure transaction consistency during the relocation process.
- B. SYSOPERprivilege should be granted to the user defined inEMP_LINKand used to connect to the remotedatabase.
- C. EMP_PDB2should be opened in read-write mode to complete the relocation process.
- D. EMP_PDB1should be dropped manually fromEMP_CDB1after executing the relocating command.
- E. EMP_LINKshould exist as a public link inEMP_CDB1andEMP_CDB2.
- F. OnlyEMP_PDB1should be in local undo mode.

Answer: CE

NEW QUESTION 92

You plan to use Information Lifecycle Management (ILM) for theORDERStable. Which is true about Heat Map statistics whenHEAT_MAPisON?

- A. They are collected for all segments except for those in theSYSTEMandSYSAUXtablespaces, and are stored in theSYSTEMtablespace.
- B. They are collected for all segments except for those in theSYSTEMandSYSAUXtablespaces, and are stored in theSYSAUXtablespace.
- C. They are collected for all segments and are stored in theSYSAUXtablespace.
- D. They are collected for all segments and are stored in theSYSTEMtablespace.
- E. They are collected only for theORDERStable if it has an associated ADO policy.

Answer: D

NEW QUESTION 93

Which statement is true about policy expressions?

- A. A named policy expression is stored in the Data Masking format library.
- B. A named policy expression applied to a column in a redacted table overrides the default expression of its redaction policy.
- C. A redacted table can have only one policy expression defined on it.
- D. A policy expression can be applied to columns in different redacted tables.
- E. A named policy expression is stored in the Enterprise Manager Database Express repository.

Answer: C

NEW QUESTION 94

In which three situations would you recommend DB Replay to be used? (Choose three.)

- A. to check the impact of schema changes such as adding new indexes or materialized views
- B. to check the impact of database migration to the cloud
- C. to check the impact of changing the storage system or the network
- D. to check the impact of partitioning a table
- E. to check the impact of new optimizer statistics
- F. to check the impact of upgrading and patching databases

Answer: BCF

NEW QUESTION 95

To which two components does the term “shape” refer in Oracle Database Cloud Service (DBaaS)? (Choose two.)

- A. number of network interface cards (NICs)
- B. number of database instances
- C. number of CPUs
- D. amount of RAM
- E. number of storage LUNs

Answer: CD

NEW QUESTION 97

In your CDB, DEPTCDB, local undo is enabled. You successfully execute this command: FLASHBACK PLUGGABLE DATABASE hrpdb to SCN 424366; Which action must you perform next?

- A. OpenHRPDB
- B. Take a backup ofDEPTCDB
- C. Take a backup ofHRPDB
- D. OpenHRPDBwithRESETLOGS
- E. OpenDEPTCDBwithRESETLOGS
- F. OpenDEPTPDB

Answer: D

NEW QUESTION 99

You create and enable a unified audit policy on a database that has the default auditing configuration.

```
$ sqlplus sys/oracle@pdb_orcl as sysdba

SQL> CREATE AUDIT POLICY aud_syspriv
      PRIVILEGES SELECT ANY TABLE, CREATE LIBRARY
      WHEN 'SYS_CONTEXT(''USERENV'', ''SESSION_USER'')='''OE'''
      EVALUATE PER STATEMENT;

Audit policy created.

SQL> AUDIT POLICY aud_syspriv;

Audit succeeded.
```

The OE user, who has the DBA role, executes these statements.

```
SQL> CONNECT OE/password@pdb_orcl

Connected.

SQL> SELECT *
      FROM HR.EMPLOYEES;
```

What is true about the SELECT statement and why?

- A. It is audited because unified auditing is disabled by default.
- B. It is audited because, by default, the database is in mixed auditing mode with default policies enabled.
- C. It is audited because, by default, all user activities in the database are audited.
- D. It is not audited because the table belongs to another schema.
- E. It is not audited because audit records are stored only when unified auditing is enabled in the database.

Answer: C

NEW QUESTION 104

Which two are true about the ADR retention advisor in Oracle Database 12c Release 2? (Choose two.)

- A. ESTIMATE (SHORTP_POLICY = 192) estimates the space requirement based on theSHORTP_POLICYvalue of 192 minutes.
- B. ESTIMATE (SHORTP_POLICY = 192, LONGP_POLICY = 2160) estimates the space requirement based on current ADR diagnostics file space usage.
- C. ESTIMATE (SIZEP_POLICY = 209715200) estimates only the long retention policy.
- D. ESTIMATE (SHORTP_POLICY = 192, LONGP_POLICY = 8760) provides estimates that users can use to setSIZEP_POLICY.
- E. ESTIMATE (SIZEP_POLICY = 209715200) estimates the value ofLONGP_POLICY.

Answer: DE

NEW QUESTION 108

InTESTDB, U1hasSYSDBAprivileges and the passwordOracle_4U. You recreate the password file:
\$ orapwd FILE=orapwtestdb FORMAT=12.2 password=Oracle_123 ENTRIES=5 Examine the command and result:
\$ sqlplus u1/Oracle_4U@testdb as sysdba ERROR:
ORA-01017: invalid username/password; logon denied What can you do to fix this error?

- A. Recreate the password file with the password set toOracle_4U.
- B. Change the password ofU1 to Oracle_123.
- C. Set theREMOTE_LOGIN_PASSWORDFILEparameter value to NONE.
- D. RegrantSYSDBA to U1.
- E. Restart the database instance.

Answer: A

NEW QUESTION 110

You notice a large number of latch: cache buffers lru chain and latch: cache buffers chains wait events. Which four might be reasons for these? (Choose four.)

- A. The same small number of blocks are repeatedly accessed by different sessions simultaneously.
- B. The buffer cache is undersized.
- C. Cursors are closed explicitly after each execution.
- D. A large number of connected user sessions are idle.
- E. DBWR is not writing the dirty buffers fast enough.
- F. Blocks are ageing out of the buffer cache frequently.
- G. Too many sort operations are being performed.

Answer: AEFG

NEW QUESTION 114

Examine this parameter:

NAME	TYPE	VALUE
optimizer_capture_sql_plan_baselines	boolean	TRUE

Examine these commands:

```
SQL EXEC DBMS_SPM.CONFIGURE('AUTO_CAPTURE_PARSING_SCHEMA_NAME','SH', true);
PL/SQL procedure successfully completed.

SQL> EXEC DBMS_SPM.CONFIGURE('AUTO_CAPTURE_PARSING_SCHEMA_NAME','SYS', true);
PL/SQL procedure successfully completed.

SQL> EXEC DBMS_SPM.CONFIGURE('AUTO_CAPTURE_SQL_TEXT','%TEST_ONLY%', false);
PL/SQL procedure successfully completed.
```

Which three are true after executing these commands? (Choose three.) (Choose three.)

- A. All statements executed by SH are captured and included in a baseline.
- B. Statements executed by both SH and SYS may be captured and included in a baseline.
- C. Only statements executed by SYS are captured and included in a baseline.
- D. Only statements executed by SH containing the "TEST_ONLY" string are excluded from capture.
- E. Statements executed by any user containing the "TEST_ONLY" string are excluded from capture.
- F. Only repeatable statements executed by SYS and SH are considered for baselines.

Answer: AEF

NEW QUESTION 117

Which three statements are true about the SQL Performance Analyzer? (Choose three.)

- A. It recommends the use of SQL Tuning Advisor for regressed SQL statements.
- B. It recommends the creation of indexes for regressed SQL statements.
- C. It compares and analyzes execution plans for the SQL statements in a SQL Tuning Set (STS).
- D. It always executes triggers that are fired recursively in FULLDML mode.
- E. It generates execution plans for each SQL statement in an STS.

Answer: ACE

NEW QUESTION 118

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your 1z0-074 Exam with Our Prep Materials Via below:

<https://www.certleader.com/1z0-074-dumps.html>