

## 1Y0-230 Dumps

### Citrix NetScaler 12 Essentials and Unified Gateway

<https://www.certleader.com/1Y0-230-dumps.html>



**NEW QUESTION 1**

Which two options should a Citrix Administrator configure to stop the First-Time wizard from automatically popping up? (Choose two.)

- A. Host Name is NOT configured on the appliance
- B. The appliance is configured with the default IP address (192.168.100.1)
- C. the default Admin Password has NOT been changed
- D. Licenses are NOT present on the appliance

**Answer: BD**

**NEW QUESTION 2**

A Citrix Administrator needs to configure single sign-on to a StoreFront server using an external, secure single URL. Which type of virtual server can the administrator use to meet this requirement?

- A. Load Balancing
- B. Content Switching
- C. VPN
- D. Unified Gateway

**Answer: D**

**NEW QUESTION 3**

Scenario: A Citrix Administrator needs to configure a group in which Contractors will have limited access to internal resources over the SSL VPN. The Contractors group should be able to access all internal IP Addresses but should NOT be able to open SSH connections to any internal resource. Which expression should the administrator use to satisfy this scenario?

- A. REQ.IP.DESTIP == 192.168.30.0 -netmask 255.255.255.0&&(REQ.TCP.DESTPORT == 22)Actionset to Allow
- B. REQ.IP.DESTIP == 192.168.30.0 -netmask 255.255.255.0&&(REQ.TCP.DESTPORT == 22)Actionset to Deny
- C. REQ.IP.DESTIP == 192.168.30.0 -netmask 255.255.255.0&&(REQ.TCP.DESTPORT == 80 || REQ.TCP.DESTPORT == 443)
- D. REQ.IP.DESTIP == 192.168.30.0 -netmask 255.255.255.0 || (REQ.TCP.DESTPORT == 22)Action set to Allow

**Answer: D**

**NEW QUESTION 4**

Which two features can a Citrix Administrator use to allow secure access to a sensitive company web server that is load-balanced by the NetScaler? (Choose two.)

- A. ICA proxy
- B. Integrated caching
- C. Application Firewall
- D. AppFlow
- E. AAA

**Answer: AC**

**NEW QUESTION 5**

A Citrix Administrator has deployed a new NetScaler MPX appliance in the demilitarized (DMZ) with one interface in the DMZ and the other on the internal network.

In which mode should the administrator deploy the NetScaler?

- A. One-Arm
- B. Two-Arm
- C. Forward Proxy
- D. Transparent

**Answer: D**

**NEW QUESTION 6**

Scenario: A Citrix Administrator needs to create local user accounts for other administrators with limited privileges. The other administrators will need only:

-Read-only access

-The ability to enable and disable services and servers

Which built-in Command Policy permission level can the administrator use?

- A. Network
- B. Operator
- C. Sysadmin
- D. Read-Only

**Answer: B**

**NEW QUESTION 7**

Which two components need to be configured for SmartAccess? (Choose two.)

- A. Configuration logging
- B. XenDesktop policies
- C. XML Trust

D. StoreFront server groups

**Answer:** CD

**NEW QUESTION 8**

Which three pieces of information are required for a NetScaler Unified Gateway deployment? (Choose three.)

- A. Valid SSL Certificates
- B. Secondary Authentication for the Unified Gateway
- C. Enterprise license or higher
- D. Content Switching virtual server
- E. Multiple IP addresses for User Access

**Answer:** ACD

**NEW QUESTION 9**

A Citrix Administrator needs to configure a NetScaler high availability (HA) pair with both NetScalers in different subnets. What does the administrator need to do for the HA pair to work in different subnets?

- A. Configure Sync VLAN
- B. Turn on HA Monitoring on all Interfaces
- C. Turn on Fail-safe Mode
- D. Turn on Independent Network Configuration (INC) mode

**Answer:** D

**NEW QUESTION 10**

TCP multiplexing is a technique that enables the reuse of existing TCP connections. Which NetScaler hardware or software platform offers a Multi-Tenant solution?

- A. VPX
- B. CPX
- C. MPX
- D. SDX

**Answer:** D

**NEW QUESTION 10**

Scenario: A Citrix Administrator configured the “-denySSLReneg” Parameter using the below command on NetScaler to enhance security.  
set ssl parameter -denySSLReneg <option>  
Which two options can the administrator use to complete the command (Choose two.)

- A. NO
- B. NONSECURE
- C. ALL
- D. HIGHSECURE
- E. FRONTEND\_CLIENT

**Answer:** AB

**NEW QUESTION 15**

Scenario: A Citrix Administrator is configuring balancing on a NetScaler appliance for the company web servers. The administrator needs to create a custom monitor that will look for a specific keyword response from the website and will be used to keep the services in an UP state. Which type of monitor can the administrator create to accomplish this scenario?

- A. An HTTP-ECV monitor with the keyword in the Special Parameters- Receive String field.
- B. A customer TCP-ECV monitor with the keyword in the Special Parameters- Receive String field.
- C. An HTTP monitor with the keyword in the Special Parameters- Response Codes field.
- D. A TCP monitor with the keyword in the Special Parameters- Response Codes field.

**Answer:** C

**NEW QUESTION 16**

Which three statements are true when comparing a Simple Access Control List (ACL) to an Extended ACL? (Choose three.)

- A. Extended ACLs have priorities
- B. Simple ACLs can be modified
- C. Extended ACLs apply first
- D. Simple ACLs can be based on the Source and Destination IP address
- E. Simple ACLs can bridge traffic
- F. Simple ACLs are based on the Source IP address only
- G. Simple ACLs apply first

**Answer:** ADG

**NEW QUESTION 18**

A NetScaler with Unified Gateway combines and to provide access to websites and applications through a single URL. (Choose the correct option to complete the sentence.)

- A. NetScaler Gateway; Load Balancing
- B. Content Switching; Authentication features
- C. Content Switching; NetScaler Gateway
- D. Authentication features; Load Balancing

**Answer: B**

**Explanation:** NetScaler Unified Gateway leverages its Authentication, Authorization and Auditing (AAA) features with content switching to enable users to access all their authorized enterprise applications through a single gateway and URL.

**NEW QUESTION 21**

Which NetScaler Access Control List (ACL) command can a Citrix Administrator use to bridge traffic originating from 192.168.10.200?

- A. add ns acl
- B. add ns simpleacl
- C. add ns acl6
- D. add ns simpleacl6

**Answer: D**

**NEW QUESTION 24**

A Citrix Administrator needs to configure a setup with a single URL so that users can log on once and achieve seamless single sign-on to the NetScaler Gateway virtual server and web application being load-balanced on the NetScaler.

Which type of virtual server can the administrator configure to fulfill this requirement?

- A. GSLB
- B. AAA
- C. Unified Gateway
- D. Load Balancing

**Answer: A**

**NEW QUESTION 29**

Which scenario will cause automatic high availability (HA) synchronization to fail?

- A. Different build versions
- B. A configuration change to the primary NetScaler
- C. A force failover
- D. Manually forced synchronization

**Answer: B**

**NEW QUESTION 34**

Scenario: A NetScaler has two interfaces as 1/1 and 1/2 with MAC-based Forwarding enabled. Below are the specifications:

-Interface 1/1 and IP 192.168.10.10 is bound to VLAN 10.

-On Interface 1/2 VLAN 20 and VLAN 30 are tagged.

-VLAN 20 is bound to IP 192.168.20.10 and VLAN 30 is bound to 192.168.30.10 The NetScaler receives a packet for VIP 192.168.30.30 on interface 1/1.

Which interface of NetScaler will send a reply back in this environment?

- A. Interface 1/1
- B. NetScaler will drop the packet received on interface 1/1
- C. Interface 1/2
- D. Netscaler will reply on interfaces 1/1 and 1/2

**Answer: D**

**NEW QUESTION 35**

Scenario: A company has three departments with proprietary applications that need to be load-balanced on the

NetScaler. The three department managers would like to use the same IP address to access their individual application, which would mean configuring three load-balanced virtual servers all using the same IP address.

How can a Citrix Administrator configure this on the NetScaler?

- A. Configure three different load-balanced virtual servers with three different IP addresses on the NetScaler
- B. Configure three SNIPs with the same IP address on the NetScaler
- C. Configure three different NetScalers that use the same IP address
- D. Configure three different admin partitions that allow the use of the same IP address for each load-balanced virtual server

**Answer: B**

**NEW QUESTION 40**

Scenario: A Citrix Administrator manages an environment that has an externally accessible website. The administrator would like to provide end-to-end encryption and use features such as caching and compression on the NetScaler.

Which setting in SSL offload should the administrator configure to meet this requirement?

- A. SSL\_TCP front-end, TCP back-end
- B. SSL front-end, HTTP back-end
- C. SSL\_TCP front-end, SSL\_TCP back-end
- D. SSL front-end, SSL back-end

**Answer: C**

**NEW QUESTION 43**

Users are experiencing resets from the Intranet server website, which is load-balanced through the NetScaler. Which NetScaler tool can a Citrix Administrator use to troubleshoot the reset issue?

- A. Take a packet trace with nstrace and analyze with WireShark.
- B. Look in the Event Viewer for packet resets from the NetScaler.
- C. View the new nslog from the command-line interface to look for packet resets from the NetScaler.
- D. Use the nslog to look for packet resets on the NetScaler.

**Answer: D**

**NEW QUESTION 47**

Scenario: Client connections to certain virtual servers are abnormally high. A Citrix Administrator needs to be alerted whenever the connections pass a certain threshold.

How can the administrator use NetScaler Management and Analytics System (MAS) to accomplish this requirement?

- A. Configure SMTP Reporting on the NetScaler MAS by adding the threshold and email address.
- B. Configure specific alerts for virtual servers using NetScaler MAS.
- C. Configure TCP Insight on the NetScaler MAS.
- D. Configure Network Reporting on the NetScaler MAS by setting the threshold and email address.

**Answer: D**

**NEW QUESTION 48**

A Citrix Administrator receives user complaints about latency while accessing an application that is being load-balanced on the NetScaler. Which tool can the administrator use to gather information regarding Response time, Client latency and Server-side processing time?

- A. aaad.debug
- B. WAN Insight
- C. NetScaler Management and Analytics System (MAS)
- D. HDX Insight

**Answer: D**

**NEW QUESTION 53**

Scenario: A Citrix Administrator has made changes to the NetScaler, deleting parts of the configuration, and then saved the new configurations. The changes caused an outage which needs to be resolved as quickly as possible. There is no NetScaler backup.

What does the administrator need to do to recover the configuration quickly?

- A. Restart the NetScaler
- B. Run Save v/s Running configuration
- C. Restore from revision history
- D. Run HA file synchronization

**Answer: D**

**NEW QUESTION 58**

After creating and correctly configuring a custom user monitor, from where do the monitor probes originate by default?

- A. Subnet IP address
- B. NetScaler IP address
- C. Mapped IP address
- D. Virtual IP address

**Answer: B**

**NEW QUESTION 60**

Which two actions must be true for a client to connect to a SSL offload virtual server without any SSL errors? (Choose two.)

- A. The Root Certificate is installed on the client's device
- B. The Server Certificate is bound to the load-balancing virtual server
- C. The Server Certificate is from a private certificate authority (CA)
- D. The Root Certificate is installed on the NetScaler

**Answer: AC**

**NEW QUESTION 64**

Scenario: A Citrix Administrator currently manages a NetScaler environment in a retail company that is growing quickly and may soon double its volume of

business. Currently, a NetScaler MPX 5550, which handles web and SSL transactions, is in place, but is closed to full capacity. Due to the forecasted growth increase, the administrator needs to find a cost-effective solution.

What can the administrator recommend to management in order to cost effectively handle the growth?

- A. Upgrade to NetScaler MPX 5650
- B. Upgrade to NetScaler MPX 8005
- C. Upgrade to NetScaler SDX 14100
- D. Add a second MPX 5550 appliance

**Answer: C**

**NEW QUESTION 66**

What are two pre-requisites for configuring SmartAccess policies on a NetScaler Gateway virtual server? (Choose two.)

- A. Universal License
- B. Pre- or Post-Endpoint Analysis configuration policy
- C. Smart card configuration policy
- D. Standard License

**Answer: AB**

**Explanation:** Make sure the Prerequisites are completed. This includes: ICA Only unchecked, Gateway Universal licenses installed, Callback URL configured at StoreFront, and Trust XML enabled on Delivery Controllers.

If you are using a Preauthentication Policy to run an Endpoint Analysis scan: References:

**NEW QUESTION 68**

Which type of policy should a Citrix Administrator configure to ensure that only users who have data antivirus protection can connect to the environment?

- A. Traffic
- B. Pre-Authentication Scan
- C. Smart Control
- D. SmartAccess

**Answer: B**

**NEW QUESTION 71**

Scenario: A Citrix Administrator is deploying a NetScaler device and would like to add the NTP server to this appliance. Currently, the NTP service is configured at 192.168.55.54.

Which command-line interface command can the administrator use to complete this task?

- A. Add ntp server 192.168.55.54
- B. Add server ntp 192.168.55.54
- C. Add servicegroup NTP UDP
- D. Add service NTP 192.168.55.54 UDP 123

**Answer: A**

**NEW QUESTION 74**

Which type of entity can a Citrix Administrator configure to support the use of an SSL rewrite policy?

- A. Global server load balancing virtual server
- B. Content Switching virtual server
- C. SSL load balancing virtual server
- D. SSL\_Bridge balancing virtual server

**Answer: B**

**NEW QUESTION 77**

Which type of policy can be applied to a NetScaler Gateway virtual server to limit access to XenDesktop resources, if the user device does NOT comply with the company's security requirements?

- A. Responder
- B. Authorization
- C. Session
- D. Traffic

**Answer: A**

**NEW QUESTION 82**

Scenario: A NetScaler is configured with the following modes:

- MAC-based Forwarding
- USIP
- USNIP
- Layer 3 mode

A Citrix Administrator configured a new router and now requires some of the incoming and outgoing traffic to take different paths through the new router. However,

the administrator notices that this is failing and takes a network trace. After a short monitoring period, the administrator notices that the packets are still NOT getting to the new router from the NetScaler.

Which mode should the administrator disable on the NetScaler to facilitate the addition of the new router and successfully route the packets?

- A. MAC-based Forwarding
- B. USIP
- C. Layer 3 mode
- D. USNIP

**Answer: D**

#### **NEW QUESTION 84**

A Citrix Administrator needs to customize the user experience for users connecting with the NetScaler Gateway plug-in. Which three options can the administrator configure in this customization, using session and traffic policies? (Choose three.)

- A. The level of user access to the applications
- B. Single sign-on
- C. Split tunneling
- D. The domains to which users are allowed access
- E. Authentication methods

**Answer: CDE**

#### **NEW QUESTION 88**

A Citrix Administrator receives complaints from some users that authentication for the NetScaler Gateway site fails. Which tool can the administrator use to find data regarding time of failure and a list of users facing this issue?

- A. Gateway Insight
- B. Security Insight
- C. Web Insight
- D. HDX Insight

**Answer: D**

#### **NEW QUESTION 90**

Scenario: A Citrix Administrator created a rewrite policy to add a custom footer for a NetScaler Gateway login page. However, the administrator is NOT able to see the changes on the login page.

Which step can the administrator perform next to see the changes on the login page?

- A. Restart the NetScaler
- B. Edit the vpn/gateway\_login\_view.js file
- C. Make changes to rc.netscaler
- D. Disable the Rewrite and Responder feature

**Answer: B**

#### **NEW QUESTION 95**

How can a Citrix Administrator provide two-factor authentication with tokens in a XenDesktop with NetScaler Gateway environment?

- A. Create a SAML IDP policy and bind it to the existing virtual server.
- B. Configure a TACACS authentication policy and bind it to the existing virtual server.
- C. Configure a RADIUS authentication policy and bind it to the existing virtual server.
- D. Create an authorization policy and bind it to the existing virtual server.

**Answer: C**

#### **NEW QUESTION 97**

Which three Unified Gateway elements can be configured by the Unified Gateway Wizard? (Choose three.)

- A. Responder policy for HTTP to HTTPS redirect
- B. A primary and any optional secondary authentication configuration
- C. The Unified Gateway primary virtual server
- D. Rewrite policy for HTTP to HTTPS redirect
- E. An SSL Server Certificate for the Unified Gateway virtual server

**Answer: BCE**

#### **NEW QUESTION 98**

Scenario: User authentication is failing through the NetScaler. A Citrix Administrator checked the Authentication, Authorization and Auditing (AAA) policy, action and virtual server and verified that the correct configuration was in place. The administrator bypassed the NetScaler and the authentication worked.

Which NetScaler utility can the administrator use to troubleshoot the access issue?

- A. nslog file
- B. aaad.debug
- C. nscon message
- D. Dashboard

**Answer: B**

**NEW QUESTION 102**

Which two items can a Citrix Administrator change when configuring a default portal theme? (Choose two.)

- A. Center logo
- B. NetScaler with Unified Gateway header
- C. Browser requirements
- D. Font color

**Answer: AD**

**NEW QUESTION 107**

Scenario: A company recently acquired three smaller companies; this adds more than 1500 employees to the company. The current NetScaler appliance does NOT support adding that many users.

A Citrix Administrator needs to use a Multi-Tenancy solution, giving each newly acquired company its own NetScaler for VPN access, load balancing, and at least 20 GBPS of throughput.

How can the administrator meet the needs of this environment?

- A. Install XenServer and configure a NetScaler VPX 3000 for each newly acquired company.
- B. Purchase a NetScaler MPX appliance for each newly acquired company.
- C. Purchase a NetScaler CPX for each newly acquired company.
- D. Purchase a NetScaler SDX appliance and configure a NetScaler Instance for each newly acquired company.

**Answer: D**

**NEW QUESTION 112**

Which mode does a Citrix Administrator need to configure in order to allow the NetScaler to forward any packets that are NOT destined for an IP address which is NOT configured on NetScaler?

- A. Layer 3
- B. USIP
- C. Layer 2
- D. MAC-based Forwarding

**Answer: C**

**NEW QUESTION 116**

Scenario: A Citrix Administrator needs to build policies that control the selection of XenApp applications to which a user has access. The administrator would like for the policy decisions to be made by leveraging the HDX settings.

Which type of policy would enable this requirement?

- A. Traffic
- B. SmartControl
- C. Authorization
- D. SmartAccess

**Answer: D**

**NEW QUESTION 118**

Scenario: A Citrix Administrator is running applications on thousands of load-balanced back-end servers in a large infrastructure. It is difficult to track and troubleshoot problems due to the large volume of traffic received.

Which feature of NetScaler Management and Analytics System (MAS) can the administrator configure to monitor and troubleshoot in detail for an environment of this size?

- A. AppFlow Analytics
- B. Application Security Analytics
- C. Application Performance Analytics
- D. Advanced Analytics with Telemetry Node installed

**Answer: D**

**NEW QUESTION 119**

Scenario: A NetScaler MPX appliance has become unresponsive while using the GUI. A Citrix Administrator needs to restart the appliance and force a core dump for analysis.

What can the administrator do to accomplish this?

- A. Use the NMI button on the back of the appliance.
- B. Connect to the USB port to issue a restart command.
- C. Use the reset button on the front of the appliance.
- D. Turn off the appliance using the power button.

**Answer: A**

**NEW QUESTION 123**

What are three possible policy results in a Default (Advanced) policy configuration? (Choose three.)

- A. Drop
- B. Bridge
- C. True
- D. False
- E. Undefined

**Answer:** ABE

#### NEW QUESTION 126

A Citrix Administrator needs to configure a policy where users will be downgraded to 'ICA Proxy Only' from 'Full VPN' in the event a user fails to meet Endpoint Analysis requirements.

Which configuration is required to satisfy this requirement?

- A. Quarantine Group with nFactor authentication
- B. Quarantine Group with two-factor authentication, using LDAP as primary authentication
- C. Quarantine Group with no Active Directory membership
- D. Quarantine Group with regular Active Directory membership

**Answer:** A

#### NEW QUESTION 129

Scenario: A Citrix Administrator needs to add 10 new servers to an existing server farm. The new servers are configured to serve the same applications and connections and are twice the capacity of the existing servers. The administrator wants to ensure that they are being fully utilized. Currently in the environment, the default load-balancing method is being used.

To ensure that only the 10 new servers are receiving twice the connections of the old servers without changing the load balancing to the rest of the environment, the administrator needs to add a weight of to the services attached to the servers. (Choose the correct option to complete the sentence.)

- A. 2; new
- B. 2; old
- C. 50; old
- D. 50; new

**Answer:** B

#### NEW QUESTION 131

Scenario: A Citrix Administrator suspects an attack on a load-balancing virtual server. The administrator needs to restrict access to the load-balancing virtual server (192.168.100.25) for 10 minutes.

Which Access Control List (ACL) will help to accomplish this requirement?

- A. add ns acl rule1 DENY -destIP 192.168.100.25- TTL 600000
- B. add simpleacl rule1 DENY- srcIP 192.168.100.25- TTL 600
- C. add ns acl rule1 DENY -destIP 192.168.100.25- TTL 600
- D. add simpleacl rule1 DENY- srcIP 192.168.100.25- TTL 600000

**Answer:** C

#### NEW QUESTION 135

Scenario: A Citrix Administrator manages an environment that has multiple websites running through a NetScaler MPX 5550. The NetScaler meets the needs of the environment throughout the year, except in December, when the capacity doubles. The administrator needs to handle this increased web traffic with a temporary, cost-effective solution.

Which action should the administrator recommend in order to handle the increased web traffic?

- A. Purchase a BurstPack License
- B. Purchase NetScaler Gateway Platform License
- C. Purchase a license to upgrade the MPX 5550 to a MPX 5650
- D. Purchase Universal License

**Answer:** A

#### NEW QUESTION 137

A Citrix Administrator needs to generate AppFlow data for internal ICA connections.

Which two connection methods could the administrator use to route internal ICA connections through NetScaler without modifying the existing network routing? (Choose two.)

- A. Policy-based Routing
- B. ICA Proxy
- C. SOCKS proxy
- D. Transparent Mode

**Answer:** AD

#### NEW QUESTION 142

A Citrix Administrator needs to ensure that a revoked certificate is NOT being used for client certificate authentication.

Which two entities can the administrator select on the NetScaler? (Choose two.)

- A. Online Certification Status Protocol
- B. Certificate Revocation List
- C. Subject Alternative certificates
- D. Server Name Indication

**Answer:** AB

**NEW QUESTION 144**

Scenario: Users belong to three Authentication, Authorization and Auditing (AAA) groups: Corporate, Finance and Software.

Show aaa groups:

>show aaa group

1) GroupName: Corporate

2) GroupName: Finance

3) GroupName: Software Done

>show aaa group Corporate GroupName: Corporate Weight: 0

Authorization Policy: pol\_1, Type: Classic, Priority: 0

> add authorization policy pol\_1 ns\_true ALLOW

> bind aaa group Corporate -policy pol\_1

The user is being denied resources while aaad.debug shows: Group 'corporate' being extracted for user User1

Why is the user being denied access?

- A. The Authorization policy is NOT configured properly.
- B. The group attribute is NOT configured in the LDAP policy.
- C. AAA group names are NOT the same as those in Active Directory/
- D. LDAP Base DN is incorrect.

**Answer:** D

**NEW QUESTION 149**

Which NetScaler mode is commonly referred to as 'inline mode'?

- A. One-Arm Mode
- B. Use Source IP (USIP)
- C. MAC-based Forwarding
- D. Two-Arm Mode

**Answer:** D

**Explanation:** In an inline mode (also called two-arm mode) setup, you connect the NetScaler appliance to the network through multiple VLANs.

**NEW QUESTION 152**

Scenario: A Citrix Administrator needs to integrate LDAP for NetScaler system administration using the current Active Directory groups. The administrator created the group on the NetScaler, exactly matching the group name in LDAP.

What can the administrator add next to complete the configuration of the LDAP?

- A. Users to the group on the NetScaler
- B. An AAA action to the group
- C. A command policy to the group to specify the permission level
- D. A nested group to the new group

**Answer:** C

**NEW QUESTION 155**

In an environment which requires secure user access, a Citrix Administrator configures Authentication, Authorization and Auditing (AAA) to redirect a user to the logon page.

Which four steps are required to complete the authentication process? (Choose four.)

- A. Configure a syslog server to capture invalid logon attempts?
- B. Verify that the user is authorized to access specific intranet content
- C. Collect the user's credentials to cache them in a directory that is accessible through LDAP
- D. Log the user accesses, including invalid login attempts, in an audit log
- E. Create a load-balancing virtual server to redirect for secure access
- F. Maintain a session timeout, after which users must authenticate again to regain access to the intranet
- G. Apply specified two-factor authentication method

**Answer:** CEF G

**NEW QUESTION 160**

Which two policy types can a Citrix Administrator apply to a NetScaler Gateway virtual server so that only users accessing with corporate laptops that belong to the network domain are allowed? (Choose two.)

- A. Pre-Authentication
- B. Responder
- C. Authorization
- D. Traffic
- E. Session

**Answer:** AB

**NEW QUESTION 162**

Scenario: A Citrix Administrator deployed a NetScaler in one-arm mode. Currently, the VLANs 20, 30 and 40 are tagged on the interface with the option of 'tagall' on the interface.

What is true regarding the VLANs, when 'tagall' is enabled on the interface?

- A. VLANs 1, 20, 30, 40 and HA packets are tagged on the interface
- B. VLANs 20, 30 and 40 are tagged on the interface
- C. VLANs 20, 30, 40 and HA packets are tagged on the interface
- D. VLANs 1, 20, 30 and 40 are tagged on the interface

**Answer:** B

**NEW QUESTION 163**

Scenario: A Citrix Administrator is looking into adopting NetScaler to handle application delivery for an environment.

The administrator would like to start with these services:

IIS and Apache Web Servers

Microsoft SQL AlwaysON Database Availability Groups

Which two NetScaler features can the administrator use to achieve this goal? (Choose two.)

- A. Load Balancing
- B. Content Switching
- C. Data Stream
- D. Cloud Bridge Integration

**Answer:** BD

**NEW QUESTION 168**

Which two deployment methods does remote desktop protocol (RDP) proxy support? (Choose two.)

- A. ICA proxy
- B. Two hops
- C. Optimal Gateway
- D. CVPN

**Answer:** AD

**NEW QUESTION 172**

Scenario: A Citrix Administrator found that whenever a NetScaler VPX high availability (HA) pair of appliances fails over, the load-balanced websites are NOT accessible. The administrator investigated the issue and found that the router and switches do NOT support gratuitous ARP (GARP). However, the administrator cannot immediately afford to upgrade the network infrastructure.

What can the administrator do immediately to resolve the issue and prevent a future outage?

- A. Migrate the VPX pair to different hypervisor hosts.
- B. Replace the NetScaler VPX appliances with NetScaler MPX appliances
- C. Configure a Virtual MAC (VMAC) on the NetScaler.
- D. Utilize IPv6 instead of IPv4.

**Answer:** D

**NEW QUESTION 175**

Scenario: A Citrix Administrator has a NetScaler SDX appliance with several instances configured. The administrator needs one instance with two interfaces connected to forward packets that are NOT destined for its MAC address. Hence, the administrator has enabled Layer 2 mode. After enabling Layer 2 mode, the administrator found the interface status going up and down.

What can the administrator perform to resolve this issue?

- A. Disable Layer 2 mode on a NetScaler instance.
- B. Enable MAC-based Forwarding mode.
- C. Enable tagging on all interfaces.
- D. Enable Layer 3 mode along with Layer 2 mode.

**Answer:** C

**NEW QUESTION 179**

Which three services can the StoreFront monitor probe to determine the state of the StoreFront server? (Choose three.)

- A. Default Domain
- B. Discovery
- C. Authentication
- D. Subscription
- E. Account

**Answer:** BCE

**NEW QUESTION 184**

Scenario: A user is attempting to access a web server, which is load-balanced by the NetScaler using HTTPS. The user received the following message:  
SSL/TLS error: You have not chosen to trust "Certificate Authority" the issuer of the server's security certificate.  
What can a Citrix Administrator do to prevent users from viewing this message?

- A. Ensure that the intermediate Certificate is linked to the Server Certificate.
- B. Ensure that the user has the Server Certificate installed.
- C. Ensure that the intermediate Certificate is linked to the Root Certificate.
- D. Ensure that the user has the Certificate's Public key.

**Answer: A**

#### NEW QUESTION 188

Scenario: A Junior Citrix Administrator needs to create a Content Switching virtual server on a NetScaler high availability (HA) pair. The NSIP addresses are 192.168.20.10 and 192.168.20.11. The junior administrator connects to NSIP address 192.168.20.10 and saves the changes. The following day, a Senior Citrix Administrator tries to test the new Content Switching virtual server, but it is NOT working. The senior administrator connects to the HA pair and everything the junior administrator configured is gone. Why did the NetScalers lose the newly added configurations?

- A. The NetScaler appliances are NOT at the same firmware version
- B. The junior administrator connected to the NSIP of the secondary NetScaler in the HA pair
- C. Both NetScalers in the HA pair restarted overnight, losing the configuration
- D. The junior administrator made the changes and did NOT force a failover to save the configuration

**Answer: C**

#### NEW QUESTION 190

Scenario: IT administrators working from remote locations, need to connect securely to internal Windows servers to manage the servers. Below are the connection requirements:

The remote client devices must be locked down, preventing installation of any additional software  
Users must authenticate at NetScaler Gateway and NetScaler Gateway must perform Single Sign-on to the Windows servers  
Connection capabilities (for example, client drive mapping) must be controlled by NetScaler Gateway Which connection method can a Citrix Administrator configure to meet these requirements?

- A. RDP Proxy
- B. Clientless VPN
- C. Full VPN
- D. Micro VPN

**Answer: A**

#### NEW QUESTION 191

In which two ways can a Citrix Administrator configure SmartAccess? (Choose two.)

- A. Enable Workspace Control within StoreFront.
- B. Update XML Service Trust to set-BrokerSite-TrustRequestsSentToTheXMLServicePort \$True
- C. Update the XML Service trust in the XenDesktop database manually.
- D. Ensure that the SmartAccess filter name on the Delivery Group matches the NetScaler Gateway policies.

**Answer: BD**

#### NEW QUESTION 193

Which option is needed to configure the NetScaler Gateway to provide users with multiple logon options after successful authentication, if the users are connected through clientless access?

- A. Client choices without using Endpoint Analysis
- B. Configuration of Endpoint Analysis
- C. Configuration of Quarantine Group
- D. Client choices options with mandatory Endpoint Analysis

**Answer: D**

#### NEW QUESTION 194

.....

## Thank You for Trying Our Product

\* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

\* One year free update

You can enjoy free update one year. 24x7 online support.

\* Trusted by Millions

We currently serve more than 30,000,000 customers.

\* Shop Securely

All transactions are protected by VeriSign!

**100% Pass Your 1Y0-230 Exam with Our Prep Materials Via below:**

<https://www.certleader.com/1Y0-230-dumps.html>