



Citrix

Exam Questions 1Y0-230

Citrix NetScaler 12 Essentials and Unified Gateway

NEW QUESTION 1

Which NetScaler feature can a Citrix Administrator use to create a customer footer for a NetScaler Gateway login page?

- A. Rewrite
- B. SmartAccess
- C. HTTP Callout
- D. Responder

Answer: A

NEW QUESTION 2

Which two options should a Citrix Administrator configure to stop the First-Time wizard from automatically popping up? (Choose two.)

- A. Host Name is NOT configured on the appliance
- B. The appliance is configured with the default IP address (192.168.100.1)
- C. the default Admin Password has NOT been changed
- D. Licenses are NOT present on the appliance

Answer: BD

NEW QUESTION 3

Scenario: A NetScaler Gateway provides ICA Proxy to an internal XenDesktop site in an environment. The security team wants the Citrix Administrator to configure the NetScaler to block client drives if the client device fails a security scan.

Which NetScaler feature allows the administrator to satisfy the security team's requirements without making changes to the XenDesktop configuration?

- A. Traffic Policy
- B. Smart Access
- C. SmartControl
- D. Authorization Policy

Answer: D

NEW QUESTION 4

Which setting can a Citrix Administrator use to reduce server load, improve response time and increase the number of SSL transactions per second on a SSL virtual server created with default settings?

- A. Session Reuse
- B. SSLv3
- C. Session Timeout
- D. SSLv2 Redirect

Answer: C

NEW QUESTION 5

Scenario: A Citrix Administrator needs to configure a group in which Contractors will have limited access to internal resources over the SSL VPN. The Contractors group should be able to access all internal IP Addresses but should NOT be able to open SSH connections to any internal resource.

Which expression should the administrator use to satisfy this scenario?

- A. REQ.IP.DESTIP = = 192.168.30.0 –netmask 255.255.255.0&&(REQ.TCP.DESTPORT = = 22)Actionset to Allow
- B. REQ.IP.DESTIP = = 192.168.30.0 –netmask 255.255.255.0&&(REQ.TCP.DESTPORT = = 22)Actionset to Deny
- C. REQ.IP.DESTIP = = 192.168.30.0 –netmask 255.255.255.0&&(REQ.TCP.DESTPORT = = 80 || REQ.TCP.DESTPORT = = 443)
- D. REQ.IP.DESTIP = = 192.168.30.0 –netmask 255.255.255.0 || (REQ.TCP.DESTPORT = = 22)Action set to Allow

Answer: D

NEW QUESTION 6

While troubleshooting an SSL issue on one of the SSL-based virtual servers, a Citrix Administrator noticed that the data captured from the TCP dump was showing in plain text.

What could be the cause of this issue?

- A. No SSL cipher suite was selected
- B. The SSL Certificate expired
- C. The selected cipher suite is obsolete
- D. Misconfiguration of the TCP profile

Answer: A

NEW QUESTION 7

A Citrix Administrator would like to define granular policies to configure and enforce user environment attributes for XenApp and XenDesktop on NetScaler Gateway.

Which type of policy would enable this requirement?

- A. SmartAccess
- B. SmartControl
- C. Authorization

D. Session

Answer: B

NEW QUESTION 8

Which two options would provide an end-to-end encryption data, while allowing the NetScaler to optimize the responses? (Choose two.)

- A. HTTP protocol for the virtual server
- B. SSL Bridge protocol for the virtual server
- C. HTTP protocol for the services
- D. SSL protocol for the virtual server
- E. SSL protocol for the services
- F. SSL Bridge protocol for the services

Answer: AB

NEW QUESTION 9

Which two features can a Citrix Administrator use to allow secure access to a sensitive company web server that is load-balanced by the NetScaler? (Choose two.)

- A. ICA proxy
- B. Integrated caching
- C. Application Firewall
- D. AppFlow
- E. AAA

Answer: AC

NEW QUESTION 10

Scenario: A Citrix Administrator has configured a NetScaler active-passive high availability (HA) pair. When the HA pair fails over, customers are unable to access the hosted websites. After some troubleshooting, the administrator found that the upstream router was NOT updating its ARP table.

What can the administrator configure to resolve this issue?

- A. Independent Network Configuration (INC) mode
- B. Virtual MAC
- C. HA monitor
- D. Route Monitor

Answer: B

NEW QUESTION 10

Scenario: A Citrix Administrator is evaluating the following policies in an environment.

Policy A:	Priority 2	Bound at the Global Default level
Policy B:	Priority 15	Bound at the User level
Policy C:	Priority 18	Bound at the Group level
Policy D:	priority 7	Bound at the Virtual Server Level

Which policy will take effect in the event of a policy conflict?

- A. Policy B
- B. Policy A
- C. Policy D
- D. Policy C

Answer: D

NEW QUESTION 14

Scenario: A Citrix Administrator needs to create local user accounts for other administrators with limited privileges. The other administrators will need only:

-Read-only access

-The ability to enable and disable services and servers

Which built-in Command Policy permission level can the administrator use?

- A. Network
- B. Operator
- C. Sysadmin
- D. Read-Only

Answer: B

NEW QUESTION 16

A Citrix Administrator needs to configure a NetScaler high availability (HA) pair with both NetScalers in different subnets.

What does the administrator need to do for the HA pair to work in different subnets?

- A. Configure Sync VLAN
- B. Turn on HA Monitoring on all Interfaces
- C. Turn on Fail-safe Mode
- D. Turn on Independent Network Configuration (INC) mode

Answer: D

NEW QUESTION 21

Scenario: A Citrix Administrator is managing a NetScaler SDX running eight NetScaler instances. The administrator first needs to upgrade the firmware on the instances. However, the administrator is concerned that it needs to be done all at once.
What upgrading flexibility does SDX provide in this scenario?

- A. The NetScaler instance can be upgraded at the SDX management level, allowing all instances to be upgraded at once.
- B. The NetScaler instances have to be upgraded at the same time.
- C. The NetScaler instance can be upgraded on an individual basis, allowing all instances to run different firmware versions.
- D. It is NOT possible to upgrade the NetScaler instances to different firmware versions.

Answer: A

NEW QUESTION 23

TCP multiplexing is a technique that enables the reuse of existing TCP connections
Which NetScaler hardware or software platform offers a Multi-Tenant solution?

- A. VPX
- B. CPX
- C. MPX
- D. SDX

Answer: D

NEW QUESTION 25

Scenario: A Citrix Administrator is troubleshooting a NetScaler issue. The administrator goes to the command line and from the Shell, tails the ns.log to view the log in real time to find the issue. After a few minutes, the administrator noticed that the logs stopped scrolling and the issue was missed.
How can troubleshooting continue using the ns.log?

- A. The ns.log service has stopped and needs to be restarted.
- B. The ns.log needs to be downloaded to the client machine for full viewing.
- C. The ns.log has reached its 100 KB limit.
- D. Press 'CTRL+C' to stop it from running and issue the command "tail-f ns.log" to resume.
- E. The ns.log is still running.
- F. Press 'Enter' and the ns.log will resume.

Answer: A

NEW QUESTION 29

Scenario: A Citrix Administrator configured the "-denySSLReneg" Parameter using the below command on NetScaler to enhance security.
set ssl parameter -denySSLReneg <option>
Which two options can the administrator use to complete the command (Choose two.)

- A. NO
- B. NONSECURE
- C. ALL
- D. HIGHSECURE
- E. FRONTEND_CLIENT

Answer: AB

NEW QUESTION 31

Scenario: A Citrix Administrator is configuring balancing on a NetScaler appliance for the company web servers. The administrator needs to create a custom monitor that will look for a specific keyword response from the website and will be used to keep the services in an UP state.
Which type of monitor can the administrator create to accomplish this scenario?

- A. An HTTP-ECV monitor with the keyword in the Special Parameters- Receive String field.
- B. A custom TCP-ECV monitor with the keyword in the Special Parameters- Receive String field.
- C. An HTTP monitor with the keyword in the Special Parameters- Response Codes field.
- D. A TCP monitor with the keyword in the Special Parameters- Response Codes field.

Answer: C

NEW QUESTION 32

A Citrix Administrator needs to utilize the client IP Address as the resource IP address for the NetScaler to server connections.
Which mode on the NetScaler will the administrator utilize to meet this requirement?

- A. Layer2
- B. USIP
- C. Layer 3
- D. USNIP

Answer: B

NEW QUESTION 33

A NetScaler with Unified Gateway combines and to provide access to websites and applications through a single URL. (Choose the correct option to complete the sentence.)

- A. NetScaler Gateway; Load Balancing
- B. Content Switching; Authentication features
- C. Content Switching; NetScaler Gateway
- D. Authentication features; Load Balancing

Answer: B

Explanation: NetScaler Unified Gateway leverages its Authentication, Authorization and Auditing (AAA) features with content switching to enable users to access all their authorized enterprise applications through a single gateway and URL.

NEW QUESTION 36

A Citrix Administrator needs to configure a setup with a single URL so that users can log on once and achieve seamless single sign-on to the NetScaler Gateway virtual server and web application being load-balanced on the NetScaler. Which type of virtual server can the administrator configure to fulfill this requirement?

- A. GSLB
- B. AAA
- C. Unified Gateway
- D. Load Balancing

Answer: A

NEW QUESTION 41

Which scenario will cause automatic high availability (HA) synchronization to fail?

- A. Different build versions
- B. A configuration change to the primary NetScaler
- C. A force failover
- D. Manually forced synchronization

Answer: B

NEW QUESTION 46

Scenario: A NetScaler has two interfaces as 1/1 and 1/2 with MAC-based Forwarding enabled. Below are the specifications:

-Interface 1/1 and IP 192.168.10.10 is bound to VLAN 10.

-On Interface 1/2 VLAN 20 and VLAN 30 are tagged.

-VLAN 20 is bound to IP 192.168.20.10 and VLAN 30 is bound to 192.168.30.10 The NetScaler receives a packet for VIP 192.168.30.30 on interface 1/1.

Which interface of NetScaler will send a reply back in this environment?

- A. Interface 1/1
- B. NetScaler will drop the packet received on interface 1/1
- C. Interface 1/2
- D. Netscaler will reply on interfaces 1/1 and 1/2

Answer: D

NEW QUESTION 50

Scenario: A company has three departments with proprietary applications that need to be load-balanced on the NetScaler. The three department managers would like to use the same IP address to access their individual application, which would mean configuring three load-balanced virtual servers all using the same IP address.

How can a Citrix Administrator configure this on the NetScaler?

- A. Configure three different load-balanced virtual servers with three different IP addresses on the NetScaler
- B. Configure three SNIPs with the same IP address on the NetScaler
- C. Configure three different NetScalers that use the same IP address
- D. Configure three different admin partitions that allow the use of the same IP address for each load-balanced virtual server

Answer: B

NEW QUESTION 51

Users are experiencing resets from the Intranet server website, which is load-balanced through the NetScaler. Which NetScaler tool can a Citrix Administrator use to troubleshoot the reset issue?

- A. Take a packet trace with nstrace and analyze with WireShark.
- B. Look in the Event Viewer for packet resets from the NetScaler.
- C. View the new nslog from the command-line interface to look for packet resets from the NetScaler.
- D. Use the nslog to look for packet resets on the NetScaler.

Answer: D

NEW QUESTION 53

Scenario: A Citrix Administrator entered the command-line interface commands below to prevent IP address 10.10.100 from accessing the NetScaler on port 80.
add simpleacl rule1 DENY- srcIP 10.10.10.100 -TTL 600 add simpleacl rule2 DENY- srcIP 10.10.10.100 -destPort 80 add ns acl rule1 DENY- srcIP

10.10.10.100-priority 10
add ns acl rule2 DENY- srcIP 10.10.10.100-priority 100 apply ns acls
Which Access Control List (ACL) will the NetScaler use to deny the IP address?

- A. add ns acl rule1 DENY-srcIP 10.10.10.100-priority 10
- B. add simpleacl rule1 DENY- srcIP 10.10.10.100 –TTL 600
- C. add simpleacl rule2 DENY- srcIP 10.10.10.100 –destPort 80
- D. add ns acl rule2 DENY- srcIP 10.10.10.100-priority 100

Answer: B

NEW QUESTION 57

Scenario: Client connects to certain virtual servers are abnormally high. A Citrix Administrator needs to be alerted whatever the connections pass a certain threshold.

How can the administrator use NetScaler Management and Analytics System (MAS) to accomplish this requirement?

- A. Configure SMTP Reporting on the NetScaler MAS by adding the threshold and email address.
- B. Configure specific alerts for virtual servers using NetScaler MAS.
- C. Configure TCP Insight on the NetScaler MAS.
- D. Configure Network Reporting on the NetScaler MAS by setting the threshold and email address.

Answer: D

NEW QUESTION 62

Scenario: A Citrix Administrator has a NetScaler SDX with four VPX instances configured. The SDX has a 10GB bandwidth license that has been configured with dedicated bandwidth of 2 GB for each instance. However, the administrator found that three instances do NOT ever reach the bandwidth limit, while one instance reaches the limit and needs 1 GB more bandwidth to accommodate increased traffic requests.

What can the administrator change on the instance that requires more bandwidth, to meet traffic requirements?

- A. Configure LA channel to increase the bandwidth
- B. Configure burst capacity of 1 GB with priority 10
- C. Purchase a SDX license to increase the bandwidth on the instances
- D. Configure burst capacity on the instance adding 1 GB of bandwidth with burst priority 0

Answer: D

NEW QUESTION 64

A Citrix Administrator receives user complaints about latency while accessing an application that is being load-balanced on the NetScaler.

Which tool can the administrator use to gather information regarding Response time, Client latency and Server-side processing time?

- A. aaad.debug
- B. WAN Insight
- C. NetScaler Management and Analytics System (MAS)
- D. HDX Insight

Answer: D

NEW QUESTION 69

Scenario: A Citrix Administrator has made changes to the NetScaler, deleting parts of the configuration, and then saved the new configurations. The changes caused an outage which needs to be resolved as quickly as possible. There is no NetScaler backup.

What does the administrator need to do to recover the configuration quickly?

- A. Restart the NetScaler
- B. Run Save v/s Running configuration
- C. Restore from revision history
- D. Run HA file synchronization

Answer: D

NEW QUESTION 72

To which three bind points can a Citrix Administrator bind a session policy, to enable Clientless access? (Choose three.)

- A. Group
- B. Service
- C. Service Group
- D. User
- E. Virtual server

Answer: BDE

NEW QUESTION 76

Scenario: A Citrix Administrator currently manages a NetScaler environment in a retail company that is growing quickly and may soon double its volume of business. Currently, a NetScaler MPX 5550, which handles web and SSL transactions, is in place, but is closed to full capacity. Due to the forecasted growth increase, the administrator needs to find a cost-effective solution.

What can the administrator recommend to management in order to cost effectively handle the growth?

- A. Upgrade to NetScaler MPX 5650
- B. Upgrade to NetScaler MPX 8005
- C. Upgrade to NetScaler SDX 14100
- D. Add a second MPX 5550 appliance

Answer: C

NEW QUESTION 81

Scenario: A Citrix Administrator is deploying a NetScaler device and would like to add the NTP server to this appliance. Currently, the NTP service is configured at 192.168.55.54.

Which command-line interface command can the administrator use to complete this task?

- A. Add ntp server 192.168.55.54
- B. Add server ntp 192.168.55.54
- C. Add servicegroup NTP UDP
- D. Add service NTP 192.168.55.54 UDP 123

Answer: A

NEW QUESTION 84

A Citrix Administrator needs to create a customized blacklist of IP addresses to supplement the Webroot reputation check, and in order to have stricter access through NetScaler.

How can the administrator create this blacklist?

- A. Create several extended Access Control List policies.
- B. Create a data set for IPv4 address matching.
- C. Enable MAC-based Forwarding.
- D. Create several simple Access Control List policies.

Answer: A

NEW QUESTION 86

A Citrix Administrator configured an external syslog server but is NOT seeing detailed TCP information. What can be causing this issue?

- A. TCP logging is NOT enabled
- B. User defined Audit Log is NOT configured
- C. Log level is NOT enabled
- D. Log facility is NOT configured

Answer: A

NEW QUESTION 88

Which type of entity can a Citrix Administrator configure to support the use of an SSL rewrite policy?

- A. Global server load balancing virtual server
- B. Content Switching virtual server
- C. SSL load balancing virtual server
- D. SSL_Bridge balancing virtual server

Answer: B

NEW QUESTION 93

Which type of policy can be applied to a NetScaler Gateway virtual server to limit access to XenDesktop resources, if the user device does NOT comply with the company's security requirements?

- A. Responder
- B. Authorization
- C. Session
- D. Traffic

Answer: A

NEW QUESTION 94

Scenario: A Citrix Administrator was notified that all contractor user IDs will start with the prefix "con." Currently SmartControl is used to restrict access to peripherals.

Which expression can the administrator use to accomplish this requirement?

- A. HTTP.REQ.USERNAME.CONTAINS("con").NOT
- B. HTTP.REQ.USER.IS_MEMBER_OF("con").NOT
- C. HTTP.REQ.USE
- D. IS_MEMBER-OF ("con")
- E. HTTP.REQ.USERNAME.CONTAINS ("con")

Answer: C

Explanation: Reference <https://support.citrix.com/article/CTX200261>

NEW QUESTION 98

Scenario: A NetScaler is configured with the following modes:

- MAC-based Forwarding
- USIP
- USNIP
- Layer 3 mode

A Citrix Administrator configured a new router and now requires some of the incoming and outgoing traffic to take different paths through the new router. However, the administrator notices that this is failing and takes a network trace. After a short monitoring period, the administrator notices that the packets are still NOT getting to the new router from the NetScaler.

Which mode should the administrator disable on the NetScaler to facilitate the addition of the new router and successfully route the packets?

- A. MAC-based Forwarding
- B. USIP
- C. Layer 3 mode
- D. USNIP

Answer: D

NEW QUESTION 103

Where should a Citrix Administrator configure SmartControl restrictions?

- A. NetScaler Gateway
- B. XenDesktop Delivery Controller
- C. NetScaler Gateway, XenDesktop Delivery Controller and StoreFront
- D. StoreFront and XenDesktop Delivery Controller

Answer: A

NEW QUESTION 106

A Citrix Administrator receives complaints from some users that authentication for the NetScaler Gateway site fails.

Which tool can the administrator use to find data regarding time of failure and a list of users facing this issue?

- A. Gateway Insight
- B. Security Insight
- C. Web Insight
- D. HDX Insight

Answer: D

NEW QUESTION 110

How does the NetScaler communicate that IP-to-MAC address bindings have changed to the switches and routers on the network, when a NetScaler high availability (HA) pair failover occurs?

- A. The NetScaler uses Reverse ARP (RARP) to update the devices on the network
- B. The NetScaler uses Proxy ARP to update the devices on the network
- C. The NetScaler uses Gratuitous ARPs (GARPs) to update the devices on the network
- D. The NetScaler uses MAC-based Forwarding to update the routers

Answer: C

NEW QUESTION 115

Which three Unified Gateway elements can be configured by the Unified Gateway Wizard? (Choose three.)

- A. Responder policy for HTTP to HTTPS redirect
- B. A primary and any optional secondary authentication configuration
- C. The Unified Gateway primary virtual server
- D. Rewrite policy for HTTP to HTTPS redirect
- E. An SSL Server Certificate for the Unified Gateway virtual server

Answer: BCE

NEW QUESTION 117

A Citrix Administrator is configuring a NetScaler high availability (HA) pair and needs to ensure that one NetScaler is UP and primary at all times to ensure the business websites are always available.

What does the administrator need to do ensure that the NetScalers still handle web traffic in the event that both nodes become unavailable or fail a health check?

- A. Disable HA Fail-safe mode on the Secondary NetScaler.
- B. Configure HA Fail-safe mode on each NetScaler independently.
- C. Disable HA Fail-safe mode on the Primary NetScaler only.
- D. Configure HA Fail-safe mode on the Primary NetScaler only.

Answer: D

NEW QUESTION 120

Scenario: A NetScaler Appliance is having intermittent issues. A Citrix Administrator is unable to identify the root cause and fix them. The administrator opened a Support ticket and the engineer assigned to the case requested all the logs and configuration information from the NetScaler. Which technical support tool can the administrator use to gather all the information on the NetScaler to send to the Support Engineer?

- A. Generate Support File
- B. Batch Configuration
- C. Start New Trace
- D. Get Back Trace

Answer: A

NEW QUESTION 121

Scenario: A company recently acquired three smaller companies; this adds more than 1500 employees to the company. The current NetScaler appliance does NOT support adding that many users. A Citrix Administrator needs to use a Multi-Tenancy solution, giving each newly acquired company its own NetScaler for VPN access, load balancing, and at least 20 GBPS of throughput. How can the administrator meet the needs of this environment?

- A. Install XenServer and configure a NetScaler VPX 3000 for each newly acquired company.
- B. Purchase a NetScaler MPX appliance for each newly acquired company.
- C. Purchase a NetScaler CPX for each newly acquired company.
- D. Purchase a NetScaler SDX appliance and configure a NetScaler Instance for each newly acquired company.

Answer: D

NEW QUESTION 126

Scenario: A Citrix Administrator needs to build policies that control the selection of XenApp applications to which a user has access. The administrator would like for the policy decisions to be made by leveraging the HDX settings. Which type of policy would enable this requirement?

- A. Traffic
- B. SmartControl
- C. Authorization
- D. SmartAccess

Answer: D

NEW QUESTION 130

Scenario: A Citrix Administrator is running applications on thousands of load-balanced back-end servers in a large infrastructure. It is difficult to track and troubleshoot problems due to the large volume of traffic received. Which feature of NetScaler Management and Analytics System (MAS) can the administrator configure to monitor and troubleshoot in detail for an environment of this size?

- A. AppFlow Analytics
- B. Application Security Analytics
- C. Application Performance Analytics
- D. Advanced Analytics with Telemetry Node installed

Answer: D

NEW QUESTION 135

A Citrix Administrator needs to configure a policy where users will be downgraded to 'ICA Proxy Only' from 'Full VPN' in the event a user fails to meet Endpoint Analysis requirements. Which configuration is required to satisfy this requirement?

- A. Quarantine Group with nFactor authentication
- B. Quarantine Group with two-factor authentication, using LDAP as primary authentication
- C. Quarantine Group with no Active Directory membership
- D. Quarantine Group with regular Active Directory membership

Answer: A

NEW QUESTION 137

Scenario: A Citrix Administrator suspects an attack on a load-balancing virtual server. The administrator needs to restrict access to the load-balancing virtual server (192.168.100.25) for 10 minutes. Which Access Control List (ACL) will help to accomplish this requirement?

- A. add ns acl rule1 DENY -destIP 192.168.100.25- TTL 600000
- B. add simpleacl rule1 DENY- srcIP 192.168.100.25- TTL 600
- C. add ns acl rule1 DENY -destIP 192.168.100.25- TTL 600
- D. add simpleacl rule1 DENY- srcIP 192.168.100.25- TTL 600000

Answer: C

NEW QUESTION 140

Scenario: A Citrix Administrator manages an environment that has multiple websites running through a NetScaler MPX 5550. The NetScaler meets the needs of the environment throughout the year, except in December, when the capacity doubles. The administrator needs to handle this increased web traffic with a

temporary, cost-effective solution.

Which action should the administrator recommend in order to handle the increased web traffic?

- A. Purchase a BurstPack License
- B. Purchase NetScaler Gateway Platform License
- C. Purchase a license to upgrade the MPX 5550 to a MPX 5650
- D. Purchase Universal License

Answer: A

NEW QUESTION 143

Scenario: A Citrix Administrator is performing a disaster recovery test and decided to fail over the NetScaler high availability (HA) pair appliances. The administrator noticed that the failover is NOT working as expected in item text, and the Secondary NetScaler is NOT taking over as Primary. The administrator suspects that networking issues may be causing the failure.

What could be the cause of this issue with the NetScalers?

- A. HA monitoring is enabled on a disabled interface of the Primary Node
- B. HA monitoring is enabled on an interface of the Secondary Node that shows as ENABLED, DOWN
- C. Independent network configuration (INC) mode is enabled
- D. HA heartbeats are only seen on some enabled interfaces of the Secondary Node

Answer: D

NEW QUESTION 146

A Citrix Administrator needs to ensure that a revoked certificate is NOT being used for client certificate authentication.

Which two entities can the administrator select on the NetScaler? (Choose two.)

- A. Online Certification Status Protocol
- B. Certificate Revocation List
- C. Subject Alternative certificates
- D. Server Name Indication

Answer: AB

NEW QUESTION 148

Scenario: Users belong to three Authentication, Authorization and Auditing (AAA) groups: Corporate, Finance and Software.

Show aaa groups:

```
>show aaa group
```

```
1) GroupName: Corporate
```

```
2) GroupName: Finance
```

```
3) GroupName: Software Done
```

```
>show aaa group Corporate GroupName: Corporate Weight: 0
```

```
Authorization Policy: pol_1, Type: Classic, Priority: 0
```

```
> add authorization policy pol_1 ns_true ALLOW
```

```
> bind aaa group Corporate -policy pol_1
```

The user is being denied resources while aaad.debug shows: Group 'corporate' being extracted for user User1

Why is the user being denied access?

- A. The Authorization policy is NOT configured properly.
- B. The group attribute is NOT configured in the LDAP policy.
- C. AAA group names are NOT the same as those in Active Directory/
- D. LDAP Base DN is incorrect.

Answer: D

NEW QUESTION 152

Which NetScaler mode is commonly referred to as 'inline mode'?

- A. One-Arm Mode
- B. Use Source IP (USIP)
- C. MAC-based Forwarding
- D. Two-Arm Mode

Answer: D

Explanation: In an inline mode (also called two-arm mode) setup, you connect the NetScaler appliance to the network through multiple VLANs.

NEW QUESTION 153

Scenario: A Citrix Administrator needs to integrate LDAP for NetScaler system administration using the current Active Directory groups. The administrator created the group on the NetScaler, exactly matching the group name in LDAP.

What can the administrator add next to complete the configuration of the LDAP?

- A. Users to the group on the NetScaler
- B. An AAA action to the group
- C. A command policy to the group to specify the permission level
- D. A nested group to the new group

Answer: C

NEW QUESTION 154

Scenario: A Citrix Administrator created four session policies and applied them to the bind points below.

- Policy A: Split tunnel ON priority 10 bound at the Virtual Server level
- Policy B: Split tunnel OFF priority 20 bound at the Group level
- Policy C: Split tunnel NOT configured priority 30 bound at the Global level
- Policy D: Split tunnel ON priority 6 bound at the Group level

Which policy will take precedence?

- A. Policy C
- B. Policy D
- C. Policy A
- D. Policy B

Answer: A

NEW QUESTION 158

In an environment which requires secure user access, a Citrix Administrator configures Authentication, Authorization and Auditing (AAA) to redirect a user to the logon page.

Which four steps are required to complete the authentication process? (Choose four.)

- A. Configure a syslog server to capture invalid logon attempts?
- B. Verify that the user is authorized to access specific intranet content
- C. Collect the user's credentials to cache them in a directory that is accessible through LDAP
- D. Log the user accesses, including invalid login attempts, in an audit log
- E. Create a load-balancing virtual server to redirect for secure access
- F. Maintain a session timeout, after which users must authenticate again to regain access to the intranet
- G. Apply specified two-factor authentication method

Answer: CEFG

NEW QUESTION 163

Which two policy types can a Citrix Administrator apply to a NetScaler Gateway virtual server so that only users accessing with corporate laptops that belong to the network domain are allowed? (Choose two.)

- A. Pre-Authentication
- B. Responder
- C. Authorization
- D. Traffic
- E. Session

Answer: AB

NEW QUESTION 165

Scenario: A Citrix Administrator of a Linux environment needs to load-balance the web servers in an environment. However, due to budget constraints, the administrator is NOT able to implement a full-scale solution.

What can the administrator do to load-balance the web servers in this scenario?

- A. Install a NetScaler CPX.
- B. Purchase NetScaler MPX.
- C. Purchase a NetScaler SDX.
- D. Install NetScaler VPX.

Answer: A

NEW QUESTION 168

Scenario: A Citrix Administrator is configuring a new Authentication, Authorization and Auditing (AAA) virtual server, and the status is DOWN. The administrator has made the following configurations:

Add lbvserver lb_vsrv_www HTTP 10.107.149.229.80- persistenceType NONOE -cltTimeout 180- authn401 ON -authnVsName SAML_SP

Bind vsriver lb_vsrv_www_ssl Red_srv Bind lb vsriver lb_vsrv_www_ssl Blue_srv

Add authentication vsriver SAML_SP SSL 10.107.149.230.443- AuthenticationDomain citrix.lab How can the administrator finish the installation to change the status of the virtual server to UP?

- A. Bind the Certificate to the virtual server SAML_SP.
- B. The LDAP server is NOT bound to the virtual server SAML_SP.
- C. Services are NOT bound to the virtual server SAML_SP.
- D. An AAA policy is NOT bound to the virtual server SAML_SP.

Answer: B

NEW QUESTION 171

What does a Citrix Administrator need to do on NetScaler Gateway to ensure that users accept the terms and conditions before they can log on using NetScaler Gateway?

- A. Configure a Responder policy.
- B. Upload an HTML file to the NetScaler appliance.

- C. Create an end user license agreement (EULA).
- D. Configure a Rewrite policy.

Answer: C

NEW QUESTION 172

Which three services can the StoreFront monitor probe to determine the state of the StoreFront server? (Choose three.)

- A. Default Domain
- B. Discovery
- C. Authentication
- D. Subscription
- E. Account

Answer: BCE

NEW QUESTION 176

Scenario: A user is attempting to access a web server, which is load-balanced by the NetScaler using HTTPS. The user received the following message:
SSL/TLS error: You have not chosen to trust "Certificate Authority" the issuer of the server's security certificate.
What can a Citrix Administrator do to prevent users from viewing this message?

- A. Ensure that the intermediate Certificate is linked to the Server Certificate.
- B. Ensure that the user has the Server Certificate installed.
- C. Ensure that the intermediate Certificate is linked to the Root Certificate.
- D. Ensure that the user has the Certificate's Public key.

Answer: A

NEW QUESTION 177

Scenario: A Junior Citrix Administrator needs to create a Content Switching virtual server on a NetScaler high availability (HA) pair. The NSIP addresses are 192.168.20.10 and 192.168.20.11. The junior administrator connects to NSIP address 192.168.20.10 and saves the changes.
The following day, a Senior Citrix Administrator tries to test the new Content Switching virtual server, but it is NOT working. The senior administrator connects to the HA pair and everything the junior administrator configured is gone.
Why did the NetScalers lose the newly added configurations?

- A. The NetScaler appliances are NOT at the same firmware version
- B. The junior administrator connected to the NSIP of the secondary NetScaler in the HA pair
- C. Both NetScalers in the HA pair restarted overnight, losing the configuration
- D. The junior administrator made the changes and did NOT force a failover to save the configuration

Answer: C

NEW QUESTION 182

In which two ways can a Citrix Administrator configure SmartAccess? (Choose two.)

- A. Enable Workspace Control within StoreFront.
- B. Update XML Service Trust to set-BrokerSite-TrustRequestsSentToTheXMLServicePort \$True
- C. Update the XML Service trust in the XenDesktop database manually.
- D. Ensure that the SmartAccess filter name on the Delivery Group matches the NetScaler Gateway policies.

Answer: BD

NEW QUESTION 185

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

1Y0-230 Practice Exam Features:

- * 1Y0-230 Questions and Answers Updated Frequently
- * 1Y0-230 Practice Questions Verified by Expert Senior Certified Staff
- * 1Y0-230 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 1Y0-230 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 1Y0-230 Practice Test Here](#)